


Pushdown Automata (PDA)

Input Tape:


$\Sigma = \{a,b,cd\}$, String: aacdbab, Length: 6

a	a	cd	b	a	b	Δ	Δ	Δ
---	---	----	---	---	---	----------	----------	----------


The START State:



The ACCEPT State:




The REJECT State:



The READ State (Outgoing: Total alphabets+1):

$\Sigma = \{a,b\}$




The PUSH State:



The POP State (Outgoing: Total alphabets+1):


$\Sigma = \{a,b\}$




Note:

- START is connected to the initial state
- Final States are connected to ACCEPT through Δ
- Non-Final States are connected to REJECT through Δ

FA:
 $\Sigma = \{a,b\}$
 $L = \text{Containing } bb$



Using the new format:




Tape: aaabbΔ

State	Tape	New State
START	aaabbΔ	READ1
READ1	<u>a</u> aabbΔ	READ1
READ1	<u>aa</u> aabbΔ	READ1
READ1	<u>aaa</u> aabbΔ	READ1
READ1	<u>aaab</u> bΔ	READ2
READ2	<u>aaabb</u> Δ	READ3
READ3	<u>aaabbΔ</u>	ACCEPT

Tape: aabΔ

State	Tape	New State
START	aabΔ	READ1
READ1	<u>a</u> abΔ	READ1
READ1	<u>aa</u> bΔ	READ1
READ1	<u>aab</u> Δ	READ2
READ2	<u>aabΔ</u>	REJECT

PDA:




Tape: aaabbbΔ

State	Tape	Stack	New State
START	aaabbbΔ	Δ	READ1
READ1	<u>a</u> aabbbΔ	Push a into the stack: aΔ	READ1
READ1	<u>aa</u> abbbΔ	Push a into the stack: aaΔ	READ1
READ1	<u>aaa</u> bbbΔ	Push a into the stack: aaaΔ	READ1
READ1	<u>aaab</u> bbΔ	POP1 a: aaΔ	READ2
READ2	<u>aaabb</u> bΔ	POP1 a: aΔ	READ2

READ2	aaabbb Δ	POP1 a: Δ	READ2
READ2	aaabbb <u>Δ</u>	POP2 Δ : Empty Stack	REJECT

PDA:





Tape: aaabbb Δ

State	Tape	Stack	New State
START	aaabbb Δ	Δ	READ1
READ1	<u>a</u> aabbb Δ	Push a into the stack: a Δ	READ1
READ1	aa aabbb Δ	Push a into the stack: aa Δ	READ1
READ1	aaa abbb Δ	Push a into the stack: aaa Δ	READ1
READ1	aaab bb Δ	POP1 a: aa Δ	READ2
READ2	aaabb b Δ	POP1 a: a Δ	READ2
READ2	aaabbb Δ	POP1 a: Δ	READ2
READ2	aaabbb <u>Δ</u>	POP2 Δ : Empty Stack	ACCEPT

Tape: aab Δ

State	Tape	Stack	New State
START	aab Δ	Δ	READ1
READ1	<u>a</u> ab Δ	Push a into the stack: a Δ	READ1
READ1	aa b Δ	Push a into the stack: aa Δ	READ1
READ1	aab Δ	POP1 a: a Δ	READ2
READ2	aab <u>Δ</u>	POP2 a: Δ	REJECT

FA:



Tape: aabbb Δ

State	Tape	New State
START	aabbbΔ	READ1
READ1	<u>a</u> abbbΔ	READ2
READ2	aa <u>b</u> bbΔ	READ1
READ1	aab <u>b</u> bbΔ	READ4
READ4	aabb <u>b</u> Δ	READ1
READ1	aabb <u>b</u> Δ	READ4
READ4	aabbb <u>Δ</u>	REJECT