

Rajalakshmi Engineering College

Name: Ubendra L
Email: 241901120@rajalakshmi.edu.in
Roll no: 241901120
Phone: 8610285702
Branch: REC
Department: CSE (CS) - Section 1
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 11

Attempt : 1
Total Mark : 20
Marks Obtained : 20

Section 1 : Project

1. Problem Statement

In Café Central, the menu is cataloged and stored in a database.

To efficiently manage the restaurant's menu using Java and JDBC, you must build a Restaurant Management System that supports:

Adding new menu items

Updating menu item prices

Viewing details of a menu item

Displaying all menu items in sorted order

You are given two files:

File 1: MenuItem.java (POJO Class)

This class represents the MenuItem entity.

A MenuItem contains the following details:

Field	Description
itemId	Unique Menu Item ID (Integer)
name	Item Name (String)
category	Item Category (String)
price	Item Price (Double)

Students must write code in the marked area:

```
class MenuItem {  
    private int itemId;  
    private String name;  
    private String category;  
    private double price;  
  
    public MenuItem() {}  
  
    public MenuItem(int itemId, String name, String category, double price) {  
        // write your code here  
    }  
  
    // Include getters and setters  
}
```

Expected in this part:

Assign parameter values to instance variables inside the constructor.

Add getters and setters for all attributes.

File 2: MenuItemDAO.java (Data Access Layer)

This class handles all database operations using JDBC.

Students must complete the missing JDBC logic in the following methods:

```
class MenuItemDAO {  
  
    public void addItem(Connection conn, MenuItem menuItem)  
    throws SQLException {  
        // write your code here  
    }  
  
    public void updateItemPrice(Connection conn, int itemId, double  
    newPrice) throws SQLException {  
        // write your code here  
    }  
  
    public void deleteMenuItem(Connection conn, int itemId) throws  
    SQLException {  
        // write your code here  
    }  
  
    public MenuItem viewItemDetails(Connection conn, int itemId) throws  
    SQLException {  
        // write your code here  
    }  
  
    public List<MenuItem> displayAllMenuItems(Connection conn) throws  
    SQLException {  
        // write your code here  
    }  
  
    private MenuItem mapToMenuItem(ResultSet rs) throws SQLException {  
        return new MenuItem(  

```

```
// write your code here  
);  
}  
}
```

Expected in this part:

Write SQL queries for INSERT, UPDATE, DELETE, SELECT.

Execute queries using PreparedStatement or Statement.

Map ResultSet rows to MenuItem objects using mapToMenuItem().

Return a List<MenuItem> where required.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The menu table has already been created with the following structure:

Table Name: menu

Input Format

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Menu Item):

- The second line consists of an integer item_id.
- The third line consists of a string name.
- The fourth line consists of a string category.
- The fifth line consists of a double price.

For choice 2 (Update Item Price):

- The second line consists of an integer item_id.
- The third line consists of a double new_price.

For choice 3 (View Item Details):

- The second line consists of an integer item_id.

For choice 4 (Display All Menu Items):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Menu Item):

- Print "Menu item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Update Item Price):

- Print "Item price updated successfully" if the price update was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (View Item Details):

- Display the item details in the format:
- ID: [item_id] | Name: [name] | Category: [category] | Price: [price]
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display All Menu Items):

- Display each item on a new line in the format:
- ID | Name | Category | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Restaurant Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

11

Margherita Pizza

Main Course

12.99

4

5

Output: Menu item added successfully

ID | Name | Category | Price

11 | Margherita Pizza | Main Course | 12.99

Exiting Restaurant Management System.

Answer

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class RestaurantManagementSystem {
```

```
    public static void main(String[] args) {
```

```
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://localhost/ri_db", "test", "test123"));
```

```
            Scanner scanner = new Scanner(System.in)) {
```

```
                boolean running = true;
```

```
                while (running) {
```

```
                    int choice = scanner.nextInt();
```

```
                    switch (choice) {
```

```
                        case 1:
```

```
                            addMenuItem(conn, scanner);
```

```
                            break;
```

```
                        case 2:
```

```
                            updateItemPrice(conn, scanner);
```

```
                            break;
```

```

        case 3:
            viewItemDetails(conn, scanner);
            break;
        case 4:
            displayAllMenuItems(conn);
            break;
        case 5:
            System.out.println("Exiting Restaurant Management System.");
            running = false;
            break;
        default:
            System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}
}

```

// You are using Java

```

public static void addItem(Connection conn, Scanner scanner) {

```

```

    //Write your code here

```

```

    int id = scanner.nextInt();

```

```

    scanner.nextLine();

```

```

    String name = scanner.nextLine();

```

```

    String category = scanner.nextLine();

```

```

    double price = scanner.nextDouble();

```

```

    try {

```

```

        String sql = "INSERT INTO menu(item_id, name, category, price) VALUES
        (?, ?, ?, ?)";

```

```

        PreparedStatement ps = conn.prepareStatement(sql);

```

```

        ps.setInt(1, id);

```

```

        ps.setString(2, name);

```

```

        ps.setString(3, category);

```

```

        ps.setDouble(4, price);

```

```

        ps.executeUpdate();

```

```

        System.out.println("Menu item added successfully");

```

```

    } catch (SQLException e) {

```

```

        System.out.println("Failed to add item.");
    }
}
}

```

```

public static void updateItemPrice(Connection conn, Scanner scanner) {

```

```

//Write your code here
int id = scanner.nextInt();
double newPrice = scanner.nextDouble();
try {
    String check = "SELECT * FROM menu WHERE item_id = ?";
    PreparedStatement checkPs = conn.prepareStatement(check);
    checkPs.setInt(1, id);
    ResultSet rs = checkPs.executeQuery();
    if (!rs.next()) {
        System.out.println("Item not found.");
        return;
    }
    String sql = "UPDATE menu SET price = ? WHERE item_id = ?";
    PreparedStatement ps = conn.prepareStatement(sql);
    ps.setDouble(1, newPrice);
    ps.setInt(2, id);
    ps.executeUpdate();
    System.out.println("Item price updated successfully");
} catch (SQLException e) {
    System.out.println("Item not found.");
}
}

public static void viewItemDetails(Connection conn, Scanner scanner) {
    //Write your code here
    int id = scanner.nextInt();
    try {
        String sql = "SELECT * FROM menu WHERE item_id = ?";
        PreparedStatement ps = conn.prepareStatement(sql);
        ps.setInt(1, id);
        ResultSet rs = ps.executeQuery();
        if (rs.next()) {
            System.out.println("ID: " + rs.getInt("item_id") +
                               " | Name: " + rs.getString("name") +
                               " | Category: " + rs.getString("category") +
                               " | Price: " + rs.getDouble("price"));
        } else {
            System.out.println("Item not found.");
        }
    } catch (SQLException e) {
        System.out.println("Item not found.");
    }
}

```



```

    }

    public static void displayAllMenuItems(Connection conn) {
        //Write your code here
        try {
            String sql = "SELECT * FROM menu ORDER BY item_id";
            Statement st = conn.createStatement();
            ResultSet rs = st.executeQuery(sql);
            System.out.println("ID | Name | Category | Price");
            while (rs.next()) {
                System.out.println(rs.getInt("item_id") + " | " +
                    rs.getString("name") + " | " +
                    rs.getString("category") + " | " +
                    String.format("%.2f", rs.getDouble("price")));
            }
        } catch (SQLException e) {}
    }
}

```

```

class MenuItem {
    private int itemId;
    private String name;
    private String category;
    private double price;

    // Constructor
    public MenuItem(int itemId, String name, String category, double price) {
        this.itemId = itemId;
        this.name = name;
        this.category = category;
        this.price = price;
    }

    //Include getters and setters
    public int getItemId() {
        return itemId;
    }

    public void setItemId(int itemId) {
        this.itemId = itemId;
    }
}

```

```
public String getName() {  
    return name;  
}  
  
public void setName(String name) {  
    this.name = name;  
}  
  
public String getCategory() {  
    return category;  
}  
  
public void setCategory(String category) {  
    this.category = category;  
}  
  
public double getPrice() {  
    return price;  
}  
  
public void setPrice(double price) {  
    this.price = price;  
}  
}  
//
```

Status : Correct

Marks : 10/10

2. Problem Statement

Create a JDBC-based Hospital Management System that handles runtime input to manage patient records. The system should allow users to:

Add a new patient (patient ID, name, age, status).

Update a patient's status.

View a specific patient's record by patient ID.

Display all patient records in the database.

Exit the application.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The patients table has already been created with the following structure:

Table Name: patients

Input Format

The first line of input consists of an integer choice, representing the operation to be performed:

(1 for Add Patient, 2 for Update Patient Status, 3 for View Patient Record, 4 for Display All Patients, 5 for Exit)

For choice 1 (Add Patient):

- The second line consists of an integer patient_id.
- The third line consists of a string name.
- The fourth line consists of an integer age.
- The fifth line consists of a string status.

For choice 2 (Update Patient Status):

- The second line consists of an integer patient_id.
- The third line consists of a string new_status.

For choice 3 (View Patient Record):

- The second line consists of an integer patient_id.

For choice 4 (Display All Patients):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Patient):

- Print "Patient added successfully" if the patient was added.
- Print "Failed to add patient." if the insertion failed.

For choice 2 (Update Patient Status):

- Print "Patient status updated successfully" if the update was successful.
- Print "Patient not found." if the specified patient ID does not exist.

For choice 3 (View Patient Record):

- Display the patient details in the format:
- ID: [patient_id] | Name: [name] | Age: [age] | Status: [status]
- Print "Patient not found." if the specified patient ID does not exist.

For choice 4 (Display All Patients):

- Display each patient on a new line in the format:
- ID | Name | Age | Status
- If no records are available, print nothing (or handle it with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Hospital Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

101

John Doe

45
Admitted
4
5

Output: Patient added successfully
ID | Name | Age | Status
101 | John Doe | 45 | Admitted
Exiting Hospital Management System.

Answer

```
import java.sql.*;
import java.util.Scanner;

class HospitalManagementSystem {
    public static void main(String[] args) {
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://
localhost/ri_db", "test", "test123");
            Scanner scanner = new Scanner(System.in)) {

            boolean running = true;

            while (running) {

                int choice = scanner.nextInt();

                switch (choice) {
                    case 1:
                        addPatient(conn, scanner);
                        break;
                    case 2:
                        updatePatientStatus(conn, scanner);
                        break;
                    case 3:
                        viewPatientRecord(conn, scanner);
                        break;
                    case 4:
                        displayAllPatients(conn);
                        break;
                    case 5:
                        System.out.println("Exiting Hospital Management System.");
                        running = false;
                        break;
                }
            }
        }
    }
}
```

```

        default:
            System.out.println("Invalid choice. Please try again.");
        }
    }
} catch (SQLException e) {
    e.printStackTrace();
}
}

// You are using Java
public static void addPatient(Connection conn, Scanner scanner) {
    // Write your code here
    try {
        int id = scanner.nextInt();
        scanner.nextLine(); // clear newline
        String name = scanner.nextLine();
        int age = scanner.nextInt();
        scanner.nextLine();
        String status = scanner.nextLine();
        String sql = "INSERT INTO patients (patient_id, name, age, status) VALUES
(?, ?, ?, ?)";
        PreparedStatement ps = conn.prepareStatement(sql);
        ps.setInt(1, id);
        ps.setString(2, name);
        ps.setInt(3, age);
        ps.setString(4, status);
        int rows = ps.executeUpdate();
        if (rows > 0) {
            System.out.println("Patient added successfully");
        } else {
            System.out.println("Failed to add patient.");
        }
    } catch (SQLException e) {
        System.out.println("Failed to add patient.");
    }
}

public static void updatePatientStatus(Connection conn, Scanner scanner) {
    // Write your code here
    try {
        int id = scanner.nextInt();
        scanner.nextLine();
        String newStatus = scanner.nextLine();
        String sql = "UPDATE patients SET status = ? WHERE patient_id = ?";

```

```

        PreparedStatement ps = conn.prepareStatement(sql);
        ps.setString(1, newStatus);
        ps.setInt(2, id);
        int rows = ps.executeUpdate();
        if (rows > 0) {
            System.out.println("Patient status updated successfully");
        } else {
            System.out.println("Patient not found.");
        }
    } catch (SQLException e) {
        System.out.println("Patient not found.");
    }
}

public static void viewPatientRecord(Connection conn, Scanner scanner) {
    // Write your code here
    try {
        int id = scanner.nextInt();
        String sql = "SELECT * FROM patients WHERE patient_id = " + id;
        Statement st = conn.createStatement();
        ResultSet rs = st.executeQuery(sql);
        if (rs.next()) {
            System.out.println(
                "ID: " + rs.getInt("patient_id") +
                " | Name: " + rs.getString("name") +
                " | Age: " + rs.getInt("age") +
                " | Status: " + rs.getString("status")
            );
        } else {
            System.out.println("Patient not found.");
        }
    } catch (SQLException e) {
        System.out.println("Patient not found.");
    }
}

public static void displayAllPatients(Connection conn) {
    // Write your code here
    try {
        String sql = "SELECT * FROM patients ORDER BY patient_id";
        Statement st = conn.createStatement();
        ResultSet rs = st.executeQuery(sql);
        System.out.println("ID | Name | Age | Status");
        while (rs.next()) {

```

```
        System.out.println(
            rs.getInt("patient_id") + " | " +
            rs.getString("name") + " | " +
            rs.getInt("age") + " | " +
            rs.getString("status")
        );
    }
} catch (SQLException e) {
    // no output needed
}
}
```

Status : Correct

Marks : 10/10