

# Rajalakshmi Engineering College

Name: Ubendra L  
Email: 241901120@rajalakshmi.edu.in  
Roll no: 241901120  
Phone: 8610285702  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Bobby is tasked with processing a sequence of numbers from a monitoring system. He needs to extract a strictly increasing subsequence using an ArrayList. The program should dynamically add numbers to the ArrayList only if they are greater than the last number currently stored in the list. Bobby aims to efficiently utilize the dynamic resizing and indexing features of the ArrayList to solve this problem.

Help Bobby implement this solution.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of elements.

The second line consists of N space-separated integers, representing the elements.

### **Output Format**

The output prints the list of integers in increasing sequence, ignoring out-of-order elements.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 7

3 5 9 1 11 7 13

Output: [3, 5, 9, 11, 13]

### **Answer**

```
import java.util.ArrayList;
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int N = sc.nextInt();
        ArrayList<Integer> increasingList = new ArrayList<>();

        for (int i = 0; i < N; i++) {
            int num = sc.nextInt();

            if (increasingList.isEmpty() || num >
                increasingList.get(increasingList.size() - 1)) {
                increasingList.add(num);
            }
        }

        System.out.println(increasingList);
        sc.close();
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Ubendra L  
Email: 241901120@rajalakshmi.edu.in  
Roll no: 241901120  
Phone: 8610285702  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 0

#### Section 1 : Coding

##### 1. Problem Statement

Vikram loves listening to music and wants to create a simple playlist manager using Java Collections. The playlist supports the following operations:

"ADD <song>" Adds the song to the end of the playlist. "REMOVE <song>" Removes the first occurrence of the song from the playlist. If the song is not found, do nothing. "SHOW" Displays all songs in the playlist in order. If the playlist is empty, print "EMPTY". "NEXT" Moves to the next song in the playlist and prints its name. If the playlist is empty, print "EMPTY".

The playlist maintains a "current song" position that starts at the first song when it's added. The NEXT command moves to the next song and prints it, wrapping around to the first song after reaching the last song. When removing songs, the current position adjusts accordingly to maintain

proper navigation.

Help Vikram implement this playlist manager.

### ***Input Format***

The first line of the input consists of an integer n, the number of operations.

The next n lines, each containing a command:

- "ADD <song>"
- "REMOVE <song>"
- "SHOW"
- "NEXT"

### ***Output Format***

For each "SHOW" command, print the songs in order, separated by spaces.

For each "NEXT" command, print the next song in the playlist.

If no song exists, print "EMPTY".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 7

ADD song1

ADD song2

SHOW

NEXT

REMOVE song2

SHOW

NEXT

Output: song1 song2

song2

song1

song1

### ***Answer***

```

import java.util.LinkedList;
import java.util.Scanner;

public class PlaylistManager {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();

        LinkedList<String> playlist = new LinkedList<>();
        int currentIndex = -1;

        for (int i = 0; i < n; i++) {
            String command = sc.nextLine().trim();

            if (command.startsWith("ADD")) {
                String song = command.split(" ")[1];
                playlist.add(song);
                if (currentIndex == -1) {
                    currentIndex = 0;
                }
            }
            else if (command.startsWith("REMOVE")) {
                String song = command.split(" ")[1];
                int removeIndex = playlist.indexOf(song);
                if (removeIndex != -1) {
                    playlist.remove(song);
                    if (playlist.isEmpty()) {
                        currentIndex = -1;
                    }
                    else if (removeIndex < currentIndex) {
                        currentIndex--;
                    }
                    else if (removeIndex == currentIndex) {
                        if (currentIndex >= playlist.size()) {
                            currentIndex = 0;
                        }
                    }
                }
            }
            else if (command.equals("SHOW")) {
                if (playlist.isEmpty()) {
                    System.out.print("EMPTY ");
                }
                else {

```

```
        for (String song : playlist) {  
            System.out.print(song + " ");  
        }  
    }  
    }  
    else if (command.equals("NEXT")) {  
        if (playlist.isEmpty()) {  
            System.out.print("EMPTY ");  
        } else {  
            currentIndex = (currentIndex + 1) % playlist.size();  
            System.out.print(playlist.get(currentIndex) + " ");  
        }  
    }  
    }  
    }  
    sc.close();  
    }  
}
```

**Status :** Wrong

**Marks :** 0/10

# Rajalakshmi Engineering College

Name: Ubendra L  
Email: 241901120@rajalakshmi.edu.in  
Roll no: 241901120  
Phone: 8610285702  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 0

#### Section 1 : Coding

##### 1. Problem Statement

Assist Pranitha in developing a program that takes an integer N as input, representing the number of names to be read. Then read N names and store them in an ArrayList. Finally, input a search string and output the frequency of that string in the list of names.

Note: Some parts of the code are provided as snippets, and you need to complete the remaining sections by writing the necessary code.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of names to be read.

The following N lines consist of N names, as a string.



The last line consists of a string, representing the name to be searched.

### **Output Format**

The output prints a single integer, representing the frequency of the specified name in the given list.

If the specified name is not found, print 0.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

Alice

Bob

Ankit

Alice

Pranitha

Alice

Output: 2

### **Answer**

```
import java.util.ArrayList;
```

```
import java.util.Scanner;
```

```
public class NameFrequency {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int N = sc.nextInt();  
        ArrayList<String> names = new ArrayList<>();
```

```
        for (int i = 0; i < N; i++) {  
            names.add(sc.next());  
        }
```

```
        String searchName = sc.next();  
        int count = 0;
```

```
        for (String name : names) {  
            if (name.equals(searchName)) {
```

```
        count++;  
    }  
}  
  
    System.out.println(count);  
    sc.close();  
}  
}
```

**Status :** Wrong

**Marks :** 0/10

# Rajalakshmi Engineering College

Name: Ubendra L  
Email: 241901120@rajalakshmi.edu.in  
Roll no: 241901120  
Phone: 8610285702  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_PAH

Attempt : 1  
Total Mark : 30  
Marks Obtained : 30

#### Section 1 : Coding

##### 1. Problem Statement

Rekha is a teacher who wants to calculate the average of marks scored by her students in a test. She needs to store all the marks dynamically because the number of students may vary each time. Using an ArrayList allows her to easily add any number of marks without worrying about the initial size.

Help her implement the task.

##### ***Input Format***

The first line of input is an integer  $n$ , representing the number of students..

The second line of input consists of  $n$  double values, representing the marks of each student, separated by a space.

### **Output Format**

The output prints: "Average of the list: " followed by the average value formatted to two decimal places.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

1.0 2.0 3.0 4.0 5.0

Output: Average of the list: 3.00

### **Answer**

```
import java.util.ArrayList;
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();

        ArrayList<Double> marks = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            marks.add(sc.nextDouble());
        }

        double sum = 0.0;
        for (double mark : marks) {
            sum += mark;
        }

        double average = sum / n;
        System.out.printf("Average of the list: %.2f", average);

        sc.close();
    }
}
```

**Status : Correct**

**Marks : 10/10**

## 2. Problem Statement

Arun is building a task manager to keep track of tasks using a LinkedList. The task manager supports the following operations:

"ADD <task>" Adds the given task to the end of the list. "REMOVE" Removes the first task from the list. "SHOW" Displays all tasks in the list in order. If the list is empty, print "EMPTY".

Help Arun implement this functionality using a LinkedList.

### ***Input Format***

The first line of the input consists of an integer n, the number of operations.

The next n lines, each containing a command:

- "ADD <task>"
- "REMOVE"
- "SHOW"

### ***Output Format***

For each "SHOW" command, the output prints the tasks in order, separated by spaces.

If no tasks exist, print "EMPTY".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

ADD homework

ADD project

SHOW

REMOVE

SHOW

Output: homework project  
project

**Answer**

```
import java.util.LinkedList;
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();

        LinkedList<String> tasks = new LinkedList<>();

        for (int i = 0; i < n; i++) {
            String command = sc.nextLine().trim();

            if (command.startsWith("ADD")) {
                String task = command.split(" ")[1];
                tasks.add(task);
            }
            else if (command.equals("REMOVE")) {
                if (!tasks.isEmpty()) {
                    tasks.removeFirst();
                }
            }
            else if (command.equals("SHOW")) {
                if (tasks.isEmpty()) {
                    System.out.print("EMPTY ");
                }
                else {
                    for (String t : tasks) {
                        System.out.print(t + " ");
                    }
                }
            }
            sc.close();
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Aditi is analyzing stock market trends and wants to find the Next Greater Element (NGE) for each stock price in a list. The Next Greater Element for an element  $x$  in an array is the first element to the right that is greater than  $x$ . If no greater element exists, return -1 for that position.

Your task is to help Aditi by efficiently computing the Next Greater Element for each element in the given array using a Stack.

Example:

Input:

6

4 5 2 10 8 6

Output:

5 10 10 -1 -1 -1

Explanation:

For each element:

4   5 (next greater element)5   102   1010   -1 (No greater element)8   -16   -1

#### ***Input Format***

The first line contains an integer  $n$ , representing the number of elements.

The second line contains  $n$  space-separated integers  $\text{arr}[i]$ , where  $\text{arr}[i]$  is the stock price on the  $i$ -th day.

#### ***Output Format***

The output prints  $n$  space-separated integers representing the Next Greater Element for each element in the array.

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: 6

4 5 2 10 8 6

Output: 5 10 10 -1 -1 -1

**Answer**

```
import java.util.Scanner;
```

```
import java.util.Stack;
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);
```

```
        int n = sc.nextInt();
```

```
        int[] arr = new int[n];
```

```
        for (int i = 0; i < n; i++) {
```

```
            arr[i] = sc.nextInt();
```

```
        }
```

```
        int[] result = new int[n];
```

```
        Stack<Integer> stack = new Stack<>();
```

```
        for (int i = n - 1; i >= 0; i--) {
```

```
            while (!stack.isEmpty() && stack.peek() <= arr[i]) {
```

```
                stack.pop();
```

```
            }
```

```
            if (stack.isEmpty()) {
```

```
                result[i] = -1;
```

```
            } else {
```

```
                result[i] = stack.peek();
```

```
            }
```

```
            stack.push(arr[i]);
```

```
        }
```

```
        for (int i = 0; i < n; i++) {
```

```
            System.out.print(result[i] + " ");
```

```
        }
```

```
        sc.close();
```

```
    }
```

```
}
```

**Status : Correct**


**Marks : 10/10**



# Rajalakshmi Engineering College

Name: Ubendra L  
Email: 241901120@rajalakshmi.edu.in  
Roll no: 241901120  
Phone: 8610285702  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 20

#### Section 1 : Coding

##### 1. Problem Statement

Sarah, a warehouse manager, is managing a list of product names in her store's inventory system. She needs to perform basic operations like adding (inserting) new products, removing products that are sold out or discontinued, displaying all the products in stock, and searching for a specific product in the inventory list.

Sarah's goal is to manage the inventory using a list of product names (strings). The system allows her to perform the following operations using ArrayList:

Insert a Product: Sarah adds a new product to the inventory. Delete a Product: Sarah removes a product from the inventory when it's sold or discontinued. Display the Inventory: Sarah checks all the products currently available in the inventory. Search for a Product: Sarah searches for a

specific product in the inventory to check if it's available.

### ***Input Format***

The input consists of multiple space-separated values representing different operations on a product list. Each operation follows a specific format:

- 1 <product\_name> - Adds <product\_name> to the product list.
- 2 <product\_name> - Removes <product\_name> from the product list if it exists.
- 3 - Print all products currently on the list.
- 4 <product\_name> - Checks if <product\_name> exists in the list.

### ***Output Format***

The output displays,

For (choice 1) prints, " <item> has been added to the list."

For (choice 2) prints, " <item> has been removed from the list."

For (choice 3) prints, "Items in the list:" followed by each item in the list on a new line, or "The list is empty." if the list is empty.

For (choice 4) prints, " <item> is found in the list." or " <item> not found in the list."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1 apple 1 banana 2 apple 3 4 apple

Output: apple has been added to the list.

banana has been added to the list.

apple has been removed from the list.

Items in the list:

banana

apple not found in the list.

### ***Answer***

```
import java.util.ArrayList;
```

```
import java.util.Scanner;
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        ArrayList<String> inventory = new ArrayList<>();

        while (sc.hasNext()) {
            int choice = sc.nextInt();

            switch (choice) {
                case 1: {
                    String item = sc.next();
                    inventory.add(item);
                    System.out.print(item + " has been added to the list. ");
                    break;
                }
                case 2: {
                    String item = sc.next();
                    if (inventory.remove(item)) {
                        System.out.print(item + " has been removed from the list. ");
                    } else {
                        System.out.print(item + " not found in the list. ");
                    }
                    break;
                }
                case 3: {
                    if (inventory.isEmpty()) {
                        System.out.print("The list is empty. ");
                    } else {
                        System.out.print("Items in the list: ");
                        for (String item : inventory) {
                            System.out.print(item + " ");
                        }
                    }
                    break;
                }
                case 4: {
                    String item = sc.next();
                    if (inventory.contains(item)) {
                        System.out.print(item + " is found in the list. ");
                    }
                }
            }
        }
    }
}
```

```

        } else {
            System.out.print(item + " not found in the list. ");
        }
        break;
    }
    default:
        break;
    }
}
}
sc.close();
}
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        ArrayList<String> list = new ArrayList<>();

        String input = sc.nextLine();
        String[] commands = input.split(" ");
        int i = 0;
        while (i < commands.length) {
            int choice = Integer.parseInt(commands[i]);
            switch (choice) {
                case 1:
                    if (i + 1 < commands.length) {
                        StringListOperations.insertItem(list, commands[i + 1]);
                        i += 2;
                    } else {
                        System.out.println("No string provided for insertion.");
                        i++;
                    }
                    break;
                case 2:
                    if (i + 1 < commands.length) {
                        StringListOperations.deleteItem(list, commands[i + 1]);
                        i += 2;
                    } else {
                        System.out.println("No string provided for deletion.");
                        i++;
                    }
                    break;
                case 3:

```

```

StringListOperations.displayList(list);
i += 1;
break;
case 4:
    if (i + 1 < commands.length) {
        StringListOperations.searchItem(list, commands[i + 1]);
        i += 2;
    } else {
        System.out.println("No string provided for searching.");
        i++;
    }
    break;
}
}
}
}
}

```

**Status : Wrong**

**Marks : 0/10**

## 2. Problem Statement

Rahul, a stock trader, wants to analyze the stock prices of a company over several days. For each day, he wants to determine the stock span, which is the number of consecutive days (including the current day) where the stock price is less than or equal to the price on that day.

The stock span helps him understand how long a stock has been continuously increasing or staying the same. You need to help Rahul by computing the stock span for each day using a Stack data structure efficiently.

Example:

Input:

7

100 80 60 70 60 75 85

Output:

1 1 1 2 1 4 6

Explanation:

For each day:

Day 1: Price = 100    Span = 1 (Only this day)  
Day 2: Price = 80    Span = 1 (Only this day)  
Day 3: Price = 60    Span = 1 (Only this day)  
Day 4: Price = 70    Span = 2 (Includes today and previous day)  
Day 5: Price = 60    Span = 1 (Only this day)  
Day 6: Price = 75    Span = 4 (Includes today and previous three days)  
Day 7: Price = 85    Span = 6 (Includes today and previous five days)

### ***Input Format***

The first line contains an integer  $n$ , the number of days.

The second line contains  $n$  space-separated integers  $prices[i]$ , where  $prices[i]$  represents the stock price on the  $i$ -th day.

### ***Output Format***

The output prints  $n$  space-separated integers representing the stock span for each day.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 7

100 80 60 70 60 75 85

Output: 1 1 1 2 1 4 6

### ***Answer***

```
import java.util.*;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        int[] prices = new int[n];  
        for (int i = 0; i < n; i++) {  
            prices[i] = sc.nextInt();  
        }  
    }  
}
```

```

int[] span = new int[n];
Stack<Integer> stack = new Stack<>();
for (int i = 0; i < n; i++) {
    while (!stack.isEmpty() && prices[stack.peek()] <= prices[i]) {
        stack.pop();
    }
    span[i] = (stack.isEmpty()) ? (i + 1) : (i - stack.peek());
    stack.push(i);
}
for (int i = 0; i < n; i++) {
    System.out.print(span[i] + " ");
}
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Mesa, a store manager, needs a program to manage inventory items. Define a class ItemType with private attributes for name, deposit, and cost per day. Create an ArrayList in the Main class to store ItemType objects, allowing input and display.

Note: Use "%-20s%-20s%-20s" for formatting output in tabular format, display double values with 1 decimal place.

#### **Input Format**

The first line of input consists of an integer n, representing the number of items.

For each of the n items, there are three lines:

1. The name of the item (a string)
2. The deposit amount (a double value)
3. The cost per day (a double value)

#### **Output Format**

The output prints a formatted table with columns for name, deposit and cost per day.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

Laptop

10000.0

250.0

Light

1000.0

50.0

Fan

1000.0

100.0

Output: Name	Deposit	Cost Per Day
--------------	---------	--------------

Laptop	10000.0	250.0
--------	---------	-------

Light	1000.0	50.0
-------	--------	------

Fan	1000.0	100.0
-----	--------	-------

### **Answer**

```
import java.util.ArrayList;
```

```
import java.util.List;
```

```
import java.util.Scanner;
```

```
import java.util.*;
```

```
class ItemType {
```

```
    private String name;
```

```
    private double deposit;
```

```
    private double costPerDay;
```

```
    public ItemType(String name, double deposit, double costPerDay) {
```

```
        this.name = name;
```

```
        this.deposit = deposit;
```

```
        this.costPerDay = costPerDay;
```

```
    }
```

```
    public String getName() {
```

```
        return name;
```

```
    }
```



```

    public double getDeposit() {
        return deposit;
    }

    public double getCostPerDay() {
        return costPerDay;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        ArrayList<ItemType> items = new ArrayList<>();

        for (int i = 0; i < n; i++) {
            String name = sc.next();
            double deposit = sc.nextDouble();
            double costPerDay = sc.nextDouble();
            items.add(new ItemType(name, deposit, costPerDay));
        }

        System.out.printf("%-20s%-20s%-20s\n", "Name", "Deposit", "Cost Per Day");
        for (ItemType item : items) {
            System.out.printf("%-20s%-20.1f%-20.1f\n",
                item.getName(), item.getDeposit(), item.getCostPerDay());
        }
    }
}

class ArrayListObjectMain {
    public static void main(String args[]) {
        List<ItemType> items = new ArrayList<>();
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        for (int i = 0; i < n; i++) {
            String name = sc.nextLine();
            Double deposit = Double.parseDouble(sc.nextLine());
            Double costPerDay = Double.parseDouble(sc.nextLine());
            items.add(new ItemType(name, deposit, costPerDay));
        }
    }
}

```

```

        System.out.format("%-20s%-20s%-20s", "Name", "Deposit", "Cost Per Day");
        System.out.println();

        for (ItemType item : items) {
            System.out.println(item);
        }
    }
}

```

**Status :** Wrong

**Marks :** 0/10

#### 4. Problem Statement

Rahul is working on a list manipulation problem where he needs to reverse a specific subarray using a stack. Given an array and two indices  $l$  and  $r$ , he wants to reverse only the portion of the array from index  $l$  to  $r$  (both inclusive) while keeping the rest of the array unchanged.

Since Rahul wants to solve this problem efficiently, he decides to use a stack to reverse the subarray in  $O(r - l)$  time.

Your task is to help Rahul by implementing this functionality.

##### **Input Format**

The first line contains an integer  $n$ , the size of the array.

The second line contains  $n$  space-separated integers  $arr[i]$ .

The third line contains two integers  $l$  and  $r$ , denoting the start and end indices of the subarray to reverse.

Note: The array follows 0-based indexing.

##### **Output Format**

The output prints the modified array after reversing the subarray between indices  $l$  and  $r$ .

Refer to the sample output for formatting specifications.

### Sample Test Case

Input: 6

1 2 3 4 5 6

1 4

Output: 1 5 4 3 2 6

### Answer

```
import java.util.*;
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);
```

```
        int n = sc.nextInt();
```

```
        int[] arr = new int[n];
```

```
        for (int i = 0; i < n; i++) {
```

```
            arr[i] = sc.nextInt();
```

```
        }
```

```
        int l = sc.nextInt();
```

```
        int r = sc.nextInt();
```

```
        Stack<Integer> stack = new Stack<>();
```

```
        for (int i = l; i <= r; i++) {
```

```
            stack.push(arr[i]);
```

```
        }
```

```
        for (int i = l; i <= r; i++) {
```

```
            arr[i] = stack.pop();
```

```
        }
```

```
        for (int i = 0; i < n; i++) {
```

```
            System.out.print(arr[i] + " ");
```

```
        }
```

```
    }
```

```
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Ubendra L  
Email: 241901120@rajalakshmi.edu.in  
Roll no: 241901120  
Phone: 8610285702  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 14

#### Section 1 : MCQ

1. Which of the following methods removes and returns the last element from a LinkedList?

**Answer**

removeLast()

**Status : Correct**

**Marks : 1/1**

2. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("apple");
```

```
list.add("banana");  
list.add("cherry");  
list.add("banana");  
System.out.println(list.lastIndexOf("banana"));  
}  
}
```

**Answer**

3

**Status : Correct**

**Marks : 1/1**

3. What does the addFirst() method of LinkedList do?

**Answer**

Adds an element to the beginning of the list

**Status : Correct**

**Marks : 1/1**

4. Which method is used to add an element to the top of the stack?

**Answer**

push()

**Status : Correct**

**Marks : 1/1**

5. What will be the output of the following code?

```
import java.util.*;  
public class Main {  
    public static void main(String[] args) {  
        Stack<Integer> stack = new Stack<>();  
        for (int i = 1; i <= 3; i++)  
            stack.push(i * 2);  
        stack.pop();  
        stack.push(10);  
        System.out.println(stack.peek());  
    }  
}
```

```
}
```

**Answer**

10

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following code?

```
import java.util.ArrayList;
```

```
public class Main {  
    public static void main(String[] args) {  
        ArrayList<Integer> list = new ArrayList<>();  
        list.add(10);  
        list.add(20);  
        list.add(30);  
        System.out.println("Size of the list: " + list.size());  
    }  
}
```

**Answer**

Size of the list: 3

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following code?

```
import java.util.*;  
class Main {  
    public static void main(String[] args) {  
        ArrayList<Integer> list = new ArrayList<>();  
        list.add(1);  
        list.add(2);  
        list.add(3);  
        list.add(4);  
        list.set(2, 10);  
        System.out.println(list);  
    }  
}
```

```
}
```

**Answer**

[1, 2, 10, 4]

**Status :** Correct

**Marks :** 1/1

8. How can you access the first element of an ArrayList named as list?

**Answer**

list.get(0);

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(1);
        list.add(2);
        list.add(3);
        list.add(4);
        list.add(5);
        System.out.println(list.get(3));
    }
}
```

**Answer**

4

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```
import java.util.*;
class Main {
```

```
public static void main(String[] args) {  
    ArrayList<Integer> list = new ArrayList<>();  
    list.add(10);  
    list.add(20);  
    list.add(30);  
    list.remove(1);  
    System.out.println(list);  
}  
}
```

**Answer**

[20, 30]

**Status :** Wrong

**Marks :** 0/1

11. What will be the output of the following code?

```
import java.util.*;  
public class Main {  
    public static void main(String[] args) {  
        Stack<Integer> s = new Stack<>();  
        s.push(10);  
        s.push(20);  
        s.push(30);  
        System.out.println(s.peek());  
    }  
}
```

**Answer**

30

**Status :** Correct

**Marks :** 1/1

12. What is Collection in Java?

**Answer**

A group of objects

**Status :** Correct

**Marks :** 1/1



13. What will be the output of the following code?

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("Apple");
        list.add("Banana");
        list.remove("Apple");
        System.out.println(list);
    }
}
```

**Answer**

[Banana]

**Status :** Correct

**Marks :** 1/1

14. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("Java");
        list.add("Python");
        list.add("Java");
        list.add("C++");
        System.out.println(list.indexOf("Java"));
    }
}
```

**Answer**

0

**Status :** Correct

**Marks :** 1/1

15. What is the correct way to create an ArrayList in Java?

**Answer**

`ArrayList<String> list = new ArrayList<>();`

**Status :** Correct

**Marks :** 1/1