
Creating FoodBox project source code



DONE BY : B.UDAY NARASA REDDY

Backend

MavenWrapperDownloader.java

```
import java.net.*; import java.io.*;
import java.nio.channels.*; import
java.util.Properties;
    public class MavenWrapperDownloader {
        private static final String WRAPPER_VERSION =
"0.5.6";      private static final String DEFAULT_DOWNLOAD_URL
=
"https://repo.maven.apache.org/maven2/io/takari/mavenwrapper/"
        + WRAPPER_VERSION + "/maven-wrapper-" +
WRAPPER_VERSION + ".jar";      private static final
String MAVEN_WRAPPER_PROPERTIES_PATH =
        ".mvn/wrapper/maven-wrapper.properties";
        private static final String MAVEN_WRAPPER_JAR_PATH =
        ".mvn/wrapper/maven-wrapper.jar";      private
static final String
PROPERTY_NAME_WRAPPER_URL = "wrapperUrl";

        public static void main(String args[]) {
            System.out.println("- Downloader started");
            File baseDirectory = new File(args[0]);
```

```
System.out.println("- Using base directory: " +
```

```
baseDirectory.getAbsolutePath());
    File mavenWrapperPropertyFile = new
File(baseDirectory, MAVEN_WRAPPER_PROPERTIES_PATH);
String url = DEFAULT_DOWNLOAD_URL;
if(mavenWrapperPropertyFile.exists()) {
FileInputStream mavenWrapperPropertyFileInputStream =
null;        try {
mavenWrapperPropertyFileInputStream = new
FileInputStream(mavenWrapperPropertyFile);
        Properties mavenWrapperProperties = new
Properties();
mavenWrapperProperties.load(mavenWrapperPropertyFileInpu
tStream);        url =
mavenWrapperProperties.getProperty(PROPERTY_NAME_WRAPPER
_URL, url);
        } catch (IOException e) {
            System.out.println("- ERROR loading '" +
MAVEN_WRAPPER_PROPERTIES_PATH + "'");
        } finally {
            try {
if(mavenWrapperPropertyFileInputStream != null) {
mavenWrapperPropertyFileInputStream.close();
            }
        } catch (IOException e) {
```




```

        System.out.println("- Downloading from: " +
url);
        File outputFile = new
File(baseDirectory.getAbsolutePath(),
MAVEN_WRAPPER_JAR_PATH);
        if(!outputFile.getParentFile().exists()) {
            if(!outputFile.getParentFile().mkdirs()) {
                System.out.println(
                    "- ERROR creating output
directory" +
outputFile.getParentFile().getAbsolutePath() + "");
            }
        }
        System.out.println("- Downloading to: " +
outputFile.getAbsolutePath());
        try {
            downloadFileFromURL(url, outputFile);
            System.out.println("Done");
            System.exit(0);
        } catch (Throwable e) {
            System.out.println("- Error downloading");
            e.printStackTrace();
            System.exit(1);
        } } private static void
downloadFileFromURL(String urlString, File

```

```
destination) throws Exception {          if
(System.getenv("MVNW_USERNAME") != null &&
System.getenv("MVNW_PASSWORD") != null) {
```

A solid dark gray horizontal rectangular bar.A solid dark gray horizontal rectangular bar.

`String username =`

```
System.getenv("MVNW_USERNAME");
char[] password =
System.getenv("MVNW_PASSWORD").toCharArray();
    Authenticator.setDefault(new Authenticator()
{
    @Override
protected PasswordAuthentication
getPasswordAuthentication() {
return new
PasswordAuthentication(username, password);
    }
});
    URL website = new URL(urlString);
ReadableByteChannel rbc;
    rbc = Channels.newChannel(website.openStream());
    FileOutputStream fos = new
FileOutputStream(destination);
    fos.getChannel().transferFrom(rbc, 0,
Long.MAX_VALUE);    fos.close();
rbc.close();
}
```

maven-wrapper.properties

```
distributionUrl=https://repo.maven.apache.org/maven2/org/apache/maven/apache-maven/3.8.2/apache-maven-3.8.2bin.zip
wrapperUrl=https://repo.maven.apache.org/maven2/io/takari/maven-wrapper/0.5.6/maven-wrapper-0.5.6.jar
```

Foodbox.sql

```
SET SQL_MODE = "NO_AUTO_VALUE_ON_ZERO";
START TRANSACTION;
SET time_zone = "+00:00";
CREATE TABLE `address` (
  `id` int(11) NOT NULL,
  `street` varchar(55) NOT NULL,
  `city` varchar(55) NOT NULL,
  `zipCode` varchar(55) NOT NULL,
  `user_id` int(55) NOT NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4;
CREATE TABLE `cuisine` (
  `id` bigint(11) NOT NULL,
  `cuisine_name` varchar(411) NOT NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4;
INSERT INTO `cuisine` (`id`, `cuisine_name`) VALUES (1,
'Arab'),
(2, 'Chinese'),
(3, 'Persian'), (4,
'Indian'),
(5, 'Italian');
CREATE TABLE `product` (
  `id` bigint(11) NOT NULL,
  `name` varchar(111) NOT NULL,
  `description` varchar(1000) DEFAULT NULL,
```



```
`price` decimal(55,0) DEFAULT NULL,  
`image_url` varchar(500) DEFAULT NULL,  
`date_created` datetime(6) DEFAULT NULL,  
`last_updated` datetime(6) DEFAULT NULL,  
`cuisine_id` bigint(11) NOT NULL  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4;  
INSERT INTO `product` (`id`, `name`, `description`,  
`price`, `image_url`, `date_created`, `last_updated`,  
`cuisine_id`) VALUES  
(1, 'Hummus', 'There's a lot of controversy as to where  
hummus is really from. Is it Israeli, Greek or Arabic?  
Although the answer is not clear, there's no doubt that  
this is a staple dish in Arabic cuisine, making hummus a  
must-try for anyone looking to get better acquainted  
with the food from this region. This simple dish is made  
of chickpeas, tahini, garlic and lemon - and is simply  
delicious. It's best to order hummus to share and eat it  
with pita bread, it makes for an amazing appetizer!',  
'20',  
'https://img.theculturetrip.com/1440x/smart/wpcontent/up  
loads/2017/07/hummus-1058001_1920.jpg', '2021-  
09-15 23:17:00.000000', '2021-09-13 23:17:03.000000',  
1),
```

```
(2, 'Fattoush', 'This delicious bread salad is
traditional to the Levantine cuisine, common in Arabic
countries such as Lebanon and Syria. Fattoush is made
with mixed greens and small pieces of fried Arabic
bread, giving some crunchiness. It often also includes
pomegranate. This is again known as a great salad to
share with others, making the dining experience a way of
bringing people together and bonding over the
mouthwatering cuisine.', '23',
'https://img.theculturetrip.com/1440x807/smart/wpcontent
/uploads/2017/07/starter-
1872862_1920e1501253889682.jpg', '2021-07-15
23:17:00.000000',
'2021-09-06 08:52:35.000000', 1),
(4, 'Manakeesh', 'The pizza of the Arabic world,
manakeesh is a round bread sprinkled with either cheese,
ground meat or herbs (zaatar). It\'s ideal for breakfast
or lunch. Varieties come from both fancy Levantine
restaurants or street vendors.', '33',
'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g
_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcnnnext%2
Fdam%2Fassets%2F170209174500-manakeesh.jpg', '2021-07-15
23:17:00.000000', '2021-07-13 23:17:03.000000', 1), (5,
'Moutabal', 'Just when you\'re ready to declare hummus
the best dip on the planet, you find moutabal. Similar
```

to baba ghanoush, the dip offers a similar consistency with an eggplant kick. Spiced up with chili, it delivers a zing.', '12',

'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcdnnext%2Fdam%2Fassets%2F170209172813-baba-ganoush.jpg', '2021-07-15 23:17:00.000000', '2021-07-15 23:17:00.000000', 1),

(6, 'Umm ali', 'Egyptian bread pudding, or umm ali, is a hearty pastry cooked in milk and cream. Versions are made with croissant pieces, raisins, pistachios, vanilla and condensed milk.', '12',

'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcdnnext%2Fdam%2Fassets%2F170209174450-umm-ali.jpg', '2021-01-19 23:24:19.000000', '2021-05-19 23:24:19.000000', 1), (7,

'Shanklish', 'This cow or sheep milk cheese is usually fashioned into golf ball-sized bites and rolled in zaatar herbs or chili flakes (the latter version favored in Syria). Also often enjoyed with diced tomato, onion and olive oil.', '31',

'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcdnnext%2

Fdam%2Fassets%2F170209174456-shanklish.jpg', '2020-05-19 23:24:19.000000', '2021-05-19 23:24:19.000000', 1), (8, 'Shish tawook', 'Served with pure garlic paste, this simple skewered chicken dish is hugely popular in Lebanon, Syria, Egypt, Iraq and the Gulf region. Dishes are served with fries and pita bread.', '44', 'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcdnnext%2Fdam%2Fassets%2F170209174452-shish-tawook.jpg', '2021-03-14 23:24:19.000000', '2021-05-19 23:24:19.000000', 1), (9, 'Dolma', 'Dolma goes horribly wrong when the stuffed vine leaves become flaccid and slimy after being left out in the sun for too long. They need to be fresh with succulent lamb or juicy vegetables.', '31', 'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcdnnext%2Fdam%2Fassets%2F170209172805-dolma.jpg', '2021-08-19 23:24:19.000000', '2021-05-19 23:24:19.000000', 1), (10, 'Kofta', 'Common in Iran and Pakistan, these balls of minced lamb or beef have a spicy, onion kick.\r\nYou can fry, grill, barbecue or bake the patties, but they\'re best served with a distinctive spicy sauce. In the Arab region, you\'ll find them in cylinder shapes, often on a stick.', '41',

'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcnnnext%2Fdam%2Fassets%2F170209172746-kofta.jpg', '2021-11-19 23:24:19.000000', '2021-05-19 23:24:19.000000', 1), (11, 'Knafeh', 'This delicious cheesecake uses Nabusi cheese, which is common to Palestine, Syria and Lebanon. The blush coloring comes from orange blossom water or rose water.', '31',

'https://dynaimage.cdn.cnn.com/cnn/q_auto,w_602,c_fill,g_auto,h_339,ar_16:9/http%3A%2F%2Fcdn.cnn.com%2Fcnnnext%2Fdam%2Fassets%2F170209172748-knafeh.jpg', '2021-07-19 23:24:19.000000', '2021-05-19 23:24:19.000000', 1), (12, 'Murgh Makhani', 'Perhaps one of the most familiar Indian dish to the American diner, butter chicken first appeared in Delhi in the 1940s. It has a mild flavor that won\'t blow out your tastebuds, but you can increase the white pepper or curry powder for a more assertive taste.', '54',

'https://www.thespruceeats.com/thmb/HkR_HR9fqAR3HaC9cYNwW9diBo=/974x0/filters:no_upscale():max_bytes(150000):strip_icc():format(webp)/butter-chicken-479366-step-123536fe3a146d4f31abafaf571790e544.jpg', '2017-08-09 23:17:00.000000', '2021-08-12 23:17:00.000000', 4), (13, 'Chole', 'In Northern India, classic and easy chole

chickpea curry often appears as a favorite menu item and as a result, has become a worldwide sensation. It can also serve a crowd, especially if you serve it hot along with fried Indian leavened bread like poori or bhatura.

Once you have the chickpeas, onions, and tomatoes, along with garlic and ginger pastes, some common Indian spices will bring it all together.', '42',

'https://www.thespruceeats.com/thmb/XfZ-PtUQPfhu9QdurxuNpaxndDQ=/1300x0/filters:no_upscale():max_bytes(150000):strip_icc():format(webp)/chole-chickpeacurry-1957946-hero-

01cddf957cc78d4032ba29ec2adbc05a97.jpg', '2018-08-18 23:17:00.000000', '2021-08-12 23:17:00.000000', 4), (14, 'Tandoori Chicken', 'Although traditionally cooked in a clay oven, you can prepare the yogurt-marinated charred chicken in a regular oven (or on the grill). You do need to plan ahead, as the chicken should sit in the refrigerator for at least 6 hours or overnight to let the flavors develop. If you prefer, you can sear the marinated chicken cubes first on the stovetop to achieve that signature tandoori char.', '52',

'https://www.thespruceeats.com/thmb/SxIRu8AgdaHqXYKo10Gc9D97D1g=/1643x0/filters:no_upscale():max_bytes(150000):strip_icc():format(webp)/ChickenTandooriSprucef238bf7413984e088268565c5b660b11.jpg', '2019-05-07

23:24:19.000000', '2021-08-12 23:17:00.000000', 4), (15, 'Chicken Vindaloo Curry', 'This is a mild and sweetly-spiced recipe for chicken vindaloo curry. Contrary to current belief, curries do not have to be hot and fiery. In fact, they never started out that way in India. Creating the curry paste is the most important part of this dish, so don\'t skimp on the ingredients.', '63', 'https://www.thespruceeats.com/thmb/F8XL5PEpY4vE38-MEe8LDuclmtw=/900x0/filters:no_upscale():max_bytes(15000):strip_icc():format(webp)/authentic-chicken-vindaloo-recipe-468712017-step-hero_1-57c6cc32841d4726b5f2eedd298b206d.jpg', '2021-08-12 23:17:00.000000', '2021-05-19 23:24:19.000000', 5), (16, 'Lemon Rice', 'South Indian lemon rice makes a great weekday meal because it comes together quickly. It often appears solo or alongside raita, yogurt, chutney, or kosambari (a type of salad).', '42', 'https://www.thespruceeats.com/thmb/MmwoX0JRUMSC3gvaSXVvyX-PHE=/1729x0/filters:no_upscale():max_bytes(15000):strip_icc():format(webp)/south-indian-lemon-rice-1957723hero-02-18047e2504ad42fa96817e047c075ac3.jpg', '2021-0519 23:24:19.000000', '2021-05-19 23:24:19.000000', 4), (17, 'Naan', 'Naan, a puffy flatbread, goes with just about

everything, including many popular dishes like tandoori chicken and all kinds of kebabs. While naan traditionally bakes in a tandoor or earthen oven, they work just as well in your own oven. The ingredient list includes yeast, flour, sugar, and water, as well as yogurt and ghee.', '24',

'https://www.thespruceeats.com/thmb/6P7g2QY-3QHws6a58LrJ2tbbw2w=/1391x0/filters:no_upscale():max_bytes(150000):strip_icc():format(webp)/naan-leavenedindian-flatbread-1957348-final-08-

116a2e523f6e4ee693b1a9655784d9b9.jpg', '2021-05-02 23:24:19.000000', '2021-05-19 23:24:19.000000', 4), (18, 'Malai Prawn', 'This Bengali speciality often appears alongside jeera rice. Cook the shrimp in creamy coconut milk with whole spices for a deeply flavorful dish. Using head-on shrimp will add even more shellfish character, but you can peel and devein them first if you prefer.', '55',

'https://www.thespruceeats.com/thmb/lyFzDP7IniEpb1eW1E21rzpcvYc=/1237x0/filters:no_upscale():max_bytes(150000):strip_icc():format(webp)/creamy-prawn-curry-1957454-hero01-9e15ed0ddd334cf4a03533f0b72919b9.jpg', '2021-05-01 23:24:19.000000', '2021-05-19 23:24:19.000000', 4), (19, 'Vegan Basmati Rice', 'Fragrant, tender, and the perfect accompaniment to just about every main, all

Indian feasts need basmati rice. Try this restaurantstyle vegan recipe that results in a wonderfully spiced grain.', '44',
'https://www.thespruceeats.com/thmb/RLpF45cRVBDZAUzr83bTUg6L914=/1633x0/filters:no_upscale():max_bytes(150000):strip_icc():format(webp)/easy-vegan-indian-basmati-ricerecipe-3378479-hero-01-35f4f27d496c41fea81589a7dce17eb1.jpg', '2021-05-19 23:24:19.000000', '2021-05-19 23:24:19.000000', 4), (20, 'Tamarind-Stuffed Fish', 'A luxurious whole fish preparation flavored with tangy tamarind and fragrant barberries, perfect for Nowruz, the Persian new year. Find barberries in well-stocked Middle Eastern groceries. Get the recipe for Persian Tamarind-Stuffed Fish » Matt Taylor-Gross', '88',
'https://www.saveur.com/uploads/2019/02/08/VWK5QXQXNQDRTGHQGR3PR32C6M.jpg', '2021-08-12 23:17:00.000000', '2021-08-12 23:17:00.000000', 3),
(21, 'Chelo ba Tahdig', 'Iranians usually serve chelo ba tahdig with stew, kebabs, or meat dishes. Herbs and alliums, feta, or walnuts often share the table. Get the recipe for Steamed Saffron Rice with Tahdig (Chelo ba Tahdig) » Zachary Zavislak', '63',
'https://www.saveur.com/uploads/2019/03/11/WSVNQHIRDDTVZ

HYCGAMFEB5ZCM-1024x768.jpg', '2017-07-02
23:17:00.000000', '2021-07-15 23:17:00.000000', 3), (22,
'Kuku Sabzi', 'A classic Persian herb-loaded egg dish
with the fragrant lift of rose petals. Get the recipe
for Persian Kuku Sabzi » Matt Taylor-Gross',
'53',
'https://www.saveur.com/uploads/2019/01/16/R2FL55HMXTZNK
X7U75S4YEYS4U-1024x769.jpg', '2021-05-19
23:24:19.000000', '2021-05-19 23:24:19.000000', 3), (23,
'Tahcheen-e Morgh', 'Bake this tahcheen, a saffron rice
with chicken, in a clear glass baking dish so you can
check on the crisping of the rice's bottom layer. Get
the recipe for Baked Saffron Yogurt Rice with
Chicken (Tahcheen-e Morgh) » Zachary Zavislak', '36',
'https://www.saveur.com/uploads/2019/03/11/SI4KF6ISWT2J7
XCCEZRWOH7DFY-1024x768.jpg', '2021-08-12
23:17:00.000000', '2021-08-12 23:17:00.000000', 3), (24,
'Adas Polo', 'A thin layer of lavash bread can be cooked
beneath the rice to serve as a tahdig. Press it flat
against the pot for even cooking.', '63',
'https://www.saveur.com/uploads/2019/03/11/L2N233EB3VWQE
43J7IJHYBS3Z4-1024x768.jpg', '2021-08-12
23:17:00.000000', '2021-08-12 23:17:00.000000', 3), (25,
'Sichuan Pork', 'Sichuan Pork, actually, poached spicy
slices of pork) is a famous Sichuan cuisine

dish.\r\n\r\nRather than cooking pork by stir-frying or deep-frying, which consumes lots of oil and can very easily overcook the pork, it is boiled in water with a coating made from egg-white and starch to preserve its freshness and tenderness.\r\n\r\nThe meaty broth is typical Sichuan cuisine, featuring a peppery and spicy taste. When eating, you'll find each piece of meat contains abundant juices with a fresh and fragrant spicy aroma.', '68',

'https://images.chinahighlights.com/allpicture/2019/11/7b3afb974d7946bbbe397f7c_894x670.webp', '2021-07-15 23:17:00.000000', '2021-07-13 23:17:03.000000', 2), (26, 'Braised Pork Balls in Gravy', 'Braised pork balls in gravy are also known as “Chinese meatballs” (many of our clients call them this). If you like meatballs and spaghetti, you'll probably appreciate Chinese meatballs as well. The super-smooth and flavory gravy is almost like a “drug sauce” keeping your taste buds wanting more and more. How many calories does it have? Trust me, you wouldn't care at all!\r\n\r\nTip: We suggest that you only order this dish in a decent restaurant where the meat quality is guaranteed and the prescribed lean: fat pork ratio of 7:3 is achieved in each meat ball.', '61', 'https://images.chinahighlights.com/allpicture/2019/11/a47d9323b7ae409ba96e628d_894x596.webp', '2022-07-29

23:17:00.000000', '2021-07-15 23:17:00.000000', 2), (27, 'Shrimp with Vermicelli and Garlic', 'Shrimp with vermicelli and is a dish not only favored by foreigners but also the Chinese younger generation in recent years as well.\r\n\r\nThis steamed dish brings out the aroma of everything it has. The heavy garlic with a seafood sauce flavor blends with the freshness of juicy shrimp. The vermicelli at the bottom absorbs every single drip of tasty juice running down. Some Chinese yellow wine to capture the aroma and highlight the flavor is the secret to this delicacy.', '14',

'https://images.chinahighlights.com/allpicture/2019/11/fd729ddd3fdf4fd9beefc79e_894x594.webp', '2021-05-19 23:24:19.000000', '2021-05-19 23:24:19.000000', 2),

(28, 'Chow Mein', '"Chow mein" (炒面 chǎomiàn) is the Cantonese pronunciation of the Chinese characters above, which means stir-fried noodles. Generally speaking, this stir-fried dish consists of noodles, meat (usually chicken, beef, shrimp, or pork), onions and celery.\r\n\r\nFor making chow mein, the noodles need to be cooked in boiling water for a while. After they becoming cool, then move to the step of stir-frying. S', '28',

'https://images.chinahighlights.com/allpicture/2018/03/1

0725167158a4b8589bf3140_894x596.webp', '2021-08-15 23:17:00.000000', '2021-05-19 23:24:19.000000', 2), (29, 'Sweet and Sour Pork', 'Sweet and sour pork has a bright orange-red color, and a delicious sweet and sour taste.\r\n\r\nAt the very beginning there was only sweet and sour pork, but to meet demands, there have been some developments on this dish. Now, the pork can be substituted by other ingredients like chicken, beef or pork ribs. See How to Cook Sweet and Sour Pork.', '68', 'https://images.chinahighlights.com/allpicture/2019/11/a4ad4a7fe0cb401cb0be6383_894x598.webp', '2021-05-25 23:24:19.000000', '2021-05-19 23:24:19.000000', 2), (31, 'Pizza', 'Though a slab of flat bread served with oil and spices was around long before the unification Italy, there's perhaps no dish that is as common or as representative of the country as the humble pizza. Easy, cheap, and filling, pizza has long been a common snack or meal, especially in Naples where tomato sauce was first added. When the Italian Queen Margherita came through the bustling city on a tour of her kingdom in 1889 she asked to try this dish that she saw so many of her subjects eating. A local entrepreneur served her the now legendary combination of tomato sauce, mozzarella, and basil, creating (or more likely, branding) the

Margherita pizza. Whether by coincidence or design, the Margherita also displays the colors of the Italian flag.', '25',

'https://www.walksofitaly.com/blog/wpcontent/uploads/2011/05/DSC_0195-768x510.jpg', '2014-0705 23:17:00.000000', '2021-07-15 23:17:00.000000', 5), (32, 'Lasagna', 'Lasagna is a wide, flat pasta noodle, usually baked in layers in the oven. Like most Italian dishes, its origins are hotly contested, but we can at least say that's its stronghold is in the region of Emilia-Romagna, where it transformed from a poor man's food to a rich meal filled with the ragù, or meat sauce.', '86', 'https://www.walksofitaly.com/blog/wpcontent/uploads/2016/07/11735294004_b68f0ab3ef_k-768x512.jpg', '2017-05-10 23:24:19.000000', '2021-05-19 23:24:19.000000', 5),

(33, 'Ossobuco', 'The world-famous ossobuco alla milanese is a bone-in veal shank, cooked low and slow until meltingly tender in a broth of meat stock, white wine, and veggies. Traditionally, it's accompanied by a gremolata (lemon zest, garlic, and parsley) but that's optional. Although the Milanese like to claim this meaty masterpiece there are as many versions of it as there are nonnas in Lombardy, which is known for hearty, often

rustic dishes that are good at coating the ribs and staving off the winter chill. Despite the popularity of


```
ossobuco (which literally means 'hollow bone'), it's not always co
see it on restaurant menus because it needs about three hours of c
time. If you do get a chance to eat it in a restaurant or home, or
cook it yourself, you should jump at the opportunity. It's usually
accompanied by polenta or the next item on our list.', '73',
'https://www.walksofitaly.com/blog/wpcontent/uploads/2014/05/Osso-
768x515.jpg', '202108-24 23:17:00.000000', '2021-05-19 23:24:19.00
5),
(34, 'Polpette', 'Polpette can be made of meat, fish, potatoes, ri
vegetables and can be prepared stewed, baked or fried.', '63',
'http://yourguidetoitaly.com/slowitaly/wpcontent/uploads/2018/03/p
c.jpg', '2021-07-15
23:17:00.000000', '2021-07-12 23:17:03.000000', 5);
CREATE TABLE `users` (
  `id` bigint(11) NOT NULL,
  `type` int(11) NOT NULL DEFAULT 0,
  `username` varchar(111) NOT NULL,  `email` varchar(111)
NOT NULL,
  `password` varchar(111) NOT NULL,
  `phone` int(22) DEFAULT NULL,
  `street` varchar(50) DEFAULT NULL,  `city` varchar(50)
DEFAULT NULL,
  `zipcode` varchar(50) DEFAULT NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4;
```



```
INSERT INTO `users` (`id`, `type`, `username`, `email`,  
`password`, `phone`, `street`, `city`, `zipcode`) VALUES
```

[REDACTED]

[REDACTED]

```
(1, 1, 'admin', 'admin@admin.com', 'admin', 5555555,
```

```
'he', 'h', 'h'),
(2, 0, 'admin2', 'admin2@admin.com', 'admin2', 21, 'he',
'h', 'h'),
(4, 0, '2', 'mm@f.com', '1314', 1414, 'Al Dawhah Al
Janubiyah, Dhahran 34457', 'Dahran', '34466'),
(5, 0, '1', '1', '1', 1, '1', '1', '1');
ALTER TABLE `address`
  ADD PRIMARY KEY (`id`); ALTER
TABLE `cuisine`
  ADD PRIMARY KEY (`id`);

ALTER TABLE `product`
  ADD PRIMARY KEY (`id`),
  ADD KEY `cuisine_id` (`cuisine_id`);
ALTER TABLE `users`
  ADD PRIMARY KEY (`id`);

ALTER TABLE `address`
  MODIFY `id` int(11) NOT NULL AUTO_INCREMENT;
ALTER TABLE `cuisine`
  MODIFY `id` bigint(11) NOT NULL AUTO_INCREMENT,
  AUTO_INCREMENT=6;

ALTER TABLE `product`
```

```
MODIFY `id` bigint(11) NOT NULL AUTO_INCREMENT,  
AUTO_INCREMENT=58;
```

```
ALTER TABLE `users`
```

```
MODIFY `id` bigint(11) NOT NULL AUTO_INCREMENT,  
  
AUTO_INCREMENT=6;  
  
USE `phpmyadmin`;  
INSERT INTO `pma__table_uiprefs` (`username`, `db_name`,  
`table_name`, `prefs`, `last_update`) VALUES  
( 'root', 'foodbox', 'product',  
'{"sorted_col\\":\\"`product`.`date_created`  ASC\\"}',  
'2021-09-17 09:43:27');  
COMMIT;
```

MyDataRestConfig.java

```
package com.simplilearn.foodbox.config; import  
com.simplilearn.foodbox.entity.User; import  
com.simplilearn.foodbox.entity.Cuisine; import  
com.simplilearn.foodbox.entity.Product; import  
org.springframework.beans.factory.annotation.Autowired;  
import  
org.springframework.context.annotation.Configuration;  
import  
org.springframework.data.rest.core.config.RepositoryRes  
t Configuration; import
```

```
org.springframework.data.rest.webmvc.config.RepositoryR  
e stConfigurer; import  
org.springframework.http.HttpMethod;
```

```
import  
org.springframework.web.servlet.config.annotation.CorsRe
```

```
gistry; import
javax.persistence.EntityManager; import
javax.persistence.metamodel.EntityType;
import java.util.ArrayList; import
java.util.List; import java.util.Set;

@Configuration
public class MyDataRestConfig implements
RepositoryRestConfigurer {
    private EntityManager
entityManager;
    @Autowired public
MyDataRestConfig(EntityManager
theEntityManager) {        entityManager
= theEntityManager;
    }

    @Override public void
configureRepositoryRestConfiguration(RepositoryRestConfi
guration config, CorsRegistry cors) {
        HttpMethod[] theUnsupportedActions =
```



```
{HttpMethod.PUT, HttpMethod.POST, HttpMethod.DELETE};  
config.getExposureConfiguration()  
.forDomainType(Product.class)
```

```
.withItemExposure((metadata, httpMethods)
```

```

-> httpMethods.disable(theUnsupportedActions))
.withCollectionExposure((metdata, httpMethods) ->
httpMethods.disable(theUnsupportedActions));

config.getExposureConfiguration()
        .forDomainType(Cuisine.class)
        .withItemExposure((metdata, httpMethods)
-> httpMethods.disable(theUnsupportedActions))
.withCollectionExposure((metdata, httpMethods) ->
httpMethods.disable(theUnsupportedActions));
config.getExposureConfiguration()
        .forDomainType(User.class)
        .withItemExposure((metdata, httpMethods)
-> httpMethods.disable(theUnsupportedActions))
.withCollectionExposure((metdata, httpMethods) ->
httpMethods.disable(theUnsupportedActions));

        // call an internal helper method
exposeIds(config);
    }                                private    void
exposeIds(RepositoryRestConfiguration config) {
    Set<EntityType<?>> entities =
entityManager.getMetamodel().getEntities();

```

```
List<Class> entityClasses = new ArrayList<>();  
for (EntityType tempEntityType : entities) {
```

```
entityClasses.add(tempEntityType.getJavaType());  
}
```

```
package com.simplilearn.foodbox.controller;  
import com.simplilearn.foodbox.dao.ProductRepository;  
import com.simplilearn.foodbox.entity.Product; import  
org.springframework.beans.factory.annotation.Autowired;  
import  
org.springframework.data.rest.webmvc.ResourceNotFoundException;  
import org.springframework.http.ResponseEntity;  
import org.springframework.web.bind.annotation.*;  
import  
java.util.HashMap; import  
java.util.List; import  
java.util.Map;  
  
@CrossOrigin(origins = "http://localhost:4200")  
@RestController  
@RequestMapping("/api/v1/")
```

```
        Class[] domainTypes = entityClasses.toArray(new  
Class[0]);        config.exposeIdsFor(domainTypes);  
    }  
}
```

productController.java

```
public class ProductController {
```

```
@Autowired    private ProductRepository
productRepository;
    // get all products
@GetMapping("/products")    public
List<Product> getAllproducts(){
return productRepository.findAll();
    }

    // create product rest api
@PostMapping("/products")    public Product
createProduct(@RequestBody Product product) {
return productRepository.save(product);    }
    @GetMapping("/products/{id}")
public ResponseEntity<Product>
getproductById(@PathVariable Long id) {
    Product product = productRepository.findById(id)
        .orElseThrow(() -> new
ResourceNotFoundException("product not exist with id :"+
id));    return
ResponseEntity.ok(product);    }
    @PutMapping("/products/{id}")
public ResponseEntity<Product>
```



```
updateProduct(@PathVariable Long id, @RequestBody
Product productDetails){
    Product product = productRepository.findById(id)
```

```
.orElseThrow(() -> new  
ResourceNotFoundException("product not exist with id :")
```

```
+ id));
product.setName(productDetails.getName());


product.setDescription(productDetails.getDescription());
product.setPrice(productDetails.getPrice());


product.setImageUrl(productDetails.getImageUrl());

        Product updatedProduct =
productRepository.save(product);                return
ResponseEntity.ok(updatedProduct);
    }

    // delete product rest api
    @DeleteMapping("/products/{id}")    public
    ResponseEntity<Map<String, Boolean>>
    deleteProduct(@PathVariable Long id){
        Product product = productRepository.findById(id)
            .orElseThrow(() -> new
ResourceNotFoundException("product not exist with id :"+ id));
        productRepository.delete(product);
```

```
        Map<String, Boolean> response = new HashMap<>();
response.put("deleted", Boolean.TRUE);           return
ResponseEntity.ok(response);
    }
}
```



UserController.java

```
package com.simplilearn.foodbox.controller;
import com.simplilearn.foodbox.dao.UserRepository;
import com.simplilearn.foodbox.entity.User; import
org.springframework.beans.factory.annotation.Autowired;
import
org.springframework.data.rest.webmvc.ResourceNotFoundException; import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*; import
java.util.List;
@CrossOrigin(origins = "http://localhost:4200")
@RestController
@RequestMapping("/api/v1/") public
class UserController {
    @Autowired    private UserRepository
userRepository;
    @GetMapping("/users")    public
List<User> getAllUsers(){    return
userRepository.findAll();    }
    @PostMapping("/users")    public User
createUser(@RequestBody User user) {    return
userRepository.save(user);    }
    @GetMapping("/users/{id}")
```



```
public ResponseEntity<User>
getUserById(@PathVariable Long id) {
    User user = userRepository.findById(id)
        .orElseThrow(() -> new
ResourceNotFoundException("user not exist with id :" +
id));
    return ResponseEntity.ok(user);
}
```

CuisineRepository.java

```
package com.simplilearn.foodbox.dao;
import com.simplilearn.foodbox.entity.Cuisine; import
org.springframework.data.jpa.repository.JpaRepository;
import
org.springframework.data.rest.core.annotation.Repository
RestResource; import
org.springframework.web.bind.annotation.CrossOrigin;
@CrossOrigin("http://localhost:4200") public
interface CuisineRepository extends
JpaRepository<Cuisine, Long> { }
```

ProductRepository.java

```
package com.simplilearn.foodbox.dao;
import
com.simplilearn.foodbox.entity.Produc
t;
```

```
import org.springframework.data.domain.Page; import
org.springframework.data.domain.Pageable; import
org.springframework.data.jpa.repository.JpaRepository;
import
org.springframework.web.bind.annotation.CrossOrigin;
import
org.springframework.web.bind.annotation.RequestParam;
@CrossOrigin("http://localhost:4200") public
interface ProductRepository extends
JpaRepository<Product, Long> {
    Page<Product> findAllByNameAsc(Pageable
pageable);

    Page<Product>
findAllByOrderByNameAsc(Pageable pageable);
    Page<Product> findByCuisine(@RequestParam("cuisine")
int cuisine, Pageable pageable);

    Page<Product>
findAllByCuisineAsc(@RequestParam("cuisine") int
cuisine, Pageable pageable);
```

```
Page<Product>
findByCuisineOrderByDateCreatedDesc(@RequestParam("cuisine") int cuisine, Pageable pageable);
// for searching
```

```
        Page<Product>
        findByNameContaining(@RequestParam("name") String name,
        Pageable pageable);

        Page<Product>
        findByNameContainingOrderByNameAsc(@RequestParam("name")
        String name, Pageable pageable);

        Page<Product>
        findByNameContainingOrderByDateCreatedDesc(@RequestParam
        ("name") String name, Pageable pageable);

    }
}
```

UserRepository.java

```
package com.simplilearn.foodbox.dao;
import com.simplilearn.foodbox.entity.User; import
org.springframework.data.domain.Page; import
org.springframework.data.domain.Pageable; import
org.springframework.data.jpa.repository.JpaRepository;
```

```
import  
org.springframework.web.bind.annotation.CrossOrigin;  
import  
org.springframework.web.bind.annotation.RequestParam;
```

```
@CrossOrigin("http://localhost:4200")
```

```
public interface UserRepository extends  
JpaRepository<User, Long> {  
  
    Page<User> findByUsername(@RequestParam("username")  
String username, Pageable pageable);  
}
```

Address.java

```
package com.simplilearn.foodbox.entity; import
lombok.Data;
import
javax.persistence.*;

@Entity
@Table(name="address")
@Data public class
Address {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    @Column(name = "id")
    private Long id;
```

Cuisine.java

```
package com.simplilearn.foodbox.entity;
import lombok.Getter; import
lombok.Setter;
```



```
import
javax.persistence.*;

@Entity
@Table(name="cuisine")
// @Data -- known bug
@Getter @Setter public
class Cuisine {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    @Column(name = "id")
    private Long id;

    @Column(name = "cuisine_name")
    private String cuisine_name;

    public String getCuisine_name() {
return cuisine_name;
    }
    public void setCuisine_name(String
cuisine_name) {
        this.cuisine_name = cuisine_name;
    }
}
```

```
    }    public Long  
getId() {    return  
id;  
    }
```


```


```

```

    public void setId(Long id) {
        this.id = id;
    }
}

```



Product.java

```
package com.simplilearn.foodbox.entity; import
lombok.Data; import
org.hibernate.annotations.CreationTimestamp; import
org.hibernate.annotations.UpdateTimestamp;
import javax.persistence.*;
import java.math.BigDecimal;
import java.util.Date;

@Entity
@Table(name="product")
@Data public class
Product {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    @Column(name = "id")
    private Long id;

    @Column(name = "cuisine_id")
    private int cuisine;

    @Column(name = "name")
    private String name;
```

```
        @Column(name = "description")
private String description;

        @Column(name = "price")
private BigDecimal price;

        @Column(name = "image_url")
private String imageUrl;

        @Column(name = "date_created")
        @CreationTimestamp
private Date dateCreated;

        @Column(name = "last_updated")
        @UpdateTimestamp
private Date lastUpdated;

    public String getName() {
return name;
    }
    public void setName(String
name) {
        this.name = name;
    }
}
```

```
    }    public String  
getDescription() {    return  
description;  
    }
```

```
public void setDescription(String description) {
```



```
        this.description = description;
    }
    public BigDecimal
getPrice() {        return price;
    }
    public void setPrice(BigDecimal
price) {        this.price = price;
    }
    public String
getImageUrl() {        return
imageUrl;
    }
    public void setImageUrl(String
imageUrl) {        this.imageUrl = imageUrl;
    }
    public Date
getDateCreated() {        return
dateCreated;
    }
    public void setDateCreated(Date
dateCreated) {        this.dateCreated =
dateCreated;
    }
    public Date
getLastUpdated() {        return
lastUpdated;
```

```
}
```

```
    public void setLastUpdated(Date lastUpdated) {  
this.lastUpdated = lastUpdated;  
    }    public Long  
getId() {    return  
id;  
    }    public void  
setId(Long id) {    this.id  
= id;  
    }  
}
```

User.java

```
package com.simplilearn.foodbox.entity; import
lombok.Data;
import
javax.persistence.*;

@Entity
@Table(name="users")
@Data public class
User {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
@Column(name = "id")
    private Long id;
```

```
@Column(name = "username")
private String username;

@Column(name = "email")
private String email;

@Column(name = "password")
private String password;

@Column(name = "phone")
private int phone;

@Column(name = "street")
private String street;
@Column(name = "city")
private String city;

@Column(name = "zipcode")
private String zipcode;
    public String getUsername()
{
    return username;
}
    public void setUsername(String
username) {
    this.username = username;
}
```


[Redacted]

[Redacted]

```
    public String getEmail() {  
return email;
```

```
    }    public void setEmail(String
email) {        this.email = email;
    }    public String
getPassword() {        return
password;
    }    public void setPassword(String
password) {        this.password = password;
    }    public int
getPhone() {        return
phone;
    }    public void setPhone(int
phone) {        this.phone = phone;
    }    public String
getStreet() {        return
street;
    }    public void setStreet(String
street) {        this.street = street;
    }
```

[Redacted]

[Redacted]

```
public String getCity() {
```



```
        return city;
    }    public void setCity(String
city) {        this.city = city;
    }    public String
getZipcode() {        return
zipcode;
    }    public void setZipcode(String
zipcode) {        this.zipcode = zipcode;
    }    public Long
getId() {        return
id;
    }    public void
setId(Long id) {        this.id
= id;
    }
}
```

Application-foodbox.java

```
package com.simplilearn.foodbox;
```

```
import org.springframework.boot.SpringApplication;
import
org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication public
class FoodboxApplication {

    public static void main(String[] args) {
        SpringApplication.run(FoodboxApplication.class,
args);
    }

}
```


FoodboxApplicationTests.java

```
package com.simplilearn.foodbox; import
org.junit.jupiter.api.Test; import
org.springframework.boot.test.context.SpringBootTest;
@SpringBootTest class
FoodboxApplicationTests {
    @Test    void
contextLoads() {
    }
}
```

Front-end

Add-product.component.html

```
<br><br>
<div class="login-form" style="width:44%" >
  <form (ngSubmit) = "handleAddProduct()">
    <h2 class="text-center">Add a New Product</h2>
    <div class="form-group">
      Name:<input [(ngModel)] = "product.name"
name = "name" type="text" class="form-control"
required="required">
    </div>
    <br>
    <div class="form-group">
      Description:
      <input [(ngModel)] = "product.description"
name = "description" type="text" class="form-control"
required="required" >
    </div>
    <br>
    <div class="form-group">
      Price:
      <input [(ngModel)] = "product.price" name =
"price" type="text" class="form-control"
required="required">
    </div>
    <br>
```



<div class="form-group">

Image URL:

```
        <input [(ngModel)] = "product.imageUrl" name
= "imageUrl" type="text" class="form-control"
required="required">
    </div>
    <br>
    <div class="form-group">
        Cuisine:
        <br>
        <select [(ngModel)]="product.cuisine" name =
"selectedCuisine">
            <option *ngFor="let cuisine of
productCuisines"
[ngValue]="cuisine.id">{{cuisine.cuisine_name}}</option>
        </select>
    </div>
    <br>
    <div class="form-group">
        <button type="submit" class="btn btn-success
btn-block">Add</button>
    </div>
</form>
</div>
```

Cart-details.component.html

```
<div class="main-content">
  <div class="section-content section-content-p30">
    <div class="container-fluid">
      <div *ngIf="username == null" class="alert
alert-danger col-md-12" role="alert">
```

You need to be registered in the system.

```



        </div>

        <div *ngIf="username != null &&
cartItems.length > 0">

            <table class="table table-bordered">
                <tr>
                    <th width="20%">Product
Image</th>
                    <th width="50%">Product
Detail</th>
                    <th width="30%"></th>
                </tr>

                <tr *ngFor="let tempCartItem of
cartItems">
                    <td>
                        
                    </td>
                    <td>
                        <p>{{ tempCartItem.name
}}</p>

```

<div class="row no-

```
gutters">
```

```
                <div class="col">
                    <button
(click)="incrementQuantity(tempCartItem)" class="btn
btn-primary btn-sm">
                        <i
class="fas fa-plus"></i>
                    </button>
                </div>
                <div class="col ml-4
```

```
mr-2">
```

```
                    {{
tempCartItem.quantity }}
                </div>
                <div class="col">
                    <button
(click)="decrementQuantity(tempCartItem)" class="btn
btn-primary btn-sm">
                        <i
class="fas fa-minus"></i>
                    </button>
                </div>
                <div class="col-
```



```

                <button
(click)="remove(tempCartItem)" class="au-btn-submit"
style="width:22px; background: red; color: white"
>Remove</button>

                <p class="mt-2"></p>
            </td>
        </tr>

        <tr>
            <td colspan="2"></td>
            <td style="font-weight: bold">
<p>Total Quantity: {{ totalQuantity }}</p>
                <p>Total Price: {{
totalPrice | currency: 'USD' }}</p>
                <a (click)="getTotalPrice()"
routerLink="/checkout"><button class="au-btn-submit"
style="width:181px; height: 55px; background: green;
color: white" >Confirm</button></a>

                <br>
            </td>
        </tr>
    </table>

```

```
<div *ngIf="cartItems.length == 0"
class="alert alert-warning col-md-12" role="alert">
    Your shopping cart is empty.
</div>
```

```
    </div>
  </div>
</div>
```

Checkout.html

```
<div class="main-content">
  <div class="section-content section-content-p30">
    <div class="container-fluid">

      <div style="margin-left: 15px;">
        <h6 style="font-size:22px;">
          <p>Thank you <b>{{username}}</b> for
purchasing our products. Your support and trust in us
are much appreciated. </p>
          <p>The total price of your bill is
<b>${{totalPrice}}</b> </p>
          <p>The products will be dilivred to you soon
to your address as following:</p>
          <p><b>city:</b> {{this.users[0]?.city}}</p>
          <p><b>street:</b>
{{this.users[0]?.street}}</p>
```

```
        <p><b>zipcode:</b>
{{this.users[0]?.zipcode}}</p>
    </h6>
</div>
    <a (click)="backHome()"><button class="au-
btnsubmit" style="width:181px; height: 55px; background:
green; color: white" >Confirm</button></a>
</div>
</div>
</div>
```

Login.component.html

```
<br>
<br>
<div class="login-form">
    <form (ngSubmit)="onSubmit()" >
        <h2 class="text-center">Log in</h2>
        <div>
            <div class="form-group">
                <input [(ngModel)] = "user.username" name =
"username" type="text" class="form-control"
placeholder="Username" required="required">
```

```
    </div>
    <br>
    <div class="form-group">
        <input [(ngModel)] = "user.password" name =
"password" type="password" class="form-control"
placeholder="Password" required="required">
    </div>
    <br>
    <div class="form-group">
        <button type="submit" class="btn btn-primary
btn-block">Log in</button>
    </div>
</div>
</form>
<p class="text-center"><a
routerLink="/register">Create an Account</a></p>
```


Product-category-menu.component.html

```
<div class="menu-sidebar-content js-scrollbar1">
  <nav class="navbar-sidebar">
    <ul class="list-unstyled navbar-list">
      <li style="margin-left: -17px; font-size: 27px;
font-family: Helvetica, sans-serif;"> Cuisines:</li>
      <li style="line-height: 2.3;"

          <i class="fa fa-angle-double-right"
style="font-size: 14px;"></i>
          <a style="text-decoration: none"
routerLink="/category"
[ngClass]="{'activelink': clicked}" (click)="Clicked()">
            All
          </a>
        </li>
      <li style="line-height: 2.3;" *ngFor="let
tempProductCategory of productCategories">
          <i class="fa fa-angle-double-right"
style="font-size: 14px;"></i>
          <a style="text-decoration: none"
routerLink="/category/{{ tempProductCategory.id }}"
routerLinkActive="active-link" (click)="UnClicked()">
            {{ tempProductCategory.cuisine_name
          }}
        </li>
    </ul>
  </nav>
</div>
```



```

        <br>

    </li>
    <br>
    <li>
        <button *ngIf="username == 'admin'"
routerLink="/add-product"    class="btn btn-primary btn-
sm">Add Product</button>
    </li>
</ul>
</nav>
</div>

```

Register.component.html

```

<br><br>
<div class="login-form" >
    <form    (ngSubmit) = "saveUser()">
        <h2 class="text-center">Register</h2>
        <div class="form-group">
            <input [(ngModel)] = "user.username" name =

```

```
"username" type="text" class="form-control"
placeholder="Username" required="required">
    </div>
    <br>
    <div class="form-group">
        <input [(ngModel)] = "user.email" name =
"email" type="text" class="form-control"
placeholder="Email" required="required">    </div>
    <br>
    <div class="form-group">
        <input [(ngModel)] = "user.password" name =
"password" type="password" class="form-control"
placeholder="Password" required="required">
    </div>
    <br>
    <div class="form-group">
        <input [(ngModel)] = "user.phone" name =
"phone" type="text" class="form-control"
placeholder="phone" required="required">
    </div>
    <br>

    <h6>Address</h6>
    <div class="form-group">
```

```
<input [(ngModel)] = "user.city" name =  
"city" type="text" class="form-control"  
placeholder="city" required="required">  
</div>  
<br>  
<div class="form-group">  
    <input [(ngModel)] = "user.street" name =  
"street" type="text" class="form-control"  
placeholder="street" required="required">  
</div>  
<br>  
<div class="form-group">  
    <input [(ngModel)] = "user.zipcode" name =  
"zipcode" type="text" class="form-control"  
placeholder="zipCode" required="required">  
</div>  
<br>  
  
    <div class="form-group">  
        <button type="submit" class="btn btn-primary  
btn-block">Register</button>  
    </div>
```

```
    </form>
    <p class="text-center"><a routerLink="/login">Back
to Login</a></p>
</div>
```

Search-component.html

```
div class="form-header">

    <input #myInput type="text"
placeholder="Search for products ..."
class="au-input au-input-xl"
        (keyup.enter)="doSearch(myInput.value)"  />

    <button (click)="doSearch(myInput.value)"
class="aubtn-submit">        Search
    </button>
</div>
```

Index.html

```
<!doctype html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>Foodbox</title>
  <base href="/">
  <meta name="viewport" content="width=device-width,
initial-scale=1">
  <link rel="icon" type="image/x-icon"
href="favicon.ico">
</head>
<body>
  <app-root></app-root>
</body>
</html>
```

Karma.conf.js

```
module.exports = function (config) {  config.set({
basePath: '',      frameworks: ['jasmine',
'@angular-devkit/buildangular'],      plugins: [
```

```
require('karma-jasmine'),      require('karma-  
chrome-launcher'),    require('karma-jasmine-html-  
reporter'),
```

```
require('karma-coverage'),
require('@angular-
devkit/buildangular/plugins/karma')
],
client: {
jasmine: {
},
clearContext: false },
jasmineHtmlReporter: {
suppressAll: true
}, coverageReporter: { dir:
require('path').join(__dirname,
'./coverage/foodbox'),
subdir: '.',
reporters: [
{ type: 'html' },
{ type: 'text-summary' }
] }, reporters:
['progress', 'kjhtml'], port:
9876, colors: true, logLevel:
config.LOG_INFO, autoWatch: true,
browsers: ['Chrome'], singleRun:
false,
restartOnFileChange: true
```



```
};
```

tsconfig.app.json

```
{
  "extends": "./tsconfig.json",
  "compilerOptions": {
    "outDir": "./out-tsc/app",
    "types": []
  },
  "files": [
    "src/main.ts",
    "src/polyfills.ts"
  ],
  "include": [
    "src/**/*.d.ts"
  ]
}
```

tsconfig.spec.json

```
{
  "extends": "./tsconfig.json",  "compilerOptions": {
```

```
"outDir": "./out-tsc/spec",
"types": [
  "jasmine"
],
"files": [
  "src/test.ts",
  "src/polyfills.ts"
],
"include": [
  "src/**/*.spec.ts",
  "src/**/*.d.ts"
]
}
```

=====X=====