

**Exp-1****Downloading and installing Hadoop on Ubuntu, Understanding different Hadoop modes, Startup scripts, Configuration files****Aim:**

To successfully install, configure, and run Hadoop on a local system using a single-node setup.

**Procedure:****1. Install Java and SSH:**

- Update your package lists and install OpenJDK 8 and SSH.

```
sudo apt update
```

```
sudo apt install openjdk-8-jdk
```

```
java -version # Verify Java installation
```

```
sudo apt install ssh
```

**2. Create Hadoop User:**

- Add a dedicated user for Hadoop and generate SSH keys for passwordless SSH.

```
sudo adduser hadoop
```

```
su - hadoop # Switch to Hadoop user
```

```
ssh-keygen -t rsa
```

```
cat ~/.ssh/id_rsa.pub >> ~/.ssh/authorized_keys
```

```
chmod 640 ~/.ssh/authorized_keys
```

```
ssh localhost # Test SSH connection to localhost
```

**3. Download and Install Hadoop:**

- Download the latest Hadoop version (3.3.6), extract the tarball, and move it to the desired location.

```
wget https://downloads.apache.org/hadoop/common/hadoop-3.3.6/hadoop-3.3.6.tar.gz
```

```
tar -xvzf hadoop-3.3.6.tar.gz
```

```
mv hadoop-3.3.6 hadoop
```

**4. Configure Environment Variables:**

- **Update. bashrc to include Hadoop and Java paths.**

```
nano ~/.bashrc
```

```
# Add the following lines at the end
```

```
export JAVA_HOME=/usr/lib/jvm/java-8-openjdk-amd64
```

```
export HADOOP_HOME=$HOME/hadoop
export PATH=$PATH:$HADOOP_HOME/bin:$HADOOP_HOME/sbin
source ~/.bashrc # Apply changes
```

## 5. Edit Hadoop Configuration Files:

- Modify configuration files to set up the necessary Hadoop directories and services.
- **core-site.xml:**

```
nano $HADOOP_HOME/etc/hadoop/core-site.xml
```

```
# Add between <configuration></configuration>:
```

```
<property>
  <name>fs.defaultFS</name>
  <value>hdfs://localhost:9000</value>
</property>
```

- **hdfs-site.xml:**

```
nano $HADOOP_HOME/etc/hadoop/hdfs-site.xml
```

**Add:**

```
<property>
  <name>dfs.replication</name>
  <value>1</value>
</property>
<property>
  <name>dfs.namenode.name.dir</name>
  <value>file:///home/hadoop/hadoopdata/hdfs/namenode</value>
</property>
<property>
  <name>dfs.datanode.data.dir</name>
  <value>file:///home/hadoop/hadoopdata/hdfs/datanode</value>
</property>
```

- **mapred-site.xml:**

```
cp $HADOOP_HOME/etc/hadoop/mapred-site.xml.template
  $HADOOP_HOME/etc/hadoop/mapred-site.xml
```

```
nano $HADOOP_HOME/etc/hadoop/mapred-site.xml
```

**Add:**

```
<property>
  <name>mapreduce.framework.name</name>
  <value>yarn</value>
</property>
```

○

**yarn-site.xml:**

```
nano $HADOOP_HOME/etc/hadoop/yarn-site.xml
```

**Add:**

```
<property>
  <name>yarn.nodemanager.aux-services</name>
  <value>mapreduce_shuffle</value>
</property>
```

**6. Format the NameNode:**

- Format the HDFS NameNode.

```
hdfs namenode -format
```

**7. Start Hadoop:**

- Start Hadoop services (NameNode, DataNode, ResourceManager, and NodeManager).

```
start-all.sh
```

```
jps # Verify running services
```

**8. Access Web Interfaces:**

- Verify that Hadoop is running by accessing the following URLs:

- **NameNode:** <http://localhost:9870>
- **Resource Manager:** <http://localhost:8088>

**9. Stop Hadoop Cluster:**

- Stop all Hadoop services.

```
stop-all.sh
```

```
sathish@admin:~$ start-all.sh
WARNING: Attempting to start all Apache Hadoop daemons as sathish in 10 seconds.
WARNING: This is not a recommended production deployment configuration.
WARNING: Use CTRL-C to abort.
Starting namenodes on [localhost]
Starting datanodes
Starting secondary namenodes [admin]
Starting resourcemanager
Starting nodemanagers
sathish@admin:~$ jps
3121 DataNode
3602 ResourceManager
4170 Jps
3723 NodeManager
3373 SecondaryNameNode
2990 NameNode
sathish@admin:~$
```

Overview 'localhost:9000' (✓active)

Started:	Sat Sep 21 21:28:23 +0530 2024
Version:	3.4.0, rbd8b77f398f626bb7791783192ee7a5dfaec760
Compiled:	Mon Mar 04 11:59:00 +0530 2024 by root from (HEAD detached at release-3.4.0-RC3)
Cluster ID:	CID-653f4afa-bc4d-4111-9842-8c068261eaa
Block Pool ID:	BP-750355565-127.0.1.1-1724908368015

Summary

Security is off.

Safemode is off.

136 files and directories, 83 blocks (83 replicated blocks, 0 erasure coded block groups) = 219 total filesystem object(s).

Heap Memory used 88.72 MB of 376.5 MB Heap Memory. Max Heap Memory is 2.23 GB.

Non Heap Memory used 53.74 MB of 55.59 MB Committed Non Heap Memory. Max Non Heap Memory is <unbounded>.

Configured Capacity:	28.87 GB
Configured Remote Capacity:	0 B
DFS Used:	24.1 MB (0.08%)
Non DFS Used:	20.04 GB
DFS Remaining:	7.31 GB (25.32%)

**RESULT:**

The step-by-step installation and configuration of Hadoop on Ubuntu system have been successfully completed.