Rajalakshmi Engineering College

Name: Udhaya Karthikeyan

Email: 241801301@rajalakshmi.edu.in

Roll no: 241801301 Phone: 9363824545

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

- 1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
- 2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

- 1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
- 2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

- 1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
- 2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

```
Output: 10 is inserted in the queue.
    Elements in the queue are: 10
    Invalid option.
    Answer
    #include <stdio.h>
    #include <stdlib.h>
    #define max 5
    int queue[max];
    int front = -1, rear = -1;
   int insertq(int *data) {
      if (rear == max - 1) {
         return 0;
      } else {
         if (front == -1) {
           front = 0;
         rear++;
         queue[rear] = *data;
         return 1;
int delq() {
      if (front == -1 || front > rear) {
         printf("Queue is empty.\n");
         return -1;
      } else {
         int deletedData = queue[front];
         front++;
         printf("Deleted number is: %d\n", deletedData);
         return deletedData;
    }
    void display() {
if (front == -1 || front > rear) {
```

```
241801301
print
} else {
nr:
        printf("Queue is empty.\n");
         printf("Elements in the queue are: ");
         for (int i = front; i <= rear; i++) {
            printf("%d ", queue[i]);
         printf("\n");
    }
    int main()
       int data, reply, option;
       while (1)
         if (scanf("%d", &option) != 1)
            break:
         switch (option)
            case 1:
              if (scanf("%d", &data) != 1)
                 break;
              reply = insertq(&data);
              if (reply == 0)
                 printf("Queue is full.\n");
              else
                 printf("%d is inserted in the queue.\n", data);
              break;
            case 2:
                          Called without arguments
              delq(); //
              break;
            case 3:
              display();
              break:
            default:
              printf("Invalid option.\n");
              break;
         }
                                                         241801301
       return 0;
```

Status: Correct Marks: 10/10