

Babel

Localization and
internationalization

Unicode

T_EX

pdfT_EX

LuaT_EX

XeT_EX

Version 3.88.12052
2023/04/30

Javier Bezos
Current maintainer

Johannes L. Braams
Original author

Contents

I	User guide	4
1	The user interface	4
1.1	Monolingual documents	4
1.2	Multilingual documents	6
1.3	Mostly monolingual documents	7
1.4	Modifiers	8
1.5	Troubleshooting	8
1.6	Plain	9
1.7	Basic language selectors	9
1.8	Auxiliary language selectors	10
1.9	More on selection	11
1.10	Shorthands	12
1.11	Package options	15
1.12	The base option	17
1.13	ini files	17
1.14	Selecting fonts	25
1.15	Modifying a language	27
1.16	Creating a language	28
1.17	Digits and counters	32
1.18	Dates	33
1.19	Accessing language info	34
1.20	Hyphenation and line breaking	35
1.21	Transforms	37
1.22	Selection based on BCP 47 tags	41
1.23	Selecting scripts	42
1.24	Selecting directions	42
1.25	Language attributes	46
1.26	Hooks	46
1.27	Languages supported by babel with ldf files	48
1.28	Unicode character properties in luatex	49
1.29	Tweaking some features	49
1.30	Tips, workarounds, known issues and notes	50
1.31	Current and future work	51
1.32	Tentative and experimental code	51
2	Loading languages with language.dat	52
2.1	Format	52
3	The interface between the core of babel and the language definition files	53
3.1	Guidelines for contributed languages	54
3.2	Basic macros	54
3.3	Skeleton	55
3.4	Support for active characters	56
3.5	Support for saving macro definitions	57
3.6	Support for extending macros	57
3.7	Macros common to a number of languages	57
3.8	Encoding-dependent strings	58
3.9	Executing code based on the selector	60
II	Source code	61
4	Identification and loading of required files	61
5	locale directory	61

6	Tools	62
6.1	Multiple languages	66
6.2	The Package File (<code>\LaTeX</code> , <code>babel.sty</code>)	67
6.3	<code>base</code>	68
6.4	<code>key=value</code> options and other general option	68
6.5	Conditional loading of shorthands	70
6.6	Interlude for Plain	71
7	Multiple languages	71
7.1	Selecting the language	74
7.2	Errors	82
7.3	Hooks	84
7.4	Setting up language files	86
7.5	Shorthands	88
7.6	Language attributes	97
7.7	Support for saving macro definitions	98
7.8	Short tags	100
7.9	Hyphens	100
7.10	Multiencoding strings	101
7.11	Macros common to a number of languages	107
7.12	Making glyphs available	108
7.12.1	Quotation marks	108
7.12.2	Letters	109
7.12.3	Shorthands for quotation marks	110
7.12.4	Umlauts and tremas	111
7.13	Layout	112
7.14	Load engine specific macros	113
7.15	Creating and modifying languages	113
8	Adjusting the Babel behavior	135
8.1	Cross referencing macros	137
8.2	Marks	140
8.3	Preventing clashes with other packages	141
8.3.1	<code>ifthen</code>	141
8.3.2	<code>varioref</code>	141
8.3.3	<code>hhline</code>	142
8.4	Encoding and fonts	143
8.5	Basic bidi support	144
8.6	Local Language Configuration	147
8.7	Language options	148
9	The kernel of Babel (<code>babel.def</code>, <code>common</code>)	151
10	Loading hyphenation patterns	151
11	Font handling with <code>fontspec</code>	155
12	Hooks for XeTeX and LuaTeX	159
12.1	XeTeX	159
12.2	Layout	161
12.3	8-bit TeX	162
12.4	LuaTeX	163
12.5	Southeast Asian scripts	169
12.6	CJK line breaking	170
12.7	Arabic justification	172
12.8	Common stuff	176
12.9	Automatic fonts and ids switching	176
12.10	Bidi	182
12.11	Layout	184

12.12	Lua: transforms	191
12.13	Lua: Auto bidi with basic and basic-r	199
13	Data for CJK	210
14	The ‘nil’ language	210
15	Calendars	211
15.1	Islamic	211
16	Hebrew	213
17	Persian	217
18	Coptic and Ethiopic	218
19	Buddhist	218
20	Support for Plain T_EX (plain.def)	218
20.1	Not renaming hyphen.tex	218
20.2	Emulating some L ^A T _E X features	219
20.3	General tools	220
20.4	Encoding related macros	223
21	Acknowledgements	226

Troubleshooting

Paragraph ended before \UTFviii@three@octets was complete	5
No hyphenation patterns were preloaded for (babel) the language ‘LANG’ into the format	5
You are loading directly a language style	8
Unknown language ‘LANG’	9
Argument of \language@active@arg” has an extra }	12
Package babel Info: The following fonts are not babel standard families	27

Part I

User guide

What is this document about? This user guide focuses on internationalization and localization with \LaTeX and pdf \TeX , xetex and luatex with the babel package. There are also some notes on its use with e-Plain and pdf-Plain \TeX . Part II describes the code, and usually it can be ignored.

What if I'm interested only in the latest changes? Changes and new features with relation to version 3.8 are highlighted with **New X.XX**, and there are some notes for the latest versions in [the babel site](#). The most recent features can be still unstable.

Can I help? Sure! If you are interested in the \TeX multilingual support, please join the [kadingira mail list](#). You can follow the development of babel in [GitHub](#) and make suggestions; feel free to fork it and make pull requests. If you are the author of a package, send to me a few test files which I'll add to mine, so that possible issues can be caught in the development phase.

It doesn't work for me! You can ask for help in some forums like tex.stackexchange, but if you have found a bug, I strongly beg you to report it in [GitHub](#), which is much better than just complaining on an e-mail list or a web forum. Remember *warnings are not errors* by themselves, they just warn about possible problems or incompatibilities.

How can I contribute a new language? See section 3.1 for contributing a language.

I only need learn the most basic features. The first subsections (1.1-1.3) describe the traditional way of loading a language (with ldf files), which is usually all you need. The alternative way based on ini files, which complements the previous one (it does *not* replace it, although it is still necessary in some languages), is described below; go to 1.13.

I don't like manuals. I prefer sample files. This manual contains lots of examples and tips, but in GitHub there are many [sample files](#).

1 The user interface

1.1 Monolingual documents

In most cases, a single language is required, and then all you need in \LaTeX is to load the package using its standard mechanism for this purpose, namely, passing that language as an optional argument. In addition, you may want to set the font and input encodings. Another approach is making the language a global option in order to let other packages detect and use it. This is the standard way in \LaTeX for an option – in this case a language – to be recognized by several packages.

Many languages are compatible with xetex and luatex. With them you can use babel to localize the documents. When these engines are used, the Latin script is covered by default in current \LaTeX (provided the document encoding is UTF-8), because the font loader is preloaded and the font is switched to `lmroman`. Other scripts require loading `fontspec`. You may want to set the font attributes with `fontspec`, too.

EXAMPLE Here is a simple full example for “traditional” \TeX engines (see below for xetex and luatex). The packages `fontenc` and `inputenc` do not belong to babel, but they are included in the example because typically you will need them. It assumes UTF-8, the default encoding:

PDF \TeX

```
\documentclass{article}

\usepackage[T1]{fontenc}
```

```

\usepackage[french]{babel}

\begin{document}

Plus ça change, plus c'est la même chose!

\end{document}

```

Now consider something like:

```

\documentclass[french]{article}
\usepackage{babel}
\usepackage{varioref}

```

With this setting, the package `varioref` will also see the option `french` and will be able to use it.

EXAMPLE And now a simple monolingual document in Russian (text from the Wikipedia) with `xetex` or `luatex`. Note neither `fontenc` nor `inputenc` are necessary, but the document should be encoded in UTF-8 and a so-called Unicode font must be loaded (in this example `\babelfont` is used, described below).

LUATEX/XETEX

```

\documentclass[russian]{article}

\usepackage{babel}

\babelfont{rm}{DejaVu Serif}

\begin{document}

Россия, находящаяся на пересечении множества культур, а также
с учётом многонационального характера её населения, — отличается
высокой степенью этнокультурного многообразия и способностью к
межкультурному диалогу.

\end{document}

```

TROUBLESHOOTING A common source of trouble is a wrong setting of the input encoding. Depending on the \TeX version you can get the following somewhat cryptic error:

```
! Paragraph ended before \UTFviii@three@octets was complete.
```

Or the more explanatory:

```
! Package inputenc Error: Invalid UTF-8 byte ...
```

Make sure you set the encoding actually used by your editor.

NOTE Because of the way `babel` has evolved, “language” can refer to (1) a set of hyphenation patterns as preloaded into the format, (2) a package option, (3) an `ldf` file, and (4) a name used in the document to select a language or dialect. So, a package option refers to a language in a generic way – sometimes it is the actual language name used to select it, sometimes it is a file name loading a language with a different name, sometimes it is a file name loading several languages. Please, read the documentation for specific languages for further info.

TROUBLESHOOTING The following warning is about hyphenation patterns, which are not under the direct control of `babel`:

```
Package babel Warning: No hyphenation patterns were preloaded for
(babel)                  the language `LANG' into the format.
(babel)                  Please, configure your TeX system to add them and
(babel)                  rebuild the format. Now I will use the patterns
(babel)                  preloaded for \language=0 instead on input line 57.
```

The document will be typeset, but very likely the text will not be correctly hyphenated. Some languages may be raising this warning wrongly (because they are not hyphenated); it is a bug to be fixed – just ignore it. See the manual of your distribution (MacTeX, MikTeX, TeXLive, etc.) for further info about how to configure it.

NOTE With hyperref you may want to set the document language with something like:

```
\usepackage[pdflang=es-MX]{hyperref}
```

This is not currently done by babel and you must set it by hand.

NOTE Although it has been customary to recommend placing `\title`, `\author` and other elements printed by `\maketitle` after `\begin{document}`, mainly because of shorthands, it is advisable to keep them in the preamble. Currently there is no real need to use shorthands in those macros.

NOTE Babel does not make any readjustments by default in font size, vertical positioning or line height by default. This is on purpose because the optimal solution depends on the document layout and the font, and very likely the most appropriate one is a combination of these settings.

1.2 Multilingual documents

In multilingual documents, just use a list of the required languages as package or class options. The last language is considered the main one, activated by default. Sometimes, the main language changes the document layout (eg, spanish and french).

EXAMPLE In \LaTeX , the preamble of the document:

```
\documentclass{article}
\usepackage[dutch,english]{babel}
```

would tell \LaTeX that the document would be written in two languages, Dutch and English, and that English would be the first language in use, and the main one.

You can also set the main language explicitly, but it is discouraged except if there is a real reason to do so:

```
\documentclass{article}
\usepackage[main=english,dutch]{babel}
```

Examples of cases where `main` is useful are the following.

EXAMPLE Some classes load babel with a hardcoded language option. Sometimes, the main language can be overridden with something like that before `\documentclass`:

```
\PassOptionsToPackage{main=english}{babel}
```

NOTE Languages may be set as global and as package option at the same time, but in such a case you should set explicitly the main language with the package option `main`:

```
\documentclass[italian]{book}
\usepackage[ngerman,main=italian]{babel}
```

WARNING In the preamble the main language has *not* been selected, except hyphenation patterns and the name assigned to `\language` (in particular, shorthands, captions and date are not activated). If you need to define boxes and the like in the preamble, you might want to use some of the language selectors described below.

To switch the language there are two basic macros, described below in detail:
`\selectlanguage` is used for blocks of text, while `\foreignlanguage` is for chunks of text inside paragraphs.

EXAMPLE A full bilingual document with pdf_{TEX} follows. The main language is french, which is activated when the document begins. It assumes UTF-8:

PDF_{TEX}

```
\documentclass{article}

\usepackage[T1]{fontenc}

\usepackage[english,french]{babel}

\begin{document}

Plus ça change, plus c'est la même chose!

\selectlanguage{english}

And an English paragraph, with a short text in
\foreignlanguage{french}{français}.

\end{document}
```

EXAMPLE With xetex and luatex, the following bilingual, single script document in UTF-8 encoding just prints a couple of ‘captions’ and `\today` in Danish and Vietnamese. No additional packages are required, because the default font supports both languages.

LUATEX/XETEX

```
\documentclass{article}

\usepackage[vietnamese,danish]{babel}

\begin{document}

\prefacename, \alsoname, \today.

\selectlanguage{vietnamese}

\prefacename, \alsoname, \today.

\end{document}
```

NOTE Once loaded a language, you can select it with the corresponding BCP47 tag. See section 1.22 for further details.

1.3 Mostly monolingual documents

New 3.39 Very often, multilingual documents consist of a main language with small pieces of text in another languages (words, idioms, short sentences). Typically, all you need is to set the line breaking rules and, perhaps, the font. In such a case, babel now does not

require declaring these secondary languages explicitly, because the basic settings are loaded on the fly when the language is selected (and also when provided in the optional argument of `\babelfont`, if used.)

This is particularly useful, too, when there are short texts of this kind coming from an external source whose contents are not known on beforehand (for example, titles in a bibliography). At this regard, it is worth remembering that `\babelfont` does *not* load any font until required, so that it can be used just in case.

EXAMPLE A trivial document with the default font in English and Spanish, and FreeSerif in Russian is:

LUATEX/XETEX

```
\documentclass[english]{article}
\usepackage{babel}

\babelfont[russian]{rm}{FreeSerif}

\begin{document}

English. \foreignlanguage{russian}{Русский}.
\foreignlanguage{spanish}{Español}.

\end{document}
```

NOTE Instead of its name, you may prefer to select the language with the corresponding BCP47 tag. This alternative, however, must be activated explicitly, because a two- or three-letter word is a valid name for a language (eg, `lu` can be the locale name with tag `khb` or the tag for `lubakatanga`). See section 1.22 for further details.

New 3.84 With `pdfTeX`, when a language is loaded on the fly (actually, with `\babelprovide`) selectors now set the font encoding based on the list provided when loading `fontenc`. Not all scripts have an associated encoding, so this feature works only with Latin, Cyrillic, Greek, Arabic, Hebrew, Cherokee, Armenian, and Georgian, provided a suitable font is found.

1.4 Modifiers

New 3.9c The basic behavior of some languages can be modified when loading `babel` by means of *modifiers*. They are set after the language name, and are prefixed with a dot (only when the language is set as package option – neither global options nor the main key accepts them). An example is (spaces are not significant and they can be added or removed):¹

```
\usepackage[latin.medieval, spanish.notilde.lcroman, danish]{babel}
```

Attributes (described below) are considered modifiers, ie, you can set an attribute by including it in the list of modifiers. However, modifiers are a more general mechanism.

1.5 Troubleshooting

- Loading directly `sty` files in \LaTeX (ie, `\usepackage{<language>}`) is deprecated and you will get the error:²

```
! Package babel Error: You are loading directly a language style.
(babel)                This syntax is deprecated and you must use
(babel)                \usepackage[language]{babel}.
```

¹No predefined “axis” for modifiers are provided because languages and their scripts have quite different needs.

²In old versions the error read “You have used an old interface to call `babel`”, not very helpful.

- Another typical error when using babel is the following:³

```
! Package babel Error: Unknown language `#1'. Either you have
(babel)                misspelled its name, it has not been installed,
(babel)                or you requested it in a previous run. Fix its name,
(babel)                install it or just rerun the file, respectively. In
(babel)                some cases, you may need to remove the aux file
```

The most frequent reason is, by far, the latest (for example, you included spanish, but you realized this language is not used after all, and therefore you removed it from the option list). In most cases, the error vanishes when the document is typeset again, but in more severe ones you will need to remove the aux file.

1.6 Plain

In e-Plain and pdf-Plain, load languages styles with `\input` and then use `\begindocument` (the latter is defined by babel):

```
\input estonian.sty
\begindocument
```

WARNING Not all languages provide a sty file and some of them are not compatible with those formats. Please, refer to [Using babel with Plain](#) for further details.

1.7 Basic language selectors

This section describes the commands to be used in the document to switch the language in multilingual documents. In most cases, only the two basic macros `\selectlanguage` and `\foreignlanguage` are necessary. The environments `otherlanguage`, `otherlanguage*` and `hyphenrules` are auxiliary, and described in the next section.

The main language is selected automatically when the document environment begins.

`\selectlanguage` $\{ \langle language \rangle \}$

When a user wants to switch from one language to another he can do so using the macro `\selectlanguage`. This macro takes the language, defined previously by a language definition file, as its argument. It calls several macros that should be defined in the language definition files to activate the special definitions for the language chosen:

```
\selectlanguage{german}
```

This command can be used as environment, too.

NOTE For “historical reasons”, a macro name is converted to a language name without the leading `\`; in other words, `\selectlanguage{\german}` is equivalent to `\selectlanguage{german}`. Using a macro instead of a “real” name is deprecated. **New 3.43** However, if the macro name does not match any language, it will get expanded as expected.

NOTE Bear in mind `\selectlanguage` can be automatically executed, in some cases, in the auxiliary files, at heads and foots, and after the environment `otherlanguage*`.

WARNING If used inside braces there might be some non-local changes, as this would be roughly equivalent to:

```
{\selectlanguage{<inner-language>} ...}\selectlanguage{<outer-language>}
```

If you want a change which is really local, you must enclose this code with an additional grouping level.

³In old versions the error read “You haven’t loaded the language LANG yet”.

WARNING There are a couple of issues related to the way the language information is written to the auxiliary files:

- `\selectlanguage` should not be used inside some boxed environments (like floats or minipage) to switch the language if you need the information written to the aux be correctly synchronized. This rarely happens, but if it were the case, you must use `otherlanguage` instead.
- In addition, this macro inserts a `\write` in vertical mode, which may break the vertical spacing in some cases (for example, between lists). **New 3.64** The behavior can be adjusted with `\babeladjust{select.write=<mode>}`, where `<mode>` is `shift` (which shifts the skips down and adds a `\penalty`); `keep` (the default – with it the `\write` and the skips are kept in the order they are written), and `omit` (which may seem a too drastic solution, because nothing is written, but more often than not this command is applied to more or less short texts with no sectioning or similar commands and therefore no language synchronization is necessary).

`\foreignlanguage` [`<option-list>`]{`<language>`}{`<text>`}

The command `\foreignlanguage` takes two arguments; the second argument is a phrase to be typeset according to the rules of the language named in its first one.

This command (1) only switches the extra definitions and the hyphenation rules for the language, *not* the names and dates, (2) does not send information about the language to auxiliary files (i.e., the surrounding language is still in force), and (3) it works even if the language has not been set as package option (but in such a case it only sets the hyphenation patterns and a warning is shown). With the `bidir` option, it also enters in horizontal mode (this is not done always for backwards compatibility), and since it is meant for phrases only the text direction (and not the paragraph one) is set.

New 3.44 As already said, captions and dates are not switched. However, with the optional argument you can switch them, too. So, you can write:

```
\foreignlanguage[date]{polish}{\today}
```

In addition, captions can be switched with `captions` (or both, of course, with `date`, `captions`). Until 3.43 you had to write something like `{\selectlanguage{..} ..}`, which was not always the most convenient way.

1.8 Auxiliary language selectors

`\begin{otherlanguage}` {`<language>`} ... **`\end{otherlanguage}`**

The environment `otherlanguage` does basically the same as `\selectlanguage`, except that language change is (mostly) local to the environment.

Actually, there might be some non-local changes, as this environment is roughly equivalent to:

```
\begingroup
\selectlanguage{<inner-language>}
...
\endgroup
\selectlanguage{<outer-language>}
```

If you want a change which is really local, you must enclose this environment with an additional grouping, like braces `{}`.

Spaces after the environment are ignored.

`\begin{otherlanguage*}` [*<option-list>*]{*<language>*} ... `\end{otherlanguage*}`

Same as `\foreignlanguage` but as environment. Spaces after the environment are *not* ignored.

This environment was originally intended for intermixing left-to-right typesetting with right-to-left typesetting in engines not supporting a change in the writing direction inside a line. However, by default it never complied with the documented behavior and it is just a version as environment of `\foreignlanguage`, except when the option `bidi` is set – in this case, `\foreignlanguage` emits a `\leavevmode`, while `otherlanguage*` does not.

1.9 More on selection

`\babeltags` {*<tag1>* = *<language1>*, *<tag2>* = *<language2>*, ...}

New 3.9i In multilingual documents with many language-switches the commands above can be cumbersome. With this tool shorter names can be defined. It adds nothing really new – it is just syntactical sugar.

It defines `\text<tag1>{<text>}` to be `\foreignlanguage{<language1>}{<text>}`, and `\begin{<tag1>}` to be `\begin{otherlanguage*}{<language1>}`, and so on. Note `\<tag1>` is also allowed, but remember to set it locally inside a group.

WARNING There is a clear drawback to this feature, namely, the ‘prefix’ `\text...` is heavily overloaded in \TeX and conflicts with existing macros may arise (`\textlatin`, `\textbar`, `\textit`, `\textcolor` and many others). The same applies to environments, because `arabic` conflicts with `\arabic`. Furthermore, and because of this overloading, detecting the language of a chunk of text by external tools can become unfeasible. Except if there is a reason for this ‘syntactical sugar’, the best option is to stick to the default selectors or to define your own alternatives.

EXAMPLE With

```
\babeltags{de = german}
```

you can write

```
text \textde{German text} text
```

and

```
text
\begin{de}
  German text
\end{de}
text
```

NOTE Something like `\babeltags{finnish = finnish}` is legitimate – it defines `\textfinnish` and `\finnish` (and, of course, `\begin{finnish}`).

`\babelensure` [*include=<commands>*, *exclude=<commands>*, *fontenc=<encoding>*]{*<language>*}

New 3.9i Except in a few languages, like `ruussian`, captions and dates are just strings, and do not switch the language. That means you should set it explicitly if you want to use them, or hyphenation (and in some cases the text itself) will be wrong. For example:

```
\foreignlanguage{ruussian}{text \foreignlanguage{polish}{\seename} text}
```

Of course, \TeX can do it for you. To avoid switching the language all the while, `\babelensure` redefines the captions for a given language to wrap them with a selector:

```
\babelensure{polish}
```

By default only the basic captions and `\today` are redefined, but you can add further macros with the key `include` in the optional argument (without commas). Macros not to be modified are listed in `exclude`. You can also enforce a font encoding with the option `fontenc`.⁴ A couple of examples:

```
\babelensure[include=\Today]{spanish}  
\babelensure[fontenc=T5]{vietnamese}
```

They are activated when the language is selected (at the `afterextras` event), and it makes some assumptions which could not be fulfilled in some languages. Note also you should include only macros defined by the language, not global macros (eg, `\TeX` of `\dag`). With `ini` files (see below), captions are ensured by default.

1.10 Shorthands

A *shorthand* is a sequence of one or two characters that expands to arbitrary \TeX code. Shorthands can be used for different kinds of things; for example: (1) in some languages shorthands such as "a are defined to be able to hyphenate the word if the encoding is OT1; (2) in some languages shorthands such as ! are used to insert the right amount of white space; (3) several kinds of discretionaries and breaks can be inserted easily with "-", "=", etc. The package `inputenc` as well as `xetex` and `luatex` have alleviated entering non-ASCII characters, but minority languages and some kinds of text can still require characters not directly available on the keyboards (and sometimes not even as separated or precomposed Unicode characters). As to the point 2, now `pdfTeX` provides `\knbcode`, and `luatex` can manipulate the glyph list. Tools for point 3 can be still very useful in general. There are four levels of shorthands: *user*, *language*, *system*, and *language user* (by order of precedence). In most cases, you will use only shorthands provided by languages.

NOTE Keep in mind the following:

1. Activated chars used for two-char shorthands cannot be followed by a closing brace `}` and the spaces following are gobbled. With one-char shorthands (eg, `:`), they are preserved.
2. If on a certain level (system, language, user, language user) there is a one-char shorthand, two-char ones starting with that char and on the same level are ignored.
3. Since they are active, a shorthand cannot contain the same character in its definition (except if deactivated with, eg, `\string`).

TROUBLESHOOTING A typical error when using shorthands is the following:

```
! Argument of \language@active@arg" has an extra }.
```

It means there is a closing brace just after a shorthand, which is not allowed (eg, `"}`). Just add `{}` after (eg, `"{} }`).

```
\shorthandon {\shorthands-list}  
\shorthandoff *{\shorthands-list}
```

It is sometimes necessary to switch a shorthand character off temporarily, because it must be used in an entirely different way. For this purpose, the user commands `\shorthandoff` and `\shorthandon` are provided. They each take a list of characters as their arguments. The command `\shorthandoff` sets the `\catcode` for each of the characters in its argument to other (12); the command `\shorthandon` sets the `\catcode` to active (13). Both commands

⁴With it, encoded strings may not work as expected.

only work on ‘known’ shorthand characters, and an error will be raised otherwise. You can check if a character is a shorthand with `\ifbabelshorthand` (see below).

New 3.9a However, `\shorthandoff` does not behave as you would expect with characters like `~` or `^`, because they usually are not “other”. For them `\shorthandoff*` is provided, so that with

```
\shorthandoff*{~^}
```

`~` is still active, very likely with the meaning of a non-breaking space, and `^` is the superscript character. The catcodes used are those when the shorthands are defined, usually when language files are loaded.

If you do not need shorthands, or prefer an alternative approach of your own, you may want to switch them off with the package option `shorthands=off`, as described below.

WARNING It is worth emphasizing these macros are meant for temporary changes. Whenever possible and if there are not conflicts with other packages, shorthands must be always enabled (or disabled).

\usesshorthands `*{\langle char \rangle}`

The command `\usesshorthands` initiates the definition of user-defined shorthand sequences. It has one argument, the character that starts these personal shorthands.

New 3.9a User shorthands are not always alive, as they may be deactivated by languages (for example, if you use `"` for your user shorthands and switch from german to french, they stop working). Therefore, a starred version `\usesshorthands*{\langle char \rangle}` is provided, which makes sure shorthands are always activated.

Currently, if the package option `shorthands` is used, you must include any character to be activated with `\usesshorthands`. This restriction will be lifted in a future release.

\defineshorthand `[\langle language \rangle, \langle language \rangle, ...]{\langle shorthand \rangle}{\langle code \rangle}`

The command `\defineshorthand` takes two arguments: the first is a one- or two-character shorthand sequence, and the second is the code the shorthand should expand to.

New 3.9a An optional argument allows to (re)define language and system shorthands (some languages do not activate shorthands, so you may want to add `\languageshorthands{\langle lang \rangle}` to the corresponding `\extras{\langle lang \rangle}`, as explained below). By default, user shorthands are (re)defined.

User shorthands override language ones, which in turn override system shorthands. Language-dependent user shorthands (new in 3.9) take precedence over “normal” user shorthands.

EXAMPLE Let’s assume you want a unified set of shorthand for discretionaries (languages do not define shorthands consistently, and `"`, `\`, `"=` have different meanings). You can start with, say:

```
\usesshorthands*{"}
\defineshorthand{"*}{\babelhyphen{soft}}
\defineshorthand{"-}{\babelhyphen{hard}}
```

However, the behavior of hyphens is language-dependent. For example, in languages like Polish and Portuguese, a hard hyphen inside compound words are repeated at the beginning of the next line. You can then set:

```
\defineshorthand[*polish,*portuguese]{"-}{\babelhyphen{repeat}}
```

Here, options with `*` set a language-dependent user shorthand, which means the generic one above only applies for the rest of languages; without `*` they would (re)define the language shorthands instead, which are overridden by user ones.

Now, you have a single unified shorthand (`"-`), with a content-based meaning (‘compound word hyphen’) whose visual behavior is that expected in each context.

`\languageshorthands` $\{\langle language \rangle\}$

The command `\languageshorthands` can be used to switch the shorthands on the language level. It takes one argument, the name of a language or none (the latter does what its name suggests).⁵ Note that for this to work the language should have been specified as an option when loading the babel package. For example, you can use in english the shorthands defined by `ngerman` with

```
\addto\extrasenglish{\languageshorthands{ngerman}}
```

(You may also need to activate them as user shorthands in the preamble with, for example, `\usesshorthands` or `\usesshorthands*`.)

EXAMPLE Very often, this is a more convenient way to deactivate shorthands than `\shorthandoff`, for example if you want to define a macro to easy typing phonetic characters with `tipa`:

```
\newcommand{\myipa}[1]{\{\languageshorthands{none}\tipaencoding#1}}
```

`\babelshorthand` $\{\langle shorthand \rangle\}$

With this command you can use a shorthand even if (1) not activated in shorthands (in this case only shorthands for the current language are taken into account, ie, not user shorthands), (2) turned off with `\shorthandoff` or (3) deactivated with the internal `\bbl@deactivate`; for example, `\babelshorthand{"u}` or `\babelshorthand{:}`. (You can conveniently define your own macros, or even your own user shorthands provided they do not overlap.)

EXAMPLE Since by default shorthands are not activated until `\begin{document}`, you may use this macro when defining the `\title` in the preamble:

```
\title{Documento científico\babelshorthand{"-}técnico}
```

For your records, here is a list of shorthands, but you must double check them, as they may change.⁶

Languages with no shorthands Croatian, English (any variety), Indonesian, Hebrew, Interlingua, Irish, Lower Sorbian, Malaysian, North Sami, Romanian, Scottish, Welsh

Languages with only " as defined shorthand character Albanian, Bulgarian, Danish, Dutch, Finnish, German (old and new orthography, also Austrian), Icelandic, Italian, Norwegian, Polish, Portuguese (also Brazilian), Russian, Serbian (with Latin script), Slovene, Swedish, Ukrainian, Upper Sorbian

Basque " ' ~

Breton : ; ? !

Catalan " ' `

Czech " -

Esperanto ^

Estonian " ~

French (all varieties) : ; ? !

Galician " . ' ~ < >

Greek ~

Hungarian `

Kurmanji ^

Latin " ^ =

⁵Actually, any name not corresponding to a language group does the same as none. However, follow this convention because it might be enforced in future releases of babel to catch possible errors.

⁶Thanks to Enrico Gregorio

Slovak " ^ ' -
Spanish " . < > ' ~
Turkish : ! =

In addition, the babel core declares ~ as a one-char shorthand which is let, like the standard ~, to a non breaking space.⁷

\ifbabelshorthand {<character>}{<true>}{<false>}

New 3.23 Tests if a character has been made a shorthand.

\aliasshorthand {<original>}{<alias>}

The command `\aliasshorthand` can be used to let another character perform the same functions as the default shorthand character. If one prefers for example to use the character / over " in typing Polish texts, this can be achieved by entering `\aliasshorthand{"}{/}`. For the reasons in the warning below, usage of this macro is not recommended.

NOTE The substitute character must *not* have been declared before as shorthand (in such a case, `\aliasshorthands` is ignored).

EXAMPLE The following example shows how to replace a shorthand by another

```
\aliasshorthand{~}{^}
\AtBeginDocument{\shorthandoff*{~}}
```

WARNING Shorthands remember somehow the original character, and the fallback value is that of the latter. So, in this example, if no shorthand is found, ^ expands to a non-breaking space, because this is the value of ~ (internally, ^ still calls `\active@char~` or `\normal@char~`). Furthermore, if you change the system value of ^ with `\defineshorthand` nothing happens.

1.11 Package options

New 3.9a These package options are processed before language options, so that they are taken into account irrespective of its order. The first three options have been available in previous versions.

KeepShorthandsActive Tells babel not to deactivate shorthands after loading a language file, so that they are also available in the preamble.

activeacute For some languages babel supports this options to set ' as a shorthand in case it is not done by default.

activegrave Same for `.

shorthands= <char><char>... | off

The only language shorthands activated are those given, like, eg:

```
\usepackage[esperanto,french,shorthands=:;!]{babel}
```

If ' is included, `activeacute` is set; if ` is included, `activegrave` is set. Active characters (like ~) should be preceded by `\string` (otherwise they will be expanded by \TeX before they are passed to the package and therefore they will not be recognized); however, t is provided for the common case of ~ (as well as c for not so common case of the comma). With `shorthands=off` no language shorthands are defined, As some languages use this mechanism for tools not available otherwise, a macro `\babelshorthand` is defined, which allows using them; see above.

⁷This declaration serves to nothing, but it is preserved for backward compatibility.

safe= none | ref | bib

Some L^AT_EX macros are redefined so that using shorthands is safe. With **safe=bib** only `\nocite`, `\bibcite` and `\bibitem` are redefined. With **safe=ref** only `\newlabel`, `\ref` and `\pageref` are redefined (as well as a few macros from `varioref` and `ifthen`).

With **safe=none** no macro is redefined. This option is strongly recommended, because a good deal of incompatibilities and errors are related to these redefinitions. As of

New 3.34, in ϵ T_EX based engines (ie, almost every engine except the oldest ones) shorthands can be used in these macros (formerly you could not).

math= active | normal

Shorthands are mainly intended for text, not for math. By setting this option with the value **normal** they are deactivated in math mode (default is **active**) and things like `#{a'}` (a closing brace after a shorthand) are not a source of trouble anymore.

config= *<file>*

Load *<file>*.`cfg` instead of the default config file `bblopts.cfg` (the file is loaded even with `noconfigs`).

main= *<language>*

Sets the main language, as explained above, ie, this language is always loaded last. If it is not given as package or global option, it is added to the list of requested languages.

headfoot= *<language>*

By default, headlines and footlines are not touched (only marks), and if they contain language-dependent macros (which is not usual) there may be unexpected results. With this option you may set the language in heads and foots.

noconfigs Global and language default config files are not loaded, so you can make sure your document is not spoilt by an unexpected `.cfg` file. However, if the key `config` is set, this file is loaded.

showlanguages Prints to the log the list of languages loaded when the format was created: number (remember dialects can share it), name, hyphenation file and exceptions file.

silent **New 3.9l** No warnings and no *infos* are written to the log file.⁸

hyphenmap= off | first | select | other | other*

New 3.9g Sets the behavior of case mapping for hyphenation, provided the language defines it.⁹ It can take the following values:

off deactivates this feature and no case mapping is applied;

first sets it at the first switching commands in the current or parent scope (typically, when the aux file is first read and at `\begin{document}`}, but also the first `\selectlanguage` in the preamble), and it's the default if a single language option has been stated;¹⁰

select sets it only at `\selectlanguage`;

other also sets it at other language;

other* also sets it at other language* as well as in heads and foots (if the option `headfoot` is used) and in auxiliary files (ie, at `\select@language`), and it's the default if several language options have been stated. The option `first` can be regarded as an optimized version of `other*` for monolingual documents.¹¹

⁸You can use alternatively the package `silence`.

⁹Turned off in plain.

¹⁰Duplicated options count as several ones.

¹¹Providing `foreign` is pointless, because the case mapping applied is that at the end of the paragraph, but if

bidi= default | basic | basic-r | bidi-l | bidi-r

New 3.14 Selects the bidi algorithm to be used in luatex and xetex. See sec. 1.24.

layout=

New 3.16 Selects which layout elements are adapted in bidi documents. See sec. 1.24.

provide= *

New 3.49 An alternative to `\babelprovide` for languages passed as options. See section 1.13, which describes also the variants `provide+=` and `provide*=`.

1.12 The base option

With this package option `babel` just loads some basic macros (those in `switch.def`), defines `\AfterBabelLanguage` and exits. It also selects the hyphenation patterns for the last language passed as option (by its name in `language.dat`). There are two main uses: classes and packages, and as a last resort in case there are, for some reason, incompatible languages. It can be used if you just want to select the hyphenation patterns of a single language, too.

\AfterBabelLanguage `{<option-name>}{<code>}`

This command is currently the only provided by `base`. Executes `<code>` when the file loaded by the corresponding package option is finished (at `\ldf@finish`). The setting is global. So

```
\AfterBabelLanguage{french}{...}
```

does ... at the end of `french.ldf`. It can be used in `ldf` files, too, but in such a case the code is executed only if `<option-name>` is the same as `\CurrentOption` (which could not be the same as the option name as set in `\usepackage!`).

EXAMPLE Consider two languages `foo` and `bar` defining the same `\macro` with `\newcommand`. An error is raised if you attempt to load both. Here is a way to overcome this problem:

```
\usepackage[base]{babel}
\AfterBabelLanguage{foo}{%
  \let\macroFoo\macro
  \let\macro\relax}
\usepackage[foo,bar]{babel}
```

NOTE With a recent version of \TeX , an alternative method to execute some code just after an `ldf` file is loaded is with `\AddToHook` and the hook `file/<language>.ldf/after`. `Babel` does not predeclare it, and you have to do it yourself with `\ActivateGenericHook`.

WARNING Currently this option is not compatible with languages loaded on the fly.

1.13 ini files

An alternative approach to define a language (or, more precisely, a *locale*) is by means of an `ini` file. Currently `babel` provides about 250 of these files containing the basic data required for a locale, plus basic templates for 500 about locales.

`ini` files are not meant only for `babel`, and they have been devised as a resource for other packages. To easy interoperability between \TeX and other systems, they are identified with the BCP 47 codes as preferred by the Unicode Common Locale Data Repository, which was used as source for most of the data provided by these files, too (the main exception being the `\...name` strings).

either `xetex` or `luatex` change this behavior it might be added. On the other hand, other is provided even if I [JBL] think it isn't really useful, but who knows.

Most of them set the date, and many also the captions (Unicode and LICR). They will be evolving with the time to add more features (something to keep in mind if backward compatibility is important). The following section shows how to make use of them by means of `\babelprovide`. In other words, `\babelprovide` is mainly meant for auxiliary tasks, and as alternative when the `ldf`, for some reason, does not work as expected.

EXAMPLE Although Georgian has its own `ldf` file, here is how to declare this language with an `ini` file in Unicode engines.

LUATEX/XETEX

```
\documentclass{book}

\usepackage{babel}
\babelprovide[import, main]{georgian}

\babelfont{rm}[Renderer=Harfbuzz]{DejaVu Sans}

\begin{document}

\tableofcontents

\chapter{სამზარეულო და სუფრის ტრადიციები}

ქართული ტრადიციული სამზარეულო ერთ-ერთი უმდიდრესია მთელ მსოფლიოში.

\end{document}
```

New 3.49 Alternatively, you can tell `babel` to load all or some languages passed as options with `\babelprovide` and not from the `ldf` file in a few few typical cases. Thus, `provide=*` means ‘load the main language with the `\babelprovide` mechanism instead of the `ldf` file’ applying the basic features, which in this case means `import, main`. There are (currently) three options:

- `provide=*` is the option just explained, for the main language;
- `provide+=*` is the same for additional languages (the main language is still the `ldf` file);
- `provide*=*` is the same for all languages, ie, main and additional.

EXAMPLE The preamble in the previous example can be more compactly written as:

```
\documentclass{book}
\usepackage[georgian, provide=*]{babel}
\babelfont{rm}[Renderer=Harfbuzz]{DejaVu Sans}
```

Or also:

```
\documentclass[georgian]{book}
\usepackage[provide=*]{babel}
\babelfont{rm}[Renderer=Harfbuzz]{DejaVu Sans}
```

NOTE The `ini` files just define and set some parameters, but the corresponding behavior is not always implemented. Also, there are some limitations in the engines. A few remarks follow (which could no longer be valid when you read this manual, if the packages involved have been updated). The `Harfbuzz` renderer has still some issues, so as a rule of thumb prefer the default renderer, and resort to `Harfbuzz` only if the former does not work for you. Fortunately, fonts can be loaded twice with different renderers; for example:

```
\babelfont[spanish]{rm}{FreeSerif}
\babelfont[hindi]{rm}[Renderer=Harfbuzz]{FreeSerif}
```

Arabic Monolingual documents mostly work in luatex, but it must be fine tuned, particularly math and graphical elements like picture. In xetex babel resorts to the bidi package, which seems to work.

Hebrew Niqqud marks seem to work in both engines, but depending on the font cantillation marks might be misplaced (xetex or luatex with Harfbuzz seems better).

Devanagari In luatex and the the default renderer many fonts work, but some others do not, the main issue being the ‘ra’. You may need to set explicitly the script to either deva or dev2, eg:

```
\newfontscript{Devanagari}{deva}
```

Other Indic scripts are still under development in the default luatex renderer, but should work with Renderer=Harfbuzz. They also work with xetex, although unlike with luatex fine tuning the font behavior is not always possible.

Southeast scripts Thai works in both luatex and xetex, but line breaking differs (rules are hard-coded in xetex, but they can be modified in luatex). Lao seems to work, too, but there are no patterns for the latter in luatex. Khemer clusters are rendered wrongly with the default renderer. The comment about Indic scripts and lualatex also applies here. Some quick patterns can help, with something similar to:

```
\babelprovide[import, hyphenrules=+]{lao}
\babelpatterns[lao]{lṇ lṃ lṂ lṁ lṅ lṅ lṅ} % Random
```

East Asia scripts Settings for either Simplified or Traditional should work out of the box, with basic line breaking with any renderer. Although for a few words and shorts texts the ini files should be fine, CJK texts are best set with a dedicated framework (CJK, luatexja, kotex, CTeX, etc.). This is what the class ltjbook does with luatex, which can be used in conjunction with the ldf for japanese, because the following piece of code loads luatexja:

```
\documentclass[japanese]{ltjbook}
\usepackage{babel}
```

Latin, Greek, Cyrillic Combining chars with the default luatex font renderer might be wrong; on the other hand, with the Harfbuzz renderer diacritics are stacked correctly, but many hyphenations points are discarded (this bug is related to kerning, so it depends on the font). With xetex both combining characters and hyphenation work as expected (not quite, but in most cases it works; the problem here are font clusters).

NOTE Wikipedia defines a *locale* as follows: “In computing, a locale is a set of parameters that defines the user’s language, region and any special variant preferences that the user wants to see in their user interface. Usually a locale identifier consists of at least a language code and a country/region code.” Babel is moving gradually from the old and fuzzy concept of *language* to the more modern of *locale*. Note each locale is by itself a separate “language”, which explains why there are so many files. This is on purpose, so that possible variants can be created and/or redefined easily.

Here is the list (u means Unicode captions, and l means LICR captions):

af	Afrikaans ^{ul}	asa	Asu
agq	Aghem	ast	Asturian ^{ul}
ak	Akan	az-Cyrl	Azerbaijani
am	Amharic ^{ul}	az-Latn	Azerbaijani
ar-DZ	Arabic ^u	az	Azerbaijani ^{ul}
ar-EG	Arabic ^u	bas	Basaa
ar-IQ	Arabic ^u	be	Belarusian ^{ul}
ar-JO	Arabic ^u	bem	Bemba
ar-LB	Arabic ^u	bez	Bena
ar-MA	Arabic ^u	bg	Bulgarian ^{ul}
ar-PS	Arabic ^u	bm	Bambara
ar-SA	Arabic ^u	bn	Bangla ^u
ar-SY	Arabic ^u	bo	Tibetan ^u
ar-TN	Arabic ^u	br	Breton ^{ul}
ar	Arabic ^u	brx	Bodo
as	Assamese ^u	bs-Cyrl	Bosnian

bs-Latn	Bosnian ^{ul}	fy	Western Frisian
bs	Bosnian ^{ul}	ga	Irish ^{ul}
ca	Catalan ^{ul}	gd	Scottish Gaelic ^{ul}
ce	Chechen	gl	Galician ^{ul}
cgg	Chiga	grc	Ancient Greek ^{ul}
chr	Cherokee	gsw	Swiss German
ckb-Arab	Central Kurdish ^u	gu	Gujarati
ckb-Latn	Central Kurdish ^u	guz	Gusii
ckb	Central Kurdish ^u	gv	Manx
cop	Coptic	ha-GH	Hausa
cs	Czech ^{ul}	ha-NE	Hausa
cu-Cyrs	Church Slavic ^u	ha	Hausa ^{ul}
cu-Glag	Church Slavic	haw	Hawaiian
cu	Church Slavic ^u	he	Hebrew ^{ul}
cy	Welsh ^{ul}	hi	Hindi ^u
da	Danish ^{ul}	hr	Croatian ^{ul}
dav	Taita	hsb	Upper Sorbian ^{ul}
de-1901	German ^{ul}	hu	Hungarian ^{ul}
de-1996	German ^{ul}	hy	Armenian ^{ul}
de-AT-1901	Austrian German ^{ul}	ia	Interlingua ^{ul}
de-AT-1996	Austrian German ^{ul}	id	Indonesian ^{ul}
de-AT	Austrian German ^{ul}	ig	Igbo
de-CH-1901	Swiss High German ^{ul}	ii	Sichuan Yi
de-CH-1996	Swiss High German ^{ul}	is	Icelandic ^{ul}
de-CH	Swiss High German ^{ul}	it	Italian ^{ul}
de	German ^{ul}	ja	Japanese ^u
dje	Zarma	jgo	Ngomba
dsb	Lower Sorbian ^{ul}	jmc	Machame
dua	Duala	ka	Georgian ^u
dyo	Jola-Fonyi	kab	Kabyle
dz	Dzongkha	kam	Kamba
ebu	Embu	kde	Makonde
ee	Ewe	kea	Kabuverdianu
el-polyton	Polytonic Greek ^{ul}	kgp	Kaingang
el	Greek ^{ul}	khq	Koyra Chiini
en-AU	Australian English ^{ul}	ki	Kikuyu
en-CA	Canadian English ^{ul}	kk	Kazakh
en-GB	British English ^{ul}	kkj	Kako
en-NZ	English ^{ul}	kl	Kalaallisut
en-US	American English ^{ul}	kln	Kalenjin
en	English ^{ul}	km	Khmer ^u
eo	Esperanto ^{ul}	kmr-Arab	Northern Kurdish ^u
es-MX	Mexican Spanish ^{ul}	kmr-Latn	Northern Kurdish ^{ul}
es	Spanish ^{ul}	kmr	Northern Kurdish ^{ul}
et	Estonian ^{ul}	kn	Kannada ^u
eu	Basque ^{ul}	ko-Hani	Korean ^u
ewo	Ewondo	ko	Korean ^u
fa	Persian ^u	kok	Konkani
ff	Fulah	ks	Kashmiri
fi	Finnish ^{ul}	ksb	Shambala
fil	Filipino	ksf	Bafia
fo	Faroese	ksh	Colognian
fr-BE	French ^{ul}	kw	Cornish
fr-CA	Canadian French ^{ul}	ky	Kyrgyz
fr-CH	Swiss French ^{ul}	la-x-classic	Classic Latin ^{ul}
fr-LU	French ^{ul}	la-x-ecclesia	Ecclesiastic Latin ^{ul}
fr	French ^{ul}	la-x-medieval	Medieval Latin ^{ul}
fur	Friulian ^{ul}	la	Latin ^{ul}

lag	Langi	rof	Rombo
lb	Luxembourgish ^{ul}	ru	Russian ^{ul}
lg	Ganda	rw	Kinyarwanda
lkt	Lakota	rwk	Rwa
ln	Lingala	sa-Beng	Sanskrit
lo	Lao ^u	sa-Deva	Sanskrit
lrc	Northern Luri	sa-Gujr	Sanskrit
lt	Lithuanian ^{ulll}	sa-Knda	Sanskrit
lu	Luba-Katanga	sa-Mlym	Sanskrit
luo	Luo	sa-Telu	Sanskrit
luy	Luyia	sa	Sanskrit
lv	Latvian ^{ul}	sah	Sakha
mas	Masai	saq	Samburu
mer	Meru	sbp	Sangu
mfe	Morisyen	sc	Sardinian
mg	Malagasy	se	Northern Sami ^{ul}
mgh	Makhuwa-Meetto	seh	Sena
mgo	Meta'	ses	Koyraboro Senni
mk	Macedonian ^{ul}	sg	Sango
ml	Malayalam ^u	shi-Latn	Tachelhit
mn	Mongolian	shi-Tfng	Tachelhit
mr	Marathi ^u	shi	Tachelhit
ms-BN	Malay	si	Sinhala ^u
ms-SG	Malay	sk	Slovak ^{ul}
ms	Malay ^{ul}	sl	Slovenian ^{ul}
mt	Maltese	smn	Inari Sami
mua	Mundang	sn	Shona
my	Burmese	so	Somali
mzn	Mazanderani	sq	Albanian ^{ul}
naq	Nama	sr-Cyrl-BA	Serbian ^{ul}
nb	Norwegian Bokmål ^{ul}	sr-Cyrl-ME	Serbian ^{ul}
nd	North Ndebele	sr-Cyrl-XK	Serbian ^{ul}
ne	Nepali	sr-Cyrl	Serbian ^{ul}
nl	Dutch ^{ul}	sr-Latn-BA	Serbian ^{ul}
nmg	Kwasio	sr-Latn-ME	Serbian ^{ul}
nn	Norwegian Nynorsk ^{ul}	sr-Latn-XK	Serbian ^{ul}
nnh	Ngiemboon	sr-Latn	Serbian ^{ul}
no	Norwegian ^{ul}	sr	Serbian ^{ul}
nus	Nuer	sv	Swedish ^{ul}
nyn	Nyankole	sw	Swahili
oc	Occitan ^{ul}	syr	Syriac
om	Oromo	ta	Tamil ^u
or	Odia	te	Telugu ^u
os	Ossetic	teo	Teso
pa-Arab	Punjabi	th	Thai ^{ul}
pa-Guru	Punjabi ^u	ti	Tigrinya
pa	Punjabi ^u	tk	Turkmen ^{ul}
pl	Polish ^{ul}	to	Tongan
pms	Piedmontese ^{ul}	tr	Turkish ^{ul}
ps	Pashto	twq	Tasawaq
pt-BR	Brazilian Portuguese ^{ul}	tzm	Central Atlas Tamazight
pt-PT	European Portuguese ^{ul}	ug	Uyghur ^u
pt	Portuguese ^{ul}	uk	Ukrainian ^{ul}
qu	Quechua	ur	Urdu ^u
rm	Romansh ^{ul}	uz-Arab	Uzbek
rn	Rundi	uz-Cyrl	Uzbek
ro-MD	Moldavian ^{ul}	uz-Latn	Uzbek
ro	Romanian ^{ul}	uz	Uzbek

vai-Latn	Vai	zgh	Standard Moroccan
vai-Vaii	Vai		Tamazight
vai	Vai	zh-Hans-HK	Chinese
vi	Vietnamese ^{ul}	zh-Hans-MO	Chinese
vun	Vunjo	zh-Hans-SG	Chinese
wae	Walser	zh-Hans	Chinese ^u
xog	Soga	zh-Hant-HK	Chinese
yav	Yangben	zh-Hant-MO	Chinese
yi	Yiddish	zh-Hant	Chinese ^u
yo	Yoruba	zh	Chinese ^u
yrl	Nheengatu	zu	Zulu
yue	Cantonese		

In some contexts (currently `\babel font`) an ini file may be loaded by its name. Here is the list of the names currently supported. With these languages, `\babel font` loads (if not done before) the language and script names (even if the language is defined as a package option with an ldf file). These are also the names recognized by `\babel provide` with a valueless `import`.

afrikaans	bosnian-latin
aghem	bosnian-latn
akan	bosnian
albanian	brazilian
american	breton
amharic	british
ancientgreek	bulgarian
arabic	burmese
arabic-algeria	canadian
arabic-DZ	cantonese
arabic-morocco	catalan
arabic-MA	centralatlastamazight
arabic-syria	centralkurdish
arabic-SY	chechen
armenian	cherokee
assamese	chiga
asturian	chinese-hans-hk
asu	chinese-hans-mo
australian	chinese-hans-sg
austrian	chinese-hans
azerbaijani-cyrillic	chinese-hant-hk
azerbaijani-cyrl	chinese-hant-mo
azerbaijani-latin	chinese-hant
azerbaijani-latn	chinese-simplified-hongkongsarchina
azerbaijani	chinese-simplified-macausarchina
bafia	chinese-simplified-singapore
bambara	chinese-simplified
basaa	chinese-traditional-hongkongsarchina
basque	chinese-traditional-macausarchina
belarusian	chinese-traditional
bemba	chinese
bena	churchslavic
bangla	churchslavic-cyrs
bodo	churchslavic-oldcyrillic ¹²
bosnian-cyrillic	churchsslavic-glag
bosnian-cyrl	churchsslavic-glagolitic

¹²The name in the CLDR is Old Church Slavonic Cyrillic, but it has been shortened for practical reasons.

colognian
cornish
croatian
czech
danish
duala
dutch
dzongkha
embu
english-au
english-australia
english-ca
english-canada
english-gb
english-newzealand
english-nz
english-unitedkingdom
english-unitedstates
english-us
english
esperanto
estonian
ewe
ewondo
faroese
filipino
finnish
french-be
french-belgium
french-ca
french-canada
french-ch
french-lu
french-luxembourg
french-switzerland
french
friulian
fulah
galician
ganda
georgian
german-at
german-austria
german-ch
german-switzerland
german
greek
gujarati
gusii
hausa-gh
hausa-ghana
hausa-ne
hausa-niger
hausa
hawaiian
hebrew
hindi
hungarian

icelandic
igbo
inarisami
indonesian
interlingua
irish
italian
japanese
jolafonyi
kabuverdianu
kabyle
kako
kalaallisut
kalenjin
kamba
kannada
kashmiri
kazakh
khmer
kikuyu
kinyarwanda
konkani
korean
koyraborosenni
koyrachiini
kwasio
kyrgyz
lakota
langi
lao
latvian
lingala
lithuanian
lowersorbian
lsorbian
lubakatanga
luo
luxembourgish
luyia
macedonian
machame
makhuwameetto
makonde
malagasy
malay-bn
malay-brunei
malay-sg
malay-singapore
malay
malayalam
maltese
manx
marathi
masai
mazanderani
meru
meta
mexican

mongolian
morisyen
mundang
nama
nepali
newzealand
ngiemboon
ngomba
norsk
northernluri
northernsami
northndebele
norwegianbokmal
norwegiannynorsk
nswissgerman
nuer
nyankole
nynorsk
occitan
oriya
oromo
ossetic
pashto
persian
piedmontese
polish
polytonicgreek
portuguese-br
portuguese-brazil
portuguese-portugal
portuguese-pt
portuguese
punjabi-arab
punjabi-arabic
punjabi-gurmukhi
punjabi-guru
punjabi
quechua
romanian
romansh
rombo
rundi
russian
rwa
sakha
samburu
samin
sango
sangu
sanskrit-beng
sanskrit-bengali
sanskrit-deva
sanskrit-devanagari
sanskrit-gujarati
sanskrit-gujr
sanskrit-kannada
sanskrit-knda
sanskrit-malayalam

sanskrit-mlym
sanskrit-telu
sanskrit-telugu
sanskrit
scottishgaelic
sena
serbian-cyrillic-bosniaherzegovina
serbian-cyrillic-kosovo
serbian-cyrillic-montenegro
serbian-cyrillic
serbian-cyrl-ba
serbian-cyrl-me
serbian-cyrl-xk
serbian-cyrl
serbian-latin-bosniaherzegovina
serbian-latin-kosovo
serbian-latin-montenegro
serbian-latin
serbian-latn-ba
serbian-latn-me
serbian-latn-xk
serbian-latn
serbian
shambala
shona
sichuanyi
sinhala
slovak
slovene
slovenian
soga
somali
spanish-mexico
spanish-mx
spanish
standardmoroccantamazight
swahili
swedish
swissgerman
tachelhit-latin
tachelhit-latn
tachelhit-tfng
tachelhit-tifnagh
tachelhit
taita
tamil
tasawaq
telugu
teso
thai
tibetan
tigrinya
tongan
turkish
turkmen
ukenglish
ukrainian
uppensorbian

urdu	vai-vaii
usenglish	vai
usorbian	vietnam
uyghur	vietnamese
uzbek-arab	vunjo
uzbek-arabic	walser
uzbek-cyrillic	welsh
uzbek-cyrl	westernfrisian
uzbek-latin	yangben
uzbek-latn	yiddish
uzbek	yoruba
vai-latin	zarma
vai-latn	zulu
vai-vai	

Modifying and adding values to ini files

New 3.39 There is a way to modify the values of ini files when they get loaded with `\babelprovide` and `import`. To set, say, `digits.native` in the `numbers` section, use something like `numbers/digits.native=abcdefghijkl`. Keys may be added, too. Without `import` you may modify the identification keys. This can be used to create private variants easily. All you need is to import the same ini file with a different locale name and different parameters.

1.14 Selecting fonts

New 3.15 Babel provides a high level interface on top of `fontspec` to select fonts. There is no need to load `fontspec` explicitly – babel does it for you with the first `\babelfont`.¹³

`\babelfont` [*<language-list>*] {*<font-family>*} [*<font-options>*] {*<font-name>*}

NOTE See the note in the previous section about some issues in specific languages.

The main purpose of `\babelfont` is to define at once in a multilingual document the fonts required by the different languages, with their corresponding language systems (script and language). So, if you load, say, 4 languages, `\babelfont{rm}{FreeSerif}` defines 4 fonts (with their variants, of course), which are switched with the language by babel. It is a tool to make things easier and transparent to the user.

Here *font-family* is `rm`, `sf` or `tt` (or newly defined ones, as explained below), and *font-name* is the same as in `fontspec` and the like.

If no language is given, then it is considered the default font for the family, activated when a language is selected.

On the other hand, if there is one or more languages in the optional argument, the font will be assigned to them, overriding the default one. Alternatively, you may set a font for a script – just precede its name (lowercase) with a star (eg, `*devanagari`). With this optional argument, the font is *not* yet defined, but just predeclared. This means you may define as many fonts as you want ‘just in case’, because if the language is never selected, the corresponding `\babelfont` declaration is just ignored.

Babel takes care of the font language and the font script when languages are selected (as well as the writing direction); see the recognized languages above. In most cases, you will not need *font-options*, which is the same as in `fontspec`, but you may add further key/value pairs if necessary.

EXAMPLE Usage in most cases is very simple. Let us assume you are setting up a document in Swedish, with some words in Hebrew, with a font suited for both languages.

¹³See also the package `combofont` for a complementary approach.

LUATEX/XETEX

```
\documentclass{article}

\usepackage[swedish, bidi=default]{babel}

\babelprovide[import]{hebrew}

\babelfont{rm}{FreeSerif}

\begin{document}

Svenska \foreignlanguage{hebrew}{עברית} svenska.

\end{document}
```

If on the other hand you have to resort to different fonts, you can replace the red line above with, say:

LUATEX/XETEX

```
\babelfont{rm}{Iwona}
\babelfont[hebrew]{rm}{FreeSerif}
```

`\babelfont` can be used to implicitly define a new font family. Just write its name instead of `rm`, `sf` or `tt`. This is the preferred way to select fonts in addition to the three basic families.

EXAMPLE Here is how to do it:

LUATEX/XETEX

```
\babelfont{kai}{FandolKai}
```

Now, `\kaifamily` and `\kaidefault`, as well as `\textkai` are at your disposal.

NOTE You may load `fontspec` explicitly. For example:

LUATEX/XETEX

```
\usepackage{fontspec}
\newfontscript{Devanagari}{deva}
\babelfont[hindi]{rm}{Shobhika}
```

This makes sure the OpenType script for Devanagari is `deva` and not `dev2`, in case it is not detected correctly. You may also pass some options to `fontspec`: with `silent`, the warnings about unavailable scripts or languages are not shown (they are only really useful when the document format is being set up).

NOTE Directionality is a property affecting margins, indentation, column order, etc., not just text. Therefore, it is under the direct control of the language, which applies both the script and the direction to the text. As a consequence, there is no need to set `Script` when declaring a font with `\babelfont` (nor `Language`). In fact, it is even discouraged.

NOTE `\fontspec` is not touched at all, only the preset font families (`rm`, `sf`, `tt`, and the like). If a language is switched when an *ad hoc* font is active, or you select the font with this command, neither the script nor the language is passed. You must add them by hand. This is by design, for several reasons—for example, each font has its own set of features and a generic setting for several of them can be problematic, and also preserving a “lower-level” font selection is useful.

NOTE The keys `Language` and `Script` just pass these values to the *font*, and do *not* set the script for the *language* (and therefore the writing direction). In other words, the `ini` file or `\babelprovide` provides default values for `\babelfont` if omitted, but the opposite is not true. See the note above for the reasons of this behavior.

WARNING Using `\setxxxxfont` and `\babelfont` at the same time is discouraged, but very often works as expected. However, be aware with `\setxxxxfont` the language system will not be set by babel and should be set with `fontspec` if necessary.

TROUBLESHOOTING *Package babel Info: The following fonts are not babel standard families.*

This is *not* an error. babel assumes that if you are using `\babelfont` for a family, very likely you want to define the rest of them. If you don't, you can find some inconsistencies between families. This checking is done at the beginning of the document, at a point where we cannot know which families will be used.

Actually, there is no real need to use `\babelfont` in a monolingual document, if you set the language system in `\setmainfont` (or not, depending on what you want).

As the message explains, *there is nothing intrinsically wrong* with not defining all the families. In fact, there is nothing intrinsically wrong with not using `\babelfont` at all. But you must be aware that this may lead to some problems.

NOTE `\babelfont` is a high level interface to `fontspec`, and therefore in xetex you can apply Mappings. For example, there is a set of [transliterations for Brahmic scripts](#) by Davis M. Jones. After installing them in you distribution, just set the map as you would do with `fontspec`.

1.15 Modifying a language

Modifying the behavior of a language (say, the chapter “caption”), is sometimes necessary, but not always trivial. In the case of caption names a specific macro is provided, because this is perhaps the most frequent change:

`\setlocalecaption` $\langle\textit{language-name}\rangle\langle\textit{caption-name}\rangle\langle\textit{string}\rangle$

New 3.51 Here *caption-name* is the name as string without the trailing name. An example, which also shows caption names are often a stylistic choice, is:

```
\setlocalecaption{english}{contents}{Table of Contents}
```

This works not only with existing caption names, because it also serves to define new ones by setting the *caption-name* to the name of your choice (name will be postpended). Captions so defined or redefined behave with the ‘new way’ described in the following note.

NOTE There are a few alternative methods:

- With data import’ed from ini files, you can modify the values of specific keys, like:

```
\babelprovide[import, captions/listtable = Lista de tablas]{spanish}
```

(In this particular case, instead of the captions group you may need to modify the `captions.licr` one.)

- The ‘old way’, still valid for many languages, to redefine a caption is the following:

```
\addto\captionenglish{%
  \renewcommand\contentsname{Foo}%
}
```

As of 3.15, there is no need to hide spaces with % (babel removes them), but it is advisable to do so. This redefinition is not activated until the language is selected.

- The ‘new way’, which is found in bulgarian, azerbaijani, spanish, french, turkish, icelandic, vietnamese and a few more, as well as in languages created with `\babelprovide` and its key import, is:

```
\renewcommand\spanishchaptername{Foo}
```

This redefinition is immediate.

NOTE Do *not* redefine a caption in the following way:

```
\AtBeginDocument{\renewcommand\contentsname{Foo}}
```

The changes may be discarded with a language selector, and the original value restored.

Macros to be run when a language is selected can be added to `\extras⟨lang⟩`:

```
\addto\extrasrussian{\mymacro}
```

There is a counterpart for code to be run when a language is unselected: `\noextras⟨lang⟩`.

NOTE These macros (`\captions⟨lang⟩`, `\extras⟨lang⟩`) may be redefined, but *must not* be used as such – they just pass information to babel, which executes them in the proper context.

Another way to modify a language loaded as a package or class option is by means of `\babelprovide`, described below in depth. So, something like:

```
\usepackage[danish]{babel}  
\babelprovide[captions=da, hyphenrules=nohyphenation]{danish}
```

first loads `danish.ldf`, and then redefines the captions for danish (as provided by the `ini` file) and prevents hyphenation. The rest of the language definitions are not touched. Without the optional argument it just loads some additional tools if provided by the `ini` file, like extra counters.

1.16 Creating a language

New 3.10 And what if there is no style for your language or none fits your needs? You may then define quickly a language with the help of the following macro in the preamble (which may be used to modify an existing language, too, as explained in the previous subsection).

`\babelprovide [⟨options⟩]{⟨language-name⟩}`

If the language `⟨language-name⟩` has not been loaded as class or package option and there are no `⟨options⟩`, it creates an “empty” one with some defaults in its internal structure: the hyphen rules, if not available, are set to the current ones, left and right hyphen mins are set to 2 and 3. In either case, caption, date and language system are not defined.

If no `ini` file is imported with `import`, `⟨language-name⟩` is still relevant because in such a case the hyphenation and like breaking rules (including those for South East Asian and CJK) are based on it as provided in the `ini` file corresponding to that name; the same applies to OpenType language and script.

Conveniently, some options allow to fill the language, and babel warns you about what to do if there is a missing string. Very likely you will find alerts like that in the log file:

```
Package babel Warning: \chaptername not set for 'mylang'. Please,  
(babel)                define it after the language has been loaded  
(babel)                (typically in the preamble) with:  
(babel)                \setlocalecaption{mylang}{chapter}{...}  
(babel)                Reported on input line 26.
```

In most cases, you will only need to define a few macros. Note languages loaded on the fly are not yet available in the preamble.

EXAMPLE If you need a language named `arhinish`:

```

\usepackage[danish]{babel}
\babelprovide{arhinish}
\setlocalecaption{arhinish}{chapter}{Chapitula}
\setlocalecaption{arhinish}{refname}{Refirenke}
\renewcommand\arhinishhyphenmins{22}

```

EXAMPLE Locales with names based on BCP 47 codes can be created with something like:

```
\babelprovide[import=en-US]{enUS}
```

Note, however, mixing ways to identify locales can lead to problems. For example, is yi the name of the language spoken by the Yi people or is it the code for Yiddish?

The main language is not changed (danish in this example). So, you must add `\selectlanguage{arhinish}` or other selectors where necessary. If the language has been loaded as an argument in `\documentclass` or `\usepackage`, then `\babelprovide` redefines the requested data.

import= *<language-tag>*

New 3.13 Imports data from an ini file, including captions and date (also line breaking rules in newly defined languages). For example:

```
\babelprovide[import=hu]{hungarian}
```

Unicode engines load the UTF-8 variants, while 8-bit engines load the LICR (ie, with macros like `\'` or `\ss`) ones.

New 3.23 It may be used without a value, and that is often the recommended option. In such a case, the ini file set in the corresponding `babel-<language>.tex` (where `<language>` is the last argument in `\babelprovide`) is imported. See the list of recognized languages above. So, the previous example is best written as:

```
\babelprovide[import]{hungarian}
```

There are about 250 ini files, with data taken from the ldf files and the CLDR provided by Unicode. Not all languages in the latter are complete, and therefore neither are the ini files. A few languages may show a warning about the current lack of suitability of some features.

Besides `\today`, this option defines an additional command for dates: `\<language>date`, which takes three arguments, namely, year, month and day numbers. In fact, `\today` calls `\<language>today`, which in turn calls

`\<language>date{\the\year}{\the\month}{\the\day}`. **New 3.44** More convenient is usually `\localedate`, which prints the date for the current locale.

captions= *<language-tag>*

Loads only the strings. For example:

```
\babelprovide[captions=hu]{hungarian}
```

hyphenrules= *<language-list>*

With this option, with a space-separated list of hyphenation rules, babel assigns to the language the first valid hyphenation rules in the list. For example:

```
\babelprovide[hyphenrules=chavacano spanish italian]{chavacano}
```

If none of the listed hyphenrules exist, the default behavior applies. Note in this example we set chavacano as first option – without it, it would select spanish even if chavacano exists.

A special value is +, which allocates a new language (in the T_EX sense). It only makes sense as the last value (or the only one; the subsequent ones are silently ignored). It is mostly useful with luatex, because you can add some patterns with \babelpatterns, as for example:

```
\babelprovide[hyphenrules=+]{neo}
\babelpatterns[neo]{a1 e1 i1 o1 u1}
```

In other engines it just suppresses hyphenation (because the pattern list is empty).

New 3.58 Another special value is unhyphenated, which is an alternative to justification=unhyphenated.

main This valueless option makes the language the main one (thus overriding that set when babel is loaded). Only in newly defined languages.

EXAMPLE Let's assume your document (xetex or luatex) is mainly in Polytonic Greek with but with some sections in Italian. Then, the first attempt should be:

```
\usepackage[italian, greek.polutoniko]{babel}
```

But if, say, accents in Greek are not shown correctly, you can try

```
\usepackage[italian, polytonicgreek, provide=*]{babel}
```

Remember there is an alternative syntax for the latter:

```
\usepackage[italian]{babel}
\babelprovide[import, main]{polytonicgreek}
```

Finally, also remember you might not need to load italian at all if there are only a few word in this language (see 1.3).

script= *<script-name>*

New 3.15 Sets the script name to be used by fontspec (eg, Devanagari). Overrides the value in the ini file. If fontspec does not define it, then babel sets its tag to that provided by the ini file. This value is particularly important because it sets the writing direction, so you must use it if for some reason the default value is wrong.

language= *<language-name>*

New 3.15 Sets the language name to be used by fontspec (eg, Hindi). Overrides the value in the ini file. If fontspec does not define it, then babel sets its tag to that provided by the ini file. Not so important, but sometimes still relevant.

alph= *<counter-name>*

Assigns to \alph that counter. See the next section.

Alph= $\langle counter-name \rangle$

Same for \Alph.

A few options (only luatex) set some properties of the writing system used by the language. These properties are *always* applied to the script, no matter which language is active. Although somewhat inconsistent, this makes setting a language up easier in most typical cases.

onchar= ids | fonts | letters

New 3.38 This option is much like an ‘event’ called when a character belonging to the script of this locale is found (as its name implies, it acts on characters, not on spaces). There are currently two ‘actions’, which can be used at the same time (separated by a space): with `ids` the `\language` and the `\localeid` are set to the values of this locale; with `fonts`, the fonts are changed to those of this locale (as set with `\babelfont`). Characters can be added or modified with `\babelcharproperty`.

New 3.81 Option `letters` restricts the ‘actions’ to letters, in the T_EX sense (i. e., with `catcode 11`). Digits and punctuation are then considered part of current locale (as set by a selector). This option is useful when the main script is non-Latin and there is a secondary one whose script is Latin.

NOTE An alternative approach with luatex and Harfbuzz is the font option `RawFeature={multiscript=auto}`. It does not switch the babel language and therefore the line breaking rules, but in many cases it can be enough.

NOTE There is no general rule to set the font for a punctuation mark, because it is a semantic decision and not a typographical one. Consider the following sentence: “یک, دو, and سه are Persian numbers”. In this case the punctuation font must be the English one, even if the commas are surrounded by non-Latin letters. Quotation marks, parenthesis, etc., are even more complex. Several criteria are possible, like the main language (the default in babel), the first letter in the paragraph, or the surrounding letters, among others, but even so manual switching can be still necessary.

intraspace= $\langle base \rangle \langle shrink \rangle \langle stretch \rangle$

Sets the interword space for the writing system of the language, in em units (so, `0.1 0` is `0em` plus `.1em`). Like `\spaceskip`, the em unit applied is that of the current text (more precisely, the previous glyph). Currently used only in Southeast Asian scripts, like Thai, and CJK.

intrapenalty= $\langle penalty \rangle$

Sets the interword penalty for the writing system of this language. Currently used only in Southeast Asian scripts, like Thai. Ignored if 0 (which is the default value).

transforms= $\langle transform-list \rangle$

See section 1.21.

justification= unhyphenated | kashida | elongated | padding

New 3.59 There are currently 4 options. Note they are language dependent, so that they will not be applied to other languages. The first one (unhyphenated) activates a line breaking mode that allows spaces to be stretched to arbitrary amounts. Although for European standards the result may look odd, in some writing systems, like Malayalam and other Indic scripts, this has been the customary (although not always the desired) practice. Because of that, no locale sets currently this mode by default (Amharic is an exception). Unlike `\sloppy`, the `\hfuzz` and the `\vfuzz` are not changed, because this line breaking mode is not really ‘sloppy’ (in other words, overfull boxes are reported as usual).

The second and the third are for the Arabic script. It sets the linebreaking and justification method, which can be based on the the ARABIC TATWEEL character or in the ‘justification alternatives’ OpenType table (jalt). For an explanation see the [babel site](#).

New 3.81 The option padding has been devised primarily for Tibetan. It’s still somewhat experimental. Again, there is an explanation in the [babel site](#).

linebreaking= **New 3.59** Just a synonymous for justification.

NOTE (1) If you need shorthands, you can define them with `\usesshorthands` and `\defineshorthand` as described above. (2) Captions and `\today` are “ensured” with `\babelensure` (this is the default in ini-based languages).

1.17 Digits and counters

New 3.20 About thirty ini files define a field named `digits.native`. When it is present, two macros are created: `\<language>digits` and `\<language>counter` (only xetex and luatex). With the first, a string of ‘Latin’ digits are converted to the native digits of that language; the second takes a counter name as argument. With the option `maparabic` in `\babelprovide`, `\arabic` is redefined to produce the native digits (this is done *globally*, to avoid inconsistencies in, for example, page numbering, and note as well dates do not rely on `\arabic`.)

For example:

```
\babelprovide[import]{telugu}
% Or also, if you want:
% \babelprovide[import, maparabic]{telugu}
\babelfont{rm}{Gautami} % With luatex, better with Harfbuzz
\begin{document}
\telugudigits{1234}
\telugucounter{section}
\end{document}
```

Languages providing native digits in all or some variants are:

Arabic	Persian	Lao	Odia	Urdu
Assamese	Gujarati	Northern Luri	Punjabi	Uzbek
Bangla	Hindi	Malayalam	Pashto	Vai
Tibetar	Khmer	Marathi	Tamil	Cantonese
Bodo	Kannada	Burmese	Telugu	Chinese
Central Kurdish	Konkani	Mazanderani	Thai	
Dzongkha	Kashmiri	Nepali	Uyghur	

New 3.30 With luatex there is an alternative approach for mapping digits, namely, `mapdigits`. Conversion is based on the language and it is applied to the typeset text (not math, PDF bookmarks, etc.) before bidi and fonts are processed (ie, to the node list as generated by the T_EX code). This means the local digits have the correct bidirectional behavior (unlike `Numbers=Arabic` in fontspec, which is not recommended).

NOTE With xetex you can use the option `Mapping` when defining a font.

\localnumeral `{\style}{\number}`
\localecounter `{\style}{\counter}`

New 3.41 Many ‘ini’ locale files has been extended with information about non-positional numerical systems, based on those predefined in CSS. They only work with xetex and luatex and are fully expendable (even inside an unprotected `\edef`). Currently, they are limited to numbers below 10000.

There are several ways to use them (for the avaiable styles in each language, see the list below):

- `\localenumeral{<style>}{<number>}`, like `\localenumeral{abjad}{15}`
- `\localecounter{<style>}{<counter>}`, like `\localecounter{lower}{section}`
- In `\babelprovide`, as an argument to the keys `alph` and `Alph`, which redefine what `\alph` and `\Alph` print. For example:

```
\babelprovide[alph=alphabetic]{thai}
```

The styles are:

Ancient Greek `lower.ancient, upper.ancient`
Amharic `afar, agaw, ari, blin, dizi, gedeo, gumuz, hadiyya, harari, kaffa, kebona, kembata, konso, kunama, meen, oromo, saho, sidama, silti, tigre, wolaita, yemsa`
Arabic `abjad, maghrebi.abjad`
Armenian `lower.letter, upper.letter`
Belarusian, Bulgarian, Church Slavic, Macedonian, Serbian `lower, upper`
Bangla `alphabetic`
Central Kurdish `alphabetic`
Chinese `cjk-earthly-branch, cjk-heavenly-stem, circled.ideograph, parenthesized.ideograph, fullwidth.lower.alpha, fullwidth.upper.alpha`
Church Slavic (Glagolitic) `letters`
Coptic `epact, lower.letters`
French `date.day` (mainly for internal use).
Georgian `letters`
Greek `lower.modern, upper.modern, lower.ancient, upper.ancient` (all with keraia)
Hebrew `letters` (neither geresh nor gershayim yet)
Hindi `alphabetic`
Italian `lower.legal, upper.legal`
Japanese `hiragana, hiragana.iroha, katakana, katakana.iroha, circled.katakana, informal, formal, cjk-earthly-branch, cjk-heavenly-stem, circled.ideograph, parenthesized.ideograph, fullwidth.lower.alpha, fullwidth.upper.alpha`
Khmer `consonant`
Korean `consonant, syllable, hanja.informal, hanja.formal, hangul.formal, cjk-earthly-branch, cjk-heavenly-stem, circled.ideograph, parenthesized.ideograph, fullwidth.lower.alpha, fullwidth.upper.alpha`
Marathi `alphabetic`
Persian `abjad, alphabetic`
Russian `lower, lower.full, upper, upper.full`
Syriac `letters`
Tamil `ancient`
Thai `alphabetic`
Ukrainian `lower, lower.full, upper, upper.full`

New 3.45 In addition, native digits (in languages defining them) may be printed with the numeral style digits.

1.18 Dates

New 3.45 When the data is taken from an ini file, you may print the date corresponding to the Gregorian calendar and other lunisolar systems with the following command.

`\localedate` [`<calendar=.., variant=.., convert>`]{`<year>`}{`<month>`}{`<day>`}

By default the calendar is the Gregorian, but an ini file may define strings for other calendars (currently `ar`, `ar-*`, `he`, `fa`, `hi`). In the latter case, the three arguments are the year, the month, and the day in those in the corresponding calendar. They are *not* the Gregorian data to be converted (which means, say, 13 is a valid month number with

calendar=hebrew and calendar=coptic). However, with the option convert it's converted (using internally the following command). Even with a certain calendar there may be variants. In Kurmanji the default variant prints something like *30. Çileyâ Pêşîn 2019*, but with variant=izafa it prints *31'ê Çileyâ Pêşînê 2019*.

\babelcalendar [*<date>*]{*<calendar>*}{*<year-macro>*}{*<month-macro>*}{*<day-macro>*}

New 3.76 Although calendars aren't the primary concern of babel, the package should be able to, at least, generate correctly the current date in the way users would expect in their own culture. Currently, \localedate can print dates in a few calendars (provided the ini locale file has been imported), but year, month and day had to be entered by hand, which is very inconvenient. With this macro, the current date is converted and stored in the three last arguments, which must be macros. Allowed calendars are

buddhist	ethiopic	islamic-civil	persian
coptic	hebrew	islamic-umalqura	

The optional argument converts the given date, in the form '*<year>*-'*<month>*-'*<day>*'. Please, refer to the page on the news for 3.76 in the babel site for further details.

1.19 Accessing language info

\language The control sequence \language contains the name of the current language.

WARNING Due to some internal inconsistencies in catcodes, it should *not* be used to test its value. Use iflang, by Heiko Oberdiek.

\iflanguage {*<language>*}{*<true>*}{*<false>*}

If more than one language is used, it might be necessary to know which language is active at a specific time. This can be checked by a call to \iflanguage, but note here "language" is used in the TeX sense, as a set of hyphenation patterns, and *not* as its babel name. This macro takes three arguments. The first argument is the name of a language; the second and third arguments are the actions to take if the result of the test is true or false respectively.

\localeinfo *{*<field>*}

New 3.38 If an ini file has been loaded for the current language, you may access the information stored in it. This macro is fully expandable, and the available fields are:

name.english as provided by the Unicode CLDR.
tag.ini is the tag of the ini file (the way this file is identified in its name).
tag.bcp47 is the full BCP 47 tag (see the warning below). This is the value to be used for the 'real' provided tag (babel may fill other fields if they are considered necessary).
language.tag.bcp47 is the BCP 47 language tag.
tag.opentype is the tag used by OpenType (usually, but not always, the same as BCP 47).
script.name, as provided by the Unicode CLDR.
script.tag.bcp47 is the BCP 47 tag of the script used by this locale. This is a required field for the fonts to be correctly set up, and therefore it should be always defined.
script.tag.opentype is the tag used by OpenType (usually, but not always, the same as BCP 47).
region.tag.bcp47 is the BCP 47 tag of the region or territory. Defined only if the locale loaded actually contains it (eg, es-MX does, but es doesn't), which is how locales behave in the CLDR. **New 3.75**
variant.tag.bcp47 is the BCP 47 tag of the variant (in the BCP 47 sense, like 1901 for German). **New 3.75**

extension.⟨s⟩.tag.bcp47 is the BCP 47 value of the extension whose singleton is ⟨s⟩ (currently the recognized singletons are x, t and u). The internal syntax can be somewhat complex, and this feature is still somewhat tentative. An example is classiclatin which sets extension.x.tag.bcp47 to classic. **New 3.75**

WARNING **New 3.46** As of version 3.46 tag.bcp47 returns the full BCP 47 tag. Formerly it returned just the language subtag, which was clearly counterintuitive.

New 3.75 Sometimes, it comes in handy to be able to use \localeinfo in an expandable way even if something went wrong (for example, the locale currently active is undefined). For these cases, localeinfo* just returns an empty string instead of raising an error. Bear in mind that babel, following the CLDR, may leave the region unset, which means \getlocaleproperty*, described below, is the preferred command, so that the existence of a field can be checked before. This also means building a string with the language and the region with \localeinfo*{language.tab.bcp47}-\localeinfo*{region.tab.bcp47} is not usually a good idea (because of the hyphen).

\getlocaleproperty *{⟨macro⟩}{⟨locale⟩}{⟨property⟩}

New 3.42 The value of any locale property as set by the ini files (or added/modified with \babelprovide) can be retrieved and stored in a macro with this command. For example, after:

```
\getlocaleproperty\hechap{hebrew}{captions/chapter}
```

the macro \hechap will contain the string פרק.

If the key does not exist, the macro is set to \relax and an error is raised. **New 3.47** With the starred version no error is raised, so that you can take your own actions with undefined properties.

\localeid Each language in the babel sense has its own unique numeric identifier, which can be retrieved with \localeid.

The \localeid is not the same as the \language identifier, which refers to a set of hyphenation patterns (which, in turn, is just a component of the line breaking algorithm described in the next section). The data about preloaded patterns are stored in an internal macro named \bbl@languages (see the code for further details), but note several locales may share a single \language, so they are separated concepts. In luatex, the \localeid is saved in each node (when it makes sense) as an attribute, too.

\LocaleForEach {⟨code⟩}

Babel remembers which ini files have been loaded. There is a loop named \LocaleForEach to traverse the list, where #1 is the name of the current item, so that \LocaleForEach{\message{ **#1** }} just shows the loaded ini's.

ensureinfo=off **New 3.75** Previously, ini files were loaded only with \babelprovide and also when languages are selected if there is a \babel font or they have not been explicitly declared. Now the ini files are loaded (and therefore the corresponding data) even if these two conditions are not met (in previous versions you had to enable it with \BabelEnsureInfo in the preamble). Because of the way this feature works, problems are very unlikely, but there is a switch as a package option to turn the new behavior off (ensureinfo=off).

1.20 Hyphenation and line breaking

Babel deals with three kinds of line breaking rules: Western, typically the LGC group, South East Asian, like Thai, and CJK, but support depends on the engine: pdftex only deals with the former; xetex also with the second one (although in a limited way), while luatex provides basic rules for the latter, too. With luatex there are also tools for non-standard hyphenation rules, explained in the next section.

`\babelhyphen` `*{\type}`
`\babelhyphen` `*{\text}`

New 3.9a It is customary to classify hyphens in two types: (1) *explicit* or *hard hyphens*, which in \TeX are entered as `-`, and (2) *optional* or *soft hyphens*, which are entered as `\-`. Strictly, a *soft hyphen* is not a hyphen, but just a breaking opportunity or, in \TeX terms, a “discretionary”; a *hard hyphen* is a hyphen with a breaking opportunity after it. A further type is a *non-breaking hyphen*, a hyphen without a breaking opportunity. In \TeX , `-` and `\-` forbid further breaking opportunities in the word. This is the desired behavior very often, but not always, and therefore many languages provide shorthands for these cases. Unfortunately, this has not been done consistently: for example, `-` in Dutch, Portuguese, Catalan or Danish is a hard hyphen, while in German, Spanish, Norwegian, Slovak or Russian is a soft hyphen. Furthermore, some of them even redefine `\-`, so that you cannot insert a soft hyphen without breaking opportunities in the rest of the word. Therefore, some macros are provided with a set of basic “hyphens” which can be used by themselves, to define a user shorthand, or even in language files.

- `\babelhyphen{soft}` and `\babelhyphen{hard}` are self explanatory.
- `\babelhyphen{repeat}` inserts a hard hyphen which is repeated at the beginning of the next line, as done in languages like Polish, Portuguese and Spanish.
- `\babelhyphen{nobreak}` inserts a hard hyphen without a break after it (even if a space follows).
- `\babelhyphen{empty}` inserts a break opportunity without a hyphen at all.
- `\babelhyphen{\text}` is a hard “hyphen” using `\text` instead. A typical case is `\babelhyphen{/}`.

With all of them, hyphenation in the rest of the word is enabled. If you don’t want to enable it, there is a starred counterpart: `\babelhyphen*{soft}` (which in most cases is equivalent to the original `\-`), `\babelhyphen*{hard}`, etc.

Note `hard` is also good for isolated prefixes (eg, *anti-*) and `nobreak` for isolated suffixes (eg, *-ism*), but in both cases `\babelhyphen*{nobreak}` is usually better.

There are also some differences with \LaTeX : (1) the character used is that set for the current font, while in \LaTeX it is hardwired to `-` (a typical value); (2) the hyphen to be used in fonts with a negative `\hyphenchar` is `-`, like in \LaTeX , but it can be changed to another value by redefining `\babelnullhyphen`; (3) a break after the hyphen is forbidden if preceded by a glue >0 pt (at the beginning of a word, provided it is not immediately preceded by, say, a parenthesis).

`\babelhyphenation` `[\langle language \rangle, \langle language \rangle, ...]{\langle exceptions \rangle}`

New 3.9a Sets hyphenation exceptions for the languages given or, without the optional argument, for *all* languages (eg, proper nouns or common loan words, and of course monolingual documents). Multiple declarations work much like `\hyphenation` (last wins), but language exceptions take precedence over global ones.

It can be used only in the preamble, and exceptions are set when the language is first selected, thus taking into account changes of `\lccodes`’s done in `\extras\lang` as well as the language-specific encoding (not set in the preamble by default). Multiple `\babelhyphenation`’s are allowed. For example:

```
\babelhyphenation{Wal-hal-la Dar-bhan-ga}
```

Listed words are saved expanded and therefore it relies on the LICR. Of course, it also works without the LICR if the input and the font encodings are the same, like in Unicode based engines.

NOTE Using `\babelhyphenation` with Southeast Asian scripts is mostly pointless. But with `\babelpatterns` (below) you may fine-tune line breaking (only `luatex`). Even if there are no patterns for the language, you can add at least some typical cases.

NOTE Use `\babelhyphenation` instead of `\hyphenation` to set hyphenation exceptions in the preamble before any language is explicitly set with a selector. In the preamble the hyphenation rules are not always fully set up and an error can be raised.

`\begin{hyphenrules} {<language>} ... \end{hyphenrules}`

The environment `hyphenrules` can be used to select *only* the hyphenation rules to be used (it can be used as command, too). This can for instance be used to select ‘nohyphenation’, provided that in `language.dat` the ‘language’ nohyphenation is defined by loading `zerohyph.tex`. It deactivates language shorthands, too (but not user shorthands). Except for these simple uses, `hyphenrules` is deprecated and other `language*` (the starred version) is preferred, because the former does not take into account possible changes in encodings of characters like, say, ‘ ’ done by some languages (eg, italian, french, ukraineb).

`\babelpatterns [<language> , <language> , ...] { <patterns> }`

New 3.9m *In luatex only*,¹⁴ adds or replaces patterns for the languages given or, without the optional argument, for *all* languages. If a pattern for a certain combination already exists, it gets replaced by the new one.

It can be used only in the preamble, and patterns are added when the language is first selected, thus taking into account changes of `\lccodes`’s done in `\extras<lang>` as well as the language-specific encoding (not set in the preamble by default). Multiple `\babelpatterns`’s are allowed.

Listed patterns are saved expanded and therefore it relies on the LICR. Of course, it also works without the LICR if the input and the font encodings are the same, like in Unicode based engines.

New 3.31 (Only luatex.) With `\babelprovide` and imported CJK languages, a simple generic line breaking algorithm (push-out-first) is applied, based on a selection of the Unicode rules (**New 3.32** it is disabled in verbatim mode, or more precisely when the `hyphenrules` are set to `nohyphenation`). It can be activated alternatively by setting explicitly the `intraspace`.

New 3.27 Interword spacing for Thai, Lao and Khemer is activated automatically if a language with one of those scripts are loaded with `\babelprovide`. See the sample on the babel repository. With both Unicode engines, spacing is based on the “current” em unit (the size of the previous char in luatex, and the font size set by the last `\selectfont` in xetex).

1.21 Transforms

Transforms (only luatex) provide a way to process the text on the typesetting level in several language-dependent ways, like non-standard hyphenation, special line breaking rules, script to script conversion, spacing conventions and so on.¹⁵

It currently embraces `\babelprehyphenation` and `\babelposthyphenation`.

New 3.57 Several ini files predefine some transforms. They are activated with the key transforms in `\babelprovide`, either if the locale is being defined with this macro or the languages has been previously loaded as a class or package option, as the following example illustrates:

```
\usepackage[magyar]{babel}
\babelprovide[transforms = digraphs.hyphen]{magyar}
```

New 3.67 Transforms predefined in the ini locale files can be made attribute-dependent, too. When an attribute between parenthesis is inserted subsequent transforms will be assigned to it (up to the list end or another attribute). For example, and provided an attribute called `\withsigmafinal` has been declared:

¹⁴With luatex exceptions and patterns can be modified almost freely. However, this is very likely a task for a separate package and babel only provides the most basic tools.

¹⁵They are similar in concept, but not the same, as those in Unicode. The main inspiration for this feature is the Omega transformation processes.

```
transforms = transliteration.omega (\withsigmafinal) sigma.final
```

This applies `transliteration.omega` always, but `sigma.final` only when `\withsigmafinal` is set.

Here are the transforms currently predefined. (A few may still require some fine-tuning. More to follow in future releases.)

Arabic	<code>transliteration.dad</code>	Applies the transliteration system devised by Yannis Haralambous for dad (simple and T _E X-friendly). Not yet complete, but sufficient for most texts.
Croatian	<code>digraphs.ligatures</code>	Ligatures <i>DŽ, Dž, dž, LJ, Lj, lj, NJ, Nj, nj</i> . It assumes they exist. This is not the recommended way to make these transformations (the best way is with OTF features), but it can get you out of a hurry.
Czech, Polish, Portuguese, Slovak, Spanish	<code>hyphen.repeat</code>	Explicit hyphens behave like <code>\babelhyphen{repeat}</code> .
Czech, Polish, Slovak	<code>oneletter.nobreak</code>	Converts a space after a non-syllabic preposition or conjunction into a non-breaking space.
Finnish	<code>prehyphen.nobreak</code>	Line breaks just after hyphens prepended to words are prevented, like in “pakastekaapit ja -arkut”.
Greek	<code>diaeresis.hyphen</code>	Removes the diaeresis above iota and upsilon if hyphenated just before. It works with the three variants.
Greek	<code>transliteration.omega</code>	Although the provided combinations are not the full set, this transform follows the syntax of Omega: = for the circumflex, v for digamma, and so on. For better compatibility with Levy’s system, ~ (as ‘string’) is an alternative to =. ' is tonos in Monotonic Greek, but oxia in Polytonic and Ancient Greek.
Greek	<code>sigma.final</code>	The transliteration system above does not convert the sigma at the end of a word (on purpose). This transforms does it. To prevent the conversion (an abbreviation, for example), write "s.
Hindi, Sanskrit	<code>transliteration.hk</code>	The Harvard-Kyoto system to romanize Devanagari.
Hindi, Sanskrit	<code>punctuation.space</code>	Inserts a space before the following four characters: !?;.
Hungarian	<code>digraphs.hyphen</code>	Hyphenates the long digraphs <i>ccs, ddz, ggy, lly, nny, ssz, tty</i> and <i>zzs</i> as <i>cs-cs, dz-dz</i> , etc.
Indic scripts	<code>danda.nobreak</code>	Prevents a line break before a danda or double danda if there is a space. For Assamese, Bengali, Gujarati, Hindi, Kannada, Malayalam, Marathi, Odia, Tamil, Telugu.
Latin	<code>digraphs.ligatures</code>	Replaces the groups <i>ae, AE, oe, OE</i> with <i>æ, Æ, œ, Œ</i> .

Latin	letters.noj	Replaces <i>j, J</i> with <i>i, I</i> .
Latin	letters.uv	Replaces <i>v, U</i> with <i>u, V</i> .
Sanskrit	transliteration.iast	The IAST system to romanize Devanagari. ¹⁶
Serbian	transliteration.gajica	(Note serbian with ini files refers to the Cyrillic script, which is here the target.) The standard system devised by Ljudevit Gaj.
Arabic, Persian	kashida.plain	Experimental. A very simple and basic transform for ‘plain’ Arabic fonts, which attempts to distribute the tatwil as evenly as possible (starting at the end of the line). See the news for version 3.59.

\babelposthyphenation [*options*]{*hyphenrules-name*}{*lua-pattern*}{*replacement*}

New 3.37-3.39 With *luatex* it is possible to define non-standard hyphenation rules, like $f-f \rightarrow ff-f$, repeated hyphens, ranked ruled (or more precisely, ‘penalized’ hyphenation points), and so on. A few rules are currently provided (see above), but they can be defined as shown in the following example, where {1} is the first captured char (between () in the pattern):

```
\babelposthyphenation{german}{([fmtrp]) | {1}}
{
  { no = {1}, pre = {1}{1}- }, % Replace first char with disc
  remove,                    % Remove automatic disc (2nd node)
  {}                          % Keep last char, untouched
}
```

In the replacements, a captured char may be mapped to another, too. For example, if the first capture reads ([*ıû*]), the replacement could be {1|*ıû*|*ıû*}, which maps *ı* to *ı*, and *û* to *ı*, so that the diaeresis is removed.

This feature is activated with the first `\babelposthyphenation` or `\babelprehyphenation`.

New 3.85 Another option is `label`, which takes a value similar to those in `\babelprovide` key transforms (in fact, the latter just applies this option). This label can be used to turn on and off transforms with a higher level interface, by means of `\enablelocaletransform` and `\disablelocaletransform` (see below).

New 3.85 When used in conjunction with `label`, this key makes a transform font dependent. As an example, the rules for Arabic kashida can differ depending on the font design. The value consists in a list of space-separated font tags:

```
\babelprehyphenation[label=transform.name, fonts=rm sf]{...}{...}
```

Tags can adopt two forms: a family, such as `rm` or `tt`, or the set family/series/shape. If a font matches one of these conditions, the transform is enabled. The second tag in `rm rm/n/it` is redundant. There are no wildcards; so, for italics you may want to write something like `sf/m/it sf/b/it`.

Transforms set for specific fonts (at least once in any language) are always reset with a font selector.

In `\babelprovide`, transform labels can be tagged before its name, with a list separated with colons, like:

```
transforms = rm:sf:transform.name
```

New 3.67 With the optional argument you can associate a user defined transform to an attribute, so that it's active only when it's set (currently its attribute value is ignored). With this mechanism transforms can be set or unset even in the middle of paragraphs, and applied to single words. To define, set and unset the attribute, the LaTeX kernel provides

the macros `\newattribute`, `\setattribute` and `\unsetattribute`. The following example shows how to use it, provided an attribute named `\latinnoj` has been declared:

```
\babelprehyphenation[attribute=\latinnoj]{latin}{ J }{ string = I }
```

See the [babel site](#) for a more detailed description and some examples. It also describes a few additional replacement types (`string`, `penalty`).

Although the main purpose of this command is non-standard hyphenation, it may actually be used for other transformations (after hyphenation is applied, so you must take discretionaries into account).

You are limited to substitutions as done by `lua`, although a future implementation may alternatively accept `lpeg`.

`\babelprehyphenation` [*options*] {*locale-name*} {*lua-pattern*} {*replacement*}

New 3.44-3-52 It is similar to the latter, but (as its name implies) applied before hyphenation, which is particularly useful in transliterations. There are other differences: (1) the first argument is the locale instead of the name of the hyphenation patterns; (2) in the search patterns `=` has no special meaning, while `|` stands for an ordinary space; (3) in the replacement, discretionaries are not accepted.

See the description above for the optional argument.

This feature is activated with the first `\babelposthyphenation` or `\babelprehyphenation`.

EXAMPLE You can replace a character (or series of them) by another character (or series of them). Thus, to enter *ž* as *zh* and *š* as *sh* in a newly created locale for transliterated Russian:

```
\babelprovide[hyphenrules=+]{russian-latin} % Create locale
\babelprehyphenation{russian-latin}{([sz])h} % Create rule
{
  string = {1|sz|šž},
  remove
}
```

EXAMPLE The following rule prevent the word “a” from being at the end of a line:

```
\babelprehyphenation{english}{|a|}
{ }, { }, % Keep first space and a
{ insert, penalty = 10000 }, % Insert penalty
{ } % Keep last space
}
```

NOTE With `luatex` there is another approach to make text transformations, with the function `fonts.handlers.otf.addfeature`, which adds new features to an OTF font (substitution and positioning). These features can be made language-dependent, and `babel` by default recognizes this setting if the font has been declared with `\babelfont`. The *transforms* mechanism supplements rather than replaces OTF features.

With `xetex`, where *transforms* are not available, there is still another approach, with font mappings, mainly meant to perform encoding conversions and transliterations. Mappings, however, are linked to fonts, not to languages.

`\enablelocaletransform` {*label*}

`\disablelocaletransform` {*label*}

New 3.85 Enables and disables the transform with the given label in the current language.

1.22 Selection based on BCP 47 tags

New 3.43 The recommended way to select languages is that described at the beginning of this document. However, BCP 47 tags are becoming customary, particularly in documents (or parts of documents) generated by external sources, and therefore babel will provide a set of tools to select the locales in different situations, adapted to the particular needs of each case. Currently, babel provides autoloading of locales as described in this section. In these contexts autoloading is particularly important because we may not know on beforehand which languages will be requested.

It must be activated explicitly, because it is primarily meant for special tasks. Mapping from BCP 47 codes to locale names are not hardcoded in babel. Instead the data is taken from the ini files, which means currently about 250 tags are already recognized. Babel performs a simple lookup in the following way: `fr-Latn-FR` → `fr-Latn` → `fr-FR` → `fr`. Languages with the same resolved name are considered the same. Case is normalized before, so that `fr-latn-fr` → `fr-Latn-FR`. If a tag and a name overlap, the tag takes precedence.

Here is a minimal example:

```
\documentclass{article}

\usepackage[danish]{babel}

\babeladjust{
  autoload.bcp47 = on,
  autoload.bcp47.options = import
}

\begin{document}

Chapter in Danish: \chaptername.

\selectlanguage{de-AT}

\localedate{2020}{1}{30}

\end{document}
```

Currently the locales loaded are based on the ini files and decoupled from the main ldf files. This is by design, to ensure code generated externally produces the same result regardless of the languages requested in the document, but an option to use the ldf instead will be added in a future release, because both options make sense depending on the particular needs of each document (there will be some restrictions, however).

The behaviour is adjusted with `\babeladjust` with the following parameters:

`autoload.bcp47` with values on and off.

`autoload.bcp47.options`, which are passed to `\babelprovide`; empty by default, but you may add `import` (features defined in the corresponding `babel-...tex` file might not be available).

`autoload.bcp47.prefix`. Although the public name used in selectors is the tag, the internal name will be different and generated by prepending a prefix, which by default is `bcp47-`. You may change it with this key.

New 3.46 If an ldf file has been loaded, you can enable the corresponding language tags as selector names with:

```
\babeladjust{ bcp47.toname = on }
```

(You can deactivate it with `off`.) So, if `dutch` is one of the package (or class) options, you can write `\selectlanguage{nl}`. Note the language name does not change (in this

example is still dutch), but you can get it with `\localeinfo` or `\getlocaleproperty`. It must be turned on explicitly for similar reasons to those explained above.

1.23 Selecting scripts

Currently babel provides no standard interface to select scripts, because they are best selected with either `\fontencoding` (low-level) or a language name (high-level). Even the Latin script may require different encodings (ie, sets of glyphs) depending on the language, and therefore such a switch would be in a sense incomplete.¹⁷

Some languages sharing the same script define macros to switch it (eg, `\textcyrillic`), but be aware they may also set the language to a certain default. Even the babel core defined `\textlatin`, but it was somewhat buggy because in some cases it messed up encodings and fonts (for example, if the main Latin encoding was LY1), and therefore it has been deprecated.¹⁸

`\ensureascii` $\langle\text{text}\rangle$

New 3.9i This macro makes sure $\langle\text{text}\rangle$ is typeset with a LICR-savvy encoding in the ASCII range. It is used to redefine `\TeX` and `\LaTeX` so that they are correctly typeset even with LGR or X2 (the complete list is stored in `\BabelNonASCII`, which by default is LGR, X2, OT2, OT3, OT6, LHE, LWN, LMA, LMC, LMS, LMU, but you can modify it). So, in some sense it fixes the bug described in the previous paragraph.

If non-ASCII encodings are not loaded (or no encoding at all), it is no-op (also `\TeX` and `\LaTeX` are not redefined); otherwise, `\ensureascii` switches to the encoding at the beginning of the document if ASCII-savvy, or else the last ASCII-savvy encoding loaded. For example, if you load LY1, LGR, then it is set to LY1, but if you load LY1, T2A it is set to T2A. The symbol encodings TS1, T3, and TS3 are not taken into account, since they are not used for “ordinary” text (they are stored in `\BabelNonText`, used in some special cases when no Latin encoding is explicitly set).

The foregoing rules (which are applied “at begin document”) cover most of the cases. No assumption is made on characters above 127, which may not follow the LICR conventions – the goal is just to ensure most of the ASCII letters and symbols are the right ones.

1.24 Selecting directions

No macros to select the writing direction are provided, either – writing direction is intrinsic to each script and therefore it is best set by the language (which can be a dummy one). Furthermore, there are in fact two right-to-left modes, depending on the language, which differ in the way ‘weak’ numeric characters are ordered (eg, Arabic %123 vs Hebrew 123%).

WARNING The current code for `text` in luatex should be considered essentially stable, but, of course, it is not bug-free and there can be improvements in the future, because setting bidi text has many subtleties (see for example <https://www.w3.org/TR/html-bidi/>). A basic stable version for other engines must wait. This applies to text; there is a basic support for **graphical** elements, including the picture environment (with `pict2e`) and `pfg/tikz`. Also, indexes and the like are under study, as well as math (there are progresses in the latter, including `amsmath` and `mathtools` too, but for example gathered may fail).

An effort is being made to avoid incompatibilities in the future (this one of the reason currently bidi must be explicitly requested as a package option, with a certain bidi model, and also the layout options described below).

WARNING If characters to be mirrored are shown without changes with luatex, try with the following line:

¹⁷The so-called Unicode fonts do not improve the situation either. So, a font suited for Vietnamese is not necessarily suited for, say, the romanization of Indic languages, and the fact it contains glyphs for Modern Greek does not mean it includes them for Classic Greek.

¹⁸But still defined for backwards compatibility.

```
\babeladjust{bidi.mirroring=off}
```

There are some package options controlling bidi writing.

bidi= default | basic | basic-r | bidi-l | bidi-r

New 3.14 Selects the bidi algorithm to be used. With default the bidi mechanism is just activated (by default it is not), but every change must be marked up. In xetex and pdftex this is the only option.

In luatex, **basic-r** provides a simple and fast method for R text, which handles numbers and unmarked L text within an R context many in typical cases. **New 3.19** Finally, **basic** supports both L and R text, and it is the preferred method (support for **basic-r** is currently limited). (They are named **basic** mainly because they only consider the intrinsic direction of scripts and weak directionality.)

New 3.29 In xetex, **bidi-r** and **bidi-l** resort to the package **bidi** (by Vafa Khalighi). Integration is still somewhat tentative, but it mostly works. For RL documents use the former, and for LR ones use the latter.

There are samples on GitHub, under `/required/babel/samples`. See particularly `lua-bidibasic.tex` and `lua-secenum.tex`.

EXAMPLE The following text comes from the Arabic Wikipedia (article about Arabia). Copy-pasting some text from the Wikipedia is a good way to test this feature. Remember **basic** is available in luatex only.

```
\documentclass{article}

\usepackage[bidi=basic]{babel}

\babelprovide[import, main]{arabic}

\babelfont{rm}{FreeSerif}

\begin{document}

    وقد عرفت شبه جزيرة العرب طيلة العصر الهيليني (الآغريقي) بـ
    Arabia أو Aravia (بالآغريقية Ἀραβία)، استخدم الرومان ثلاث
    بادئات بـ “Arabia” على ثلاث مناطق من شبه الجزيرة العربية، إلا أنها
    حقيقةً كانت أكبر مما تعرف عليه اليوم.

\end{document}
```

EXAMPLE With **bidi=basic** both L and R text can be mixed without explicit markup (the latter will be only necessary in some special cases where the Unicode algorithm fails). It is used much like **bidi=basic-r**, but with R text inside L text you may want to map the font so that the correct features are in force. This is accomplished with an option in `\babelprovide`, as illustrated:

```
\documentclass{book}

\usepackage[english, bidi=basic]{babel}

\babelprovide[onchar=ids fonts]{arabic}

\babelfont{rm}{Crimson}
\babelfont[*arabic]{rm}{FreeSerif}

\begin{document}

    Most Arabic speakers consider the two varieties to be two registers
```

```
of one language, although the two registers can be referred to in
Arabic as فصحي العصر \textit{fuṣḥā l-‘aṣr} (MSA) and
فصحي التراث \textit{fuṣḥā t-turāth} (CA).
```

```
\end{document}
```

In this example, and thanks to `onchar=ids` fonts, any Arabic letter (because the language is arabic) changes its font to that set for this language (here defined via `*arabic`, because Crimson does not provide Arabic letters).

NOTE Boxes are “black boxes”. Numbers inside an `\hbox` (for example in a `\ref`) do not know anything about the surrounding chars. So, `\ref{A}-\ref{B}` are not rendered in the visual order A-B, but in the wrong one B-A (because the hyphen does not “see” the digits inside the `\hbox`’es). If you need `\ref` ranges, the best option is to define a dedicated macro like this (to avoid explicit direction changes in the body; here `\texthe` must be defined to select the main language):

```
\newcommand\refrange[2]{\babelsublr{\texthe{\ref{#1}}-\texthe{\ref{#2}}}}
```

In the future a more complete method, reading recursively boxed text, may be added.

layout= sectioning | counters | lists | contents | footnotes | captions | columns | graphics | extras

New 3.16 *To be expanded.* Selects which layout elements are adapted in bidi documents, including some text elements (except with options loading the `bidi` package, which provides its own mechanism to control these elements). You may use several options with a space-separated list, like `layout=counters contents sectioning` (in **New 3.85** spaces are to be preferred over dots, which was the former syntax). This list will be expanded in future releases. Note not all options are required by all engines.

sectioning makes sure the sectioning macros are typeset in the main language, but with the title text in the current language (see below `\BabelPatchSection` for further details).

counters required in all engines (except `luatex` with `bidi=basic`) to reorder section numbers and the like (eg, `<subsection>.<section>`); required in `xetex` and `pdftex` for counters in general, as well as in `luatex` with `bidi=default`; required in `luatex` for numeric footnote marks `>9` with `bidi=basic-r` (but *not* with `bidi=basic`); note, however, it can depend on the counter format.

With counters, `\arabic` is not only considered L text always (with `\babelsublr`, see below), but also an “isolated” block which does not interact with the surrounding chars. So, while `1.2` in R text is rendered in that order with `bidi=basic` (as a decimal number), in `\arabic{c1}.\arabic{c2}` the visual order is `c2.c1`. Of course, you may always adjust the order by changing the language, if necessary.

New 3.84 Since `\thepage` is (indirectly) redefined, `makeindex` will reject many entries as invalid. With `counters*` `babel` attempts to remove the conflicting macros.

lists required in `xetex` and `pdftex`, but only in bidirectional (with both R and L paragraphs) documents in `luatex`.

WARNING As of April 2019 there is a bug with `\parshape` in `luatex` (a `TEX` primitive) which makes lists to be horizontally misplaced if they are inside a `\vbox` (like `minipage`) and the current direction is different from the main one. A workaround is to restore the main language before the box and then set the local one inside.

contents required in `xetex` and `pdftex`; in `luatex` toc entries are R by default if the main language is R.

columns required in `xetex` and `pdftex` to reverse the column order (currently only the standard two-column mode); in `luatex` they are R by default if the main language is R (including `multicol`).

footnotes not required in monolingual documents, but it may be useful in bidirectional documents (with both R and L paragraphs) in all engines; you may use alternatively `\BabelFootnote` described below (what this option does exactly is also explained there).

captions is similar to sectioning, but for `\caption`; not required in monolingual documents with `luatex`, but may be required in `xetex` and `pdfTeX` in some styles (support for the latter two engines is still experimental) **New 3.18** .

tabular required in `luatex` for R tabular, so that the first column is the right one (it has been tested only with simple tables, so expect some readjustments in the future); ignored in `pdfTeX` or `xetex` (which will not support a similar option in the short term). It patches an internal command, so it might be ignored by some packages and classes (or even raise an error). **New 3.18** .

graphics modifies the `picture` environment so that the whole figure is L but the text is R. It *does not* work with the standard `picture`, and `pict2e` is required. It attempts to do the same for `pgf/tikz`. Somewhat experimental. **New 3.32** .

extras is used for miscellaneous readjustments which do not fit into the previous groups. Currently redefines in `luatex` `\underline` and `\LaTeX2e` **New 3.19** .

EXAMPLE Typically, in an Arabic document you would need:

```
\usepackage[bidi=basic,
             layout=counters tabular]{babel}
```

\babelsublr `{\langle lr-text \rangle}`

Digits in `pdfTeX` must be marked up explicitly (unlike `luatex` with `bidi=basic` or `bidi=basic-r` and, usually, `xetex`). This command is provided to set `{\langle lr-text \rangle}` in L mode if necessary. It's intended for what Unicode calls weak characters, because words are best set with the corresponding language. For this reason, there is no `r1` counterpart. Any `\babelsublr` in *explicit* L mode is ignored. However, with `bidi=basic` and *implicit* L, it first returns to R and then switches to explicit L. To clarify this point, consider, in an R context:

```
RTL A ltr text \thechapter{} and still ltr RTL B
```

There are *three* R blocks and *two* L blocks, and the order is *RTL B and still ltr 1 ltr text RTL A*. This is by design to provide the proper behavior in the most usual cases — but if you need to use `\ref` in an L text inside R, the L text must be marked up explicitly; for example:

```
RTL A \foreignlanguage{english}{ltr text \thechapter{} and still ltr} RTL B
```

\localerestoredirs

New 3.86 *LuaTeX*. This command resets the internal text, paragraph and body directions to those of the current locale (if different). Sometimes changing directly these values can be useful for some hacks, and this command helps in restoring the directions to the correct ones. It can be used in `>` arguments of `array`, too.

\BabelPatchSection `{\langle section-name \rangle}`

Mainly for bidi text, but it can be useful in other cases. `\BabelPatchSection` and the corresponding option `layout=sectioning` takes a more logical approach (at least in many cases) because it applies the global language to the section format (including the `\chaptername` in `\chapter`), while the section text is still the current language. The latter is passed to `tocs` and `marks`, too, and with `sectioning` in `layout` they both reset the “global” language to the main one, while the text uses the “local” language.

With `layout=sectioning` all the standard sectioning commands are redefined (it also “isolates” the page number in heads, for a proper bidi behavior), but with this command you can set them individually if necessary (but note then tocs and marks are not touched).

`\BabelFootnote` $\langle cmd \rangle \langle local-language \rangle \langle before \rangle \langle after \rangle$

New 3.17 Something like:

```
\BabelFootnote{\parsfootnote}{\language}\language{(){} }
```

defines `\parsfootnote` so that `\parsfootnote{note}` is equivalent to:

```
\footnote{(\foreignlanguage{\language}\language){note}}}
```

but the footnote itself is typeset in the main language (to unify its direction). In addition, `\parsfootnotetext` is defined. The option `footnotes` just does the following:

```
\BabelFootnote{\footnote}{\language}\language{}{}%
\BabelFootnote{\localfootnote}{\language}\language{}{}%
\BabelFootnote{\mainfootnote}{\language}\language{}{}%
```

(which also redefine `\footnotetext` and define `\localfootnotetext` and `\mainfootnotetext`). If the language argument is empty, then no language is selected inside the argument of the footnote. Note this command is available always in bidi documents, even without `layout=footnotes`.

EXAMPLE If you want to preserve directionality in footnotes and there are many footnotes entirely in English, you can define:

```
\BabelFootnote{\enfootnote}{english}{.}{.}
```

It adds a period outside the English part, so that it is placed at the left in the last line. This means the dot the end of the footnote text should be omitted.

1.25 Language attributes

`\languageattribute`

This is a user-level command, to be used in the preamble of a document (after `\usepackage[...]{babel}`), that declares which attributes are to be used for a given language. It takes two arguments: the first is the name of the language; the second, a (list of) attribute(s) to be used. Attributes must be set in the preamble and only once – they cannot be turned on and off. The command checks whether the language is known in this document and whether the attribute(s) are known for this language.

Very often, using a *modifier* in a package option is better.

Several language definition files use their own methods to set options. For example, `french` uses `\frenchsetup`, `magyar` (1.5) uses `\magyarOptions`; modifiers provided by `spanish` have no attribute counterparts. Macros setting options are also used (eg, `\ProsodicMarksOn` in `latin`).

1.26 Hooks

New 3.9a A hook is a piece of code to be executed at certain events. Some hooks are predefined when `luatex` and `xetex` are used.

New 3.64 This is not the only way to inject code at those points. The events listed below can be used as a hook name in `\AddToHook` in the form `babel/⟨language-name⟩/⟨event-name⟩` (with `*` it's applied to all languages), but there is a limitation, because the parameters passed with the `babel` mechanism are not allowed. The `\AddToHook` mechanism does *not* replace the current one in ‘`babel`’. Its main advantage is you can reconfigure ‘`babel`’ even before loading it. See the example below.

\AddBabelHook [*<lang>*]{*<name>*}{*<event>*}{*<code>*}

The same name can be applied to several events. Hooks with a certain *<name>* may be enabled and disabled for all defined events with `\EnableBabelHook{<name>}`, `\DisableBabelHook{<name>}`. Names containing the string `babel` are reserved (they are used, for example, by `\usesshortands*` to add a hook for the event `afterextras`).

New 3.33 They may be also applied to a specific language with the optional argument; language-specific settings are executed after global ones.

Current events are the following; in some of them you can use one to three \TeX parameters (`#1`, `#2`, `#3`), with the meaning given:

addialect (language name, dialect name) Used by `luababel.def` to load the patterns if not preloaded.

patterns (language name, language with encoding) Executed just after the `\language` has been set. The second argument has the patterns name actually selected (in the form of either `lang:ENC` or `lang`).

hyphenation (language name, language with encoding) Executed locally just before exceptions given in `\babelhyphenation` are actually set.

defaultcommands Used (locally) in `\StartBabelCommands`.

encodedcommands (input, font encodings) Used (locally) in `\StartBabelCommands`. Both `xetex` and `luatex` make sure the encoded text is read correctly.

stopcommands Used to reset the above, if necessary.

write This event comes just after the switching commands are written to the aux file.

beforeextras Just before executing `\extras<language>`. This event and the next one should not contain language-dependent code (for that, add it to `\extras<language>`).

afterextras Just after executing `\extras<language>`. For example, the following deactivates shorthands in all languages:

```
\AddBabelHook{noshort}{afterextras}{\languageshorthands{none}}
```

stringprocess Instead of a parameter, you can manipulate the macro `\BabelString` containing the string to be defined with `\SetString`. For example, to use an expanded version of the string in the definition, write:

```
\AddBabelHook{myhook}{stringprocess}{%  
  \protected@edef\BabelString{\BabelString}}
```

initiateactive (char as active, char as other, original char) **New 3.9i** Executed just after a shorthand has been ‘initiated’. The three parameters are the same character with different catcodes: active, other (`\string’ed`) and the original one.

afterreset **New 3.9i** Executed when selecting a language just after `\originalTeX` is run and reset to its base value, before executing `\captions<language>` and `\date<language>`.

begindocument **New 3.88** Executed before the code written by `ldf` files with `\AtBeginDocument`. The optional argument with the language in this particular case is the language that wrote the code. The special value `/` means ‘return to the core `babel` definitions’ (in other words, what follows hasn’t been written by any language).

Four events are used in `hyphen.cfg`, which are handled in a quite different way for efficiency reasons – unlike the precedent ones, they only have a single hook and replace a default definition.

everylanguage (language) Executed before every language patterns are loaded.

loadkernel (file) By default just defines a few basic commands. It can be used to define different versions of them or to load a file.

loadpatterns (patterns file) Loads the patterns file. Used by `luababel.def`.

loadexceptions (exceptions file) Loads the exceptions file. Used by `luababel.def`.

EXAMPLE The generic unlocalized \TeX hooks are predefined, so that you can write:


```
\AddToHook{babel/*/afterextras}{\frenchspacing}
```

which is executed always after the extras for the language being selected (and just before the non-localized hooks defined with `\AddBabelHook`).

In addition, locale-specific hooks in the form `babel/⟨language-name⟩/⟨event-name⟩` are *recognized* (executed just before the localized babel hooks), but they are *not predefined*. You have to do it yourself. For example, to set `\frenchspacing` only in bengali:

```
\ActivateGenericHook{babel/bengali/afterextras}
\AddToHook{babel/bengali/afterextras}{\frenchspacing}
```

\BabelContentsFiles New 3.9a This macro contains a list of “toc” types requiring a command to switch the language. Its default value is `toc,lof,lot`, but you may redefine it with `\renewcommand` (it’s up to you to make sure no toc type is duplicated).

1.27 Languages supported by babel with ldf files

In the following table most of the languages supported by babel with and .ldf file are listed, together with the names of the option which you can load babel with for each language. Note this list is open and the current options may be different. It does not include ini files.

Afrikaans afrikaans
Azerbaijani azerbaijani
Basque basque
Breton breton
Bulgarian bulgarian
Catalan catalan
Croatian croatian
Czech czech
Danish danish
Dutch dutch
English english, USenglish, american, UKenglish, british, canadian, australian, newzealand
Esperanto esperanto
Estonian estonian
Finnish finnish
French french, francais, canadien, acadian
Galician galician
German austrian, german, germanb, ngerman, naustrian
Greek greek, polutonikogreek
Hebrew hebrew
Icelandic icelandic
Indonesian indonesian (bahasa, indon, bahasai)
Interlingua interlingua
Irish Gaelic irish
Italian italian
Latin latin
Lower Sorbian lowersorbian
Malay malay, melayu (bahasam)
North Sami samin
Norwegian norsk, nynorsk
Polish polish
Portuguese portuguese, brazilian (portuges, brazil)¹⁹
Romanian romanian

¹⁹The two last name comes from the times when they had to be shortened to 8 characters

Russian russian
Scottish Gaelic scottish
Spanish spanish
Slovakian slovak
Slovenian slovene
Swedish swedish
Serbian serbian
Turkish turkish
Ukrainian ukrainian
Upper Sorbian upporsorbian
Welsh welsh

There are more languages not listed above, including hindi, thai, thaicjk, latvian, turkmen, magyar, mongolian, romansh, lithuanian, spanglish, vietnamese, japanese, pinyin, arabic, farsi, ibygreek, bgreek, serbianc, frenchle, ethiop and friulan. Most of them work out of the box, but some may require extra fonts, encoding files, a preprocessor or even a complete framework (like CJK or luatexja). For example, if you have got the velthuis/devnag package, you can create a file with extension .dn:

```

\documentclass{article}
\usepackage[hindi]{babel}
\begin{document}
{\dn devaanaa.m priya.h}
\end{document}

```

Then you preprocess it with devnag $\langle file \rangle$, which creates $\langle file \rangle$.tex; you can then typeset the latter with \LaTeX .

1.28 Unicode character properties in luatex

New 3.32 Part of the babel job is to apply Unicode rules to some script-specific features based on some properties. Currently, they are 3, namely, direction (ie, bidi class), mirroring glyphs, and line breaking for CJK scripts. These properties are stored in lua tables, which you can modify with the following macro (for example, to set them for glyphs in the PUA).

\backslash babelcharproperty $\{\langle char-code \rangle\}[\langle to-char-code \rangle]\{\langle property \rangle\}\{\langle value \rangle\}$

New 3.32 Here, $\{\langle char-code \rangle\}$ is a number (with \TeX syntax). With the optional argument, you can set a range of values. There are three properties (with a short name, taken from Unicode): direction (bc), mirror (bmg), linebreak (lb). The settings are global, and this command is allowed only in vertical mode (the preamble or between paragraphs). For example:

```

\babelcharproperty{`\z}{mirror}{`?}
\babelcharproperty{`-}{direction}{1} % or al, r, en, an, on, et, cs
\babelcharproperty{`)}{linebreak}{cl} % or id, op, cl, ns, ex, in, hy

```

Please, refer to the Unicode standard (Annex #9 and Annex #14) for the meaning of the available codes. For example, en is ‘European number’ and id is ‘ideographic’.

New 3.39 Another property is locale, which adds characters to the list used by onchar in \backslash babelprovide, or, if the last argument is empty, removes them. The last argument is the locale name:

```

\babelcharproperty{`,`}{locale}{english}

```

1.29 Tweaking some features

`\babeladjust` $\{ \langle \textit{key-value-list} \rangle \}$

New 3.36 Sometimes you might need to disable some babel features. Currently this macro understands the following keys [to be documented], with values on or off:

<code>bidi.mirroring</code>	<code>linebreak.cjk</code>	<code>autoload.bcp47</code>
<code>bidi.text</code>	<code>justify.arabic</code>	<code>bcp47.toname</code>
<code>bidi.math</code>	<code>layout.tabular</code>	
<code>linebreak.sea</code>	<code>layout.lists</code>	

Other keys [to be documented] are:

<code>autoload.options</code>	<code>autoload.bcp47.options</code>	<code>select.write</code>
<code>autoload.bcp47.prefix</code>	<code>prehyphenation.disable</code>	<code>select.encoding</code>

For example, you can set `\babeladjust{bidi.text=off}` if you are using an alternative algorithm or with large sections not requiring it. Use with care, because these options do not deactivate other related options (like paragraph direction with `bidi.text`).

1.30 Tips, workarounds, known issues and notes

- If you use the document class *book* and you use `\ref` inside the argument of `\chapter` (or just use `\ref` inside `\MakeUppercase`), \LaTeX will keep complaining about an undefined label. To prevent such problems, you can revert to using uppercase labels, you can use `\lowercase{\ref{foo}}` inside the argument of `\chapter`, or, if you will not use shorthands in labels, set the `safe` option to `none` or `bib`.
- Both `ltxdoc` and `babel` use `\AtBeginDocument` to change some catcodes, and `babel` reloads `hline` to make sure `:` has the right one, so if you want to change the catcode of `|` it has to be done using the same method at the proper place, with

```
\AtBeginDocument{\DeleteShortVerb{\|}}
```

before loading `babel`. This way, when the document begins the sequence is (1) make `|` active (`ltxdoc`); (2) make it unactive (your settings); (3) make `babel` shorthands active (`babel`); (4) reload `hline` (`babel`, now with the correct catcodes for `|` and `:`).

- Documents with several input encodings are not frequent, but sometimes are useful. You can set different encodings for different languages as the following example shows:

```
\addto\extrasfrench{\inputencoding{latin1}}
\addto\extrarussian{\inputencoding{koi8-r}}
```

- For the hyphenation to work correctly, `lccodes` cannot change, because \TeX only takes into account the values when the paragraph is hyphenated, i.e., when it has been finished.²⁰ So, if you write a chunk of French text with `\foreignlanguage`, the apostrophes might not be taken into account. This is a limitation of \TeX , not of `babel`. Alternatively, you may use `\usesshorthands` to activate `'` and `\defineshorthand`, or redefine `\textquoteright` (the latter is called by the non-ASCII right quote).
- `\bibitem` is out of sync with `\selectlanguage` in the `.aux` file. The reason is `\bibitem` uses `\immediate` (and others, in fact), while `\selectlanguage` doesn't. There is a similar issue with floats, too. There is no known workaround.

²⁰This explains why \LaTeX assumes the lowercase mapping of T1 and does not provide a tool for multiple mappings. Unfortunately, `\savingshyphcodes` is not a solution either, because `lccodes` for hyphenation are frozen in the format and cannot be changed.

- Babel does not take into account `\normalsfcodes` and (non-)French spacing is not always properly (un)set by languages. However, problems are unlikely to happen and therefore this part remains untouched in version 3.9 (but it is in the ‘to do’ list).
- Using a character mathematically active (ie, with math code "8000) as a shorthand can make \TeX enter in an infinite loop in some rare cases. (Another issue in the ‘to do’ list, although there is a partial solution.)

The following packages can be useful, too (the list is still far from complete):

csquotes Logical markup for quotes.
iflang Tests correctly the current language.
hyphsubst Selects a different set of patterns for a language.
translator An open platform for packages that need to be localized.
siunitx Typesetting of numbers and physical quantities.
biblatex Programmable bibliographies and citations.
bicaption Bilingual captions.
babelbib Multilingual bibliographies.
microtype Adjusts the typesetting according to some languages (kerning and spacing). Ligatures can be disabled.
substitutefont Combines fonts in several encodings.
mkpattern Generates hyphenation patterns.
tracklang Tracks which languages have been requested.
ucharclasses (xetex) Switches fonts when you switch from one Unicode block to another.
zhspacing Spacing for CJK documents in xetex.

1.31 Current and future work

The current work is focused on the so-called complex scripts in luatex . In 8-bit engines, babel provided a basic support for bidi text as part of the style for Hebrew, but it is somewhat unsatisfactory and internally replaces some hardwired commands by other hardwired commands (generic changes would be much better).

Useful additions would be, for example, time, currency, addresses and personal names.²¹ But that is the easy part, because they don’t require modifying the \TeX internals.

Calendars (Arabic, Persian, Indic, etc.) are under study.

Also interesting are differences in the sentence structure or related to it. For example, in Basque the number precedes the name (including chapters), in Hungarian “from (1)” is “(1)-ből”, but “from (3)” is “(3)-ből”, in Spanish an item labelled “3.^o” may be referred to as either “ítem 3.^o” or “3.^{er} ítem”, and so on.

An option to manage bidirectional document layout in luatex (lists, footnotes, etc.) is almost finished, but xetex required more work. Unfortunately, proper support for xetex requires patching somehow lots of macros and packages (and some issues related to `\specials` remain, like color and hyperlinks), so babel resorts to the bidi package (by Vafa Khalighi). See the babel repository for a small example (xe-bidi).

1.32 Tentative and experimental code

See the code section for `\foreignlanguage*` (a new starred version of `\foreignlanguage`). For old an deprecated functions, see the babel site.

Options for locales loaded on the fly

New 3.51 `\babeladjust{ autoloading.options = ... }` sets the options when a language is loaded on the fly (by default, no options). A typical value would be `import t`, which defines captions, date, numerals, etc., but ignores the code in the tex file (for example, extended numerals in Greek).

Labels

²¹See for example POSIX, ISO 14652 and the Unicode Common Locale Data Repository (CLDR). Those systems, however, have limited application to \TeX because their aim is just to display information and not fine typesetting.

New 3.48 There is some work in progress for babel to deal with labels, both with the relation to captions (chapters, part), and how counters are used to define them. It is still somewhat tentative because it is far from trivial – see the babel site for further details.

2 Loading languages with `language.dat`

T_EX and most engines based on it (pdfT_EX, xetex, ϵ -T_EX, the main exception being luatex) require hyphenation patterns to be preloaded when a format is created (eg, L^AT_EX, XeL^AT_EX, pdfL^AT_EX). babel provides a tool which has become standard in many distributions and based on a “configuration file” named `language.dat`. The exact way this file is used depends on the distribution, so please, read the documentation for the latter (note also some distributions generate the file with some tool).

New 3.9q With luatex, however, patterns are loaded on the fly when requested by the language (except the “0th” language, typically english, which is preloaded always).²² Until 3.9n, this task was delegated to the package `luatex-hyphen`, by Khaled Hosny, Élie Roux, and Manuel Pégourié-Gonnard, and required an extra file named `language.dat.lua`, but now a new mechanism has been devised based solely on `language.dat`. **You must rebuild the formats** if upgrading from a previous version. You may want to have a local `language.dat` for a particular project (for example, a book on Chemistry).²³

2.1 Format

In that file the person who maintains a T_EX environment has to record for which languages he has hyphenation patterns *and* in which files these are stored²⁴. When hyphenation exceptions are stored in a separate file this can be indicated by naming that file *after* the file with the hyphenation patterns.

The file can contain empty lines and comments, as well as lines which start with an equals (=) sign. Such a line will instruct L^AT_EX that the hyphenation patterns just processed have to be known under an alternative name. Here is an example:

```
% File      : language.dat
% Purpose   : tell iniTeX what files with patterns to load.
english     english.hyphenations
=british

dutch       hyphen.dutch exceptions.dutch % Nederlands
german      hyphen.ger
```

You may also set the font encoding the patterns are intended for by following the language name by a colon and the encoding code.²⁵ For example:

```
german:T1 hyphenT1.ger
german hyphen.ger
```

With the previous settings, if the encoding when the language is selected is T1 then the patterns in `hyphenT1.ger` are used, but otherwise use those in `hyphen.ger` (note the encoding can be set in `\extras{lang}`).

A typical error when using babel is the following:

²²This feature was added to 3.9o, but it was buggy. Both 3.9o and 3.9p are deprecated.

²³The loader for lua(e)tex is slightly different as it's not based on babel but on `etex.src`. Until 3.9p it just didn't work, but thanks to the new code it works by reloading the data in the babel way, i.e., with `language.dat`.

²⁴This is because different operating systems sometimes use very different file-naming conventions.

²⁵This is not a new feature, but in former versions it didn't work correctly.

```
No hyphenation patterns were preloaded for
the language '<lang>' into the format.
Please, configure your TeX system to add them and
rebuild the format. Now I will use the patterns
preloaded for english instead}}
```

It simply means you must reconfigure `language.dat`, either by hand or with the tools provided by your distribution.

3 The interface between the core of babel and the language definition files

The *language definition files* (`ldf`) must conform to a number of conventions, because these files have to fill in the gaps left by the common code in `babel.def`, i. e., the definitions of the macros that produce texts. Also the language-switching possibility which has been built into the babel system has its implications.

The following assumptions are made:

- Some of the language-specific definitions might be used by plain \TeX users, so the files have to be coded so that they can be read by both \LaTeX and plain \TeX . The current format can be checked by looking at the value of the macro `\fmtname`.
- The common part of the babel system redefines a number of macros and environments (defined previously in the document style) to put in the names of macros that replace the previously hard-wired texts. These macros have to be defined in the language definition files.
- The language definition files must define five macros, used to activate and deactivate the language-specific definitions. These macros are `\<lang>hyphenmins`, `\<lang>captions`, `\<lang>date`, `\<lang>extras` and `\<lang>noextras` (the last two may be left empty); where `<lang>` is either the name of the language definition file or the name of the \LaTeX option that is to be used. These macros and their functions are discussed below. You must define all or none for a language (or a dialect); defining, say, `\<lang>date` but not `\<lang>captions` does not raise an error but can lead to unexpected results.
- When a language definition file is loaded, it can define `\l@<lang>` to be a dialect of `\language0` when `\l@<lang>` is undefined.
- Language names must be all lowercase. If an unknown language is selected, babel will attempt setting it after lowercasing its name.
- The semantics of modifiers is not defined (on purpose). In most cases, they will just be simple separated options (eg, `spanish`), but a language might require, say, a set of options organized as a tree with suboptions (in such a case, the recommended separator is `/`).

Some recommendations:

- The preferred shorthand is `"`, which is not used in \LaTeX (quotes are entered as `` `` and `' '`). Other good choices are characters which are not used in a certain context (eg, `=` in an ancient language). Note however `=`, `<`, `>`, `:` and the like can be dangerous, because they may be used as part of the syntax of some elements (numeric expressions, key/value pairs, etc.).
- Captions should not contain shorthands or encoding-dependent commands (the latter is not always possible, but should be clearly documented). They should be defined using the LICR. You may also use the new tools for encoded strings, described below.

- Avoid adding things to `\noextras⟨lang⟩` except for `umlauthigh` and friends, `\bbl@deactivate`, `\bbl@(non)frenchspacing`, and language-specific macros. Use always, if possible, `\babel@save` and `\babel@savevariable` (except if you still want to have access to the previous value). Do not reset a macro or a setting to a hardcoded value. Never. Instead save its value in `\extras⟨lang⟩`.
- Do not switch scripts. If you want to make sure a set of glyphs is used, switch either the font encoding (low-level) or the language (high-level, which in turn may switch the font encoding). Usage of things like `\latintext` is deprecated.²⁶
- Please, for “private” internal macros do not use the `\bbl@` prefix. It is used by `babel` and it can lead to incompatibilities.

There are no special requirements for documenting your language files. Now they are not included in the base `babel` manual, so provide a standalone document suited for your needs, as well as other files you think can be useful. A PDF and a “readme” are strongly recommended.

3.1 Guidelines for contributed languages

Currently, the easiest way to contribute a new language is by taking one of the 500 or so `ini` templates available on GitHub as a basis. Just make a pull request or download it and then, after filling the fields, send it to me. Feel free to ask for help or to make feature requests.

As to `ldf` files, now language files are “outsourced” and are located in a separate directory (`/macros/latex/contrib/babel-contrib`), so that they are contributed directly to CTAN (please, do not send to me language styles just to upload them to CTAN).

Of course, placing your style files in this directory is not mandatory, but if you want to do it, here are a few guidelines.

- Do not hesitate stating on the file heads you are the author and the maintainer, if you actually are. There is no need to state the `babel` maintainer(s) as authors if they have not contributed significantly to your language files.
- Fonts are not strictly part of a language, so they are best placed in the corresponding TeX tree. This includes not only `tfm`, `vf`, `ps1`, `otf`, `mf` files and the like, but also `fd` ones.
- Font and input encodings are usually best placed in the corresponding tree, too, but sometimes they belong more naturally to the `babel` style. Note you may also need to define a LICR.
- `Babel` `ldf` files may just interface a framework, as it happens often with Oriental languages/scripts. This framework is best placed in its own directory.

The following page provides a starting point for `ldf` files:

<http://www.texnia.com/incubator.html>. See also

<https://latex3.github.io/babel/guides/list-of-locale-templates.html>.

If you need further assistance and technical advice in the development of language styles, I am willing to help you. And of course, you can make any suggestion you like.

3.2 Basic macros

In the core of the `babel` system, several macros are defined for use in language definition files. Their purpose is to make a new language known. The first two are related to hyphenation patterns.

`\addlanguage` The macro `\addlanguage` is a non-outer version of the macro `\newlanguage`, defined in `plain.tex` version 3.x. Here “language” is used in the TeX sense of set of hyphenation patterns.

`\adddialect` The macro `\adddialect` can be used when two languages can (or must) use the same

²⁶But not removed, for backward compatibility.

hyphenation patterns. This can also be useful for languages for which no patterns are preloaded in the format. In such cases the default behavior of the babel system is to define this language as a ‘dialect’ of the language for which the patterns were loaded as `\language0`. Here “language” is used in the \TeX sense of set of hyphenation patterns.

`\<lang>hyphenmins` The macro `\<lang>hyphenmins` is used to store the values of the `\lefthyphenmin` and `\righthyphenmin`. Redefine this macro to set your own values, with two numbers corresponding to these two parameters. For example:

```
\renewcommand\spanishhyphenmins{34}
```

(Assigning `\lefthyphenmin` and `\righthyphenmin` directly in `\extras<lang>` has no effect.)

`\providehyphenmins` The macro `\providehyphenmins` should be used in the language definition files to set `\lefthyphenmin` and `\righthyphenmin`. This macro will check whether these parameters were provided by the hyphenation file before it takes any action. If these values have been already set, this command is ignored (currently, default pattern files do *not* set them).

`\captions<lang>` The macro `\captions<lang>` defines the macros that hold the texts to replace the original hard-wired texts.

`\date<lang>` The macro `\date<lang>` defines `\today`.

`\extras<lang>` The macro `\extras<lang>` contains all the extra definitions needed for a specific language. This macro, like the following, is a hook – you can add things to it, but it must not be used directly.

`\noextras<lang>` Because we want to let the user switch between languages, but we do not know what state \TeX might be in after the execution of `\extras<lang>`, a macro that brings \TeX into a predefined state is needed. It will be no surprise that the name of this macro is `\noextras<lang>`.

`\bbl@declare@ttribute` This is a command to be used in the language definition files for declaring a language attribute. It takes three arguments: the name of the language, the attribute to be defined, and the code to be executed when the attribute is to be used.

`\main@language` To postpone the activation of the definitions needed for a language until the beginning of a document, all language definition files should use `\main@language` instead of `\selectlanguage`. This will just store the name of the language, and the proper language will be activated at the start of the document.

`\ProvidesLanguage` The macro `\ProvidesLanguage` should be used to identify the language definition files. Its syntax is similar to the syntax of the \TeX command `\ProvidesPackage`.

`\LdfInit` The macro `\LdfInit` performs a couple of standard checks that must be made at the beginning of a language definition file, such as checking the category code of the `@`-sign, preventing the `.ldf` file from being processed twice, etc.

`\ldf@quit` The macro `\ldf@quit` does work needed if a `.ldf` file was processed earlier. This includes resetting the category code of the `@`-sign, preparing the language to be activated at `\begin{document}` time, and ending the input stream.

`\ldf@finish` The macro `\ldf@finish` does work needed at the end of each `.ldf` file. This includes resetting the category code of the `@`-sign, loading a local configuration file, and preparing the language to be activated at `\begin{document}` time.

`\loadlocalcfg` After processing a language definition file, \TeX can be instructed to load a local configuration file. This file can, for instance, be used to add strings to `\captions<lang>` to support local document classes. The user will be informed that this configuration file has been loaded. This macro is called by `\ldf@finish`.

`\substitutefontfamily` (Deprecated.) This command takes three arguments, a font encoding and two font family names. It creates a font description file for the first font in the given encoding. This `.fd` file will instruct \TeX to use a font from the second family when a font from the first family in the given encoding seems to be needed.

3.3 Skeleton

Here is the basic structure of an `ldf` file, with a language, a dialect and an attribute. Strings are best defined using the method explained in sec. 3.8 (babel 3.9 and later).


```

\ProvidesLanguage{<language>}
[2016/04/23 v0.0 <Language> support from the babel system]
\LdfInit{<language>}{captions<language>}

\ifx\undefined\l@<language>
  \nopatterns{<Language>}
  \adddialect\l@<language>0
\fi

\adddialect\l@<dialect>\l@<language>

\bbI\declare@ttribute{<language>}{<attrib>}{%
  \expandafter\addto\expandafter\extras<language>
  \expandafter{\extras<attrib><language>}%
  \let\captions<language>\captions<attrib><language>}

\providehyphenmins{<language>}{\tw@\thr@@}

\StartBabelCommands*{<language>}{captions}
\SetString\chaptername{<chapter name>}
% More strings

\StartBabelCommands*{<language>}{date}
\SetString\monthinname{<name of first month>}
% More strings

\StartBabelCommands*{<dialect>}{captions}
\SetString\chaptername{<chapter name>}
% More strings

\StartBabelCommands*{<dialect>}{date}
\SetString\monthinname{<name of first month>}
% More strings

\EndBabelCommands

\addto\extras<language>{}
\addto\noextras<language>{}
\let\extras<dialect>\extras<language>
\let\noextras<dialect>\noextras<language>

\ldf@finish{<language>}

```

NOTE If for some reason you want to load a package in your style, you should be aware it cannot be done directly in the ldf file, but it can be delayed with `\AtEndOfPackage`. Macros from external packages can be used *inside* definitions in the ldf itself (for example, `\extras<language>`), but if executed directly, the code must be placed inside `\AtEndOfPackage`. A trivial example illustrating these points is:

```

\AtEndOfPackage{%
  \RequirePackage{dingbat}%      Delay package
  \savebox{\myeye}{\eye}}%      And direct usage
\newsavebox{\myeye}
\newcommand\myanchor{\anchor}%  But OK inside command

```

3.4 Support for active characters

In quite a number of language definition files, active characters are introduced. To facilitate this, some support macros are provided.

`\initiate@active@char` The internal macro `\initiate@active@char` is used in language definition files to instruct

	<p> \LaTeX to give a character the category code ‘active’. When a character has been made active it will remain that way until the end of the document. Its definition may vary. </p>
<code>\bbl@activate</code>	The command <code>\bbl@activate</code> is used to change the way an active character expands.
<code>\bbl@deactivate</code>	<code>\bbl@activate</code> ‘switches on’ the active behavior of the character. <code>\bbl@deactivate</code> lets the active character expand to its former (mostly) non-active self.
<code>\declare@shorthand</code>	The macro <code>\declare@shorthand</code> is used to define the various shorthands. It takes three arguments: the name for the collection of shorthands this definition belongs to; the character (sequence) that makes up the shorthand, i.e. <code>~</code> or <code>"a</code> ; and the code to be executed when the shorthand is encountered. (It does <i>not</i> raise an error if the shorthand character has not been “initiated”.)
<code>\bbl@add@special</code>	<p> The \TeXbook states: “Plain \TeX includes a macro called <code>\dospecials</code> that is essentially a set macro, representing the set of all characters that have a special category code.” [4, p. 380] It is used to set text ‘verbatim’. To make this work if more characters get a special category code, you have to add this character to the macro <code>\dospecial</code>. \LaTeX adds another macro called <code>\@sanitize</code> representing the same character set, but without the curly braces. The macros <code>\bbl@add@special⟨char⟩</code> and <code>\bbl@remove@special⟨char⟩</code> add and remove the character <code>⟨char⟩</code> to these two sets. </p>
<code>\bbl@remove@special</code>	
<code>\@safe@activetrue</code>	Enables and disables the “safe” mode. It is a tool for package and class authors. See the description below.
<code>\@safe@activetrue</code>	

3.5 Support for saving macro definitions

Language definition files may want to *redefine* macros that already exist. Therefore a mechanism for saving (and restoring) the original definition of those macros is provided. We provide two macros for this²⁷.

<code>\babel@save</code>	To save the current meaning of any control sequence, the macro <code>\babel@save</code> is provided. It takes one argument, <code>⟨cname⟩</code> , the control sequence for which the meaning has to be saved.
<code>\babel@savevariable</code>	<p>A second macro is provided to save the current value of a variable. In this context, anything that is allowed after the <code>\the</code> primitive is considered to be a variable. The macro takes one argument, the <code>⟨variable⟩</code>.</p> <p>The effect of the preceding macros is to append a piece of code to the current definition of <code>\originalTeX</code>. When <code>\originalTeX</code> is expanded, this code restores the previous definition of the control sequence or the previous value of the variable.</p>

3.6 Support for extending macros

<code>\addto</code>	<p>The macro <code>\addto{⟨control sequence⟩}{⟨\TeX code⟩}</code> can be used to extend the definition of a macro. The macro need not be defined (ie, it can be undefined or <code>\relax</code>). This macro can, for instance, be used in adding instructions to a macro like <code>\extrasenglish</code>. Be careful when using this macro, because depending on the case the assignment can be either global (usually) or local (sometimes). That does not seem very consistent, but this behavior is preserved for backward compatibility. If you are using <code>etoolbox</code>, by Philipp Lehman, consider using the tools provided by this package instead of <code>\addto</code>.</p>
---------------------	---

3.7 Macros common to a number of languages

<code>\bbl@allowhyphens</code>	In several languages compound words are used. This means that when \TeX has to hyphenate such a compound word, it only does so at the ‘-’ that is used in such words. To allow hyphenation in the rest of such a compound word, the macro <code>\bbl@allowhyphens</code> can be used.
<code>\allowhyphens</code>	<p>Same as <code>\bbl@allowhyphens</code>, but does nothing if the encoding is T1. It is intended mainly for characters provided as real glyphs by this encoding but constructed with <code>\accent</code> in OT1.</p> <p>Note the previous command (<code>\bbl@allowhyphens</code>) has different applications (hyphens and discretionaries) than this one (composite chars). Note also prior to version 3.7, <code>\allowhyphens</code> had the behavior of <code>\bbl@allowhyphens</code>.</p>

²⁷This mechanism was introduced by Bernd Raichle.

`\set@low@box` For some languages, quotes need to be lowered to the baseline. For this purpose the macro `\set@low@box` is available. It takes one argument and puts that argument in an `\hbox`, at the baseline. The result is available in `\box0` for further processing.

`\save@sf@q` Sometimes it is necessary to preserve the `\spacefactor`. For this purpose the macro `\save@sf@q` is available. It takes one argument, saves the current `\spacefactor`, executes the argument, and restores the `\spacefactor`.

`\bbl@frenchspacing` The commands `\bbl@frenchspacing` and `\bbl@nonfrenchspacing` can be used to

`\bbl@nonfrenchspacing` properly switch French spacing on and off.

3.8 Encoding-dependent strings

New 3.9a Babel 3.9 provides a way of defining strings in several encodings, intended mainly for `luatex` and `xetex`, although the old way of defining/switching strings still works and it's used by default.

It consists of a series of blocks started with `\StartBabelCommands`. The last block is closed with `\EndBabelCommands`. Each block is a single group (ie, local declarations apply until the next `\StartBabelCommands` or `\EndBabelCommands`). An `ldf` may contain several series of this kind.

Thanks to this new feature, string values and string language switching are not mixed any more. Furthermore, strings do not need to be wrapped with formatting commands (eg, to select the writing direction) because babel takes care of it automatically. (See also `\setlocalecaption`.)

`\StartBabelCommands` $\langle\text{language-list}\rangle\{\langle\text{category}\rangle\}[\langle\text{selector}\rangle]$

The $\langle\text{language-list}\rangle$ specifies which languages the block is intended for. A block is taken into account only if the `\CurrentOption` is listed here. Alternatively, you can define `\BabelLanguages` to a comma-separated list of languages to be defined (if undefined, `\StartBabelCommands` sets it to `\CurrentOption`). You may write `\CurrentOption` as the language, but this is discouraged – an explicit name (or names) is much better and clearer. A “selector” selects a group of definitions to be used, optionally followed by extra info about the encodings to be used. The name `unicode` must be used for `xetex` and `luatex`. Without a selector, the LICR representation (ie, with macros like `\~{n}` instead of `ñ`) is assumed.

If a string is set several times (because several blocks are read), the first one takes precedence (ie, it works much like `\providecommand`).

Encoding info is `charset=` followed by a `charset`, which if given sets how the strings should be translated to the internal representation used by the engine, typically `utf8`, which is the only value supported currently (default is no translations). Note `charset` is applied by `luatex` and `xetex` when reading the file, not when the macro or string is used in the document.

A list of font encodings which the strings are expected to work with can be given after `fontenc=` (separated with spaces, if two or more) – recommended, but not mandatory, although blocks without this key are not taken into account if you have requested `strings=encoded`.

Blocks without a selector are read always. They provide fallback values, and therefore they must be the last ones; they should be provided always if possible and all strings should be defined somehow inside it; they can be the only blocks (mainly LGC scripts using the LICR). The $\langle\text{category}\rangle$ is either `captions`, `date` or `extras`. You must stick to these three categories, even if no error is raised when using other name.²⁸ It may be empty, too, but in such a case using `\SetString` is an error.

```
\StartBabelCommands{language}{captions}
  [unicode, fontenc=TU EU1 EU2, charset=utf8]
\SetString{chaptername}{utf8-string}
```

²⁸In future releases further categories may be added.

```

\StartBabelCommands{language}{captions}
\SetString{chaptername}{ascii-maybe-LICR-string}

\EndBabelCommands

```

A real example is:

```

\StartBabelCommands{austrian}{date}
[unicode, fontenc=TU EU1 EU2, charset=utf8]
\SetString\monthiname{Jänner}

\StartBabelCommands{german,austrian}{date}
[unicode, fontenc=TU EU1 EU2, charset=utf8]
\SetString\monthiiname{März}

\StartBabelCommands{austrian}{date}
\SetString\monthiname{J\"a}nner}

\StartBabelCommands{german}{date}
\SetString\monthiname{Januar}

\StartBabelCommands{german,austrian}{date}
\SetString\monthiiname{Februar}
\SetString\monthiiname{M\"a}rz}
\SetString\monthivname{April}
\SetString\monthvname{Mai}
\SetString\monthviname{Juni}
\SetString\monthviiname{Juli}
\SetString\monthviiname{August}
\SetString\monthixname{September}
\SetString\monthxname{Oktober}
\SetString\monthxiname{November}
\SetString\monthxiiname{Dezenber}
\SetString\today{\number\day.-%
\csname month\romannumeral\month name\endcsname\space
\number\year}

\StartBabelCommands{german,austrian}{captions}
\SetString\prefacename{Vorwort}
[etc.]

\EndBabelCommands

```

When used in ldf files, previous values of `\category` `\language` are overridden, which means the old way to define strings still works and used by default (to be precise, is first set to undefined and then strings are added). However, when used in the preamble or in a package, new settings are added to the previous ones, if the language exists (in the babel sense, ie, if `\date\language` exists).

NOTE The package option `strings` introduced in version 3.9 (around 2013) when Unicode engines were still minority, is now deprecated.

`\StartBabelCommands` * `{\language-list}{\category}[<selector>]`

The starred version just forces strings to take a value – if not set as package option, then the default for the engine is used. This is not done by default to prevent backward incompatibilities, but if you are creating a new language this version is better. It's up to the maintainers of the current languages to decide if using it is appropriate.²⁹

²⁹This replaces in 3.9g a short-lived `\UseStrings` which has been removed because it did not work.

\EndBabelCommands Marks the end of the series of blocks.

\AfterBabelCommands $\{\langle code \rangle\}$

The code is delayed and executed at the global scope just after `\EndBabelCommands`.

\SetString $\{\langle macro-name \rangle\}\{\langle string \rangle\}$

Adds $\langle macro-name \rangle$ to the current category, and defines globally $\langle lang-macro-name \rangle$ to $\langle code \rangle$ (after applying the transformation corresponding to the current charset or defined with the hook `stringprocess`).

Use this command to define strings, without including any “logic” if possible, which should be a separated macro. See the example above for the date.

\SetStringLoop $\{\langle macro-name \rangle\}\{\langle string-list \rangle\}$

A convenient way to define several ordered names at once. For example, to define `\abmoniname`, `\abmoniname`, etc. (and similarly with `abday`):

```
\SetStringLoop{abmon#1name}{en,fb,mr,ab,my,jn,jl,ag,sp,oc,nv,dc}
\SetStringLoop{abday#1name}{lu,ma,mi,ju,vi,sa,do}
```

#1 is replaced by the roman numeral.

\SetCase $[\langle map-list \rangle]\{\langle toupper-code \rangle\}\{\langle tolower-code \rangle\}$

WARNING This feature doesn’t work any longer after some changes in the \LaTeX kernel. It’s now deprecated and an alternative is on the way.

\SetHyphenMap $\{\langle to-lower-macros \rangle\}$

New 3.9g Case mapping serves in \TeX for two unrelated purposes: case transforms (upper/lower) and hyphenation. Hyphenation is handled by `\SetHyphenMap` and controlled with the package option `hyphenmap`.

There are three helper macros to be used inside `\SetHyphenMap`:

- `\BabelLower $\{\langle uccode \rangle\}\{\langle lccode \rangle\}$` is similar to `\lccode` but it’s ignored if the char has been set and saves the original `\lccode` to restore it when switching the language (except with `hyphenmap=first`).
- `\BabelLowerMM $\{\langle uccode-from \rangle\}\{\langle uccode-to \rangle\}\{\langle step \rangle\}\{\langle lccode-from \rangle\}$` loops though the given uppercase codes, using the step, and assigns them the `\lccode`, which is also increased (MM stands for *many-to-many*).
- `\BabelLowerMO $\{\langle uccode-from \rangle\}\{\langle uccode-to \rangle\}\{\langle step \rangle\}\{\langle lccode \rangle\}$` loops though the given uppercase codes, using the step, and assigns them the `\lccode`, which is fixed (MO stands for *many-to-one*).

An example is (which is redundant, because these assignments are done by both `luatex` and `xetex`):

```
\SetHyphenMap{\BabelLowerMM{"100}{{"11F}{2}{{"101}}
```

This macro is not intended to fix wrong mappings done by Unicode (which are the default in both `xetex` and `luatex`) – if an assignment is wrong, fix it directly.

3.9 Executing code based on the selector

`\IfBabelSelectorTF {<selectors>}{<true>}{<false>}`

New 3.67 Sometimes a different setup is desired depending on the selector used. Values allowed in `<selectors>` are `select`, `other`, `foreign`, `other*` (and also `foreign*` for the tentative starred version), and it can consist of a comma-separated list. For example:

```
\IfBabelSelectorTF{other, other*}{A}{B}
```

is true with these two environment selectors.
Its natural place of use is in hooks or in `\extras<language>`.

Part II

Source code

babel is being developed incrementally, which means parts of the code are under development and therefore incomplete. Only documented features are considered complete. In other words, use babel only as documented (except, of course, if you want to explore and test them – you can post suggestions about multilingual issues to kadingira@tug.org on <http://tug.org/mailman/listinfo/kadingira>).

4 Identification and loading of required files

Code documentation is still under revision.

The following description is no longer valid, because switch and plain have been merged into babel.def.

The babel package after unpacking consists of the following files:

switch.def defines macros to set and switch languages.

babel.def defines the rest of macros. It has two parts: a generic one and a second one only for LaTeX.

babel.sty is the \TeX package, which set options and load language styles.

plain.def defines some \TeX macros required by `babel.def` and provides a few tools for Plain.

hyphen.cfg is the file to be used when generating the formats to load hyphenation patterns.

The babel installer extends docstrip with a few “pseudo-guards” to set “variables” used at installation time. They are used with `<@name@>` at the appropriated places in the source code and shown below with `<<name>>`. That brings a little bit of literate programming.

5 locale directory

A required component of babel is a set of ini files with basic definitions for about 200 languages. They are distributed as a separate zip file, not packed as dtx. With them, babel will fully support Unicode engines.

Most of them are essentially finished (except bugs and mistakes, of course). Some of them are still incomplete (but they will be usable), and there are some omissions (eg, Latin and polytonic Greek, and there are no geographic areas in Spanish). Hindi, French, Occitan and Breton will show a warning related to dates. Not all include LICR variants.

This is a preliminary documentation.

ini files contain the actual data; tex files are currently just proxies to the corresponding ini files.

Most keys are self-explanatory.

charset the encoding used in the ini file.

version of the ini file

level “version” of the ini specification . which keys are available (they may grow in a compatible way) and how they should be read.

encodings a descriptive list of font encodings.

[captions] section of captions in the file charset

[captions.licr] same, but in pure ASCII using the LICR

date.long fields are as in the CLDR, but the syntax is different. Anything inside brackets is a date field (eg, MMM for the month name) and anything outside is text. In addition, [] is a non breakable space and [.] is an abbreviation dot.

Keys may be further qualified in a particular language with a suffix starting with a uppercase letter. It can be just a letter (eg, babel.name.A, babel.name.B) or a name (eg, date.long.Nominative, date.long.Formal, but no language is currently using the latter). *Multi-letter* qualifiers are forward compatible in the sense they won't conflict with new "global" keys (which start always with a lowercase case). There is an exception, however: the section counters has been devised to have arbitrary keys, so you can add lowercased keys if you want.

6 Tools

```
1 <<version=3.88.12052>>
2 <<date=2023/04/30>>
```

Do not use the following macros in ldf files. They may change in the future. This applies mainly to those recently added for replacing, trimming and looping. The older ones, like \bbl@afterfi, will not change.

We define some basic macros which just make the code cleaner. \bbl@add is now used internally instead of \addto because of the unpredictable behavior of the latter. Used in babel.def and in babel.sty, which means in L^AT_EX is executed twice, but we need them when defining options and babel.def cannot be load until options have been defined. This does not hurt, but should be fixed somehow.

```
3 <<(*Basic macros)>> ≡
4 \bbl@trace{Basic macros}
5 \def\bbl@stripslash{\expandafter\@gobble\string}
6 \def\bbl@add#1#2{%
7   \bbl@ifunset{\bbl@stripslash#1}%
8     {\def#1{#2}}%
9     {\expandafter\def\expandafter#1\expandafter{#1#2}}
10 \def\bbl@xin@{\@expandtwoargs\in@}
11 \def\bbl@carg#1#2{\expandafter#1\csname#2\endcsname}%
12 \def\bbl@ncarg#1#2#3{\expandafter#1\expandafter#2\csname#3\endcsname}%
13 \def\bbl@ccarg#1#2#3{%
14   \expandafter#1\csname#2\expandafter\endcsname\csname#3\endcsname}%
15 \def\bbl@csarg#1#2{\expandafter#1\csname bbl@#2\endcsname}%
16 \def\bbl@cs#1{\csname bbl@#1\endcsname}
17 \def\bbl@cl#1{\csname bbl@#1@language\endcsname}
18 \def\bbl@loop#1#2#3{\bbl@loop#1{#3}#2,\@nnil,}
19 \def\bbl@loopx#1#2{\expandafter\bbl@loop\expandafter#1\expandafter{#2}}
20 \def\bbl@loop#1#2#3,{%
21   \ifx\@nnil#3\relax\else
22     \def#1{#3}#2\bbl@afterfi\bbl@loop#1{#2}%
23   \fi}
24 \def\bbl@for#1#2#3{\bbl@loopx#1{#2}{\ifx#1@empty\else#3\fi}}
```

\bbl@add@list This internal macro adds its second argument to a comma separated list in its first argument. When the list is not defined yet (or empty), it will be initiated. It presumes expandable character strings.

```
25 \def\bbl@add@list#1#2{%
26   \edef#1{%
27     \bbl@ifunset{\bbl@stripslash#1}%
28     {}%
29     {\ifx#1@empty\else#1,\fi}%
30   #2}}
```

\bbl@afterelse Because the code that is used in the handling of active characters may need to look ahead, we take extra care to "throw" it over the \else and \fi parts of an \if-statement³⁰. These macros will break if another \if... \fi statement appears in one of the arguments and it is not enclosed in braces.

```
31 \long\def\bbl@afterelse#1\else#2\fi{\fi#1}
32 \long\def\bbl@afterfi#1\fi{\fi#1}
```

³⁰This code is based on code presented in TUGboat vol. 12, no2, June 1991 in "An expansion Power Lemma" by Sonja Maus.

`\bbl@exp` Now, just syntactical sugar, but it makes partial expansion of some code a lot more simple and readable. Here `\` stands for `\noexpand`, `\<.>` for `\noexpand` applied to a built macro name (which does not define the macro if undefined to `\relax`, because it is created locally), and `\[. .]` for one-level expansion (where `. .` is the macro name without the backslash). The result may be followed by extra arguments, if necessary.

```

33 \def\bbl@exp#1{%
34   \begingroup
35   \let\<\noexpand
36   \let\<\bbl@exp@en
37   \let\[\bbl@exp@ue
38   \edef\bbl@exp@aux{\endgroup#1}%
39   \bbl@exp@aux}
40 \def\bbl@exp@en#1>{\expandafter\noexpand\csname#1\endcsname}%
41 \def\bbl@exp@ue#1]{%
42   \unexpanded\expandafter\expandafter\expandafter{\csname#1\endcsname}}%

```

`\bbl@trim` The following piece of code is stolen (with some changes) from `keyval`, by David Carlisle. It defines two macros: `\bbl@trim` and `\bbl@trim@def`. The first one strips the leading and trailing spaces from the second argument and then applies the first argument (a macro, `\toks@` and the like). The second one, as its name suggests, defines the first argument as the stripped second argument.

```

43 \def\bbl@tempa#1{%
44   \long\def\bbl@trim##1##2{%
45     \futurelet\bbl@trim@a\bbl@trim@c##2\@nil\@nil#1\@nil\relax{##1}}%
46   \def\bbl@trim@c{%
47     \ifx\bbl@trim@a\@sptoken
48       \expandafter\bbl@trim@b
49     \else
50       \expandafter\bbl@trim@b\expandafter#1%
51     \fi}%
52   \long\def\bbl@trim@b#1##1 \@nil{\bbl@trim@i##1}}
53 \bbl@tempa{ }
54 \long\def\bbl@trim@i#1\@nil#2\relax#3{#3{#1}}
55 \long\def\bbl@trim@def#1{\bbl@trim{\def#1}}

```

`\bbl@ifunset` To check if a macro is defined, we create a new macro, which does the same as `\@ifundefined`. However, in an ϵ -tex engine, it is based on `\ifcsname`, which is more efficient, and does not waste memory. Defined inside a group, to avoid `\ifcsname` being implicitly set to `\relax` by the `\csname` test.

```

56 \begingroup
57   \gdef\bbl@ifunset#1{%
58     \expandafter\ifx\csname#1\endcsname\relax
59       \expandafter\@firstoftwo
60     \else
61       \expandafter\@secondoftwo
62     \fi}
63   \bbl@ifunset{ifcsname}%
64   {}%
65   {\gdef\bbl@ifunset#1{%
66     \ifcsname#1\endcsname
67       \expandafter\ifx\csname#1\endcsname\relax
68         \bbl@afterelse\expandafter\@firstoftwo
69       \else
70         \bbl@afterfi\expandafter\@secondoftwo
71       \fi
72     \else
73       \expandafter\@firstoftwo
74     \fi}}
75 \endgroup

```

`\bbl@ifblank` A tool from `url`, by Donald Arseneau, which tests if a string is empty or space. The companion macros tests if a macro is defined with some 'real' value, ie, not `\relax` and not empty,

```

76 \def\bbl@ifblank#1{%

```



```

77 \bbl@ifblank@i#1\@nil\@nil\@secondoftwo\@firstoftwo\@nil}
78 \long\def\bbl@ifblank@i#1#2\@nil#3#4#5\@nil{#4}
79 \def\bbl@ifset#1#2#3{%
80 \bbl@ifunset{#1}{#3}{\bbl@exp{\bbl@ifblank{\@nameuse{#1}}}{#3}{#2}}}

```

For each element in the comma separated <key>=<value> list, execute <code> with #1 and #2 as the key and the value of current item (trimmed). In addition, the item is passed verbatim as #3. With the <key> alone, it passes \@empty (ie, the macro thus named, not an empty argument, which is what you get with <key>= and no value).

```

81 \def\bbl@forkv#1#2{%
82 \def\bbl@kvcmd##1##2##3{#2}%
83 \bbl@kvnext#1,\@nil,}
84 \def\bbl@kvnext#1,{%
85 \ifx\@nil#1\relax\else
86 \bbl@ifblank{#1}{\bbl@forkv@eq#1=\@empty=\@nil{#1}}%
87 \expandafter\bbl@kvnext
88 \fi}
89 \def\bbl@forkv@eq#1=#2=#3\@nil#4{%
90 \bbl@trim\def\bbl@forkv@a{#1}%
91 \bbl@trim{\expandafter\bbl@kvcmd\expandafter{\bbl@forkv@a}{#2}{#4}}

```

A *for* loop. Each item (trimmed), is #1. It cannot be nested (it's doable, but we don't need it).

```

92 \def\bbl@vforeach#1#2{%
93 \def\bbl@forcmd##1{#2}%
94 \bbl@fornext#1,\@nil,}
95 \def\bbl@fornext#1,{%
96 \ifx\@nil#1\relax\else
97 \bbl@ifblank{#1}{\bbl@trim\bbl@forcmd{#1}}%
98 \expandafter\bbl@fornext
99 \fi}
100 \def\bbl@foreach#1{\expandafter\bbl@vforeach\expandafter{#1}}

```

\bbl@replace Returns implicitly \toks@ with the modified string.

```

101 \def\bbl@replace#1#2#3{% in #1 -> repl #2 by #3
102 \toks@{}}%
103 \def\bbl@replace@aux##1#2##2#2{%
104 \ifx\bbl@nil##2%
105 \toks@\expandafter{\the\toks@##1}%
106 \else
107 \toks@\expandafter{\the\toks@##1#3}%
108 \bbl@afterfi
109 \bbl@replace@aux##2#2%
110 \fi}%
111 \expandafter\bbl@replace@aux#1#2\bbl@nil#2%
112 \edef#1{\the\toks@}}

```

An extension to the previous macro. It takes into account the parameters, and it is string based (ie, if you replace elax by ho, then \relax becomes \rho). No checking is done at all, because it is not a general purpose macro, and it is used by babel only when it works (an example where it does *not* work is in \bbl@TG@@date, and also fails if there are macros with spaces, because they are retokenized). It may change! (or even merged with \bbl@replace; I'm not sure ckecking the replacement is really necessary or just paranoia).

```

113 \ifx\detokenize\undefined\else % Unused macros if old Plain TeX
114 \bbl@exp{\def\bbl@parsedef##1\detokenize{macro:}}#2->#3\relax{%
115 \def\bbl@tempa{#1}%
116 \def\bbl@tempb{#2}%
117 \def\bbl@tempe{#3}}
118 \def\bbl@sreplace#1#2#3{%
119 \begingroup
120 \expandafter\bbl@parsedef\meaning#1\relax
121 \def\bbl@tempc{#2}%
122 \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
123 \def\bbl@tempd{#3}%

```

```

124 \edef\bbl@tempd{\expandafter\strip@prefix\meaning\bbl@tempd}%
125 \bbl@xin@\bbl@tempc{\bbl@tempe}% If not in macro, do nothing
126 \ifin@
127 \bbl@exp{\bbl@replace\bbl@tempe{\bbl@tempc}{\bbl@tempd}}%
128 \def\bbl@tempc{% Expanded an executed below as 'uplevel'
129 \\\makeatletter % "internal" macros with @ are assumed
130 \\\scantokens{%
131 \bbl@tempa\\@namedef{\bbl@stripslash#1}\bbl@tempb{\bbl@tempe}}%
132 \catcode64=\the\catcode64\relax}% Restore @
133 \else
134 \let\bbl@tempc\@empty % Not \relax
135 \fi
136 \bbl@exp{% For the 'uplevel' assignments
137 \endgroup
138 \bbl@tempc}} % empty or expand to set #1 with changes
139 \fi

```

Two further tools. `\bbl@ifsamestring` first expand its arguments and then compare their expansion (sanitized, so that the catcodes do not matter). `\bbl@engine` takes the following values: 0 is pdfTeX, 1 is luatex, and 2 is xetex. You may use the latter it in your language style if you want.

```

140 \def\bbl@ifsamestring#1#2{%
141 \begingroup
142 \protected@edef\bbl@tempb{#1}%
143 \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
144 \protected@edef\bbl@tempc{#2}%
145 \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
146 \ifx\bbl@tempb\bbl@tempc
147 \aftergroup\@firstoftwo
148 \else
149 \aftergroup\@secondoftwo
150 \fi
151 \endgroup}
152 \chardef\bbl@engine=%
153 \ifx\directlua\@undefined
154 \ifx\XeTeXinputencoding\@undefined
155 \z@
156 \else
157 \tw@
158 \fi
159 \else
160 \@ne
161 \fi

```

A somewhat hackish tool (hence its name) to avoid spurious spaces in some contexts.

```

162 \def\bbl@bsphack{%
163 \ifhmode
164 \hskip\z@skip
165 \def\bbl@esphack{\loop\ifdim\lastskip>\z@\unskip\repeat\unskip}%
166 \else
167 \let\bbl@esphack\@empty
168 \fi}

```

Another hackish tool, to apply case changes inside a protected macros. It's based on the internal `\let`'s made by `\MakeUppercase` and `\MakeLowercase` between things like `\oe` and `\OE`.

```

169 \def\bbl@cased{%
170 \ifx\oe\OE
171 \expandafter\in@\expandafter
172 {\expandafter\OE\expandafter}\expandafter{\oe}%
173 \ifin@
174 \bbl@afterelse\expandafter\MakeUppercase
175 \else
176 \bbl@afterfi\expandafter\MakeLowercase
177 \fi

```

```

178 \else
179 \expandafter\@firstofone
180 \fi}

```

The following adds some code to `\extras...` both before and after, while avoiding doing it twice. It's somewhat convoluted, to deal with `#`'s. Used to deal with `alph`, `Alph` and `frenchspacing` when there are already changes (with `\babel@save`).

```

181 \def\bbl@extras@wrap#1#2#3{% 1:in-test, 2:before, 3:after
182 \toks@\expandafter\expandafter\expandafter{%
183 \csname extras\language\endcsname}%
184 \bbl@exp{\in@{#1}\the\toks@}}%
185 \ifin@ \else
186 \@temptokena{#2}%
187 \edef\bbl@tempc{\the\@temptokena\the\toks@}%
188 \toks@\expandafter{\bbl@tempc#3}%
189 \expandafter\edef\csname extras\language\endcsname{\the\toks@}%
190 \fi}
191 <</Basic macros>>

```

Some files identify themselves with a \TeX macro. The following code is placed before them to define (and then undefine) if not in \TeX .

```

192 <<*Make sure ProvidesFile is defined>> ≡
193 \ifx\ProvidesFile\@undefined
194 \def\ProvidesFile#1[#2 #3 #4]{%
195 \wlog{File: #1 #4 #3 <#2>}%
196 \let\ProvidesFile\@undefined}
197 \fi
198 <</Make sure ProvidesFile is defined>>

```

6.1 Multiple languages

`\language` Plain \TeX version 3.0 provides the primitive `\language` that is used to store the current language. When used with a pre-3.0 version this function has to be implemented by allocating a counter. The following block is used in `switch.def` and `hyphen.cfg`; the latter may seem redundant, but remember `babel` doesn't require loading `switch.def` in the format.

```

199 <<*Define core switching macros>> ≡
200 \ifx\language\@undefined
201 \csname newcount\endcsname\language
202 \fi
203 <</Define core switching macros>>

```

`\last@language` Another counter is used to keep track of the allocated languages. \TeX and \LaTeX reserves for this purpose the count 19.

`\addlanguage` This macro was introduced for $\TeX < 2$. Preserved for compatibility.

```

204 <<*Define core switching macros>> ≡
205 \countdef\last@language=19
206 \def\addlanguage{\csname newlanguage\endcsname}
207 <</Define core switching macros>>

```

Now we make sure all required files are loaded. When the command `\AtBeginDocument` doesn't exist we assume that we are dealing with a plain-based format. In that case the file `plain.def` is needed (which also defines `\AtBeginDocument`, and therefore it is not loaded twice). We need the first part when the format is created, and `\orig@dump` is used as a flag. Otherwise, we need to use the second part, so `\orig@dump` is not defined (`plain.def` undefines it).

Check if the current version of `switch.def` has been previously loaded (mainly, `hyphen.cfg`). If not, load it now. We cannot load `babel.def` here because we first need to declare and process the package options.

6.2 The Package File (LaTeX, babel.sty)

```
208 <*package>
209 \NeedsTeXFormat{LaTeX2e}[2005/12/01]
210 \ProvidesPackage{babel}[<date>] <version> The Babel package]
```

Start with some “private” debugging tool, and then define macros for errors.

```
211 \@ifpackagewith{babel}{debug}
212   {\providecommand\bbl@trace[1]{\message{^^J[ #1 ]}}}%
213   \let\bbl@debug\@firstofone
214   \ifx\directlua\@undefined\else
215     \directlua{ Babel = Babel or {}
216       Babel.debug = true }%
217     \input{babel-debug.tex}%
218   \fi}
219 {\providecommand\bbl@trace[1]}%
220 \let\bbl@debug\@gobble
221 \ifx\directlua\@undefined\else
222   \directlua{ Babel = Babel or {}
223     Babel.debug = false }%
224   \fi}
225 \def\bbl@error#1#2{%
226   \begingroup
227     \def\{\MessageBreak}%
228     \PackageError{babel}{#1}{#2}%
229   \endgroup}
230 \def\bbl@warning#1{%
231   \begingroup
232     \def\{\MessageBreak}%
233     \PackageWarning{babel}{#1}%
234   \endgroup}
235 \def\bbl@infowarn#1{%
236   \begingroup
237     \def\{\MessageBreak}%
238     \PackageNote{babel}{#1}%
239   \endgroup}
240 \def\bbl@info#1{%
241   \begingroup
242     \def\{\MessageBreak}%
243     \PackageInfo{babel}{#1}%
244   \endgroup}
```

This file also takes care of a number of compatibility issues with other packages and defines a few additional package options. Apart from all the language options below we also have a few options that influence the behavior of language definition files.

Many of the following options don’t do anything themselves, they are just defined in order to make it possible for babel and language definition files to check if one of them was specified by the user. But first, include here the *Basic macros* defined above.

```
245 <<Basic macros>>
246 \@ifpackagewith{babel}{silent}
247   {\let\bbl@info\@gobble
248     \let\bbl@infowarn\@gobble
249     \let\bbl@warning\@gobble}
250   {}
251 %
252 \def\AfterBabelLanguage#1{%
253   \global\expandafter\bbl@add\csname#1.ldf-h@@k\endcsname}%

```

If the format created a list of loaded languages (in \bbl@languages), get the name of the 0-th to show the actual language used. Also available with base, because it just shows info.

```
254 \ifx\bbl@languages\@undefined\else
255   \begingroup
256     \catcode\^^I=12
257     \@ifpackagewith{babel}{showlanguages}{%
258       \begingroup
```

```

259     \def\bbl@elt#1#2#3#4{\wlog{#2^^I#1^^I#3^^I#4}}}%
260     \wlog{<*languages>}%
261     \bbl@languages
262     \wlog{</languages>}%
263     \endgroup{}}
264 \endgroup
265 \def\bbl@elt#1#2#3#4{%
266     \ifnum#2=\z@
267         \gdef\bbl@nulllanguage{#1}%
268         \def\bbl@elt##1##2##3##4{%
269             \fi}%
270     \bbl@languages
271 \fi%

```

6.3 base

The first ‘real’ option to be processed is base, which set the hyphenation patterns then resets `ver@babel.sty` so that \TeX forgets about the first loading. After a subset of `babel.def` has been loaded (the old `switch.def`) and `\AfterBabelLanguage` defined, it exits. Now the base option. With it we can define (and load, with `luatex`) hyphenation patterns, even if we are not interested in the rest of `babel`.

```

272 \bbl@trace{Defining option 'base'}
273 \@ifpackagewith{babel}{base}{%
274     \let\bbl@onlyswitch\@empty
275     \let\bbl@provide@locale\relax
276     \input babel.def
277     \let\bbl@onlyswitch\@undefined
278     \ifx\directlua\@undefined
279         \DeclareOption*{\bbl@patterns{\CurrentOption}}%
280     \else
281         \input luababel.def
282         \DeclareOption*{\bbl@patterns@lua{\CurrentOption}}%
283     \fi
284     \DeclareOption{base}{}%
285     \DeclareOption{showlanguages}{}%
286     \ProcessOptions
287     \global\expandafter\let\csname opt@babel.sty\endcsname\relax
288     \global\expandafter\let\csname ver@babel.sty\endcsname\relax
289     \global\let@ifl@ter@@\@ifl@ter
290     \def@ifl@ter#1#2#3#4#5{\global\let@ifl@ter\@ifl@ter@@}%
291     \endinput{}%

```

6.4 key=value options and other general option

The following macros extract language modifiers, and only real package options are kept in the option list. Modifiers are saved and assigned to `\BabelModifiers` at `\bbl@load@language`; when no modifiers have been given, the former is `\relax`. How modifiers are handled are left to language styles; they can use `\in@`, loop them with `\@for` or load `keyval`, for example.

```

292 \bbl@trace{key=value and another general options}
293 \bbl@csarg\let{tempa\expandafter}\csname opt@babel.sty\endcsname
294 \def\bbl@tempb#1.#2{% Remove trailing dot
295     #1\ifx\@empty#2\else,\bbl@afterfi\bbl@tempb#2\fi}%
296 \def\bbl@tempd#1.#2\@nnil{% TODO. Refactor lists?
297     \ifx\@empty#2%
298         \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
299     \else
300         \in@{,provide=}{, #1}%
301         \ifin@
302             \edef\bbl@tempc{%
303                 \ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.\bbl@tempb#2}%
304         \else
305             \in@{=}{#1}%
306             \ifin@

```

```

307     \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.#2}%
308     \else
309     \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
310     \bbl@csarg\edef{mod#1}{\bbl@tempb#2}%
311     \fi
312   \fi
313 \fi}
314 \let\bbl@tempc\@empty
315 \bbl@foreach\bbl@tempa{\bbl@tempd#1.\@empty\@nnil}
316 \expandafter\let\csname opt@babel.sty\endcsname\bbl@tempc

```

The next option tells babel to leave shorthand characters active at the end of processing the package. This is *not* the default as it can cause problems with other packages, but for those who want to use the shorthand characters in the preamble of their documents this can help.

```

317 \DeclareOption{KeepShorthandsActive}{}
318 \DeclareOption{activeacute}{}
319 \DeclareOption{activegrave}{}
320 \DeclareOption{debug}{}
321 \DeclareOption{noconfigs}{}
322 \DeclareOption{showlanguages}{}
323 \DeclareOption{silent}{}
324 % \DeclareOption{mono}{}
325 \DeclareOption{shorthands=off}{\bbl@tempa shorthands=\bbl@tempa}
326 \chardef\bbl@iniflag\z@
327 \DeclareOption{provide=*}{\chardef\bbl@iniflag\@ne}    % main -> +1
328 \DeclareOption{provide+=*}{\chardef\bbl@iniflag\@tw@}  % add = 2
329 \DeclareOption{provide*=*}{\chardef\bbl@iniflag\@thr@@} % add + main
330 % A separate option
331 \let\bbl@autoload@options\@empty
332 \DeclareOption{provide@=*}{\def\bbl@autoload@options{import}}
333 % Don't use. Experimental. TODO.
334 \newif\ifbbl@single
335 \DeclareOption{selectors=off}{\bbl@singletrue}
336 <(More package options)>

```

Handling of package options is done in three passes. (I [JBL] am not very happy with the idea, anyway.) The first one processes options which has been declared above or follow the syntax <key>=<value>, the second one loads the requested languages, except the main one if set with the key main, and the third one loads the latter. First, we “flag” valid keys with a nil value.

```

337 \let\bbl@opt@shorthands\@nnil
338 \let\bbl@opt@config\@nnil
339 \let\bbl@opt@main\@nnil
340 \let\bbl@opt@headfoot\@nnil
341 \let\bbl@opt@layout\@nnil
342 \let\bbl@opt@provide\@nnil

```

The following tool is defined temporarily to store the values of options.

```

343 \def\bbl@tempa#1=#2\bbl@tempa{%
344   \bbl@csarg\ifx{opt#1}\@nnil
345     \bbl@csarg\edef{opt#1}{#2}%
346   \else
347     \bbl@error
348     {Bad option '#1=#2'. Either you have misspelled the\\%
349     key or there is a previous setting of '#1'. Valid\\%
350     keys are, among others, 'shorthands', 'main', 'bidi',\\%
351     'strings', 'config', 'headfoot', 'safe', 'math'.}%
352     {See the manual for further details.}
353   \fi}

```

Now the option list is processed, taking into account only currently declared options (including those declared with a =), and <key>=<value> options (the former take precedence). Unrecognized options are saved in \bbl@language@opts, because they are language options.

```

354 \let\bbl@language@opts\@empty
355 \DeclareOption*{%

```

```

356 \bbl@xin@{\string=}{\CurrentOption}%
357 \ifin@
358 \expandafter\bbl@tempa\CurrentOption\bbl@tempa
359 \else
360 \bbl@add@list\bbl@language@opts{\CurrentOption}%
361 \fi}

```

Now we finish the first pass (and start over).

```

362 \ProcessOptions*
363 \ifx\bbl@opt@provide\@nnil
364 \let\bbl@opt@provide\@empty %%%% MOVE above
365 \else
366 \chardef\bbl@iniflag\@ne
367 \bbl@exp{\bbl@forkv{\@nameuse{@raw@opt@babel.sty}}}{%
368 \in@{,provide,}{, #1,}%
369 \ifin@
370 \def\bbl@opt@provide{#2}%
371 \bbl@replace\bbl@opt@provide{;}{,}%
372 \fi}
373 \fi
374 %

```

6.5 Conditional loading of shorthands

If there is no shorthands=<chars>, the original babel macros are left untouched, but if there is, these macros are wrapped (in babel.def) to define only those given.

A bit of optimization: if there is no shorthands=, then \bbl@ifshorthand is always true, and it is always false if shorthands is empty. Also, some code makes sense only with shorthands=...

```

375 \bbl@trace{Conditional loading of shorthands}
376 \def\bbl@sh@string#1{%
377 \ifx#1\@empty\else
378 \ifx#1t\string~%
379 \else\ifx#1c\string,%
380 \else\string#1%
381 \fi\fi
382 \expandafter\bbl@sh@string
383 \fi}
384 \ifx\bbl@opt@shorthands\@nnil
385 \def\bbl@ifshorthand#1#2#3{#2}%
386 \else\ifx\bbl@opt@shorthands\@empty
387 \def\bbl@ifshorthand#1#2#3{#3}%
388 \else

```

The following macro tests if a shorthand is one of the allowed ones.

```

389 \def\bbl@ifshorthand#1{%
390 \bbl@xin@{\string#1}{\bbl@opt@shorthands}%
391 \ifin@
392 \expandafter\@firstoftwo
393 \else
394 \expandafter\@secondoftwo
395 \fi}

```

We make sure all chars in the string are ‘other’, with the help of an auxiliary macro defined above (which also zaps spaces).

```

396 \edef\bbl@opt@shorthands{%
397 \expandafter\bbl@sh@string\bbl@opt@shorthands\@empty}%

```

The following is ignored with shorthands=off, since it is intended to take some additional actions for certain chars.

```

398 \bbl@ifshorthand{'}%
399 {\PassOptionsToPackage{activeacute}{babel}}{}
400 \bbl@ifshorthand{`}%
401 {\PassOptionsToPackage{activegrave}{babel}}{}
402 \fi\fi

```

With `headfoot=lang` we can set the language used in heads/foots. For example, in `babel/3796` just adds `headfoot=english`. It misuses `\resetactivechars` but seems to work.

```
403 \ifx\bbbl@opt@headfoot\@nnil\else
404   \g@addto@macro\resetactivechars{%
405     \set@typeset@protect
406     \expandafter\select@language@x\expandafter{\bbbl@opt@headfoot}%
407     \let\protect\noexpand}
408 \fi
```

For the option `safe` we use a different approach – `\bbbl@opt@safe` says which macros are redefined (B for bibs and R for refs). By default, both are currently set, but in a future release it will be set to none.

```
409 \ifx\bbbl@opt@safe\@undefined
410   \def\bbbl@opt@safe{BR}
411   % \let\bbbl@opt@safe\empty % Pending of \cite
412 \fi
```

For layout an auxiliary macro is provided, available for packages and language styles. Optimization: if there is no layout, just do nothing.

```
413 \bbbl@trace{Defining IfBabelLayout}
414 \ifx\bbbl@opt@layout\@nnil
415   \newcommand\IfBabelLayout[3]{#3}%
416 \else
417   \bbbl@exp{\bbbl@forkv{\@nameuse{@raw@opt@babel.sty}}}{%
418     \in@{,layout,}{, #1,}%
419     \ifin@
420       \def\bbbl@opt@layout{#2}%
421       \bbbl@replace\bbbl@opt@layout{ }{.}%
422     \fi}
423   \newcommand\IfBabelLayout[1]{%
424     \@expandtwoargs\in@{.#1.}{.\bbbl@opt@layout.}%
425     \ifin@
426       \expandafter\@firstoftwo
427     \else
428       \expandafter\@secondoftwo
429     \fi}
430 \fi
431 </package>
432 <*core>
```

6.6 Interlude for Plain

Because of the way `docstrip` works, we need to insert some code for Plain here. However, the tools provided by the `babel` installer for literate programming makes this section a short interlude, because the actual code is below, tagged as *Emulate LaTeX*.

```
433 \ifx\ldf@quit\@undefined\else
434 \endinput\fi % Same line!
435 <<Make sure ProvidesFile is defined>>
436 \ProvidesFile{babel.def}[\<date>] [\<version>] Babel common definitions]
437 \ifx\AtBeginDocument\@undefined % TODO. change test.
438   <<Emulate LaTeX>>
439 \fi
```

That is all for the moment. Now follows some common stuff, for both Plain and \LaTeX . After it, we will resume the \LaTeX -only stuff.

```
440 </core>
441 <*package | core>
```

7 Multiple languages

This is not a separate file (`switch.def`) anymore.

Plain \TeX version 3.0 provides the primitive `\language` that is used to store the current language. When used with a pre-3.0 version this function has to be implemented by allocating a counter.


```

442 \def\bbl@version{\<<version>>}
443 \def\bbl@date{\<<date>>}
444 \<Define core switching macros>

```

`\adddialect` The macro `\adddialect` can be used to add the name of a dialect or variant language, for which an already defined hyphenation table can be used.

```

445 \def\adddialect#1#2{%
446   \global\chardef#1#2\relax
447   \bbl@usehooks{adddialect}{\#1}{\#2}}%
448   \begingroup
449     \count@#1\relax
450     \def\bbl@elt##1##2##3##4{%
451       \ifnum\count@=##2\relax
452         \edef\bbl@tempa{\expandafter\@gobbletwo\string#1}%
453         \bbl@info{Hyphen rules for '\expandafter\@gobble\bbl@tempa'
454           set to \expandafter\string\csname l@##1\endcsname\%
455           (\string\language\the\count@). Reported}%
456         \def\bbl@elt####1####2####3####4{%
457           \fi}%
458         \bbl@cs{languages}%
459       \endgroup}

```

`\bbl@iflanguage` executes code only if the language `l@` exists. Otherwise raises an error. The argument of `\bbl@fixname` has to be a macro name, as it may get “fixed” if casing (lc/uc) is wrong. It’s an attempt to fix a long-standing bug when `\foreignlanguage` and the like appear in a `\MakeXXXcase`. However, a lowercase form is not imposed to improve backward compatibility (perhaps you defined a language named MYLANG, but unfortunately mixed case names cannot be trapped). Note `l@` is encapsulated, so that its case does not change.

```

460 \def\bbl@fixname#1{%
461   \begingroup
462   \def\bbl@tempe{l@}%
463   \edef\bbl@tempd{\noexpand\@ifundefined{\noexpand\bbl@tempe#1}}%
464   \bbl@tempd
465     {\lowercase\expandafter{\bbl@tempd}%
466     {\uppercase\expandafter{\bbl@tempd}%
467     \@empty
468     {\edef\bbl@tempd{\def\noexpand#1{\#1}}%
469     {\uppercase\expandafter{\bbl@tempd}}}%
470     {\edef\bbl@tempd{\def\noexpand#1{\#1}}%
471     {\lowercase\expandafter{\bbl@tempd}}}%
472     \@empty
473     \edef\bbl@tempd{\endgroup\def\noexpand#1{\#1}}%
474   \bbl@tempd
475   \bbl@exp{\bbl@usehooks{language}{\#1}}%
476 \def\bbl@iflanguage#1{%
477   \@ifundefined{l@#1}{\@nolanerr{#1}\@gobble}\@firstofone}

```

After a name has been ‘fixed’, the selectors will try to load the language. If even the fixed name is not defined, will load it on the fly, either based on its name, or if activated, its BCP47 code.

We first need a couple of macros for a simple BCP 47 look up. It also makes sure, with `\bbl@bcpcase`, casing is the correct one, so that `sr-latn-ba` becomes `fr-Latn-BA`. Note #4 may contain some `\@empty`’s, but they are eventually removed. `\bbl@bcpllookup` either returns the found ini or it is `\relax`.

```

478 \def\bbl@bcpcase#1#2#3#4\@#5{%
479   \ifx\@empty#3%
480     \uppercase{\def#5{\#1#2}}%
481   \else
482     \uppercase{\def#5{\#1}}%
483     \lowercase{\edef#5{\#5#2#3#4}}%
484   \fi}
485 \def\bbl@bcpllookup#1-#2-#3-#4\@#5{%
486   \let\bbl@bcp\relax
487   \lowercase{\def\bbl@tempa{\#1}}%
488   \ifx\@empty#2%

```

```

489 \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
490 \else\ifx\@empty#3%
491 \bbl@bcpcase#2\@empty\@empty\@bbl@tempb
492 \IfFileExists{babel-\bbl@tempa-\bbl@tempb.ini}%
493 {\edef\bbl@bcp{\bbl@tempa-\bbl@tempb}}%
494 }%
495 \ifx\bbl@bcp\relax
496 \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
497 \fi
498 \else
499 \bbl@bcpcase#2\@empty\@empty\@bbl@tempb
500 \bbl@bcpcase#3\@empty\@empty\@bbl@tempc
501 \IfFileExists{babel-\bbl@tempa-\bbl@tempb-\bbl@tempc.ini}%
502 {\edef\bbl@bcp{\bbl@tempa-\bbl@tempb-\bbl@tempc}}%
503 }%
504 \ifx\bbl@bcp\relax
505 \IfFileExists{babel-\bbl@tempa-\bbl@tempc.ini}%
506 {\edef\bbl@bcp{\bbl@tempa-\bbl@tempc}}%
507 }%
508 \fi
509 \ifx\bbl@bcp\relax
510 \IfFileExists{babel-\bbl@tempa-\bbl@tempc.ini}%
511 {\edef\bbl@bcp{\bbl@tempa-\bbl@tempc}}%
512 }%
513 \fi
514 \ifx\bbl@bcp\relax
515 \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
516 \fi
517 \fi\fi}
518 \let\bbl@initoload\relax
519 \def\bbl@provide@locale{%
520 \ifx\babelprovide\undefined
521 \bbl@error{For a language to be defined on the fly 'base'\\%
522 is not enough, and the whole package must be\\%
523 loaded. Either delete the 'base' option or\\%
524 request the languages explicitly}%
525 {See the manual for further details.}%
526 \fi
527 \let\bbl@auxname\language\name % Still necessary. TODO
528 \bbl@ifunset{\bbl@bcp@map@\language\name}{}% Move uplevel??
529 {\edef\language\name{\@nameuse{\bbl@bcp@map@\language\name}}}%
530 \ifbbl@bcp@allowed
531 \expandafter\ifx\csname date\language\name\endcsname\relax
532 \expandafter
533 \bbl@bcp@lookup\language\name-\@empty-\@empty-\@empty\@
534 \ifx\bbl@bcp\relax\else % Returned by \bbl@bcp@lookup
535 \edef\language\name{\bbl@bcp@prefix\bbl@bcp}%
536 \edef\localename{\bbl@bcp@prefix\bbl@bcp}%
537 \expandafter\ifx\csname date\language\name\endcsname\relax
538 \let\bbl@initoload\bbl@bcp
539 \bbl@exp{\bbl@babelprovide[\bbl@autoload@bcptoptions]{\language\name}}%
540 \let\bbl@initoload\relax
541 \fi
542 \bbl@csarg\xdef{\bcp@map@\bbl@bcp}{\localename}%
543 \fi
544 \fi
545 \fi
546 \expandafter\ifx\csname date\language\name\endcsname\relax
547 \IfFileExists{babel-\language\name.tex}%
548 {\bbl@exp{\bbl@babelprovide[\bbl@autoload@options]{\language\name}}}%
549 }%
550 \fi}

```

`\iflanguage` Users might want to test (in a private package for instance) which language is currently active. For this we provide a test macro, `\iflanguage`, that has three arguments. It checks whether the first argument is a known language. If so, it compares the first argument with the value of `\language`. Then, depending on the result of the comparison, it executes either the second or the third argument.

```

551 \def\iflanguage#1{%
552   \bbl@iflanguage{#1}{%
553     \ifnum\csname l@#1\endcsname=\language
554       \expandafter\@firstoftwo
555     \else
556       \expandafter\@secondoftwo
557   \fi}}

```

7.1 Selecting the language

`\selectlanguage` The macro `\selectlanguage` checks whether the language is already defined before it performs its actual task, which is to update `\language` and activate language-specific definitions.

```

558 \let\bbl@select@type\z@
559 \edef\selectlanguage{%
560   \noexpand\protect
561   \expandafter\noexpand\csname selectlanguage \endcsname}

```

Because the command `\selectlanguage` could be used in a moving argument it expands to `\protect\selectlanguage`. Therefore, we have to make sure that a macro `\protect` exists. If it doesn't it is `\let` to `\relax`.

```

562 \ifx\@undefined\protect\let\protect\relax\fi

```

The following definition is preserved for backwards compatibility (eg, arabi, koma). It is related to a trick for 2.09, now discarded.

```

563 \let\xstring\string

```

Since version 3.5 babel writes entries to the auxiliary files in order to typeset table of contents etc. in the correct language environment.

`\bbl@pop@language` But when the language change happens *inside* a group the end of the group doesn't write anything to the auxiliary files. Therefore we need TeX's `aftergroup` mechanism to help us. The command `\aftergroup` stores the token immediately following it to be executed when the current group is closed. So we define a temporary control sequence `\bbl@pop@language` to be executed at the end of the group. It calls `\bbl@set@language` with the name of the current language as its argument.

`\bbl@language@stack` The previous solution works for one level of nesting groups, but as soon as more levels are used it is no longer adequate. For that case we need to keep track of the nested languages using a stack mechanism. This stack is called `\bbl@language@stack` and initially empty.

```

564 \def\bbl@language@stack{}

```

When using a stack we need a mechanism to push an element on the stack and to retrieve the information afterwards.

`\bbl@push@language` The stack is simply a list of languagenames, separated with a '+' sign; the push function can be simple:
`\bbl@pop@language`

```

565 \def\bbl@push@language{%
566   \ifx\language\@undefined\else
567     \ifx\currentgrouplevel\@undefined
568       \xdef\bbl@language@stack{\language+\bbl@language@stack}%
569     \else
570       \ifnum\currentgrouplevel=\z@
571         \xdef\bbl@language@stack{\language+}%
572       \else
573         \xdef\bbl@language@stack{\language+\bbl@language@stack}%
574     \fi
575   \fi
576 \fi}

```

Retrieving information from the stack is a little bit less simple, as we need to remove the element from the stack while storing it in the macro `\language`. For this we first define a helper function.

`\bbl@pop@lang` This macro stores its first element (which is delimited by the ‘+’-sign) in `\language` and stores the rest of the string in `\bbl@language@stack`.

```
577 \def\bbl@pop@lang#1+#2\@@{%
578   \edef\language{#1}%
579   \xdef\bbl@language@stack{#2}}
```

The reason for the somewhat weird arrangement of arguments to the helper function is the fact it is called in the following way. This means that before `\bbl@pop@lang` is executed TeX first *expands* the stack, stored in `\bbl@language@stack`. The result of that is that the argument string of `\bbl@pop@lang` contains one or more language names, each followed by a ‘+’-sign (zero language names won’t occur as this macro will only be called after something has been pushed on the stack).

```
580 \let\bbl@ifrestoring\@secondoftwo
581 \def\bbl@pop@language{%
582   \expandafter\bbl@pop@lang\bbl@language@stack\@@
583   \let\bbl@ifrestoring\@firstoftwo
584   \expandafter\bbl@set@language\expandafter{\language}%
585   \let\bbl@ifrestoring\@secondoftwo}
```

Once the name of the previous language is retrieved from the stack, it is fed to `\bbl@set@language` to do the actual work of switching everything that needs switching.

An alternative way to identify languages (in the babel sense) with a numerical value is introduced in 3.30. This is one of the first steps for a new interface based on the concept of locale, which explains the name of `\localeid`. This means `\l@...` will be reserved for hyphenation patterns (so that two locales can share the same rules).

```
586 \chardef\localeid\z@
587 \def\bbl@id@last{0} % No real need for a new counter
588 \def\bbl@id@assign{%
589   \bbl@ifunset\bbl@id@\@language}%
590   {\count@\bbl@id@last\relax
591    \advance\count@\@ne
592    \bbl@csarg\chardef{id@\@language}\count@
593    \edef\bbl@id@last{\the\count@}%
594    \ifcase\bbl@engine\or
595      \directlua{
596        Babel = Babel or {}
597        Babel.locale_props = Babel.locale_props or {}
598        Babel.locale_props[\bbl@id@last] = {}
599        Babel.locale_props[\bbl@id@last].name = '\language'
600      }%
601    \fi}%
602  {}%
603  \chardef\localeid\bbl@cl{id@}}
```

The unprotected part of `\selectlanguage`.

```
604 \expandafter\def\csname selectlanguage \endcsname#1{%
605   \ifnum\bbl@hymapsel=\ccclv\let\bbl@hymapsel\tw@\fi
606   \bbl@push@language
607   \aftergroup\bbl@pop@language
608   \bbl@set@language{#1}}
```

`\bbl@set@language` The macro `\bbl@set@language` takes care of switching the language environment *and* of writing entries on the auxiliary files. For historical reasons, language names can be either language of `\language`. To catch either form a trick is used, but unfortunately as a side effect the catcodes of letters in `\language` are messed up. This is a bug, but preserved for backwards compatibility. The list of auxiliary files can be extended by redefining `\BabelContentsFiles`, but make sure they are loaded inside a group (as aux, toc, lof, and lot do) or the last language of the document will remain active afterwards.

We also write a command to change the current language in the auxiliary files.

`\bbl@savelastskip` is used to deal with skips before the write whatsit (as suggested by U Fischer). Adapted from `hyperref`, but it might fail, so I’ll consider it a temporary hack, while I study other options (the ideal, but very likely unfeasible except perhaps in `luatex`, is to avoid the `\write` altogether when not needed).

```

609 \def\BabelContentsFiles{toc,lof,lot}
610 \def\bbl@set@language#1{% from selectlanguage, pop@
611 % The old buggy way. Preserved for compatibility.
612 \edef\language{%
613 \ifnum\escapechar=\expandafter`\string#1\@empty
614 \else\string#1\@empty\fi}%
615 \ifcat\relax\noexpand#1%
616 \expandafter\ifx\csname date\language\endcsname\relax
617 \edef\language{#1}%
618 \let\localename\language
619 \else
620 \bbl@info{Using '\string\language' instead of 'language' is\\%
621 deprecated. If what you want is to use a\\%
622 macro containing the actual locale, make\\%
623 sure it does not not match any language.\\%
624 Reported}%
625 \ifx\scantokens\@undefined
626 \def\localename{??}%
627 \else
628 \scantokens\expandafter{\expandafter
629 \def\expandafter\localename\expandafter{\language}}%
630 \fi
631 \fi
632 \else
633 \def\localename{#1}% This one has the correct catcodes
634 \fi
635 \select@language{\language}%
636 % write to aux
637 \expandafter\ifx\csname date\language\endcsname\relax\else
638 \if@filesw
639 \ifx\babel@aux\@gobbles\else % Set if single in the first, redundant
640 \bbl@savelastskip
641 \protected@write\@auxout{}\string\babel@aux{\bbl@auxname}{}}%
642 \bbl@restorelastskip
643 \fi
644 \bbl@usehooks{write}{}%
645 \fi
646 \fi}
647 %
648 \let\bbl@restorelastskip\relax
649 \let\bbl@savelastskip\relax
650 %
651 \newif\ifbbl@bcpallowed
652 \bbl@bcpallowedfalse
653 \def\select@language#1{% from set@, babel@aux
654 \ifx\bbl@selectorname\@empty
655 \def\bbl@selectorname{select}%
656 % set hymap
657 \fi
658 \ifnum\bbl@hymapsel=\@cclv\chardef\bbl@hymapsel4\relax\fi
659 % set name
660 \edef\language{#1}%
661 \bbl@fixname\language
662 % TODO. name@map must be here?
663 \bbl@provide@locale
664 \bbl@iflanguage\language{%
665 \let\bbl@select@type\z@
666 \expandafter\bbl@switch\expandafter{\language}}
667 \def\babel@aux#1#2{%
668 \select@language{#1}%
669 \bbl@foreach\BabelContentsFiles{% \relax -> don't assume vertical mode
670 \@writefile{##1}{\babel@toc{#1}{#2}\relax}}% TODO - plain?
671 \def\babel@toc#1#2{%

```

```
672 \select@language{#1}}
```

First, check if the user asks for a known language. If so, update the value of `\language` and call `\originalTeX` to bring \TeX in a certain pre-defined state.

The name of the language is stored in the control sequence `\language`.

Then we have to *redefine* `\originalTeX` to compensate for the things that have been activated. To save memory space for the macro definition of `\originalTeX`, we construct the control sequence name for the `\noextras<lang>` command at definition time by expanding the `\csname` primitive. Now activate the language-specific definitions. This is done by constructing the names of three macros by concatenating three words with the argument of `\selectlanguage`, and calling these macros.

The switching of the values of `\lefthyphenmin` and `\righthyphenmin` is somewhat different. First we save their current values, then we check if `\<lang>hyphenmins` is defined. If it is not, we set default values (2 and 3), otherwise the values in `\<lang>hyphenmins` will be used.

```
673 \newif\ifbbl@usedategroup
674 \let\bbl@savextras\@empty
675 \def\bbl@switch#1{% from select@, foreign@
676 % make sure there is info for the language if so requested
677 \bbl@ensureinfo{#1}%
678 % restore
679 \originalTeX
680 \expandafter\def\expandafter\originalTeX\expandafter{%
681 \csname noextras#1\endcsname
682 \let\originalTeX\@empty
683 \babel@beginsave}%
684 \bbl@usehooks{afterreset}{}%
685 \languageshorthands{none}%
686 % set the locale id
687 \bbl@id@assign
688 % switch captions, date
689 % No text is supposed to be added here, so we remove any
690 % spurious spaces.
691 \bbl@bsphack
692 \ifcase\bbl@select@type
693 \csname captions#1\endcsname\relax
694 \csname date#1\endcsname\relax
695 \else
696 \bbl@xin@{,captions,}{, \bbl@select@opts,}%
697 \ifin@
698 \csname captions#1\endcsname\relax
699 \fi
700 \bbl@xin@{,date,}{, \bbl@select@opts,}%
701 \ifin@ % if \foreign... within \<lang>date
702 \csname date#1\endcsname\relax
703 \fi
704 \fi
705 \bbl@esphack
706 % switch extras
707 \csname bbl@preextras@#1\endcsname
708 \bbl@usehooks{beforeextras}{}%
709 \csname extras#1\endcsname\relax
710 \bbl@usehooks{afterextras}{}%
711 % > babel-ensure
712 % > babel-sh-<short>
713 % > babel-bidi
714 % > babel-fontspec
715 \let\bbl@savextras\@empty
716 % hyphenation - case mapping
717 \ifcase\bbl@opt@hyphenmap\or
718 \def\BabelLower##1##2{\lccode##1=##2\relax}%
719 \ifnum\bbl@hymapsel>4\else
720 \csname\language @bbl@hyphenmap\endcsname
721 \fi
```

```

722 \chardef\bbl@opt@hyphenmap\z@
723 \else
724 \ifnum\bbl@hymapsel>\bbl@opt@hyphenmap\else
725 \csname\language\language @bbl@hyphenmap\endcsname
726 \fi
727 \fi
728 \let\bbl@hymapsel\@cclv
729 % hyphenation - select rules
730 \ifnum\csname l@language\endcsname=\l@unhyphenated
731 \edef\bbl@tempa{u}%
732 \else
733 \edef\bbl@tempa{\bbl@cl{lbrk}}%
734 \fi
735 % linebreaking - handle u, e, k (v in the future)
736 \bbl@xin@{/u}{/\bbl@tempa}%
737 \ifin@else\bbl@xin@{/e}{/\bbl@tempa}\fi % elongated forms
738 \ifin@else\bbl@xin@{/k}{/\bbl@tempa}\fi % only kashida
739 \ifin@else\bbl@xin@{/p}{/\bbl@tempa}\fi % padding (eg, Tibetan)
740 \ifin@else\bbl@xin@{/v}{/\bbl@tempa}\fi % variable font
741 \ifin@
742 % unhyphenated/kashida/elongated/padding = allow stretching
743 \language\l@unhyphenated
744 \babel@savevariable\emergencystretch
745 \emergencystretch\maxdimen
746 \babel@savevariable\hbadness
747 \hbadness\@M
748 \else
749 % other = select patterns
750 \bbl@patterns{#1}%
751 \fi
752 % hyphenation - mins
753 \babel@savevariable\lefthyphenmin
754 \babel@savevariable\righthyphenmin
755 \expandafter\ifx\csname #1hyphenmins\endcsname\relax
756 \set@hyphenmins\tw@\thr@@\relax
757 \else
758 \expandafter\expandafter\expandafter\set@hyphenmins
759 \csname #1hyphenmins\endcsname\relax
760 \fi
761 \let\bbl@selectorname\@empty}

```

otherlanguage (env.) The other language environment can be used as an alternative to using the `\selectlanguage` declarative command. When you are typesetting a document which mixes left-to-right and right-to-left typesetting you have to use this environment in order to let things work as you expect them to.

The `\ignorespaces` command is necessary to hide the environment when it is entered in horizontal mode.

```

762 \long\def\otherlanguage#1{%
763 \def\bbl@selectorname{other}%
764 \ifnum\bbl@hymapsel=\@cclv\let\bbl@hymapsel\thr@@\fi
765 \csname selectlanguage \endcsname{#1}%
766 \ignorespaces}

```

The `\endotherlanguage` part of the environment tries to hide itself when it is called in horizontal mode.

```

767 \long\def\endotherlanguage{%
768 \global\@ignoretrue\ignorespaces}

```

otherlanguage* (env.) The other language environment is meant to be used when a large part of text from a different language needs to be typeset, but without changing the translation of words such as ‘figure’. This environment makes use of `\foreign@language`.

```

769 \expandafter\def\csname otherlanguage*\endcsname{%
770 \@ifnextchar[\bbl@otherlanguage@s{\bbl@otherlanguage@s[]}}

```

```

771 \def\bbl@otherlanguage@s[#1]#2{%
772   \def\bbl@selectorname{other*}%
773   \ifnum\bbl@hymapset=\@cclv\chardef\bbl@hymapset4\relax\fi
774   \def\bbl@select@opts{#1}%
775   \foreign@language{#2}}

```

At the end of the environment we need to switch off the extra definitions. The grouping mechanism of the environment will take care of resetting the correct hyphenation rules and “extras”.

```

776 \expandafter\let\csname endotherlanguage*\endcsname\relax

```

\foreignlanguage The `\foreignlanguage` command is another substitute for the `\selectlanguage` command. This command takes two arguments, the first argument is the name of the language to use for typesetting the text specified in the second argument.

Unlike `\selectlanguage` this command doesn’t switch *everything*, it only switches the hyphenation rules and the extra definitions for the language specified. It does this within a group and assumes the `\extras⟨lang⟩` command doesn’t make any `\global` changes. The coding is very similar to part of `\selectlanguage`.

`\bbl@beforeforeign` is a trick to fix a bug in bidi texts. `\foreignlanguage` is supposed to be a ‘text’ command, and therefore it must emit a `\leavevmode`, but it does not, and therefore the indent is placed on the opposite margin. For backward compatibility, however, it is done only if a right-to-left script is requested; otherwise, it is no-op.

(3.11) `\foreignlanguage*` is a temporary, experimental macro for a few lines with a different script direction, while preserving the paragraph format (thank the braces around `\par`, things like `\hangindent` are not reset). Do not use it in production, because its semantics and its syntax may change (and very likely will, or even it could be removed altogether). Currently it enters in `vmode` and then selects the language (which in turn sets the paragraph direction).

(3.11) Also experimental are the hook `foreign` and `foreign*`. With them you can redefine `\BabelText` which by default does nothing. Its behavior is not well defined yet. So, use it in horizontal mode only if you do not want surprises.

In other words, at the beginning of a paragraph `\foreignlanguage` enters into `hmode` with the surrounding `lang`, and with `\foreignlanguage*` with the new `lang`.

```

777 \providecommand\bbl@beforeforeign{}
778 \edef\foreignlanguage{%
779   \noexpand\protect
780   \expandafter\noexpand\csname foreignlanguage \endcsname}
781 \expandafter\def\csname foreignlanguage \endcsname{%
782   \@ifstar\bbl@foreign@s\bbl@foreign@x}
783 \providecommand\bbl@foreign@x[3][]{%
784   \begingroup
785     \def\bbl@selectorname{foreign}%
786     \def\bbl@select@opts{#1}%
787     \let\BabelText\@firstofone
788     \bbl@beforeforeign
789     \foreign@language{#2}%
790     \bbl@usehooks{foreign}{}%
791     \BabelText{#3}% Now in horizontal mode!
792   \endgroup}
793 \def\bbl@foreign@s#1#2{% TODO - \shapemode, \@setpar, ?\@@par
794   \begingroup
795     {\par}%
796     \def\bbl@selectorname{foreign*}%
797     \let\bbl@select@opts\@empty
798     \let\BabelText\@firstofone
799     \foreign@language{#1}%
800     \bbl@usehooks{foreign*}{}%
801     \bbl@dirparastext
802     \BabelText{#2}% Still in vertical mode!
803     {\par}%
804   \endgroup}

```

\foreign@language This macro does the work for `\foreignlanguage` and the `otherlanguage*` environment. First we need to store the name of the language and check that it is a known language. Then it just calls `bbl@switch`.


```

805 \def\foreign@language#1{%
806   % set name
807   \edef\language#1{%
808     \ifbbl@usedategroup
809       \bbl@add\bbl@select@opts{,date,}%
810       \bbl@usedategroupfalse
811     \fi
812     \bbl@fixname\language
813     % TODO. name@map here?
814     \bbl@provide@locale
815     \bbl@iflanguage\language{%
816       \let\bbl@select@type\@ne
817       \expandafter\bbl@switch\expandafter{\language}}

```

The following macro executes conditionally some code based on the selector being used.

```

818 \def\IfBabelSelectorTF#1{%
819   \bbl@xin@{,\bbl@selectorname,}{,\zap@space#1 \@empty,}%
820   \ifin@
821     \expandafter\@firstoftwo
822   \else
823     \expandafter\@secondoftwo
824   \fi}

```

\bbl@patterns This macro selects the hyphenation patterns by changing the `\language` register. If special hyphenation patterns are available specifically for the current font encoding, use them instead of the default.

It also sets hyphenation exceptions, but only once, because they are global (here language `\lccode's` has been set, too). `\bbl@hyphenation@` is set to relax until the very first `\babelhyphenation`, so do nothing with this value. If the exceptions for a language (by its number, not its name, so that `:ENC` is taken into account) has been set, then use `\hyphenation` with both global and language exceptions and empty the latter to mark they must not be set again.

```

825 \let\bbl@hyphlist\@empty
826 \let\bbl@hyphenation@\relax
827 \let\bbl@pttnlist\@empty
828 \let\bbl@patterns@\relax
829 \let\bbl@hymapsel=\@cclv
830 \def\bbl@patterns#1{%
831   \language=\expandafter\ifx\csname l@#1:\f@encoding\endcsname\relax
832     \csname l@#1\endcsname
833     \edef\bbl@tempa{#1}%
834   \else
835     \csname l@#1:\f@encoding\endcsname
836     \edef\bbl@tempa{#1:\f@encoding}%
837   \fi
838   \@expandtwoargs\bbl@usehooks{patterns}{#1}{\bbl@tempa}}%
839   % > luatex
840   \@ifundefined{bbl@hyphenation@}{% Can be \relax!
841     \begingroup
842       \bbl@xin@{,\number\language,}{,\bbl@hyphlist}%
843       \ifin@
844         \@expandtwoargs\bbl@usehooks{hyphenation}{#1}{\bbl@tempa}}%
845       \hyphenation{%
846         \bbl@hyphenation@
847         \@ifundefined{bbl@hyphenation@#1}%
848         \@empty
849         {\space\csname bbl@hyphenation@#1\endcsname}}%
850       \xdef\bbl@hyphlist{\bbl@hyphlist\number\language,}%
851     \fi
852   \endgroup}

```

hyphenrules (*env.*) The environment `hyphenrules` can be used to select *just* the hyphenation rules. This environment does *not* change `\language` and when the hyphenation rules specified were not loaded it has no

effect. Note however, `\lccode's` and font encodings are not set at all, so in most cases you should use `otherlanguage*`.

```

853 \def\hyphenrules#1{%
854   \edef\bbl@tempf{#1}%
855   \bbl@fixname\bbl@tempf
856   \bbl@iflanguage\bbl@tempf{%
857     \expandafter\bbl@patterns\expandafter{\bbl@tempf}%
858     \ifx\languageshorthands@undefined\else
859       \languageshorthands{none}%
860     \fi
861     \expandafter\ifx\csname\bbl@tempf hyphenmins\endcsname\relax
862       \set@hyphenmins\tw@\thr@\relax
863     \else
864       \expandafter\expandafter\expandafter\set@hyphenmins
865       \csname\bbl@tempf hyphenmins\endcsname\relax
866     \fi}}
867 \let\endhyphenrules\empty

```

`\providehyphenmins` The macro `\providehyphenmins` should be used in the language definition files to provide a *default* setting for the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`. If the macro `\langhyphenmins` is already defined this command has no effect.

```

868 \def\providehyphenmins#1#2{%
869   \expandafter\ifx\csname #1hyphenmins\endcsname\relax
870     \namedef{#1hyphenmins}{#2}%
871   \fi}

```

`\set@hyphenmins` This macro sets the values of `\lefthyphenmin` and `\righthyphenmin`. It expects two values as its argument.

```

872 \def\set@hyphenmins#1#2{%
873   \lefthyphenmin#1\relax
874   \righthyphenmin#2\relax}

```

`\ProvidesLanguage` The identification code for each file is something that was introduced in $\text{\LaTeX 2}_{\epsilon}$. When the command `\ProvidesFile` does not exist, a dummy definition is provided temporarily. For use in the language definition file the command `\ProvidesLanguage` is defined by babel. Depending on the format, ie, on if the former is defined, we use a similar definition or not.

```

875 \ifx\ProvidesFile\@undefined
876   \def\ProvidesLanguage#1[#2 #3 #4]{%
877     \wlog{Language: #1 #4 #3 <#2>}%
878   }
879 \else
880   \def\ProvidesLanguage#1{%
881     \begingroup
882     \catcode`\ 10 %
883     \@makeother\/%
884     \@ifnextchar[%]
885       {\@provideslanguage{#1}}{\@provideslanguage{#1}[]}
886   \def\@provideslanguage#1[#2]{%
887     \wlog{Language: #1 #2}%
888     \expandafter\xdef\csname ver@#1.ldf\endcsname{#2}%
889   \endgroup}
890 \fi

```

`\originalTeX` The macro `\originalTeX` should be known to \TeX at this moment. As it has to be expandable we `\let` it to `\empty` instead of `\relax`.

```

891 \ifx\originalTeX\@undefined\let\originalTeX\empty\fi

```

Because this part of the code can be included in a format, we make sure that the macro which initializes the save mechanism, `\babel@beginsave`, is not considered to be undefined.

```

892 \ifx\babel@beginsave\@undefined\let\babel@beginsave\relax\fi

```

A few macro names are reserved for future releases of babel, which will use the concept of ‘locale’:

```

893 \providecommand\setlocale{%
894   \bbl@error
895   {Not yet available}%
896   {Find an armchair, sit down and wait}}
897 \let\uselocale\setlocale
898 \let\locale\setlocale
899 \let\selectlocale\setlocale
900 \let\textlocale\setlocale
901 \let\textlanguage\setlocale
902 \let\languagetext\setlocale

```

7.2 Errors

`\@nolanerr` The babel package will signal an error when a documents tries to select a language that hasn’t been defined earlier. When a user selects a language for which no hyphenation patterns were loaded into the format he will be given a warning about that fact. We revert to the patterns for `\language=0` in that case. In most formats that will be (US)english, but it might also be empty.

`\@noopterr` When the package was loaded without options not everything will work as expected. An error message is issued in that case.
When the format knows about `\PackageError` it must be \LaTeX 2\epsilon , so we can safely use its error handling interface. Otherwise we’ll have to ‘keep it simple’.
Infos are not written to the console, but on the other hand many people think warnings are errors, so a further message type is defined: an important info which is sent to the console.

```

903 \edef\bbl@nulllanguage{\string\language=0}
904 \def\bbl@nocaption{\protect\bbl@nocaption@i}
905 \def\bbl@nocaption@i#1#2{% 1: text to be printed 2: caption macro \langXname
906   \global\@namedef{#2}{\textbf{?#1?}}%
907   \@nameuse{#2}%
908   \edef\bbl@tempa{#1}%
909   \bbl@sreplace\bbl@tempa{name}{}}%
910   \bbl@warning{%
911     \@backslashchar#1 not set for '\language'. Please,\\%
912     define it after the language has been loaded\\%
913     (typically in the preamble) with:\\%
914     \string\setlocalecaption{\language}{\bbl@tempa}{..}\\%
915     Feel free to contribute on github.com/latex3/babel.\\%
916     Reported}}
917 \def\bbl@tentative{\protect\bbl@tentative@i}
918 \def\bbl@tentative@i#1{%
919   \bbl@warning{%
920     Some functions for '#1' are tentative.\\%
921     They might not work as expected and their behavior\\%
922     could change in the future.\\%
923     Reported}}
924 \def\@nolanerr#1{%
925   \bbl@error
926   {You haven't defined the language '#1' yet.\\%
927     Perhaps you misspelled it or your installation\\%
928     is not complete}%
929   {Your command will be ignored, type <return> to proceed}}
930 \def\@nopatterns#1{%
931   \bbl@warning
932   {No hyphenation patterns were preloaded for\\%
933     the language '#1' into the format.\\%
934     Please, configure your TeX system to add them and\\%
935     rebuild the format. Now I will use the patterns\\%
936     preloaded for \bbl@nulllanguage\space instead}}
937 \let\bbl@usehooks\@gobbles
938 \ifx\bbl@onlyswitch\empty\endinput\fi
939 % Here ended switch.def

```

Here ended the now discarded `switch.def`. Here also (currently) ends the base option.

```

940 \ifx\directlua\@undefined\else
941   \ifx\bbl@luapatterns\@undefined
942     \input luababel.def
943   \fi
944 \fi
945 <Basic macros>
946 \bbl@trace{Compatibility with language.def}
947 \ifx\bbl@languages\@undefined
948   \ifx\directlua\@undefined
949     \openin1 = language.def % TODO. Remove hardcoded number
950     \ifeof1
951       \closein1
952       \message{I couldn't find the file language.def}
953     \else
954       \closein1
955       \begingroup
956         \def\addlanguage#1#2#3#4#5{%
957           \expandafter\ifx\csname lang@#1\endcsname\relax\else
958             \global\expandafter\let\csname l@#1\endcsname
959             \csname lang@#1\endcsname
960           \fi}%
961         \def\uselanguage#1{%
962           \input language.def
963         \endgroup
964       \fi
965     \fi
966     \chardef\l@english\z@
967 \fi

```

`\addto` It takes two arguments, a *<control sequence>* and \TeX -code to be added to the *<control sequence>*. If the *<control sequence>* has not been defined before it is defined now. The control sequence could also expand to `\relax`, in which case a circular definition results. The net result is a stack overflow. Note there is an inconsistency, because the assignment in the last branch is global.

```

968 \def\addto#1#2{%
969   \ifx#1\@undefined
970     \def#1{#2}%
971   \else
972     \ifx#1\relax
973       \def#1{#2}%
974     \else
975       {\toks@\expandafter{#1#2}%
976        \xdef#1{\the\toks@}}%
977     \fi
978   \fi}

```

The macro `\initiate@active@char` below takes all the necessary actions to make its argument a shorthand character. The real work is performed once for each character. But first we define a little tool.

```

979 \def\bbl@withactive#1#2{%
980   \begingroup
981   \lccode`~=#2\relax
982   \lowercase{\endgroup#1~}}

```

`\bbl@redefine` To redefine a command, we save the old meaning of the macro. Then we redefine it to call the original macro with the ‘sanitized’ argument. The reason why we do it this way is that we don’t want to redefine the \TeX macros completely in case their definitions change (they have changed in the past). A macro named `\macro` will be saved new control sequences named `\org@macro`.

```

983 \def\bbl@redefine#1{%
984   \edef\bbl@tempa{\bbl@stripslash#1}%
985   \expandafter\let\csname org@\bbl@tempa\endcsname#1%
986   \expandafter\def\csname\bbl@tempa\endcsname{
987     \@onlypreamble\bbl@redefine

```

`\bbl@redefine@long` This version of `\babel@redefine` can be used to redefine `\long` commands such as `\ifthenelse`.

```

988 \def\bbl@redefine@long#1{%
989   \edef\bbl@tempa{\bbl@stripslash#1}%
990   \expandafter\let\csname org@\bbl@tempa\endcsname#1%
991   \long\expandafter\def\csname\bbl@tempa\endcsname}
992 \@onlypreamble\bbl@redefine@long

```

`\bbl@redefineroobust` For commands that are redefined, but which *might* be robust we need a slightly more intelligent macro. A robust command `foo` is defined to expand to `\protect\foo_`. So it is necessary to check whether `\foo_` exists. The result is that the command that is being redefined is always robust afterwards. Therefore all we need to do now is define `\foo_`.

```

993 \def\bbl@redefineroobust#1{%
994   \edef\bbl@tempa{\bbl@stripslash#1}%
995   \bbl@ifunset{\bbl@tempa\space}%
996     {\expandafter\let\csname org@\bbl@tempa\endcsname#1%
997       \bbl@exp{\def\#1{\protect\<\bbl@tempa\space>}}}%
998     {\bbl@exp{\let\<org@\bbl@tempa>\<\bbl@tempa\space>}}}%
999   \@namedef{\bbl@tempa\space}}
1000 \@onlypreamble\bbl@redefineroobust

```

7.3 Hooks

Admittedly, the current implementation is a somewhat simplistic and does very little to catch errors, but it is meant for developers, after all. `\bbl@usehooks` is the commands used by `babel` to execute hooks defined for an event.

```

1001 \bbl@trace{Hooks}
1002 \newcommand\AddBabelHook[3][]{%
1003   \bbl@ifunset{\bbl@hk@#2}{\EnableBabelHook{#2}}}%
1004   \def\bbl@tempa##1,##2,##3\@empty{\def\bbl@tempb{##2}}%
1005   \expandafter\bbl@tempa\bbl@evargs,##3,\@empty
1006   \bbl@ifunset{\bbl@ev@#2@#3@#1}%
1007     {\bbl@csarg\bbl@add{ev@#3@#1}{\bbl@elth{#2}}}%
1008     {\bbl@csarg\let{ev@#2@#3@#1}\relax}%
1009   \bbl@csarg\newcommand{ev@#2@#3@#1}[\bbl@tempb]}
1010 \newcommand\EnableBabelHook[1]{\bbl@csarg\let{hk@#1}\@firstofone}
1011 \newcommand\DisableBabelHook[1]{\bbl@csarg\let{hk@#1}\@gobble}
1012 \def\bbl@usehooks{\bbl@usehooks@lang\language}
1013 \def\bbl@usehooks@lang#1#2#3{%
1014   \ifx\UseHook\undefined\else\UseHook{babel/*/#2}\fi
1015   \def\bbl@elth#1{%
1016     \bbl@cs{hk@#1}{\bbl@cs{ev@#1@#2@#3}}%
1017     \bbl@cs{ev@#2@#3}}
1018   \ifx\language\undefined\else % Test required for Plain (?)
1019     \ifx\UseHook\undefined\else\UseHook{babel/#1/#2}\fi
1020     \def\bbl@elth#1{%
1021       \bbl@cs{hk@#1}{\bbl@cs{ev@#1@#2@#1@#3}}%
1022       \bbl@cs{ev@#2@#1}}
1023   \fi}

```

To ensure forward compatibility, arguments in hooks are set implicitly. So, if a further argument is added in the future, there is no need to change the existing code. Note events intended for `hyphen.cfg` are also loaded (just in case you need them for some reason).

```

1024 \def\bbl@evargs{,% <- don't delete this comma
1025   everylanguage=1,loadkernel=1,loadpatterns=1,loadexceptions=1,%
1026   adddialect=2,patterns=2,defaultcommands=0,encodedcommands=2,write=0,%
1027   beforeextras=0,afterextras=0,stopcommands=0,stringprocess=0,%
1028   hyphenation=2,initiateactive=3,afterreset=0,foreign=0,foreign*=0,%
1029   beforestart=0,language=2,begindocument=1}
1030 \ifx\NewHook\undefined\else
1031   \def\bbl@tempa#1=#2\@{\NewHook{babel/#1}}
1032   \bbl@foreach\bbl@evargs{\bbl@tempa#1\@}
1033 \fi

```

`\babelensure` The user command just parses the optional argument and creates a new macro named `\bbl@e@<language>`. We register a hook at the `afterextras` event which just executes this macro in a “complete” selection (which, if undefined, is `\relax` and does nothing). This part is somewhat involved because we have to make sure things are expanded the correct number of times. The macro `\bbl@e@<language>` contains `\bbl@ensure{<include>}{<exclude>}{<fontenc>}`, which in turn loops over the macros names in `\bbl@captionslist`, excluding (with the help of `\in@`) those in the `exclude` list. If the `fontenc` is given (and not `\relax`), the `\fontencoding` is also added. Then we loop over the `include` list, but if the macro already contains `\foreignlanguage`, nothing is done. Note this macro (1) is not restricted to the preamble, and (2) changes are local.

```

1034 \bbl@trace{Defining babelensure}
1035 \newcommand\babelensure[2][{}]{%
1036   \AddBabelHook{babel-ensure}{afterextras}{%
1037     \ifcase\bbl@select@type
1038       \bbl@c{l}{e}%
1039     \fi}%
1040   \begingroup
1041     \let\bbl@ens@include\@empty
1042     \let\bbl@ens@exclude\@empty
1043     \def\bbl@ens@fontenc{\relax}%
1044     \def\bbl@tempb##1{%
1045       \ifx\@empty##1\else\noexpand##1\expandafter\bbl@tempb\fi}%
1046     \edef\bbl@tempa{\bbl@tempb#1\@empty}%
1047     \def\bbl@tempb##1=##2\@{\@namedef\bbl@ens@##1}{##2}}%
1048     \bbl@foreach\bbl@tempa{\bbl@tempb##1\@}%
1049     \def\bbl@tempc{\bbl@ensure}%
1050     \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
1051       \expandafter{\bbl@ens@include}}%
1052     \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
1053       \expandafter{\bbl@ens@exclude}}%
1054     \toks@\expandafter{\bbl@tempc}%
1055     \bbl@exp{%
1056   \endgroup
1057   \def\<bbl@e@#2>{\the\toks@{\bbl@ens@fontenc}}}%
1058   \def\bbl@ensure#1#2#3{% 1: include 2: exclude 3: fontenc
1059     \def\bbl@tempb##1{% elt for (excluding) \bbl@captionslist list
1060       \ifx##1\undefined % 3.32 - Don't assume the macro exists
1061         \edef##1{\noexpand\bbl@nocaption
1062           {\bbl@stripslash##1}{\language\name\bbl@stripslash##1}}%
1063       \fi
1064       \ifx##1\@empty\else
1065         \in@{##1}{#2}%
1066         \ifin@ \else
1067           \bbl@ifunset{\bbl@ensure@\language\name}%
1068             {\bbl@exp{%
1069               \\DeclareRobustCommand\<bbl@ensure@\language\name>[1]{%
1070                 \\foreignlanguage{\language\name}%
1071                 {\ifx\relax#3\else
1072                   \\fontencoding{#3}\\selectfont
1073                 \fi
1074                 #####1}}}%
1075             }%
1076           \toks@\expandafter{##1}%
1077           \edef##1{%
1078             \bbl@csarg\noexpand{ensure@\language\name}%
1079             {\the\toks@}}%
1080           \fi
1081           \expandafter\bbl@tempb
1082         \fi}%
1083     \expandafter\bbl@tempb\bbl@captionslist\today\@empty
1084     \def\bbl@tempa##1{% elt for include list
1085       \ifx##1\@empty\else
1086         \bbl@csarg\in@{ensure@\language\name}\expandafter}\expandafter{##1}%
1087       \ifin@ \else

```

```

1088      \bbl@tempb##1\@empty
1089      \fi
1090      \expandafter\bbl@tempa
1091      \fi}%
1092      \bbl@tempa#1\@empty}
1093 \def\bbl@captionslist{%
1094   \prefacename\refname\abstractname\bibname\chaptername\appendixname
1095   \contentsname\listfigurename\listtablename\indexname\figurename
1096   \tablename\partname\enclname\ccname\headtoname\pagename\seename
1097   \alsoname\proofname\glossaryname}

```

7.4 Setting up language files

`\LdfInit` `\LdfInit` macro takes two arguments. The first argument is the name of the language that will be defined in the language definition file; the second argument is either a control sequence or a string from which a control sequence should be constructed. The existence of the control sequence indicates that the file has been processed before.

At the start of processing a language definition file we always check the category code of the at-sign. We make sure that it is a ‘letter’ during the processing of the file. We also save its name as the last called option, even if not loaded.

Another character that needs to have the correct category code during processing of language definition files is the equals sign, ‘=’, because it is sometimes used in constructions with the `\let` primitive. Therefore we store its current catcode and restore it later on.

Now we check whether we should perhaps stop the processing of this file. To do this we first need to check whether the second argument that is passed to `\LdfInit` is a control sequence. We do that by looking at the first token after passing #2 through string. When it is equal to `@backslashchar` we are dealing with a control sequence which we can compare with `\undefined`.

If so, we call `\ldf@quit` to set the main language, restore the category code of the @-sign and call `\endinput`

When #2 was *not* a control sequence we construct one and compare it with `\relax`.

Finally we check `\originalTeX`.

```

1098 \bbl@trace{Macros for setting language files up}
1099 \def\bbl@ldfinit{%
1100   \let\bbl@screset\@empty
1101   \let\BabelStrings\bbl@opt@string
1102   \let\BabelOptions\@empty
1103   \let\BabelLanguages\relax
1104   \ifx\originalTeX\@undefined
1105     \let\originalTeX\@empty
1106   \else
1107     \originalTeX
1108   \fi}
1109 \def\LdfInit#1#2{%
1110   \chardef\atcatcode=\catcode`\@
1111   \catcode`\@=11\relax
1112   \chardef\eqcatcode=\catcode`\=
1113   \catcode`\==12\relax
1114   \expandafter\if\expandafter\@backslashchar
1115     \expandafter\@car\string#2\@nil
1116   \ifx#2\@undefined\else
1117     \ldf@quit{#1}%
1118   \fi
1119   \else
1120     \expandafter\ifx\csname#2\endcsname\relax\else
1121       \ldf@quit{#1}%
1122     \fi
1123   \fi
1124   \bbl@ldfinit}

```

`\ldf@quit` This macro interrupts the processing of a language definition file.

```

1125 \def\ldf@quit#1{%
1126   \expandafter\main@language\expandafter{#1}%

```

```

1127 \catcode`\@=\atcatcode \let\atcatcode\relax
1128 \catcode`\==\eqcatcode \let\eqcatcode\relax
1129 \endinput}

```

`\ldf@finish` This macro takes one argument. It is the name of the language that was defined in the language definition file.

We load the local configuration file if one is present, we set the main language (taking into account that the argument might be a control sequence that needs to be expanded) and reset the category code of the @-sign.

```

1130 \def\bbl@afterldf#1{% TODO. Merge into the next macro? Unused elsewhere
1131 \bbl@afterlang
1132 \let\bbl@afterlang\relax
1133 \let\BabelModifiers\relax
1134 \let\bbl@screset\relax}%
1135 \def\ldf@finish#1{%
1136 \loadlocalcfg{#1}%
1137 \bbl@afterldf{#1}%
1138 \expandafter\main@language\expandafter{#1}%
1139 \catcode`\@=\atcatcode \let\atcatcode\relax
1140 \catcode`\==\eqcatcode \let\eqcatcode\relax}

```

After the preamble of the document the commands `\LdfInit`, `\ldf@quit` and `\ldf@finish` are no longer needed. Therefore they are turned into warning messages in `LTEX`.

```

1141 \@onlypreamble\LdfInit
1142 \@onlypreamble\ldf@quit
1143 \@onlypreamble\ldf@finish

```

`\main@language` This command should be used in the various language definition files. It stores its argument in `\bbl@main@language` to be used to switch to the correct language at the beginning of the document.

```

1144 \def\main@language#1{%
1145 \def\bbl@main@language{#1}%
1146 \let\language\bbl@main@language % TODO. Set localename
1147 \bbl@id@assign
1148 \bbl@patterns{\language}%

```

We also have to make sure that some code gets executed at the beginning of the document, either when the aux file is read or, if it does not exist, when the `\AtBeginDocument` is executed. Languages do not set `\pagedir`, so we set here for the whole document to the main `\bodydir`.

```

1149 \def\bbl@beforestart{%
1150 \def\@nolanerr##1{%
1151 \bbl@warning{Undefined language '##1' in aux.\\Reported}}%
1152 \bbl@usehooks{beforestart}{}%
1153 \global\let\bbl@beforestart\relax}
1154 \AtBeginDocument{%
1155 {\@nameuse{bbl@beforestart}}% Group!
1156 \if@filesw
1157 \providecommand\babel@aux[2]{}%
1158 \immediate\write\@mainaux{%
1159 \string\providecommand\string\babel@aux[2]{}%
1160 \immediate\write\@mainaux{\string\@nameuse{bbl@beforestart}}%
1161 \fi
1162 \expandafter\selectlanguage\expandafter{\bbl@main@language}%
1163 \ifbbl@single % must go after the line above.
1164 \renewcommand\selectlanguage[1]{}%
1165 \renewcommand\foreignlanguage[2]{#2}%
1166 \global\let\babel@aux\@gobbles % Also as flag
1167 \fi}
1168 \ifcase\bbl@engine\or
1169 \AtBeginDocument{\pagedir\bodydir} % TODO - a better place
1170 \fi

```

A bit of optimization. Select in heads/foots the language only if necessary.


```

1171 \def\select@language@x#1{%
1172   \ifcase\bb1@select@type
1173     \bb1@ifsamestring\language@name{#1}{\select@language{#1}}%
1174   \else
1175     \select@language{#1}%
1176   \fi}

```

7.5 Shorthands

`\bb1@add@special` The macro `\bb1@add@special` is used to add a new character (or single character control sequence) to the macro `\dospecials` (and `\@sanitize` if \LaTeX is used). It is used only at one place, namely when `\initiate@active@char` is called (which is ignored if the char has been made active before). Because `\@sanitize` can be undefined, we put the definition inside a conditional. Items are added to the lists without checking its existence or the original catcode. It does not hurt, but should be fixed. It's already done with `\nfss@catcodes`, added in 3.10.

```

1177 \bb1@trace{Shorthands}
1178 \def\bb1@add@special#1{% 1:a macro like \", \?, etc.
1179   \bb1@add\dospecials{\do#1}% test \@sanitize = \relax, for back. compat.
1180   \bb1@ifunset{\@sanitize}{\bb1@add\@sanitize{\@makeother#1}}%
1181   \ifx\nfss@catcodes\@undefined\else % TODO - same for above
1182     \begingroup
1183       \catcode`#1\active
1184       \nfss@catcodes
1185       \ifnum\catcode`#1=\active
1186         \endgroup
1187         \bb1@add\nfss@catcodes{\@makeother#1}%
1188       \else
1189         \endgroup
1190       \fi
1191   \fi}

```

`\bb1@remove@special` The companion of the former macro is `\bb1@remove@special`. It removes a character from the set macros `\dospecials` and `\@sanitize`, but it is not used at all in the babel core.

```

1192 \def\bb1@remove@special#1{%
1193   \begingroup
1194     \def\x##1##2{\ifnum`#1=##2\noexpand\@empty
1195       \else\noexpand##1\noexpand##2\fi}%
1196     \def\do{\x\do}%
1197     \def\@makeother{\x\@makeother}%
1198   \edef\x{\endgroup
1199     \def\noexpand\dospecials{\dospecials}%
1200     \expandafter\ifx\csname \@sanitize\endcsname\relax\else
1201       \def\noexpand\@sanitize{\@sanitize}%
1202     \fi}%
1203   \x}

```

`\initiate@active@char` A language definition file can call this macro to make a character active. This macro takes one argument, the character that is to be made active. When the character was already active this macro does nothing. Otherwise, this macro defines the control sequence `\normal@char⟨char⟩` to expand to the character in its ‘normal state’ and it defines the active character to expand to `\normal@char⟨char⟩` by default (`⟨char⟩` being the character to be made active). Later its definition can be changed to expand to `\active@char⟨char⟩` by calling `\bb1@activate{⟨char⟩}`. For example, to make the double quote character active one could have `\initiate@active@char{"}` in a language definition file. This defines " as `\active@prefix "active@char` (where the first " is the character with its original catcode, when the shorthand is created, and `\active@char` is a single token). In protected contexts, it expands to `\protect " or \noexpand "` (ie, with the original "); otherwise `\active@char` is executed. This macro in turn expands to `\normal@char` in “safe” contexts (eg, `\label`), but `\user@active` in normal “unsafe” ones. The latter search a definition in the user, language and system levels, in this order, but if none is found, `\normal@char` is used. However, a deactivated shorthand (with `\bb1@deactivate` is defined as `\active@prefix "\normal@char`.

The following macro is used to define shorthands in the three levels. It takes 4 arguments: the (string'ed) character, \<level>@group, <level>@active and <next-level>@active (except in system).

```

1204 \def\bbl@active@def#1#2#3#4{%
1205   \@namedef{#3#1}{%
1206     \expandafter\ifx\csname#2@sh@#1\endcsname\relax
1207       \bbl@afterelse\bbl@sh@select#2#1{#3@arg#1}{#4#1}%
1208     \else
1209       \bbl@afterfi\csname#2@sh@#1\endcsname
1210     \fi}%

```

When there is also no current-level shorthand with an argument we will check whether there is a next-level defined shorthand for this active character.

```

1211   \long\@namedef{#3@arg#1}##1{%
1212     \expandafter\ifx\csname#2@sh@#1\string##1\endcsname\relax
1213       \bbl@afterelse\csname#4#1\endcsname##1%
1214     \else
1215       \bbl@afterfi\csname#2@sh@#1\string##1\endcsname
1216     \fi}}%

```

\initiate@active@char calls \@initiate@active@char with 3 arguments. All of them are the same character with different catcodes: active, other (\string'ed) and the original one. This trick simplifies the code a lot.

```

1217 \def\initiate@active@char#1{%
1218   \bbl@ifunset{active@char\string#1}%
1219   {\bbl@withactive
1220     {\expandafter\@initiate@active@char\expandafter}#1\string#1#1}%
1221   {}}

```

The very first thing to do is saving the original catcode and the original definition, even if not active, which is possible (undefined characters require a special treatment to avoid making them \relax and preserving some degree of protection).

```

1222 \def\@initiate@active@char#1#2#3{%
1223   \bbl@csarg\edef{oricat@#2}{\catcode`#2=\the\catcode`#2\relax}%
1224   \ifx#1\undefined
1225     \bbl@csarg\def{oridef@#2}{\def#1{\active@prefix#1\undefined}}%
1226   \else
1227     \bbl@csarg\let{oridef@#2}#1%
1228     \bbl@csarg\edef{oridef@#2}{%
1229       \let\noexpand#1%
1230       \expandafter\noexpand\csname bbl@oridef@#2\endcsname}%
1231   \fi

```

If the character is already active we provide the default expansion under this shorthand mechanism. Otherwise we write a message in the transcript file, and define \normal@char<char> to expand to the character in its default state. If the character is mathematically active when babel is loaded (for example ') the normal expansion is somewhat different to avoid an infinite loop (but it does not prevent the loop if the mathcode is set to "8000 *a posteriori*).

```

1232   \ifx#1#3\relax
1233     \expandafter\let\csname normal@char#2\endcsname#3%
1234   \else
1235     \bbl@info{Making #2 an active character}%
1236     \ifnum\mathcode`#2=\ifodd\bbl@engine"1000000 \else"8000 \fi
1237     \@namedef{normal@char#2}{%
1238       \textormath{#3}{\csname bbl@oridef@#2\endcsname}}%
1239   \else
1240     \@namedef{normal@char#2}{#3}%
1241   \fi

```

To prevent problems with the loading of other packages after babel we reset the catcode of the character to the original one at the end of the package and of each language file (except with KeepShorthandsActive). It is re-activate again at \begin{document}. We also need to make sure that the shorthands are active during the processing of the .aux file. Otherwise some citations may give

unexpected results in the printout when a shorthand was used in the optional argument of `\bibitem` for example. Then we make it active (not strictly necessary, but done for backward compatibility).

```

1242 \bbl@restoreactive{#2}%
1243 \AtBeginDocument{%
1244   \catcode`#2\active
1245   \if@filesw
1246     \immediate\write\@mainaux{\catcode`\string#2\active}%
1247   \fi}%
1248 \expandafter\bbl@add@special\csname#2\endcsname
1249 \catcode`#2\active
1250 \fi

```

Now we have set `\normal@char⟨char⟩`, we must define `\active@char⟨char⟩`, to be executed when the character is activated. We define the first level expansion of `\active@char⟨char⟩` to check the status of the `@safe@actives` flag. If it is set to true we expand to the ‘normal’ version of this character; otherwise we call `\user@active⟨char⟩` to start the search of a definition in the user, language and system levels (or eventually `normal@char⟨char⟩`).

```

1251 \let\bbl@tempa\@firstoftwo
1252 \if\string^#2%
1253   \def\bbl@tempa{\noexpand\textormath}%
1254 \else
1255   \ifx\bbl@mathnormal\@undefined\else
1256     \let\bbl@tempa\bbl@mathnormal
1257   \fi
1258 \fi
1259 \expandafter\edef\csname active@char#2\endcsname{%
1260   \bbl@tempa
1261   {\noexpand\if@safe@actives
1262     \noexpand\expandafter
1263     \expandafter\noexpand\csname normal@char#2\endcsname
1264     \noexpand\else
1265       \noexpand\expandafter
1266       \expandafter\noexpand\csname bbl@doactive#2\endcsname
1267       \noexpand\fi}%
1268   {\expandafter\noexpand\csname normal@char#2\endcsname}}%
1269 \bbl@csarg\edef{doactive#2}{%
1270   \expandafter\noexpand\csname user@active#2\endcsname}%

```

We now define the default values which the shorthand is set to when activated or deactivated. It is set to the deactivated form (globally), so that the character expands to

`\active@prefix⟨char⟩\normal@char⟨char⟩`

(where `\active@char⟨char⟩` is *one* control sequence!).

```

1271 \bbl@csarg\edef{active@#2}{%
1272   \noexpand\active@prefix\noexpand#1%
1273   \expandafter\noexpand\csname active@char#2\endcsname}%
1274 \bbl@csarg\edef{normal@#2}{%
1275   \noexpand\active@prefix\noexpand#1%
1276   \expandafter\noexpand\csname normal@char#2\endcsname}%
1277 \bbl@ncarg\let#1\bbl@normal@#2}%

```

The next level of the code checks whether a user has defined a shorthand for himself with this character. First we check for a single character shorthand. If that doesn’t exist we check for a shorthand with an argument.

```

1278 \bbl@active@def#2\user@group{user@active}{language@active}%
1279 \bbl@active@def#2\language@group{language@active}{system@active}%
1280 \bbl@active@def#2\system@group{system@active}{normal@char}%

```

In order to do the right thing when a shorthand with an argument is used by itself at the end of the line we provide a definition for the case of an empty argument. For that case we let the shorthand character expand to its non-active self. Also, When a shorthand combination such as ‘ ’ ends up in a heading TeX would see `\protect'\protect'`. To prevent this from happening a couple of shorthand needs to be defined at user level.

```

1281 \expandafter\edef\csname\user@group @sh@#2@@\endcsname
1282 {\expandafter\noexpand\csname normal@char#2\endcsname}%
1283 \expandafter\edef\csname\user@group @sh@#2@\string\protect@\endcsname
1284 {\expandafter\noexpand\csname user@active#2\endcsname}%

```

Finally, a couple of special cases are taken care of. (1) If we are making the right quote (') active we need to change \pr@m@s as well. Also, make sure that a single ' in math mode 'does the right thing'. (2) If we are using the caret (^) as a shorthand character special care should be taken to make sure math still works. Therefore an extra level of expansion is introduced with a check for math mode on the upper level.

```

1285 \if\string'#2%
1286 \let\prim@s\bb1@prim@s
1287 \let\active@math@prime#1%
1288 \fi
1289 \bb1@usehooks{initiateactive}{{#1}{#2}{#3}}

```

The following package options control the behavior of shorthands in math mode.

```

1290 <<{*More package options}> \equiv
1291 \DeclareOption{math=active}{}
1292 \DeclareOption{math=normal}{{\def\bb1@mathnormal{\noexpand\textormath}}}
1293 <</More package options>>

```

Initiating a shorthand makes active the char. That is not strictly necessary but it is still done for backward compatibility. So we need to restore the original catcode at the end of package *and* and the end of the ldf.

```

1294 \@ifpackagewith{babel}{KeepShorthandsActive}%
1295 {\let\bb1@restoreactive\@gobble}%
1296 {\def\bb1@restoreactive#1{%
1297 \bb1@exp{%
1298 \\\AfterBabelLanguage\\CurrentOption
1299 {\catcode`#1=\the\catcode`#1\relax}%
1300 \\\AtEndOfPackage
1301 {\catcode`#1=\the\catcode`#1\relax}}}%
1302 \AtEndOfPackage{\let\bb1@restoreactive\@gobble}}

```

\bb1@sh@select This command helps the shorthand supporting macros to select how to proceed. Note that this macro needs to be expandable as do all the shorthand macros in order for them to work in expansion-only environments such as the argument of \hyphenation.

This macro expects the name of a group of shorthands in its first argument and a shorthand character in its second argument. It will expand to either \bb1@firstcs or \bb1@scndcs. Hence two more arguments need to follow it.

```

1303 \def\bb1@sh@select#1#2{%
1304 \expandafter\ifx\csname#1@sh@#2@sel\endcsname\relax
1305 \bb1@afterelse\bb1@scndcs
1306 \else
1307 \bb1@afterfi\csname#1@sh@#2@sel\endcsname
1308 \fi}

```

\active@prefix The command \active@prefix which is used in the expansion of active characters has a function similar to \OT1-cmd in that it \protects the active character whenever \protect is *not* \@typeset@protect. The \@gobble is needed to remove a token such as \activechar: (when the double colon was the active character to be dealt with). There are two definitions, depending of \ifincsname is available. If there is, the expansion will be more robust.

```

1309 \begingroup
1310 \bb1@ifunset{ifincsname}% TODO. Ugly. Correct? Only Plain?
1311 {\gdef\active@prefix#1{%
1312 \ifx\protect\@typeset@protect
1313 \else
1314 \ifx\protect\@unexpandable@protect
1315 \noexpand#1%
1316 \else
1317 \protect#1%
1318 \fi

```

```

1319     \expandafter\@gobble
1320     \fi}}
1321 {\gdef\active@prefix#1{%
1322     \ifincsname
1323     \string#1%
1324     \expandafter\@gobble
1325     \else
1326     \ifx\protect\@typeset@protect
1327     \else
1328     \ifx\protect\@unexpandable@protect
1329     \noexpand#1%
1330     \else
1331     \protect#1%
1332     \fi
1333     \expandafter\expandafter\expandafter\@gobble
1334     \fi
1335     \fi}}
1336 \endgroup

```

`\if@safe@actives` In some circumstances it is necessary to be able to reset the shorthand to its ‘normal’ value (usually the character with catcode ‘other’) on the fly. For this purpose the switch `@safe@actives` is available. The setting of this switch should be checked in the first level expansion of `\active@char⟨char⟩`. When this expansion mode is active (with `\@safe@activetrue`), something like `"13"13` becomes `"12"12` in an `\edef` (in other words, shorthands are `\string`’ed). This contrasts with `\protected@edef`, where catcodes are always left unchanged. Once converted, they can be used safely even after this expansion mode is deactivated (with `\@safe@activefalse`).

```

1337 \newif\if@safe@actives
1338 \@safe@activesfalse

```

`\bbl@restore@actives` When the output routine kicks in while the active characters were made “safe” this must be undone in the headers to prevent unexpected typeset results. For this situation we define a command to make them “unsafe” again.

```

1339 \def\bbl@restore@actives{\if@safe@actives\@safe@activesfalse\fi}

```

`\bbl@activate` Both macros take one argument, like `\initiate@active@char`. The macro is used to change the definition of an active character to expand to `\active@char⟨char⟩` in the case of `\bbl@activate`, or `\normal@char⟨char⟩` in the case of `\bbl@deactivate`.

```

1340 \chardef\bbl@activated\z@
1341 \def\bbl@activate#1{%
1342     \chardef\bbl@activated\@ne
1343     \bbl@withactive{\expandafter\let\expandafter}#1%
1344     \csname bbl@active@\string#1\endcsname}
1345 \def\bbl@deactivate#1{%
1346     \chardef\bbl@activated\tw@
1347     \bbl@withactive{\expandafter\let\expandafter}#1%
1348     \csname bbl@normal@\string#1\endcsname}

```

`\bbl@firstcs` These macros are used only as a trick when declaring shorthands.

```

\bbl@scndcs
1349 \def\bbl@firstcs#1#2{\csname#1\endcsname}
1350 \def\bbl@scndcs#1#2{\csname#2\endcsname}

```

`\declare@shorthand` The command `\declare@shorthand` is used to declare a shorthand on a certain level. It takes three arguments:

1. a name for the collection of shorthands, i.e. ‘system’, or ‘dutch’;
2. the character (sequence) that makes up the shorthand, i.e. `~` or `"a`;
3. the code to be executed when the shorthand is encountered.

The auxiliary macro `\babel@texpdf` improves the interoperativity with `hyperref` and takes 4 arguments: (1) The \TeX code in text mode, (2) the string for `hyperref`, (3) the \TeX code in math mode, and (4), which is currently ignored, but it’s meant for a string in math mode, like a minus sign instead of an hyphen (currently `hyperref` doesn’t discriminate the mode). This macro may be used in `ldf` files.

```

1351 \def\babel@texpdf#1#2#3#4{%
1352   \ifx\texorpdfstring\undefined
1353     \textormath{#1}{#3}%
1354   \else
1355     \texorpdfstring{\textormath{#1}{#3}}{#2}%
1356   % \texorpdfstring{\textormath{#1}{#3}}{\textormath{#2}{#4}}%
1357   \fi}
1358 %
1359 \def\declare@shorthand#1#2{\@decl@short{#1}#2\@nil}
1360 \def\@decl@short#1#2#3\@nil#4{%
1361   \def\bbl@tempa{#3}%
1362   \ifx\bbl@tempa\empty
1363     \expandafter\let\csname #1sh@\string#2@sel\endcsname\bbl@scndcs
1364     \bbl@ifunset{#1sh@\string#2@}{}%
1365     {\def\bbl@tempa{#4}%
1366      \expandafter\ifx\csname#1sh@\string#2@\endcsname\bbl@tempa
1367      \else
1368        \bbl@info
1369        {Redefining #1 shorthand \string#2\\%
1370         in language \CurrentOption}%
1371      \fi}%
1372     \@namedef{#1sh@\string#2@}{#4}%
1373   \else
1374     \expandafter\let\csname #1sh@\string#2@sel\endcsname\bbl@firstcs
1375     \bbl@ifunset{#1sh@\string#2@\string#3@}{}%
1376     {\def\bbl@tempa{#4}%
1377      \expandafter\ifx\csname#1sh@\string#2@\string#3@\endcsname\bbl@tempa
1378      \else
1379        \bbl@info
1380        {Redefining #1 shorthand \string#2\string#3\\%
1381         in language \CurrentOption}%
1382      \fi}%
1383     \@namedef{#1sh@\string#2@\string#3@}{#4}%
1384   \fi}

```

`\textormath` Some of the shorthands that will be declared by the language definition files have to be usable in both text and mathmode. To achieve this the helper macro `\textormath` is provided.

```

1385 \def\textormath{%
1386   \ifmmode
1387     \expandafter\@secondoftwo
1388   \else
1389     \expandafter\@firstoftwo
1390   \fi}

```

`\user@group` The current concept of ‘shorthands’ supports three levels or groups of shorthands. For each level the `\language@group` name of the level or group is stored in a macro. The default is to have a user group; use language `\system@group` group ‘english’ and have a system group called ‘system’.

```

1391 \def\user@group{user}
1392 \def\language@group{english} % TODO. I don't like defaults
1393 \def\system@group{system}

```

`\usesshorthands` This is the user level macro. It initializes and activates the character for use as a shorthand character (ie, it’s active in the preamble). Languages can deactivate shorthands, so a starred version is also provided which activates them always after the language has been switched.

```

1394 \def\usesshorthands{%
1395   \@ifstar\bbl@uses@s{\bbl@uses@x{}}
1396   \def\bbl@uses@s#1{%
1397     \bbl@uses@x
1398     {\AddBabelHook{babel-sh-\string#1}{afterextras}}{\bbl@activate{#1}}}%
1399   {#1}}
1400 \def\bbl@uses@x#1#2{%
1401   \bbl@ifshorthand{#2}%
1402   {\def\user@group{user}%

```

```

1403 \initiate@active@char{#2}%
1404 #1%
1405 \bbl@activate{#2}}%
1406 {\bbl@error
1407 {I can't declare a shorthand turned off (\string#2)}
1408 {Sorry, but you can't use shorthands which have been\\%
1409 turned off in the package options}}}

```

`\defineshorthand` Currently we only support two groups of user level shorthands, named internally `user` and `user@<lang>` (language-dependent user shorthands). By default, only the first one is taken into account, but if the former is also used (in the optional argument of `\defineshorthand`) a new level is inserted for it (`user@generic`, done by `\bbl@set@user@generic`); we make also sure `{}` and `\protect` are taken into account in this new top level.

```

1410 \def\user@language@group{user@\language@group}
1411 \def\bbl@set@user@generic#1#2{%
1412 \bbl@ifunset{user@generic@active#1}%
1413 {\bbl@active@def#1\user@language@group{user@active}{user@generic@active}%
1414 \bbl@active@def#1\user@group{user@generic@active}{language@active}%
1415 \expandafter\edef\csname#2@sh@#1@\endcsname{%
1416 \expandafter\noexpand\csname normal@char#1\endcsname}%
1417 \expandafter\edef\csname#2@sh@#1@\string\protect\endcsname{%
1418 \expandafter\noexpand\csname user@active#1\endcsname}}%
1419 \@empty}
1420 \newcommand\defineshorthand[3][user]{%
1421 \edef\bbl@tempa{\zap@space#1 \@empty}%
1422 \bbl@for\bbl@tempb\bbl@tempa{%
1423 \if*\expandafter\@car\bbl@tempb\@nil
1424 \edef\bbl@tempb{user@\expandafter\@gobble\bbl@tempb}%
1425 \@expandtwoargs
1426 \bbl@set@user@generic{\expandafter\string\@car#2\@nil}\bbl@tempb
1427 \fi
1428 \declare@shorthand{\bbl@tempb}{#2}{#3}}}

```

`\languageshorthands` A user level command to change the language from which shorthands are used. Unfortunately, `babel` currently does not keep track of defined groups, and therefore there is no way to catch a possible change in casing to fix it in the same way languages names are fixed. [TODO].

```

1429 \def\languageshorthands#1{\def\language@group{#1}}

```

`\aliasshorthand` First the new shorthand needs to be initialized. Then, we define the new shorthand in terms of the original one, but note with `\aliasshorthands{"}{/}` is `\active@prefix / \active@char /`, so we still need to let the latest to `\active@char`.

```

1430 \def\aliasshorthand#1#2{%
1431 \bbl@ifshorthand{#2}%
1432 {\expandafter\ifx\csname active@char\string#2\endcsname\relax
1433 \ifx\document\@notprerr
1434 \@notshorthand{#2}%
1435 \else
1436 \initiate@active@char{#2}%
1437 \bbl@ccarg\let{active@char\string#2}{active@char\string#1}%
1438 \bbl@ccarg\let{normal@char\string#2}{normal@char\string#1}%
1439 \bbl@activate{#2}%
1440 \fi
1441 \fi}%
1442 {\bbl@error
1443 {Cannot declare a shorthand turned off (\string#2)}
1444 {Sorry, but you cannot use shorthands which have been\\%
1445 turned off in the package options}}}

```

`\@notshorthand`

```

1446 \def\@notshorthand#1{%
1447 \bbl@error{%
1448 The character '\string #1' should be made a shorthand character;\\%
1449 add the command \string\useshorthands\string{#1\string} to

```

```

1450 the preamble.\%
1451 I will ignore your instruction}%
1452 {You may proceed, but expect unexpected results}}

```

\shorthandon The first level definition of these macros just passes the argument on to \bbl@switch@sh, adding \shorthandoff \@nil at the end to denote the end of the list of characters.

```

1453 \newcommand*\shorthandon[1]{\bbl@switch@sh\@ne#1\@nnil}
1454 \DeclareRobustCommand*\shorthandoff{%
1455   \@ifstar{\bbl@shorthandoff\tw@}{\bbl@shorthandoff\z@}}
1456 \def\bbl@shorthandoff#1#2{\bbl@switch@sh#1#2\@nnil}

```

\bbl@switch@sh The macro \bbl@switch@sh takes the list of characters apart one by one and subsequently switches the category code of the shorthand character according to the first argument of \bbl@switch@sh. But before any of this switching takes place we make sure that the character we are dealing with is known as a shorthand character. If it is, a macro such as \active@char" should exist. Switching off and on is easy – we just set the category code to ‘other’ (12) and \active. With the starred version, the original catcode and the original definition, saved in @initiate@active@char, are restored.

```

1457 \def\bbl@switch@sh#1#2{%
1458   \ifx#2\@nnil\else
1459     \bbl@ifunset{\bbl@active@\string#2}%
1460     {\bbl@error
1461       {I can't switch '\string#2' on or off--not a shorthand}%
1462       {This character is not a shorthand. Maybe you made\%
1463         a typing mistake? I will ignore your instruction.}}%
1464     {\ifcase#1% off, on, off*
1465       \catcode`#2\relax
1466       \or
1467       \catcode`#2\active
1468       \bbl@ifunset{\bbl@shdef@\string#2}%
1469       {}%
1470       {\bbl@withactive{\expandafter\let\expandafter}%#2%
1471         \csname bbl@shdef@\string#2\endcsname
1472         \bbl@csarg\let{shdef@\string#2}\relax}%
1473       \ifcase\bbl@activated\or
1474       \bbl@activate{#2}%
1475       \else
1476       \bbl@deactivate{#2}%
1477       \fi
1478       \or
1479       \bbl@ifunset{\bbl@shdef@\string#2}%
1480       {\bbl@withactive{\bbl@csarg\let{shdef@\string#2}}%#2%
1481       {}%
1482       \csname bbl@oricat@\string#2\endcsname
1483       \csname bbl@oridef@\string#2\endcsname
1484       \fi}%
1485     \bbl@afterfi\bbl@switch@sh#1%
1486   \fi}

```

Note the value is that at the expansion time; eg, in the preamble shorhands are usually deactivated.

```

1487 \def\babelshorthand{\active@prefix\babelshorthand\bbl@putsh}
1488 \def\bbl@putsh#1{%
1489   \bbl@ifunset{\bbl@active@\string#1}%
1490   {\bbl@putsh@i#1\@empty\@nnil}%
1491   {\csname bbl@active@\string#1\endcsname}}
1492 \def\bbl@putsh@i#1#2\@nnil{%
1493   \csname\language@group @sh@\string#1@%
1494   \ifx\@empty#2\else\string#2\fi\endcsname}
1495 %
1496 \ifx\bbl@opt@shorthands\@nnil\else
1497   \let\bbl@s@initiate@active@char\initiate@active@char
1498   \def\initiate@active@char#1{%
1499     \bbl@ifshorthand{#1}{\bbl@s@initiate@active@char{#1}}{}}

```



```

1500 \let\bbl@switch@sh\bbl@switch@sh
1501 \def\bbl@switch@sh#1#2{%
1502   \ifx#2\@nnil\else
1503     \bbl@afterfi
1504     \bbl@ifshorthand{#2}{\bbl@switch@sh#1{#2}}{\bbl@switch@sh#1}%
1505   \fi}
1506 \let\bbl@s@activate\bbl@activate
1507 \def\bbl@activate#1{%
1508   \bbl@ifshorthand{#1}{\bbl@s@activate{#1}}{}}
1509 \let\bbl@s@deactivate\bbl@deactivate
1510 \def\bbl@deactivate#1{%
1511   \bbl@ifshorthand{#1}{\bbl@s@deactivate{#1}}{}}
1512 \fi

```

You may want to test if a character is a shorthand. Note it does not test whether the shorthand is on or off.

```

1513 \newcommand\ifbabelshorthand[3]{\bbl@ifunset{bbl@active@string#1}{#3}{#2}}

```

\bbl@prim@s One of the internal macros that are involved in substituting `\prime` for each right quote in mathmode is `\prim@s`. This checks if the next character is a right quote. When the right quote is active, the definition of this macro needs to be adapted to look also for an active right quote; the hat could be active, too.

\bbl@pr@m@s

```

1514 \def\bbl@prim@s{%
1515   \prime\futurelet\@let@token\bbl@pr@m@s}
1516 \def\bbl@if@primes#1#2{%
1517   \ifx#1\@let@token
1518     \expandafter\@firstoftwo
1519   \else\ifx#2\@let@token
1520     \bbl@afterelse\expandafter\@firstoftwo
1521   \else
1522     \bbl@afterfi\expandafter\@secondoftwo
1523   \fi\fi}
1524 \begingroup
1525   \catcode`\^=7 \catcode`\*=\active \lccode`\*=\^
1526   \catcode`\'=12 \catcode`\"=\active \lccode`\"=\'
1527   \lowercase{%
1528     \gdef\bbl@pr@m@s{%
1529       \bbl@if@primes""%
1530       \pr@@@s
1531       {\bbl@if@primes*\^{\pr@@@t\egroup}}}
1532 \endgroup

```

Usually the `~` is active and expands to `\penalty\@M\.`. When it is written to the `.aux` file it is written expanded. To prevent that and to be able to use the character `~` as a start character for a shorthand, it is redefined here as a one character shorthand on system level. The system declaration is in most cases redundant (when `~` is still a non-break space), and in some cases is inconvenient (if `~` has been redefined); however, for backward compatibility it is maintained (some existing documents may rely on the babel value).

```

1533 \initiate@active@char{~}
1534 \declare@shorthand{system}{~}{\leavevmode\nobreak\ }
1535 \bbl@activate{~}

```

\OT1dqpos The position of the double quote character is different for the OT1 and T1 encodings. It will later be selected using the `\f@encoding` macro. Therefore we define two macros here to store the position of the character in these encodings.

\T1dqpos

```

1536 \expandafter\def\csname OT1dqpos\endcsname{127}
1537 \expandafter\def\csname T1dqpos\endcsname{4}

```

When the macro `\f@encoding` is undefined (as it is in plain \TeX) we define it here to expand to OT1

```

1538 \ifx\f@encoding\undefined
1539   \def\f@encoding{OT1}
1540 \fi

```

7.6 Language attributes

Language attributes provide a means to give the user control over which features of the language definition files he wants to enable.

`\languageattribute` The macro `\languageattribute` checks whether its arguments are valid and then activates the selected language attribute. First check whether the language is known, and then process each attribute in the list.

```
1541 \bbl@trace{Language attributes}
1542 \newcommand\languageattribute[2]{%
1543   \def\bbl@tempc{#1}%
1544   \bbl@fixname\bbl@tempc
1545   \bbl@iflanguage\bbl@tempc{%
1546     \bbl@vforeach{#2}{%
```

We want to make sure that each attribute is selected only once; therefore we store the already selected attributes in `\bbl@known@attrs`. When that control sequence is not yet defined this attribute is certainly not selected before.

```
1547     \ifx\bbl@known@attrs\undefined
1548       \in@false
1549     \else
1550       \bbl@xin@{,\bbl@tempc-##1,}{,\bbl@known@attrs,}%
1551     \fi
1552     \ifin@
1553       \bbl@warning{%
1554         You have more than once selected the attribute '##1'\%
1555         for language #1. Reported}%
1556     \else
```

When we end up here the attribute is not selected before. So, we add it to the list of selected attributes and execute the associated \TeX -code.

```
1557       \bbl@exp{%
1558         \\bbl@add@list\\bbl@known@attrs{\bbl@tempc-##1}}%
1559       \edef\bbl@tempa{\bbl@tempc-##1}%
1560       \expandafter\bbl@ifknown@ttrib\expandafter{\bbl@tempa}\bbl@attributes%
1561       {\csname\bbl@tempc @attr@##1\endcsname}%
1562       {\@attrerr{\bbl@tempc}{##1}}%
1563     \fi}}
1564 \onlypreamble\languageattribute
```

The error text to be issued when an unknown attribute is selected.

```
1565 \newcommand*{\@attrerr}[2]{%
1566   \bbl@error
1567   {The attribute #2 is unknown for language #1.}%
1568   {Your command will be ignored, type <return> to proceed}}
```

`\bbl@declare@ttribute` This command adds the new language/attribute combination to the list of known attributes. Then it defines a control sequence to be executed when the attribute is used in a document. The result of this should be that the macro `\extras...` for the current language is extended, otherwise the attribute will not work as its code is removed from memory at `\begin{document}`.

```
1569 \def\bbl@declare@ttribute#1#2#3{%
1570   \bbl@xin@{,#2,}{,\BabelModifiers,}%
1571   \ifin@
1572     \AfterBabelLanguage{#1}{\languageattribute{#1}{#2}}%
1573   \fi
1574   \bbl@add@list\bbl@attributes{#1-#2}%
1575   \expandafter\def\csname#1@attr@#2\endcsname{#3}}
```

`\bbl@ifattributeset` This internal macro has 4 arguments. It can be used to interpret \TeX code based on whether a certain attribute was set. This command should appear inside the argument to `\AtBeginDocument` because the attributes are set in the document preamble, *after* babel is loaded. The first argument is the language, the second argument the attribute being checked, and the third and fourth arguments are the true and false clauses.

```

1576 \def\bbl@ifattributeset#1#2#3#4{%
1577   \ifx\bbl@known@attrs\@undefined
1578     \in@false
1579   \else
1580     \bbl@xin@{,#1-#2,}{,\bbl@known@attrs,}%
1581   \fi
1582   \ifin@
1583     \bbl@afterelse#3%
1584   \else
1585     \bbl@afterfi#4%
1586   \fi}

```

`\bbl@ifknown@ttrib` An internal macro to check whether a given language/attribute is known. The macro takes 4 arguments, the language/attribute, the attribute list, the \TeX -code to be executed when the attribute is known and the \TeX -code to be executed otherwise. We first assume the attribute is unknown. Then we loop over the list of known attributes, trying to find a match.

```

1587 \def\bbl@ifknown@ttrib#1#2{%
1588   \let\bbl@tempa\@secondoftwo
1589   \bbl@loopx\bbl@tempb{#2}{%
1590     \expandafter\in@\expandafter{\expandafter,\bbl@tempb,}{,#1,}%
1591   \ifin@
1592     \let\bbl@tempa\@firstoftwo
1593   \else
1594     \fi}%
1595   \bbl@tempa}

```

`\bbl@clear@ttribs` This macro removes all the attribute code from \TeX 's memory at `\begin{document}` time (if any is present).

```

1596 \def\bbl@clear@ttribs{%
1597   \ifx\bbl@attributes\@undefined\else
1598     \bbl@loopx\bbl@tempa{\bbl@attributes}{%
1599       \expandafter\bbl@clear@ttrib\bbl@tempa.}%
1600     \let\bbl@attributes\@undefined
1601   \fi}
1602 \def\bbl@clear@ttrib#1-#2.{%
1603   \expandafter\let\csname#1@attr#2\endcsname\@undefined}
1604 \AtBeginDocument{\bbl@clear@ttribs}

```

7.7 Support for saving macro definitions

To save the meaning of control sequences using `\babel@save`, we use temporary control sequences. To save hash table entries for these control sequences, we don't use the name of the control sequence to be saved to construct the temporary name. Instead we simply use the value of a counter, which is reset to zero each time we begin to save new values. This works well because we release the saved meanings before we begin to save a new set of control sequence meanings (see `\selectlanguage` and `\originalTeX`). Note undefined macros are not undefined any more when saved – they are `\relax`'ed.

`\babel@savecnt` The initialization of a new save cycle: reset the counter to zero.
`\babel@beginsave`

```

1605 \bbl@trace{Macros for saving definitions}
1606 \def\babel@beginsave{\babel@savecnt\z@}

```

Before it's forgotten, allocate the counter and initialize all.

```

1607 \newcount\babel@savecnt
1608 \babel@beginsave

```

`\babel@save` The macro `\babel@save⟨csname⟩` saves the current meaning of the control sequence `⟨csname⟩` to `\originalTeX`³¹. To do this, we let the current meaning to a temporary control sequence, the restore commands are appended to `\originalTeX` and the counter is incremented. The macro `\babel@savevariable⟨variable⟩` saves the value of the variable. `⟨variable⟩` can be anything allowed

³¹`\originalTeX` has to be expandable, i.e. you shouldn't let it to `\relax`.

after the \the primitive. To avoid messing saved definitions up, they are saved only the very first time.

```

1609 \def\babel@save#1{%
1610   \def\bbl@tempa{{, #1,}}% Clumsy, for Plain
1611   \expandafter\bbl@add\expandafter\bbl@tempa\expandafter{%
1612     \expandafter\expandafter,\bbl@savextras,}%
1613   \expandafter\in\bbl@tempa
1614   \ifin@ \else
1615     \bbl@add\bbl@savextras{, #1,}%
1616     \bbl@carg\let\babel@number\babel@savecnt\#1\relax
1617     \toks@ \expandafter\originalTeX\let#1=%
1618     \bbl@exp{%
1619       \def\originalTeX{\the\toks@<\babel@number\babel@savecnt>\relax}}%
1620     \advance\babel@savecnt\@ne
1621   \fi}
1622 \def\babel@savevariable#1{%
1623   \toks@ \expandafter\originalTeX #1=%
1624   \bbl@exp{\def\originalTeX{\the\toks@ \the#1\relax}}

```

\bbl@frenchspacing Some languages need to have \frenchspacing in effect. Others don't want that. The command \bbl@nonfrenchspacing switches it on when it isn't already in effect and \bbl@nonfrenchspacing switches it off if necessary. A more refined way to switch the catcodes is done with ini files. Here an auxiliary macro is defined, but the main part is in \babelprovide. This new method should be ideally the default one.

```

1625 \def\bbl@frenchspacing{%
1626   \ifnum\the\scode\.=\@m
1627     \let\bbl@nonfrenchspacing\relax
1628   \else
1629     \frenchspacing
1630     \let\bbl@nonfrenchspacing\nonfrenchspacing
1631   \fi}
1632 \let\bbl@nonfrenchspacing\nonfrenchspacing
1633 \let\bbl@elt\relax
1634 \edef\bbl@fs@chars{%
1635   \bbl@elt{\string.}\@m{3000}\bbl@elt{\string?}\@m{3000}%
1636   \bbl@elt{\string!}\@m{3000}\bbl@elt{\string:}\@m{2000}%
1637   \bbl@elt{\string;}\@m{1500}\bbl@elt{\string,}\@m{1250}}
1638 \def\bbl@pre@fs{%
1639   \def\bbl@elt##1##2##3{\scode`##1=\the\scode`##1\relax}%
1640   \edef\bbl@save@sfcodes{\bbl@fs@chars}%
1641 \def\bbl@post@fs{%
1642   \bbl@save@sfcodes
1643   \edef\bbl@tempa{\bbl@cl{frspc}}%
1644   \edef\bbl@tempa{\expandafter\@car\bbl@tempa\@nil}%
1645   \if u\bbl@tempa % do nothing
1646   \elseif n\bbl@tempa % non french
1647     \def\bbl@elt##1##2##3{%
1648       \ifnum\scode`##1=##2\relax
1649         \babel@savevariable{\scode`##1}%
1650         \scode`##1=##3\relax
1651       \fi}%
1652   \bbl@fs@chars
1653   \elseif y\bbl@tempa % french
1654     \def\bbl@elt##1##2##3{%
1655       \ifnum\scode`##1=##3\relax
1656         \babel@savevariable{\scode`##1}%
1657         \scode`##1=##2\relax
1658       \fi}%
1659   \bbl@fs@chars
1660   \fi\fi\fi}

```

7.8 Short tags

`\babeltags` This macro is straightforward. After zapping spaces, we loop over the list and define the macros `\text{<tag>}` and `\<tag>`. Definitions are first expanded so that they don't contain `\csname` but the actual macro.

```

1661 \bbl@trace{Short tags}
1662 \def\babeltags#1{%
1663   \edef\bbl@tempa{\zap@space#1 \@empty}%
1664   \def\bbl@tempb##1=##2\@{%
1665     \edef\bbl@tempc{%
1666       \noexpand\newcommand
1667       \expandafter\noexpand\csname ##1\endcsname{%
1668         \noexpand\protect
1669         \expandafter\noexpand\csname other language*\endcsname{##2}}
1670       \noexpand\newcommand
1671       \expandafter\noexpand\csname text##1\endcsname{%
1672         \noexpand\foreignlanguage{##2}}
1673     \bbl@tempc}%
1674   \bbl@for\bbl@tempa\bbl@tempa{%
1675     \expandafter\bbl@tempb\bbl@tempa\@}%

```

7.9 Hyphens

`\babelhyphenation` This macro saves hyphenation exceptions. Two macros are used to store them: `\bbl@hyphenation@` for the global ones and `\bbl@hyphenation<lang>` for language ones. See `\bbl@patterns` above for further details. We make sure there is a space between words when multiple commands are used.

```

1676 \bbl@trace{Hyphens}
1677 \@onlypreamble\babelhyphenation
1678 \AtEndOfPackage{%
1679   \newcommand\babelhyphenation[2][\@empty]{%
1680     \ifx\bbl@hyphenation@relax
1681       \let\bbl@hyphenation@\@empty
1682     \fi
1683     \ifx\bbl@hyphlist\@empty\else
1684       \bbl@warning{%
1685         You must not intermingle \string\selectlanguage\space and\%
1686         \string\babelhyphenation\space or some exceptions will not\%
1687         be taken into account. Reported}%
1688     \fi
1689     \ifx\@empty#1%
1690       \protected@edef\bbl@hyphenation@{\bbl@hyphenation@\space#2}%
1691     \else
1692       \bbl@vforeach{#1}{%
1693         \def\bbl@tempa{##1}%
1694         \bbl@fixname\bbl@tempa
1695         \bbl@iflanguage\bbl@tempa{%
1696           \bbl@csarg\protected@edef{hyphenation@\bbl@tempa}{%
1697             \bbl@ifunset{bbl@hyphenation@\bbl@tempa}%
1698             {}%
1699             {\csname bbl@hyphenation@\bbl@tempa\endcsname\space}%
1700             #2}}}%
1701       \fi}}

```

`\bbl@allowhyphens` This macro makes hyphenation possible. Basically its definition is nothing more than `\nobreak \hskip Opt plus Opt`³².

```

1702 \def\bbl@allowhyphens{\ifvmode\else\nobreak\hskip\z@skip\fi}
1703 \def\bbl@t@one{T1}
1704 \def\allowhyphens{\ifx\cf@encoding\bbl@t@one\else\bbl@allowhyphens\fi}

```

`\babelhyphen` Macros to insert common hyphens. Note the space before `@` in `\babelhyphen`. Instead of protecting it with `\DeclareRobustCommand`, which could insert a `\relax`, we use the same procedure as shorthands, with `\active@prefix`.

³² \TeX begins and ends a word for hyphenation at a glue node. The penalty prevents a linebreak at this glue node.

```

1705 \newcommand\babelnullhyphen{\char\hyphenchar\font}
1706 \def\babelhyphen{\active@prefix\babelhyphen\bb1@hyphen}
1707 \def\bb1@hyphen{%
1708   \@ifstar{\bb1@hyphen@i @}{\bb1@hyphen@i\@empty}}
1709 \def\bb1@hyphen@i#1#2{%
1710   \bb1@ifunset{\bb1@hy#1#2\@empty}%
1711     {\csname bb1@#1usehyphen\endcsname{\discretionary{#2}{}{#2}}}%
1712     {\csname bb1@hy#1#2\@empty\endcsname}}

```

The following two commands are used to wrap the “hyphen” and set the behavior of the rest of the word – the version with a single @ is used when further hyphenation is allowed, while that with @@ if no more hyphens are allowed. In both cases, if the hyphen is preceded by a positive space, breaking after the hyphen is disallowed.

There should not be a discretionary after a hyphen at the beginning of a word, so it is prevented if preceded by a skip. Unfortunately, this does handle cases like “(-suffix)”. \nobreak is always preceded by \leavevmode, in case the shorthand starts a paragraph.

```

1713 \def\bb1@usehyphen#1{%
1714   \leavevmode
1715   \ifdim\lastskip>\z@\mbox{#1}\else\nobreak#1\fi
1716   \nobreak\hskip\z@skip}
1717 \def\bb1@@usehyphen#1{%
1718   \leavevmode\ifdim\lastskip>\z@\mbox{#1}\else#1\fi}

```

The following macro inserts the hyphen char.

```

1719 \def\bb1@hyphenchar{%
1720   \ifnum\hyphenchar\font=\m@ne
1721     \babelnullhyphen
1722   \else
1723     \char\hyphenchar\font
1724   \fi}

```

Finally, we define the hyphen “types”. Their names will not change, so you may use them in ldf’s. After a space, the \mbox in \bb1@hy@nobreak is redundant.

```

1725 \def\bb1@hy@soft{\bb1@usehyphen{\discretionary{\bb1@hyphenchar}{}}{}}
1726 \def\bb1@hy@@soft{\bb1@usehyphen{\discretionary{\bb1@hyphenchar}{}}{}}
1727 \def\bb1@hy@hard{\bb1@usehyphen\bb1@hyphenchar}
1728 \def\bb1@hy@@hard{\bb1@usehyphen\bb1@hyphenchar}
1729 \def\bb1@hy@nobreak{\bb1@usehyphen{\mbox{\bb1@hyphenchar}}}
1730 \def\bb1@hy@@nobreak{\mbox{\bb1@hyphenchar}}
1731 \def\bb1@hy@repeat{%
1732   \bb1@usehyphen{%
1733     \discretionary{\bb1@hyphenchar}{\bb1@hyphenchar}{\bb1@hyphenchar}}}
1734 \def\bb1@hy@@repeat{%
1735   \bb1@usehyphen{%
1736     \discretionary{\bb1@hyphenchar}{\bb1@hyphenchar}{\bb1@hyphenchar}}}
1737 \def\bb1@hy@empty{\hskip\z@skip}
1738 \def\bb1@hy@@empty{\discretionary{}{}{}}

```

\bb1@disc For some languages the macro \bb1@disc is used to ease the insertion of discretionaries for letters that behave ‘abnormally’ at a breakpoint.

```

1739 \def\bb1@disc#1#2{\nobreak\discretionary{#2-}{}{#1}\bb1@allowhyphens}

```

7.10 Multiencoding strings

The aim following commands is to provide a common interface for strings in several encodings. They also contains several hooks which can be used by luatex and xetex. The code is organized here with pseudo-guards, so we start with the basic commands.

Tools But first, a tool. It makes global a local variable. This is not the best solution, but it works.

```

1740 \bb1@trace{Multiencoding strings}
1741 \def\bb1@tglobal#1{\global\let#1#1}

```

The second one. We need to patch `\@uclclist`, but it is done once and only if `\SetCase` is used or if strings are encoded. The code is far from satisfactory for several reasons, including the fact `\@uclclist` is not a list any more. Therefore a package option is added to ignore it. Instead of gobbling the macro getting the next two elements (usually `\reserved@a`), we pass it as argument to `\bbl@uclc`. The parser is restarted inside `\lang@bbl@uclc` because we do not know how many expansions are necessary (depends on whether strings are encoded). The last part is tricky – when uppercasing, we have:

```
\let\bbl@tolower\@empty\bbl@toupper\@empty
```

and starts over (and similarly when lowercasing).

```
1742 \@ifpackagewith{babel}{nocase}%
1743   {\let\bbl@patchuclc\relax}%
1744   {\def\bbl@patchuclc{% TODO. Delete. Doesn't work any more.
1745     \global\let\bbl@patchuclc\relax
1746     \g@addto@macro\@uclclist{\reserved@b{\reserved@b\bbl@uclc}}%
1747     \gdef\bbl@uclc##1{%
1748       \let\bbl@encoded\bbl@encoded@uclc
1749       \bbl@ifunset{\language @bbl@uclc}% and resumes it
1750       {##1}%
1751       {\let\bbl@tempa##1\relax % Used by LANG@bbl@uclc
1752         \csname\language @bbl@uclc\endcsname}%
1753       {\bbl@tolower\@empty}\bbl@toupper\@empty}}%
1754     \gdef\bbl@tolower{\csname\language @bbl@lc\endcsname}%
1755     \gdef\bbl@toupper{\csname\language @bbl@uc\endcsname}}%
1756 \langle *More package options\rangle \equiv
1757 \DeclareOption{nocase}{}
1758 \rangle /More package options\rangle
```

The following package options control the behavior of `\SetString`.

```
1759 \langle *More package options\rangle \equiv
1760 \let\bbl@opt@strings\@nnil % accept strings=value
1761 \DeclareOption{strings}{\def\bbl@opt@strings{\BabelStringsDefault}}
1762 \DeclareOption{strings=encoded}{\let\bbl@opt@strings\relax}
1763 \def\BabelStringsDefault{generic}
1764 \rangle /More package options\rangle
```

Main command This is the main command. With the first use it is redefined to omit the basic setup in subsequent blocks. We make sure strings contain actual letters in the range 128-255, not active characters.

```
1765 \@onlypreamble\StartBabelCommands
1766 \def\StartBabelCommands{%
1767   \begingroup
1768   \@tempcnta="7F
1769   \def\bbl@tempa{%
1770     \ifnum\@tempcnta>"FF\else
1771       \catcode\@tempcnta=11
1772       \advance\@tempcnta@ne
1773       \expandafter\bbl@tempa
1774     \fi}%
1775   \bbl@tempa
1776   \langle Macros local to BabelCommands\rangle
1777   \def\bbl@provstring##1##2{%
1778     \providecommand##1{##2}%
1779     \bbl@toglobal##1}%
1780   \global\let\bbl@scafter\@empty
1781   \let\StartBabelCommands\bbl@startcmds
1782   \ifx\BabelLanguages\relax
1783     \let\BabelLanguages\CurrentOption
1784   \fi
1785   \begingroup
```

```

1786 \let\bbl@screset\@nnil % local flag - disable 1st stopcommands
1787 \StartBabelCommands}
1788 \def\bbl@startcmds{%
1789 \ifx\bbl@screset\@nnil\else
1790 \bbl@usehooks{stopcommands}{}%
1791 \fi
1792 \endgroup
1793 \begingroup
1794 \@ifstar
1795 {\ifx\bbl@opt@strings\@nnil
1796 \let\bbl@opt@strings\BabelStringsDefault
1797 \fi
1798 \bbl@startcmds@i}%
1799 \bbl@startcmds@i}
1800 \def\bbl@startcmds@i#1#2{%
1801 \edef\bbl@L{\zap@space#1 \@empty}%
1802 \edef\bbl@G{\zap@space#2 \@empty}%
1803 \bbl@startcmds@ii}
1804 \let\bbl@startcmds\StartBabelCommands

```

Parse the encoding info to get the label, input, and font parts.

Select the behavior of \SetString. There are two main cases, depending of if there is an optional argument: without it and strings=encoded, strings are defined always; otherwise, they are set only if they are still undefined (ie, fallback values). With labelled blocks and strings=encoded, define the strings, but with another value, define strings only if the current label or font encoding is the value of strings; otherwise (ie, no strings or a block whose label is not in strings=) do nothing. We presume the current block is not loaded, and therefore set (above) a couple of default values to gobble the arguments. Then, these macros are redefined if necessary according to several parameters.

```

1805 \newcommand\bbl@startcmds@ii[1][\@empty]{%
1806 \let\SetString\gobbletwo
1807 \let\bbl@stringdef\gobbletwo
1808 \let\AfterBabelCommands\gobble
1809 \ifx\@empty#1%
1810 \def\bbl@sc@label{generic}%
1811 \def\bbl@encstring##1##2{%
1812 \ProvideTextCommandDefault##1{##2}%
1813 \bbl@tglobal##1%
1814 \expandafter\bbl@tglobal\curname\string?\string##1\endcsname}%
1815 \let\bbl@sctest\in@true
1816 \else
1817 \let\bbl@sc@charset\space % <- zapped below
1818 \let\bbl@sc@fontenc\space % <- " "
1819 \def\bbl@tempa##1=##2\@nil{%
1820 \bbl@csarg\edef{sc@\zap@space##1 \@empty}{##2 }}%
1821 \bbl@vforeach{label=#1}{\bbl@tempa##1\@nil}%
1822 \def\bbl@tempa##1 ##2{% space -> comma
1823 ##1%
1824 \ifx\@empty##2\else\ifx,##1,\else,\fi\bbl@afterfi\bbl@tempa##2\fi}%
1825 \edef\bbl@sc@fontenc{\expandafter\bbl@tempa\bbl@sc@fontenc\@empty}%
1826 \edef\bbl@sc@label{\expandafter\zap@space\bbl@sc@label\@empty}%
1827 \edef\bbl@sc@charset{\expandafter\zap@space\bbl@sc@charset\@empty}%
1828 \def\bbl@encstring##1##2{%
1829 \bbl@foreach\bbl@sc@fontenc{%
1830 \bbl@ifunset{T#####1}%
1831 }%
1832 {\ProvideTextCommand##1{#####1}{##2}%
1833 \bbl@tglobal##1%
1834 \expandafter
1835 \bbl@tglobal\curname#####1\string##1\endcsname}}}%
1836 \def\bbl@sctest{%
1837 \bbl@xin@{\bbl@opt@strings,}{,\bbl@sc@label,\bbl@sc@fontenc,}%
1838 \fi

```



```

1839 \ifx\bbbl@opt@strings\@nnil % ie, no strings key -> defaults
1840 \else\ifx\bbbl@opt@strings\relax % ie, strings=encoded
1841 \let\AfterBabelCommands\bbbl@aftercmds
1842 \let\SetString\bbbl@setstring
1843 \let\bbbl@stringdef\bbbl@encstring
1844 \else % ie, strings=value
1845 \bbbl@sctest
1846 \ifin@
1847 \let\AfterBabelCommands\bbbl@aftercmds
1848 \let\SetString\bbbl@setstring
1849 \let\bbbl@stringdef\bbbl@provstring
1850 \fi\fi\fi
1851 \bbbl@scswitch
1852 \ifx\bbbl@G\@empty
1853 \def\SetString##1##2{%
1854 \bbbl@error{Missing group for string \string##1}%
1855 {You must assign strings to some category, typically\%
1856 captions or extras, but you set none}}%
1857 \fi
1858 \ifx\@empty#1%
1859 \bbbl@usehooks{defaultcommands}{}%
1860 \else
1861 \@expandtwoargs
1862 \bbbl@usehooks{encodedcommands}{\bbbl@sc@charset}\bbbl@sc@fontenc}%
1863 \fi}

```

There are two versions of `\bbbl@scswitch`. The first version is used when `ldfs` are read, and it makes sure `\group` *(language)* is reset, but only once (`\bbbl@screset` is used to keep track of this). The second version is used in the preamble and packages loaded after `babel` and does nothing. The macro `\bbbl@forlang` loops `\bbbl@L` but its body is executed only if the value is in `\BabelLanguages` (inside `babel`) or `\date` *(language)* is defined (after `babel` has been loaded). There are also two version of `\bbbl@forlang`. The first one skips the current iteration if the language is not in `\BabelLanguages` (used in `ldfs`), and the second one skips undefined languages (after `babel` has been loaded).

```

1864 \def\bbbl@forlang#1#2{%
1865 \bbbl@for#1\bbbl@L{%
1866 \bbbl@xin@{, #1, }, {\BabelLanguages,}%
1867 \ifin#2\relax\fi}}
1868 \def\bbbl@scswitch{%
1869 \bbbl@forlang\bbbl@tempa{%
1870 \ifx\bbbl@G\@empty\else
1871 \ifx\SetString\gobbletwo\else
1872 \edef\bbbl@GL{\bbbl@G\bbbl@tempa}%
1873 \bbbl@xin@{, \bbbl@GL, }, {\bbbl@screset,}%
1874 \ifin@ \else
1875 \global\expandafter\let\csname\bbbl@GL\endcsname\@undefined
1876 \xdef\bbbl@screset{\bbbl@screset, \bbbl@GL}%
1877 \fi
1878 \fi
1879 \fi}}
1880 \AtEndOfPackage{%
1881 \def\bbbl@forlang#1#2{\bbbl@for#1\bbbl@L{\bbbl@ifunset{date#1}{}{#2}}}%
1882 \let\bbbl@scswitch\relax}
1883 \@onlypreamble\EndBabelCommands
1884 \def\EndBabelCommands{%
1885 \bbbl@usehooks{stopcommands}{}%
1886 \endgroup
1887 \endgroup
1888 \bbbl@scafter}
1889 \let\bbbl@endcommands\EndBabelCommands

```

Now we define commands to be used inside `\StartBabelCommands`.

Strings The following macro is the actual definition of `\SetString` when it is “active”

First save the “switcher”. Create it if undefined. Strings are defined only if undefined (ie, like `\providescommand`). With the event `stringprocess` you can preprocess the string by manipulating the value of `\BabelString`. If there are several hooks assigned to this event, preprocessing is done in the same order as defined. Finally, the string is set.

```

1890 \def\bbl@setstring#1#2{% eg, \prefacename{<string>}
1891   \bbl@forlang\bbl@tempa{%
1892     \edef\bbl@LC{\bbl@tempa\bbl@stripslash#1}%
1893     \bbl@ifunset{\bbl@LC}% eg, \germanchaptername
1894       {\bbl@exp{%
1895         \global\\bbl@add\<\bbl@G\bbl@tempa>{\bbl@scset\\#1\<\bbl@LC>}}}%
1896       }%
1897   \def\BabelString{#2}%
1898   \bbl@usehooks{stringprocess}{}%
1899   \expandafter\bbl@stringdef
1900     \csname\bbl@LC\expandafter\endcsname\expandafter{\BabelString}}}
```

Now, some additional stuff to be used when encoded strings are used. Captions then include `\bbl@encoded` for string to be expanded in case transformations. It is `\relax` by default, but in `\MakeUppercase` and `\MakeLowercase` its value is a modified expandable `\@changed@cmd`.

```

1901 \ifx\bbl@opt@strings\relax
1902   \def\bbl@scset#1#2{\def#1{\bbl@encoded#2}}
1903   \bbl@patchuclc
1904   \let\bbl@encoded\relax
1905   \def\bbl@encoded@uclc#1{%
1906     \@inmathwarn#1%
1907     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
1908       \expandafter\ifx\csname ?\string#1\endcsname\relax
1909         \TextSymbolUnavailable#1%
1910       \else
1911         \csname ?\string#1\endcsname
1912       \fi
1913     \else
1914       \csname\cf@encoding\string#1\endcsname
1915     \fi}
1916 \else
1917   \def\bbl@scset#1#2{\def#1{#2}}
1918 \fi
```

Define `\SetStringLoop`, which is actually set inside `\StartBabelCommands`. The current definition is somewhat complicated because we need a count, but `\count@` is not under our control (remember `\SetString` may call hooks). Instead of defining a dedicated count, we just “pre-expand” its value.

```

1919 <<{*Macros local to BabelCommands}>> ≡
1920 \def\SetStringLoop##1##2{%
1921   \def\bbl@templ####1{\expandafter\noexpand\csname##1\endcsname}%
1922   \count@\z@
1923   \bbl@loop\bbl@tempa{##2}{% empty items and spaces are ok
1924     \advance\count@\@ne
1925     \toks@\expandafter{\bbl@tempa}%
1926     \bbl@exp{%
1927       \\SetString\bbl@templ{\romannumeral\count@}{\the\toks@}%
1928       \count@=\the\count@\relax}}}%
1929 <</Macros local to BabelCommands>>
```

Delaying code Now the definition of `\AfterBabelCommands` when it is activated.

```

1930 \def\bbl@aftercmds#1{%
1931   \toks@\expandafter{\bbl@scafter#1}%
1932   \xdef\bbl@scafter{\the\toks@}}
```

Case mapping The command `\SetCase` provides a way to change the behavior of `\MakeUppercase` and `\MakeLowercase`. `\bbl@tempa` is set by the patched `\@uclclist` to the parsing command. *Deprecated.*

```

1933 <<{*Macros local to BabelCommands}>> ≡
```

```

1934 \newcommand\SetCase[3][]{%
1935   \bbl@patchuc1c
1936   \bbl@forlang\bbl@tempa{%
1937     \bbl@carg\bbl@encstring{\bbl@tempa @bbl@uc1c}{\bbl@tempa##1}%
1938     \bbl@carg\bbl@encstring{\bbl@tempa @bbl@uc}{##2}%
1939     \bbl@carg\bbl@encstring{\bbl@tempa @bbl@lc}{##3}}}%
1940 <</Macros local to BabelCommands>>

```

Macros to deal with case mapping for hyphenation. To decide if the document is monolingual or multilingual, we make a rough guess – just see if there is a comma in the languages list, built in the first pass of the package options.

```

1941 <<(*Macros local to BabelCommands)>> ≡
1942 \newcommand\SetHyphenMap[1]{%
1943   \bbl@forlang\bbl@tempa{%
1944     \expandafter\bbl@stringdef
1945     \csname\bbl@tempa @bbl@hyphenmap\endcsname{##1}}}%
1946 <</Macros local to BabelCommands>>

```

There are 3 helper macros which do most of the work for you.

```

1947 \newcommand\BabelLower[2]{% one to one.
1948   \ifnum\lccode#1=#2\else
1949     \babel@savevariable{\lccode#1}%
1950     \lccode#1=#2\relax
1951   \fi}
1952 \newcommand\BabelLowerMM[4]{% many-to-many
1953   \@tempcnta=#1\relax
1954   \@tempcntb=#4\relax
1955   \def\bbl@tempa{%
1956     \ifnum\@tempcnta>#2\else
1957       \expandtwoargs\BabelLower{\the\@tempcnta}{\the\@tempcntb}%
1958       \advance\@tempcnta#3\relax
1959       \advance\@tempcntb#3\relax
1960       \expandafter\bbl@tempa
1961     \fi}%
1962   \bbl@tempa}
1963 \newcommand\BabelLowerMO[4]{% many-to-one
1964   \@tempcnta=#1\relax
1965   \def\bbl@tempa{%
1966     \ifnum\@tempcnta>#2\else
1967       \expandtwoargs\BabelLower{\the\@tempcnta}{#4}%
1968       \advance\@tempcnta#3
1969       \expandafter\bbl@tempa
1970     \fi}%
1971   \bbl@tempa}

```

The following package options control the behavior of hyphenation mapping.

```

1972 <<(*More package options)>> ≡
1973 \DeclareOption{hyphenmap=off}{\chardef\bbl@opt@hyphenmap\z@}
1974 \DeclareOption{hyphenmap=first}{\chardef\bbl@opt@hyphenmap\@ne}
1975 \DeclareOption{hyphenmap=select}{\chardef\bbl@opt@hyphenmap\tw@}
1976 \DeclareOption{hyphenmap=other}{\chardef\bbl@opt@hyphenmap\thr@@}
1977 \DeclareOption{hyphenmap=other*}{\chardef\bbl@opt@hyphenmap4\relax}
1978 <</More package options>>

```

Initial setup to provide a default behavior if hyphenmap is not set.

```

1979 \AtEndOfPackage{%
1980   \ifx\bbl@opt@hyphenmap\undefined
1981     \bbl@xin@{,}{\bbl@language@opts}%
1982     \chardef\bbl@opt@hyphenmap\ifin4\else\@ne\fi
1983   \fi}

```

This sections ends with a general tool for resetting the caption names with a unique interface. With the old way, which mixes the switcher and the string, we convert it to the new one, which separates these two steps.

```

1984 \newcommand\setlocalecaption{% TODO. Catch typos.
1985 \ifstar\bbbl@setcaption@s\bbbl@setcaption@x}
1986 \def\bbbl@setcaption@x#1#2#3{% language caption-name string
1987 \bbbl@trim@def\bbbl@tempa{#2}%
1988 \bbbl@xin@{.template}{\bbbl@tempa}%
1989 \ifin@
1990 \bbbl@ini@captions@template{#3}{#1}%
1991 \else
1992 \edef\bbbl@tempd{%
1993 \expandafter\expandafter\expandafter
1994 \strip@prefix\expandafter\meaning\csname captions#1\endcsname}%
1995 \bbbl@xin@
1996 {\expandafter\string\csname #2name\endcsname}%
1997 {\bbbl@tempd}%
1998 \ifin@ % Renew caption
1999 \bbbl@xin@{\string\bbbl@scset}{\bbbl@tempd}%
2000 \ifin@
2001 \bbbl@exp{%
2002 \\\bbbl@ifsamestring{\bbbl@tempa}{\language}%
2003 {\\\bbbl@scset\<#2name>\<#1#2name>}%
2004 {}}%
2005 \else % Old way converts to new way
2006 \bbbl@ifunset{#1#2name}%
2007 {\bbbl@exp{%
2008 \\\bbbl@add\<captions#1>{\def\<#2name>{\<#1#2name>}}%
2009 \\\bbbl@ifsamestring{\bbbl@tempa}{\language}%
2010 {\def\<#2name>{\<#1#2name>}}%
2011 {}}}%
2012 {}}%
2013 \fi
2014 \else
2015 \bbbl@xin@{\string\bbbl@scset}{\bbbl@tempd}% New
2016 \ifin@ % New way
2017 \bbbl@exp{%
2018 \\\bbbl@add\<captions#1>{\\\bbbl@scset\<#2name>\<#1#2name>}%
2019 \\\bbbl@ifsamestring{\bbbl@tempa}{\language}%
2020 {\\\bbbl@scset\<#2name>\<#1#2name>}%
2021 {}}%
2022 \else % Old way, but defined in the new way
2023 \bbbl@exp{%
2024 \\\bbbl@add\<captions#1>{\def\<#2name>{\<#1#2name>}}%
2025 \\\bbbl@ifsamestring{\bbbl@tempa}{\language}%
2026 {\def\<#2name>{\<#1#2name>}}%
2027 {}}%
2028 \fi%
2029 \fi
2030 \@namedef{#1#2name}{#3}%
2031 \toks@\expandafter{\bbbl@captionslist}%
2032 \bbbl@exp{\in@{\<#2name>}{\the\toks@}}%
2033 \ifin@ \else
2034 \bbbl@exp{\\\bbbl@add\\bbbl@captionslist{\<#2name>}}%
2035 \bbbl@tglobal\bbbl@captionslist
2036 \fi
2037 \fi}
2038 % \def\bbbl@setcaption@s#1#2#3{} % TODO. Not yet implemented (w/o 'name')

```

7.11 Macros common to a number of languages

`\set@low@box` The following macro is used to lower quotes to the same level as the comma. It prepares its argument in box register 0.

```

2039 \bbbl@trace{Macros related to glyphs}
2040 \def\set@low@box#1{\setbox\tw@hbox{,}\setbox\z@hbox{#1}%
2041 \dimen\z@ht\z@ \advance\dimen\z@ -\ht\tw@%

```

```
2042 \setbox\z@\hbox{\lower\dimen\z@ \box\z@}\ht\z@\ht\tw@ \dp\z@\dp\tw@}
```

`\save@sf@q` The macro `\save@sf@q` is used to save and reset the current space factor.

```
2043 \def\save@sf@q#1{\leavevmode
2044 \begingroup
2045 \edef\@SF{\spacefactor\the\spacefactor}\#1\@SF
2046 \endgroup}
```

7.12 Making glyphs available

This section makes a number of glyphs available that either do not exist in the OT1 encoding and have to be ‘faked’, or that are not accessible through `T1enc.def`.

7.12.1 Quotation marks

`\quotedblbase` In the T1 encoding the opening double quote at the baseline is available as a separate character, accessible via `\quotedblbase`. In the OT1 encoding it is not available, therefore we make it available by lowering the normal open quote character to the baseline.

```
2047 \ProvideTextCommand{\quotedblbase}{OT1}{%
2048 \save@sf@q{\set@low@box{\textquotedblright\}%
2049 \box\z@\kern-.04em\bbl@allowhyphens}}
```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```
2050 \ProvideTextCommandDefault{\quotedblbase}{%
2051 \UseTextSymbol{OT1}{\quotedblbase}}
```

`\quotesinglbase` We also need the single quote character at the baseline.

```
2052 \ProvideTextCommand{\quotesinglbase}{OT1}{%
2053 \save@sf@q{\set@low@box{\textquoteright\}%
2054 \box\z@\kern-.04em\bbl@allowhyphens}}
```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```
2055 \ProvideTextCommandDefault{\quotesinglbase}{%
2056 \UseTextSymbol{OT1}{\quotesinglbase}}
```

`\guillemetleft` `\guillemetright` The guillemet characters are not available in OT1 encoding. They are faked. (Wrong names with o preserved for compatibility.)

```
2057 \ProvideTextCommand{\guillemetleft}{OT1}{%
2058 \ifmmode
2059 \ll
2060 \else
2061 \save@sf@q{\nobreak
2062 \raise.2ex\hbox{$\scriptscriptstyle\ll$}\bbl@allowhyphens}%
2063 \fi}
2064 \ProvideTextCommand{\guillemetright}{OT1}{%
2065 \ifmmode
2066 \gg
2067 \else
2068 \save@sf@q{\nobreak
2069 \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
2070 \fi}
2071 \ProvideTextCommand{\guillemotleft}{OT1}{%
2072 \ifmmode
2073 \ll
2074 \else
2075 \save@sf@q{\nobreak
2076 \raise.2ex\hbox{$\scriptscriptstyle\ll$}\bbl@allowhyphens}%
2077 \fi}
2078 \ProvideTextCommand{\guillemotright}{OT1}{%
2079 \ifmmode
2080 \gg
2081 \else
```

```

2082 \save@sf@q{\nobreak
2083 \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
2084 \fi}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2085 \ProvideTextCommandDefault{\guillemetleft}{%
2086 \UseTextSymbol{OT1}{\guillemetleft}}
2087 \ProvideTextCommandDefault{\guillemetright}{%
2088 \UseTextSymbol{OT1}{\guillemetright}}
2089 \ProvideTextCommandDefault{\guillemotleft}{%
2090 \UseTextSymbol{OT1}{\guillemotleft}}
2091 \ProvideTextCommandDefault{\guillemotright}{%
2092 \UseTextSymbol{OT1}{\guillemotright}}

```

`\guilsinglleft` The single guillemets are not available in OT1 encoding. They are faked.
`\guilsinglright`

```

2093 \ProvideTextCommand{\guilsinglleft}{OT1}{%
2094 \ifmmode
2095 <%
2096 \else
2097 \save@sf@q{\nobreak
2098 \raise.2ex\hbox{$\scriptscriptstyle<$}\bbl@allowhyphens}%
2099 \fi}
2100 \ProvideTextCommand{\guilsinglright}{OT1}{%
2101 \ifmmode
2102 >%
2103 \else
2104 \save@sf@q{\nobreak
2105 \raise.2ex\hbox{$\scriptscriptstyle>$}\bbl@allowhyphens}%
2106 \fi}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2107 \ProvideTextCommandDefault{\guilsinglleft}{%
2108 \UseTextSymbol{OT1}{\guilsinglleft}}
2109 \ProvideTextCommandDefault{\guilsinglright}{%
2110 \UseTextSymbol{OT1}{\guilsinglright}}

```

7.12.2 Letters

`\ij` The dutch language uses the letter ‘ij’. It is available in T1 encoded fonts, but not in the OT1 encoded `\IJ` fonts. Therefore we fake it for the OT1 encoding.

```

2111 \DeclareTextCommand{\ij}{OT1}{%
2112 i\kern-0.02em\bbl@allowhyphens j}
2113 \DeclareTextCommand{\IJ}{OT1}{%
2114 I\kern-0.02em\bbl@allowhyphens J}
2115 \DeclareTextCommand{\ij}{T1}{\char188}
2116 \DeclareTextCommand{\IJ}{T1}{\char156}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2117 \ProvideTextCommandDefault{\ij}{%
2118 \UseTextSymbol{OT1}{\ij}}
2119 \ProvideTextCommandDefault{\IJ}{%
2120 \UseTextSymbol{OT1}{\IJ}}

```

`\dj` The croatian language needs the letters `\dj` and `\DJ`; they are available in the T1 encoding, but not in `\DJ` the OT1 encoding by default.

Some code to construct these glyphs for the OT1 encoding was made available to me by Stipčević Mario, (stipcevic@olimp.irb.hr).

```

2121 \def\crrtic@{\hrule height0.1ex width0.3em}
2122 \def\crrtic@{\hrule height0.1ex width0.33em}
2123 \def\dj@{%
2124 \setbox0\hbox{d}\dimen@=\ht0
2125 \advance\dimen@1ex
2126 \dimen@.45\dimen@

```

```

2127 \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
2128 \advance\dimen@ii.5ex
2129 \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crttic@}}}}
2130 \def\DDJ@{%
2131 \setbox0\hbox{D}\dimen@=.55\ht0
2132 \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
2133 \advance\dimen@ii.15ex % correction for the dash position
2134 \advance\dimen@ii-.15\fontdimen7\font % correction for cmtt font
2135 \dimen\thr@@\expandafter\rem@pt\the\fontdimen7\font\dimen@
2136 \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crttic@}}}}
2137 %
2138 \DeclareTextCommand{\dj}{OT1}{\ddj@ d}
2139 \DeclareTextCommand{\DJ}{OT1}{\DDJ@ D}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2140 \ProvideTextCommandDefault{\dj}{%
2141 \UseTextSymbol{OT1}{\dj}}
2142 \ProvideTextCommandDefault{\DJ}{%
2143 \UseTextSymbol{OT1}{\DJ}}

```

\SS For the T1 encoding \SS is defined and selects a specific glyph from the font, but for other encodings it is not available. Therefore we make it available here.

```

2144 \DeclareTextCommand{\SS}{OT1}{\SS}
2145 \ProvideTextCommandDefault{\SS}{\UseTextSymbol{OT1}{\SS}}

```

7.12.3 Shorthands for quotation marks

Shorthands are provided for a number of different quotation marks, which make them usable both outside and inside mathmode. They are defined with \ProvideTextCommandDefault, but this is very likely not required because their definitions are based on encoding-dependent macros.

\glq The ‘german’ single quotes.

\grq

```

2146 \ProvideTextCommandDefault{\glq}{%
2147 \textormath{\quotesinglbase}{\mbox{\quotesinglbase}}}

```

The definition of \grq depends on the fontencoding. With T1 encoding no extra kerning is needed.

```

2148 \ProvideTextCommand{\grq}{T1}{%
2149 \textormath{\kern\z@\textquoteleft}{\mbox{\textquoteleft}}}
2150 \ProvideTextCommand{\grq}{TU}{%
2151 \textormath{\textquoteleft}{\mbox{\textquoteleft}}}
2152 \ProvideTextCommand{\grq}{OT1}{%
2153 \save@sf@q{\kern-.0125em
2154 \textormath{\textquoteleft}{\mbox{\textquoteleft}}}%
2155 \kern.07em\relax}}
2156 \ProvideTextCommandDefault{\grq}{\UseTextSymbol{OT1}\grq}

```

\glqq The ‘german’ double quotes.

\grqq

```

2157 \ProvideTextCommandDefault{\glqq}{%
2158 \textormath{\quotedblbase}{\mbox{\quotedblbase}}}

```

The definition of \grqq depends on the fontencoding. With T1 encoding no extra kerning is needed.

```

2159 \ProvideTextCommand{\grqq}{T1}{%
2160 \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}
2161 \ProvideTextCommand{\grqq}{TU}{%
2162 \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}
2163 \ProvideTextCommand{\grqq}{OT1}{%
2164 \save@sf@q{\kern-.07em
2165 \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}%
2166 \kern.07em\relax}}
2167 \ProvideTextCommandDefault{\grqq}{\UseTextSymbol{OT1}\grqq}

```

```

\flq The ‘french’ single guillemets.
\frq
2168 \ProvideTextCommandDefault{\flq}{%
2169   \textormath{\guilsinglleft}{\mbox{\guilsinglleft}}}
2170 \ProvideTextCommandDefault{\frq}{%
2171   \textormath{\guilsinglright}{\mbox{\guilsinglright}}}

```

```

\flqq The ‘french’ double guillemets.
\frqq
2172 \ProvideTextCommandDefault{\flqq}{%
2173   \textormath{\guillemetleft}{\mbox{\guillemetleft}}}
2174 \ProvideTextCommandDefault{\frqq}{%
2175   \textormath{\guillemetright}{\mbox{\guillemetright}}}

```

7.12.4 Umlauts and tremas

The command `\` needs to have a different effect for different languages. For German for instance, the ‘umlaut’ should be positioned lower than the default position for placing it over the letters a, o, u, A, O and U. When placed over an e, i, E or I it can retain its normal position. For Dutch the same glyph is always placed in the lower position.

`\umlauthigh` To be able to provide both positions of `\` we provide two commands to switch the positioning, the default will be `\umlauthigh` (the normal positioning).

```

2176 \def\umlauthigh{%
2177   \def\bbl@umlauta##1{\leavevmode\bgroup%
2178     \accent\csname\fontencoding dqpos\endcsname
2179     ##1\bbl@allowhyphens\egroup}%
2180   \let\bbl@umlaute\bbl@umlauta}
2181 \def\umlautlow{%
2182   \def\bbl@umlauta{\protect\lower@umlaut}}
2183 \def\umlautelow{%
2184   \def\bbl@umlaute{\protect\lower@umlaut}}
2185 \umlauthigh

```

`\lower@umlaut` The command `\lower@umlaut` is used to position the `\` closer to the letter. We want the umlaut character lowered, nearer to the letter. To do this we need an extra *dimen* register.

```

2186 \expandafter\ifx\csname U@D\endcsname\relax
2187   \csname newdimen\endcsname\U@D
2188 \fi

```

The following code fools T_EX’s `make_accent` procedure about the current x-height of the font to force another placement of the umlaut character. First we have to save the current x-height of the font, because we’ll change this font dimension and this is always done globally.

Then we compute the new x-height in such a way that the umlaut character is lowered to the base character. The value of `.45ex` depends on the METAFONT parameters with which the fonts were built. (Just try out, which value will look best.) If the new x-height is too low, it is not changed. Finally we call the `\accent` primitive, reset the old x-height and insert the base character in the argument.

```

2189 \def\lower@umlaut#1{%
2190   \leavevmode\bgroup
2191   \U@D 1ex%
2192   {\setbox\z@\hbox{%
2193     \char\csname\fontencoding dqpos\endcsname}%
2194     \dimen@ -.45ex\advance\dimen@\ht\z@
2195     \ifdim 1ex<\dimen@ \fontdimen5\font\dimen@ \fi}%
2196   \accent\csname\fontencoding dqpos\endcsname
2197   \fontdimen5\font\U@D #1%
2198   \egroup}

```

For all vowels we declare `\` to be a composite command which uses `\bbl@umlauta` or `\bbl@umlaute` to position the umlaut character. We need to be sure that these definitions override the ones that are provided when the package `fontenc` with option `OT1` is used. Therefore these declarations are postponed until the beginning of the document. Note these definitions only apply to some languages,

but babel sets them for *all* languages – you may want to redefine `\bbl@umlauta` and/or `\bbl@umlaute` for a language in the corresponding ldf (using the babel switching mechanism, of course).

```

2199 \AtBeginDocument{%
2200   \DeclareTextCompositeCommand{"}{OT1}{a}{\bbl@umlauta{a}}%
2201   \DeclareTextCompositeCommand{"}{OT1}{e}{\bbl@umlaute{e}}%
2202   \DeclareTextCompositeCommand{"}{OT1}{i}{\bbl@umlaute{i}}%
2203   \DeclareTextCompositeCommand{"}{OT1}{\i}{\bbl@umlaute{i}}%
2204   \DeclareTextCompositeCommand{"}{OT1}{o}{\bbl@umlauta{o}}%
2205   \DeclareTextCompositeCommand{"}{OT1}{u}{\bbl@umlauta{u}}%
2206   \DeclareTextCompositeCommand{"}{OT1}{A}{\bbl@umlauta{A}}%
2207   \DeclareTextCompositeCommand{"}{OT1}{E}{\bbl@umlaute{E}}%
2208   \DeclareTextCompositeCommand{"}{OT1}{I}{\bbl@umlaute{I}}%
2209   \DeclareTextCompositeCommand{"}{OT1}{O}{\bbl@umlauta{O}}%
2210   \DeclareTextCompositeCommand{"}{OT1}{U}{\bbl@umlauta{U}}%

```

Finally, make sure the default hyphenrules are defined (even if empty). For internal use, another empty `\language` is defined. Currently used in Amharic.

```

2211 \ifx\l@english\undefined
2212   \chardef\l@english\z@
2213 \fi
2214 % The following is used to cancel rules in ini files (see Amharic).
2215 \ifx\l@unhyphenated\undefined
2216   \newlanguage\l@unhyphenated
2217 \fi

```

7.13 Layout

Layout is mainly intended to set bidi documents, but there is at least a tool useful in general.

```

2218 \bbl@trace{Bidi layout}
2219 \providecommand\IfBabelLayout[3]{#3}%
2220 \newcommand\BabelPatchSection[1]{%
2221   \@ifundefined{#1}{}%
2222   \bbl@exp{\let<bbl@ss@#1>\<#1>}%
2223   \@namedef{#1}{%
2224     \@ifstar{\bbl@presec@s{#1}}%
2225     {\dblarg{\bbl@presec@x{#1}}}}%
2226 \def\bbl@presec@x#1[#2]#3{%
2227   \bbl@exp{%
2228     \\\select@language@x{\bbl@main@language}%
2229     \\\bbl@cs{sspre@#1}%
2230     \\\bbl@cs{ss@#1}%
2231     [\\foreignlanguage{\language}{\unexpanded{#2}}]%
2232     {\foreignlanguage{\language}{\unexpanded{#3}}}%
2233     \\\select@language@x{\language}}%
2234 \def\bbl@presec@s#1#2{%
2235   \bbl@exp{%
2236     \\\select@language@x{\bbl@main@language}%
2237     \\\bbl@cs{sspre@#1}%
2238     \\\bbl@cs{ss@#1}*%
2239     {\foreignlanguage{\language}{\unexpanded{#2}}}%
2240     \\\select@language@x{\language}}%
2241 \IfBabelLayout{sectioning}%
2242   {\BabelPatchSection{part}%
2243    \BabelPatchSection{chapter}%
2244    \BabelPatchSection{section}%
2245    \BabelPatchSection{subsection}%
2246    \BabelPatchSection{subsubsection}%
2247    \BabelPatchSection{paragraph}%
2248    \BabelPatchSection{subparagraph}%
2249    \def\babel@toc#1{%
2250      \select@language@x{\bbl@main@language}}}%
2251 \IfBabelLayout{captions}%
2252   {\BabelPatchSection{caption}}%

```

7.14 Load engine specific macros

Some macros are not defined in all engines, so, after loading the files define them if necessary to raise an error.

```
2253 \bbl@trace{Input engine specific macros}
2254 \ifcase\bbl@engine
2255   \input txtbabel.def
2256 \or
2257   \input luababel.def
2258 \or
2259   \input xebabel.def
2260 \fi
2261 \providecommand\babelfont{%
2262   \bbl@error
2263   {This macro is available only in LuaLaTeX and XeLaTeX.}%
2264   {Consider switching to these engines.}}
2265 \providecommand\babelprehyphenation{%
2266   \bbl@error
2267   {This macro is available only in LuaLaTeX.}%
2268   {Consider switching to that engine.}}
2269 \ifx\babelposthyphenation\undefined
2270   \let\babelposthyphenation\babelprehyphenation
2271   \let\babelpatterns\babelprehyphenation
2272   \let\babelcharproperty\babelprehyphenation
2273 \fi
```

7.15 Creating and modifying languages

`\babelprovide` is a general purpose tool for creating and modifying languages. It creates the language infrastructure, and loads, if requested, an ini file. It may be used in conjunction to previously loaded ldf files.

```
2274 \bbl@trace{Creating languages and reading ini files}
2275 \let\bbl@extend@ini@gobble
2276 \newcommand\babelprovide[2][]{%
2277   \let\bbl@savelangname\language
2278   \edef\bbl@savelocaleid{\the\localeid}%
2279   % Set name and locale id
2280   \edef\language{#2}%
2281   \bbl@id@assign
2282   % Initialize keys
2283   \bbl@foreach{captions,date,import,main,script,language,%
2284     hyphenrules,linebreaking,justification,mapfont,maparabic,%
2285     mapdigits,intraspaces,intrapenalty,onchar,transforms,alph,%
2286     Alph,labels,labels*,calendar,date,casing}%
2287     {\bbl@csarg\let{KVP@##1}\@nnil}%
2288   \global\let\bbl@release@transforms\@empty
2289   \let\bbl@calendars\@empty
2290   \global\let\bbl@inidata\@empty
2291   \global\let\bbl@extend@ini@gobble
2292   \global\let\bbl@included@inis\@empty
2293   \gdef\bbl@key@list{;}%
2294   \bbl@forkv{#1}{%
2295     \in@{/}{##1}% With /, (re)sets a value in the ini
2296     \ifin@
2297       \global\let\bbl@extend@ini\bbl@extend@ini@aux
2298       \bbl@renewinikey##1\@{##2}%
2299     \else
2300       \bbl@csarg\ifx{KVP@##1}\@nnil\else
2301         \bbl@error
2302         {Unknown key '##1' in \string\babelprovide}%
2303         {See the manual for valid keys}%
2304       \fi
2305       \bbl@csarg\def{KVP@##1}{##2}%
```

```

2306 \fi}%
2307 \chardef\bbbl@howloaded=% 0:none; 1:ldf without ini; 2:ini
2308 \bbbl@ifunset{date#2}\z@{\bbbl@ifunset{\bbbl@llevel@#2}\@ne\tw@}%
2309 % == init ==
2310 \ifx\bbbl@screset\@undefined
2311 \bbbl@ldfinit
2312 \fi
2313 % == date (as option) ==
2314 % \ifx\bbbl@KVP@date\@nnil\else
2315 % \fi
2316 % ==
2317 \let\bbbl@lbfkflag\relax % \@empty = do setup linebreak, only in 3 cases:
2318 \ifcase\bbbl@howloaded
2319 \let\bbbl@lbfkflag\@empty % new
2320 \else
2321 \ifx\bbbl@KVP@hyphenrules\@nnil\else
2322 \let\bbbl@lbfkflag\@empty
2323 \fi
2324 \ifx\bbbl@KVP@import\@nnil\else
2325 \let\bbbl@lbfkflag\@empty
2326 \fi
2327 \fi
2328 % == import, captions ==
2329 \ifx\bbbl@KVP@import\@nnil\else
2330 \bbbl@exp{\bbbl@ifblank{\bbbl@KVP@import}}%
2331 {\ifx\bbbl@initoload\relax
2332 \begingroup
2333 \def\BabelBeforeIni##1##2{\gdef\bbbl@KVP@import{##1}\endinput}%
2334 \bbbl@input@texini{#2}%
2335 \endgroup
2336 \else
2337 \xdef\bbbl@KVP@import{\bbbl@initoload}%
2338 \fi}%
2339 {}%
2340 \let\bbbl@KVP@date\@empty
2341 \fi
2342 \let\bbbl@KVP@captions@\bbbl@KVP@captions % TODO. A dirty hack
2343 \ifx\bbbl@KVP@captions\@nnil
2344 \let\bbbl@KVP@captions\bbbl@KVP@import
2345 \fi
2346 % ==
2347 \ifx\bbbl@KVP@transforms\@nnil\else
2348 \bbbl@replace\bbbl@KVP@transforms{ },}%
2349 \fi
2350 % == Load ini ==
2351 \ifcase\bbbl@howloaded
2352 \bbbl@provide@new{#2}%
2353 \else
2354 \bbbl@ifblank{#1}%
2355 {}% With \bbbl@load@basic below
2356 {\bbbl@provide@renew{#2}}%
2357 \fi
2358 % == include == TODO
2359 % \ifx\bbbl@included@inis\@empty\else
2360 % \bbbl@replace\bbbl@included@inis{ },}%
2361 % \bbbl@foreach\bbbl@included@inis{%
2362 % \openin\bbbl@readstream=babel-##1.ini
2363 % \bbbl@extend@ini{#2}}%
2364 % \closein\bbbl@readstream
2365 % \fi
2366 % Post tasks
2367 % -----
2368 % == subsequent calls after the first provide for a locale ==

```

```

2369 \ifx\bbl@inidata\@empty\else
2370 \bbl@extend@ini{#2}%
2371 \fi
2372 % == ensure captions ==
2373 \ifx\bbl@KVP@captions\@nnil\else
2374 \bbl@ifunset{\bbl@extracaps@#2}%
2375 {\bbl@exp{\bbl@babelensure[exclude=\\today]{#2}}}%
2376 {\bbl@exp{\bbl@babelensure[exclude=\\today,
2377 include=\[bbl@extracaps@#2]]{#2}}}%
2378 \bbl@ifunset{\bbl@ensure@language}%
2379 {\bbl@exp{%
2380 \\\DeclareRobustCommand\<bbl@ensure@language>[1]{%
2381 \\\foreignlanguage{language}%
2382 {###1}}}%
2383 }%
2384 \bbl@exp{%
2385 \\\bbl@tglobal\<bbl@ensure@language>%
2386 \\\bbl@tglobal\<bbl@ensure@language\space>%
2387 \fi
2388 % ==
2389 % At this point all parameters are defined if 'import'. Now we
2390 % execute some code depending on them. But what about if nothing was
2391 % imported? We just set the basic parameters, but still loading the
2392 % whole ini file.
2393 \bbl@load@basic{#2}%
2394 % == script, language ==
2395 % Override the values from ini or defines them
2396 \ifx\bbl@KVP@script\@nnil\else
2397 \bbl@csarg\edef{sname@#2}{\bbl@KVP@script}%
2398 \fi
2399 \ifx\bbl@KVP@language\@nnil\else
2400 \bbl@csarg\edef{lname@#2}{\bbl@KVP@language}%
2401 \fi
2402 \ifcase\bbl@engine\or
2403 \bbl@ifunset{\bbl@chrng@language}{}%
2404 {\directlua{
2405 Babel.set_chranges_b('\bbl@cl{sbc}', '\bbl@cl{chrng}') }}%
2406 \fi
2407 % == onchar ==
2408 \ifx\bbl@KVP@onchar\@nnil\else
2409 \bbl@luahyphenate
2410 \bbl@exp{%
2411 \\\AddToHook{env/document/before}{\select@language{#2}}}%
2412 \directlua{
2413 if Babel.locale_mapped == nil then
2414 Babel.locale_mapped = true
2415 Babel.linebreaking.add_before(Babel.locale_map, 1)
2416 Babel.loc_to_scr = {}
2417 Babel.chr_to_loc = Babel.chr_to_loc or {}
2418 end
2419 Babel.locale_props[\the\localeid].letters = false
2420 }%
2421 \bbl@xin@{ letters }{ \bbl@KVP@onchar\space}%
2422 \ifin@
2423 \directlua{
2424 Babel.locale_props[\the\localeid].letters = true
2425 }%
2426 \fi
2427 \bbl@xin@{ ids }{ \bbl@KVP@onchar\space}%
2428 \ifin@
2429 \ifx\bbl@starthyphens\@undefined % Needed if no explicit selection
2430 \AddBabelHook{babel-onchar}{beforestart}{\bbl@starthyphens}%
2431 \fi

```

```

2432 \bbl@exp{\bbl@add\bbl@starthyphens
2433 {\bbl@patterns@lua{\language}}}%
2434 % TODO - error/warning if no script
2435 \directlua{
2436   if Babel.script_blocks['\bbl@cl{sbc}'] then
2437     Babel.loc_to_scr[\the\localeid] =
2438       Babel.script_blocks['\bbl@cl{sbc}']
2439     Babel.locale_props[\the\localeid].lc = \the\localeid\space
2440     Babel.locale_props[\the\localeid].lg = \the@nameuse{l@\language}\space
2441   end
2442 }%
2443 \fi
2444 \bbl@xin@{ fonts }{\bbl@KVP@onchar\space}%
2445 \ifin@
2446 \bbl@ifunset{bbl@sys@\language}{\bbl@provide@sys@\language}}}%
2447 \bbl@ifunset{bbl@wdir@\language}{\bbl@provide@dirs@\language}}}%
2448 \directlua{
2449   if Babel.script_blocks['\bbl@cl{sbc}'] then
2450     Babel.loc_to_scr[\the\localeid] =
2451       Babel.script_blocks['\bbl@cl{sbc}']
2452   end}%
2453 \ifx\bbl@mapselect\undefined % TODO. almost the same as mapfont
2454 \AtBeginDocument{%
2455   \bbl@patchfont{\bbl@mapselect}}%
2456   {\selectfont}}%
2457 \def\bbl@mapselect{%
2458   \let\bbl@mapselect\relax
2459   \edef\bbl@prefontid{\fontid\font}}%
2460 \def\bbl@mapdir##1{%
2461   {\def\language{##1}%
2462     \let\bbl@ifrestoring\@firstoftwo % To avoid font warning
2463     \bbl@switchfont
2464     \ifnum\fontid\font>\z@ % A hack, for the pgf nullfont hack
2465       \directlua{
2466         Babel.locale_props[\the\csname bbl@id@##1\endcsname]%
2467           ['\bbl@prefontid'] = \fontid\font\space}%
2468       \fi}}%
2469 \fi
2470 \bbl@exp{\bbl@add\bbl@mapselect{\bbl@mapdir{\language}}}%
2471 \fi
2472 % TODO - catch non-valid values
2473 \fi
2474 % == mapfont ==
2475 % For bidi texts, to switch the font based on direction
2476 \ifx\bbl@KVP@mapfont\@nnil\else
2477 \bbl@ifsamestring{\bbl@KVP@mapfont}{direction}}}%
2478 {\bbl@error{Option '\bbl@KVP@mapfont' unknown for\%
2479   mapfont. Use 'direction'.%
2480   {See the manual for details.}}}%
2481 \bbl@ifunset{bbl@sys@\language}{\bbl@provide@sys@\language}}}%
2482 \bbl@ifunset{bbl@wdir@\language}{\bbl@provide@dirs@\language}}}%
2483 \ifx\bbl@mapselect\undefined % TODO. See onchar.
2484 \AtBeginDocument{%
2485   \bbl@patchfont{\bbl@mapselect}}%
2486   {\selectfont}}%
2487 \def\bbl@mapselect{%
2488   \let\bbl@mapselect\relax
2489   \edef\bbl@prefontid{\fontid\font}}%
2490 \def\bbl@mapdir##1{%
2491   {\def\language{##1}%
2492     \let\bbl@ifrestoring\@firstoftwo % avoid font warning
2493     \bbl@switchfont
2494     \directlua{Babel.fontmap

```

```

2495         [\the\csname bbl@wdir@##1\endcsname]%
2496         [\bbl@prefontid]=\fontid\font}}}%
2497     \fi
2498     \bbl@exp{\bbl@add\bbl@mapselect{\bbl@mapdir{\language\language}}}%
2499 \fi
2500 % == Line breaking: intraspace, intrapenalty ==
2501 % For CJK, East Asian, Southeast Asian, if interspace in ini
2502 \ifx\bbl@KVP@intraspace\@nnil\else % We can override the ini or set
2503     \bbl@csarg\edef{intsp#2}{\bbl@KVP@intraspace}%
2504 \fi
2505 \bbl@provide@intraspace
2506 % == Line breaking: CJK quotes == TODO -> @extras
2507 \ifcase\bbl@engine\or
2508     \bbl@xin@{/c}{\bbl@cl{lnbrk}}}%
2509 \ifin@
2510     \bbl@ifunset{\bbl@quote@\language\language}}{%
2511         {\directlua{
2512             Babel.locale_props[\the\localeid].cjk_quotes = {}
2513             local cs = 'op'
2514             for c in string.utfvalues(
2515                 [[\csname bbl@quote@\language\language\endcsname]]) do
2516                 if Babel.cjk_characters[c].c == 'qu' then
2517                     Babel.locale_props[\the\localeid].cjk_quotes[c] = cs
2518                 end
2519                 cs = ( cs == 'op') and 'cl' or 'op'
2520             end
2521         }}}%
2522     \fi
2523 \fi
2524 % == Line breaking: justification ==
2525 \ifx\bbl@KVP@justification\@nnil\else
2526     \let\bbl@KVP@linebreaking\bbl@KVP@justification
2527 \fi
2528 \ifx\bbl@KVP@linebreaking\@nnil\else
2529     \bbl@xin@{\bbl@KVP@linebreaking,}%
2530     {,elongated,kashida,cjk,padding,unhyphenated,}%
2531 \ifin@
2532     \bbl@csarg\xdef
2533     {\lnbrk@\language\language}{\expandafter\@car\bbl@KVP@linebreaking\@nil}%
2534 \fi
2535 \fi
2536 \bbl@xin@{/e}{\bbl@cl{lnbrk}}}%
2537 \ifin@\else\bbl@xin@{/k}{\bbl@cl{lnbrk}}}\fi
2538 \ifin@\bbl@arabicjust\fi
2539 \bbl@xin@{/p}{\bbl@cl{lnbrk}}}%
2540 \ifin@\AtBeginDocument{\@nameuse{\bbl@tibetanjust}}\fi
2541 % == Line breaking: hyphenate.other.(locale|script) ==
2542 \ifx\bbl@lbkflag\@empty
2543     \bbl@ifunset{\bbl@hyotl@\language\language}}{%
2544         {\bbl@csarg\bbl@replace{\hyotl@\language\language}{ }{,}%
2545         \bbl@startcommands*\language\language}}{%
2546         \bbl@csarg\bbl@foreach{\hyotl@\language\language}{%
2547             \ifcase\bbl@engine
2548                 \ifnum##1<257
2549                     \SetHyphenMap{\BabelLower{##1}{##1}}%
2550                 \fi
2551                 \else
2552                     \SetHyphenMap{\BabelLower{##1}{##1}}%
2553                 \fi}%
2554         \bbl@endcommands}%
2555     \bbl@ifunset{\bbl@hyots@\language\language}}{%
2556         {\bbl@csarg\bbl@replace{\hyots@\language\language}{ }{,}%
2557         \bbl@csarg\bbl@foreach{\hyots@\language\language}{%

```

```

2558 \ifcase\bb1@engine
2559 \ifnum##1<257
2560 \global\lccode##1=##1\relax
2561 \fi
2562 \else
2563 \global\lccode##1=##1\relax
2564 \fi}%
2565 \fi
2566 % == Counters: maparabic ==
2567 % Native digits, if provided in ini (TeX level, xe and lua)
2568 \ifcase\bb1@engine\else
2569 \bb1@ifunset{\bb1@dgnat@\languagename}{}%
2570 {\expandafter\ifx\csname \bb1@dgnat@\languagename\endcsname\@empty\else
2571 \expandafter\expandafter\expandafter
2572 \bb1@setdigits\csname \bb1@dgnat@\languagename\endcsname
2573 \ifx\bb1@KVP@maparabic\@nnil\else
2574 \ifx\bb1@latinarabic\@undefined
2575 \expandafter\let\expandafter\@arabic
2576 \csname \bb1@counter@\languagename\endcsname
2577 \else % ie, if layout=counters, which redefines \@arabic
2578 \expandafter\let\expandafter\bb1@latinarabic
2579 \csname \bb1@counter@\languagename\endcsname
2580 \fi
2581 \fi
2582 \fi}%
2583 \fi
2584 % == Counters: mapdigits ==
2585 % > luababel.def
2586 % == Counters: alph, Alph ==
2587 \ifx\bb1@KVP@alph\@nnil\else
2588 \bb1@exp{%
2589 \\\bb1@add\<\bb1@preextras@\languagename>{%
2590 \\\babel@save\\\@alph
2591 \let\\\@alph\<\bb1@cntr@\bb1@KVP@alph @\languagename>}}%
2592 \fi
2593 \ifx\bb1@KVP@Alph\@nnil\else
2594 \bb1@exp{%
2595 \\\bb1@add\<\bb1@preextras@\languagename>{%
2596 \\\babel@save\\\@Alph
2597 \let\\\@Alph\<\bb1@cntr@\bb1@KVP@Alph @\languagename>}}%
2598 \fi
2599 % == Casing ==
2600 \bb1@exp{\def\<\bb1@casing@\languagename>%
2601 {\<\bb1@lbcpr@\languagename>%
2602 \ifx\bb1@KVP@casing\@nnil\else-x-\bb1@KVP@casing\fi}}%
2603 % == Calendars ==
2604 \ifx\bb1@KVP@calendar\@nnil
2605 \edef\bb1@KVP@calendar{\bb1@cl{calpr}}%
2606 \fi
2607 \def\bb1@tempe##1 ##2\@{% Get first calendar
2608 \def\bb1@tempa{##1}}%
2609 \bb1@exp{\\\bb1@tempe\bb1@KVP@calendar\space\\\@}%
2610 \def\bb1@tempe##1.##2.##3\@{%
2611 \def\bb1@tempc{##1}}%
2612 \def\bb1@tempb{##2}}%
2613 \expandafter\bb1@tempe\bb1@tempa.\@
2614 \bb1@csarg\edef{calpr@\languagename}{%
2615 \ifx\bb1@tempc\@empty\else
2616 calendar=\bb1@tempc
2617 \fi
2618 \ifx\bb1@tempb\@empty\else
2619 ,variant=\bb1@tempb
2620 \fi}%

```

```

2621 % == engine specific extensions ==
2622 % Defined in XXXbabel.def
2623 \bbl@provide@extra{#2}%
2624 % == require.babel in ini ==
2625 % To load or reload the babel-*.tex, if require.babel in ini
2626 \ifx\bbl@beforestart\relax\else % But not in doc aux or body
2627   \bbl@ifunset{\bbl@rqtex@language\language}{}%
2628     {\expandafter\ifx\csname\bbl@rqtex@language\endcsname\empty\else
2629       \let\BabelBeforeIni\@gobbles
2630       \chardef\atcatcode=\catcode`\@
2631       \catcode`\@=11\relax
2632       \bbl@input@texini{\bbl@cs{rqtex@language}}%
2633       \catcode`\@=\atcatcode
2634       \let\atcatcode\relax
2635       \global\bbl@csarg\let{rqtex@language}\relax
2636     \fi}%
2637 \bbl@foreach\bbl@calendars{%
2638   \bbl@ifunset{\bbl@ca##1}{%
2639     \chardef\atcatcode=\catcode`\@
2640     \catcode`\@=11\relax
2641     \InputIfFileExists{babel-ca-##1.tex}{\fi}%
2642     \catcode`\@=\atcatcode
2643     \let\atcatcode\relax}%
2644   }%
2645 \fi
2646 % == frenchspacing ==
2647 \ifcase\bbl@howloaded\in@true\else\in@false\fi
2648 \ifin@else\bbl@xin@{typography/frenchspacing}{\bbl@key@list}\fi
2649 \ifin@
2650   \bbl@extras@wrap{\bbl@pre@fs}%
2651   {\bbl@pre@fs}%
2652   {\bbl@post@fs}%
2653 \fi
2654 % == transforms ==
2655 % > luababel.def
2656 % == main ==
2657 \ifx\bbl@KVP@main\@nnil % Restore only if not 'main'
2658   \let\language\bbl@savelangname
2659   \chardef\localeid\bbl@savelocaleid\relax
2660 \fi
2661 % == hyphenrules (apply if current) ==
2662 \ifx\bbl@KVP@hyphenrules\@nnil\else
2663   \ifnum\bbl@savelocaleid=\localeid
2664     \language\@nameuse{l@language}%
2665   \fi
2666 \fi}

```

Depending on whether or not the language exists (based on `\date<language>`), we define two macros. Remember `\bbl@startcommands` opens a group.

```

2667 \def\bbl@provide@new#1{%
2668   \@namedef{date#1}{}% marks lang exists - required by \StartBabelCommands
2669   \@namedef{extras#1}{}%
2670   \@namedef{noextras#1}{}%
2671   \bbl@startcommands*{#1}{captions}%
2672   \ifx\bbl@KVP@captions\@nnil % and also if import, implicit
2673     \def\bbl@tempb##1{% elt for \bbl@captionslist
2674       \ifx##1\empty\else
2675         \bbl@exp{%
2676           \\\SetString\\##1{%
2677             \\\bbl@nocaption{\bbl@stripslash##1}{#1\bbl@stripslash##1}}%
2678           \expandafter\bbl@tempb
2679         \fi}%
2680     \expandafter\bbl@tempb\bbl@captionslist\empty

```



```

2681 \else
2682 \ifx\bbbl@initoload\relax
2683 \bbbl@read@ini{\bbbl@KVP@captions}2% % Here letters cat = 11
2684 \else
2685 \bbbl@read@ini{\bbbl@initoload}2% % Same
2686 \fi
2687 \fi
2688 \StartBabelCommands*{#1}{date}%
2689 \ifx\bbbl@KVP@date\@nnil
2690 \bbbl@exp{%
2691 \SetString\bbbl@nocaption{today}{#1today}}}%
2692 \else
2693 \bbbl@savetoday
2694 \bbbl@savedate
2695 \fi
2696 \bbbl@endcommands
2697 \bbbl@load@basic{#1}%
2698 % == hyphenmins == (only if new)
2699 \bbbl@exp{%
2700 \gdef\<#1hyphenmins>{%
2701 {\bbbl@ifunset{\bbbl@lfthm@#1}{2}{\bbbl@cs{lfthm@#1}}}%
2702 {\bbbl@ifunset{\bbbl@rgthm@#1}{3}{\bbbl@cs{rgthm@#1}}}%
2703 % == hyphenrules (also in renew) ==
2704 \bbbl@provide@hyphens{#1}%
2705 \ifx\bbbl@KVP@main\@nnil\else
2706 \expandafter\main@language\expandafter{#1}%
2707 \fi}
2708 %
2709 \def\bbbl@provide@renew#1{%
2710 \ifx\bbbl@KVP@captions\@nnil\else
2711 \StartBabelCommands*{#1}{captions}%
2712 \bbbl@read@ini{\bbbl@KVP@captions}2% % Here all letters cat = 11
2713 \EndBabelCommands
2714 \fi
2715 \ifx\bbbl@KVP@date\@nnil\else
2716 \StartBabelCommands*{#1}{date}%
2717 \bbbl@savetoday
2718 \bbbl@savedate
2719 \EndBabelCommands
2720 \fi
2721 % == hyphenrules (also in new) ==
2722 \ifx\bbbl@lbfkflag\@empty
2723 \bbbl@provide@hyphens{#1}%
2724 \fi}

```

Load the basic parameters (ids, typography, counters, and a few more), while captions and dates are left out. But it may happen some data has been loaded before automatically, so we first discard the saved values. (TODO. But preserving previous values would be useful.)

```

2725 \def\bbbl@load@basic#1{%
2726 \ifcase\bbbl@howloaded\or\or
2727 \ifcase\csname bbl@llevel@\language\endcsname
2728 \bbbl@csarg\let{lname@\language}\relax
2729 \fi
2730 \fi
2731 \bbbl@ifunset{\bbbl@lname@#1}%
2732 {\def\BabelBeforeIni##1##2{%
2733 \begingroup
2734 \let\bbbl@ini@captions@aux\@gobbletwo
2735 \def\bbbl@inidate ####1.####2.####3.####4\relax ####5####6}%
2736 \bbbl@read@ini{##1}%
2737 \ifx\bbbl@initoload\relax\endinput\fi
2738 \endgroup}%
2739 \begingroup % boxed, to avoid extra spaces:

```

```

2740 \ifx\bb1@initoload\relax
2741 \bb1@input@texini{#1}%
2742 \else
2743 \setbox\z@\hbox{\BabelBeforeIni{\bb1@initoload}{}}%
2744 \fi
2745 \endgroup}%
2746 {}

```

The hyphenrules option is handled with an auxiliary macro. This macro is called in three cases: when a language is first declared with \babelprovide, with hyphenrules and with import.

```

2747 \def\bb1@provide@hyphens#1{%
2748 \@tempcnta\m@ne % a flag
2749 \ifx\bb1@KVP@hyphenrules\@nnil\else
2750 \bb1@replace\bb1@KVP@hyphenrules{ }{,}%
2751 \bb1@foreach\bb1@KVP@hyphenrules{%
2752 \ifnum\@tempcnta=\m@ne % if not yet found
2753 \bb1@ifsamestring{##1}{+}%
2754 {\bb1@carg\addlanguage{l@##1}}%
2755 }%
2756 \bb1@ifunset{l@##1}% After a possible +
2757 {}%
2758 {\@tempcnta\@nameuse{l@##1}}%
2759 \fi}%
2760 \ifnum\@tempcnta=\m@ne
2761 \bb1@warning{%
2762 Requested 'hyphenrules' for '\language' not found:\%
2763 \bb1@KVP@hyphenrules.\%
2764 Using the default value. Reported}%
2765 \fi
2766 \fi
2767 \ifnum\@tempcnta=\m@ne % if no opt or no language in opt found
2768 \ifx\bb1@KVP@captions@\@nnil % TODO. Hackish. See above.
2769 \bb1@ifunset{\bb1@hyphr@#1}{}% use value in ini, if exists
2770 {\bb1@exp{\bb1@ifblank{\bb1@cs{hyphr@#1}}}%
2771 {}%
2772 {\bb1@ifunset{l@bb1@cl{hyphr}}}%
2773 {}% if hyphenrules found:
2774 {\@tempcnta\@nameuse{l@bb1@cl{hyphr}}}%
2775 \fi
2776 \fi
2777 \bb1@ifunset{l@#1}%
2778 {\ifnum\@tempcnta=\m@ne
2779 \bb1@carg\adddialect{l@#1}\language
2780 \else
2781 \bb1@carg\adddialect{l@#1}\@tempcnta
2782 \fi}%
2783 {\ifnum\@tempcnta=\m@ne\else
2784 \global\bb1@carg\chardef{l@#1}\@tempcnta
2785 \fi}}

```

The reader of babel-...tex files. We reset temporarily some catcodes.

```

2786 \def\bb1@input@texini#1{%
2787 \bb1@bsphack
2788 \bb1@exp{%
2789 \catcode`\%%=14 \catcode`\==0
2790 \catcode`\{=1 \catcode`\}=2
2791 \lowercase{\InputIfFileExists{babel-#1.tex}{}}%
2792 \catcode`\the\catcode`\relax
2793 \catcode`\==\the\catcode`\relax
2794 \catcode`\{=\the\catcode`\relax
2795 \catcode`\}= \the\catcode`\relax}%
2796 \bb1@esphack}

```

The following macros read and store ini files (but don't process them). For each line, there are 3

possible actions: ignore if starts with ;, switch section if starts with [, and store otherwise. There are used in the first step of \bbl@read@ini.

```

2797 \def\bbl@inline#1\bbl@inline{%
2798   \@ifnextchar[\bbl@iniset{\@ifnextchar\bbl@iniskip\bbl@inistore}#1\@@}% ]
2799 \def\bbl@iniset[#1]#2\@@{\def\bbl@section{#1}}
2800 \def\bbl@iniskip#1\@@{%      if starts with ;
2801 \def\bbl@inistore#1=#2\@@{%   full (default)
2802   \bbl@trim@def\bbl@tempa{#1}%
2803   \bbl@trim\toks@{#2}%
2804   \bbl@xin@{\bbl@section/\bbl@tempa;}{\bbl@key@list}%
2805   \ifin@ \else
2806     \bbl@xin@{,identification/include.}%
2807     {,\bbl@section/\bbl@tempa}%
2808     \ifin@\xdef\bbl@included@inis{\the\toks@}\fi
2809     \bbl@exp{%
2810       \\g@addto@macro\\bbl@inidata{%
2811         \\bbl@elt{\bbl@section}{\bbl@tempa}{\the\toks@}}}%
2812     \fi}
2813 \def\bbl@inistore@min#1=#2\@@{% minimal (maybe set in \bbl@read@ini)
2814   \bbl@trim@def\bbl@tempa{#1}%
2815   \bbl@trim\toks@{#2}%
2816   \bbl@xin@{.identification.}{.\bbl@section.}%
2817   \ifin@
2818     \bbl@exp{\\g@addto@macro\\bbl@inidata{%
2819       \\bbl@elt{identification}{\bbl@tempa}{\the\toks@}}}%
2820   \fi}

```

Now, the ‘main loop’, which ****must be executed inside a group****. At this point, \bbl@inidata may contain data declared in \babelprovide, with ‘slashed’ keys. There are 3 steps: first read the ini file and store it; then traverse the stored values, and process some groups if required (date, captions, labels, counters); finally, ‘export’ some values by defining global macros (identification, typography, characters, numbers). The second argument is 0 when called to read the minimal data for fonts; with \babelprovide it’s either 1 or 2.

```

2821 \def\bbl@loop@ini{%
2822   \loop
2823     \if T\ifeof\bbl@readstream F\fi T\relax % Trick, because inside \loop
2824     \endlinechar\m@ne
2825     \read\bbl@readstream to \bbl@line
2826     \endlinechar``^^M
2827     \ifx\bbl@line\empty\else
2828       \expandafter\bbl@inline\bbl@line\bbl@inline
2829     \fi
2830     \repeat}
2831 \ifx\bbl@readstream\undefined
2832   \csname newread\endcsname\bbl@readstream
2833 \fi
2834 \def\bbl@read@ini#1#2{%
2835   \global\let\bbl@extend@ini\gobble
2836   \openin\bbl@readstream=babel-#1.ini
2837   \ifeof\bbl@readstream
2838     \bbl@error
2839     {There is no ini file for the requested language\\%
2840      (#1: \language). Perhaps you misspelled it or your\\%
2841      installation is not complete.}%
2842     {Fix the name or reinstall babel.}%
2843   \else
2844     % == Store ini data in \bbl@inidata ==
2845     \catcode`\[=12 \catcode`\]=12 \catcode`\==12 \catcode`\&=12
2846     \catcode`\;=12 \catcode`\|=12 \catcode`\%=14 \catcode`\-=12
2847     \bbl@info{Importing
2848       \ifcase#2font and identification \or basic \fi
2849       data for \language\\%
2850       from babel-#1.ini. Reported}%

```

```

2851 \ifnum#2=\z@
2852   \global\let\bbl@inidata@\empty
2853   \let\bbl@inistore\bbl@inistore@min % Remember it's local
2854   \fi
2855   \def\bbl@section{identification}%
2856   \bbl@exp{\bbl@inistore tag.ini=#1\\@}%
2857   \bbl@inistore load.level=#2\\@
2858   \bbl@loop@ini
2859   % == Process stored data ==
2860   \bbl@csarg\xdef{lini@language}{#1}%
2861   \bbl@read@ini@aux
2862   % == 'Export' data ==
2863   \bbl@ini@exports{#2}%
2864   \global\bbl@csarg\let{inidata@language}\bbl@inidata
2865   \global\let\bbl@inidata@\empty
2866   \bbl@exp{\bbl@add@list\bbl@ini@loaded{language}}%
2867   \bbl@tglobal\bbl@ini@loaded
2868   \fi
2869   \closein\bbl@readstream}
2870 \def\bbl@read@ini@aux{%
2871   \let\bbl@savestrings@\empty
2872   \let\bbl@savetoday@\empty
2873   \let\bbl@savestate@\empty
2874   \def\bbl@elt##1##2##3{%
2875     \def\bbl@section{##1}%
2876     \in@{=date.}{##1}% Find a better place
2877     \ifin@
2878       \bbl@ifunset{bbl@inikv@##1}%
2879       {\bbl@ini@calendar{##1}}%
2880       {}%
2881     \fi
2882     \bbl@ifunset{bbl@inikv@##1}{}%
2883     {\csname bbl@inikv@##1\endcsname{##2}{##3}}%
2884     \bbl@inidata}

```

A variant to be used when the ini file has been already loaded, because it's not the first \babelprovide for this language.

```

2885 \def\bbl@extend@ini@aux#1{%
2886   \bbl@startcommands*{#1}{captions}%
2887   % Activate captions/... and modify exports
2888   \bbl@csarg\def{inikv@captions.licr}##1##2{%
2889     \setlocalecaption{#1}{##1}{##2}}%
2890   \def\bbl@inikv@captions##1##2{%
2891     \bbl@ini@captions@aux{##1}{##2}}%
2892   \def\bbl@stringdef##1##2{\gdef##1{##2}}%
2893   \def\bbl@exportkey##1##2##3{%
2894     \bbl@ifunset{bbl@kv@##2}{%
2895       {\expandafter\ifx\csname bbl@kv@##2\endcsname\@empty\else
2896         \bbl@exp{\global\let<bbl@##1@language>\<bbl@kv@##2>}}%
2897       \fi}}%
2898   % As with \bbl@read@ini, but with some changes
2899   \bbl@read@ini@aux
2900   \bbl@ini@exports\tw@
2901   % Update inidata@lang by pretending the ini is read.
2902   \def\bbl@elt##1##2##3{%
2903     \def\bbl@section{##1}%
2904     \bbl@iniline##2=##3\bbl@iniline}%
2905     \csname bbl@inidata@#1\endcsname
2906     \global\bbl@csarg\let{inidata@#1}\bbl@inidata
2907   \StartBabelCommands*{#1}{date}% And from the import stuff
2908   \def\bbl@stringdef##1##2{\gdef##1{##2}}%
2909   \bbl@savetoday
2910   \bbl@savestate

```

```
2911 \bbl@endcommands}
```

A somewhat hackish tool to handle calendar sections. TODO. To be improved.

```
2912 \def\bbl@ini@calendar#1{%
2913 \lowercase{\def\bbl@tempa{=#1=}}%
2914 \bbl@replace\bbl@tempa{=date.gregorian}{}%
2915 \bbl@replace\bbl@tempa{=date.}{}%
2916 \in@{.licr=}{#1=}%
2917 \ifin@
2918 \ifcase\bbl@engine
2919 \bbl@replace\bbl@tempa{.licr=}{}%
2920 \else
2921 \let\bbl@tempa\relax
2922 \fi
2923 \fi
2924 \ifx\bbl@tempa\relax\else
2925 \bbl@replace\bbl@tempa{=}{}%
2926 \ifx\bbl@tempa\@empty\else
2927 \xdef\bbl@calendars{\bbl@calendars,\bbl@tempa}%
2928 \fi
2929 \bbl@exp{%
2930 \def\<bbl@inikv@#1>####1####2{%
2931 \\\bbl@inidate####1...\relax{####2}{\bbl@tempa}}}%
2932 \fi}
```

A key with a slash in \babelprovide replaces the value in the ini file (which is ignored altogether). The mechanism is simple (but suboptimal): add the data to the ini one (at this point the ini file has not yet been read), and define a dummy macro. When the ini file is read, just skip the corresponding key and reset the macro (in \bbl@inistore above).

```
2933 \def\bbl@renewinikey#1/#2\@#3{%
2934 \edef\bbl@tempa{\zap@space #1 \@empty}% section
2935 \edef\bbl@tempb{\zap@space #2 \@empty}% key
2936 \bbl@trim\toks@{#3}% value
2937 \bbl@exp{%
2938 \edef\\bbl@key@list{\bbl@key@list \bbl@tempa/\bbl@tempb;}%
2939 \\g@addto@macro\\bbl@inidata{%
2940 \\\bbl@elt{\bbl@tempa}{\bbl@tempb}{\the\toks@}}}%
2941 }
```

The previous assignments are local, so we need to export them. If the value is empty, we can provide a default value.

```
2941 \def\bbl@exportkey#1#2#3{%
2942 \bbl@ifunset{\bbl@kv@#2}%
2943 {\bbl@csarg\gdef{#1@\language}\{#3}}%
2944 {\expandafter\ifx\csname \bbl@kv@#2\endcsname\@empty
2945 \bbl@csarg\gdef{#1@\language}\{#3}}%
2946 \else
2947 \bbl@exp{\global\let\<bbl@#1@\language>\<bbl@kv@#2>}%
2948 \fi}}
```

Key-value pairs are treated differently depending on the section in the ini file. The following macros are the readers for identification and typography. Note \bbl@ini@exports is called always (via \bbl@inisec), while \bbl@after@ini must be called explicitly after \bbl@read@ini if necessary. Although BCP 47 doesn't treat '-x-' as an extension, the CLDR and many other sources do (as a *private use extension*). For consistency with other single-letter subtags or 'singletons', here is considered an extension, too.

```
2949 \def\bbl@iniwarning#1{%
2950 \bbl@ifunset{\bbl@kv@identification.warning#1}{}%
2951 {\bbl@warning{%
2952 From babel-\bbl@cs{lini@\language}.ini:\%
2953 \bbl@cs{kv@identification.warning#1}\%
2954 Reported }}}
2955 %
2956 \let\bbl@release@transforms\@empty
2957 \def\bbl@ini@exports#1{%
```

```

2958 % Identification always exported
2959 \bbl@iniwarning{}%
2960 \ifcase\bbl@engine
2961   \bbl@iniwarning{.pdflatex}%
2962 \or
2963   \bbl@iniwarning{.lualatex}%
2964 \or
2965   \bbl@iniwarning{.xelatex}%
2966 \fi%
2967 \bbl@exportkey{llevel}{identification.load.level}{}%
2968 \bbl@exportkey{elname}{identification.name.english}{}%
2969 \bbl@exp{\bbl@exportkey{lname}{identification.name.opentype}%
2970   {\csname bbl@elname@languagename\endcsname}}%
2971 \bbl@exportkey{tbcpr}{identification.tag.bcp47}{}%
2972 \bbl@exportkey{lbcpr}{identification.language.tag.bcp47}{}%
2973 % Somewhat hackish. TODO
2974 \bbl@exportkey{casing}{identification.language.tag.bcp47}{}%
2975 \bbl@exportkey{lotf}{identification.tag.opentype}{dflt}%
2976 \bbl@exportkey{esname}{identification.script.name}{}%
2977 \bbl@exp{\bbl@exportkey{sname}{identification.script.name.opentype}%
2978   {\csname bbl@esname@languagename\endcsname}}%
2979 \bbl@exportkey{sbcpr}{identification.script.tag.bcp47}{}%
2980 \bbl@exportkey{sotf}{identification.script.tag.opentype}{DFLT}%
2981 \bbl@exportkey{rbcp}{identification.region.tag.bcp47}{}%
2982 \bbl@exportkey{vbcp}{identification.variant.tag.bcp47}{}%
2983 \bbl@exportkey{extt}{identification.extension.t.tag.bcp47}{}%
2984 \bbl@exportkey{extu}{identification.extension.u.tag.bcp47}{}%
2985 \bbl@exportkey{extx}{identification.extension.x.tag.bcp47}{}%
2986 % Also maps bcp47 -> languagename
2987 \ifbbl@bcptoname
2988   \bbl@csarg\xdef{bcp@map@bbl@cl{tbcpr}}{\languagename}%
2989 \fi
2990 % Conditional
2991 \ifnum#1>z@ % 0 = only info, 1, 2 = basic, (re)new
2992   \bbl@exportkey{calpr}{date.calendar.preferred}{}%
2993   \bbl@exportkey{lnbrk}{typography.linebreaking}{h}%
2994   \bbl@exportkey{hyphr}{typography.hyphenrules}{}%
2995   \bbl@exportkey{lftm}{typography.lefthyphenmin}{2}%
2996   \bbl@exportkey{rgtm}{typography.righthyphenmin}{3}%
2997   \bbl@exportkey{prehc}{typography.prehyphenchar}{}%
2998   \bbl@exportkey{hyotl}{typography.hyphenate.other.locale}{}%
2999   \bbl@exportkey{hyots}{typography.hyphenate.other.script}{}%
3000   \bbl@exportkey{intsp}{typography.intraspaces}{}%
3001   \bbl@exportkey{frspc}{typography.frenchspacing}{u}%
3002   \bbl@exportkey{chrng}{characters.ranges}{}%
3003   \bbl@exportkey{quote}{characters.delimiters.quotes}{}%
3004   \bbl@exportkey{dgnat}{numbers.digits.native}{}%
3005   \ifnum#1=tw@ % only (re)new
3006     \bbl@exportkey{rqtex}{identification.require.babel}{}%
3007     \bbl@tglobal\bbl@savetoday
3008     \bbl@tglobal\bbl@savestate
3009     \bbl@savestrings
3010   \fi
3011 \fi}

A shared handler for key=val lines to be stored in \bbl@kv@<section>.<key>.
3012 \def\bbl@inikv#1#2{%      key=value
3013   \toks@{#2}%             This hides #'s from ini values
3014   \bbl@csarg\edef{@kv@bbl@section.#1}{\the\toks@}}

By default, the following sections are just read. Actions are taken later.
3015 \let\bbl@inikv@identification\bbl@inikv
3016 \let\bbl@inikv@date\bbl@inikv
3017 \let\bbl@inikv@typography\bbl@inikv

```

```

3018 \let\bbl@inikv@characters\bbl@inikv
3019 \let\bbl@inikv@numbers\bbl@inikv

```

Additive numerals require an additional definition. When .1 is found, two macros are defined – the basic one, without .1 called by \localnumeral, and another one preserving the trailing .1 for the ‘units’.

```

3020 \def\bbl@inikv@counters#1#2{%
3021   \bbl@ifsamestring{#1}{digits}%
3022   {\bbl@error{The counter name 'digits' is reserved for mapping\\%
3023     decimal digits}%
3024     {Use another name.}}%
3025   }%
3026   \def\bbl@tempc{#1}%
3027   \bbl@trim@def{\bbl@tempb*}{#2}%
3028   \in@{.1$}{#1$}%
3029   \ifin@
3030     \bbl@replace\bbl@tempc{.1}{}%
3031     \bbl@csarg\protected@xdef{cntr@\bbl@tempc @\language}\bbl@tempc{%
3032       \noexpand\bbl@alphanumeric{\bbl@tempc}}%
3033   \fi
3034   \in@{.F.}{#1}%
3035   \ifin@ \else \in@{.S.}{#1} \fi
3036   \ifin@
3037     \bbl@csarg\protected@xdef{cntr@#1@\language}\bbl@tempb*}%
3038   \else
3039     \toks@{}% Required by \bbl@buildifcase, which returns \bbl@tempa
3040     \expandafter\bbl@buildifcase\bbl@tempb* \ \ % Space after \ \
3041     \bbl@csarg{\global\expandafter\let}{cntr@#1@\language}\bbl@tempa
3042   \fi}

```

Now captions and captions.licr, depending on the engine. And below also for dates. They rely on a few auxiliary macros. It is expected the ini file provides the complete set in Unicode and LICR, in that order.

```

3043 \ifcase\bbl@engine
3044   \bbl@csarg\def{inikv@captions.licr}#1#2{%
3045     \bbl@ini@captions@aux{#1}{#2}}
3046 \else
3047   \def\bbl@inikv@captions#1#2{%
3048     \bbl@ini@captions@aux{#1}{#2}}
3049 \fi

```

The auxiliary macro for captions define \<caption>name.

```

3050 \def\bbl@ini@captions@template#1#2{% string language tempa=capt-name
3051   \bbl@replace\bbl@tempa{.template}{}%
3052   \def\bbl@toreplace{#1}{}%
3053   \bbl@replace\bbl@toreplace{[ ]}{\nobreakspace}}%
3054   \bbl@replace\bbl@toreplace{[ ]}{\csname}%
3055   \bbl@replace\bbl@toreplace{[ ]}{\csname the}%
3056   \bbl@replace\bbl@toreplace{[ ]}{\name\endcsname}}%
3057   \bbl@replace\bbl@toreplace{[ ]}{\endcsname}}%
3058   \bbl@xin@{,\bbl@tempa,}{,chapter,appendix,part,}%
3059   \ifin@
3060     \@nameuse{\bbl@patch\bbl@tempa}%
3061     \global\bbl@csarg\let{\bbl@tempa fmt@#2}\bbl@toreplace
3062   \fi
3063   \bbl@xin@{,\bbl@tempa,}{,figure,table,}%
3064   \ifin@
3065     \global\bbl@csarg\let{\bbl@tempa fmt@#2}\bbl@toreplace
3066     \bbl@exp{\gdef\<fnum@\bbl@tempa>{%
3067       \\\bbl@ifunset{\bbl@tempa fmt@\\language}%
3068       {[fnum@\bbl@tempa]}%
3069       {\\\@nameuse{\bbl@tempa fmt@\\language}}}%
3070     \fi}
3071 \def\bbl@ini@captions@aux#1#2{%

```

```

3072 \bbl@trim@def\bbl@tempa{#1}%
3073 \bbl@xin@{.template}{\bbl@tempa}%
3074 \ifin@
3075 \bbl@ini@captions@template{#2}\language\name
3076 \else
3077 \bbl@ifblank{#2}%
3078 {\bbl@exp{%
3079 \toks@{\bbl@nocaption{\bbl@tempa}{\language\name\bbl@tempa name}}}%
3080 {\bbl@trim\toks@{#2}}}%
3081 \bbl@exp{%
3082 \bbl@add\bbl@savestrings{%
3083 \SetString\<\bbl@tempa name>{\the\toks@}}}%
3084 \toks@\expandafter{\bbl@captionslist}%
3085 \bbl@exp{\in@{\<\bbl@tempa name>}{\the\toks@}}}%
3086 \ifin@
3087 \bbl@exp{%
3088 \bbl@add\<\bbl@extracaps@\language\name>{\<\bbl@tempa name>}%
3089 \bbl@to\global\<\bbl@extracaps@\language\name>}%
3090 \fi
3091 \fi}

```

Labels. Captions must contain just strings, no format at all, so there is new group in ini files.

```

3092 \def\bbl@list@the{%
3093 part,chapter,section,subsection,subsubsection,paragraph,%
3094 subparagraph,enumi,enumii,enumiii,enumiv,equation,figure,%
3095 table,page,footnote,mpfootnote,mpfn}
3096 \def\bbl@map@cnt#1{% #1:roman,etc, // #2:enumi,etc
3097 \bbl@ifunset{\bbl@map@#1@\language\name}%
3098 {\@nameuse{#1}}%
3099 {\@nameuse{\bbl@map@#1@\language\name}}}%
3100 \def\bbl@inikv@labels#1#2{%
3101 \in@{.map}{#1}%
3102 \ifin@
3103 \ifx\bbl@KVP@labels\@nnil\else
3104 \bbl@xin@{ map }{\bbl@KVP@labels\space}%
3105 \ifin@
3106 \def\bbl@tempc{#1}%
3107 \bbl@replace\bbl@tempc{.map}{}%
3108 \in@{#2,}{arabic,roman,Roman,alph,Alph,fnsymbol,}%
3109 \bbl@exp{%
3110 \gdef\<\bbl@map@\bbl@tempc @\language\name>%
3111 {\ifin@\<#2>\else\\localecounter{#2}\fi}}%
3112 \bbl@foreach\bbl@list@the{%
3113 \bbl@ifunset{the##1}{}%
3114 {\bbl@exp{\let\bbl@tempd\<the##1>}%
3115 \bbl@exp{%
3116 \bbl@sreplace\<the##1>%
3117 {\<\bbl@tempc>{##1}}{\bbl@map@cnt{\bbl@tempc}{##1}}}%
3118 \bbl@sreplace\<the##1>%
3119 {\<\@empty @\bbl@tempc>\<c@##1>}{\bbl@map@cnt{\bbl@tempc}{##1}}}%
3120 \expandafter\ifx\csname the##1\endcsname\bbl@tempd\else
3121 \toks@\expandafter\expandafter\expandafter{%
3122 \csname the##1\endcsname}%
3123 \expandafter\edef\csname the##1\endcsname{\the\toks@}%
3124 \fi}}}%
3125 \fi
3126 \fi
3127 %
3128 \else
3129 %
3130 % The following code is still under study. You can test it and make
3131 % suggestions. Eg, enumerate.2 = ([enumi]).([enumii]). It's
3132 % language dependent.

```



```

3133 \in@{enumerate.}{#1}%
3134 \ifin@
3135 \def\bb@tempa{#1}%
3136 \bb@replace\bb@tempa{enumerate.}{}%
3137 \def\bb@toreplace{#2}%
3138 \bb@replace\bb@toreplace{[ ]}{\nobreakspace{}}%
3139 \bb@replace\bb@toreplace{[]}{\csname the}%
3140 \bb@replace\bb@toreplace{[]}{\endcsname{}}%
3141 \toks@ \expandafter{\bb@toreplace}%
3142 % TODO. Execute only once:
3143 \bb@exp{%
3144 \\\bb@add\<extras\language>{%
3145 \\\babel@save\<labelenum\romannumeral\bb@tempa>%
3146 \def\<labelenum\romannumeral\bb@tempa>{\the\toks@}}%
3147 \\\bb@tglobal\<extras\language>}%
3148 \fi
3149 \fi}

```

To show correctly some captions in a few languages, we need to patch some internal macros, because the order is hardcoded. For example, in Japanese the chapter number is surrounded by two string, while in Hungarian is placed after. These replacement works in many classes, but not all. Actually, the following lines are somewhat tentative.

```

3150 \def\bb@chapttype{chapter}
3151 \ifx\@makechapterhead\@undefined
3152 \let\bb@patchchapter\relax
3153 \else\ifx\thechapter\@undefined
3154 \let\bb@patchchapter\relax
3155 \else\ifx\ps@headings\@undefined
3156 \let\bb@patchchapter\relax
3157 \else
3158 \def\bb@patchchapter{%
3159 \global\let\bb@patchchapter\relax
3160 \gdef\bb@chfmt{%
3161 \bb@ifunset{\bb@bb@chapttype fmt@\language}%
3162 {\@chapapp\space\thechapter}
3163 {\@nameuse{\bb@bb@chapttype fmt@\language}}}}
3164 \bb@add\appendix{\def\bb@chapttype{appendix}}% Not harmful, I hope
3165 \bb@sreplace\ps@headings{\@chapapp\ \thechapter}{\bb@chfmt}%
3166 \bb@sreplace\chaptermark{\@chapapp\ \thechapter}{\bb@chfmt}%
3167 \bb@sreplace\@makechapterhead{\@chapapp\space\thechapter}{\bb@chfmt}%
3168 \bb@tglobal\appendix
3169 \bb@tglobal\ps@headings
3170 \bb@tglobal\chaptermark
3171 \bb@tglobal\@makechapterhead}
3172 \let\bb@patchappendix\bb@patchchapter
3173 \fi\fi\fi
3174 \ifx\@part\@undefined
3175 \let\bb@patchpart\relax
3176 \else
3177 \def\bb@patchpart{%
3178 \global\let\bb@patchpart\relax
3179 \gdef\bb@partformat{%
3180 \bb@ifunset{\bb@partfmt@\language}%
3181 {\partname\nobreakspace\thepart}
3182 {\@nameuse{\bb@partfmt@\language}}}}
3183 \bb@sreplace\@part{\partname\nobreakspace\thepart}{\bb@partformat}%
3184 \bb@tglobal\@part}
3185 \fi

```

Date. Arguments (year, month, day) are *not* protected, on purpose. In \today, arguments are always gregorian, and therefore always converted with other calendars. TODO. Document

```

3186 \let\bb@calendar\@empty
3187 \DeclareRobustCommand\localedate[1][\bb@localedate{#1}]
3188 \def\bb@localedate#1#2#3#4{%

```

```

3189 \begingroup
3190 \edef\bbl@they{#2}%
3191 \edef\bbl@them{#3}%
3192 \edef\bbl@thed{#4}%
3193 \edef\bbl@tempe{%
3194     \bbl@ifunset{\bbl@calpr@\language\name}{\bbl@cl{calpr}},%
3195     #1}%
3196 \bbl@replace\bbl@tempe{ }{}%
3197 \bbl@replace\bbl@tempe{CONVERT}{convert}% Hackish
3198 \bbl@replace\bbl@tempe{convert}{convert}%
3199 \let\bbl@ld@calendar\@empty
3200 \let\bbl@ld@variant\@empty
3201 \let\bbl@ld@convert\relax
3202 \def\bbl@tempb##1=##2\@{\@namedef{\bbl@ld@##1}{##2}}%
3203 \bbl@foreach\bbl@tempe{\bbl@tempb##1\@}%
3204 \bbl@replace\bbl@ld@calendar{gregorian}{}%
3205 \ifx\bbl@ld@calendar\@empty\else
3206     \ifx\bbl@ld@convert\relax\else
3207         \babelcalendar[\bbl@they-\bbl@them-\bbl@thed]%
3208         {\bbl@ld@calendar}\bbl@they\bbl@them\bbl@thed
3209     \fi
3210 \fi
3211 \@nameuse{\bbl@precalendar}% Remove, eg, +, -civil (-ca-islamic)
3212 \edef\bbl@calendar{% Used in \month..., too
3213     \bbl@ld@calendar
3214     \ifx\bbl@ld@variant\@empty\else
3215         .\bbl@ld@variant
3216     \fi}%
3217 \bbl@cased
3218     {\@nameuse{\bbl@date@\language\name @\bbl@calendar}%
3219     \bbl@they\bbl@them\bbl@thed}%
3220 \endgroup}
3221 % eg: 1=months, 2=wide, 3=1, 4=dummy, 5=value, 6=calendar
3222 \def\bbl@inidate#1.#2.#3.#4\relax#5#6{% TODO - ignore with 'captions'
3223     \bbl@trim@def\bbl@tempa{#1.#2}%
3224     \bbl@ifsamestring{\bbl@tempa}{months.wide}% to savedate
3225     {\bbl@trim@def\bbl@tempa{#3}%
3226     \bbl@trim\toks@{#5}%
3227     \@temptokena\expandafter{\bbl@savedate}%
3228     \bbl@exp{% Reverse order - in ini last wins
3229         \def\\bbl@savedate{%
3230             \\SetString\<month\romannumeral\bbl@tempa#6name>{\the\toks@}%
3231             \the\@temptokena}}%
3232     {\bbl@ifsamestring{\bbl@tempa}{date.long}% defined now
3233     {\lowercase{\def\bbl@tempb{#6}}%
3234     \bbl@trim@def\bbl@toreplace{#5}%
3235     \bbl@TG@date
3236     \global\bbl@csarg\let{date@\language\name @\bbl@tempb}\bbl@toreplace
3237     \ifx\bbl@savetoday\@empty
3238     \bbl@exp{% TODO. Move to a better place.
3239         \\AfterBabelCommands{%
3240             \def\<\language\name date>{\\protect\<\language\name date >}%
3241             \\newcommand\<\language\name date >[4][{%
3242                 \\bbl@usedategroupttrue
3243                 \<\bbl@ensure@\language\name>{%
3244                     \\localedate[####1]{####2}{####3}{####4}}}%
3245             \def\\bbl@savetoday{%
3246                 \\SetString\\today{%
3247                     \<\language\name date>[convert]%
3248                     {\the\year}{\the\month}{\the\day}}}%
3249         \fi}%
3250     {}}

```

Dates will require some macros for the basic formatting. They may be redefined by language, so

“semi-public” names (camel case) are used. Oddly enough, the CLDR places particles like “de” inconsistently in either in the date or in the month name. Note after \bbl@replace\toks@ contains the resulting string, which is used by \bbl@replace@finish@iii (this implicit behavior doesn’t seem a good idea, but it’s efficient).

```

3251 \let\bbl@calendar\@empty
3252 \newcommand\babelcalendar[2][\the\year-\the\month-\the\day]{%
3253   \@nameuse{bbl@ca#2}#1\@}
3254 \newcommand\BabelDateSpace{\nobreakspace}
3255 \newcommand\BabelDateDot{.\@} % TODO. \let instead of repeating
3256 \newcommand\BabelDated[1]{\number#1}
3257 \newcommand\BabelDatedd[1]{\ifnum#1<10 0\fi\number#1}
3258 \newcommand\BabelDateM[1]{\number#1}
3259 \newcommand\BabelDateMM[1]{\ifnum#1<10 0\fi\number#1}
3260 \newcommand\BabelDateMMMM[1]{%
3261   \csname month\romannumeral#1\bbl@calendar name\endcsname}%
3262 \newcommand\BabelDatey[1]{\number#1}%
3263 \newcommand\BabelDateyy[1]{%
3264   \ifnum#1<10 0\number#1 %
3265   \else\ifnum#1<100 \number#1 %
3266   \else\ifnum#1<1000 \expandafter\@gobble\number#1 %
3267   \else\ifnum#1<10000 \expandafter\@gobbletwo\number#1 %
3268   \else
3269     \bbl@error
3270     {Currently two-digit years are restricted to the\
3271       range 0-9999.}%
3272     {There is little you can do. Sorry.}%
3273   \fi\fi\fi\fi}
3274 \newcommand\BabelDateyyyy[1]{\number#1} % TODO - add leading 0
3275 \def\bbl@replace@finish@iii#1{%
3276   \bbl@exp{\def\#1####1####2####3{\the\toks@}}
3277 \def\bbl@TG@@date{%
3278   \bbl@replace\bbl@toreplace{[ ]}{\BabelDateSpace{}}%
3279   \bbl@replace\bbl@toreplace{[.]}{\BabelDateDot{}}%
3280   \bbl@replace\bbl@toreplace{[d]}{\BabelDated{####3}}%
3281   \bbl@replace\bbl@toreplace{[dd]}{\BabelDatedd{####3}}%
3282   \bbl@replace\bbl@toreplace{[M]}{\BabelDateM{####2}}%
3283   \bbl@replace\bbl@toreplace{[MM]}{\BabelDateMM{####2}}%
3284   \bbl@replace\bbl@toreplace{[MMMM]}{\BabelDateMMMM{####2}}%
3285   \bbl@replace\bbl@toreplace{[y]}{\BabelDatey{####1}}%
3286   \bbl@replace\bbl@toreplace{[yy]}{\BabelDateyy{####1}}%
3287   \bbl@replace\bbl@toreplace{[yyyy]}{\BabelDateyyyy{####1}}%
3288   \bbl@replace\bbl@toreplace{[y|]}{\bbl@datecctr[####1|]}%
3289   \bbl@replace\bbl@toreplace{[m|]}{\bbl@datecctr[####2|]}%
3290   \bbl@replace\bbl@toreplace{[d|]}{\bbl@datecctr[####3|]}%
3291   \bbl@replace@finish@iii\bbl@toreplace}
3292 \def\bbl@datecctr{\expandafter\bbl@xdatecctr\expandafter}
3293 \def\bbl@xdatecctr[#1|#2]{\localenumeral{#2}{#1}}

```

Transforms.

```

3294 \let\bbl@release@transforms\@empty
3295 \bbl@csarg\let{inikv@transforms.prehyphenation}\bbl@inikv
3296 \bbl@csarg\let{inikv@transforms.posthyphenation}\bbl@inikv
3297 \def\bbl@transforms@aux#1#2#3#4,#5\relax{%
3298   #1[#2]{#3}{#4}{#5}}
3299 \begingroup % A hack. TODO. Don't require an specific order
3300   \catcode\%=12
3301   \catcode\&=14
3302   \gdef\bbl@transforms#1#2#3{&%
3303     \directlua{
3304       local str = [=[#2]=]
3305       str = str:gsub('%.%d+%.%d+$', '')
3306       token.set_macro('babeltempa', str)
3307     }&%

```

```

3308 \def\babeltempc{}&%
3309 \bbl@xin@{\babeltempa,}{,\bbl@KVP@transforms,}&%
3310 \ifin@&else
3311 \bbl@xin@{\babeltempa,}{,\bbl@KVP@transforms,}&%
3312 \fi
3313 \ifin@
3314 \bbl@foreach\bbl@KVP@transforms{&%
3315 \bbl@xin@{\babeltempa,}{,##1,}&%
3316 \ifin@ &% font:font:transform syntax
3317 \directlua{
3318 local t = {}
3319 for m in string.gmatch('##1'..':', '(.-):') do
3320 table.insert(t, m)
3321 end
3322 table.remove(t)
3323 token.set_macro('babeltempc', ',font=' .. table.concat(t, ' '))
3324 }&%
3325 \fi}&%
3326 \in@{.0$}{#2$}&%
3327 \ifin@
3328 \directlua{&% (\attribute) syntax
3329 local str = string.match([[ \bbl@KVP@transforms]],
3330 '%([^(%-)%)^[^%)]-\babeltempa')
3331 if str == nil then
3332 token.set_macro('babeltempb', '')
3333 else
3334 token.set_macro('babeltempb', ',attribute=' .. str)
3335 end
3336 }&%
3337 \toks@{#3}&%
3338 \bbl@exp{&%
3339 \\\g@addto@macro\\\bbl@release@transforms{&%
3340 \relax &% Closes previous \bbl@transforms@aux
3341 \\\bbl@transforms@aux
3342 \\\#1{label=\babeltempa\babeltempb\babeltempc}&%
3343 {\language\the\toks@}}&%
3344 \else
3345 \g@addto@macro\bbl@release@transforms{, {#3}}&%
3346 \fi
3347 \fi}
3348 \endgroup

```

Language and Script values to be used when defining a font or setting the direction are set with the following macros.

```

3349 \def\bbl@provide@lsys#1{%
3350 \bbl@ifunset{bbl@lname@#1}%
3351 {\bbl@load@info{#1}}%
3352 {}%
3353 \bbl@csarg\let{lsys@#1}\@empty
3354 \bbl@ifunset{bbl@sname@#1}{\bbl@csarg\gdef{sname@#1}{Default}}{}%
3355 \bbl@ifunset{bbl@sotf@#1}{\bbl@csarg\gdef{sotf@#1}{DFLT}}{}%
3356 \bbl@csarg\bbl@add@list{lsys@#1}{Script=\bbl@cs{sname@#1}}%
3357 \bbl@ifunset{bbl@lname@#1}{}%
3358 {\bbl@csarg\bbl@add@list{lsys@#1}{Language=\bbl@cs{lname@#1}}}%
3359 \ifcase\bbl@engine\or\or
3360 \bbl@ifunset{bbl@prehc@#1}{}%
3361 {\bbl@exp{\\\bbl@ifblank{\bbl@cs{prehc@#1}}}%
3362 {}%
3363 {\ifx\bbl@xenoxyph\undefined
3364 \global\let\bbl@xenoxyph\bbl@xenoxyph@d
3365 \ifx\AtBeginDocument\@notprerr
3366 \expandafter\@secondoftwo % to execute right now
3367 \fi

```

```

3368 \AtBeginDocument{%
3369 \bbl@patchfont{\bbl@xenoxyph}%
3370 \expandafter\select@language\expandafter{\language}%
3371 \fi}%
3372 \fi
3373 \bbl@csarg\bbl@tglobal{lsys@#1}}
3374 \def\bbl@xenoxyph@d{%
3375 \bbl@ifset{bbl@prehc@\language}%
3376 {\ifnum\hyphenchar\font=\defaultshyphenchar
3377 \iffontchar\font\bbl@cl{prehc}\relax
3378 \hyphenchar\font\bbl@cl{prehc}\relax
3379 \else\iffontchar\font"200B
3380 \hyphenchar\font"200B
3381 \else
3382 \bbl@warning
3383 {Neither 0 nor ZERO WIDTH SPACE are available\\%
3384 in the current font, and therefore the hyphen\\%
3385 will be printed. Try changing the fontspec's\\%
3386 'HyphenChar' to another value, but be aware\\%
3387 this setting is not safe (see the manual).\\%
3388 Reported}%
3389 \hyphenchar\font\defaultshyphenchar
3390 \fi\fi
3391 \fi}%
3392 {\hyphenchar\font\defaultshyphenchar}}
3393 % \fi}

```

The following ini reader ignores everything but the identification section. It is called when a font is defined (ie, when the language is first selected) to know which script/language must be enabled. This means we must make sure a few characters are not active. The ini is not read directly, but with a proxy tex file named as the language (which means any code in it must be skipped, too).

```

3394 \def\bbl@load@info#1{%
3395 \def\BabelBeforeIni##1##2{%
3396 \begingroup
3397 \bbl@read@ini{##1}0%
3398 \endinput % babel- .tex may contain onlypreamble's
3399 \endgroup}% boxed, to avoid extra spaces:
3400 {\bbl@input@texini{##1}}

```

A tool to define the macros for native digits from the list provided in the ini file. Somewhat convoluted because there are 10 digits, but only 9 arguments in T_EX. Non-digits characters are kept. The first macro is the generic “localized” command.

```

3401 \def\bbl@setdigits#1#2#3#4#5{%
3402 \bbl@exp{%
3403 \def\<\language digits>####1{% ie, \langdigits
3404 \<\bbl@digits@\language>####1\\\nil}%
3405 \let\<\bbl@cntr@digits@\language>\<\language digits>%
3406 \def\<\language counter>####1{% ie, \langcounter
3407 \\\expandafter\<\bbl@counter@\language>%
3408 \\\csname c#####1\endcsname}%
3409 \def\<\bbl@counter@\language>####1{% ie, \bbl@counter@lang
3410 \\\expandafter\<\bbl@digits@\language>%
3411 \\\number####1\\\nil}}%
3412 \def\bbl@tempa##1##2##3##4##5{%
3413 \bbl@exp{% Wow, quite a lot of hashes! :-(
3414 \def\<\bbl@digits@\language>#####1{%
3415 \\\ifx#####1\\\nil % ie, \bbl@digits@lang
3416 \\\else
3417 \\\ifx0#####1#1%
3418 \\\else\\\ifx1#####1#2%
3419 \\\else\\\ifx2#####1#3%
3420 \\\else\\\ifx3#####1#4%
3421 \\\else\\\ifx4#####1#5%
3422 \\\else\\\ifx5#####1##1%

```

[illegible]

```

3432 \def\bbl@buildifcase#1 {% Returns \bbl@tempa, requires \toks@={%
3433   \ifx\\#1%           % \\ before, in case #1 is multiletter
3434     \bbl@exp{%
3435       \def\\bbl@tempa####1{%
3436         \<ifcase>####1\space\the\toks@\<else>\\@ctrerrr\<fi>}}%
3437   \else
3438     \toks@\expandafter{\the\toks@\or #1}%
3439     \expandafter\bbl@buildifcase
3440 \fi}

```

```

3441 \newcommand\localenumberal[2]{\bbl@cs{cntr@#1\language}\#2}}
3442 \def\bbl@localecntr#1#2{\localenumberal{#2}{#1}}
3443 \newcommand\localecounter[2]{%
3444   \expandafter\bbl@localecntr
3445   \expandafter{\number\csname c@#2\endcsname}{#1}}
3446 \def\bbl@alphnumerical#1#2{%
3447   \expandafter\bbl@alphnumerical@i\number#2 76543210\@@{#1}}
3448 \def\bbl@alphnumerical@i#1#2#3#4#5#6#7#8\@@#9{%
3449   \ifcase\car#8\@nil\or    % Currenty <10000, but prepared for bigger
3450     \bbl@alphnumerical@ii{#9}000000#1\or
3451     \bbl@alphnumerical@ii{#9}00000#1#2\or
3452     \bbl@alphnumerical@ii{#9}0000#1#2#3\or
3453     \bbl@alphnumerical@ii{#9}000#1#2#3#4\else
3454     \bbl@alphnum@invalid{>9999}%
3455   \fi}
3456 \def\bbl@alphnumerical@ii#1#2#3#4#5#6#7#8{%
3457   \bbl@ifunset{\bbl@cntr@#1.F.\number#5#6#7#8\language}%
3458     {\bbl@cs{cntr@#1.4\language}#5%
3459     \bbl@cs{cntr@#1.3\language}#6%
3460     \bbl@cs{cntr@#1.2\language}#7%
3461     \bbl@cs{cntr@#1.1\language}#8%
3462     \ifnum#6#7#8>\z@ % TODO. An ad hoc rule for Greek. Ugly.
3463       \bbl@ifunset{\bbl@cntr@#1.S.321\language}{}%
3464       {\bbl@cs{cntr@#1.S.321\language}}%
3465     \fi}%
3466   {\bbl@cs{cntr@#1.F.\number#5#6#7#8\language}}}
3467 \def\bbl@alphnum@invalid#1{%
3468   \bbl@error{Alphabetic numeral too large (#1)}%
3469   {Currently this is the limit.}}

```

```

3470 \def\bbl@localeinfo#1#2{%
3471   \bbl@ifunset{\bbl@info@#2}{#1}%
3472   {\bbl@ifunset{\bbl@\csname bbl@info@#2\endcsname @\languagename}{#1}%
3473    {\bbl@cs{\csname bbl@info@#2\endcsname @\languagename}}}}
3474 \newcommand\localeinfo[1]{%
3475   \ifx*#1\@empty   % TODO. A bit hackish to make it expandable.

```

```

3476 \bbl@afterelse\bbl@localeinfo{}}%
3477 \else
3478 \bbl@localeinfo
3479 {\bbl@error{I've found no info for the current locale.\%
3480 The corresponding ini file has not been loaded\\%
3481 Perhaps it doesn't exist}%
3482 {See the manual for details.}}%
3483 {#1}%
3484 \fi}
3485 % \@namedef{bbl@info@name.locale}{lcname}
3486 \@namedef{bbl@info@tag.ini}{lini}
3487 \@namedef{bbl@info@name.english}{elname}
3488 \@namedef{bbl@info@name.opentype}{lname}
3489 \@namedef{bbl@info@tag.bcp47}{tbcp}
3490 \@namedef{bbl@info@language.tag.bcp47}{lbcp}
3491 \@namedef{bbl@info@tag.opentype}{lotf}
3492 \@namedef{bbl@info@script.name}{esname}
3493 \@namedef{bbl@info@script.name.opentype}{sname}
3494 \@namedef{bbl@info@script.tag.bcp47}{sbcp}
3495 \@namedef{bbl@info@script.tag.opentype}{sotf}
3496 \@namedef{bbl@info@region.tag.bcp47}{rbcp}
3497 \@namedef{bbl@info@variant.tag.bcp47}{vbcp}
3498 \@namedef{bbl@info@extension.t.tag.bcp47}{extt}
3499 \@namedef{bbl@info@extension.u.tag.bcp47}{extu}
3500 \@namedef{bbl@info@extension.x.tag.bcp47}{extx}

```

\LaTeX needs to know the BCP 47 codes for some features. For that, it expects `\BCPdata` to be defined. While language, region, script, and variant are recognized, extension.⟨s⟩ for singletons may change.

```

3501 \providecommand\BCPdata{}
3502 \ifx\renewcommand\@undefined\else % For plain. TODO. It's a quick fix
3503 \renewcommand\BCPdata[1]{\bbl@bcpdata@i#1\@empty}
3504 \def\bbl@bcpdata@i#1#2#3#4#5#6\@empty{%
3505 \@nameuse{str_if_eq:nnTF}{#1#2#3#4#5}{main.}%
3506 {\bbl@bcpdata@ii#6}\bbl@main@language}%
3507 {\bbl@bcpdata@ii#1#2#3#4#5#6}\@language}%
3508 \def\bbl@bcpdata@ii#1#2{%
3509 \bbl@ifunset{bbl@info@#1.tag.bcp47}%
3510 {\bbl@error{Unknown field '#1' in \string\BCPdata.\%
3511 Perhaps you misspelled it.}%
3512 {See the manual for details.}}%
3513 {\bbl@ifunset{bbl@csname bbl@info@#1.tag.bcp47\endcsname @#2}{}%
3514 {\bbl@cs{\csname bbl@info@#1.tag.bcp47\endcsname @#2}}}%
3515 \fi
3516 % Still somewhat hackish:
3517 \@namedef{bbl@info@casing.tag.bcp47}{casing}

```

With version 3.75 `\BabelEnsureInfo` is executed always, but there is an option to disable it.

```

3518 <<{*More package options}>> ≡
3519 \DeclareOption{ensureinfo=off}{}
3520 <</More package options>>
3521 %
3522 \let\bbl@ensureinfo\@gobble
3523 \newcommand\BabelEnsureInfo{%
3524 \ifx\InputIfFileExists\@undefined\else
3525 \def\bbl@ensureinfo##1{%
3526 \bbl@ifunset{bbl@lname@##1}{\bbl@load@info{##1}}{}}%
3527 \fi
3528 \bbl@foreach\bbl@loaded{%
3529 \let\bbl@ensuring\@empty % Flag used in a couple of babel-*.tex files
3530 \def\@language{##1}%
3531 \bbl@ensureinfo{##1}}}%
3532 \@ifpackagewith{babel}{ensureinfo=off}{}%
3533 {\AtEndOfPackage{% Test for plain.

```

```
3534 \ifx\@undefined\bbl@loaded\else\BabelEnsureInfo\fi}}
```

More general, but non-expandable, is `\getlocaleproperty`. To inspect every possible loaded ini, we define `\LocaleForEach`, where `\bbl@ini@loaded` is a comma-separated list of locales, built by `\bbl@read@ini`.

```
3535 \newcommand\getlocaleproperty{%
3536 \@ifstar\bbl@getproperty@s\bbl@getproperty@x}
3537 \def\bbl@getproperty@s#1#2#3{%
3538 \let#1\relax
3539 \def\bbl@elt##1##2##3{%
3540 \bbl@ifsamestring{##1/##2}{##3}%
3541 {\providecommand#1{##3}%
3542 \def\bbl@elt####1####2####3{}}%
3543 {}}%
3544 \bbl@cs{inidata@#2}}%
3545 \def\bbl@getproperty@x#1#2#3{%
3546 \bbl@getproperty@s{#1}{#2}{#3}%
3547 \ifx#1\relax
3548 \bbl@error
3549 {Unknown key for locale '#2':\%
3550 #3\%
3551 \string#1 will be set to \relax}%
3552 {Perhaps you misspelled it.}%
3553 \fi}
3554 \let\bbl@ini@loaded\@empty
3555 \newcommand\LocaleForEach{\bbl@foreach\bbl@ini@loaded}
```

8 Adjusting the Babel behavior

A generic high level interface is provided to adjust some global and general settings.

```
3556 \newcommand\babeladjust[1]{% TODO. Error handling.
3557 \bbl@forkv{#1}{%
3558 \bbl@ifunset{\bbl@ADJ@##1@##2}%
3559 {\bbl@cs{ADJ@##1}{##2}}%
3560 {\bbl@cs{ADJ@##1@##2}}}
3561 %
3562 \def\bbl@adjust@lua#1#2{%
3563 \ifvmode
3564 \ifnum\currentgrouplevel=\z@
3565 \directlua{ Babel.#2 }%
3566 \expandafter\expandafter\expandafter@gobble
3567 \fi
3568 \fi
3569 {\bbl@error % The error is gobbled if everything went ok.
3570 {Currently, #1 related features can be adjusted only\%
3571 in the main vertical list.}%
3572 {Maybe things change in the future, but this is what it is.}}}
3573 \@namedef{\bbl@ADJ@bidi.mirroring@on}{%
3574 \bbl@adjust@lua{bidi}{mirroring_enabled=true}}
3575 \@namedef{\bbl@ADJ@bidi.mirroring@off}{%
3576 \bbl@adjust@lua{bidi}{mirroring_enabled=false}}
3577 \@namedef{\bbl@ADJ@bidi.text@on}{%
3578 \bbl@adjust@lua{bidi}{bidi_enabled=true}}
3579 \@namedef{\bbl@ADJ@bidi.text@off}{%
3580 \bbl@adjust@lua{bidi}{bidi_enabled=false}}
3581 \@namedef{\bbl@ADJ@bidi.math@on}{%
3582 \let\bbl@noamsmath\@empty}
3583 \@namedef{\bbl@ADJ@bidi.math@off}{%
3584 \let\bbl@noamsmath\relax}
3585 \@namedef{\bbl@ADJ@bidi.mapdigits@on}{%
3586 \bbl@adjust@lua{bidi}{digits_mapped=true}}
3587 \@namedef{\bbl@ADJ@bidi.mapdigits@off}{%
```



```

3588 \bbl@adjust@lua{bidi}{digits_mapped=false}}
3589 %
3590 \@namedef{bbl@ADJ@linebreak.sea@on}{%
3591 \bbl@adjust@lua{linebreak}{sea_enabled=true}}
3592 \@namedef{bbl@ADJ@linebreak.sea@off}{%
3593 \bbl@adjust@lua{linebreak}{sea_enabled=false}}
3594 \@namedef{bbl@ADJ@linebreak.cjk@on}{%
3595 \bbl@adjust@lua{linebreak}{cjk_enabled=true}}
3596 \@namedef{bbl@ADJ@linebreak.cjk@off}{%
3597 \bbl@adjust@lua{linebreak}{cjk_enabled=false}}
3598 \@namedef{bbl@ADJ@justify.arabic@on}{%
3599 \bbl@adjust@lua{linebreak}{arabic.justify_enabled=true}}
3600 \@namedef{bbl@ADJ@justify.arabic@off}{%
3601 \bbl@adjust@lua{linebreak}{arabic.justify_enabled=false}}
3602 %
3603 \def\bbl@adjust@layout#1{%
3604 \ifvmode
3605 #1%
3606 \expandafter\@gobble
3607 \fi
3608 {\bbl@error % The error is gobbled if everything went ok.
3609 {Currently, layout related features can be adjusted only\\%
3610 in vertical mode.}%
3611 {Maybe things change in the future, but this is what it is.}}}
3612 \@namedef{bbl@ADJ@layout.tabular@on}{%
3613 \ifnum\bbl@tabular@mode=\tw@
3614 \bbl@adjust@layout{\let\@tabular\bbl@NL@tabular}%
3615 \else
3616 \chardef\bbl@tabular@mode\@ne
3617 \fi}
3618 \@namedef{bbl@ADJ@layout.tabular@off}{%
3619 \ifnum\bbl@tabular@mode=\tw@
3620 \bbl@adjust@layout{\let\@tabular\bbl@OL@tabular}%
3621 \else
3622 \chardef\bbl@tabular@mode\z@
3623 \fi}
3624 \@namedef{bbl@ADJ@layout.lists@on}{%
3625 \bbl@adjust@layout{\let\list\bbl@NL@list}}
3626 \@namedef{bbl@ADJ@layout.lists@off}{%
3627 \bbl@adjust@layout{\let\list\bbl@OL@list}}
3628 %
3629 \@namedef{bbl@ADJ@autoload.bcp47@on}{%
3630 \bbl@bcpallowedtrue}
3631 \@namedef{bbl@ADJ@autoload.bcp47@off}{%
3632 \bbl@bcpallowedfalse}
3633 \@namedef{bbl@ADJ@autoload.bcp47.prefix}#1{%
3634 \def\bbl@bcp@prefix{#1}}
3635 \def\bbl@bcp@prefix{bcp47-}
3636 \@namedef{bbl@ADJ@autoload.options}#1{%
3637 \def\bbl@autoload@options{#1}}
3638 \let\bbl@autoload@bcptoptions\@empty
3639 \@namedef{bbl@ADJ@autoload.bcp47.options}#1{%
3640 \def\bbl@autoload@bcptoptions{#1}}
3641 \newif\ifbbl@bcptoname
3642 \@namedef{bbl@ADJ@bcp47.toname@on}{%
3643 \bbl@bcptonametrue}
3644 \BabelEnsureInfo}
3645 \@namedef{bbl@ADJ@bcp47.toname@off}{%
3646 \bbl@bcptonamefalse}
3647 \@namedef{bbl@ADJ@prehyphenation.disable@nohyphenation}{%
3648 \directlua{ Babel.ignore_pre_char = function(node)
3649 return (node.lang == \the\csname l@nohyphenation\endcsname)
3650 end }}

```

```

3651 \@namedef{bbl@ADJ@prehyphenation.disable@off}{%
3652   \directlua{ Babel.ignore_pre_char = function(node)
3653     return false
3654   end }}
3655 \@namedef{bbl@ADJ@select.write@shift}{%
3656   \let\bbl@restorelastskip\relax
3657   \def\bbl@savelastskip{%
3658     \let\bbl@restorelastskip\relax
3659     \ifvmode
3660       \ifdim\lastskip=\z@
3661         \let\bbl@restorelastskip\nobreak
3662       \else
3663         \bbl@exp{%
3664           \def\\bbl@restorelastskip{%
3665             \skip@=\the\lastskip
3666             \\nobreak \vskip-\skip@ \vskip\skip@}}%
3667         \fi
3668       \fi}}
3669 \@namedef{bbl@ADJ@select.write@keep}{%
3670   \let\bbl@restorelastskip\relax
3671   \let\bbl@savelastskip\relax}
3672 \@namedef{bbl@ADJ@select.write@omit}{%
3673   \AddBabelHook{babel-select}{beforestart}{%
3674     \expandafter\babel@aux\expandafter{\bbl@main@language}}}%
3675   \let\bbl@restorelastskip\relax
3676   \def\bbl@savelastskip##1\bbl@restorelastskip{}}
3677 \@namedef{bbl@ADJ@select.encoding@off}{%
3678   \let\bbl@encoding@select@off@empty}

```

As the final task, load the code for lua. TODO: use babel name, override

```

3679 \ifx\directlua\@undefined\else
3680   \ifx\bbl@luapatterns\@undefined
3681     \input luababel.def
3682   \fi
3683 \fi

```

Continue with \LaTeX .

```

3684 </package | core>
3685 <*package>

```

8.1 Cross referencing macros

The \LaTeX book states:

The *key* argument is any sequence of letters, digits, and punctuation symbols; upper- and lowercase letters are regarded as different.

When the above quote should still be true when a document is typeset in a language that has active characters, special care has to be taken of the category codes of these characters when they appear in an argument of the cross referencing macros.

When a cross referencing command processes its argument, all tokens in this argument should be character tokens with category ‘letter’ or ‘other’.

The following package options control which macros are to be redefined.

```

3686 <(*More package options)> ≡
3687 \DeclareOption{safe=none}{\let\bbl@opt@safe\@empty}
3688 \DeclareOption{safe=bib}{\def\bbl@opt@safe{B}}
3689 \DeclareOption{safe=ref}{\def\bbl@opt@safe{R}}
3690 \DeclareOption{safe=refbib}{\def\bbl@opt@safe{BR}}
3691 \DeclareOption{safe=bibref}{\def\bbl@opt@safe{BR}}
3692 <\/More package options>

```

`\@newl@bel` First we open a new group to keep the changed setting of `\protect` local and then we set the `@safe@actives` switch to true to make sure that any shorthand that appears in any of the arguments immediately expands to its non-active self.

```

3693 \bbl@trace{Cross referencing macros}
3694 \ifx\bbl@opt@safe\empty\else % ie, if 'ref' and/or 'bib'
3695   \def\@newl@bel#1#2#3{%
3696     {\@safe@activetrue
3697       \bbl@ifunset{#1@#2}%
3698       \relax
3699       {\gdef\@multiplelabels{%
3700         \@latex@warning@no@line{There were multiply-defined labels}}}%
3701         \@latex@warning@no@line{Label `#2' multiply defined}}}%
3702   \global\@namedef{#1@#2}{#3}}

```

\@testdef An internal \TeX macro used to test if the labels that have been written on the .aux file have changed. It is called by the \enddocument macro.

```

3703   \CheckCommand*\@testdef[3]{%
3704     \def\reserved@a{#3}%
3705     \expandafter\ifx\csname#1@#2\endcsname\reserved@a
3706     \else
3707       \@tempswatrue
3708     \fi}

```

Now that we made sure that \@testdef still has the same definition we can rewrite it. First we make the shorthands ‘safe’. Then we use \bbl@tempa as an ‘alias’ for the macro that contains the label which is being checked. Then we define \bbl@tempb just as \@newl@bel does it. When the label is defined we replace the definition of \bbl@tempa by its meaning. If the label didn’t change, \bbl@tempa and \bbl@tempb should be identical macros.

```

3709   \def\@testdef#1#2#3{% TODO. With @samestring?
3710     \@safe@activetrue
3711     \expandafter\let\expandafter\bbl@tempa\csname #1@#2\endcsname
3712     \def\bbl@tempb{#3}%
3713     \@safe@activetrue
3714     \ifx\bbl@tempa\relax
3715     \else
3716       \edef\bbl@tempa{\expandafter\strip@prefix\meaning\bbl@tempa}%
3717     \fi
3718     \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
3719     \ifx\bbl@tempa\bbl@tempb
3720     \else
3721       \@tempswatrue
3722     \fi}
3723 \fi

```

\ref The same holds for the macro \ref that references a label and \pageref to reference a page. We \pageref make them robust as well (if they weren’t already) to prevent problems if they should become expanded at the wrong moment.

```

3724 \bbl@xin@{R}\bbl@opt@safe
3725 \ifin@
3726   \edef\bbl@tempc{\expandafter\string\csname ref code\endcsname}%
3727   \bbl@xin@{\expandafter\strip@prefix\meaning\bbl@tempc}%
3728   {\expandafter\strip@prefix\meaning\ref}%
3729   \ifin@
3730   \bbl@redefine\@kernel@ref#1{%
3731     \@safe@activetrue\org@@kernel@ref{#1}\@safe@activetrue}
3732   \bbl@redefine\@kernel@pageref#1{%
3733     \@safe@activetrue\org@@kernel@pageref{#1}\@safe@activetrue}
3734   \bbl@redefine\@kernel@sref#1{%
3735     \@safe@activetrue\org@@kernel@sref{#1}\@safe@activetrue}
3736   \bbl@redefine\@kernel@spageref#1{%
3737     \@safe@activetrue\org@@kernel@spageref{#1}\@safe@activetrue}
3738   \else
3739     \bbl@redefineroobust\ref#1{%
3740       \@safe@activetrue\org@ref{#1}\@safe@activetrue}
3741     \bbl@redefineroobust\pageref#1{%
3742       \@safe@activetrue\org@pageref{#1}\@safe@activetrue}

```

```

3743 \fi
3744 \else
3745 \let\org@ref\ref
3746 \let\org@pageref\pageref
3747 \fi

```

`\@citex` The macro used to cite from a bibliography, `\cite`, uses an internal macro, `\@citex`. It is this internal macro that picks up the argument(s), so we redefine this internal macro and leave `\cite` alone. The first argument is used for typesetting, so the shorthands need only be deactivated in the second argument.

```

3748 \bbl@xin@{B}\bbl@opt@safe
3749 \ifin@
3750 \bbl@redefine\@citex[#1]#2{%
3751 \@safe@activetrue\edef\@tempa{#2}\@safe@activesfalse
3752 \org@@citex[#1]{\@tempa}}

```

Unfortunately, the packages `natbib` and `cite` need a different definition of `\@citex`... To begin with, `natbib` has a definition for `\@citex` with *three* arguments... We only know that a package is loaded when `\begin{document}` is executed, so we need to postpone the different redefinition.

```

3753 \AtBeginDocument{%
3754 \ifpackageloaded{natbib}{%

```

Notice that we use `\def` here instead of `\bbl@redefine` because `\org@@citex` is already defined and we don't want to overwrite that definition (it would result in parameter stack overflow because of a circular definition).

(Recent versions of `natbib` change dynamically `\@citex`, so PR4087 doesn't seem fixable in a simple way. Just load `natbib` before.)

```

3755 \def\@citex[#1][#2]#3{%
3756 \@safe@activetrue\edef\@tempa{#3}\@safe@activesfalse
3757 \org@@citex[#1][#2]{\@tempa}}%
3758 }{}

```

The package `cite` has a definition of `\@citex` where the shorthands need to be turned off in both arguments.

```

3759 \AtBeginDocument{%
3760 \ifpackageloaded{cite}{%
3761 \def\@citex[#1]#2{%
3762 \@safe@activetrue\org@@citex[#1][#2]\@safe@activesfalse}%
3763 }{}

```

`\nocite` The macro `\nocite` which is used to instruct `BiBTeX` to extract uncited references from the database.

```

3764 \bbl@redefine\nocite#1{%
3765 \@safe@activetrue\org@nocite{#1}\@safe@activesfalse}

```

`\bibcite` The macro that is used in the `.aux` file to define citation labels. When packages such as `natbib` or `cite` are not loaded its second argument is used to typeset the citation label. In that case, this second argument can contain active characters but is used in an environment where `\@safe@activetrue` is in effect. This switch needs to be reset inside the `\hbox` which contains the citation label. In order to determine during `.aux` file processing which definition of `\bibcite` is needed we define `\bbl@bibcite` in such a way that it redefines itself with the proper definition. We call `\bbl@cite@choice` to select the proper definition for `\bbl@bibcite`. This new definition is then activated.

```

3766 \bbl@redefine\bbl@bibcite{%
3767 \bbl@cite@choice
3768 \bbl@bibcite}

```

`\bbl@bibcite` The macro `\bbl@bibcite` holds the definition of `\bbl@bibcite` needed when neither `natbib` nor `cite` is loaded.

```

3769 \def\bbl@bibcite#1#2{%
3770 \org@bibcite{#1}{\@safe@activesfalse#2}}

```

`\bbl@cite@choice` The macro `\bbl@cite@choice` determines which definition of `\bbl@bibcite` is needed. First we give `\bbl@bibcite` its default definition.

```

3771 \def\bbl@cite@choice{%
3772   \global\let\bibcite\bbl@bibcite
3773   \ifpackageloaded{natbib}{\global\let\bibcite\org@bibcite}{}%
3774   \ifpackageloaded{cite}{\global\let\bibcite\org@bibcite}{}%
3775   \global\let\bbl@cite@choice\relax}

```

When a document is run for the first time, no .aux file is available, and \bibcite will not yet be properly defined. In this case, this has to happen before the document starts.

```

3776 \AtBeginDocument{\bbl@cite@choice}

```

\@bibitem One of the two internal \TeX macros called by \bibitem that write the citation label on the .aux file.

```

3777 \bbl@redefine\@bibitem#1{%
3778   \@safe@activetrue\org@@bibitem{#1}\@safe@activesfalse}
3779 \else
3780   \let\org@nocite\nocite
3781   \let\org@@citex\@citex
3782   \let\org@bibcite\bibcite
3783   \let\org@@bibitem\@bibitem
3784 \fi

```

8.2 Marks

\markright Because the output routine is asynchronous, we must pass the current language attribute to the head lines. To achieve this we need to adapt the definition of \markright and \markboth somewhat. However, headlines and footlines can contain text outside marks; for that we must take some actions in the output routine if the 'headfoot' options is used. We need to make some redefinitions to the output routine to avoid an endless loop and to correctly handle the page number in bidi documents.

```

3785 \bbl@trace{Marks}
3786 \IfBabelLayout{sectioning}
3787   {\ifx\bbl@opt@headfoot\@nnil
3788     \g@addto@macro\resetactivechars{%
3789       \set@typeset@protect
3790       \expandafter\select@language@x\expandafter{\bbl@main@language}%
3791       \let\protect\noexpand
3792       \ifcase\bbl@bidimode\else % Only with bidi. See also above
3793         \edef\thepage{%
3794           \noexpand\babelsublr{\unexpanded\expandafter{\thepage}}}%
3795       \fi}%
3796   \fi}
3797 {\ifbbl@single\else
3798   \bbl@ifunset{markright }{\bbl@redefine\bbl@redefineroobust
3799     \markright#1{%
3800       \bbl@ifblank{#1}%
3801       {\org@markright{}}}%
3802       {\toks@{#1}%
3803        \bbl@exp{%
3804          \org@markright{\protect\foreignlanguage{\language}\thepage}%
3805          {\protect\bbl@restore@actives\the\toks@}}}%

```

\markboth The definition of \markboth is equivalent to that of \markright, except that we need two token registers. The documentclasses report and book define and set the headings for the page. While doing so they also store a copy of \markboth in \@mkboth. Therefore we need to check whether \@mkboth has already been set. If so we need to do that again with the new definition of \markboth. (As of Oct 2019, \TeX stores the definition in an intermediate macro, so it's not necessary anymore, but it's preserved for older versions.)

```

3806   \ifx\@mkboth\markboth
3807     \def\bbl@tempc{\let\@mkboth\markboth}%
3808   \else
3809     \def\bbl@tempc{}%
3810   \fi
3811   \bbl@ifunset{markboth }{\bbl@redefine\bbl@redefineroobust

```

```

3812 \markboth#1#2{%
3813 \protected@edef\bbl@tempb##1{%
3814 \protect\foreignlanguage
3815 {\language\name}\protect\bbl@restore@actives##1}}%
3816 \bbl@ifblank{#1}%
3817 {\toks@{}}%
3818 {\toks@\expandafter{\bbl@tempb{#1}}}%
3819 \bbl@ifblank{#2}%
3820 {\@temptokena{}}%
3821 {\@temptokena\expandafter{\bbl@tempb{#2}}}%
3822 \bbl@exp{\org@markboth{\the\toks@}{\the\@temptokena}}}%
3823 \bbl@tempc
3824 \fi} % end ifbbl@single, end \IfBabelLayout

```

8.3 Preventing clashes with other packages

8.3.1 ifthen

`\ifthenelse` Sometimes a document writer wants to create a special effect depending on the page a certain fragment of text appears on. This can be achieved by the following piece of code:

```

\ifthenelse{\isodd{\pageref{some:label}}}
{code for odd pages}
{code for even pages}

```

In order for this to work the argument of `\isodd` needs to be fully expandable. With the above redefinition of `\pageref` it is not in the case of this example. To overcome that, we add some code to the definition of `\ifthenelse` to make things work.

We want to revert the definition of `\pageref` and `\ref` to their original definition for the first argument of `\ifthenelse`, so we first need to store their current meanings.

Then we can set the `\@safe@actives` switch and call the original `\ifthenelse`. In order to be able to use shorthands in the second and third arguments of `\ifthenelse` the resetting of the switch *and* the definition of `\pageref` happens inside those arguments.

```

3825 \bbl@trace{Preventing clashes with other packages}
3826 \ifx\org@ref\undefined\else
3827 \bbl@xin@{R}\bbl@opt@safe
3828 \ifin@
3829 \AtBeginDocument{%
3830 \ifpackageloaded{ifthen}{%
3831 \bbl@redefine@long\ifthenelse#1#2#3{%
3832 \let\bbl@temp@pref\pageref
3833 \let\pageref\org@pageref
3834 \let\bbl@temp@ref\ref
3835 \let\ref\org@ref
3836 \@safe@activestrue
3837 \org@ifthenelse{#1}%
3838 {\let\pageref\bbl@temp@pref
3839 \let\ref\bbl@temp@ref
3840 \@safe@activesfalse
3841 #2}%
3842 {\let\pageref\bbl@temp@pref
3843 \let\ref\bbl@temp@ref
3844 \@safe@activesfalse
3845 #3}%
3846 }%
3847 }}%
3848 }
3849 \fi

```

8.3.2 varioref

`\@vpageref` When the package `varioref` is in use we need to modify its internal command `\@vpageref` in order
`\vrefpagenum` to prevent problems when an active character ends up in the argument of `\vref`. The same needs to
`\Ref`

happen for \vrefpagenum.

```

3850 \AtBeginDocument{%
3851   \@ifpackageloaded{varioref}{%
3852     \bbl@redefine\@vpageref#1[#2]#3{%
3853       \@safe@activetrue
3854       \org@@vpageref{#1}[#2]#3}%
3855     \@safe@activesfalse}%
3856   \bbl@redefine\vrefpagenum#1#2{%
3857     \@safe@activetrue
3858     \org@vrefpagenum{#1}#2}%
3859   \@safe@activesfalse}%

```

The package varioref defines \Ref to be a robust command wich uppercases the first character of the reference text. In order to be able to do that it needs to access the expandable form of \ref. So we employ a little trick here. We redefine the (internal) command \Ref_␣ to call \org@ref instead of \ref. The disadvantage of this solution is that whenever the definition of \Ref changes, this definition needs to be updated as well.

```

3860   \expandafter\def\csname Ref \endcsname#1{%
3861     \protected@edef\@tempa{\org@ref{#1}}\expandafter\MakeUppercase\@tempa}
3862   }{}%
3863 }
3864 \fi

```

8.3.3 hhline

\hhline Delaying the activation of the shorthand characters has introduced a problem with the hhline package. The reason is that it uses the ‘:’ character which is made active by the french support in babel. Therefore we need to *reload* the package when the ‘:’ is an active character. Note that this happens *after* the category code of the @-sign has been changed to other, so we need to temporarily change it to letter again.

```

3865 \AtEndOfPackage{%
3866   \AtBeginDocument{%
3867     \@ifpackageloaded{hhline}%
3868     {\expandafter\ifx\csname normal@char\string\endcsname\relax
3869       \else
3870         \makeatletter
3871         \def\@currname{hhline}\input{hhline.sty}\makeatother
3872       \fi}%
3873     {}}

```

\substitutefontfamily Deprecated. Use the tools provides by L^AT_EX. The command \substitutefontfamily creates an .fd file on the fly. The first argument is an encoding mnemonic, the second and third arguments are font family names.

```

3874 \def\substitutefontfamily#1#2#3{%
3875   \lowercase{\immediate\openout15=#1#2.fd\relax}%
3876   \immediate\write15{%
3877     \string\ProvidesFile{#1#2.fd}%
3878     [\the\year/\two@digits\the\month]/\two@digits\the\day}
3879   \space generated font description file^^J
3880   \string\DeclareFontFamily{#1}{#2}{}^^J
3881   \string\DeclareFontShape{#1}{#2}{m}{n}{<->ssub * #3/m/n}{}^^J
3882   \string\DeclareFontShape{#1}{#2}{m}{it}{<->ssub * #3/m/it}{}^^J
3883   \string\DeclareFontShape{#1}{#2}{m}{sl}{<->ssub * #3/m/sl}{}^^J
3884   \string\DeclareFontShape{#1}{#2}{m}{sc}{<->ssub * #3/m/sc}{}^^J
3885   \string\DeclareFontShape{#1}{#2}{b}{n}{<->ssub * #3/bx/n}{}^^J
3886   \string\DeclareFontShape{#1}{#2}{b}{it}{<->ssub * #3/bx/it}{}^^J
3887   \string\DeclareFontShape{#1}{#2}{b}{sl}{<->ssub * #3/bx/sl}{}^^J
3888   \string\DeclareFontShape{#1}{#2}{b}{sc}{<->ssub * #3/bx/sc}{}^^J
3889   }%
3890   \closeout15
3891 }
3892 \@onlypreamble\substitutefontfamily

```

8.4 Encoding and fonts

Because documents may use non-ASCII font encodings, we make sure that the logos of \TeX and \LaTeX always come out in the right encoding. There is a list of non-ASCII encodings. Requested encodings are currently stored in `\@fontenc@load@list`. If a non-ASCII has been loaded, we define versions of \TeX and \LaTeX for them using `\ensureascii`. The default ASCII encoding is set, too (in reverse order): the “main” encoding (when the document begins), the last loaded, or OT1.

`\ensureascii`

```

3893 \bbl@trace{Encoding and fonts}
3894 \newcommand\BabelNonASCII{LGR,X2,OT2,OT3,OT6,LHE,LWN,LMA,LMC,LMS,LMU}
3895 \newcommand\BabelNonText{TS1,T3,TS3}
3896 \let\org@TeX\TeX
3897 \let\org@LaTeX\LaTeX
3898 \let\ensureascii\@firstofone
3899 \AtBeginDocument{%
3900   \def\@elt#1{,#1,}%
3901   \edef\bbl@tempa{\expandafter\@gobbletwo\@fontenc@load@list}%
3902   \let\@elt\relax
3903   \let\bbl@tempb\@empty
3904   \def\bbl@tempc{OT1}%
3905   \bbl@foreach\BabelNonASCII{% LGR loaded in a non-standard way
3906     \bbl@ifunset{T@#1}{\def\bbl@tempb{#1}}}%
3907   \bbl@foreach\bbl@tempa{%
3908     \bbl@xin@{#1}{\BabelNonASCII}%
3909     \ifin@
3910       \def\bbl@tempb{#1}% Store last non-ascii
3911     \else\bbl@xin@{#1}{\BabelNonText}% Pass
3912       \ifin@
3913       \def\bbl@tempc{#1}% Store last ascii
3914     \fi
3915   \fi}%
3916   \ifx\bbl@tempb\@empty\else
3917     \bbl@xin@{\cf@encoding,}{\BabelNonASCII,\BabelNonText,}%
3918     \ifin@
3919     \edef\bbl@tempc{\cf@encoding}% The default if ascii wins
3920   \fi
3921   \edef\ensureascii#1{%
3922     {\noexpand\fontencoding{\bbl@tempc}\noexpand\selectfont#1}}%
3923   \DeclareTextCommandDefault{\TeX}{\ensureascii\org@TeX}%
3924   \DeclareTextCommandDefault{\LaTeX}{\ensureascii\org@LaTeX}%
3925   \fi}

```

Now comes the old deprecated stuff (with a little change in 3.9l, for fontspec). The first thing we need to do is to determine, at `\begin{document}`, which latin fontencoding to use.

`\latinencoding` When text is being typeset in an encoding other than ‘latin’ (OT1 or T1), it would be nice to still have Roman numerals come out in the Latin encoding. So we first assume that the current encoding at the end of processing the package is the Latin encoding.

```

3926 \AtEndOfPackage{\edef\latinencoding{\cf@encoding}}

```

But this might be overruled with a later loading of the package `fontenc`. Therefore we check at the execution of `\begin{document}` whether it was loaded with the T1 option. The normal way to do this (using `\ifpackageloaded`) is disabled for this package. Now we have to revert to parsing the internal macro `\@filelist` which contains all the filenames loaded.

```

3927 \AtBeginDocument{%
3928   \ifpackageloaded{fontspec}%
3929   {\xdef\latinencoding{%
3930     \ifx\UTFencname\@undefined
3931       EU\ifcase\bbl@engine\or2\or1\fi
3932     \else
3933       \UTFencname
3934     \fi}}%
3935   {\gdef\latinencoding{OT1}%

```



```

3936 \ifx\cf@encoding\bbl@t@one
3937 \xdef\latinencoding{\bbl@t@one}%
3938 \else
3939 \def\@elt#1{, #1,}%
3940 \edef\bbl@tempa{\expandafter\@gobbletwo\@fontenc@load@list}%
3941 \let\@elt\relax
3942 \bbl@xin@{, T1, }\bbl@tempa
3943 \ifin@
3944 \xdef\latinencoding{\bbl@t@one}%
3945 \fi
3946 \fi}}

```

`\latintext` Then we can define the command `\latintext` which is a declarative switch to a latin font-encoding. Usage of this macro is deprecated.

```

3947 \DeclareRobustCommand{\latintext}{%
3948 \fontencoding{\latinencoding}\selectfont
3949 \def\encodingdefault{\latinencoding}}

```

`\textlatin` This command takes an argument which is then typeset using the requested font encoding. In order to avoid many encoding switches it operates in a local scope.

```

3950 \ifx\@undefined\DeclareTextFontCommand
3951 \DeclareRobustCommand{\textlatin}[1]{\leavevmode{\latintext #1}}
3952 \else
3953 \DeclareTextFontCommand{\textlatin}{\latintext}
3954 \fi

```

For several functions, we need to execute some code with `\selectfont`. With \LaTeX 2021-06-01, there is a hook for this purpose.

```

3955 \def\bbl@patchfont#1{\AddToHook{selectfont}{#1}}

```

8.5 Basic bidi support

Work in progress. This code is currently placed here for practical reasons. It will be moved to the correct place soon, I hope.

It is loosely based on `rlbabel.def`, but most of it has been developed from scratch. This `babel` module (by Johannes Braams and Boris Lavva) has served the purpose of typesetting R documents for two decades, and despite its flaws I think it is still a good starting point (some parts have been copied here almost verbatim), partly thanks to its simplicity. I’ve also looked at `ARABI` (by Youssef Jabri), which is compatible with `babel`.

There are two ways of modifying macros to make them “bidi”, namely, by patching the internal low-level macros (which is what I have done with lists, columns, counters, tocs, much like `rlbabel` did), and by introducing a “middle layer” just below the user interface (sectioning, footnotes).

- `pdfTeX` provides a minimal support for bidi text, and it must be done by hand. Vertical typesetting is not possible.
- `xetex` is somewhat better, thanks to its font engine (even if not always reliable) and a few additional tools. However, very little is done at the paragraph level. Another challenging problem is text direction does not honour \TeX grouping.
- `luatex` can provide the most complete solution, as we can manipulate almost freely the node list, the generated lines, and so on, but bidi text does not work out of the box and some development is necessary. It also provides tools to properly set left-to-right and right-to-left page layouts. As `Lua \TeX -ja` shows, vertical typesetting is possible, too.

```

3956 \bbl@trace{Loading basic (internal) bidi support}
3957 \ifodd\bbl@engine
3958 \else % TODO. Move to txtbabel
3959 \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200
3960 \bbl@error
3961 {The bidi method 'basic' is available only in\%
3962 luatex. I'll continue with 'bidi=default', so\%
3963 expect wrong results}%
3964 {See the manual for further details.}%
3965 \let\bbl@beforeforeign\leavevmode

```

```

3966 \AtEndOfPackage{%
3967     \EnableBabelHook{babel-bidi}%
3968     \bbl@xebidipar}
3969 \fi\fi
3970 \def\bbl@loadxebidi#1{%
3971     \ifx\RTLfootnotetext\@undefined
3972         \AtEndOfPackage{%
3973             \EnableBabelHook{babel-bidi}%
3974             \bbl@loadfontspec % bidi needs fontspec
3975             \usepackage#1{bidi}}%
3976         \fi}
3977 \ifnum\bbl@bidimode>200
3978     \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
3979         \bbl@tentative{bidi=bidi}
3980         \bbl@loadxebidi{}
3981     \or
3982         \bbl@loadxebidi{[rldocument]}
3983     \or
3984         \bbl@loadxebidi{}
3985     \fi
3986 \fi
3987 \fi
3988 % TODO? Separate:
3989 \ifnum\bbl@bidimode=\@ne
3990     \let\bbl@beforeforeign\leavevmode
3991     \ifodd\bbl@engine
3992         \newattribute\bbl@attr@dir
3993         \directlua{ Babel.attr_dir = luatexbase.registernumber'bbl@attr@dir' }
3994         \bbl@exp{\output{\bodydir\pagedir\the\output}}
3995     \fi
3996 \AtEndOfPackage{%
3997     \EnableBabelHook{babel-bidi}%
3998     \ifodd\bbl@engine\else
3999         \bbl@xebidipar
4000     \fi}
4001 \fi

```

Now come the macros used to set the direction when a language is switched. First the (mostly) common macros.

```

4002 \bbl@trace{Macros to switch the text direction}
4003 \def\bbl@alscripts{,Arabic,Syriac,Thaana,}
4004 \def\bbl@rscripts{% TODO. Base on codes ??
4005     ,Imperial Aramaic,Avestan,Cypriot,Hatran,Hebrew,%
4006     Old Hungarian,Lydian,Mandaean,Manichaeen,%
4007     Meroitic Cursive,Meroitic,Old North Arabian,%
4008     Nabataean,N'Ko,Orkhon,Palmyrene,Inscriptional Pahlavi,%
4009     Psalter Pahlavi,Phoenician,Inscriptional Parthian,Samaritan,%
4010     Old South Arabian,}%
4011 \def\bbl@provide@dirs#1{%
4012     \bbl@xin@{\csname bbl@sname@#1\endcsname}{\bbl@alscripts\bbl@rscripts}%
4013     \ifin@
4014         \global\bbl@csarg\chardef{wdir@#1}\@ne
4015         \bbl@xin@{\csname bbl@sname@#1\endcsname}{\bbl@alscripts}%
4016         \ifin@
4017             \global\bbl@csarg\chardef{wdir@#1}\tw@ % useless in xetex
4018         \fi
4019     \else
4020         \global\bbl@csarg\chardef{wdir@#1}\z@
4021     \fi
4022 \ifodd\bbl@engine
4023     \bbl@csarg\ifcase{wdir@#1}%
4024     \directlua{ Babel.locale_props[\the\localeid].texmdir = 'l' }%
4025     \or

```

```

4026 \directlua{ Babel.locale_props[\the\localeid].texdir = 'r' }%
4027 \or
4028 \directlua{ Babel.locale_props[\the\localeid].texdir = 'al' }%
4029 \fi
4030 \fi}
4031 \def\bbl@switchdir{%
4032 \bbl@ifunset{bbl@lsys@\languagename}{\bbl@provide@lsys{\languagename}}{}%
4033 \bbl@ifunset{bbl@wdir@\languagename}{\bbl@provide@dirs{\languagename}}{}%
4034 \bbl@exp{\bbl@setdirs\bbl@cl{wdir}}%
4035 \def\bbl@setdirs#1{% TODO - math
4036 \ifcase\bbl@select@type % TODO - strictly, not the right test
4037 \bbl@bodydir{#1}%
4038 \bbl@pardir{#1}% <- Must precede \bbl@texdir
4039 \fi
4040 \bbl@texdir{#1}}
4041 % TODO. Only if \bbl@bidimode > 0?:
4042 \AddBabelHook{babel-bidi}{afterextras}{\bbl@switchdir}
4043 \DisableBabelHook{babel-bidi}

```

Now the engine-dependent macros. TODO. Must be moved to the engine files.

```

4044 \ifodd\bbl@engine % luatex=1
4045 \else % pdftex=0, xetex=2
4046 \newcount\bbl@dirlevel
4047 \chardef\bbl@thetexdir\z@
4048 \chardef\bbl@thepardir\z@
4049 \def\bbl@texdir#1{%
4050 \ifcase#1\relax
4051 \chardef\bbl@thetexdir\z@
4052 \bbl@texdir@i\beginL\endL
4053 \else
4054 \chardef\bbl@thetexdir@ne
4055 \bbl@texdir@i\beginR\endR
4056 \fi}
4057 \def\bbl@texdir@i#1#2{%
4058 \ifhmode
4059 \ifnum\currentgrouplevel>\z@
4060 \ifnum\currentgrouplevel=\bbl@dirlevel
4061 \bbl@error{Multiple bidi settings inside a group}%
4062 {I'll insert a new group, but expect wrong results.}%
4063 \bgroup\aftergroup#2\aftergroup\egroup
4064 \else
4065 \ifcase\currentgrouptype\or % 0 bottom
4066 \aftergroup#2% 1 simple {}
4067 \or
4068 \bgroup\aftergroup#2\aftergroup\egroup % 2 hbox
4069 \or
4070 \bgroup\aftergroup#2\aftergroup\egroup % 3 adj hbox
4071 \or\or\or % vbox vtop align
4072 \or
4073 \bgroup\aftergroup#2\aftergroup\egroup % 7 noalign
4074 \or\or\or\or\or\or % output math disc insert vcent mathchoice
4075 \or
4076 \aftergroup#2% 14 \begingroup
4077 \else
4078 \bgroup\aftergroup#2\aftergroup\egroup % 15 adj
4079 \fi
4080 \fi
4081 \bbl@dirlevel\currentgrouplevel
4082 \fi
4083 #1%
4084 \fi}
4085 \def\bbl@pardir#1{\chardef\bbl@thepardir#1\relax}
4086 \let\bbl@bodydir@gobble

```

```

4087 \let\bbl@pagedir\@gobble
4088 \def\bbl@dirparastext{\chardef\bbl@thepardir\bbl@thetextdir}

```

The following command is executed only if there is a right-to-left script (once). It activates the `\everypar` hack for xetex, to properly handle the par direction. Note text and par dirs are decoupled to some extent (although not completely).

```

4089 \def\bbl@xebidipar{%
4090   \let\bbl@xebidipar\relax
4091   \TeXeTstate\@ne
4092   \def\bbl@xeeverypar{%
4093     \ifcase\bbl@thepardir
4094       \ifcase\bbl@thetextdir\else\beginR\fi
4095     \else
4096       {\setbox\z@\lastbox\beginR\box\z@}%
4097     \fi}%
4098   \let\bbl@severypar\everypar
4099   \newtoks\everypar
4100   \everypar=\bbl@severypar
4101   \bbl@severypar{\bbl@xeeverypar\the\everypar}}
4102 \ifnum\bbl@bidimode>200
4103   \let\bbl@textdir@i\@gobbletwo
4104   \let\bbl@xebidipar\@empty
4105   \AddBabelHook{bidi}{foreign}{%
4106     \def\bbl@tempa{\def\BabelText####1}%
4107     \ifcase\bbl@thetextdir
4108       \expandafter\bbl@tempa\expandafter{\BabelText{\LR{##1}}}%
4109     \else
4110       \expandafter\bbl@tempa\expandafter{\BabelText{\RL{##1}}}%
4111     \fi}
4112   \def\bbl@pardir#1{\ifcase#1\relax\setLR\else\setRL\fi}
4113 \fi
4114 \fi

```

A tool for weak L (mainly digits). We also disable warnings with hyperref.

```

4115 \DeclareRobustCommand\babelsublr[1]{\leavevmode{\bbl@textdir\z@#1}}
4116 \AtBeginDocument{%
4117   \ifx\pdfstringdefDisableCommands\@undefined\else
4118     \ifx\pdfstringdefDisableCommands\relax\else
4119       \pdfstringdefDisableCommands{\let\babelsublr\@firstofone}%
4120     \fi
4121   \fi}

```

8.6 Local Language Configuration

`\loadlocalcfg` At some sites it may be necessary to add site-specific actions to a language definition file. This can be done by creating a file with the same name as the language definition file, but with the extension `.cfg`. For instance the file `norsk.cfg` will be loaded when the language definition file `norsk.ldf` is loaded.

For plain-based formats we don't want to override the definition of `\loadlocalcfg` from `plain.def`.

```

4122 \bbl@trace{Local Language Configuration}
4123 \ifx\loadlocalcfg\@undefined
4124   \@ifpackagewith{babel}{noconfigs}%
4125   {\let\loadlocalcfg\@gobble}%
4126   {\def\loadlocalcfg#1{%
4127     \InputIfFileExists{#1.cfg}%
4128     {\typeout{*****^J%
4129               * Local config file #1.cfg used^^J%
4130             *}}%
4131     \@empty}}
4132 \fi

```

8.7 Language options

Languages are loaded when processing the corresponding option *except* if a main language has been set. In such a case, it is not loaded until all options has been processed. The following macro inputs the ldf file and does some additional checks (\input works, too, but possible errors are not caught).

```

4133 \bbl@trace{Language options}
4134 \let\bbl@afterlang\relax
4135 \let\BabelModifiers\relax
4136 \let\bbl@loaded\@empty
4137 \def\bbl@load@language#1{%
4138   \InputIfFileExists{#1.ldf}%
4139   {\edef\bbl@loaded{\CurrentOption
4140     \ifx\bbl@loaded\@empty\else,\bbl@loaded\fi}%
4141     \expandafter\let\expandafter\bbl@afterlang
4142     \csname\CurrentOption.ldf-h@k\endcsname
4143     \expandafter\let\expandafter\BabelModifiers
4144     \csname bbl@mod@\CurrentOption\endcsname
4145     \bbl@exp{\AtBeginDocument{%
4146       \bbl@usehooks@lang{\CurrentOption}{\begin{document}}{\CurrentOption}}}%
4147     {\bbl@error{%
4148       Unknown option '\CurrentOption'. Either you misspelled it\\%
4149       or the language definition file \CurrentOption.ldf was not found}}%
4150     Valid options are, among others: shorthands=, KeepShorthandsActive,\\%
4151     activeacute, activegrave, noconfigs, safe=, main=, math=\\%
4152     headfoot=, strings=, config=, hyphenmap=, or a language name.}}}
```

Now, we set a few language options whose names are different from ldf files. These declarations are preserved for backwards compatibility, but they must be eventually removed. Use proxy files instead.

```

4153 \def\bbl@try@load@lang#1#2#3{%
4154   \IfFileExists{\CurrentOption.ldf}%
4155   {\bbl@load@language{\CurrentOption}}%
4156   {#1\bbl@load@language{#2}#3}}
4157 %
4158 \DeclareOption{hebrew}{%
4159   \input{rlbabel.def}%
4160   \bbl@load@language{hebrew}}
4161 \DeclareOption{hungarian}{\bbl@try@load@lang{}{magyar}{}}
4162 \DeclareOption{lowersorbian}{\bbl@try@load@lang{}{lsorbian}{}}
4163 \DeclareOption{nynorsk}{\bbl@try@load@lang{}{norsk}{}}
4164 \DeclareOption{polutonikogreek}{%
4165   \bbl@try@load@lang{}{greek}{\languageattribute{greek}{polutoniko}}}
4166 \DeclareOption{russian}{\bbl@try@load@lang{}{russianb}{}}
4167 \DeclareOption{ukrainian}{\bbl@try@load@lang{}{ukraineb}{}}
4168 \DeclareOption{uppersorbian}{\bbl@try@load@lang{}{usorbian}{}}
```

Another way to extend the list of ‘known’ options for babel was to create the file `bblopts.cfg` in which one can add option declarations. However, this mechanism is deprecated – if you want an alternative name for a language, just create a new .ldf file loading the actual one. You can also set the name of the file with the package option `config=<name>`, which will load `<name>.cfg` instead.

```

4169 \ifx\bbl@opt@config\@nnil
4170   \@ifpackagewith{babel}{noconfigs}{}%
4171   {\InputIfFileExists{bblopts.cfg}%
4172     {\typeout{*****^J%
4173       * Local config file bblopts.cfg used^^J%
4174       *}}%
4175     {}}%
4176 \else
4177   \InputIfFileExists{\bbl@opt@config.cfg}%
4178   {\typeout{*****^J%
4179     * Local config file \bbl@opt@config.cfg used^^J%
4180     *}}%
4181   {\bbl@error{%
4182     Local config file '\bbl@opt@config.cfg' not found}}%
```

```

4183     Perhaps you misspelled it.}}%
4184 \fi

```

Recognizing global options in packages not having a closed set of them is not trivial, as for them to be processed they must be defined explicitly. So, package options not yet taken into account and stored in `\bbl@language@opts` are assumed to be languages. If not declared above, the names of the option and the file are the same. We first pre-process the class and package options to determine the main language, which is processed in the third ‘main’ pass, *except* if all files are `ldf` *and* there is no main key. In the latter case (`\bbl@opt@main` is still `\@nnil`), the traditional way to set the main language is kept — the last loaded is the main language.

```

4185 \ifx\bbl@opt@main\@nnil
4186   \ifnum\bbl@iniflag>\z@ % if all ldf's: set implicitly, no main pass
4187     \let\bbl@tempb\@empty
4188     \edef\bbl@tempa{\@classoptionslist,\bbl@language@opts}%
4189     \bbl@foreach\bbl@tempa{\edef\bbl@tempb{#1,\bbl@tempb}}%
4190     \bbl@foreach\bbl@tempb{%       \bbl@tempb is a reversed list
4191       \ifx\bbl@opt@main\@nnil % ie, if not yet assigned
4192         \ifodd\bbl@iniflag % = *=
4193           \IfFileExists{babel-#1.tex}{\def\bbl@opt@main{#1}}}%
4194         \else % n +=
4195           \IfFileExists{#1.ldf}{\def\bbl@opt@main{#1}}}%
4196       \fi
4197     \fi}%
4198 \fi
4199 \else
4200   \bbl@info{Main language set with 'main='. Except if you have\\%
4201             problems, prefer the default mechanism for setting\\%
4202             the main language, ie, as the last declared.\\%
4203             Reported}%
4204 \fi

```

A few languages are still defined explicitly. They are stored in case they are needed in the ‘main’ pass (the value can be `\relax`).

```

4205 \ifx\bbl@opt@main\@nnil\else
4206   \bbl@ncarg\let\bbl@loadmain{ds@\bbl@opt@main}%
4207   \expandafter\let\csname ds@\bbl@opt@main\endcsname\relax
4208 \fi

```

Now define the corresponding loaders. With package options, assume the language exists. With class options, check if the option is a language by checking if the correspondin file exists.

```

4209 \bbl@foreach\bbl@language@opts{%
4210   \def\bbl@tempa{#1}%
4211   \ifx\bbl@tempa\bbl@opt@main\else
4212     \ifnum\bbl@iniflag<\tw@ % 0 0 (other = ldf)
4213       \bbl@ifunset{ds@#1}%
4214       {\DeclareOption{#1}{\bbl@load@language{#1}}}%
4215       {}%
4216     \else % + * (other = ini)
4217       \DeclareOption{#1}{%
4218         \bbl@ldfinit
4219         \babelprovide[import]{#1}%
4220         \bbl@afterldf}}%
4221     \fi
4222   \fi}%
4223 \bbl@foreach\@classoptionslist{%
4224   \def\bbl@tempa{#1}%
4225   \ifx\bbl@tempa\bbl@opt@main\else
4226     \ifnum\bbl@iniflag<\tw@ % 0 0 (other = ldf)
4227       \bbl@ifunset{ds@#1}%
4228       {\IfFileExists{#1.ldf}%
4229        {\DeclareOption{#1}{\bbl@load@language{#1}}}%
4230        {}}%
4231       {}%
4232     \else % + * (other = ini)

```

```

4233     \IfFileExists{babel-#1.tex}%
4234     {\DeclareOption{#1}{%
4235         \bbl@ldfinit
4236         \babelprovide[import]{#1}%
4237         \bbl@afterldf{}}}%
4238     }%
4239     \fi
4240 \fi}

```

And we are done, because all options for this pass has been declared. Those already processed in the first pass are just ignored.

The options have to be processed in the order in which the user specified them (but remember class options are processed before):

```

4241 \def\AfterBabelLanguage#1{%
4242     \bbl@ifsamestring\CurrentOption{#1}{\global\bbl@add\bbl@afterlang}{}}
4243 \DeclareOption*{}
4244 \ProcessOptions*

```

This finished the second pass. Now the third one begins, which loads the main language set with the key main. A warning is raised if the main language is not the same as the last named one, or if the value of the key main is not a language. With some options in provide, the package luatexbase is loaded (and immediately used), and therefore \babelprovide can't go inside a \DeclareOption; this explains why it's executed directly, with a dummy declaration. Then all languages have been loaded, so we deactivate \AfterBabelLanguage.

```

4245 \bbl@trace{Option 'main'}
4246 \ifx\bbl@opt@main\@nnil
4247     \edef\bbl@tempa{\@classoptionslist,\bbl@language@opts}
4248     \let\bbl@tempc\@empty
4249     \edef\bbl@templ{\bbl@loaded,}
4250     \edef\bbl@templ{\expandafter\strip@prefix\meaning\bbl@templ}
4251     \bbl@for\bbl@tempb\bbl@tempa{%
4252         \edef\bbl@tempd{\bbl@tempb,}%
4253         \edef\bbl@tempd{\expandafter\strip@prefix\meaning\bbl@tempd}%
4254         \bbl@xin@{\bbl@tempd}{\bbl@templ}%
4255         \ifin@edef\bbl@tempc{\bbl@tempb}\fi}
4256     \def\bbl@tempa#1,#2\@nnil{\def\bbl@tempb{#1}}
4257     \expandafter\bbl@tempa\bbl@loaded,\@nnil
4258     \ifx\bbl@tempb\bbl@tempc\else
4259         \bbl@warning{%
4260             Last declared language option is '\bbl@tempc',\%
4261             but the last processed one was '\bbl@tempb'.\%
4262             The main language can't be set as both a global\%
4263             and a package option. Use 'main=\bbl@tempc' as\%
4264             option. Reported}
4265     \fi
4266 \else
4267     \ifodd\bbl@iniflag % case 1,3 (main is ini)
4268         \bbl@ldfinit
4269         \let\CurrentOption\bbl@opt@main
4270         \bbl@exp{% \bbl@opt@provide = empty if *
4271             \\\babelprovide[\bbl@opt@provide,import,main]{\bbl@opt@main}}%
4272         \bbl@afterldf{}
4273         \DeclareOption{\bbl@opt@main}{}
4274     \else % case 0,2 (main is ldf)
4275         \ifx\bbl@loadmain\relax
4276             \DeclareOption{\bbl@opt@main}{\bbl@load@language{\bbl@opt@main}}
4277         \else
4278             \DeclareOption{\bbl@opt@main}{\bbl@loadmain}
4279         \fi
4280         \ExecuteOptions{\bbl@opt@main}
4281         \@namedef{ds@\bbl@opt@main}{}%
4282     \fi
4283     \DeclareOption*{}
4284     \ProcessOptions*

```

```

4285 \fi
4286 \bbl@exp{%
4287   \\\AtBeginDocument{\bbl@usehooks@lang{/}{\begindocument}{}}}%
4288 \def\AfterBabelLanguage{%
4289   \bbl@error
4290     {Too late for \string\AfterBabelLanguage}%
4291     {Languages have been loaded, so I can do nothing}}

```

In order to catch the case where the user didn't specify a language we check whether `\bbl@main@language`, has become defined. If not, the `nil` language is loaded.

```

4292 \ifx\bbl@main@language\undefined
4293   \bbl@info{%
4294     You haven't specified a language as a class or package\%
4295     option. I'll load 'nil'. Reported}
4296     \bbl@load@language{nil}
4297 \fi
4298 \</package>

```

9 The kernel of Babel (`babel.def`, `common`)

The kernel of the babel system is currently stored in `babel.def`. The file `babel.def` contains most of the code. The file `hyphen.cfg` is a file that can be loaded into the format, which is necessary when you want to be able to switch hyphenation patterns.

Because plain \TeX users might want to use some of the features of the babel system too, care has to be taken that plain \TeX can process the files. For this reason the current format will have to be checked in a number of places. Some of the code below is common to plain \TeX and \LaTeX , some of it is for the \LaTeX case only.

Plain formats based on `etex` (`etex`, `xetex`, `luatex`) don't load `hyphen.cfg` but `etex.src`, which follows a different naming convention, so we need to define the babel names. It presumes `language.def` exists and it is the same file used when formats were created.

A proxy file for `switch.def`

```

4299 \<*kernel>
4300 \let\bbl@onlyswitch\@empty
4301 \input babel.def
4302 \let\bbl@onlyswitch\@undefined
4303 \</kernel>
4304 \<*patterns>

```

10 Loading hyphenation patterns

The following code is meant to be read by $\text{ini}\TeX$ because it should instruct \TeX to read hyphenation patterns. To this end the `docstrip` option `patterns` is used to include this code in the file `hyphen.cfg`. Code is written with lower level macros.

```

4305 \<\Make sure ProvidesFile is defined>
4306 \ProvidesFile{hyphen.cfg}[\<\date>\<\version>\<Babel hyphens>]
4307 \xdef\bbl@format{\jobname}
4308 \def\bbl@version{\<\version>}
4309 \def\bbl@date{\<\date>}
4310 \ifx\AtBeginDocument\@undefined
4311   \def\@empty{}
4312 \fi
4313 \<\Define core switching macros>

```

`\process@line` Each line in the file `language.dat` is processed by `\process@line` after it is read. The first thing this macro does is to check whether the line starts with `=`. When the first token of a line is an `=`, the macro `\process@synonym` is called; otherwise the macro `\process@language` will continue.

```

4314 \def\process@line#1#2 #3 #4 {%
4315   \ifx=#1%
4316     \process@synonym{#2}%
4317   \else
4318     \process@language{#1#2}{#3}{#4}%

```



```

4319 \fi
4320 \ignorespaces}

```

`\process@synonym` This macro takes care of the lines which start with an `=`. It needs an empty token register to begin with. `\bbl@languages` is also set to empty.

```

4321 \toks@{}
4322 \def\bbl@languages{}

```

When no languages have been loaded yet, the name following the `=` will be a synonym for hyphenation register 0. So, it is stored in a token register and executed when the first pattern file has been processed. (The `\relax` just helps to the `\if` below catching synonyms without a language.) Otherwise the name will be a synonym for the language loaded last. We also need to copy the `hyphenmins` parameters for the synonym.

```

4323 \def\process@synonym#1{%
4324   \ifnum\last@language=\m@ne
4325     \toks@\expandafter{\the\toks@\relax\process@synonym{#1}}%
4326   \else
4327     \expandafter\chardef\csname l@#1\endcsname\last@language
4328     \wlog{\string\l@#1=\string\language\the\last@language}%
4329     \expandafter\let\csname #1hyphenmins\expandafter\endcsname
4330       \csname\language\hyphenmins\endcsname
4331     \let\bbl@elt\relax
4332     \edef\bbl@languages{\bbl@languages\bbl@elt{#1}{\the\last@language}{}}%
4333   \fi}

```

`\process@language` The macro `\process@language` is used to process a non-empty line from the ‘configuration file’. It has three arguments, each delimited by white space. The first argument is the ‘name’ of a language; the second is the name of the file that contains the patterns. The optional third argument is the name of a file containing hyphenation exceptions.

The first thing to do is call `\addlanguage` to allocate a pattern register and to make that register ‘active’. Then the pattern file is read.

For some hyphenation patterns it is needed to load them with a specific font encoding selected. This can be specified in the file `language.dat` by adding for instance ‘:T1’ to the name of the language. The macro `\bbl@get@enc` extracts the font encoding from the language name and stores it in `\bbl@hyph@enc`. The latter can be used in hyphenation files if you need to set a behavior depending on the given encoding (it is set to empty if no encoding is given).

Pattern files may contain assignments to `\lefthyphenmin` and `\righthyphenmin`. \TeX does not keep track of these assignments. Therefore we try to detect such assignments and store them in the `\langle lang \rangle hyphenmins` macro. When no assignments were made we provide a default setting. Some pattern files contain changes to the `\lccode` en `\uccode` arrays. Such changes should remain local to the language; therefore we process the pattern file in a group; the `\patterns` command acts globally so its effect will be remembered.

Then we globally store the settings of `\lefthyphenmin` and `\righthyphenmin` and close the group. When the hyphenation patterns have been processed we need to see if a file with hyphenation exceptions needs to be read. This is the case when the third argument is not empty and when it does not contain a space token. (Note however there is no need to save hyphenation exceptions into the format.)

`\bbl@languages` saves a snapshot of the loaded languages in the form `\bbl@elt{\langle language-name \rangle}{\langle number \rangle}{\langle patterns-file \rangle}{\langle exceptions-file \rangle}`. Note the last 2 arguments are empty in ‘dialects’ defined in `language.dat` with `=`. Note also the language name can have encoding info.

Finally, if the counter `\language` is equal to zero we execute the synonyms stored.

```

4334 \def\process@language#1#2#3{%
4335   \expandafter\addlanguage\csname l@#1\endcsname
4336   \expandafter\language\csname l@#1\endcsname
4337   \edef\language\language{#1}%
4338   \bbl@hook@everylanguage{#1}%
4339   % > luatex
4340   \bbl@get@enc#1::\@@@
4341   \begingroup
4342     \lefthyphenmin\m@ne
4343     \bbl@hook@loadpatterns{#2}%
4344   % > luatex

```

```

4345 \ifnum\lefthyphenmin=\m@ne
4346 \else
4347 \expandafter\xdef\csname #1hyphenmins\endcsname{%
4348 \the\lefthyphenmin\the\righthyphenmin}%
4349 \fi
4350 \endgroup
4351 \def\bbl@tempa{#3}%
4352 \ifx\bbl@tempa\@empty\else
4353 \bbl@hook@loadexceptions{#3}%
4354 % > luatex
4355 \fi
4356 \let\bbl@elt\relax
4357 \edef\bbl@languages{%
4358 \bbl@languages\bbl@elt{#1}{\the\language}{#2}{\bbl@tempa}}%
4359 \ifnum\the\language=\z@
4360 \expandafter\ifx\csname #1hyphenmins\endcsname\relax
4361 \set@hyphenmins\tw@\thr@\relax
4362 \else
4363 \expandafter\expandafter\expandafter\set@hyphenmins
4364 \csname #1hyphenmins\endcsname
4365 \fi
4366 \the\toks@
4367 \toks@{}%
4368 \fi}

```

\bbl@get@enc The macro \bbl@get@enc extracts the font encoding from the language name and stores it in \bbl@hyph@enc. It uses delimited arguments to achieve this.

```

4369 \def\bbl@get@enc#1:#2:#3\@@{\def\bbl@hyph@enc{#2}}

```

Now, hooks are defined. For efficiency reasons, they are dealt here in a special way. Besides luatex, format-specific configuration files are taken into account. loadkernel currently loads nothing, but define some basic macros instead.

```

4370 \def\bbl@hook@everylanguage#1{}
4371 \def\bbl@hook@loadpatterns#1{\input #1\relax}
4372 \let\bbl@hook@loadexceptions\bbl@hook@loadpatterns
4373 \def\bbl@hook@loadkernel#1{%
4374 \def\addlanguage{\csname newlanguage\endcsname}%
4375 \def\adddialect##1##2{%
4376 \global\chardef##1##2\relax
4377 \wlog{\string##1 = a dialect from \string\language##2}}%
4378 \def\iflanguage##1{%
4379 \expandafter\ifx\csname l@##1\endcsname\relax
4380 \nolanerr{##1}%
4381 \else
4382 \ifnum\csname l@##1\endcsname=\language
4383 \expandafter\expandafter\expandafter\@firstoftwo
4384 \else
4385 \expandafter\expandafter\expandafter\@secondoftwo
4386 \fi
4387 \fi}%
4388 \def\providehyphenmins##1##2{%
4389 \expandafter\ifx\csname ##1hyphenmins\endcsname\relax
4390 \namedef{##1hyphenmins}{##2}%
4391 \fi}%
4392 \def\set@hyphenmins##1##2{%
4393 \lefthyphenmin##1\relax
4394 \righthyphenmin##2\relax}%
4395 \def\selectlanguage{%
4396 \errhelp{Selecting a language requires a package supporting it}%
4397 \errmessage{Not loaded}}%
4398 \let\foreignlanguage\selectlanguage
4399 \let\otherlanguage\selectlanguage
4400 \expandafter\let\csname otherlanguage*\endcsname\selectlanguage

```

```

4401 \def\bbl@usehooks##1##2{% TODO. Temporary!!
4402 \def\setlocale{%
4403   \errhelp{Find an armchair, sit down and wait}%
4404   \errmessage{Not yet available}}%
4405 \let\uselocale\setlocale
4406 \let\locale\setlocale
4407 \let\selectlocale\setlocale
4408 \let\localename\setlocale
4409 \let\textlocale\setlocale
4410 \let\textlanguage\setlocale
4411 \let\languagetext\setlocale}
4412 \begingroup
4413 \def\AddBabelHook#1#2{%
4414   \expandafter\ifx\csname bbl@hook@#2\endcsname\relax
4415     \def\next{\toks1}%
4416     \else
4417       \def\next{\expandafter\gdef\csname bbl@hook@#2\endcsname####1}%
4418     \fi
4419     \next}
4420 \ifx\directlua\@undefined
4421   \ifx\XeTeXinputencoding\@undefined\else
4422     \input xebabel.def
4423   \fi
4424 \else
4425   \input luababel.def
4426 \fi
4427 \openin1 = babel-\bbl@format.cfg
4428 \ifeof1
4429 \else
4430   \input babel-\bbl@format.cfg\relax
4431 \fi
4432 \closein1
4433 \endgroup
4434 \bbl@hook@loadkernel{switch.def}

```

\readconfigfile The configuration file can now be opened for reading.

```

4435 \openin1 = language.dat

```

See if the file exists, if not, use the default hyphenation file hyphen.tex. The user will be informed about this.

```

4436 \def\languagename{english}%
4437 \ifeof1
4438   \message{I couldn't find the file language.dat,\space
4439     I will try the file hyphen.tex}
4440   \input hyphen.tex\relax
4441   \chardef\l@english\z@
4442 \else

```

Pattern registers are allocated using count register \last@language. Its initial value is 0. The definition of the macro \newlanguage is such that it first increments the count register and then defines the language. In order to have the first patterns loaded in pattern register number 0 we initialize \last@language with the value -1.

```

4443 \last@language\m@ne

```

We now read lines from the file until the end is found. While reading from the input, it is useful to switch off recognition of the end-of-line character. This saves us stripping off spaces from the contents of the control sequence.

```

4444 \loop
4445   \endlinechar\m@ne
4446   \read1 to \bbl@line
4447   \endlinechar\^^M

```

If the file has reached its end, exit from the loop here. If not, empty lines are skipped. Add 3 space characters to the end of `\bbl@line`. This is needed to be able to recognize the arguments of `\process@line` later on. The default language should be the very first one.

```

4448 \if T\ifeof1F\fi T\relax
4449 \ifx\bbl@line\@empty\else
4450 \edef\bbl@line{\bbl@line\space\space\space}%
4451 \expandafter\process@line\bbl@line\relax
4452 \fi
4453 \repeat

```

Check for the end of the file. We must reverse the test for `\ifeof` without `\else`. Then reactivate the default patterns, and close the configuration file.

```

4454 \begingroup
4455 \def\bbl@elt#1#2#3#4{%
4456 \global\language=#2\relax
4457 \gdef\language#1}%
4458 \def\bbl@elt##1##2##3##4{}}%
4459 \bbl@languages
4460 \endgroup
4461 \fi
4462 \closein1

```

We add a message about the fact that babel is loaded in the format and with which language patterns to the `\everyjob` register.

```

4463 \if/\the\toks@/\else
4464 \errhelp{language.dat loads no language, only synonyms}
4465 \errmessage{Orphan language synonym}
4466 \fi

```

Also remove some macros from memory and raise an error if `\toks@` is not empty. Finally load `switch.def`, but the latter is not required and the line inputting it may be commented out.

```

4467 \let\bbl@line\@undefined
4468 \let\process@line\@undefined
4469 \let\process@synonym\@undefined
4470 \let\process@language\@undefined
4471 \let\bbl@get@enc\@undefined
4472 \let\bbl@hyph@enc\@undefined
4473 \let\bbl@tempa\@undefined
4474 \let\bbl@hook@loadkernel\@undefined
4475 \let\bbl@hook@everylanguage\@undefined
4476 \let\bbl@hook@loadpatterns\@undefined
4477 \let\bbl@hook@loadexceptions\@undefined
4478 \</patterns>

```

Here the code for `iniTEX` ends.

11 Font handling with fontspec

Add the bidi handler just before `luaotfload`, which is loaded by default by LaTeX. Just in case, consider the possibility it has not been loaded. First, a couple of definitions related to bidi [misplaced].

```

4479 <<More package options>> ≡
4480 \chardef\bbl@bidimode\z@
4481 \DeclareOption{bidi=default}{\chardef\bbl@bidimode=\@ne}
4482 \DeclareOption{bidi=basic}{\chardef\bbl@bidimode=101 }
4483 \DeclareOption{bidi=basic-r}{\chardef\bbl@bidimode=102 }
4484 \DeclareOption{bidi=bidi}{\chardef\bbl@bidimode=201 }
4485 \DeclareOption{bidi=bidi-r}{\chardef\bbl@bidimode=202 }
4486 \DeclareOption{bidi=bidi-l}{\chardef\bbl@bidimode=203 }
4487 <</More package options>>

```

With explicit languages, we could define the font at once, but we don't. Just wait and see if the language is actually activated. `bbl@font` replaces hardcoded font names inside `\. . family` by the corresponding macro `\. . default`.

At the time of this writing, fontspec shows a warning about there are languages not available, which some people think refers to babel, even if there is nothing wrong. Here is hack to patch fontspec to avoid the misleading (and mostly useless) message.

```

4488 <(*Font selection)> ≡
4489 \bbl@trace{Font handling with fontspec}
4490 \ifx\ExplSyntaxOn\@undefined\else
4491   \def\bbl@fs@warn@nx#1#2{% \bbl@tempfs is the original macro
4492     \in@{,#1,}{,no-script,language-not-exist,}%
4493     \ifin@else\bbl@tempfs@nx{#1}{#2}\fi}
4494   \def\bbl@fs@warn@nxx#1#2#3{%
4495     \in@{,#1,}{,no-script,language-not-exist,}%
4496     \ifin@else\bbl@tempfs@nxx{#1}{#2}{#3}\fi}
4497   \def\bbl@loadfontspec{%
4498     \let\bbl@loadfontspec\relax
4499     \ifx\fontspec\@undefined
4500       \usepackage{fontspec}%
4501     \fi}%
4502 \fi
4503 \@onlypreamble\babelfont
4504 \newcommand\babelfont[2][{}]{% 1=langs/scripts 2=fam
4505   \bbl@foreach{#1}{%
4506     \expandafter\ifx\csname date##1\endcsname\relax
4507       \IfFileExists{babel-##1.tex}%
4508         {\babelprovide{##1}}%
4509       {}%
4510     \fi}%
4511   \edef\bbl@tempa{#1}%
4512   \def\bbl@tempb{#2}% Used by \bbl@bblfont
4513   \bbl@loadfontspec
4514   \EnableBabelHook{babel-fontspec}% Just calls \bbl@switchfont
4515   \bbl@bblfont}
4516 \newcommand\bbl@bblfont[2][{}]{% 1=features 2=fontname, @font=rm|sf|tt
4517   \bbl@ifunset{\bbl@tempb family}%
4518     {\bbl@providefam{\bbl@tempb}}%
4519     {}%
4520   % For the default font, just in case:
4521   \bbl@ifunset{\bbl@lsys@languagename}{\bbl@provide@lsys{languagename}}}%
4522   \expandafter\bbl@ifblank\expandafter{\bbl@tempa}%
4523     {\bbl@csarg\edef{\bbl@tempb dflt@}{<>{#1}{#2}}% save bbl@rmdflt@
4524     \bbl@exp{%
4525       \let<\bbl@tempb dflt@\languagename>\<\bbl@tempb dflt@>%
4526       \<\bbl@fontset<\bbl@tempb dflt@\languagename>%
4527         \<\bbl@tempb default>\<\bbl@tempb family>}}%
4528     {\bbl@foreach\bbl@tempa{% ie bbl@rmdflt@lang / *scrt
4529       \bbl@csarg\def{\bbl@tempb dflt@##1}{<>{#1}{#2}}}%

```

If the family in the previous command does not exist, it must be defined. Here is how:

```

4530 \def\bbl@providefam#1{%
4531   \bbl@exp{%
4532     \<\newcommand<#1default>{}% Just define it
4533     \<\bbl@add@list<\bbl@font@fams{#1}%
4534     \<\DeclareRobustCommand<#1family>{}%
4535     \<\not@math@alphabet<#1family>\relax
4536     % \<\prepare@family@series@update{#1}<#1default>% TODO. Fails
4537     \<\fontfamily<#1default>%
4538     \<\ifx>\<\UseHooks<\<\undefined<else>\<\UseHook{#1family}<\<fi>%
4539     \<\selectfont>%
4540     \<\DeclareTextFontCommand{\<text#1>}<#1family>}}%

```

The following macro is activated when the hook babel-fontspec is enabled. But before, we define a macro for a warning, which sets a flag to avoid duplicate them.

```

4541 \def\bbl@nostdfont#1{%
4542   \bbl@ifunset{\bbl@WFF@f@family}%

```

```

4543 {\bbl@csarg\gdef{WFF@\f@family}}}% Flag, to avoid dupl warns
4544 \bbl@infowarn{The current font is not a babel standard family:\%
4545 #1%
4546 \fontname\font\%
4547 There is nothing intrinsically wrong with this warning, and\%
4548 you can ignore it altogether if you do not need these\%
4549 families. But if they are used in the document, you should be\%
4550 aware 'babel' will not set Script and Language for them, so\%
4551 you may consider defining a new family with \string\babelfont.\%
4552 See the manual for further details about \string\babelfont.\%
4553 Reported}}
4554 {}}%
4555 \gdef\bbl@switchfont{%
4556 \bbl@ifunset{\bbl@sys@\languagename}{\bbl@provide@sys{\languagename}}}%
4557 \bbl@exp{% eg Arabic -> arabic
4558 \lowercase{\edef\bbl@tempa{\bbl@cl{sname}}}}%
4559 \bbl@foreach\bbl@font@fams{%
4560 \bbl@ifunset{\bbl@##1dflt@\languagename}% (1) language?
4561 {\bbl@ifunset{\bbl@##1dflt@*\bbl@tempa}% (2) from script?
4562 {\bbl@ifunset{\bbl@##1dflt@}% 2=F - (3) from generic?
4563 {}% 123=F - nothing!
4564 {\bbl@exp{% 3=T - from generic
4565 \global\let<\bbl@##1dflt@\languagename>%
4566 \<\bbl@##1dflt@>}}}%
4567 {\bbl@exp{% 2=T - from script
4568 \global\let<\bbl@##1dflt@\languagename>%
4569 \<\bbl@##1dflt@*\bbl@tempa>}}}%
4570 {}}% 1=T - language, already defined
4571 \def\bbl@tempa{\bbl@nostdfont{}}% TODO. Don't use \bbl@tempa
4572 \bbl@foreach\bbl@font@fams{% don't gather with prev for
4573 \bbl@ifunset{\bbl@##1dflt@\languagename}%
4574 {\bbl@cs{famrst@##1}%
4575 \global\bbl@csarg\let{famrst@##1}\relax}%
4576 {\bbl@exp{% order is relevant. TODO: but sometimes wrong!
4577 \\\bbl@add\\originalTeX{%
4578 \\\bbl@font@rst{\bbl@cl{##1dflt}}}%
4579 \<##1default>\<##1family>{##1}}}%
4580 \\\bbl@font@set<\bbl@##1dflt@\languagename>% the main part!
4581 \<##1default>\<##1family>}}}%
4582 \bbl@ifrestoring{\bbl@tempa}}%

```

The following is executed at the beginning of the aux file or the document to warn about fonts not defined with \babelfont.

```

4583 \ifx\f@family\undefined\else % if latex
4584 \ifcase\bbl@engine % if pdftex
4585 \let\bbl@cckstdfonts\relax
4586 \else
4587 \def\bbl@cckstdfonts{%
4588 \begingroup
4589 \global\let\bbl@cckstdfonts\relax
4590 \let\bbl@tempa\@empty
4591 \bbl@foreach\bbl@font@fams{%
4592 \bbl@ifunset{\bbl@##1dflt@}%
4593 {\@nameuse{##1family}%
4594 \bbl@csarg\gdef{WFF@\f@family}}}% Flag
4595 \bbl@exp{\\\bbl@add\\bbl@tempa{* \<##1family>= \f@family\\\%
4596 \space\space\fontname\font\\\}}}%
4597 \bbl@csarg\xdef{##1dflt@}{\f@family}%
4598 \expandafter\xdef\csname ##1default\endcsname{\f@family}}}%
4599 {}}%
4600 \ifx\bbl@tempa\@empty\else
4601 \bbl@infowarn{The following font families will use the default\%
4602 settings for all or some languages:\%

```

```

4603         \bbl@tempa
4604         There is nothing intrinsically wrong with it, but\\%
4605         'babel' will no set Script and Language, which could\\%
4606         be relevant in some languages. If your document uses\\%
4607         these families, consider redefining them with \string\babelfont.\\%
4608         Reported}%
4609     \fi
4610 \endgroup}
4611 \fi
4612 \fi

```

Now the macros defining the font with fontspec.

When there are repeated keys in fontspec, the last value wins. So, we just place the ini settings at the beginning, and user settings will take precedence. We must deactivate temporarily \bbl@mapselect because \selectfont is called internally when a font is defined.

```

4613 \def\bbl@font@set#1#2#3{% eg \bbl@rmdflt@lang \rmdefault \rmfamily
4614   \bbl@xin@{<>}{#1}%
4615   \ifin@
4616     \bbl@exp{\\bbl@fontspec@set\\#1\expandafter@gobbles#1\\#3}%
4617   \fi
4618   \bbl@exp{%
4619     \def\\#2{#1}% eg, \rmdefault{\bbl@rmdflt@lang}
4620     \\bbl@ifsamestring{#2}{\f@family}%
4621     {\\#3%
4622       \\bbl@ifsamestring{\f@series}{\bfdefault}{\\bfseries}{}}%
4623     \let\\bbl@tempa\relax}%
4624   {}}
4625 % TODO - next should be global?, but even local does its job. I'm
4626 % still not sure -- must investigate:
4627 \def\bbl@fontspec@set#1#2#3#4{% eg \bbl@rmdflt@lang fnt-opt fnt-nme \xxfamily
4628   \let\bbl@tempa\bbl@mapselect
4629   \let\bbl@mapselect\relax
4630   \let\bbl@temp@fam#4% eg, '\rmfamily', to be restored below
4631   \let#4@empty % Make sure \renewfontfamily is valid
4632   \bbl@exp{%
4633     \let\\bbl@temp@pfam\<\bbl@stripslash#4\space>% eg, '\rmfamily '
4634     \<keys_if_exist:nnF>{fontspec-opentype}{Script/\bbl@cl{sname}}}%
4635     {\newfontscript{\bbl@cl{sname}}{\bbl@cl{sotf}}}%
4636     \<keys_if_exist:nnF>{fontspec-opentype}{Language/\bbl@cl{lname}}}%
4637     {\newfontlanguage{\bbl@cl{lname}}{\bbl@cl{lotf}}}%
4638     \let\\bbl@tempfs@nx\<__fontspec_warning:nx>%
4639     \let\<__fontspec_warning:nx>\\bbl@fs@warn@nx
4640     \let\\bbl@tempfs@nxx\<__fontspec_warning:nxx>%
4641     \let\<__fontspec_warning:nxx>\\bbl@fs@warn@nxx
4642     \\renewfontfamily\\#4%
4643     [\bbl@cl{lsys},#2]{#3}% ie \bbl@exp{..}{#3}
4644   \bbl@exp{%
4645     \let\<__fontspec_warning:nx>\\bbl@tempfs@nx
4646     \let\<__fontspec_warning:nxx>\\bbl@tempfs@nxx}%
4647   \begingroup
4648     #4%
4649     \xdef#1{\f@family}% eg, \bbl@rmdflt@lang{FreeSerif(0)}
4650   \endgroup
4651   \let#4\bbl@temp@fam
4652   \bbl@exp{\let\<\bbl@stripslash#4\space>}\bbl@temp@pfam
4653   \let\bbl@mapselect\bbl@tempa}%

```

font@rst and famrst are only used when there is no global settings, to save and restore de previous families. Not really necessary, but done for optimization.

```

4654 \def\bbl@font@rst#1#2#3#4{%
4655   \bbl@csarg\def{famrst@#4}{\bbl@font@set{#1}#2#3}}

```

The default font families. They are eurocentric, but the list can be expanded easily with \babelfont.

```

4656 \def\bbl@font@fams{rm,sf,tt}

```

```
4657 <</Font selection>>
```

12 Hooks for XeTeX and LuaTeX

12.1 XeTeX

Unfortunately, the current encoding cannot be retrieved and therefore it is reset always to utf8, which seems a sensible default.

```
4658 <<{*Footnote changes}>> ≡
4659 \bbl@trace{Bidi footnotes}
4660 \ifnum\bbl@bidimode>\z@
4661   \def\bbl@footnote#1#2#3{%
4662     \@ifnextchar[%
4663       {\bbl@footnote@o{#1}{#2}{#3}}%
4664       {\bbl@footnote@x{#1}{#2}{#3}}}
4665   \long\def\bbl@footnote@x#1#2#3#4{%
4666     \bgroup
4667     \select@language@x{\bbl@main@language}%
4668     \bbl@fn@footnote{#2#1{\ignorespaces#4}#3}%
4669     \egroup}
4670   \long\def\bbl@footnote@o#1#2#3[#4]#5{%
4671     \bgroup
4672     \select@language@x{\bbl@main@language}%
4673     \bbl@fn@footnote[#4]{#2#1{\ignorespaces#5}#3}%
4674     \egroup}
4675   \def\bbl@footnotetext#1#2#3{%
4676     \@ifnextchar[%
4677       {\bbl@footnotetext@o{#1}{#2}{#3}}%
4678       {\bbl@footnotetext@x{#1}{#2}{#3}}}
4679   \long\def\bbl@footnotetext@x#1#2#3#4{%
4680     \bgroup
4681     \select@language@x{\bbl@main@language}%
4682     \bbl@fn@footnotetext{#2#1{\ignorespaces#4}#3}%
4683     \egroup}
4684   \long\def\bbl@footnotetext@o#1#2#3[#4]#5{%
4685     \bgroup
4686     \select@language@x{\bbl@main@language}%
4687     \bbl@fn@footnotetext[#4]{#2#1{\ignorespaces#5}#3}%
4688     \egroup}
4689   \def\BabelFootnote#1#2#3#4{%
4690     \ifx\bbl@fn@footnote\undefined
4691       \let\bbl@fn@footnote\footnote
4692     \fi
4693     \ifx\bbl@fn@footnotetext\undefined
4694       \let\bbl@fn@footnotetext\footnotetext
4695     \fi
4696     \bbl@ifblank{#2}%
4697       {\def#1{\bbl@footnote{\@firstofone}{#3}{#4}}
4698        \@namedef{\bbl@stripslash#1text}%
4699         {\bbl@footnotetext{\@firstofone}{#3}{#4}}}%
4700       {\def#1{\bbl@exp{\bbl@footnote{\foreignlanguage{#2}}}{#3}{#4}}%
4701        \@namedef{\bbl@stripslash#1text}%
4702         {\bbl@exp{\bbl@footnotetext{\foreignlanguage{#2}}}{#3}{#4}}}%
4703   \fi
4704 <</Footnote changes>>
```

Now, the code.

```
4705 <{*xetex}>
4706 \def\BabelStringsDefault{unicode}
4707 \let\xebbl@stop\relax
4708 \AddBabelHook{xetex}{encodedcommands}{%
4709   \def\bbl@tempa{#1}%

```



```

4710 \ifx\bbbl@tempa\@empty
4711 \XeTeXinputencoding"bytes"%
4712 \else
4713 \XeTeXinputencoding"#1"%
4714 \fi
4715 \def\xebbl@stop{\XeTeXinputencoding"utf8"}}
4716 \AddBabelHook{xetex}{stopcommands}{%
4717 \xebbl@stop
4718 \let\xebbl@stop\relax}
4719 \def\bbbl@intraspace#1 #2 #3\@@{%
4720 \bbbl@csarg\gdef{xersp@\languagename}%
4721 {\XeTeXlinebreakskip #1em plus #2em minus #3em\relax}}
4722 \def\bbbl@intrapenalty#1\@@{%
4723 \bbbl@csarg\gdef{xecipn@\languagename}%
4724 {\XeTeXlinebreakpenalty #1\relax}}
4725 \def\bbbl@provide@intraspace{%
4726 \bbbl@xin@{/s}{/\bbbl@cl{lnbrk}}%
4727 \ifin@ \else \bbbl@xin@{/c}{/\bbbl@cl{lnbrk}} \fi
4728 \ifin@
4729 \bbbl@ifunset{bbbl@intsp@\languagename}{}%
4730 {\expandafter\ifx\csname bbl@intsp@\languagename\endcsname\@empty\else
4731 \ifx\bbbl@KVP@intraspace\@nnil
4732 \bbbl@exp{%
4733 \\\bbbl@intraspace\bbbl@cl{intsp}\@@}%
4734 \fi
4735 \ifx\bbbl@KVP@intrapenalty\@nnil
4736 \bbbl@intrapenalty0\@@
4737 \fi
4738 \fi
4739 \ifx\bbbl@KVP@intraspace\@nnil\else % We may override the ini
4740 \expandafter\bbbl@intraspace\bbbl@KVP@intraspace\@@
4741 \fi
4742 \ifx\bbbl@KVP@intrapenalty\@nnil\else
4743 \expandafter\bbbl@intrapenalty\bbbl@KVP@intrapenalty\@@
4744 \fi
4745 \bbbl@exp{%
4746 % TODO. Execute only once (but redundant):
4747 \\\bbbl@add\<extras\languagename>{%
4748 \XeTeXlinebreaklocale "\bbbl@cl{tbcpr}"%
4749 \<bbbl@xersp@\languagename>%
4750 \<bbbl@xeipn@\languagename>%
4751 \\\bbbl@tglobal\<extras\languagename>%
4752 \\\bbbl@add\<noextras\languagename>{%
4753 \XeTeXlinebreaklocale ""}%
4754 \\\bbbl@tglobal\<noextras\languagename>%
4755 \ifx\bbbl@ispacesize\@undefined
4756 \gdef\bbbl@ispacesize{\bbbl@cl{xersp}}%
4757 \ifx\AtBeginDocument\@notprerr
4758 \expandafter\@secondoftwo % to execute right now
4759 \fi
4760 \AtBeginDocument{\bbbl@patchfont{\bbbl@ispacesize}}%
4761 \fi}%
4762 \fi}
4763 \ifx\DisableBabelHook\@undefined\endinput\fi
4764 \AddBabelHook{babel-fontspec}{afterextras}{\bbbl@switchfont}
4765 \AddBabelHook{babel-fontspec}{beforestart}{\bbbl@cckstdfonts}
4766 \DisableBabelHook{babel-fontspec}
4767 <Font selection>
4768 \def\bbbl@provide@extra#1{}
4769 </xetex>

```

12.2 Layout

Note elements like headlines and margins can be modified easily with packages like fancyhdr, typearea or titles, and geometry.
`\bbl@startskip` and `\bbl@endskip` are available to package authors. Thanks to the T_EX expansion mechanism the following constructs are valid: `\adim\bbl@startskip`, `\advance\bbl@startskip\adim`, `\bbl@startskip\adim`.
 Consider `txtbabel` as a shorthand for *tex-xet babel*, which is the bidi model in both pdf_{tex} and xet_{ex}.

```

4770 <*xetex | texxet>
4771 \providecommand\bbl@provide@intraspace{}
4772 \bbl@trace{Redefinitions for bidi layout}
4773 \def\bbl@sspre@caption{%
4774   \bbl@exp{\everyhbox{\bbl@texdir\bbl@cs{wdir@\bbl@main@language}}}}
4775 \ifx\bbl@opt@layout@nnil\else % if layout=..
4776 \def\bbl@startskip{\ifcase\bbl@thepardir\leftskip\else\rightskip\fi}
4777 \def\bbl@endskip{\ifcase\bbl@thepardir\rightskip\else\leftskip\fi}
4778 \ifx\bbl@beforeforeign\leavevmode % A poor test for bidi=
4779   \def\hangfrom#1{%
4780     \setbox\@tempboxa\hbox{#1}%
4781     \hangindent\ifcase\bbl@thepardir\wd\@tempboxa\else-\wd\@tempboxa\fi
4782     \noindent\box\@tempboxa}
4783 \def\raggedright{%
4784   \let\@centercr
4785   \bbl@startskip\z@skip
4786   \@rightskip\@flushglue
4787   \bbl@endskip\@rightskip
4788   \parindent\z@
4789   \parfillskip\bbl@startskip}
4790 \def\raggedleft{%
4791   \let\@centercr
4792   \bbl@startskip\@flushglue
4793   \bbl@endskip\z@skip
4794   \parindent\z@
4795   \parfillskip\bbl@endskip}
4796 \fi
4797 \IfBabelLayout{lists}
4798 {\bbl@sreplace\list
4799   {\@totalleftmargin\leftmargin}{\@totalleftmargin\bbl@listleftmargin}%
4800   \def\bbl@listleftmargin{%
4801     \ifcase\bbl@thepardir\leftmargin\else\rightmargin\fi}%
4802   \ifcase\bbl@engine
4803     \def\labelenumii{}\theenumii{)% pdftex doesn't reverse ()
4804     \def\p@enumiii{\p@enumii}\theenumii{)%
4805     \fi
4806     \bbl@sreplace\@verbatim
4807     {\leftskip\@totalleftmargin}%
4808     {\bbl@startskip\textwidth
4809       \advance\bbl@startskip-\linewidth}%
4810     \bbl@sreplace\@verbatim
4811     {\rightskip\z@skip}%
4812     {\bbl@endskip\z@skip}}%
4813 {}
4814 \IfBabelLayout{contents}
4815 {\bbl@sreplace\@dottedtocline{\leftskip}{\bbl@startskip}%
4816   \bbl@sreplace\@dottedtocline{\rightskip}{\bbl@endskip}}
4817 {}
4818 \IfBabelLayout{columns}
4819 {\bbl@sreplace\@outputdblcol{\hb@xt@\textwidth}{\bbl@outputbox}%
4820   \def\bbl@outputbox#1{%
4821     \hb@xt@\textwidth{%
4822       \hskip\columnwidth
4823       \hfil
4824       {\normalcolor\vrule \width\columnseprule}%

```

```

4825      \hfil
4826      \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
4827      \hskip-\textwidth
4828      \hb@xt@\columnwidth{\box\@outputbox \hss}%
4829      \hskip\columnsep
4830      \hskip\columnwidth}}}%
4831  {}
4832  <<Footnote changes>>
4833  \IfBabelLayout{footnotes}%
4834  {\BabelFootnote\footnote\languagename{}}}%
4835   \BabelFootnote\localfootnote\languagename{}}}%
4836   \BabelFootnote\mainfootnote{}}{}%
4837  {}

```

Implicitly reverses sectioning labels in bidi=basic, because the full stop is not in contact with L numbers any more. I think there must be a better way.

```

4838  \IfBabelLayout{counters*}%
4839  {\bbl@add\bbl@opt@layout{.counters.}%
4840   \AddToHook{shipout/before}{%
4841    \let\bbl@tempa\babelsublr
4842    \let\babelsublr\@firstofone
4843    \let\bbl@save@thepage\thepage
4844    \protected@edef\thepage{\thepage}%
4845    \let\babelsublr\bbl@tempa}%
4846   \AddToHook{shipout/after}{%
4847    \let\thepage\bbl@save@thepage}}}%
4848  \IfBabelLayout{counters}%
4849  {\let\bbl@latinarabic=\@arabic
4850   \def\@arabic#1{\babelsublr{\bbl@latinarabic#1}}}%
4851   \let\bbl@asciroman=\@roman
4852   \def\@roman#1{\babelsublr{\ensureascii{\bbl@asciroman#1}}}%
4853   \let\bbl@asciiRoman=\@Roman
4854   \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asciiRoman#1}}}}}%
4855  \fi % end if layout
4856  </xetex | texxet>

```

12.3 8-bit TeX

Which start just above, because some code is shared with xetex. Now, 8-bit specific stuff.

```

4857  <*texxet>
4858  \def\bbl@provide@extra#1{%
4859   % == auto-select encoding ==
4860   \ifx\bbl@encoding@select@off\@empty\else
4861     \bbl@ifunset{\bbl@encoding@#1}%
4862     {\def\@elt##1{,##1},}%
4863     \edef\bbl@tempe{\expandafter\@gobbletwo\@fontenc@load@list}%
4864     \count@\z@
4865     \bbl@foreach\bbl@tempe{%
4866       \def\bbl@tempd{##1}% Save last declared
4867       \advance\count@\@ne}%
4868     \ifnum\count@>\@ne
4869       \getlocaleproperty*\bbl@tempa{#1}{identification/encodings}%
4870       \ifx\bbl@tempa\relax \let\bbl@tempa\@empty \fi
4871       \bbl@replace\bbl@tempa{ },}%
4872       \global\bbl@csarg\let{encoding@#1}\@empty
4873       \bbl@xin@{,\bbl@tempd,}{,\bbl@tempa,}%
4874       \ifin\@else % if main encoding included in ini, do nothing
4875         \let\bbl@tempb\relax
4876         \bbl@foreach\bbl@tempa{%
4877           \ifx\bbl@tempb\relax
4878             \bbl@xin@{,##1,}{,\bbl@tempe,}%
4879             \ifin\@def\bbl@tempb{##1}\fi
4880           \fi}%

```

```

4881      \ifx\bb1@tempb\relax\else
4882      \bb1@exp{%
4883      \global\<bb1@add>\<bb1@preextras@#1>\<bb1@encoding@#1>}%
4884      \gdef\<bb1@encoding@#1>{%
4885      \\\babel@save\\f@encoding
4886      \\\bb1@add\\originalTeX{\selectfont}%
4887      \\\fontencoding{\bb1@tempb}%
4888      \\\selectfont}}%
4889      \fi
4890      \fi
4891      \fi}%
4892      }%
4893      \fi}
4894      \texp

```

12.4 LuaTeX

The loader for luatex is based solely on `language.dat`, which is read on the fly. The code shouldn't be executed when the format is build, so we check if `\AddBabelHook` is defined. Then comes a modified version of the loader in `hyphen.cfg` (without the `hyphenmins` stuff, which is under the direct control of `babel`).

The names `\l@<language>` are defined and take some value from the beginning because all `ldf` files assume this for the corresponding language to be considered valid, but patterns are not loaded (except the first one). This is done later, when the language is first selected (which usually means when the `ldf` finishes). If a language has been loaded, `\bb1@hyphendata@<num>` exists (with the names of the files read).

The default setup preloads the first language into the format. This is intended mainly for 'english', so that it's available without further intervention from the user. To avoid duplicating it, the following rule applies: if the "0th" language and the first language in `language.dat` have the same name then just ignore the latter. If there are new synonymous, they are added, but note if the language patterns have not been preloaded they won't at run time.

Other preloaded languages could be read twice, if they have been preloaded into the format. This is not optimal, but it shouldn't happen very often – with luatex patterns are best loaded when the document is typeset, and the "0th" language is preloaded just for backwards compatibility.

As of 1.1b, lua(e)tex is taken into account. Formerly, loading of patterns on the fly didn't work in this format, but with the new loader it does. Unfortunately, the format is not based on `babel`, and data could be duplicated, because languages are reassigned above those in the format (nothing serious, anyway). Note even with this format `language.dat` is used (under the principle of a single source), instead of `language.def`.

Of course, there is room for improvements, like tools to read and reassign languages, which would require modifying the language list, and better error handling.

We need catcode tables, but no format (targeted by `babel`) provide a command to allocate them (although there are packages like `ctablestack`). FIX - This isn't true anymore. For the moment, a dangerous approach is used - just allocate a high random number and cross the fingers. To complicate things, `etex.sty` changes the way languages are allocated.

This files is read at three places: (1) when `plain.def`, `babel.sty` starts, to read the list of available languages from `language.dat` (for the base option); (2) at `hyphen.cfg`, to modify some macros; (3) in the middle of `plain.def` and `babel.sty`, by `babel.def`, with the commands and other definitions for luatex (eg, `\babelpatterns`).

```

4895 \*luatex
4896 \ifx\AddBabelHook\@undefined % When plain.def, babel.sty starts
4897 \bb1@trace{Read language.dat}
4898 \ifx\bb1@readstream\@undefined
4899   \csname newread\endcsname\bb1@readstream
4900 \fi
4901 \begingroup
4902   \toks@{}
4903   \count@% 0=start, 1=0th, 2=normal
4904   \def\bb1@process@line#1#2 #3 #4 {%
4905     \ifx=#1%
4906       \bb1@process@synonym{#2}%
4907     \else
4908       \bb1@process@language{#1#2}{#3}{#4}%

```

```

4909 \fi
4910 \ignorespaces}
4911 \def\bbl@manylang{%
4912 \ifnum\bbl@last>\@ne
4913 \bbl@info{Non-standard hyphenation setup}%
4914 \fi
4915 \let\bbl@manylang\relax}
4916 \def\bbl@process@language#1#2#3{%
4917 \ifcase\count@
4918 \ifundefined{zth@#1}{\count@tw@}{\count@ne}%
4919 \or
4920 \count@tw@
4921 \fi
4922 \ifnum\count@=tw@
4923 \expandafter\addlanguage\csname l@#1\endcsname
4924 \language\allocationnumber
4925 \chardef\bbl@last\allocationnumber
4926 \bbl@manylang
4927 \let\bbl@elt\relax
4928 \xdef\bbl@languages{%
4929 \bbl@languages\bbl@elt{#1}{\the\language}{#2}{#3}}%
4930 \fi
4931 \the\toks@
4932 \toks@{}}
4933 \def\bbl@process@synonym@aux#1#2{%
4934 \global\expandafter\chardef\csname l@#1\endcsname#2\relax
4935 \let\bbl@elt\relax
4936 \xdef\bbl@languages{%
4937 \bbl@languages\bbl@elt{#1}{#2}{}}}%
4938 \def\bbl@process@synonym#1{%
4939 \ifcase\count@
4940 \toks@\expandafter{\the\toks@\relax\bbl@process@synonym{#1}}%
4941 \or
4942 \ifundefined{zth@#1}{\bbl@process@synonym@aux{#1}{0}}}%
4943 \else
4944 \bbl@process@synonym@aux{#1}{\the\bbl@last}%
4945 \fi}
4946 \ifx\bbl@languages\undefined % Just a (sensible?) guess
4947 \chardef\l@english\z@
4948 \chardef\l@USenglish\z@
4949 \chardef\bbl@last\z@
4950 \global\@namedef{bbl@hyphendata@0}{{hyphen.tex}}
4951 \gdef\bbl@languages{%
4952 \bbl@elt{english}{0}{hyphen.tex}}%
4953 \bbl@elt{USenglish}{0}{}}
4954 \else
4955 \global\let\bbl@languages@format\bbl@languages
4956 \def\bbl@elt#1#2#3#4{% Remove all except language 0
4957 \ifnum#2>\z@
4958 \noexpand\bbl@elt{#1}{#2}{#3}{#4}%
4959 \fi}%
4960 \xdef\bbl@languages{\bbl@languages}%
4961 \fi
4962 \def\bbl@elt#1#2#3#4{\@namedef{zth@#1}{}} % Define flags
4963 \bbl@languages
4964 \openin\bbl@readstream=language.dat
4965 \ifeof\bbl@readstream
4966 \bbl@warning{I couldn't find language.dat. No additional\%
4967 patterns loaded. Reported}%
4968 \else
4969 \loop
4970 \endlinechar\m@ne
4971 \read\bbl@readstream to \bbl@line

```

```

4972 \endlinechar\^^M
4973 \if T\ifeof\bbl@readstream F\fi T\relax
4974 \ifx\bbl@line\empty\else
4975 \edef\bbl@line{\bbl@line\space\space\space}%
4976 \expandafter\bbl@process@line\bbl@line\relax
4977 \fi
4978 \repeat
4979 \fi
4980 \closein\bbl@readstream
4981 \endgroup
4982 \bbl@trace{Macros for reading patterns files}
4983 \def\bbl@get@enc#1:#2:#3\@@{\def\bbl@hyph@enc{#2}}
4984 \ifx\babelcatcodetablenum\undefined
4985 \ifx\newcatcodetable\undefined
4986 \def\babelcatcodetablenum{5211}
4987 \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
4988 \else
4989 \newcatcodetable\babelcatcodetablenum
4990 \newcatcodetable\bbl@pattcodes
4991 \fi
4992 \else
4993 \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
4994 \fi
4995 \def\bbl@luapatterns#1#2{%
4996 \bbl@get@enc#1::\@@
4997 \setbox\z@\hbox\bgroup
4998 \begingroup
4999 \savecatcodetable\babelcatcodetablenum\relax
5000 \initcatcodetable\bbl@pattcodes\relax
5001 \catcodetable\bbl@pattcodes\relax
5002 \catcode\#=6 \catcode\$=3 \catcode\&=4 \catcode\^=7
5003 \catcode\_ =8 \catcode\{=1 \catcode\}=2 \catcode\~=13
5004 \catcode\@=11 \catcode\^^I=10 \catcode\^^J=12
5005 \catcode\<=12 \catcode\>=12 \catcode\*=12 \catcode\.=12
5006 \catcode\-=12 \catcode\/=12 \catcode\[=12 \catcode\]=12
5007 \catcode\`=12 \catcode\'=12 \catcode\"=12
5008 \input #1\relax
5009 \catcodetable\babelcatcodetablenum\relax
5010 \endgroup
5011 \def\bbl@tempa{#2}%
5012 \ifx\bbl@tempa\empty\else
5013 \input #2\relax
5014 \fi
5015 \egroup}%
5016 \def\bbl@patterns@lua#1{%
5017 \language=\expandafter\ifx\csname l@#1:\f@encoding\endcsname\relax
5018 \csname l@#1\endcsname
5019 \edef\bbl@tempa{#1}%
5020 \else
5021 \csname l@#1:\f@encoding\endcsname
5022 \edef\bbl@tempa{#1:\f@encoding}%
5023 \fi\relax
5024 \@namedef{luatexhyphen@loaded@the\language}{}% Temp
5025 \@ifundefined{bbl@hyphendata@the\language}%
5026 {\def\bbl@elt##1##2##3##4{%
5027 \ifnum##2=\csname l@bbl@tempa\endcsname % #2=spanish, dutch:OT1...
5028 \def\bbl@tempb{##3}%
5029 \ifx\bbl@tempb\empty\else % if not a synonymous
5030 \def\bbl@tempc{##3}{##4}%
5031 \fi
5032 \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
5033 \fi}%
5034 \bbl@languages

```

```

5035 \ifundefined{bbl@hyphendata@the\language}%
5036 {\bbl@info{No hyphenation patterns were set for\%
5037 language '\bbl@tempa'. Reported}}%
5038 {\expandafter\expandafter\expandafter\bbl@luapatterns
5039 \csname bbl@hyphendata@the\language\endcsname}}{}
5040 \endinput\fi
5041 % Here ends \ifx\AddBabelHook\@undefined
5042 % A few lines are only read by hyphen.cfg
5043 \ifx\DisableBabelHook\@undefined
5044 \AddBabelHook{luatex}{everylanguage}{%
5045 \def\process@language##1##2##3{%
5046 \def\process@line####1####2 ####3 ####4 {}}}
5047 \AddBabelHook{luatex}{loadpatterns}{%
5048 \input #1\relax
5049 \expandafter\gdef\csname bbl@hyphendata@the\language\endcsname
5050 {{#1}}}}
5051 \AddBabelHook{luatex}{loadexceptions}{%
5052 \input #1\relax
5053 \def\bbl@tempb##1##2{{##1}{#1}}%
5054 \expandafter\xdef\csname bbl@hyphendata@the\language\endcsname
5055 {\expandafter\expandafter\expandafter\bbl@tempb
5056 \csname bbl@hyphendata@the\language\endcsname}}
5057 \endinput\fi
5058 % Here stops reading code for hyphen.cfg
5059 % The following is read the 2nd time it's loaded
5060 \begingroup % TODO - to a lua file
5061 \catcode\%=12
5062 \catcode\'=12
5063 \catcode\"=12
5064 \catcode\:=12
5065 \directlua{
5066 Babel = Babel or {}
5067 function Babel.bytes(line)
5068 return line:gsub("(.)",
5069 function (chr) return unicode.utf8.char(string.byte(chr)) end)
5070 end
5071 function Babel.begin_process_input()
5072 if luatexbase and luatexbase.add_to_callback then
5073 luatexbase.add_to_callback('process_input_buffer',
5074 Babel.bytes,'Babel.bytes')
5075 else
5076 Babel.callback = callback.find('process_input_buffer')
5077 callback.register('process_input_buffer',Babel.bytes)
5078 end
5079 end
5080 function Babel.end_process_input ()
5081 if luatexbase and luatexbase.remove_from_callback then
5082 luatexbase.remove_from_callback('process_input_buffer','Babel.bytes')
5083 else
5084 callback.register('process_input_buffer',Babel.callback)
5085 end
5086 end
5087 function Babel.addpatterns(pp, lg)
5088 local lg = lang.new(lg)
5089 local pats = lang.patterns(lg) or ''
5090 lang.clear_patterns(lg)
5091 for p in pp:gmatch('[^%s]+') do
5092 ss = ''
5093 for i in string.utfcharacters(p:gsub('%d', '')) do
5094 ss = ss .. '%d?' .. i
5095 end
5096 ss = ss:gsub('^%d%?%.', '%%.') .. '%d?'
5097 ss = ss:gsub('%.%d%?$', '%%.')

```

```

5098     pats, n = pats:gsub('%s' .. ss .. '%s', ' ' .. p .. ' ')
5099     if n == 0 then
5100         tex.sprint(
5101             [[\string\csname\space bbl@info\endcsname{New pattern: }]]
5102             .. p .. [[]])
5103         pats = pats .. ' ' .. p
5104     else
5105         tex.sprint(
5106             [[\string\csname\space bbl@info\endcsname{Renew pattern: }]]
5107             .. p .. [[]])
5108     end
5109 end
5110 lang.patterns(lg, pats)
5111 end
5112 Babel.characters = Babel.characters or {}
5113 Babel.ranges = Babel.ranges or {}
5114 function Babel.hlist_has_bidi(head)
5115     local has_bidi = false
5116     local ranges = Babel.ranges
5117     for item in node.traverse(head) do
5118         if item.id == node.id'glyph' then
5119             local itemchar = item.char
5120             local chardata = Babel.characters[itemchar]
5121             local dir = chardata and chardata.d or nil
5122             if not dir then
5123                 for nn, et in ipairs(ranges) do
5124                     if itemchar < et[1] then
5125                         break
5126                     elseif itemchar <= et[2] then
5127                         dir = et[3]
5128                         break
5129                     end
5130                 end
5131             end
5132             if dir and (dir == 'al' or dir == 'r') then
5133                 has_bidi = true
5134             end
5135         end
5136     end
5137     return has_bidi
5138 end
5139 function Babel.set_chranges_b (script, chrng)
5140     if chrng == '' then return end
5141     texio.write('Replacing ' .. script .. ' script ranges')
5142     Babel.script_blocks[script] = {}
5143     for s, e in string.gmatch(chrng..' ', '(.-%.-%.-%s') do
5144         table.insert(
5145             Babel.script_blocks[script], {tonumber(s,16), tonumber(e,16)})
5146     end
5147 end
5148 function Babel.discard_sublr(str)
5149     if str:find( [[\string\indexentry]] ) and
5150        str:find( [[\string\babelsublr]] ) then
5151         str = str:gsub( [[\string\babelsublr%s*(%b{})]],
5152             function(m) return m:sub(2,-2) end )
5153     end
5154     return str
5155 end
5156 }
5157 \endgroup
5158 \ifx\newattribute\@undefined\else
5159     \newattribute\bbl@attr@locale
5160     \directlua{ Babel.attr_locale = luatexbase.registernumber'bbl@attr@locale' }

```



```

5161 \AddBabelHook{luatex}{beforeextras}{%
5162 \setattribute\bbl@attr@locale\localeid}
5163 \fi
5164 \def\BabelStringsDefault{unicode}
5165 \let\luabbl@stop\relax
5166 \AddBabelHook{luatex}{encodedcommands}{%
5167 \def\bbl@tempa{utf8}\def\bbl@tempb{#1}%
5168 \ifx\bbl@tempa\bbl@tempb\else
5169 \directlua{Babel.begin_process_input()}%
5170 \def\luabbl@stop{%
5171 \directlua{Babel.end_process_input()}}%
5172 \fi}%
5173 \AddBabelHook{luatex}{stopcommands}{%
5174 \luabbl@stop
5175 \let\luabbl@stop\relax}
5176 \AddBabelHook{luatex}{patterns}{%
5177 \@ifundefined{bbl@hyphendata@the\language}%
5178 {\def\bbl@elt##1##2##3##4{%
5179 \ifnum##2=\csname l@##2\endcsname % #2=spanish, dutch:OT1...
5180 \def\bbl@tempb{##3}%
5181 \ifx\bbl@tempb\empty\else % if not a synonymous
5182 \def\bbl@tempc{##3}{##4}}%
5183 \fi
5184 \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
5185 \fi}%
5186 \bbl@languages
5187 \@ifundefined{bbl@hyphendata@the\language}%
5188 {\bbl@info{No hyphenation patterns were set for\%
5189 language '#2'. Reported}}%
5190 {\expandafter\expandafter\expandafter\bbl@luapatterns
5191 \csname bbl@hyphendata@the\language\endcsname}}}%
5192 \@ifundefined{bbl@patterns@}{}%
5193 \begingroup
5194 \bbl@xin@{\number\language,}{\bbl@pttnlist}%
5195 \ifin@ \else
5196 \ifx\bbl@patterns@\empty\else
5197 \directlua{ Babel.addpatterns(
5198 [[\bbl@patterns@]], \number\language) }%
5199 \fi
5200 \@ifundefined{bbl@patterns@#1}%
5201 \empty
5202 {\directlua{ Babel.addpatterns(
5203 [[\space\csname bbl@patterns@#1\endcsname]],
5204 \number\language) }}%
5205 \xdef\bbl@pttnlist{\bbl@pttnlist\number\language,}%
5206 \fi
5207 \endgroup}%
5208 \bbl@exp{%
5209 \bbl@ifunset{bbl@prehc@\languagename}{}%
5210 {\bbl@ifblank{\bbl@cs{prehc@\languagename}}}%
5211 {\prehyphenchar=\bbl@cl{prehc}\relax}}}

```

`\babelpatterns` This macro adds patterns. Two macros are used to store them: `\bbl@patterns@` for the global ones and `\bbl@patterns@<lang>` for language ones. We make sure there is a space between words when multiple commands are used.

```

5212 \@onlypreamble\babelpatterns
5213 \AtEndOfPackage{%
5214 \newcommand\babelpatterns[2][\empty]{%
5215 \ifx\bbl@patterns@\relax
5216 \let\bbl@patterns@\empty
5217 \fi
5218 \ifx\bbl@pttnlist\empty\else
5219 \bbl@warning{%

```

```

5220     You must not intermingle \string\selectlanguage\space and\\%
5221     \string\babelpatterns\space or some patterns will not\\%
5222     be taken into account. Reported}%
5223 \fi
5224 \ifx\@empty#1%
5225     \protected@edef\bbl@patterns@\bbl@patterns@\space#2}%
5226 \else
5227     \edef\bbl@tempb{\zap@space#1 \@empty}%
5228     \bbl@for\bbl@tempa\bbl@tempb{%
5229         \bbl@fixname\bbl@tempa
5230         \bbl@iflanguage\bbl@tempa{%
5231             \bbl@csarg\protected@edef{patterns@\bbl@tempa}{%
5232                 \@ifundefined{bbl@patterns@\bbl@tempa}%
5233                 \@empty
5234                 {\csname bbl@patterns@\bbl@tempa\endcsname\space}%
5235                 #2}}}%
5236 \fi}}

```

12.5 Southeast Asian scripts

First, some general code for line breaking, used by `\babelposthyphenation`. Replace regular (ie, implicit) discretionaries by spaceskips, based on the previous glyph (which I think makes sense, because the hyphen and the previous char go always together). Other discretionaries are not touched. See Unicode UAX 14.

```

5237% TODO - to a lua file
5238\directlua{
5239    Babel = Babel or {}
5240    Babel.linebreaking = Babel.linebreaking or {}
5241    Babel.linebreaking.before = {}
5242    Babel.linebreaking.after = {}
5243    Babel.locale = {} % Free to use, indexed by \localeid
5244    function Babel.linebreaking.add_before(func, pos)
5245        tex.print([[ \noexpand\csname bbl@luahyphenate\endcsname]])
5246        if pos == nil then
5247            table.insert(Babel.linebreaking.before, func)
5248        else
5249            table.insert(Babel.linebreaking.before, pos, func)
5250        end
5251    end
5252    function Babel.linebreaking.add_after(func)
5253        tex.print([[ \noexpand\csname bbl@luahyphenate\endcsname]])
5254        table.insert(Babel.linebreaking.after, func)
5255    end
5256 }
5257\def\bbl@intraspace#1 #2 #3\@{
5258    \directlua{
5259        Babel = Babel or {}
5260        Babel.intraspaces = Babel.intraspaces or {}
5261        Babel.intraspaces['\csname bbl@sbc@language\endcsname'] = %
5262            {b = #1, p = #2, m = #3}
5263        Babel.locale_props[\the\localeid].intraspace = %
5264            {b = #1, p = #2, m = #3}
5265    }}
5266\def\bbl@intrapenalty#1\@{
5267    \directlua{
5268        Babel = Babel or {}
5269        Babel.intrapenalties = Babel.intrapenalties or {}
5270        Babel.intrapenalties['\csname bbl@sbc@language\endcsname'] = #1
5271        Babel.locale_props[\the\localeid].intrapenalty = #1
5272    }}
5273\begingroup
5274\catcode`\%=12
5275\catcode`\^=14

```

```

5276 \catcode`\'=12
5277 \catcode`\~ =12
5278 \gdef\bbl@seaintraspace{^
5279 \let\bbl@seaintraspace\relax
5280 \directlua{
5281   Babel = Babel or {}
5282   Babel.sea_enabled = true
5283   Babel.sea_ranges = Babel.sea_ranges or {}
5284   function Babel.set_chranges (script, chrng)
5285     local c = 0
5286     for s, e in string.gmatch(chrng..' ', '(.-%.%.(-)%s') do
5287       Babel.sea_ranges[script..c]={tonumber(s,16), tonumber(e,16)}
5288       c = c + 1
5289     end
5290   end
5291   function Babel.sea_disc_to_space (head)
5292     local sea_ranges = Babel.sea_ranges
5293     local last_char = nil
5294     local quad = 655360      ^% 10 pt = 655360 = 10 * 65536
5295     for item in node.traverse(head) do
5296       local i = item.id
5297       if i == node.id'glyph' then
5298         last_char = item
5299       elseif i == 7 and item.subtype == 3 and last_char
5300         and last_char.char > 0x0C99 then
5301         quad = font.getfont(last_char.font).size
5302         for lg, rg in pairs(sea_ranges) do
5303           if last_char.char > rg[1] and last_char.char < rg[2] then
5304             lg = lg:sub(1, 4) ^% Remove trailing number of, eg, Cyril1
5305             local intraspace = Babel.intraspaces[lg]
5306             local intrapenalty = Babel.intrapenalties[lg]
5307             local n
5308             if intrapenalty ~= 0 then
5309               n = node.new(14, 0)      ^% penalty
5310               n.penalty = intrapenalty
5311               node.insert_before(head, item, n)
5312             end
5313             n = node.new(12, 13)      ^% (glue, spaceskip)
5314             node.setglue(n, intraspace.b * quad,
5315               intraspace.p * quad,
5316               intraspace.m * quad)
5317             node.insert_before(head, item, n)
5318             node.remove(head, item)
5319           end
5320         end
5321       end
5322     end
5323   end
5324 }^^
5325 \bbl@luahyphenate}

```

12.6 CJK line breaking

Minimal line breaking for CJK scripts, mainly intended for simple documents and short texts as a secondary language. Only line breaking, with a little stretching for justification, without any attempt to adjust the spacing. It is based on (but does not strictly follow) the Unicode algorithm.

We first need a little table with the corresponding line breaking properties. A few characters have an additional key for the width (fullwidth vs. halfwidth), not yet used. There is a separate file, defined below.

```

5326 \catcode`\%=14
5327 \gdef\bbl@cjkkintraspace{%
5328 \let\bbl@cjkkintraspace\relax
5329 \directlua{

```

```

5330 Babel = Babel or {}
5331 require('babel-data-cjk.lua')
5332 Babel.cjk_enabled = true
5333 function Babel.cjk_linebreak(head)
5334     local GLYPH = node.id'glyph'
5335     local last_char = nil
5336     local quad = 655360          % 10 pt = 655360 = 10 * 65536
5337     local last_class = nil
5338     local last_lang = nil
5339
5340     for item in node.traverse(head) do
5341         if item.id == GLYPH then
5342
5343             local lang = item.lang
5344
5345             local LOCALE = node.get_attribute(item,
5346                 Babel.attr_locale)
5347             local props = Babel.locale_props[LOCALE]
5348
5349             local class = Babel.cjk_class[item.char].c
5350
5351             if props.cjk_quotes and props.cjk_quotes[item.char] then
5352                 class = props.cjk_quotes[item.char]
5353             end
5354
5355             if class == 'cp' then class = 'cl' end % ]] as CL
5356             if class == 'id' then class = 'I' end
5357
5358             local br = 0
5359             if class and last_class and Babel.cjk_breaks[last_class][class] then
5360                 br = Babel.cjk_breaks[last_class][class]
5361             end
5362
5363             if br == 1 and props.linebreak == 'c' and
5364                 lang ~= \the\l@nohyphenation\space and
5365                 last_lang ~= \the\l@nohyphenation then
5366                 local intrapenalty = props.intrapenalty
5367                 if intrapenalty ~= 0 then
5368                     local n = node.new(14, 0)      % penalty
5369                     n.penalty = intrapenalty
5370                     node.insert_before(head, item, n)
5371                 end
5372                 local intraspace = props.intraspace
5373                 local n = node.new(12, 13)         % (glue, spaceskip)
5374                 node.setglue(n, intraspace.b * quad,
5375                     intraspace.p * quad,
5376                     intraspace.m * quad)
5377                 node.insert_before(head, item, n)
5378             end
5379
5380             if font.getfont(item.font) then
5381                 quad = font.getfont(item.font).size
5382             end
5383             last_class = class
5384             last_lang = lang
5385             else % if penalty, glue or anything else
5386                 last_class = nil
5387             end
5388         end
5389     end
5390     lang.hyphenate(head)
5391 }%
5392 \bbl@luahyphenate}

```

```

5393 \gdef\bbl@luahyphenate{%
5394   \let\bbl@luahyphenate\relax
5395   \directlua{
5396     luatexbase.add_to_callback('hyphenate',
5397       function(head, tail)
5398         if Babel.linebreaking.before then
5399           for k, func in ipairs(Babel.linebreaking.before) do
5400             func(head)
5401           end
5402         end
5403         if Babel.cjk_enabled then
5404           Babel.cjk_linebreak(head)
5405         end
5406         lang.hyphenate(head)
5407         if Babel.linebreaking.after then
5408           for k, func in ipairs(Babel.linebreaking.after) do
5409             func(head)
5410           end
5411         end
5412         if Babel.sea_enabled then
5413           Babel.sea_disc_to_space(head)
5414         end
5415       end,
5416       'Babel.hyphenate')
5417   }
5418 }
5419 \endgroup
5420 \def\bbl@provide@intraspace{%
5421   \bbl@ifunset{bbl@intsp@language}{%
5422     {\expandafter\ifx\cename bbl@intsp@language\endcsname\@empty\else
5423       \bbl@xin@{/c}{\bbl@cl{lnbrk}}%
5424       \ifin@           % cjk
5425       \bbl@cjk@intraspace
5426       \directlua{
5427         Babel = Babel or {}
5428         Babel.locale_props = Babel.locale_props or {}
5429         Babel.locale_props[\the\localeid].linebreak = 'c'
5430       }%
5431       \bbl@exp{\bbl@intraspace\bbl@cl{intsp}\@}%
5432       \ifx\bbl@KVP@intrapenalty\@nnil
5433         \bbl@intrapenalty0\@@
5434       \fi
5435     \else           % sea
5436       \bbl@sea@intraspace
5437       \bbl@exp{\bbl@intraspace\bbl@cl{intsp}\@}%
5438       \directlua{
5439         Babel = Babel or {}
5440         Babel.sea_ranges = Babel.sea_ranges or {}
5441         Babel.set_chranges('\bbl@cl{sbcpr}',
5442           '\bbl@cl{chrng}')
5443       }%
5444       \ifx\bbl@KVP@intrapenalty\@nnil
5445         \bbl@intrapenalty0\@@
5446       \fi
5447     \fi
5448   \fi
5449   \ifx\bbl@KVP@intrapenalty\@nnil\else
5450     \expandafter\bbl@intrapenalty\bbl@KVP@intrapenalty\@@
5451   \fi}}

```

12.7 Arabic justification

```

5452 \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200

```

```

5453 \def\bblar@chars{%
5454   0628,0629,062A,062B,062C,062D,062E,062F,0630,0631,0632,0633,%
5455   0634,0635,0636,0637,0638,0639,063A,063B,063C,063D,063E,063F,%
5456   0640,0641,0642,0643,0644,0645,0646,0647,0649}
5457 \def\bblar@elongated{%
5458   0626,0628,062A,062B,0633,0634,0635,0636,063B,%
5459   063C,063D,063E,063F,0641,0642,0643,0644,0646,%
5460   0649,064A}
5461 \begingroup
5462   \catcode`\_ =11 \catcode`\:=11
5463   \gdef\bblar@nofswarn{\gdef\msg_warning:nx##1##2##3{}}
5464 \endgroup
5465 \gdef\bbl@arabicjust{%
5466   \let\bbl@arabicjust\relax
5467   \newattribute\bblar@kashida
5468   \directlua{ Babel.attr_kashida = luatexbase.registernumber'bblar@kashida' }%
5469   \bblar@kashida=\z@
5470   \bbl@patchfont{\bbl@parsejalt}%
5471   \directlua{
5472     Babel.arabic.elong_map = Babel.arabic.elong_map or {}
5473     Babel.arabic.elong_map[\the\localeid] = {}
5474     luatexbase.add_to_callback('post_linebreak_filter',
5475       Babel.arabic.justify, 'Babel.arabic.justify')
5476     luatexbase.add_to_callback('hpack_filter',
5477       Babel.arabic.justify_hbox, 'Babel.arabic.justify_hbox')
5478   }%
5479 % Save both node lists to make replacement. TODO. Save also widths to
5480 % make computations
5481 \def\bblar@fetchjalt#1#2#3#4{%
5482   \bbl@exp{\bbl@foreach{#1}}{%
5483     \bbl@ifunset{bblar@JE@##1}%
5484     {\setbox\z@\hbox{^^^200d\char"##1#2}}%
5485     {\setbox\z@\hbox{^^^200d\char"\@nameuse{bblar@JE@##1}#2}}%
5486   \directlua{%
5487     local last = nil
5488     for item in node.traverse(tex.box[0].head) do
5489       if item.id == node.id'glyph' and item.char > 0x600 and
5490         not (item.char == 0x200D) then
5491         last = item
5492       end
5493     end
5494     Babel.arabic.#3['##1#4'] = last.char
5495   }}
5496 % Brute force. No rules at all, yet. The ideal: look at jalt table. And
5497 % perhaps other tables (falt?, csw?). What about kaf? And diacritic
5498 % positioning?
5499 \gdef\bbl@parsejalt{%
5500   \ifx\addfontfeature\undefined\else
5501     \bbl@xin{/e}{\bbl@c{lnbrk}}%
5502     \fin@
5503     \directlua{%
5504       if Babel.arabic.elong_map[\the\localeid][\fontid\font] == nil then
5505         Babel.arabic.elong_map[\the\localeid][\fontid\font] = {}
5506         tex.print([[string\curname\space bbl@parsejalti\endcurname]])
5507       end
5508     }%
5509   \fi
5510 \fi}
5511 \gdef\bbl@parsejalti{%
5512   \begingroup
5513     \let\bbl@parsejalt\relax % To avoid infinite loop
5514     \edef\bbl@tempb{\fontid\font}%
5515     \bblar@nofswarn

```

```

5516 \bblar@fetchjalt\bblar@elongated{}{from}{}%
5517 \bblar@fetchjalt\bblar@chars{^^^^064a}{from}{a}% Alef maksura
5518 \bblar@fetchjalt\bblar@chars{^^^^0649}{from}{y}% Yeh
5519 \addfontfeature{RawFeature+=jalt}%
5520 % \@namedef{bblar@JE@0643}{06AA}% todo: catch medial kaf
5521 \bblar@fetchjalt\bblar@elongated{}{dest}{}%
5522 \bblar@fetchjalt\bblar@chars{^^^^064a}{dest}{a}%
5523 \bblar@fetchjalt\bblar@chars{^^^^0649}{dest}{y}%
5524 \directlua{%
5525     for k, v in pairs(Babel.arabic.from) do
5526         if Babel.arabic.dest[k] and
5527             not (Babel.arabic.from[k] == Babel.arabic.dest[k]) then
5528             Babel.arabic.elong_map[\the\localeid][\bbl@tempb]
5529                 [Babel.arabic.from[k]] = Babel.arabic.dest[k]
5530         end
5531     end
5532 }%
5533 \endgroup}
5534 %
5535 \begingroup
5536 \catcode`#=11
5537 \catcode`~=11
5538 \directlua{
5539
5540 Babel.arabic = Babel.arabic or {}
5541 Babel.arabic.from = {}
5542 Babel.arabic.dest = {}
5543 Babel.arabic.justify_factor = 0.95
5544 Babel.arabic.justify_enabled = true
5545
5546 function Babel.arabic.justify(head)
5547     if not Babel.arabic.justify_enabled then return head end
5548     for line in node.traverse_id(node.id'hlist', head) do
5549         Babel.arabic.justify_hlist(head, line)
5550     end
5551     return head
5552 end
5553
5554 function Babel.arabic.justify_hbox(head, gc, size, pack)
5555     local has_inf = false
5556     if Babel.arabic.justify_enabled and pack == 'exactly' then
5557         for n in node.traverse_id(12, head) do
5558             if n.stretch_order > 0 then has_inf = true end
5559         end
5560         if not has_inf then
5561             Babel.arabic.justify_hlist(head, nil, gc, size, pack)
5562         end
5563     end
5564     return head
5565 end
5566
5567 function Babel.arabic.justify_hlist(head, line, gc, size, pack)
5568     local d, new
5569     local k_list, k_item, pos_inline
5570     local width, width_new, full, k_curr, wt_pos, goal, shift
5571     local subst_done = false
5572     local elong_map = Babel.arabic.elong_map
5573     local last_line
5574     local GLYPH = node.id'glyph'
5575     local KASHIDA = Babel.attr_kashida
5576     local LOCALE = Babel.attr_locale
5577
5578     if line == nil then

```

```

5579     line = {}
5580     line.glue_sign = 1
5581     line.glue_order = 0
5582     line.head = head
5583     line.shift = 0
5584     line.width = size
5585 end
5586
5587 % Exclude last line. todo. But-- it discards one-word lines, too!
5588 % ? Look for glue = 12:15
5589 if (line.glue_sign == 1 and line.glue_order == 0) then
5590     elongs = {}      % Stores elongated candidates of each line
5591     k_list = {}      % And all letters with kashida
5592     pos_inline = 0   % Not yet used
5593
5594     for n in node.traverse_id(GLYPH, line.head) do
5595         pos_inline = pos_inline + 1 % To find where it is. Not used.
5596
5597         % Elongated glyphs
5598         if elong_map then
5599             local locale = node.get_attribute(n, LOCALE)
5600             if elong_map[locale] and elong_map[locale][n.font] and
5601                 elong_map[locale][n.font][n.char] then
5602                 table.insert(elongs, {node = n, locale = locale} )
5603                 node.set_attribute(n.prev, KASHIDA, 0)
5604             end
5605         end
5606
5607         % Tatwil
5608         if Babel.kashida_wts then
5609             local k_wt = node.get_attribute(n, KASHIDA)
5610             if k_wt > 0 then % todo. parameter for multi inserts
5611                 table.insert(k_list, {node = n, weight = k_wt, pos = pos_inline})
5612             end
5613         end
5614
5615     end % of node.traverse_id
5616
5617     if #elongs == 0 and #k_list == 0 then goto next_line end
5618     full = line.width
5619     shift = line.shift
5620     goal = full * Babel.arabic.justify_factor % A bit crude
5621     width = node.dimensions(line.head) % The 'natural' width
5622
5623     % == Elongated ==
5624     % Original idea taken from 'chickenize'
5625     while (#elongs > 0 and width < goal) do
5626         subst_done = true
5627         local x = #elongs
5628         local curr = elongs[x].node
5629         local oldchar = curr.char
5630         curr.char = elong_map[elongs[x].locale][curr.font][curr.char]
5631         width = node.dimensions(line.head) % Check if the line is too wide
5632         % Substitute back if the line would be too wide and break:
5633         if width > goal then
5634             curr.char = oldchar
5635             break
5636         end
5637         % If continue, pop the just substituted node from the list:
5638         table.remove(elongs, x)
5639     end
5640
5641     % == Tatwil ==

```



```

5642   if #k_list == 0 then goto next_line end
5643
5644   width = node.dimensions(line.head)    % The 'natural' width
5645   k_curr = #k_list
5646   wt_pos = 1
5647
5648   while width < goal do
5649     subst_done = true
5650     k_item = k_list[k_curr].node
5651     if k_list[k_curr].weight == Babel.kashida_wts[wt_pos] then
5652       d = node.copy(k_item)
5653       d.char = 0x0640
5654       line.head, new = node.insert_after(line.head, k_item, d)
5655       width_new = node.dimensions(line.head)
5656       if width > goal or width == width_new then
5657         node.remove(line.head, new) % Better compute before
5658         break
5659       end
5660       width = width_new
5661     end
5662     if k_curr == 1 then
5663       k_curr = #k_list
5664       wt_pos = (wt_pos >= table.getn(Babel.kashida_wts)) and 1 or wt_pos+1
5665     else
5666       k_curr = k_curr - 1
5667     end
5668   end
5669
5670   ::next_line::
5671
5672   % Must take into account marks and ins, see luatex manual.
5673   % Have to be executed only if there are changes. Investigate
5674   % what's going on exactly.
5675   if subst_done and not gc then
5676     d = node.hpack(line.head, full, 'exactly')
5677     d.shift = shift
5678     node.insert_before(head, line, d)
5679     node.remove(head, line)
5680   end
5681 end % if process line
5682 end
5683 }
5684 \endgroup
5685 \fi\fi % Arabic just block

```

12.8 Common stuff

```

5686 \AddBabelHook{babel-fontspec}{afterextras}{\bbl@switchfont}
5687 \AddBabelHook{babel-fontspec}{beforestart}{\bbl@ccheckstdfonts}
5688 \DisableBabelHook{babel-fontspec}
5689 <\Font selection>

```

12.9 Automatic fonts and ids switching

After defining the blocks for a number of scripts (must be extended and very likely fine tuned), we define a short function which just traverse the node list to carry out the replacements. The table `loc_to_scr` gets the locale from a script range (note the locale is the key, and that there is an intermediate table built on the fly for optimization). This locale is then used to get the `\language` and the `\localeid` as stored in `locale_props`, as well as the font (as requested). In the latter table a key starting with `/` maps the font from the global one (the key) to the local one (the value). Maths are skipped and discretionaries are handled in a special way.

```

5690 % TODO - to a lua file
5691 \directlua{
5692 Babel.script_blocks = {

```

```

5693 ['df1t'] = {},
5694 ['Arab'] = {{0x0600, 0x06FF}, {0x08A0, 0x08FF}, {0x0750, 0x077F},
5695             {0xFE70, 0xFEFF}, {0xFB50, 0xFDFF}, {0x1EE00, 0x1EEFF}},
5696 ['Armn'] = {{0x0530, 0x058F}},
5697 ['Beng'] = {{0x0980, 0x09FF}},
5698 ['Cher'] = {{0x13A0, 0x13FF}, {0xAB70, 0xABBF}},
5699 ['Copt'] = {{0x03E2, 0x03EF}, {0x2C80, 0x2CFF}, {0x102E0, 0x102FF}},
5700 ['Cyr1'] = {{0x0400, 0x04FF}, {0x0500, 0x052F}, {0x1C80, 0x1C8F},
5701             {0x2DE0, 0x2DFF}, {0xA640, 0xA69F}},
5702 ['Deva'] = {{0x0900, 0x097F}, {0xA8E0, 0xA8FF}},
5703 ['Ethi'] = {{0x1200, 0x137F}, {0x1380, 0x139F}, {0x2D80, 0x2DDF},
5704             {0xAB00, 0xAB2F}},
5705 ['Geor'] = {{0x10A0, 0x10FF}, {0x2D00, 0x2D2F}},
5706 % Don't follow strictly Unicode, which places some Coptic letters in
5707 % the 'Greek and Coptic' block
5708 ['Grek'] = {{0x0370, 0x03E1}, {0x03F0, 0x03FF}, {0x1F00, 0x1FFF}},
5709 ['Hans'] = {{0x2E80, 0x2EFF}, {0x3000, 0x303F}, {0x31C0, 0x31EF},
5710             {0x3300, 0x33FF}, {0x3400, 0x4DBF}, {0x4E00, 0x9FFF},
5711             {0xF900, 0xFAFF}, {0xFE30, 0xFE4F}, {0xFF00, 0xFFEF},
5712             {0x20000, 0x2A6DF}, {0x2A700, 0x2B73F},
5713             {0x2B740, 0x2B81F}, {0x2B820, 0x2CEAF},
5714             {0x2CEB0, 0x2EBEF}, {0x2F800, 0x2FA1F}},
5715 ['Hebr'] = {{0x0590, 0x05FF}},
5716 ['Jpan'] = {{0x3000, 0x303F}, {0x3040, 0x309F}, {0x30A0, 0x30FF},
5717             {0x4E00, 0x9FAF}, {0xFF00, 0xFFEF}},
5718 ['Khmr'] = {{0x1780, 0x17FF}, {0x19E0, 0x19FF}},
5719 ['Knda'] = {{0x0C80, 0x0CFF}},
5720 ['Kore'] = {{0x1100, 0x11FF}, {0x3000, 0x303F}, {0x3130, 0x318F},
5721             {0x4E00, 0x9FAF}, {0xA960, 0xA97F}, {0xAC00, 0xD7AF},
5722             {0xD7B0, 0xD7FF}, {0xFF00, 0xFFEF}},
5723 ['Laoo'] = {{0x0E80, 0x0EFF}},
5724 ['Latn'] = {{0x0000, 0x007F}, {0x0080, 0x00FF}, {0x0100, 0x017F},
5725             {0x0180, 0x024F}, {0x1E00, 0x1EFF}, {0x2C60, 0x2C7F},
5726             {0xA720, 0xA7FF}, {0xAB30, 0xAB6F}},
5727 ['Mahj'] = {{0x11150, 0x1117F}},
5728 ['Mlym'] = {{0x0D00, 0x0D7F}},
5729 ['Mymr'] = {{0x1000, 0x109F}, {0xAA60, 0xAA7F}, {0xA9E0, 0xA9FF}},
5730 ['Orya'] = {{0x0B00, 0x0B7F}},
5731 ['Sinh'] = {{0x0D80, 0x0DFF}, {0x111E0, 0x111FF}},
5732 ['SyrC'] = {{0x0700, 0x074F}, {0x0860, 0x086F}},
5733 ['Taml'] = {{0x0B80, 0x0BFF}},
5734 ['Telu'] = {{0x0C00, 0x0C7F}},
5735 ['Tfng'] = {{0x2D30, 0x2D7F}},
5736 ['Thai'] = {{0x0E00, 0x0E7F}},
5737 ['Tibt'] = {{0x0F00, 0x0FFF}},
5738 ['Vaii'] = {{0xA500, 0xA63F}},
5739 ['Yiii'] = {{0xA000, 0xA48F}, {0xA490, 0xA4CF}}
5740 }
5741
5742 Babel.script_blocks.Cyrs = Babel.script_blocks.Cyr1
5743 Babel.script_blocks.Hant = Babel.script_blocks.Hans
5744 Babel.script_blocks.Kana = Babel.script_blocks.Jpan
5745
5746 function Babel.locale_map(head)
5747   if not Babel.locale_mapped then return head end
5748
5749   local LOCALE = Babel.attr_locale
5750   local GLYPH = node.id('glyph')
5751   local inmath = false
5752   local toloc_save
5753   for item in node.traverse(head) do
5754     local toloc
5755     if not inmath and item.id == GLYPH then

```

```

5756 % Optimization: build a table with the chars found
5757 if Babel.chr_to_loc[item.char] then
5758   toloc = Babel.chr_to_loc[item.char]
5759 else
5760   for lc, maps in pairs(Babel.loc_to_scr) do
5761     for _, rg in pairs(maps) do
5762       if item.char >= rg[1] and item.char <= rg[2] then
5763         Babel.chr_to_loc[item.char] = lc
5764         toloc = lc
5765         break
5766       end
5767     end
5768   end
5769 end
5770 % Now, take action, but treat composite chars in a different
5771 % fashion, because they 'inherit' the previous locale. Not yet
5772 % optimized.
5773 if not toloc and
5774   (item.char >= 0x0300 and item.char <= 0x036F) or
5775   (item.char >= 0x1AB0 and item.char <= 0x1AFF) or
5776   (item.char >= 0x1DC0 and item.char <= 0x1DFF) then
5777   toloc = toloc_save
5778 end
5779 if toloc and Babel.locale_props[toloc] and
5780   Babel.locale_props[toloc].letters and
5781   tex.getcatcode(item.char) \string= 11 then
5782   toloc = nil
5783 end
5784 if toloc and toloc > -1 then
5785   if Babel.locale_props[toloc].lg then
5786     item.lang = Babel.locale_props[toloc].lg
5787     node.set_attribute(item, LOCALE, toloc)
5788   end
5789   if Babel.locale_props[toloc]['/'..item.font] then
5790     item.font = Babel.locale_props[toloc]['/'..item.font]
5791   end
5792   toloc_save = toloc
5793 end
5794 elseif not inmath and item.id == 7 then % Apply recursively
5795   item.replace = item.replace and Babel.locale_map(item.replace)
5796   item.pre = item.pre and Babel.locale_map(item.pre)
5797   item.post = item.post and Babel.locale_map(item.post)
5798 elseif item.id == node.id'math' then
5799   inmath = (item.subtype == 0)
5800 end
5801 end
5802 return head
5803 end
5804 }

```

The code for \babelcharproperty is straightforward. Just note the modified lua table can be different.

```

5805 \newcommand\babelcharproperty[1]{%
5806   \count@=#1\relax
5807   \ifvmode
5808     \expandafter\bbl@chprop
5809   \else
5810     \bbl@error{\string\babelcharproperty\space can be used only in\%
5811       vertical mode (preamble or between paragraphs)}%
5812     {See the manual for futher info}%
5813   \fi}
5814 \newcommand\bbl@chprop[3][\the\count@]{%
5815   \@tempcnta=#1\relax

```

```

5816 \bbl@ifunset{bbl@chprop@#2}%
5817 {\bbl@error{No property named '#2'. Allowed values are\\%
5818             direction (bc), mirror (bmg), and linebreak (lb)}}%
5819 {See the manual for futher info}}%
5820 {}%
5821 \loop
5822   \bbl@cs{chprop@#2}{#3}%
5823   \ifnum\count@<\@tempcnta
5824     \advance\count@\@ne
5825   \repeat}
5826 \def\bbl@chprop@direction#1{%
5827   \directlua{
5828     Babel.characters[\the\count@] = Babel.characters[\the\count@] or {}
5829     Babel.characters[\the\count@]['d'] = '#1'
5830   }}
5831 \let\bbl@chprop@bc\bbl@chprop@direction
5832 \def\bbl@chprop@mirror#1{%
5833   \directlua{
5834     Babel.characters[\the\count@] = Babel.characters[\the\count@] or {}
5835     Babel.characters[\the\count@]['m'] = '\number#1'
5836   }}
5837 \let\bbl@chprop@bmg\bbl@chprop@mirror
5838 \def\bbl@chprop@linebreak#1{%
5839   \directlua{
5840     Babel.cjk_characters[\the\count@] = Babel.cjk_characters[\the\count@] or {}
5841     Babel.cjk_characters[\the\count@]['c'] = '#1'
5842   }}
5843 \let\bbl@chprop@lb\bbl@chprop@linebreak
5844 \def\bbl@chprop@locale#1{%
5845   \directlua{
5846     Babel.chr_to_loc = Babel.chr_to_loc or {}
5847     Babel.chr_to_loc[\the\count@] =
5848       \bbl@ifblank{#1}{-1000}{\the\bbl@cs{id@#1}}\space
5849   }}

```

Post-handling hyphenation patterns for non-standard rules, like ff to ff-f. There are still some issues with speed (not very slow, but still slow). The Lua code is below.

```

5850 \directlua{
5851   Babel.nohyphenation = \the\l@nohyphenation
5852 }

```

Now the TeX high level interface, which requires the function defined above for converting strings to functions returning a string. These functions handle the $\{n\}$ syntax. For example, $\text{pre}=\{1\}\{1\}$ becomes $\text{function}(m) \text{ return } m[1]..m[1]..'-' \text{ end}$, where m are the matches returned after applying the pattern. With a mapped capture the functions are similar to $\text{function}(m) \text{ return } \text{Babel.capt_map}(m[1], 1) \text{ end}$, where the last argument identifies the mapping to be applied to $m[1]$. The way it is carried out is somewhat tricky, but the effect is not dissimilar to lua load – save the code as string in a TeX macro, and expand this macro at the appropriate place. As directlua does not take into account the current catcode of $@$, we just avoid this character in macro names (which explains the internal group, too).

```

5853 \begingroup
5854 \catcode`\~ = 12
5855 \catcode`\% = 12
5856 \catcode`\& = 14
5857 \catcode`\| = 12
5858 \gdef\babelprehyphenation{&&
5859   \@ifnextchar[{\bbl@settransform{0}}{\bbl@settransform{0}}[]]}
5860 \gdef\babelposthyphenation{&&
5861   \@ifnextchar[{\bbl@settransform{1}}{\bbl@settransform{1}}[]]}
5862 \gdef\bbl@postlinebreak{\bbl@settransform{2}}[] && WIP
5863 \gdef\bbl@settransform#1[#2]#3#4#5{&&
5864   \ifcase#1
5865     \bbl@activateprehyphen
5866   \or

```

```

5867 \bbl@activateposthyphen
5868 \fi
5869 \begingroup
5870 \def\babeltempa{\bbl@add@list\babeltempb}&%
5871 \let\babeltempb\@empty
5872 \def\bbl@tempa{#5}&%
5873 \bbl@replace\bbl@tempa{,}{,}&% TODO. Ugly trick to preserve {}
5874 \expandafter\bbl@foreach\expandafter{\bbl@tempa}&%
5875 \bbl@ifsamestring{##1}{remove}&%
5876 {\bbl@add@list\babeltempb{nil}}&%
5877 {\directlua{
5878     local rep = [= [##1]=]
5879     rep = rep:gsub('^%s*(remove)%s*$', 'remove = true')
5880     rep = rep:gsub('^%s*(insert)%s*', 'insert = true, ')
5881     rep = rep:gsub('(string)%s*=%s*([^\s,]*)', Babel.capture_func)
5882     if #1 == 0 or #1 == 2 then
5883         rep = rep:gsub('(space)%s*=%s*([%d%.]+)%s+([%d%.]+)%s+([%d%.]+)',
5884             'space = {' .. '%2, %3, %4' .. '}')
5885         rep = rep:gsub('(spacefactor)%s*=%s*([%d%.]+)%s+([%d%.]+)%s+([%d%.]+)',
5886             'spacefactor = {' .. '%2, %3, %4' .. '}')
5887         rep = rep:gsub('(kashida)%s*=%s*([^\s,]*)', Babel.capture_kashida)
5888     else
5889         rep = rep:gsub('(no)%s*=%s*([^\s,]*)', Babel.capture_func)
5890         rep = rep:gsub('(pre)%s*=%s*([^\s,]*)', Babel.capture_func)
5891         rep = rep:gsub('(post)%s*=%s*([^\s,]*)', Babel.capture_func)
5892     end
5893     tex.print([[\\string\babeltempa{}}] .. rep .. [[]]])
5894 }}&%
5895 \bbl@foreach\babeltempb{&%
5896 \bbl@forkv{##1}&%
5897 \in@{,###1,}{,nil,step,data,remove,insert,string,no,pre,&%
5898 no,post,penalty,kashida,space,spacefactor,}&%
5899 \ifin@else
5900 \bbl@error
5901 {Bad option '###1' in a transform.\\&%
5902 I'll ignore it but expect more errors}&%
5903 {See the manual for further info.}&%
5904 \fi}&%
5905 \let\bbl@kv@attribute\relax
5906 \let\bbl@kv@label\relax
5907 \let\bbl@kv@fonts\@empty
5908 \bbl@forkv{#2}{\bbl@csarg\edef{kv##1}{##2}}&%
5909 \ifx\bbl@kv@fonts\@empty\else\bbl@settransfont\fi
5910 \ifx\bbl@kv@attribute\relax
5911 \ifx\bbl@kv@label\relax\else
5912 \bbl@exp{\bbl@trim@def\bbl@kv@fonts{\bbl@kv@fonts}}&%
5913 \bbl@replace\bbl@kv@fonts{ }{,}&%
5914 \edef\bbl@kv@attribute{\bbl@ATR\bbl@kv@label @#3@\bbl@kv@fonts}&%
5915 \count@ \z@
5916 \def\bbl@elt##1##2##3{&%
5917 \bbl@ifsamestring{#3,\bbl@kv@label}{##1,##2}&%
5918 {\bbl@ifsamestring{\bbl@kv@fonts}{##3}&%
5919 {\count@ \@ne}&%
5920 {\bbl@error
5921 {Transforms cannot be re-assigned to different\\&%
5922 fonts. The conflict is in '\bbl@kv@label'.\\&%
5923 Apply the same fonts or use a different label}&%
5924 {See the manual for further details.}}}&%
5925 }}&%
5926 \bbl@transfont@list
5927 \ifnum\count@=\z@
5928 \bbl@exp{\global\bbl@add\bbl@transfont@list
5929 {\bbl@elt{#3}{\bbl@kv@label}{\bbl@kv@fonts}}}&%

```

```

5930     \fi
5931     \bbl@ifunset{\bbl@kv@attribute}&%
5932     {\global\bbl@carg\newattribute{\bbl@kv@attribute}}&%
5933     }&%
5934     \global\bbl@carg\setattribute{\bbl@kv@attribute}\@ne
5935   \fi
5936 \else
5937   \edef\bbl@kv@attribute{\expandafter\bbl@stripslash\bbl@kv@attribute}&%
5938 \fi
5939 \directlua{
5940   local lbkr = Babel.linebreaking.replacements[#1]
5941   local u = unicode.utf8
5942   local id, attr, label
5943   if #1 == 0 or #1 == 2 then
5944     id = \the\csname bbl@id@#3\endcsname\space
5945   else
5946     id = \the\csname l@#3\endcsname\space
5947   end
5948   \ifx\bbl@kv@attribute\relax
5949     attr = -1
5950   \else
5951     attr = luatexbase.registernumber'\bbl@kv@attribute'
5952   \fi
5953   \ifx\bbl@kv@label\relax\else  &% Same refs:
5954     label = [==[\bbl@kv@label]==]
5955   \fi
5956   &% Convert pattern:
5957   local patt = string.gsub([==[#4]==], '%s', '')
5958   if #1 == 0 or #1 == 2 then
5959     patt = string.gsub(patt, '|', ' ')
5960   end
5961   if not u.find(patt, '()', nil, true) then
5962     patt = '()' .. patt .. '()'
5963   end
5964   if #1 == 1 then
5965     patt = string.gsub(patt, '%(%)%', '^()')
5966     patt = string.gsub(patt, '%$(%)', '()$')
5967   end
5968   patt = u.gsub(patt, '{(.)}',
5969     function (n)
5970       return '%' .. (tonumber(n) and (tonumber(n)+1) or n)
5971     end)
5972   patt = u.gsub(patt, '{(%x%x%x%x+)}',
5973     function (n)
5974       return u.gsub(u.char(tonumber(n, 16)), '(%p)', '%%%1')
5975     end)
5976   lbkr[id] = lbkr[id] or {}
5977   table.insert(lbkr[id],
5978     { label=label, attr=attr, pattern=patt, replace={\babeltempb} })
5979 }&%
5980 \endgroup}
5981 \endgroup
5982 \let\bbl@transfont@list\@empty
5983 \def\bbl@settransfont{%
5984   \global\let\bbl@settransfont\relax % Execute only once
5985   \gdef\bbl@transfont{%
5986     \def\bbl@elt####1####2####3{%
5987       \bbl@ifblank{####3}%
5988       {\count@tw@}% Do nothing if no fonts
5989       {\count@z@
5990         \bbl@vforeach{####3}{%
5991           \def\bbl@tempd{#####1}%
5992           \edef\bbl@tempe{\bbl@transfam/\f@series/\f@shape}%

```

```

5993         \ifx\bb1@tempd\bb1@tempe
5994         \count@\@ne
5995         \else\ifx\bb1@tempd\bb1@transfam
5996         \count@\@ne
5997         \fi\fi}%
5998     \ifcase\count@
5999         \bb1@csarg\unsetattribute{ATR@###2@###1@###3}%
6000     \or
6001         \bb1@csarg\setattribute{ATR@###2@###1@###3}\@ne
6002     \fi}}%
6003     \bb1@transfont@list}%
6004 \AddToHook{selectfont}{\bb1@transfont}% Hooks are global.
6005 \gdef\bb1@transfam{-unknown-}%
6006 \bb1@foreach\bb1@font@fams{%
6007     \AddToHook{##1family}{\def\bb1@transfam{##1}}}%
6008     \bb1@ifsamestring{\@nameuse{##1default}}\familydefault
6009     {\xdef\bb1@transfam{##1}}}%
6010     {}}
6011 \DeclareRobustCommand\enablelocaletransform[1]{%
6012     \bb1@ifunset{\bb1@ATR@#1\@language @}%
6013     {\bb1@error
6014         {'#1' for '\@language' cannot be enabled.\\%
6015         Maybe there is a typo or it's a font-dependent transform}%
6016         {See the manual for further details.}}%
6017     {\bb1@csarg\setattribute{ATR@#1\@language @}\@ne}}
6018 \DeclareRobustCommand\disablelocaletransform[1]{%
6019     \bb1@ifunset{\bb1@ATR@#1\@language @}%
6020     {\bb1@error
6021         {'#1' for '\@language' cannot be disabled.\\%
6022         Maybe there is a typo or it's a font-dependent transform}%
6023         {See the manual for further details.}}%
6024     {\bb1@csarg\unsetattribute{ATR@#1\@language @}}}
6025 \def\bb1@activateposthyphen{%
6026     \let\bb1@activateposthyphen\relax
6027     \directlua{
6028         require('babel-transforms.lua')
6029         Babel.linebreaking.add_after(Babel.post_hyphenate_replace)
6030     }}
6031 \def\bb1@activateprehyphen{%
6032     \let\bb1@activateprehyphen\relax
6033     \directlua{
6034         require('babel-transforms.lua')
6035         Babel.linebreaking.add_before(Babel.pre_hyphenate_replace)
6036     }}

```

12.10 Bidi

As a first step, add a handler for bidi and digits (and potentially other processes) just before `luaotfload` is applied, which is loaded by default by \LaTeX . Just in case, consider the possibility it has not been loaded.

```

6037 \def\bb1@activate@preotf{%
6038     \let\bb1@activate@preotf\relax % only once
6039     \directlua{
6040         Babel = Babel or {}
6041         %
6042         function Babel.pre_otfload_v(head)
6043             if Babel.numbers and Babel.digits_mapped then
6044                 head = Babel.numbers(head)
6045             end
6046             if Babel.bidi_enabled then
6047                 head = Babel.bidi(head, false, dir)
6048             end
6049             return head

```

```

6050 end
6051 %
6052 function Babel.pre_otfload_h(head, gc, sz, pt, dir)
6053   if Babel.numbers and Babel.digits_mapped then
6054     head = Babel.numbers(head)
6055   end
6056   if Babel.bidi_enabled then
6057     head = Babel.bidi(head, false, dir)
6058   end
6059   return head
6060 end
6061 %
6062 luatexbase.add_to_callback('pre_linebreak_filter',
6063   Babel.pre_otfload_v,
6064   'Babel.pre_otfload_v',
6065   luatexbase.priority_in_callback('pre_linebreak_filter',
6066     'luaotfload.node_processor') or nil)
6067 %
6068 luatexbase.add_to_callback('hpack_filter',
6069   Babel.pre_otfload_h,
6070   'Babel.pre_otfload_h',
6071   luatexbase.priority_in_callback('hpack_filter',
6072     'luaotfload.node_processor') or nil)
6073 }}

```

The basic setup. The output is modified at a very low level to set the `\bodydir` to the `\pagedir`. Sadly, we have to deal with boxes in math with basic, so the `\bbl@mathboxdir` hack is activated every math with the package option `bidi=`.

```

6074 \ifnum\bbl@bidimode>\@ne % Excludes default=1
6075   \let\bbl@beforeforeign\leavevmode
6076   \AtEndOfPackage{\EnableBabelHook{babel-bidi}}
6077   \RequirePackage{luatexbase}
6078   \bbl@activate@preotf
6079   \directlua{
6080     require('babel-data-bidi.lua')
6081     \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
6082       require('babel-bidi-basic.lua')
6083     \or
6084       require('babel-bidi-basic-r.lua')
6085     \fi}
6086   \newattribute\bbl@attr@dir
6087   \directlua{ Babel.attr_dir = luatexbase.registernumber'bbl@attr@dir' }
6088   \bbl@exp{\output{\bodydir\pagedir\the\output}}
6089 \fi
6090 \chardef\bbl@thetextdir\z@
6091 \chardef\bbl@thepardir\z@
6092 \def\bbl@getluadir#1{%
6093   \directlua{
6094     if tex.#1dir == 'TLT' then
6095       tex.sprint('0')
6096     elseif tex.#1dir == 'TRT' then
6097       tex.sprint('1')
6098     end}}
6099 \def\bbl@setluadir#1#2#3{% 1=text/par.. 2=\textdir.. 3=0 lr/1 rl
6100   \ifcase#3\relax
6101     \ifcase\bbl@getluadir{#1}\relax\else
6102       #2 TLT\relax
6103     \fi
6104   \else
6105     \ifcase\bbl@getluadir{#1}\relax
6106       #2 TRT\relax
6107     \fi
6108   \fi}

```



```

6109% ..00PPTT, with masks 0xC (par dir) and 0x3 (text dir)
6110\def\bbl@thedir{0}
6111\def\bbl@texkdir#1{%
6112  \bbl@setluadir{text}\texkdir{#1}%
6113  \chardef\bbl@thetexkdir#1\relax
6114  \edef\bbl@thedir{\the\numexpr\bbl@thepardir*4+#1}%
6115  \setattribute\bbl@attr@dir{\numexpr\bbl@thepardir*4+#1}}
6116\def\bbl@pardir#1{% Used twice
6117  \bbl@setluadir{par}\pardir{#1}%
6118  \chardef\bbl@thepardir#1\relax}
6119\def\bbl@bodydir{\bbl@setluadir{body}\bodydir}% Used once
6120\def\bbl@pagedir{\bbl@setluadir{page}\pagedir}% Unused
6121\def\bbl@dirparastext{\pardir\the\texkdir\relax}% Used once

```

RTL text inside math needs special attention. It affects not only to actual math stuff, but also to ‘tabular’, which is based on a fake math.

```

6122\ifnum\bbl@bidimode>\z@
6123  \def\bbl@insidemath{0}%
6124  \def\bbl@everymath{\def\bbl@insidemath{1}}
6125  \def\bbl@everydisplay{\def\bbl@insidemath{2}}
6126  \frozen@everymath\expandafter{%
6127    \expandafter\bbl@everymath\the\frozen@everymath}
6128  \frozen@everydisplay\expandafter{%
6129    \expandafter\bbl@everydisplay\the\frozen@everydisplay}
6130  \AtBeginDocument{
6131    \directlua{
6132      function Babel.math_box_dir(head)
6133        if not (token.get_macro('bbl@insidemath') == '0') then
6134          if Babel.hlist_has_bidi(head) then
6135            local d = node.new(node.id'dir')
6136            d.dir = '+TRT'
6137            node.insert_before(head, node.has_glyph(head), d)
6138            for item in node.traverse(head) do
6139              node.set_attribute(item,
6140                Babel.attr_dir, token.get_macro('bbl@thedir'))
6141            end
6142          end
6143        end
6144        return head
6145      end
6146      luatexbase.add_to_callback("hpack_filter", Babel.math_box_dir,
6147        "Babel.math_box_dir", 0)
6148    }}%
6149\fi

```

12.11 Layout

Unlike xetex, luatex requires only minimal changes for right-to-left layouts, particularly in monolingual documents (the engine itself reverses boxes – including column order or headings –, margins, etc.) with `bidi=basic`, without having to patch almost any macro where text direction is relevant.

`\@hangfrom` is useful in many contexts and it is redefined always with the `Layout` option.

There are, however, a number of issues when the text direction is not the same as the box direction (as set by `\bodydir`), and when `\parbox` and `\hangindent` are involved. Fortunately, latest releases of luatex simplify a lot the solution with `\shapemode`.

With the issue #15 I realized commands are best patched, instead of redefined. With a few lines, a modification could be applied to several classes and packages. Now, `tabular` seems to work (at least in simple cases) with `array`, `tabularx`, `hhline`, `colortbl`, `longtable`, `booktabs`, etc. However, `dcolumn` still fails.

```

6150\bbl@trace{Redefinitions for bidi layout}
6151%
6152\langle{*More package options}\rangle ≡
6153\chardef\bbl@eqnpos\z@

```

```

6154 \DeclareOption{leqno}{\chardef\bbl@eqnpos\@ne}
6155 \DeclareOption{fleqn}{\chardef\bbl@eqnpos\tw@}
6156 <\/More package options>
6157 %
6158 \ifnum\bbl@bidimode>\z@
6159   \ifx\matheqdirmode\undefined\else
6160     \matheqdirmode\@ne % A luatex primitive
6161   \fi
6162   \let\bbl@eqnodir\relax
6163   \def\bbl@eqdel{()}
6164   \def\bbl@eqnum{%
6165     {\normalfont\normalcolor
6166       \expandafter\@firstoftwo\bbl@eqdel
6167       \theequation
6168       \expandafter\@secondoftwo\bbl@eqdel}}
6169   \def\bbl@puteqno#1{\eqno\hbox{#1}}
6170   \def\bbl@putleqno#1{\leqno\hbox{#1}}
6171   \def\bbl@eqno@flip#1{%
6172     \ifdim\predisplaysize=-\maxdimen
6173       \eqno
6174       \hb@xt@.01pt{\hb@xt@\displaywidth{\hss{#1}}\hss}%
6175     \else
6176       \leqno\hbox{#1}%
6177     \fi}
6178   \def\bbl@leqno@flip#1{%
6179     \ifdim\predisplaysize=-\maxdimen
6180       \leqno
6181       \hb@xt@.01pt{\hss\hb@xt@\displaywidth{{#1}\hss}}%
6182     \else
6183       \eqno\hbox{#1}%
6184     \fi}
6185   \AtBeginDocument{%
6186     \ifx\bbl@noamsmath\relax\else
6187       \ifx\maketag@@@\undefined % Normal equation, eqnarray
6188         \AddToHook{env/equation/begin}{%
6189           \ifnum\bbl@thetextdir>\z@
6190             \def\bbl@mathboxdir{\def\bbl@insidemath{1}}%
6191             \let\@eqnnum\bbl@eqnum
6192             \edef\bbl@eqnodir{\noexpand\bbl@textdir{\the\bbl@thetextdir}}%
6193             \chardef\bbl@thetextdir\z@
6194             \bbl@add\normalfont{\bbl@eqnodir}%
6195             \ifcase\bbl@eqnpos
6196               \let\bbl@puteqno\bbl@eqno@flip
6197             \or
6198               \let\bbl@puteqno\bbl@leqno@flip
6199             \fi
6200           \fi}%
6201         \ifnum\bbl@eqnpos=\tw@\else
6202           \def\endequation{\bbl@puteqno{\@eqnnum}$$\@ignoretrue}%
6203         \fi
6204         \AddToHook{env/eqnarray/begin}{%
6205           \ifnum\bbl@thetextdir>\z@
6206             \def\bbl@mathboxdir{\def\bbl@insidemath{1}}%
6207             \edef\bbl@eqnodir{\noexpand\bbl@textdir{\the\bbl@thetextdir}}%
6208             \chardef\bbl@thetextdir\z@
6209             \bbl@add\normalfont{\bbl@eqnodir}%
6210             \ifnum\bbl@eqnpos=\@ne
6211               \def\@eqnnum{%
6212                 \setbox\z@\hbox{\bbl@eqnum}%
6213                 \hbox to0.01pt{\hss\hbox to\displaywidth{\box\z@\hss}}}%
6214             \else
6215               \let\@eqnnum\bbl@eqnum
6216             \fi

```

```

6217     \fi}
6218     % Hack. YA luatex bug?:
6219     \expandafter\bb1@sreplace\csname] \endcsname{$$}{\eqno\kern.001pt$}$}%
6220 \else % amstex
6221     \bb1@exp{% Hack to hide maybe undefined conditionals:
6222         \chardef\bb1@eqnpos=0%
6223         \<iftagsleft@>1\<else>\<if@fleqn>2\<fi>\<fi>\relax}%
6224     \ifnum\bb1@eqnpos=\@ne
6225         \let\bb1@ams@lap\hbox
6226     \else
6227         \let\bb1@ams@lap\llap
6228     \fi
6229     \ExplSyntaxOn % Required by \bb1@sreplace with \intertext@
6230     \bb1@sreplace\intertext@{\normalbaselines}%
6231     {\normalbaselines
6232         \ifx\bb1@eqnodir\relax\else\bb1@pardir\@ne\bb1@eqnodir\fi}%
6233     \ExplSyntaxOff
6234     \def\bb1@ams@tagbox#1#2{#1{\bb1@eqnodir#2}}% #1=hbox|@lap|flip
6235     \ifx\bb1@ams@lap\hbox % leqno
6236         \def\bb1@ams@flip#1{%
6237             \hbox to 0.01pt{\hss\hbox to\displaywidth{{#1}\hss}}}%
6238     \else % eqno
6239         \def\bb1@ams@flip#1{%
6240             \hbox to 0.01pt{\hbox to\displaywidth{\hss{#1}}\hss}}%
6241     \fi
6242     \def\bb1@ams@preset#1{%
6243         \def\bb1@mathboxdir{\def\bb1@insidemath{1}}%
6244         \ifnum\bb1@thetextdir>\z@
6245             \edef\bb1@eqnodir{\noexpand\bb1@textdir{\the\bb1@thetextdir}}%
6246             \bb1@sreplace\textdef@{\hbox}{\bb1@ams@tagbox\hbox}%
6247             \bb1@sreplace\maketag@@@{\hbox}{\bb1@ams@tagbox#1}%
6248             \fi}%
6249     \ifnum\bb1@eqnpos=\tw@ \else
6250         \def\bb1@ams@equation{%
6251             \def\bb1@mathboxdir{\def\bb1@insidemath{1}}%
6252             \ifnum\bb1@thetextdir>\z@
6253                 \edef\bb1@eqnodir{\noexpand\bb1@textdir{\the\bb1@thetextdir}}%
6254                 \chardef\bb1@thetextdir\z@
6255                 \bb1@add\normalfont{\bb1@eqnodir}%
6256                 \ifcase\bb1@eqnpos
6257                     \def\veqno##1##2{\bb1@eqno@flip{##1##2}}%
6258                 \or
6259                     \def\veqno##1##2{\bb1@leqno@flip{##1##2}}%
6260                 \fi
6261             \fi}%
6262         \AddToHook{env/equation/begin}{\bb1@ams@equation}%
6263         \AddToHook{env/equation*/begin}{\bb1@ams@equation}%
6264     \fi
6265     \AddToHook{env/cases/begin}{\bb1@ams@preset\bb1@ams@lap}%
6266     \AddToHook{env/multline/begin}{\bb1@ams@preset\hbox}%
6267     \AddToHook{env/gather/begin}{\bb1@ams@preset\bb1@ams@lap}%
6268     \AddToHook{env/gather*/begin}{\bb1@ams@preset\bb1@ams@lap}%
6269     \AddToHook{env/align/begin}{\bb1@ams@preset\bb1@ams@lap}%
6270     \AddToHook{env/align*/begin}{\bb1@ams@preset\bb1@ams@lap}%
6271     \AddToHook{env/eqnalign/begin}{\bb1@ams@preset\hbox}%
6272     % Hackish, for proper alignment. Don't ask me why it works!:
6273     \bb1@exp{% Avoid a 'visible' conditional
6274         \\\AddToHook{env/align*/end}{\<iftag@>\<else>\\tag*{\<fi>}}%
6275     \AddToHook{env/flalign/begin}{\bb1@ams@preset\hbox}%
6276     \AddToHook{env/split/before}{%
6277         \def\bb1@mathboxdir{\def\bb1@insidemath{1}}%
6278         \ifnum\bb1@thetextdir>\z@
6279             \bb1@ifsamestring\@currenvir{equation}%

```

```

6280         {\ifx\bb1@ams@lap\hbox % leqno
6281         \def\bb1@ams@flip#1{%
6282         \hbox to 0.01pt{\hbox to \displaywidth{#{1}\hss}\hss}}%
6283         \else
6284         \def\bb1@ams@flip#1{%
6285         \hbox to 0.01pt{\hss\hbox to \displaywidth{\hss{#1}}}%
6286         \fi}%
6287     }%
6288     \fi}%
6289 \fi\fi}
6290 \fi
6291 \def\bb1@provide@extra#1{%
6292 % == Counters: mapdigits ==
6293 % Native digits
6294 \ifx\bb1@KVP@mapdigits\@nnil\else
6295 \bb1@ifunset{\bb1@dgnat\language\name}{}%
6296 {\RequirePackage{luatexbase}%
6297 \bb1@activate@preotf
6298 \directlua{
6299     Babel = Babel or {} %% -> presets in luababel
6300     Babel.digits_mapped = true
6301     Babel.digits = Babel.digits or {}
6302     Babel.digits[\the\localeid] =
6303     table.pack(string.utfvalue('\bb1@cl{dgnat}'))
6304     if not Babel.numbers then
6305     function Babel.numbers(head)
6306         local LOCALE = Babel.attr_locale
6307         local GLYPH = node.id'glyph'
6308         local inmath = false
6309         for item in node.traverse(head) do
6310             if not inmath and item.id == GLYPH then
6311                 local temp = node.get_attribute(item, LOCALE)
6312                 if Babel.digits[temp] then
6313                     local chr = item.char
6314                     if chr > 47 and chr < 58 then
6315                         item.char = Babel.digits[temp][chr-47]
6316                     end
6317                 end
6318                 elseif item.id == node.id'math' then
6319                     inmath = (item.subtype == 0)
6320                 end
6321             end
6322         return head
6323     end
6324     end
6325 }}%
6326 \fi
6327 % == transforms ==
6328 \ifx\bb1@KVP@transforms\@nnil\else
6329 \def\bb1@elt##1##2##3{%
6330 \in@{${transforms.}}{##1}%
6331 \ifin@
6332 \def\bb1@tempa{##1}%
6333 \bb1@replace\bb1@tempa{transforms.}{}%
6334 \bb1@carg\bb1@transforms{babel\bb1@tempa}{##2}{##3}%
6335 \fi}%
6336 \csname bbl@inidata@\language\name\endcsname
6337 \bb1@release@transforms\relax % \relax closes the last item.
6338 \fi}
6339 % Start tabular here:
6340 \def\localerestoredirs{%
6341 \ifcase\bb1@thetextdir
6342 \ifnum\textdirection=\z@\else\textdir TLT\fi

```

```

6343 \else
6344 \ifnum\textdirection=\@ne\else\textdir TRT\fi
6345 \fi
6346 \ifcase\bbl@thepardir
6347 \ifnum\pardirection=\z@\else\pardir TLT\bodydir TLT\fi
6348 \else
6349 \ifnum\pardirection=\@ne\else\pardir TRT\bodydir TRT\fi
6350 \fi}
6351 \IfBabelLayout{tabular}%
6352 {\chardef\bbl@tabular@mode\tw}% All RTL
6353 {\IfBabelLayout{notabular}%
6354 {\chardef\bbl@tabular@mode\z}%
6355 {\chardef\bbl@tabular@mode\@ne}}% Mixed, with LTR cols
6356 \ifnum\bbl@bidimode>\@ne
6357 \ifnum\bbl@tabular@mode=\@ne
6358 \let\bbl@parabefore\relax
6359 \AddToHook{para/before}{\bbl@parabefore}
6360 \AtBeginDocument{%
6361 \bbl@replace\@tabular{$}{$}%
6362 \def\bbl@insidemath{0}%
6363 \def\bbl@parabefore{\localerestoredirs}}%
6364 \ifnum\bbl@tabular@mode=\@ne
6365 \bbl@ifunset{@tabclassz}{}%
6366 \bbl@exp{% Hide conditionals
6367 \\\bbl@sreplace\\ \@tabclassz
6368 {\<ifcase>\\ \@chnum}%
6369 {\\\localerestoredirs\<ifcase>\\ \@chnum}}}%
6370 \@ifpackageloaded{colortbl}%
6371 {\bbl@sreplace\@classz
6372 {\hbox\bgroup\bgroup}{\hbox\bgroup\bgroup\localerestoredirs}}%
6373 {\@ifpackageloaded{array}%
6374 {\bbl@exp{% Hide conditionals
6375 \\\bbl@sreplace\\ \@classz
6376 {\<ifcase>\\ \@chnum}%
6377 {\bgroup\\ \localerestoredirs\<ifcase>\\ \@chnum}%
6378 \\\bbl@sreplace\\ \@classz
6379 {\\\do@row@strut\<fi>}{\\do@row@strut\<fi>\egroup}}}%
6380 {}}%
6381 \fi}
6382 \fi
6383 \AtBeginDocument{%
6384 \@ifpackageloaded{multicol}%
6385 {\toks@\expandafter{\multi@column@out}}%
6386 \edef\multi@column@out{\bodydir\pagedir\the\toks@}%
6387 {}}
6388 \fi
6389 \ifx\bbl@opt@layout\@nnil\endinput\fi % if no layout

```

OMEGA provided a companion to `\mathdir` (`\nextfake`) for those cases where we did not want it to be applied, so that the writing direction of the main text was left unchanged. `\bbl@nextfake` is an attempt to emulate it, because `luatex` has removed it without an alternative. Also, `\hangindent` does not honour direction changes by default, so we need to redefine `\@hangfrom`.

```

6390 \ifnum\bbl@bidimode>\z@
6391 \def\bbl@nextfake#1{% non-local changes, use always inside a group!
6392 \bbl@exp{%
6393 \def\\bbl@insidemath{0}%
6394 \mathdir\the\bodydir
6395 #1% Once entered in math, set boxes to restore values
6396 \<ifmmode>%
6397 \everyvbox{%
6398 \the\everyvbox
6399 \bodydir\the\bodydir
6400 \mathdir\the\mathdir

```

```

6401         \everyhbox{\the\everyhbox}%
6402         \everyvbox{\the\everyvbox}}%
6403     \everyhbox{%
6404         \the\everyhbox
6405         \bodydir\the\bodydir
6406         \mathdir\the\mathdir
6407         \everyhbox{\the\everyhbox}%
6408         \everyvbox{\the\everyvbox}}%
6409     \<fi>}}%
6410 \def\@hangfrom#1{%
6411     \setbox\@tempboxa\hbox{\{#1\}}%
6412     \hangindent\wd\@tempboxa
6413     \ifnum\bb1@getluadir{page}=\bb1@getluadir{par}\else
6414         \shapemode\@ne
6415     \fi
6416     \noindent\box\@tempboxa}
6417 \fi
6418 \IfBabelLayout{tabular}
6419 {\let\bb1@OL@tabular\@tabular
6420  \bb1@replace\@tabular{\$}\bb1@nextfake$}%
6421 \let\bb1@NL@tabular\@tabular
6422 \AtBeginDocument{%
6423     \ifx\bb1@NL@tabular\@tabular\else
6424         \bb1@replace\@tabular{\$}\bb1@nextfake$}%
6425     \let\bb1@NL@tabular\@tabular
6426     \fi}}
6427 {}
6428 \IfBabelLayout{lists}
6429 {\let\bb1@OL@list\list
6430  \bb1@sreplace\list{\parshape}\bb1@listparshape}%
6431 \let\bb1@NL@list\list
6432 \def\bb1@listparshape#1#2#3{%
6433     \parshape #1 #2 #3 %
6434     \ifnum\bb1@getluadir{page}=\bb1@getluadir{par}\else
6435         \shapemode\tw@
6436     \fi}}
6437 {}
6438 \IfBabelLayout{graphics}
6439 {\let\bb1@pictresetdir\relax
6440  \def\bb1@pictsetdir#1{%
6441      \ifcase\bb1@thetextdir
6442          \let\bb1@pictresetdir\relax
6443      \else
6444          \ifcase#1\bodydir TLT % Remember this sets the inner boxes
6445              \or\textdir TLT
6446              \else\bodydir TLT \textdir TLT
6447          \fi
6448          % \(\text|par)dir required in pgf:
6449          \def\bb1@pictresetdir{\bodydir TRT\pardir TRT\textdir TRT\relax}%
6450      \fi}%
6451 \AddToHook{env/picture/begin}{\bb1@pictsetdir\tw@}%
6452 \directlua{
6453     Babel.get_picture_dir = true
6454     Babel.picture_has_bidi = 0
6455     %
6456     function Babel.picture_dir (head)
6457         if not Babel.get_picture_dir then return head end
6458         if Babel.hlist_has_bidi(head) then
6459             Babel.picture_has_bidi = 1
6460         end
6461         return head
6462     end
6463     luatexbase.add_to_callback("hpack_filter", Babel.picture_dir,

```

```

6464 "Babel.picture_dir")
6465 }%
6466 \AtBeginDocument{%
6467   \def\LS@rot{%
6468     \setbox\@outputbox\vbox{%
6469       \hbox dir TLT{\rotatebox{90}{\box\@outputbox}}}%
6470   \long\def\put(#1,#2)#3{%
6471     \@killglue
6472     % Try:
6473     \ifx\bbbl@pictresetdir\relax
6474       \def\bbbl@tempc{0}%
6475     \else
6476       \directlua{
6477         Babel.get_picture_dir = true
6478         Babel.picture_has_bidi = 0
6479       }%
6480       \setbox\z@\hb@xt@\z@{%
6481         \@defaultunitsset\@tempdimc{#1}\unitlength
6482         \kern\@tempdimc
6483         #3\hss}% TODO: #3 executed twice (below). That's bad.
6484       \edef\bbbl@tempc{\directlua{tex.print(Babel.picture_has_bidi)}}%
6485     \fi
6486     % Do:
6487     \@defaultunitsset\@tempdimc{#2}\unitlength
6488     \raise\@tempdimc\hb@xt@\z@{%
6489       \@defaultunitsset\@tempdimc{#1}\unitlength
6490       \kern\@tempdimc
6491       {\ifnum\bbbl@tempc>\z@\bbbl@pictresetdir\fi#3}\hss}%
6492     \ignorespaces}%
6493   \MakeRobust\put}%
6494 \AtBeginDocument
6495 {\AddToHook{cmd/diagbox@pict/before}{\let\bbbl@pictsetdir\@gobble}%
6496 \ifx\pgfpicture\@undefined\else % TODO. Allow deactivate?
6497   \AddToHook{env/pgfpicture/begin}{\bbbl@pictsetdir\@ne}%
6498   \bbbl@add\pgfinterruptpicture{\bbbl@pictresetdir}%
6499   \bbbl@add\pgfsys@beginpicture{\bbbl@pictsetdir\z@}%
6500 \fi
6501 \ifx\tikzpicture\@undefined\else
6502   \AddToHook{env/tikzpicture/begin}{\bbbl@pictsetdir\tw@}%
6503   \bbbl@add\tikz@atbegin@node{\bbbl@pictresetdir}%
6504   \bbbl@sreplace\tikz{\begingroup}{\begingroup\bbbl@pictsetdir\tw@}%
6505 \fi
6506 \ifx\tcolorbox\@undefined\else
6507   \def\tcb@drawing@env@begin{%
6508     \csname tcb@before@tcb@split@state\endcsname
6509     \bbbl@pictsetdir\tw@
6510     \begin{\kvtcb@graphenv}%
6511     \tcb@bbdraw%
6512     \tcb@apply@graph@patches
6513   }%
6514   \def\tcb@drawing@env@end{%
6515     \end{\kvtcb@graphenv}%
6516     \bbbl@pictresetdir
6517     \csname tcb@after@tcb@split@state\endcsname
6518   }%
6519 \fi
6520 }}
6521 {}

```

Implicitly reverses sectioning labels in bidi=basic-r, because the full stop is not in contact with L numbers any more. I think there must be a better way. Assumes bidi=basic, but there are some additional readjustments for bidi=default.

```

6522 \IfBabelLayout{counters*}%

```

```

6523 {\bbl@add\bbl@opt@layout{.counters.}%
6524 \directlua{
6525   luatexbase.add_to_callback("process_output_buffer",
6526     Babel.discard_sublr , "Babel.discard_sublr") }%
6527 }{}
6528 \IfBabelLayout{counters}%
6529 {\let\bbl@OL@textsuperscript\@textsuperscript
6530 \bbl@sreplace\@textsuperscript{\m@th}{\m@th\mathdir\pagedir}%
6531 \let\bbl@latinarabic=\@arabic
6532 \let\bbl@OL@arabic\@arabic
6533 \def\@arabic#1{\babelsublr{\bbl@latinarabic#1}}%
6534 \@ifpackagewith{babel}{bidi=default}%
6535 {\let\bbl@asciroman=\@roman
6536 \let\bbl@OL@roman\@roman
6537 \def\@roman#1{\babelsublr{\ensureascii{\bbl@asciroman#1}}}%
6538 \let\bbl@asciiRoman=\@Roman
6539 \let\bbl@OL@roman\@Roman
6540 \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asciiRoman#1}}}%
6541 \let\bbl@OL@labelenumii\labelenumii
6542 \def\labelenumii{}\theenumii}%
6543 \let\bbl@OL@p@enumiii\p@enumiii
6544 \def\p@enumiii{\p@enumii}\theenumii{}}{}{}
6545 <Footnote changes>
6546 \IfBabelLayout{footnotes}%
6547 {\let\bbl@OL@footnote\footnote
6548 \BabelFootnote\footnote\language{}}{}%
6549 \BabelFootnote\localfootnote\language{}}{}%
6550 \BabelFootnote\mainfootnote{}}{}{}
6551 {}

```

Some \TeX macros use internally the math mode for text formatting. They have very little in common and are grouped here, as a single option.

```

6552 \IfBabelLayout{extras}%
6553 {\let\bbl@OL@underline\underline
6554 \bbl@sreplace\underline{$\@@underline}{\bbl@nextfake$\@@underline}%
6555 \let\bbl@OL@LaTeX2e\LaTeX2e
6556 \DeclareRobustCommand{\LaTeXe}{\mbox{\m@th
6557 \if b\expandafter\@car\@series\@nil\boldmath\fi
6558 \babelsublr}%
6559 \LaTeX\kern.15em2\bbl@nextfake$_{\textstyle\varepsilon}$}}
6560 {}
6561 </luatex>

```

12.12 Lua: transforms

After declaring the table containing the patterns with their replacements, we define some auxiliary functions: `str_to_nodes` converts the string returned by a function to a node list, taking the node at base as a model (font, language, etc.); `fetch_word` fetches a series of glyphs and discretionaries, which pattern is matched against (if there is a match, it is called again before trying other patterns, and this is very likely the main bottleneck).

`post_hyphenate_replace` is the callback applied after `lang.hyphenate`. This means the automatic hyphenation points are known. As empty captures return a byte position (as explained in the `luatex` manual), we must convert it to a utf8 position. With `first`, the last byte can be the leading byte in a utf8 sequence, so we just remove it and add 1 to the resulting length. With `last` we must take into account the capture position points to the next character. Here `word_head` points to the starting node of the text to be matched.

```

6562 <*transforms>
6563 Babel.linebreaking.replacements = {}
6564 Babel.linebreaking.replacements[0] = {} -- pre
6565 Babel.linebreaking.replacements[1] = {} -- post
6566 Babel.linebreaking.replacements[2] = {} -- post-line WIP
6567
6568 -- Discretionaries contain strings as nodes

```



```

6569 function Babel.str_to_nodes(fn, matches, base)
6570   local n, head, last
6571   if fn == nil then return nil end
6572   for s in string.utfvalues(fn(matches)) do
6573     if base.id == 7 then
6574       base = base.replace
6575     end
6576     n = node.copy(base)
6577     n.char = s
6578     if not head then
6579       head = n
6580     else
6581       last.next = n
6582     end
6583     last = n
6584   end
6585   return head
6586 end
6587
6588 Babel.fetch_subtext = {}
6589
6590 Babel.ignore_pre_char = function(node)
6591   return (node.lang == Babel.nohyphenation)
6592 end
6593
6594 -- Merging both functions doesn't seem feasible, because there are too
6595 -- many differences.
6596 Babel.fetch_subtext[0] = function(head)
6597   local word_string = ''
6598   local word_nodes = {}
6599   local lang
6600   local item = head
6601   local inmath = false
6602
6603   while item do
6604
6605     if item.id == 11 then
6606       inmath = (item.subtype == 0)
6607     end
6608
6609     if inmath then
6610       -- pass
6611     elseif item.id == 29 then
6612       local locale = node.get_attribute(item, Babel.attr_locale)
6613
6614       if lang == locale or lang == nil then
6615         lang = lang or locale
6616         if Babel.ignore_pre_char(item) then
6617           word_string = word_string .. Babel.us_char
6618         else
6619           word_string = word_string .. unicode.utf8.char(item.char)
6620         end
6621         word_nodes[#word_nodes+1] = item
6622       else
6623         break
6624       end
6625     end
6626
6627     elseif item.id == 12 and item.subtype == 13 then
6628       word_string = word_string .. ' '
6629       word_nodes[#word_nodes+1] = item
6630
6631     -- Ignore leading unrecognized nodes, too.

```

```

6632     elseif word_string ~= '' then
6633         word_string = word_string .. Babel.us_char
6634         word_nodes[#word_nodes+1] = item -- Will be ignored
6635     end
6636
6637     item = item.next
6638 end
6639
6640 -- Here and above we remove some trailing chars but not the
6641 -- corresponding nodes. But they aren't accessed.
6642 if word_string:sub(-1) == ' ' then
6643     word_string = word_string:sub(1,-2)
6644 end
6645 word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
6646 return word_string, word_nodes, item, lang
6647 end
6648
6649 Babel.fetch_subtext[1] = function(head)
6650     local word_string = ''
6651     local word_nodes = {}
6652     local lang
6653     local item = head
6654     local inmath = false
6655
6656     while item do
6657
6658         if item.id == 11 then
6659             inmath = (item.subtype == 0)
6660         end
6661
6662         if inmath then
6663             -- pass
6664
6665         elseif item.id == 29 then
6666             if item.lang == lang or lang == nil then
6667                 if (item.char ~= 124) and (item.char ~= 61) then -- not =, not |
6668                     lang = lang or item.lang
6669                     word_string = word_string .. unicode.utf8.char(item.char)
6670                     word_nodes[#word_nodes+1] = item
6671                 end
6672             else
6673                 break
6674             end
6675
6676         elseif item.id == 7 and item.subtype == 2 then
6677             word_string = word_string .. '='
6678             word_nodes[#word_nodes+1] = item
6679
6680         elseif item.id == 7 and item.subtype == 3 then
6681             word_string = word_string .. '|'
6682             word_nodes[#word_nodes+1] = item
6683
6684         -- (1) Go to next word if nothing was found, and (2) implicitly
6685         -- remove leading USs.
6686         elseif word_string == '' then
6687             -- pass
6688
6689         -- This is the responsible for splitting by words.
6690         elseif (item.id == 12 and item.subtype == 13) then
6691             break
6692
6693         else
6694             word_string = word_string .. Babel.us_char

```

```

6695     word_nodes[#word_nodes+1] = item -- Will be ignored
6696 end
6697
6698     item = item.next
6699 end
6700
6701 word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
6702 return word_string, word_nodes, item, lang
6703 end
6704
6705 function Babel.pre_hyphenate_replace(head)
6706     Babel.hyphenate_replace(head, 0)
6707 end
6708
6709 function Babel.post_hyphenate_replace(head)
6710     Babel.hyphenate_replace(head, 1)
6711 end
6712
6713 Babel.us_char = string.char(31)
6714
6715 function Babel.hyphenate_replace(head, mode)
6716     local u = unicode.utf8
6717     local lbkr = Babel.linebreaking.replacements[mode]
6718     if mode == 2 then mode = 0 end -- WIP
6719
6720     local word_head = head
6721
6722     while true do -- for each subtext block
6723
6724         local w, w_nodes, nw, lang = Babel.fetch_subtext[mode](word_head)
6725
6726         if Babel.debug then
6727             print()
6728             print((mode == 0) and '@@@<' or '@@@>', w)
6729         end
6730
6731         if nw == nil and w == '' then break end
6732
6733         if not lang then goto next end
6734         if not lbkr[lang] then goto next end
6735
6736         -- For each saved (pre|post)hyphenation. TODO. Reconsider how
6737         -- loops are nested.
6738         for k=1, #lbkr[lang] do
6739             local p = lbkr[lang][k].pattern
6740             local r = lbkr[lang][k].replace
6741             local attr = lbkr[lang][k].attr or -1
6742
6743             if Babel.debug then
6744                 print('*****', p, mode)
6745             end
6746
6747             -- This variable is set in some cases below to the first *byte*
6748             -- after the match, either as found by u.match (faster) or the
6749             -- computed position based on sc if w has changed.
6750             local last_match = 0
6751             local step = 0
6752
6753             -- For every match.
6754             while true do
6755                 if Babel.debug then
6756                     print('====')
6757                 end

```

```

6758     local new -- used when inserting and removing nodes
6759
6760     local matches = { u.match(w, p, last_match) }
6761
6762     if #matches < 2 then break end
6763
6764     -- Get and remove empty captures (with ()'s, which return a
6765     -- number with the position), and keep actual captures
6766     -- (from (...)), if any, in matches.
6767     local first = table.remove(matches, 1)
6768     local last  = table.remove(matches, #matches)
6769     -- Non re-fetched substrings may contain \31, which separates
6770     -- subsubstrings.
6771     if string.find(w:sub(first, last-1), Babel.us_char) then break end
6772
6773     local save_last = last -- with A()BC()D, points to D
6774
6775     -- Fix offsets, from bytes to unicode. Explained above.
6776     first = u.len(w:sub(1, first-1)) + 1
6777     last  = u.len(w:sub(1, last-1)) -- now last points to C
6778
6779     -- This loop stores in a small table the nodes
6780     -- corresponding to the pattern. Used by 'data' to provide a
6781     -- predictable behavior with 'insert' (w_nodes is modified on
6782     -- the fly), and also access to 'remove'd nodes.
6783     local sc = first-1 -- Used below, too
6784     local data_nodes = {}
6785
6786     local enabled = true
6787     for q = 1, last-first+1 do
6788         data_nodes[q] = w_nodes[sc+q]
6789         if enabled
6790             and attr > -1
6791             and not node.has_attribute(data_nodes[q], attr)
6792         then
6793             enabled = false
6794         end
6795     end
6796
6797     -- This loop traverses the matched substring and takes the
6798     -- corresponding action stored in the replacement list.
6799     -- sc = the position in substr nodes / string
6800     -- rc = the replacement table index
6801     local rc = 0
6802
6803     while rc < last-first+1 do -- for each replacement
6804         if Babel.debug then
6805             print('.....', rc + 1)
6806         end
6807         sc = sc + 1
6808         rc = rc + 1
6809
6810         if Babel.debug then
6811             Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
6812             local ss = ''
6813             for itt in node.traverse(head) do
6814                 if itt.id == 29 then
6815                     ss = ss .. unicode.utf8.char(itt.char)
6816                 else
6817                     ss = ss .. '{' .. itt.id .. '}'
6818                 end
6819             end
6820             print('*****', ss)

```

```

6821
6822     end
6823
6824     local crep = r[rc]
6825     local item = w_nodes[sc]
6826     local item_base = item
6827     local placeholder = Babel.us_char
6828     local d
6829
6830     if crep and crep.data then
6831         item_base = data_nodes[crep.data]
6832     end
6833
6834     if crep then
6835         step = crep.step or 0
6836     end
6837
6838     if (not enabled) or (crep and next(crep) == nil) then -- = {}
6839         last_match = save_last    -- Optimization
6840         goto next
6841
6842     elseif crep == nil or crep.remove then
6843         node.remove(head, item)
6844         table.remove(w_nodes, sc)
6845         w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
6846         sc = sc - 1    -- Nothing has been inserted.
6847         last_match = utf8.offset(w, sc+1+step)
6848         goto next
6849
6850     elseif crep and crep.kashida then -- Experimental
6851         node.set_attribute(item,
6852             Babel.attr_kashida,
6853             crep.kashida)
6854         last_match = utf8.offset(w, sc+1+step)
6855         goto next
6856
6857     elseif crep and crep.string then
6858         local str = crep.string(matches)
6859         if str == '' then -- Gather with nil
6860             node.remove(head, item)
6861             table.remove(w_nodes, sc)
6862             w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
6863             sc = sc - 1    -- Nothing has been inserted.
6864         else
6865             local loop_first = true
6866             for s in string.utfvalues(str) do
6867                 d = node.copy(item_base)
6868                 d.char = s
6869                 if loop_first then
6870                     loop_first = false
6871                     head, new = node.insert_before(head, item, d)
6872                     if sc == 1 then
6873                         word_head = head
6874                     end
6875                     w_nodes[sc] = d
6876                     w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc+1)
6877                 else
6878                     sc = sc + 1
6879                     head, new = node.insert_before(head, item, d)
6880                     table.insert(w_nodes, sc, new)
6881                     w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc)
6882                 end
6883                 if Babel.debug then

```

```

6884         print('.....', 'str')
6885         Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
6886     end
6887     end -- for
6888     node.remove(head, item)
6889 end -- if ''
6890 last_match = utf8.offset(w, sc+1+step)
6891 goto next
6892
6893 elseif mode == 1 and crep and (crep.pre or crep.no or crep.post) then
6894     d = node.new(7, 3) -- (disc, regular)
6895     d.pre = Babel.str_to_nodes(crep.pre, matches, item_base)
6896     d.post = Babel.str_to_nodes(crep.post, matches, item_base)
6897     d.replace = Babel.str_to_nodes(crep.no, matches, item_base)
6898     d.attr = item_base.attr
6899     if crep.pre == nil then -- TeXbook p96
6900         d.penalty = crep.penalty or tex.hyphenpenalty
6901     else
6902         d.penalty = crep.penalty or tex.exhyphenpenalty
6903     end
6904     placeholder = '|'
6905     head, new = node.insert_before(head, item, d)
6906
6907 elseif mode == 0 and crep and (crep.pre or crep.no or crep.post) then
6908     -- ERROR
6909
6910 elseif crep and crep.penalty then
6911     d = node.new(14, 0) -- (penalty, userpenalty)
6912     d.attr = item_base.attr
6913     d.penalty = crep.penalty
6914     head, new = node.insert_before(head, item, d)
6915
6916 elseif crep and crep.space then
6917     -- 655360 = 10 pt = 10 * 65536 sp
6918     d = node.new(12, 13) -- (glue, spaceskip)
6919     local quad = font.getfont(item_base.font).size or 655360
6920     node.setglue(d, crep.space[1] * quad,
6921                 crep.space[2] * quad,
6922                 crep.space[3] * quad)
6923     if mode == 0 then
6924         placeholder = ' '
6925     end
6926     head, new = node.insert_before(head, item, d)
6927
6928 elseif crep and crep.spacefactor then
6929     d = node.new(12, 13) -- (glue, spaceskip)
6930     local base_font = font.getfont(item_base.font)
6931     node.setglue(d,
6932                 crep.spacefactor[1] * base_font.parameters['space'],
6933                 crep.spacefactor[2] * base_font.parameters['space_stretch'],
6934                 crep.spacefactor[3] * base_font.parameters['space_shrink'])
6935     if mode == 0 then
6936         placeholder = ' '
6937     end
6938     head, new = node.insert_before(head, item, d)
6939
6940 elseif mode == 0 and crep and crep.space then
6941     -- ERROR
6942
6943 end -- ie replacement cases
6944
6945 -- Shared by disc, space and penalty.
6946 if sc == 1 then

```

```

6947         word_head = head
6948     end
6949     if crep.insert then
6950         w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc)
6951         table.insert(w_nodes, sc, new)
6952         last = last + 1
6953     else
6954         w_nodes[sc] = d
6955         node.remove(head, item)
6956         w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc+1)
6957     end
6958
6959     last_match = utf8.offset(w, sc+1+step)
6960
6961     ::next::
6962
6963     end -- for each replacement
6964
6965     if Babel.debug then
6966         print('....', '/')
6967         Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
6968     end
6969
6970     end -- for match
6971
6972     end -- for patterns
6973
6974     ::next::
6975     word_head = nw
6976 end -- for substring
6977 return head
6978 end
6979
6980 -- This table stores capture maps, numbered consecutively
6981 Babel.capture_maps = {}
6982
6983 -- The following functions belong to the next macro
6984 function Babel.capture_func(key, cap)
6985     local ret = "[" .. cap:gsub('{{[0-9]}}', "]]..m[%1]..[" .. "]"
6986     local cnt
6987     local u = unicode.utf8
6988     ret, cnt = ret:gsub('{{[0-9]}|(^|+)|(.-)}', Babel.capture_func_map)
6989     if cnt == 0 then
6990         ret = u.gsub(ret, '{{(%x%x%x%x+)}',
6991             function (n)
6992                 return u.char(tonumber(n, 16))
6993             end)
6994     end
6995     ret = ret:gsub("%[%[%]]%.", '')
6996     ret = ret:gsub("%.%[%[%]]%", '')
6997     return key .. [[=function(m) return ]] .. ret .. [[ end]]
6998 end
6999
7000 function Babel.capt_map(from, mapno)
7001     return Babel.capture_maps[mapno][from] or from
7002 end
7003
7004 -- Handle the {n|abc|ABC} syntax in captures
7005 function Babel.capture_func_map(capno, from, to)
7006     local u = unicode.utf8
7007     from = u.gsub(from, '{{(%x%x%x%x+)}',
7008         function (n)
7009             return u.char(tonumber(n, 16))

```

```

7010     end)
7011 to = u.gsub(to, '{(%x%x%x%x+)}',
7012     function (n)
7013         return u.char(tonumber(n, 16))
7014     end)
7015 local froms = {}
7016 for s in string.utfcharacters(from) do
7017     table.insert(froms, s)
7018 end
7019 local cnt = 1
7020 table.insert(Babel.capture_maps, {})
7021 local mlen = table.getn(Babel.capture_maps)
7022 for s in string.utfcharacters(to) do
7023     Babel.capture_maps[mlen][froms[cnt]] = s
7024     cnt = cnt + 1
7025 end
7026 return "]]..Babel.capt_map(m[" .. capno .. "], " ..
7027     (mlen) .. ").." .. "["
7028 end
7029
7030 -- Create/Extend reversed sorted list of kashida weights:
7031 function Babel.capture_kashida(key, wt)
7032     wt = tonumber(wt)
7033     if Babel.kashida_wts then
7034         for p, q in ipairs(Babel.kashida_wts) do
7035             if wt == q then
7036                 break
7037             elseif wt > q then
7038                 table.insert(Babel.kashida_wts, p, wt)
7039                 break
7040             elseif table.getn(Babel.kashida_wts) == p then
7041                 table.insert(Babel.kashida_wts, wt)
7042             end
7043         end
7044     else
7045         Babel.kashida_wts = { wt }
7046     end
7047     return 'kashida = ' .. wt
7048 end
7049 </transforms>

```

12.13 Lua: Auto bidi with basic and basic-r

The file `babel-data-bidi.lua` currently only contains data. It is a large and boring file and it is not shown here (see the generated file), but here is a sample:

```

[0x25]={d='et'},
[0x26]={d='on'},
[0x27]={d='on'},
[0x28]={d='on', m=0x29},
[0x29]={d='on', m=0x28},
[0x2A]={d='on'},
[0x2B]={d='es'},
[0x2C]={d='cs'},

```

For the meaning of these codes, see the Unicode standard.

Now the `basic-r` bidi mode. One of the aims is to implement a fast and simple bidi algorithm, with a single loop. I managed to do it for R texts, with a second smaller loop for a special case. The code is still somewhat chaotic, but its behavior is essentially correct. I cannot resist copying the following text from Emacs `bidi.c` (which also attempts to implement the bidi algorithm with a single loop):

Arrrrgh!! The UAX#9 algorithm is too deeply entrenched in the assumption of batch-style processing [...]. May the fleas of a thousand camels infest the armpits of those who design

supposedly general-purpose algorithms by looking at their own implementations, and fail to consider other possible implementations!

Well, it took me some time to guess what the batch rules in UAX#9 actually mean (in other word, *what* they do and *why*, and not only *how*), but I think (or I hope) I've managed to understand them. In some sense, there are two bidi modes, one for numbers, and the other for text. Furthermore, setting just the direction in R text is not enough, because there are actually *two* R modes (set explicitly in Unicode with RLM and ALM). In babel the dir is set by a higher protocol based on the language/script, which in turn sets the correct dir (<l>, <r> or <al>).

From UAX#9: “Where available, markup should be used instead of the explicit formatting characters”. So, this simple version just ignores formatting characters. Actually, most of that annex is devoted to how to handle them.

BD14-BD16 are not implemented. Unicode (and the W3C) are making a great effort to deal with some special problematic cases in “streamed” plain text. I don't think this is the way to go – particular issues should be fixed by a high level interface taking into account the needs of the document. And here is where luatex excels, because everything related to bidi writing is under our control.

```
7050 {*basic-r}
7051 Babel = Babel or {}
7052
7053 Babel.bidi_enabled = true
7054
7055 require('babel-data-bidi.lua')
7056
7057 local characters = Babel.characters
7058 local ranges = Babel.ranges
7059
7060 local DIR = node.id("dir")
7061
7062 local function dir_mark(head, from, to, outer)
7063   dir = (outer == 'r') and 'TLT' or 'TRT' -- ie, reverse
7064   local d = node.new(DIR)
7065   d.dir = '+' .. dir
7066   node.insert_before(head, from, d)
7067   d = node.new(DIR)
7068   d.dir = '-' .. dir
7069   node.insert_after(head, to, d)
7070 end
7071
7072 function Babel.bidi(head, ispar)
7073   local first_n, last_n          -- first and last char with nums
7074   local last_es                  -- an auxiliary 'last' used with nums
7075   local first_d, last_d          -- first and last char in L/R block
7076   local dir, dir_real
```

Next also depends on script/lang (<al>/<r>). To be set by babel. tex.pardir is dangerous, could be (re)set but it should be changed only in vmode. There are two strong's – strong = l/al/r and strong_lr = l/r (there must be a better way):

```
7077   local strong = ('TRT' == tex.pardir) and 'r' or 'l'
7078   local strong_lr = (strong == 'l') and 'l' or 'r'
7079   local outer = strong
7080
7081   local new_dir = false
7082   local first_dir = false
7083   local inmath = false
7084
7085   local last_lr
7086
7087   local type_n = ''
7088
7089   for item in node.traverse(head) do
7090
7091     -- three cases: glyph, dir, otherwise
7092     if item.id == node.id'glyph'
```

```

7093     or (item.id == 7 and item.subtype == 2) then
7094
7095     local itemchar
7096     if item.id == 7 and item.subtype == 2 then
7097         itemchar = item.replace.char
7098     else
7099         itemchar = item.char
7100     end
7101     local chardata = characters[itemchar]
7102     dir = chardata and chardata.d or nil
7103     if not dir then
7104         for nn, et in ipairs(ranges) do
7105             if itemchar < et[1] then
7106                 break
7107             elseif itemchar <= et[2] then
7108                 dir = et[3]
7109                 break
7110             end
7111         end
7112     end
7113     dir = dir or 'l'
7114     if inmath then dir = ('TRT' == tex.mathdir) and 'r' or 'l' end

```

Next is based on the assumption babel sets the language AND switches the script with its dir. We treat a language block as a separate Unicode sequence. The following piece of code is executed at the first glyph after a ‘dir’ node. We don’t know the current language until then. This is not exactly true, as the math mode may insert explicit dirs in the node list, so, for the moment there is a hack by brute force (just above).

```

7115     if new_dir then
7116         attr_dir = 0
7117         for at in node.traverse(item.attr) do
7118             if at.number == Babel.attr_dir then
7119                 attr_dir = at.value & 0x3
7120             end
7121         end
7122         if attr_dir == 1 then
7123             strong = 'r'
7124         elseif attr_dir == 2 then
7125             strong = 'al'
7126         else
7127             strong = 'l'
7128         end
7129         strong_lr = (strong == 'l') and 'l' or 'r'
7130         outer = strong_lr
7131         new_dir = false
7132     end
7133
7134     if dir == 'nsm' then dir = strong end -- W1

```

Numbers. The dual <al>/<r> system for R is somewhat cumbersome.

```

7135     dir_real = dir -- We need dir_real to set strong below
7136     if dir == 'al' then dir = 'r' end -- W3

```

By W2, there are no <en> <et> <es> if strong == <al>, only <an>. Therefore, there are not <et en> nor <en et>, W5 can be ignored, and W6 applied:

```

7137     if strong == 'al' then
7138         if dir == 'en' then dir = 'an' end -- W2
7139         if dir == 'et' or dir == 'es' then dir = 'on' end -- W6
7140         strong_lr = 'r' -- W3
7141     end

```

Once finished the basic setup for glyphs, consider the two other cases: dir node and the rest.

```

7142     elseif item.id == node.id'dir' and not inmath then
7143         new_dir = true

```

```

7144     dir = nil
7145   elseif item.id == node.id'math' then
7146     inmath = (item.subtype == 0)
7147   else
7148     dir = nil          -- Not a char
7149   end

```

Numbers in R mode. A sequence of <en>, <et>, <an>, <es> and <cs> is typeset (with some rules) in L mode. We store the starting and ending points, and only when anything different is found (including nil, ie, a non-char), the textdir is set. This means you cannot insert, say, a whatsit, but this is what I would expect (with luacolor you may colorize some digits). Anyway, this behavior could be changed with a switch in the future. Note in the first branch only <an> is relevant if <al>.

```

7150   if dir == 'en' or dir == 'an' or dir == 'et' then
7151     if dir ~= 'et' then
7152       type_n = dir
7153     end
7154     first_n = first_n or item
7155     last_n = last_es or item
7156     last_es = nil
7157   elseif dir == 'es' and last_n then -- W3+W6
7158     last_es = item
7159   elseif dir == 'cs' then          -- it's right - do nothing
7160   elseif first_n then -- & if dir = any but en, et, an, es, cs, inc nil
7161     if strong_lr == 'r' and type_n ~= '' then
7162       dir_mark(head, first_n, last_n, 'r')
7163     elseif strong_lr == 'l' and first_d and type_n == 'an' then
7164       dir_mark(head, first_n, last_n, 'r')
7165       dir_mark(head, first_d, last_d, outer)
7166       first_d, last_d = nil, nil
7167     elseif strong_lr == 'l' and type_n ~= '' then
7168       last_d = last_n
7169     end
7170     type_n = ''
7171     first_n, last_n = nil, nil
7172   end

```

R text in L, or L text in R. Order of dir_ mark's are relevant: d goes outside n, and therefore it's emitted after. See dir_mark to understand why (but is the nesting actually necessary or is a flat dir structure enough?). Only L, R (and AL) chars are taken into account – everything else, including spaces, whatsits, etc., are ignored:

```

7173   if dir == 'l' or dir == 'r' then
7174     if dir ~= outer then
7175       first_d = first_d or item
7176       last_d = item
7177     elseif first_d and dir ~= strong_lr then
7178       dir_mark(head, first_d, last_d, outer)
7179       first_d, last_d = nil, nil
7180     end
7181   end

```

Mirroring. Each chunk of text in a certain language is considered a “closed” sequence. If <r on r> and <l on l>, it's clearly <r> and <l>, resp'tly, but with other combinations depends on outer. From all these, we select only those resolving <on> → <r>. At the beginning (when last_lr is nil) of an R text, they are mirrored directly.

TODO - numbers in R mode are processed. It doesn't hurt, but should not be done.

```

7182   if dir and not last_lr and dir ~= 'l' and outer == 'r' then
7183     item.char = characters[item.char] and
7184       characters[item.char].m or item.char
7185   elseif (dir or new_dir) and last_lr ~= item then
7186     local mir = outer .. strong_lr .. (dir or outer)
7187     if mir == 'rrr' or mir == 'lrr' or mir == 'rrl' or mir == 'rlr' then
7188       for ch in node.traverse(node.next(last_lr)) do
7189         if ch == item then break end
7190         if ch.id == node.id'glyph' and characters[ch.char] then

```

```

7191         ch.char = characters[ch.char].m or ch.char
7192     end
7193 end
7194 end
7195 end

```

Save some values for the next iteration. If the current node is 'dir', open a new sequence. Since dir could be changed, strong is set with its real value (dir_real).

```

7196     if dir == 'l' or dir == 'r' then
7197         last_lr = item
7198         strong = dir_real          -- Don't search back - best save now
7199         strong_lr = (strong == 'l') and 'l' or 'r'
7200     elseif new_dir then
7201         last_lr = nil
7202     end
7203 end

```

Mirror the last chars if they are no directed. And make sure any open block is closed, too.

```

7204     if last_lr and outer == 'r' then
7205         for ch in node.traverse_id(node.id'glyph', node.next(last_lr)) do
7206             if characters[ch.char] then
7207                 ch.char = characters[ch.char].m or ch.char
7208             end
7209         end
7210     end
7211     if first_n then
7212         dir_mark(head, first_n, last_n, outer)
7213     end
7214     if first_d then
7215         dir_mark(head, first_d, last_d, outer)
7216     end

```

In boxes, the dir node could be added before the original head, so the actual head is the previous node.

```

7217     return node.prev(head) or head
7218 end
7219 </basic-r>

```

And here the Lua code for bidi=basic:

```

7220 <*basic>
7221 Babel = Babel or {}
7222
7223 -- eg, Babel.fontmap[1][<prefontid>]=<dirfontid>
7224
7225 Babel.fontmap = Babel.fontmap or {}
7226 Babel.fontmap[0] = {}          -- l
7227 Babel.fontmap[1] = {}          -- r
7228 Babel.fontmap[2] = {}          -- al/an
7229
7230 Babel.bidi_enabled = true
7231 Babel.mirroring_enabled = true
7232
7233 require('babel-data-bidi.lua')
7234
7235 local characters = Babel.characters
7236 local ranges = Babel.ranges
7237
7238 local DIR = node.id('dir')
7239 local GLYPH = node.id('glyph')
7240
7241 local function insert_implicit(head, state, outer)
7242     local new_state = state
7243     if state.sim and state.eim and state.sim ~= state.eim then
7244         dir = ((outer == 'r') and 'TLT' or 'TRT') -- ie, reverse

```

```

7245     local d = node.new(DIR)
7246     d.dir = '+' .. dir
7247     node.insert_before(head, state.sim, d)
7248     local d = node.new(DIR)
7249     d.dir = '-' .. dir
7250     node.insert_after(head, state.eim, d)
7251 end
7252 new_state.sim, new_state.eim = nil, nil
7253 return head, new_state
7254 end
7255
7256 local function insert_numeric(head, state)
7257     local new
7258     local new_state = state
7259     if state.san and state.ean and state.san ~= state.ean then
7260         local d = node.new(DIR)
7261         d.dir = '+TLT'
7262         _, new = node.insert_before(head, state.san, d)
7263         if state.san == state.sim then state.sim = new end
7264         local d = node.new(DIR)
7265         d.dir = '-TLT'
7266         _, new = node.insert_after(head, state.ean, d)
7267         if state.ean == state.eim then state.eim = new end
7268     end
7269     new_state.san, new_state.ean = nil, nil
7270     return head, new_state
7271 end
7272
7273 -- TODO - \hbox with an explicit dir can lead to wrong results
7274 -- <R \hbox dir TLT{<R>}> and <L \hbox dir TRT{<L>}>. A small attempt
7275 -- was s made to improve the situation, but the problem is the 3-dir
7276 -- model in babel/Unicode and the 2-dir model in LuaTeX don't fit
7277 -- well.
7278
7279 function Babel.bidi(head, ispar, hdir)
7280     local d -- d is used mainly for computations in a loop
7281     local prev_d = ''
7282     local new_d = false
7283
7284     local nodes = {}
7285     local outer_first = nil
7286     local inmath = false
7287
7288     local glue_d = nil
7289     local glue_i = nil
7290
7291     local has_en = false
7292     local first_et = nil
7293
7294     local has_hyperlink = false
7295
7296     local ATDIR = Babel.attr_dir
7297
7298     local save_outer
7299     local temp = node.get_attribute(head, ATDIR)
7300     if temp then
7301         temp = temp & 0x3
7302         save_outer = (temp == 0 and 'l') or
7303                     (temp == 1 and 'r') or
7304                     (temp == 2 and 'al')
7305     elseif ispar then -- Or error? Shouldn't happen
7306         save_outer = ('TRT' == tex.pardir) and 'r' or 'l'
7307     else -- Or error? Shouldn't happen

```

```

7308     save_outer = ('TRT' == hdir) and 'r' or 'l'
7309 end
7310 -- when the callback is called, we are just _after_ the box,
7311 -- and the textdir is that of the surrounding text
7312 -- if not ispar and hdir ~= tex.textdir then
7313 --     save_outer = ('TRT' == hdir) and 'r' or 'l'
7314 -- end
7315 local outer = save_outer
7316 local last = outer
7317 -- 'al' is only taken into account in the first, current loop
7318 if save_outer == 'al' then save_outer = 'r' end
7319
7320 local fontmap = Babel.fontmap
7321
7322 for item in node.traverse(head) do
7323
7324     -- In what follows, #node is the last (previous) node, because the
7325     -- current one is not added until we start processing the neutrals.
7326
7327     -- three cases: glyph, dir, otherwise
7328     if item.id == GLYPH
7329         or (item.id == 7 and item.subtype == 2) then
7330
7331         local d_font = nil
7332         local item_r
7333         if item.id == 7 and item.subtype == 2 then
7334             item_r = item.replace -- automatic discs have just 1 glyph
7335         else
7336             item_r = item
7337         end
7338         local chardata = characters[item_r.char]
7339         d = chardata and chardata.d or nil
7340         if not d or d == 'nsm' then
7341             for nn, et in ipairs(ranges) do
7342                 if item_r.char < et[1] then
7343                     break
7344                 elseif item_r.char <= et[2] then
7345                     if not d then d = et[3]
7346                     elseif d == 'nsm' then d_font = et[3]
7347                     end
7348                     break
7349                 end
7350             end
7351         end
7352         d = d or 'l'
7353
7354         -- A short 'pause' in bidi for mapfont
7355         d_font = d_font or d
7356         d_font = (d_font == 'l' and 0) or
7357             (d_font == 'nsm' and 0) or
7358             (d_font == 'r' and 1) or
7359             (d_font == 'al' and 2) or
7360             (d_font == 'an' and 2) or nil
7361         if d_font and fontmap and fontmap[d_font][item_r.font] then
7362             item_r.font = fontmap[d_font][item_r.font]
7363         end
7364
7365         if new_d then
7366             table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})
7367             if inmath then
7368                 attr_d = 0
7369             else
7370                 attr_d = node.get_attribute(item, ATDIR)

```

```

7371         attr_d = attr_d & 0x3
7372     end
7373     if attr_d == 1 then
7374         outer_first = 'r'
7375         last = 'r'
7376     elseif attr_d == 2 then
7377         outer_first = 'r'
7378         last = 'al'
7379     else
7380         outer_first = 'l'
7381         last = 'l'
7382     end
7383     outer = last
7384     has_en = false
7385     first_et = nil
7386     new_d = false
7387 end
7388
7389 if glue_d then
7390     if (d == 'l' and 'l' or 'r') ~= glue_d then
7391         table.insert(nodes, {glue_i, 'on', nil})
7392     end
7393     glue_d = nil
7394     glue_i = nil
7395 end
7396
7397 elseif item.id == DIR then
7398     d = nil
7399
7400     if head ~= item then new_d = true end
7401
7402 elseif item.id == node.id'glue' and item.subtype == 13 then
7403     glue_d = d
7404     glue_i = item
7405     d = nil
7406
7407 elseif item.id == node.id'math' then
7408     inmath = (item.subtype == 0)
7409
7410 elseif item.id == 8 and item.subtype == 19 then
7411     has_hyperlink = true
7412
7413 else
7414     d = nil
7415 end
7416
7417 -- AL <= EN/ET/ES      -- W2 + W3 + W6
7418 if last == 'al' and d == 'en' then
7419     d = 'an'          -- W3
7420 elseif last == 'al' and (d == 'et' or d == 'es') then
7421     d = 'on'          -- W6
7422 end
7423
7424 -- EN + CS/ES + EN      -- W4
7425 if d == 'en' and #nodes >= 2 then
7426     if (nodes[#nodes][2] == 'es' or nodes[#nodes][2] == 'cs')
7427         and nodes[#nodes-1][2] == 'en' then
7428         nodes[#nodes][2] = 'en'
7429     end
7430 end
7431
7432 -- AN + CS + AN          -- W4 too, because uax9 mixes both cases
7433 if d == 'an' and #nodes >= 2 then

```

```

7434     if (nodes[#nodes][2] == 'cs')
7435         and nodes[#nodes-1][2] == 'an' then
7436         nodes[#nodes][2] = 'an'
7437     end
7438 end
7439
7440 -- ET/EN          -- W5 + W7->l / W6->on
7441 if d == 'et' then
7442     first_et = first_et or (#nodes + 1)
7443 elseif d == 'en' then
7444     has_en = true
7445     first_et = first_et or (#nodes + 1)
7446 elseif first_et then      -- d may be nil here !
7447     if has_en then
7448         if last == 'l' then
7449             temp = 'l'      -- W7
7450         else
7451             temp = 'en'     -- W5
7452         end
7453     else
7454         temp = 'on'        -- W6
7455     end
7456     for e = first_et, #nodes do
7457         if nodes[e][1].id == GLYPH then nodes[e][2] = temp end
7458     end
7459     first_et = nil
7460     has_en = false
7461 end
7462
7463 -- Force mathdir in math if ON (currently works as expected only
7464 -- with 'l')
7465 if inmath and d == 'on' then
7466     d = ('TRT' == tex.mathdir) and 'r' or 'l'
7467 end
7468
7469 if d then
7470     if d == 'al' then
7471         d = 'r'
7472         last = 'al'
7473     elseif d == 'l' or d == 'r' then
7474         last = d
7475     end
7476     prev_d = d
7477     table.insert(nodes, {item, d, outer_first})
7478 end
7479
7480 outer_first = nil
7481
7482 end
7483
7484 -- TODO -- repeated here in case EN/ET is the last node. Find a
7485 -- better way of doing things:
7486 if first_et then      -- dir may be nil here !
7487     if has_en then
7488         if last == 'l' then
7489             temp = 'l'      -- W7
7490         else
7491             temp = 'en'     -- W5
7492         end
7493     else
7494         temp = 'on'        -- W6
7495     end
7496     for e = first_et, #nodes do

```



```

7497     if nodes[e][1].id == GLYPH then nodes[e][2] = temp end
7498     end
7499 end
7500
7501 -- dummy node, to close things
7502 table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})
7503
7504 ----- NEUTRAL -----
7505
7506 outer = save_outer
7507 last = outer
7508
7509 local first_on = nil
7510
7511 for q = 1, #nodes do
7512     local item
7513
7514     local outer_first = nodes[q][3]
7515     outer = outer_first or outer
7516     last = outer_first or last
7517
7518     local d = nodes[q][2]
7519     if d == 'an' or d == 'en' then d = 'r' end
7520     if d == 'cs' or d == 'et' or d == 'es' then d = 'on' end --- W6
7521
7522     if d == 'on' then
7523         first_on = first_on or q
7524     elseif first_on then
7525         if last == d then
7526             temp = d
7527         else
7528             temp = outer
7529         end
7530         for r = first_on, q - 1 do
7531             nodes[r][2] = temp
7532             item = nodes[r][1] -- MIRRORING
7533             if Babel.mirroring_enabled and item.id == GLYPH
7534                 and temp == 'r' and characters[item.char] then
7535                 local font_mode = ''
7536                 if item.font > 0 and font.fonts[item.font].properties then
7537                     font_mode = font.fonts[item.font].properties.mode
7538                 end
7539                 if font_mode ~= 'harf' and font_mode ~= 'plug' then
7540                     item.char = characters[item.char].m or item.char
7541                 end
7542             end
7543         end
7544         first_on = nil
7545     end
7546
7547     if d == 'r' or d == 'l' then last = d end
7548 end
7549
7550 ----- IMPLICIT, REORDER -----
7551
7552 outer = save_outer
7553 last = outer
7554
7555 local state = {}
7556 state.has_r = false
7557
7558 for q = 1, #nodes do
7559

```

```

7560     local item = nodes[q][1]
7561
7562     outer = nodes[q][3] or outer
7563
7564     local d = nodes[q][2]
7565
7566     if d == 'nsm' then d = last end          -- W1
7567     if d == 'en' then d = 'an' end
7568     local isdir = (d == 'r' or d == 'l')
7569
7570     if outer == 'l' and d == 'an' then
7571         state.san = state.san or item
7572         state.ean = item
7573     elseif state.san then
7574         head, state = insert_numeric(head, state)
7575     end
7576
7577     if outer == 'l' then
7578         if d == 'an' or d == 'r' then      -- im -> implicit
7579             if d == 'r' then state.has_r = true end
7580             state.sim = state.sim or item
7581             state.eim = item
7582         elseif d == 'l' and state.sim and state.has_r then
7583             head, state = insert_implicit(head, state, outer)
7584         elseif d == 'l' then
7585             state.sim, state.eim, state.has_r = nil, nil, false
7586         end
7587     else
7588         if d == 'an' or d == 'l' then
7589             if nodes[q][3] then -- nil except after an explicit dir
7590                 state.sim = item -- so we move sim 'inside' the group
7591             else
7592                 state.sim = state.sim or item
7593             end
7594             state.eim = item
7595         elseif d == 'r' and state.sim then
7596             head, state = insert_implicit(head, state, outer)
7597         elseif d == 'r' then
7598             state.sim, state.eim = nil, nil
7599         end
7600     end
7601
7602     if isdir then
7603         last = d          -- Don't search back - best save now
7604     elseif d == 'on' and state.san then
7605         state.san = state.san or item
7606         state.ean = item
7607     end
7608
7609 end
7610
7611 head = node.prev(head) or head
7612
7613 ----- FIX HYPERLINKS -----
7614
7615 if has_hyperlink then
7616     local flag, linking = 0, 0
7617     for item in node.traverse(head) do
7618         if item.id == DIR then
7619             if item.dir == '+TRT' or item.dir == '+TLT' then
7620                 flag = flag + 1
7621             elseif item.dir == '-TRT' or item.dir == '-TLT' then
7622                 flag = flag - 1

```

```

7623         end
7624     elseif item.id == 8 and item.subtype == 19 then
7625         linking = flag
7626     elseif item.id == 8 and item.subtype == 20 then
7627         if linking > 0 then
7628             if item.prev.id == DIR and
7629                 (item.prev.dir == '-TRT' or item.prev.dir == '-TLT') then
7630                 d = node.new(DIR)
7631                 d.dir = item.prev.dir
7632                 node.remove(head, item.prev)
7633                 node.insert_after(head, item, d)
7634             end
7635         end
7636         linking = 0
7637     end
7638 end
7639 end
7640
7641 return head
7642 end
7643 </basic>

```

13 Data for CJK

It is a boring file and it is not shown here (see the generated file), but here is a sample:

```

[0x0021]={c='ex'},
[0x0024]={c='pr'},
[0x0025]={c='po'},
[0x0028]={c='op'},
[0x0029]={c='cp'},
[0x002B]={c='pr'},

```

For the meaning of these codes, see the Unicode standard.

14 The ‘nil’ language

This ‘language’ does nothing, except setting the hyphenation patterns to nohyphenation.

For this language currently no special definitions are needed or available.

The macro `\LdfInit` takes care of preventing that this file is loaded more than once, checking the category code of the `@` sign, etc.

```

7644 <*nil>
7645 \ProvidesLanguage{nil}[<<date>>] <<version>> Nil language]
7646 \LdfInit{nil}{datenil}

```

When this file is read as an option, i.e. by the `\usepackage` command, nil could be an ‘unknown’ language in which case we have to make it known.

```

7647 \ifx\l@nil\undefined
7648   \newlanguage\l@nil
7649   \@namedef{bbl@hyphendata@the\l@nil}{}{}{}% Remove warning
7650   \let\bbl@elt\relax
7651   \edef\bbl@languages{% Add it to the list of languages
7652     \bbl@languages\bbl@elt{nil}{the\l@nil}{}{}
7653 \fi

```

This macro is used to store the values of the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`.

```

7654 \providehyphenmins{\CurrentOption}{\m@ne\m@ne}

```

The next step consists of defining commands to switch to (and from) the ‘nil’ language.

```

\captionnil
\datenil 7655 \let\captionnil\@empty
7656 \let\datenil\@empty

```

There is no locale file for this pseudo-language, so the corresponding fields are defined here.

```

7657 \def\bbl@inidata@nil{%
7658   \bbl@elt{identification}{tag.ini}{und}%
7659   \bbl@elt{identification}{load.level}{0}%
7660   \bbl@elt{identification}{charset}{utf8}%
7661   \bbl@elt{identification}{version}{1.0}%
7662   \bbl@elt{identification}{date}{2022-05-16}%
7663   \bbl@elt{identification}{name.local}{nil}%
7664   \bbl@elt{identification}{name.english}{nil}%
7665   \bbl@elt{identification}{name.babel}{nil}%
7666   \bbl@elt{identification}{tag.bcp47}{und}%
7667   \bbl@elt{identification}{language.tag.bcp47}{und}%
7668   \bbl@elt{identification}{tag.opentype}{dflt}%
7669   \bbl@elt{identification}{script.name}{Latin}%
7670   \bbl@elt{identification}{script.tag.bcp47}{Latn}%
7671   \bbl@elt{identification}{script.tag.opentype}{DFLT}%
7672   \bbl@elt{identification}{level}{1}%
7673   \bbl@elt{identification}{encodings}{}%
7674   \bbl@elt{identification}{derivate}{no}}
7675 \@namedef{bbl@tbc@nil}{und}
7676 \@namedef{bbl@lbc@nil}{und}
7677 \@namedef{bbl@casing@nil}{und} % TODO
7678 \@namedef{bbl@lotf@nil}{dflt}
7679 \@namedef{bbl@elname@nil}{nil}
7680 \@namedef{bbl@lname@nil}{nil}
7681 \@namedef{bbl@esname@nil}{Latin}
7682 \@namedef{bbl@sname@nil}{Latin}
7683 \@namedef{bbl@sbc@nil}{Latn}
7684 \@namedef{bbl@sotf@nil}{Latn}

```

The macro `\ldf@finish` takes care of looking for a configuration file, setting the main language to be switched on at `\begin{document}` and resetting the category code of `@` to its original value.

```

7685 \ldf@finish{nil}
7686 \nil

```

15 Calendars

The code for specific calendars are placed in the specific files, loaded when requested by an ini file in the identification section with `require.calendars`.

Start with function to compute the Julian day. It's based on the little library `calendar.js`, by John Walker, in the public domain.

```

7687 <<Compute Julian day>> ≡
7688 \def\bbl@fpmo#1#2{(#1-#2*floo(#1/#2))}
7689 \def\bbl@cs@gregleap#1{%
7690   (\bbl@fpmo{#1}{4} == 0) &&
7691   (!((\bbl@fpmo{#1}{100} == 0) && (\bbl@fpmo{#1}{400} != 0)))}
7692 \def\bbl@cs@jd#1#2#3{% year, month, day
7693   \fp_eval:n{ 1721424.5 + (365 * (#1 - 1)) +
7694     floo((#1 - 1) / 4) + (-floo((#1 - 1) / 100)) +
7695     floo((#1 - 1) / 400) + floo((((367 * #2) - 362) / 12) +
7696     ((#2 <= 2) ? 0 : (\bbl@cs@gregleap{#1} ? -1 : -2)) + #3) }}
7697 <</Compute Julian day>>

```

15.1 Islamic

The code for the Civil calendar is based on it, too.

```

7698 <ca-islamic>

```

```

7699 \ExplSyntaxOn
7700 <<Compute Julian day>>
7701 % == islamic (default)
7702 % Not yet implemented
7703 \def\bbl@ca@islamic#1-#2-#3\@#4#5#6{
The Civil calendar.
7704 \def\bbl@cs@isltojd#1#2#3{ % year, month, day
7705   ((#3 + ceil(29.5 * (#2 - 1)) +
7706   (#1 - 1) * 354 + floor((3 + (11 * #1)) / 30) +
7707   1948439.5) - 1) }
7708 \@namedef{bbl@ca@islamic-civil++}{\bbl@ca@islamicv1x{+2}}
7709 \@namedef{bbl@ca@islamic-civil+}{\bbl@ca@islamicv1x{+1}}
7710 \@namedef{bbl@ca@islamic-civil}{\bbl@ca@islamicv1x{}}
7711 \@namedef{bbl@ca@islamic-civil-}{\bbl@ca@islamicv1x{-1}}
7712 \@namedef{bbl@ca@islamic-civil--}{\bbl@ca@islamicv1x{-2}}
7713 \def\bbl@ca@islamicv1x#1#2-#3-#4\@#5#6#7{%
7714   \edef\bbl@tempa{%
7715     \fp_eval:n{ floor(\bbl@cs@jd{#2}{#3}{#4})+0.5 #1}}%
7716   \edef#5{%
7717     \fp_eval:n{ floor(((30*(\bbl@tempa-1948439.5)) + 10646)/10631) }}%
7718   \edef#6{\fp_eval:n{
7719     min(12,ceil((\bbl@tempa-(29+\bbl@cs@isltojd{#5}{1}{1}))/29.5)+1) }}%
7720   \edef#7{\fp_eval:n{ \bbl@tempa - \bbl@cs@isltojd{#5}{#6}{1} + 1} }}
The Umm al-Qura calendar, used mainly in Saudi Arabia, is based on moment-hijri, by Abdullah
Alsigar (license MIT).
Since the main aim is to provide a suitable \today, and maybe some close dates, data just covers
Hijri ~1435/~1460 (Gregorian ~2014/~2038).
7721 \def\bbl@cs@umalqura@data{56660, 56690,56719,56749,56778,56808,%
7722 56837,56867,56897,56926,56956,56985,57015,57044,57074,57103,%
7723 57133,57162,57192,57221,57251,57280,57310,57340,57369,57399,%
7724 57429,57458,57487,57517,57546,57576,57605,57634,57664,57694,%
7725 57723,57753,57783,57813,57842,57871,57901,57930,57959,57989,%
7726 58018,58048,58077,58107,58137,58167,58196,58226,58255,58285,%
7727 58314,58343,58373,58402,58432,58461,58491,58521,58551,58580,%
7728 58610,58639,58669,58698,58727,58757,58786,58816,58845,58875,%
7729 58905,58934,58964,58994,59023,59053,59082,59111,59141,59170,%
7730 59200,59229,59259,59288,59318,59348,59377,59407,59436,59466,%
7731 59495,59525,59554,59584,59613,59643,59672,59702,59731,59761,%
7732 59791,59820,59850,59879,59909,59939,59968,59997,60027,60056,%
7733 60086,60115,60145,60174,60204,60234,60264,60293,60323,60352,%
7734 60381,60411,60440,60469,60499,60528,60558,60588,60618,60648,%
7735 60677,60707,60736,60765,60795,60824,60853,60883,60912,60942,%
7736 60972,61002,61031,61061,61090,61120,61149,61179,61208,61237,%
7737 61267,61296,61326,61356,61385,61415,61445,61474,61504,61533,%
7738 61563,61592,61621,61651,61680,61710,61739,61769,61799,61828,%
7739 61858,61888,61917,61947,61976,62006,62035,62064,62094,62123,%
7740 62153,62182,62212,62242,62271,62301,62331,62360,62390,62419,%
7741 62448,62478,62507,62537,62566,62596,62625,62655,62685,62715,%
7742 62744,62774,62803,62832,62862,62891,62921,62950,62980,63009,%
7743 63039,63069,63099,63128,63157,63187,63216,63246,63275,63305,%
7744 63334,63363,63393,63423,63453,63482,63512,63541,63571,63600,%
7745 63630,63659,63689,63718,63747,63777,63807,63836,63866,63895,%
7746 63925,63955,63984,64014,64043,64073,64102,64131,64161,64190,%
7747 64220,64249,64279,64309,64339,64368,64398,64427,64457,64486,%
7748 64515,64545,64574,64603,64633,64663,64692,64722,64752,64782,%
7749 64811,64841,64870,64899,64929,64958,64987,65017,65047,65076,%
7750 65106,65136,65166,65195,65225,65254,65283,65313,65342,65371,%
7751 65401,65431,65460,65490,65520}
7752 \@namedef{bbl@ca@islamic-umalqura+}{\bbl@ca@islamcuqr{x{+1}}}
7753 \@namedef{bbl@ca@islamic-umalqura}{\bbl@ca@islamcuqr{x{}}}
7754 \@namedef{bbl@ca@islamic-umalqura-}{\bbl@ca@islamcuqr{x{-1}}}
7755 \def\bbl@ca@islamcuqr{x#1#2-#3-#4\@#5#6#7{%

```

```

7756 \ifnum#2>2014 \ifnum#2<2038
7757 \bbl@afterfi\expandafter\@gobble
7758 \fi\fi
7759 {\bbl@error{Year~out~of~range}{The~allowed~range~is~2014-2038}}%
7760 \edef\bbl@tempd{\fp_eval:n{ % (Julian) day
7761 \bbl@cs@jd{#2}{#3}{#4} + 0.5 - 2400000 #1}}%
7762 \count@\@ne
7763 \bbl@foreach\bbl@cs@umalqura@data{%
7764 \advance\count@\@ne
7765 \ifnum##1>\bbl@tempd\else
7766 \edef\bbl@tempe{\the\count@}%
7767 \edef\bbl@tempb{##1}%
7768 \fi}%
7769 \edef\bbl@templ{\fp_eval:n{ \bbl@tempe + 16260 + 949 }}% month~lunar
7770 \edef\bbl@tempa{\fp_eval:n{ floor((\bbl@templ - 1 ) / 12) }}% annus
7771 \edef#5{\fp_eval:n{ \bbl@tempa + 1 }}%
7772 \edef#6{\fp_eval:n{ \bbl@templ - (12 * \bbl@tempa) }}%
7773 \edef#7{\fp_eval:n{ \bbl@tempd - \bbl@tempb + 1 }}%
7774 \ExplSyntaxOff
7775 \bbl@add\bbl@precalendar{%
7776 \bbl@replace\bbl@ld@calendar{-civil}{}}%
7777 \bbl@replace\bbl@ld@calendar{-umalqura}{}}%
7778 \bbl@replace\bbl@ld@calendar{+}{}}%
7779 \bbl@replace\bbl@ld@calendar{-}{}}
7780 </ca-islamic>

```

16 Hebrew

This is basically the set of macros written by Michail Rozman in 1991, with corrections and adaptations by Rama Porrat, Misha, Dan Haran and Boris Lavva. This must be eventually replaced by computations with l3fp. An explanation of what's going on can be found in hebcal.sty

```

7781 <*ca-hebrew>
7782 \newcount\bbl@cntcommon
7783 \def\bbl@remainder#1#2#3{%
7784 #3=#1\relax
7785 \divide #3 by #2\relax
7786 \multiply #3 by -#2\relax
7787 \advance #3 by #1\relax}%
7788 \newif\ifbbl@divisible
7789 \def\bbl@checkifdivisible#1#2{%
7790 {\countdef\tmp=0
7791 \bbl@remainder{#1}{#2}{\tmp}%
7792 \ifnum \tmp=0
7793 \global\bbl@divisibletrue
7794 \else
7795 \global\bbl@divisiblefalse
7796 \fi}}
7797 \newif\ifbbl@gregleap
7798 \def\bbl@ifgregleap#1{%
7799 \bbl@checkifdivisible{#1}{4}%
7800 \ifbbl@divisible
7801 \bbl@checkifdivisible{#1}{100}%
7802 \ifbbl@divisible
7803 \bbl@checkifdivisible{#1}{400}%
7804 \ifbbl@divisible
7805 \bbl@gregleaptrue
7806 \else
7807 \bbl@gregleapfalse
7808 \fi
7809 \else
7810 \bbl@gregleaptrue
7811 \fi

```

```

7812 \else
7813     \bbl@gregleapfalse
7814 \fi
7815 \ifbbl@gregleap}
7816 \def\bbl@gregdayspriormonths#1#2#3{%
7817     {#3=\ifcase #1 0 \or 0 \or 31 \or 59 \or 90 \or 120 \or 151 \or
7818         181 \or 212 \or 243 \or 273 \or 304 \or 334 \fi
7819     \bbl@ifgregleap{#2}%
7820     \ifnum #1 > 2
7821         \advance #3 by 1
7822     \fi
7823 \fi
7824 \global\bbl@cntcommon=#3}%
7825 #3=\bbl@cntcommon}
7826 \def\bbl@gregdaysprioryears#1#2{%
7827     {\countdef\tmpc=4
7828     \countdef\tmpb=2
7829     \tmpb=#1\relax
7830     \advance \tmpb by -1
7831     \tmpc=\tmpb
7832     \multiply \tmpc by 365
7833     #2=\tmpc
7834     \tmpc=\tmpb
7835     \divide \tmpc by 4
7836     \advance #2 by \tmpc
7837     \tmpc=\tmpb
7838     \divide \tmpc by 100
7839     \advance #2 by -\tmpc
7840     \tmpc=\tmpb
7841     \divide \tmpc by 400
7842     \advance #2 by \tmpc
7843     \global\bbl@cntcommon=#2\relax}%
7844     #2=\bbl@cntcommon}
7845 \def\bbl@absfromgreg#1#2#3#4{%
7846     {\countdef\tmpd=0
7847     #4=#1\relax
7848     \bbl@gregdayspriormonths{#2}{#3}{\tmpd}%
7849     \advance #4 by \tmpd
7850     \bbl@gregdaysprioryears{#3}{\tmpd}%
7851     \advance #4 by \tmpd
7852     \global\bbl@cntcommon=#4\relax}%
7853     #4=\bbl@cntcommon}
7854 \newif\ifbbl@hebrleap
7855 \def\bbl@checkleaphebrewyear#1{%
7856     {\countdef\tmpa=0
7857     \countdef\tmpb=1
7858     \tmpa=#1\relax
7859     \multiply \tmpa by 7
7860     \advance \tmpa by 1
7861     \bbl@remainder{\tmpa}{19}{\tmpb}%
7862     \ifnum \tmpb < 7
7863         \global\bbl@hebrleaptrue
7864     \else
7865         \global\bbl@hebrleapfalse
7866     \fi}}
7867 \def\bbl@hebreleapsedmonths#1#2{%
7868     {\countdef\tmpa=0
7869     \countdef\tmpb=1
7870     \countdef\tmpc=2
7871     \tmpa=#1\relax
7872     \advance \tmpa by -1
7873     #2=\tmpa
7874     \divide #2 by 19

```

```

7875 \multiply #2 by 235
7876 \bbl@remainder{\tmpa}{19}{\tmpb}% \tmpa=years%19-years this cycle
7877 \tmpc=\tmpb
7878 \multiply \tmpb by 12
7879 \advance #2 by \tmpb
7880 \multiply \tmpc by 7
7881 \advance \tmpc by 1
7882 \divide \tmpc by 19
7883 \advance #2 by \tmpc
7884 \global\bbl@cntcommon=#2}%
7885 #2=\bbl@cntcommon}
7886 \def\bbl@hebrelapseddays#1#2{%
7887 {\countdef\tmpa=0
7888 \countdef\tmpb=1
7889 \countdef\tmpc=2
7890 \bbl@hebrelapseddmonths{#1}{#2}%
7891 \tmpa=#2\relax
7892 \multiply \tmpa by 13753
7893 \advance \tmpa by 5604
7894 \bbl@remainder{\tmpa}{25920}{\tmpc}% \tmpc == ConjunctionParts
7895 \divide \tmpa by 25920
7896 \multiply #2 by 29
7897 \advance #2 by 1
7898 \advance #2 by \tmpa
7899 \bbl@remainder{#2}{7}{\tmpa}%
7900 \ifnum \tmpc < 19440
7901 \ifnum \tmpc < 9924
7902 \else
7903 \ifnum \tmpa=2
7904 \bbl@checkleaphebrewyear{#1}% of a common year
7905 \ifbbl@hebrleap
7906 \else
7907 \advance #2 by 1
7908 \fi
7909 \fi
7910 \fi
7911 \ifnum \tmpc < 16789
7912 \else
7913 \ifnum \tmpa=1
7914 \advance #1 by -1
7915 \bbl@checkleaphebrewyear{#1}% at the end of leap year
7916 \ifbbl@hebrleap
7917 \advance #2 by 1
7918 \fi
7919 \fi
7920 \fi
7921 \else
7922 \advance #2 by 1
7923 \fi
7924 \bbl@remainder{#2}{7}{\tmpa}%
7925 \ifnum \tmpa=0
7926 \advance #2 by 1
7927 \else
7928 \ifnum \tmpa=3
7929 \advance #2 by 1
7930 \else
7931 \ifnum \tmpa=5
7932 \advance #2 by 1
7933 \fi
7934 \fi
7935 \fi
7936 \global\bbl@cntcommon=#2\relax}%
7937 #2=\bbl@cntcommon}

```



```

7938 \def\bbl@daysinhebrewyear#1#2{%
7939   {\countdef\tmpe=12
7940    \bbl@hebreleapseddays{#1}{\tmpe}%
7941    \advance #1 by 1
7942    \bbl@hebreleapseddays{#1}{#2}%
7943    \advance #2 by -\tmpe
7944    \global\bbl@cntcommon=#2}%
7945   #2=\bbl@cntcommon}
7946 \def\bbl@hebrdayspriormonths#1#2#3{%
7947   {\countdef\tmpf= 14
7948    #3=\ifcase #1\relax
7949      0 \or
7950      0 \or
7951      30 \or
7952      59 \or
7953      89 \or
7954      118 \or
7955      148 \or
7956      148 \or
7957      177 \or
7958      207 \or
7959      236 \or
7960      266 \or
7961      295 \or
7962      325 \or
7963      400
7964    \fi
7965    \bbl@checkleaphebrewyear{#2}%
7966    \ifbbl@hebrleap
7967      \ifnum #1 > 6
7968        \advance #3 by 30
7969      \fi
7970    \fi
7971    \bbl@daysinhebrewyear{#2}{\tmpf}%
7972    \ifnum #1 > 3
7973      \ifnum \tmpf=353
7974        \advance #3 by -1
7975      \fi
7976      \ifnum \tmpf=383
7977        \advance #3 by -1
7978      \fi
7979    \fi
7980    \ifnum #1 > 2
7981      \ifnum \tmpf=355
7982        \advance #3 by 1
7983      \fi
7984      \ifnum \tmpf=385
7985        \advance #3 by 1
7986      \fi
7987    \fi
7988    \global\bbl@cntcommon=#3\relax}%
7989   #3=\bbl@cntcommon}
7990 \def\bbl@absfromhebr#1#2#3#4{%
7991   {#4=#1\relax
7992    \bbl@hebrdayspriormonths{#2}{#3}{#1}%
7993    \advance #4 by #1\relax
7994    \bbl@hebreleapseddays{#3}{#1}%
7995    \advance #4 by #1\relax
7996    \advance #4 by -1373429
7997    \global\bbl@cntcommon=#4\relax}%
7998   #4=\bbl@cntcommon}
7999 \def\bbl@hebrfromgreg#1#2#3#4#5#6{%
8000   {\countdef\tmpx= 17

```

```

8001 \countdef\tmpy= 18
8002 \countdef\tmpz= 19
8003 #6=#3\relax
8004 \global\advance #6 by 3761
8005 \bbl@absfromgreg{#1}{#2}{#3}{#4}%
8006 \tmpz=1 \tmpy=1
8007 \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
8008 \ifnum \tmpx > #4\relax
8009     \global\advance #6 by -1
8010     \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
8011 \fi
8012 \advance #4 by -\tmpx
8013 \advance #4 by 1
8014 #5=#4\relax
8015 \divide #5 by 30
8016 \loop
8017     \bbl@hebrdayspriormonths{#5}{#6}{\tmpx}%
8018     \ifnum \tmpx < #4\relax
8019         \advance #5 by 1
8020         \tmpy=\tmpx
8021 \repeat
8022 \global\advance #5 by -1
8023 \global\advance #4 by -\tmpy}}
8024 \newcount\bbl@hebrday \newcount\bbl@hebrmonth \newcount\bbl@hebryear
8025 \newcount\bbl@gregday \newcount\bbl@gregmonth \newcount\bbl@gregyear
8026 \def\bbl@ca@hebrew#1-#2-#3\@@#4#5#6{%
8027     \bbl@gregday=#3\relax \bbl@gregmonth=#2\relax \bbl@gregyear=#1\relax
8028     \bbl@hebrfromgreg
8029     {\bbl@gregday}{\bbl@gregmonth}{\bbl@gregyear}%
8030     {\bbl@hebrday}{\bbl@hebrmonth}{\bbl@hebryear}%
8031     \edef#4{\the\bbl@hebryear}%
8032     \edef#5{\the\bbl@hebrmonth}%
8033     \edef#6{\the\bbl@hebrday}}
8034 \</ca-hebrew>

```

17 Persian

There is an algorithm written in TeX by Jabri, Abolhassani, Pournader and Esfahbod, created for the first versions of the FarsiTeX system (no longer available), but the original license is GPL, so its use with LPPL is problematic. The code here follows loosely that by John Walker, which is free and accurate, but sadly very complex, so the relevant data for the years 2013-2050 have been pre-calculated and stored. Actually, all we need is the first day (either March 20 or March 21).

```

8035 \<ca-persian>
8036 \ExplSyntaxOn
8037 \<Compute Julian day>
8038 \def\bbl@cs@firstjal@xx{2012,2016,2020,2024,2028,2029,% March 20
8039     2032,2033,2036,2037,2040,2041,2044,2045,2048,2049}
8040 \def\bbl@ca@persian#1-#2-#3\@@#4#5#6{%
8041     \edef\bbl@tempa{#1}% 20XX-03-\bbl@tempe = 1 farvardin:
8042     \ifnum\bbl@tempa>2012 \ifnum\bbl@tempa<2051
8043         \bbl@afterfi\expandafter\gobble
8044     \fi\fi
8045     {\bbl@error{Year-out-of-range}{The~allowed~range-is~2013-2050}}}%
8046 \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%
8047 \ifin@def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
8048 \edef\bbl@tempc{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{#2}{#3}+.5}}% current
8049 \edef\bbl@tempb{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{03}{\bbl@tempe}+.5}}% begin
8050 \ifnum\bbl@tempc<\bbl@tempb
8051     \edef\bbl@tempa{\fp_eval:n{\bbl@tempa-1}}% go back 1 year and redo
8052     \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%
8053     \ifin@def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
8054     \edef\bbl@tempb{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{03}{\bbl@tempe}+.5}}%

```

```

8055 \fi
8056 \edef#4{\fp_eval:n{\bbl@tempa-621}}% set Jalali year
8057 \edef#6{\fp_eval:n{\bbl@tempc-\bbl@tempb+1}}% days from 1 farvardin
8058 \edef#5{\fp_eval:n{% set Jalali month
8059   (#6 <= 186) ? ceil(#6 / 31) : ceil((#6 - 6) / 30)}}
8060 \edef#6{\fp_eval:n{% set Jalali day
8061   (#6 - ((#5 <= 7) ? ((#5 - 1) * 31) : (((#5 - 1) * 30) + 6)))}}
8062 \ExplSyntaxOff
8063 </ca-persian>

```

18 Coptic and Ethiopic

Adapted from `jquery.calendars.package-1.1.4`, written by Keith Wood, 2010. Dual license: GPL and MIT. The only difference is the epoch.

```

8064 <*ca-coptic>
8065 \ExplSyntaxOn
8066 <<Compute Julian day>>
8067 \def\bbl@ca@coptic#1-#2-#3\@#4#5#6{%
8068   \edef\bbl@tempd{\fp_eval:n{floor(\bbl@cs@jd{#1}{#2}{#3}) + 0.5}}%
8069   \edef\bbl@tempc{\fp_eval:n{\bbl@tempd - 1825029.5}}%
8070   \edef#4{\fp_eval:n{%
8071     floor((\bbl@tempc - floor((\bbl@tempc+366) / 1461)) / 365) + 1}}%
8072   \edef\bbl@tempc{\fp_eval:n{%
8073     \bbl@tempd - (#4-1) * 365 - floor(#4/4) - 1825029.5}}%
8074   \edef#5{\fp_eval:n{floor(\bbl@tempc / 30) + 1}}%
8075   \edef#6{\fp_eval:n{\bbl@tempc - (#5 - 1) * 30 + 1}}
8076 \ExplSyntaxOff
8077 </ca-coptic>
8078 <*ca-ethiopic>
8079 \ExplSyntaxOn
8080 <<Compute Julian day>>
8081 \def\bbl@ca@ethiopic#1-#2-#3\@#4#5#6{%
8082   \edef\bbl@tempd{\fp_eval:n{floor(\bbl@cs@jd{#1}{#2}{#3}) + 0.5}}%
8083   \edef\bbl@tempc{\fp_eval:n{\bbl@tempd - 1724220.5}}%
8084   \edef#4{\fp_eval:n{%
8085     floor((\bbl@tempc - floor((\bbl@tempc+366) / 1461)) / 365) + 1}}%
8086   \edef\bbl@tempc{\fp_eval:n{%
8087     \bbl@tempd - (#4-1) * 365 - floor(#4/4) - 1724220.5}}%
8088   \edef#5{\fp_eval:n{floor(\bbl@tempc / 30) + 1}}%
8089   \edef#6{\fp_eval:n{\bbl@tempc - (#5 - 1) * 30 + 1}}
8090 \ExplSyntaxOff
8091 </ca-ethiopic>

```

19 Buddhist

That's very simple.

```

8092 <*ca-buddhist>
8093 \def\bbl@ca@buddhist#1-#2-#3\@#4#5#6{%
8094   \edef#4{\number\numexpr#1+543\relax}%
8095   \edef#5{#2}%
8096   \edef#6{#3}}
8097 </ca-buddhist>

```

20 Support for Plain T_EX (plain.def)

20.1 Not renaming hyphen.tex

As Don Knuth has declared that the filename `hyphen.tex` may only be used to designate *his* version of the american English hyphenation patterns, a new solution has to be found in order to be able to


```

8124 \closein0
8125 {\immediate\write16{*****}%
8126 \immediate\write16{* Local config file #1.cfg used}%
8127 \immediate\write16{*}%
8128 }
8129 \input #1.cfg\relax
8130 \fi
8131 \@endofldf}

```

20.3 General tools

A number of \LaTeX macro's that are needed later on.

```

8132 \long\def\@firstofone#1{#1}
8133 \long\def\@firstoftwo#1#2{#1}
8134 \long\def\@secondoftwo#1#2{#2}
8135 \def\@nnil{\nil}
8136 \def\@gobbletwo#1#2{}
8137 \def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}
8138 \def\@star@or@long#1{%
8139 \ifstar
8140 {\let\l@ngrel@x\relax#1}%
8141 {\let\l@ngrel@x\long#1}}
8142 \let\l@ngrel@x\relax
8143 \def\@car#1#2\@nil{#1}
8144 \def\@cdr#1#2\@nil{#2}
8145 \let\@typeset@protect\relax
8146 \let\protected@edef\edef
8147 \long\def\@gobble#1{}
8148 \edef\@backslashchar{\expandafter\@gobble\string\}
8149 \def\strip@prefix#1>{}
8150 \def\g@addto@macro#1#2{{%
8151 \toks@\expandafter{#1#2}%
8152 \xdef#1{\the\toks@}}
8153 \def\@namedef#1{\expandafter\def\csname #1\endcsname}
8154 \def\@nameuse#1{\csname #1\endcsname}
8155 \def\@ifundefined#1{%
8156 \expandafter\ifx\csname#1\endcsname\relax
8157 \expandafter\@firstoftwo
8158 \else
8159 \expandafter\@secondoftwo
8160 \fi}
8161 \def\@expandtwoargs#1#2#3{%
8162 \edef\reserved@a{\noexpand#1{#2}{#3}}\reserved@a}
8163 \def\zap@space#1 #2{%
8164 #1%
8165 \ifx#2\@empty\else\expandafter\zap@space\fi
8166 #2}
8167 \let\bbl@trace\@gobble
8168 \def\bbl@error#1#2{%
8169 \begingroup
8170 \newlinechar=`^^J
8171 \def\{^^J(babel) }%
8172 \errhelp{#2}\errmessage{\#1}%
8173 \endgroup}
8174 \def\bbl@warning#1{%
8175 \begingroup
8176 \newlinechar=`^^J
8177 \def\{^^J(babel) }%
8178 \message{\#1}%
8179 \endgroup}
8180 \let\bbl@infowarn\bbl@warning
8181 \def\bbl@info#1{%
8182 \begingroup

```

```

8183 \newlinechar=`^^J
8184 \def\{^^J}%
8185 \wlog{#1}%
8186 \endgroup}

```

\TeX 2 ϵ has the command `\onlypreamble` which adds commands to a list of commands that are no longer needed after `\begin{document}`.

```

8187 \ifx\@preamblecmds\undefined
8188 \def\@preamblecmds{}
8189 \fi
8190 \def\onlypreamble#1{%
8191 \expandafter\gdef\expandafter\@preamblecmds\expandafter{%
8192 \@preamblecmds\do#1}}
8193 \@onlypreamble\onlypreamble

```

Mimick \TeX 's `\AtBeginDocument`; for this to work the user needs to add `\begindocument` to his file.

```

8194 \def\begindocument{%
8195 \begindocumenthook
8196 \global\let\@begindocumenthook\undefined
8197 \def\do##1{\global\let##1\undefined}%
8198 \@preamblecmds
8199 \global\let\do\noexpand}

8200 \ifx\@begindocumenthook\undefined
8201 \def\@begindocumenthook{}
8202 \fi
8203 \@onlypreamble\@begindocumenthook
8204 \def\AtBeginDocument{\g@addto@macro\@begindocumenthook}

```

We also have to mimick \TeX 's `\AtEndOfPackage`. Our replacement macro is much simpler; it stores its argument in `\@endofldf`.

```

8205 \def\AtEndOfPackage#1{\g@addto@macro\@endofldf{#1}}
8206 \@onlypreamble\AtEndOfPackage
8207 \def\@endofldf{}
8208 \@onlypreamble\@endofldf
8209 \let\bbl@afterlang\@empty
8210 \chardef\bbl@opt@hyphenmap\z@

```

\TeX needs to be able to switch off writing to its auxiliary files; plain doesn't have them by default. There is a trick to hide some conditional commands from the outer `\ifx`. The same trick is applied below.

```

8211 \catcode`\&=\z@
8212 \ifx&\if@files\@undefined
8213 \expandafter\let\csname if@files\expandafter\endcsname
8214 \csname iffalse\endcsname
8215 \fi
8216 \catcode`\&=4

```

Mimick \TeX 's commands to define control sequences.

```

8217 \def\newcommand{\@star@or@long\new@command}
8218 \def\new@command#1{%
8219 \@testopt{\@newcommand#1}0}
8220 \def\@newcommand#1[#2]{%
8221 \@ifnextchar [{\@xargdef#1[#2]}%
8222 {\@argdef#1[#2]}}
8223 \long\def\@argdef#1[#2]#3{%
8224 \@yargdef#1\@ne{#2}{#3}}
8225 \long\def\@xargdef#1[#2][#3]#4{%
8226 \expandafter\def\expandafter#1\expandafter{%
8227 \expandafter\@protected@testopt\expandafter #1%
8228 \csname\string#1\expandafter\endcsname{#3}}}%
8229 \expandafter\@yargdef \csname\string#1\endcsname
8230 \tw@{#2}{#4}}
8231 \long\def\@yargdef#1#2#3{%

```

```

8232 \@tempcnta#3\relax
8233 \advance \@tempcnta \@ne
8234 \let\@hash@\relax
8235 \edef\reserved@a{\ifx#2\tw@ [\@hash@1]\fi}%
8236 \@tempcntb #2%
8237 \@whilenum\@tempcntb <\@tempcnta
8238 \do{%
8239     \edef\reserved@a{\reserved@a\@hash@\the\@tempcntb}%
8240     \advance\@tempcntb \@ne}%
8241 \let\@hash@##%
8242 \l@ngrel@x\expandafter\def\expandafter#1\reserved@a{
8243 \def\providecommand{\@star@or@long\provide@command}
8244 \def\provide@command#1{%
8245     \begingroup
8246         \escapechar\m@ne\xdef\@gtempa{\string#1}%
8247     \endgroup
8248     \expandafter\@ifundefined\@gtempa
8249         {\def\reserved@a{\new@command#1}}%
8250         {\let\reserved@a\relax
8251          \def\reserved@a{\new@command\reserved@a}}%
8252     \reserved@a}%
8253 \def\DeclareRobustCommand{\@star@or@long\declare@robustcommand}
8254 \def\declare@robustcommand#1{%
8255     \edef\reserved@a{\string#1}%
8256     \def\reserved@b{#1}%
8257     \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
8258     \edef#1{%
8259         \ifx\reserved@a\reserved@b
8260             \noexpand\x@protect
8261             \noexpand#1%
8262         \fi
8263         \noexpand\protect
8264         \expandafter\noexpand\csname
8265             \expandafter\@gobble\string#1 \endcsname
8266     }%
8267     \expandafter\new@command\csname
8268         \expandafter\@gobble\string#1 \endcsname
8269 }
8270 \def\x@protect#1{%
8271     \ifx\protect\@typeset@protect\else
8272         \@x@protect#1%
8273     \fi
8274 }
8275 \catcode\&=\z@ % Trick to hide conditionals
8276 \def\@x@protect#1&fi#2#3{&fi\protect#1}

```

The following little macro `\in@` is taken from `latex.ltx`; it checks whether its first argument is part of its second argument. It uses the boolean `\in@`; allocating a new boolean inside conditionally executed code is not possible, hence the construct with the temporary definition of `\bbl@tempa`.

```

8277 \def\bbl@tempa{\csname newif\endcsname&ifin@}
8278 \catcode\&=4
8279 \ifx\in@\@undefined
8280     \def\in@#1#2{%
8281         \def\in@@##1##2##3\in@@{%
8282             \ifx\in@@##2\in@false\else\in@true\fi}%
8283         \in@@##1\in@\in@@}
8284 \else
8285     \let\bbl@tempa\@empty
8286 \fi
8287 \bbl@tempa

```

\TeX has a macro to check whether a certain package was loaded with specific options. The command has two extra arguments which are code to be executed in either the true or false case. This is used to detect whether the document needs one of the accents to be activated (activegrave and

activeacute). For plain \TeX we assume that the user wants them to be active by default. Therefore the only thing we do is execute the third argument (the code for the true case).

```
8288 \def\ifpackagewith#1#2#3#4{#3}
```

The \TeX macro `\ifl@aded` checks whether a file was loaded. This functionality is not needed for plain \TeX but we need the macro to be defined as a no-op.

```
8289 \def\ifl@aded#1#2#3#4{}
```

For the following code we need to make sure that the commands `\newcommand` and `\providecommand` exist with some sensible definition. They are not fully equivalent to their $\TeX 2_{\epsilon}$ versions; just enough to make things work in plain \TeX environments.

```
8290 \ifx\@tempcnta\@undefined
8291   \csname newcount\endcsname\@tempcnta\relax
8292 \fi
8293 \ifx\@tempcntb\@undefined
8294   \csname newcount\endcsname\@tempcntb\relax
8295 \fi
```

To prevent wasting two counters in \TeX (because counters with the same name are allocated later by it) we reset the counter that holds the next free counter (`\count10`).

```
8296 \ifx\bye\@undefined
8297   \advance\count10 by -2\relax
8298 \fi
8299 \ifx\@ifnextchar\@undefined
8300   \def\@ifnextchar#1#2#3{%
8301     \let\reserved@d=#1%
8302     \def\reserved@a{#2}\def\reserved@b{#3}%
8303     \futurelet\@let@token\@ifnch}
8304   \def\@ifnch{%
8305     \ifx\@let@token\@sptoken
8306       \let\reserved@c\@xifnch
8307     \else
8308       \ifx\@let@token\reserved@d
8309         \let\reserved@c\reserved@a
8310       \else
8311         \let\reserved@c\reserved@b
8312       \fi
8313     \fi
8314     \reserved@c}
8315   \def\:{\let\@sptoken= } \: % this makes \@sptoken a space token
8316   \def\:{\@xifnch} \expandafter\def\:{\futurelet\@let@token\@ifnch}
8317 \fi
8318 \def\@testopt#1#2{%
8319   \@ifnextchar[#{#1}{#1[#2]}}
8320 \def\@protected@testopt#1{%
8321   \ifx\protect\@typeset@protect
8322     \expandafter\@testopt
8323   \else
8324     \@x@protect#1%
8325   \fi}
8326 \long\def\@whilenum#1\do #2{\ifnum #1\relax #2\relax\@iwhilenum{#1\relax
8327   #2\relax}\fi}
8328 \long\def\@iwhilenum#1{\ifnum #1\expandafter\@iwhilenum
8329   \else\expandafter\@gobble\fi{#1}}
```

20.4 Encoding related macros

Code from `ltoutenc.dtx`, adapted for use in the plain \TeX environment.

```
8330 \def\DeclareTextCommand{%
8331   \@dec@text@cmd\providecommand
8332 }
8333 \def\ProvideTextCommand{%
8334   \@dec@text@cmd\providecommand
```



```

8335 }
8336 \def\DeclareTextSymbol#1#2#3{%
8337   \@dec@text@cmd\chardef#1{#2}#3\relax
8338 }
8339 \def\@dec@text@cmd#1#2#3{%
8340   \expandafter\def\expandafter#2%
8341     \expandafter{%
8342       \csname#3-cmd\expandafter\endcsname
8343       \expandafter#2%
8344       \csname#3\string#2\endcsname
8345     }%
8346 %   \let\@ifdefinable\@rc@ifdefinable
8347   \expandafter#1\csname#3\string#2\endcsname
8348 }
8349 \def\@current@cmd#1{%
8350   \ifx\protect\@typeset@protect\else
8351     \noexpand#1\expandafter\@gobble
8352   \fi
8353 }
8354 \def\@changed@cmd#1#2{%
8355   \ifx\protect\@typeset@protect
8356     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
8357       \expandafter\ifx\csname ?\string#1\endcsname\relax
8358         \expandafter\def\csname ?\string#1\endcsname{%
8359           \@changed@x@err{#1}%
8360         }%
8361       \fi
8362       \global\expandafter\let
8363         \csname\cf@encoding\string#1\expandafter\endcsname
8364         \csname ?\string#1\endcsname
8365       \fi
8366       \csname\cf@encoding\string#1%
8367         \expandafter\endcsname
8368     \else
8369       \noexpand#1%
8370     \fi
8371 }
8372 \def\@changed@x@err#1{%
8373   \errhelp{Your command will be ignored, type <return> to proceed}%
8374   \errmessage{Command \protect#1 undefined in encoding \cf@encoding}}
8375 \def\DeclareTextCommandDefault#1{%
8376   \DeclareTextCommand#1?%
8377 }
8378 \def\ProvideTextCommandDefault#1{%
8379   \ProvideTextCommand#1?%
8380 }
8381 \expandafter\let\csname OT1-cmd\endcsname\@current@cmd
8382 \expandafter\let\csname?-cmd\endcsname\@changed@cmd
8383 \def\DeclareTextAccent#1#2#3{%
8384   \DeclareTextCommand#1{#2}[1]{\accent#3 #1}
8385 }
8386 \def\DeclareTextCompositeCommand#1#2#3#4{%
8387   \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
8388   \edef\reserved@b{\string##1}%
8389   \edef\reserved@c{%
8390     \expandafter\@strip@args\meaning\reserved@a:-\@strip@args}%
8391   \ifx\reserved@b\reserved@c
8392     \expandafter\expandafter\expandafter\ifx
8393       \expandafter\@car\reserved@a\relax\relax\@nil
8394     \@text@composite
8395   \else
8396     \edef\reserved@b##1{%
8397       \def\expandafter\noexpand

```

```

8398         \csname#2\string#1\endcsname####1{%
8399         \noexpand\@text@composite
8400         \expandafter\noexpand\csname#2\string#1\endcsname
8401         #####1\noexpand\@empty\noexpand\@text@composite
8402         {##1}%
8403     }%
8404 }%
8405     \expandafter\reserved@b\expandafter{\reserved@a{##1}}%
8406 \fi
8407     \expandafter\def\csname\expandafter\string\csname
8408     #2\endcsname\string#1-\string#3\endcsname{#4}
8409 \else
8410     \errhelp{Your command will be ignored, type <return> to proceed}%
8411     \errmessage{\string\DeclareTextCompositeCommand\space used on
8412     inappropriate command \protect#1}
8413 \fi
8414 }
8415 \def\@text@composite#1#2#3\@text@composite{%
8416     \expandafter\@text@composite@x
8417     \csname\string#1-\string#2\endcsname
8418 }
8419 \def\@text@composite@x#1#2{%
8420     \ifx#1\relax
8421         #2%
8422     \else
8423         #1%
8424     \fi
8425 }
8426 %
8427 \def\@strip@args#1:#2-#3\@strip@args{#2}
8428 \def\DeclareTextComposite#1#2#3#4{%
8429     \def\reserved@a{\DeclareTextCompositeCommand#1{#2}{#3}}%
8430     \bgroup
8431         \lccode`\@=#4%
8432         \lowercase{%
8433     \egroup
8434     \reserved@a @%
8435 }%
8436 }
8437 %
8438 \def\UseTextSymbol#1#2{#2}
8439 \def\UseTextAccent#1#2#3{}
8440 \def\@use@text@encoding#1{}
8441 \def\DeclareTextSymbolDefault#1#2{%
8442     \DeclareTextCommandDefault#1{\UseTextSymbol{#2}#1}%
8443 }
8444 \def\DeclareTextAccentDefault#1#2{%
8445     \DeclareTextCommandDefault#1{\UseTextAccent{#2}#1}%
8446 }
8447 \def\cf@encoding{OT1}

```

Currently we only use the \LaTeX 2_ϵ method for accents for those that are known to be made active in *some* language definition file.

```

8448 \DeclareTextAccent{"}{OT1}{127}
8449 \DeclareTextAccent{'}{OT1}{19}
8450 \DeclareTextAccent{^}{OT1}{94}
8451 \DeclareTextAccent`}{OT1}{18}
8452 \DeclareTextAccent{~}{OT1}{126}

```

The following control sequences are used in `babel.def` but are not defined for PLAIN \TeX .

```

8453 \DeclareTextSymbol{\textquotedblleft}{OT1}{92}
8454 \DeclareTextSymbol{\textquotedblright}{OT1}{`\"}
8455 \DeclareTextSymbol{\textquoteleft}{OT1}{``}
8456 \DeclareTextSymbol{\textquoteright}{OT1}{``'}

```

```

8457 \DeclareTextSymbol{\i}{OT1}{16}
8458 \DeclareTextSymbol{\ss}{OT1}{25}

```

For a couple of languages we need the \LaTeX -control sequence `\scriptsize` to be available. Because plain \TeX doesn't have such a sophisticated font mechanism as \LaTeX has, we just `\let` it to `\sevenrm`.

```

8459 \ifx\scriptsize\@undefined
8460   \let\scriptsize\sevenrm
8461 \fi

```

And a few more “dummy” definitions.

```

8462 \def\language{english}%
8463 \let\bbl@opt@shorthands\@nnil
8464 \def\bbl@ifshorthand#1#2#3{#2}%
8465 \let\bbl@language@opts\@empty
8466 \ifx\babeloptionstrings\@undefined
8467   \let\bbl@opt@strings\@nnil
8468 \else
8469   \let\bbl@opt@strings\babeloptionstrings
8470 \fi
8471 \def\BabelStringsDefault{generic}
8472 \def\bbl@tempa{normal}
8473 \ifx\babeloptionmath\bbl@tempa
8474   \def\bbl@mathnormal{\noexpand\textormath}
8475 \fi
8476 \def\AfterBabelLanguage#1#2{}
8477 \ifx\BabelModifiers\@undefined\let\BabelModifiers\relax\fi
8478 \let\bbl@afterlang\relax
8479 \def\bbl@opt@safe{BR}
8480 \ifx\@uclclist\@undefined\let\@uclclist\@empty\fi
8481 \ifx\bbl@trace\@undefined\def\bbl@trace#1{}\fi
8482 \expandafter\newif\csname ifbbl@single\endcsname
8483 \chardef\bbl@bidimode\z@
8484 <</Emulate LaTeX>>

```

A proxy file:

```

8485 <*plain>
8486 \input babel.def
8487 </plain>

```

21 Acknowledgements

I would like to thank all who volunteered as β -testers for their time. Michel Goossens supplied contributions for most of the other languages. Nico Poppelier helped polish the text of the documentation and supplied parts of the macros for the Dutch language. Paul Wackers and Werenfried Spit helped find and repair bugs. During the further development of the babel system I received much help from Bernd Raichle, for which I am grateful.

References

- [1] Huda Smitshuijzen Abifares, *Arabic Typography*, Saqi, 2001.
- [2] Johannes Braams, Victor Eijkhout and Nico Poppelier, *The development of national \LaTeX styles*, *TUGboat* 10 (1989) #3, p. 401–406.
- [3] Yannis Haralambous, *Fonts & Encodings*, O'Reilly, 2007.
- [4] Donald E. Knuth, *The \TeX book*, Addison-Wesley, 1986.
- [5] Jukka K. Korpela, *Unicode Explained*, O'Reilly, 2006.
- [6] Leslie Lamport, *\LaTeX , A document preparation System*, Addison-Wesley, 1986.
- [7] Leslie Lamport, in: \TeX hax Digest, Volume 89, #13, 17 February 1989.
- [8] Ken Lunde, *CJKV Information Processing*, O'Reilly, 2nd ed., 2009.

- [9] Edward M. Reingold and Nachum Dershowitz, *Calendrical Calculations: The Ultimate Edition*, Cambridge University Press, 2018
- [10] Hubert Partl, *German T_EX*, *TUGboat* 9 (1988) #1, p. 70–72.
- [11] Joachim Schrod, *International L^AT_EX is ready to use*, *TUGboat* 11 (1990) #1, p. 87–90.
- [12] Apostolos Syropoulos, Antonis Tsolomitis and Nick Sofroniu, *Digital typography using L^AT_EX*, Springer, 2002, p. 301–373.
- [13] K.F. Treebus. *Tekstwijzer; een gids voor het grafisch verwerken van tekst*, SDU Uitgeverij ('s-Gravenhage, 1988).