

Babel

Localization and
internationalization

Unicode

T_EX

pdfT_EX

LuaT_EX

XeT_EX

Version 3.76.2772
2022/06/18

Javier Bezos
Current maintainer

Johannes L. Braams
Original author

Contents

I	User guide	4
1	The user interface	4
1.1	Monolingual documents	4
1.2	Multilingual documents	6
1.3	Mostly monolingual documents	7
1.4	Modifiers	8
1.5	Troubleshooting	8
1.6	Plain	9
1.7	Basic language selectors	9
1.8	Auxiliary language selectors	10
1.9	More on selection	10
1.10	Shorthands	12
1.11	Package options	15
1.12	The base option	17
1.13	ini files	17
1.14	Selecting fonts	25
1.15	Modifying a language	27
1.16	Creating a language	28
1.17	Digits and counters	31
1.18	Dates	33
1.19	Accessing language info	33
1.20	Hyphenation and line breaking	35
1.21	Transforms	37
1.22	Selection based on BCP 47 tags	39
1.23	Selecting scripts	40
1.24	Selecting directions	41
1.25	Language attributes	45
1.26	Hooks	45
1.27	Languages supported by babel with ldf files	47
1.28	Unicode character properties in luatex	48
1.29	Tweaking some features	48
1.30	Tips, workarounds, known issues and notes	48
1.31	Current and future work	50
1.32	Tentative and experimental code	50
2	Loading languages with language.dat	50
2.1	Format	51
3	The interface between the core of babel and the language definition files	51
3.1	Guidelines for contributed languages	52
3.2	Basic macros	53
3.3	Skeleton	54
3.4	Support for active characters	55
3.5	Support for saving macro definitions	55
3.6	Support for extending macros	56
3.7	Macros common to a number of languages	56
3.8	Encoding-dependent strings	56
3.9	Executing code based on the selector	59
II	Source code	60
4	Identification and loading of required files	60
5	locale directory	60

6	Tools	61
6.1	Multiple languages	65
6.2	The Package File (<code>\LaTeX</code> , <code>babel.sty</code>)	66
6.3	<code>base</code>	67
6.4	<code>key=value</code> options and other general option	67
6.5	Conditional loading of shorthands	69
6.6	Interlude for Plain	70
7	Multiple languages	70
7.1	Selecting the language	73
7.2	Errors	81
7.3	Hooks	83
7.4	Setting up language files	85
7.5	Shorthands	87
7.6	Language attributes	96
7.7	Support for saving macro definitions	97
7.8	Short tags	98
7.9	Hyphens	99
7.10	Multiencoding strings	100
7.11	Macros common to a number of languages	107
7.12	Making glyphs available	107
7.12.1	Quotation marks	107
7.12.2	Letters	108
7.12.3	Shorthands for quotation marks	109
7.12.4	Umlauts and tremas	110
7.13	Layout	111
7.14	Load engine specific macros	112
7.15	Creating and modifying languages	112
8	Adjusting the Babel behavior	134
8.1	Cross referencing macros	135
8.2	Marks	138
8.3	Preventing clashes with other packages	139
8.3.1	<code>ifthen</code>	139
8.3.2	<code>varioref</code>	140
8.3.3	<code>hhline</code>	140
8.4	Encoding and fonts	141
8.5	Basic bidi support	142
8.6	Local Language Configuration	146
8.7	Language options	146
9	The kernel of Babel (<code>babel.def</code>, <code>common</code>)	149
10	Loading hyphenation patterns	149
11	Font handling with <code>fontspec</code>	153
12	Hooks for XeTeX and LuaTeX	158
12.1	XeTeX	158
12.2	Layout	159
12.3	LuaTeX	161
12.4	Southeast Asian scripts	167
12.5	CJK line breaking	168
12.6	Arabic justification	170
12.7	Common stuff	174
12.8	Automatic fonts and ids switching	174
12.9	Bidi	179
12.10	Layout	181
12.11	Lua: transforms	186

12.12	Lua: Auto bidi with basic and basic-r	194
13	Data for CJK	204
14	The ‘nil’ language	204
15	Calendars	205
15.1	Islamic	205
16	Hebrew	207
17	Persian	211
18	Coptic	212
19	Buddhist	212
20	Support for Plain T_EX (plain.def)	212
20.1	Not renaming hyphen.tex	212
20.2	Emulating some L ^A T _E X features	213
20.3	General tools	213
20.4	Encoding related macros	217
21	Acknowledgements	220

Troubleshoooting

Paragraph ended before \UTFviii@three@octets was complete	5
No hyphenation patterns were preloaded for (babel) the language ‘LANG’ into the format	5
You are loading directly a language style	8
Unknown language ‘LANG’	8
Argument of \language@active@arg” has an extra }	12
Package fontspec Warning: ‘Language ‘LANG’ not available for font ‘FONT’ with script ‘SCRIPT’ ‘Default’ language used instead’	26
Package babel Info: The following fonts are not babel standard families	26

Part I

User guide

What is this document about? This user guide focuses on internationalization and localization with \LaTeX and pdf \TeX , xetex and luatex with the babel package. There are also some notes on its use with e-Plain and pdf-Plain \TeX . Part II describes the code, and usually it can be ignored.

What if I'm interested only in the latest changes? Changes and new features with relation to version 3.8 are highlighted with **New X.XX**, and there are some notes for the latest versions in [the babel site](#). The most recent features can be still unstable.

Can I help? Sure! If you are interested in the \TeX multilingual support, please join the [kadingira mail list](#). You can follow the development of babel in [GitHub](#) and make suggestions; feel free to fork it and make pull requests. If you are the author of a package, send to me a few test files which I'll add to mine, so that possible issues can be caught in the development phase.

It doesn't work for me! You can ask for help in some forums like tex.stackexchange, but if you have found a bug, I strongly beg you to report it in [GitHub](#), which is much better than just complaining on an e-mail list or a web forum. Remember *warnings are not errors* by themselves, they just warn about possible problems or incompatibilities.

How can I contribute a new language? See section 3.1 for contributing a language.

I only need learn the most basic features. The first subsections (1.1-1.3) describe the traditional way of loading a language (with ldf files), which is usually all you need. The alternative way based on ini files, which complements the previous one (it does *not* replace it, although it is still necessary in some languages), is described below; go to 1.13.

I don't like manuals. I prefer sample files. This manual contains lots of examples and tips, but in GitHub there are many [sample files](#).

1 The user interface

1.1 Monolingual documents

In most cases, a single language is required, and then all you need in \LaTeX is to load the package using its standard mechanism for this purpose, namely, passing that language as an optional argument. In addition, you may want to set the font and input encodings. Another approach is making the language a global option in order to let other packages detect and use it. This is the standard way in \LaTeX for an option – in this case a language – to be recognized by several packages.

Many languages are compatible with xetex and luatex. With them you can use babel to localize the documents. When these engines are used, the Latin script is covered by default in current \LaTeX (provided the document encoding is UTF-8), because the font loader is preloaded and the font is switched to `lmroman`. Other scripts require loading `fontspec`. You may want to set the font attributes with `fontspec`, too.

EXAMPLE Here is a simple full example for “traditional” \TeX engines (see below for xetex and luatex). The packages `fontenc` and `inputenc` do not belong to babel, but they are included in the example because typically you will need them. It assumes UTF-8, the default encoding:

PDF \TeX

```
\documentclass{article}

\usepackage[T1]{fontenc}
```

```

\usepackage[french]{babel}

\begin{document}

Plus ça change, plus c'est la même chose!

\end{document}

```

Now consider something like:

```

\documentclass[french]{article}
\usepackage{babel}
\usepackage{varioref}

```

With this setting, the package `varioref` will also see the option `french` and will be able to use it.

EXAMPLE And now a simple monolingual document in Russian (text from the Wikipedia) with `xetex` or `luatex`. Note neither `fontenc` nor `inputenc` are necessary, but the document should be encoded in UTF-8 and a so-called Unicode font must be loaded (in this example `\babelfont` is used, described below).

LUATEX/XETEX

```

\documentclass[russian]{article}

\usepackage{babel}

\babelfont{rm}{DejaVu Serif}

\begin{document}

Россия, находящаяся на пересечении множества культур, а также
с учётом многонационального характера её населения, — отличается
высокой степенью этнокультурного многообразия и способностью к
межкультурному диалогу.

\end{document}

```

TROUBLESHOOTING A common source of trouble is a wrong setting of the input encoding. Depending on the \TeX version you can get the following somewhat cryptic error:

```
! Paragraph ended before \UTFviii@three@octets was complete.
```

Or the more explanatory:

```
! Package inputenc Error: Invalid UTF-8 byte ...
```

Make sure you set the encoding actually used by your editor.

NOTE Because of the way `babel` has evolved, “language” can refer to (1) a set of hyphenation patterns as preloaded into the format, (2) a package option, (3) an `ldf` file, and (4) a name used in the document to select a language or dialect. So, a package option refers to a language in a generic way – sometimes it is the actual language name used to select it, sometimes it is a file name loading a language with a different name, sometimes it is a file name loading several languages. Please, read the documentation for specific languages for further info.

TROUBLESHOOTING The following warning is about hyphenation patterns, which are not under the direct control of `babel`:

```
Package babel Warning: No hyphenation patterns were preloaded for
(babel)                  the language `LANG' into the format.
(babel)                  Please, configure your TeX system to add them and
(babel)                  rebuild the format. Now I will use the patterns
(babel)                  preloaded for \language=0 instead on input line 57.
```

The document will be typeset, but very likely the text will not be correctly hyphenated. Some languages may be raising this warning wrongly (because they are not hyphenated); it is a bug to be fixed – just ignore it. See the manual of your distribution (MacTeX, MikTeX, TeXLive, etc.) for further info about how to configure it.

NOTE With `hyperref` you may want to set the document language with something like:

```
\usepackage[pdflang=es-MX]{hyperref}
```

This is not currently done by `babel` and you must set it by hand.

NOTE Although it has been customary to recommend placing `\title`, `\author` and other elements printed by `\maketitle` after `\begin{document}`, mainly because of shorthands, it is advisable to keep them in the preamble. Currently there is no real need to use shorthands in those macros.

1.2 Multilingual documents

In multilingual documents, just use a list of the required languages as package or class options. The last language is considered the main one, activated by default. Sometimes, the main language changes the document layout (eg, spanish and french).

EXAMPLE In \LaTeX , the preamble of the document:

```
\documentclass{article}
\usepackage[dutch,english]{babel}
```

would tell \LaTeX that the document would be written in two languages, Dutch and English, and that English would be the first language in use, and the main one.

You can also set the main language explicitly, but it is discouraged except if there is a real reason to do so:

```
\documentclass{article}
\usepackage[main=english,dutch]{babel}
```

Examples of cases where `main` is useful are the following.

NOTE Some classes load `babel` with a hardcoded language option. Sometimes, the main language can be overridden with something like that before `\documentclass`:

```
\PassOptionsToPackage{main=english}{babel}
```

WARNING Languages may be set as global and as package option at the same time, but in such a case you should set explicitly the main language with the package option `main`:

```
\documentclass[italian]{book}
\usepackage[ngerman,main=italian]{babel}
```

WARNING In the preamble the main language has *not* been selected, except hyphenation patterns and the name assigned to `\language` (in particular, shorthands, captions and date are not activated). If you need to define boxes and the like in the preamble, you might want to use some of the language selectors described below.

To switch the language there are two basic macros, described below in detail:
`\selectlanguage` is used for blocks of text, while `\foreignlanguage` is for chunks of text inside paragraphs.

EXAMPLE A full bilingual document with pdf_{tex} follows. The main language is french, which is activated when the document begins. It assumes UTF-8:

PDF_{TEX}

```
\documentclass{article}

\usepackage[T1]{fontenc}

\usepackage[english,french]{babel}

\begin{document}

Plus ça change, plus c'est la même chose!

\selectlanguage{english}

And an English paragraph, with a short text in
\foreignlanguage{french}{français}.

\end{document}
```

EXAMPLE With xetex and luatex, the following bilingual, single script document in UTF-8 encoding just prints a couple of ‘captions’ and `\today` in Danish and Vietnamese. No additional packages are required.

LUATEX/XETEX

```
\documentclass{article}

\usepackage[vietnamese,danish]{babel}

\begin{document}

\prefacename{} -- \alsoname{} -- \today

\selectlanguage{vietnamese}

\prefacename{} -- \alsoname{} -- \today

\end{document}
```

NOTE Once loaded a language, you can select it with the corresponding BCP47 tag. See section 1.22 for further details.

1.3 Mostly monolingual documents

New 3.39 Very often, multilingual documents consist of a main language with small pieces of text in another languages (words, idioms, short sentences). Typically, all you need is to set the line breaking rules and, perhaps, the font. In such a case, babel now does not require declaring these secondary languages explicitly, because the basic settings are loaded on the fly when the language is selected (and also when provided in the optional argument of `\babelfont`, if used.)

This is particularly useful, too, when there are short texts of this kind coming from an external source whose contents are not known on beforehand (for example, titles in a bibliography). At this regard, it is worth remembering that `\babelfont` does *not* load any font until required, so that it can be used just in case.

EXAMPLE A trivial document with the default font in English and Spanish, and FreeSerif in Russian is:


```
\documentclass[english]{article}
\usepackage{babel}

\babelfont[russian]{rm}{FreeSerif}

\begin{document}

English. \foreignlanguage{russian}{Русский}.
\foreignlanguage{spanish}{Español}.

\end{document}
```

NOTE Instead of its name, you may prefer to select the language with the corresponding BCP47 tag. This alternative, however, must be activated explicitly, because a two- or tree-letter word is a valid name for a language (eg, yi). See section 1.22 for further details.

1.4 Modifiers

New 3.9c The basic behavior of some languages can be modified when loading babel by means of *modifiers*. They are set after the language name, and are prefixed with a dot (only when the language is set as package option – neither global options nor the main key accepts them). An example is (spaces are not significant and they can be added or removed):¹

```
\usepackage[latin.medieval, spanish.notilde.lcroman, danish]{babel}
```

Attributes (described below) are considered modifiers, ie, you can set an attribute by including it in the list of modifiers. However, modifiers are a more general mechanism.

1.5 Troubleshooting

- Loading directly sty files in L^AT_EX (ie, `\usepackage{<language>}`) is deprecated and you will get the error:²

```
! Package babel Error: You are loading directly a language style.
(babel)                This syntax is deprecated and you must use
(babel)                \usepackage[language]{babel}.
```

- Another typical error when using babel is the following:³

```
! Package babel Error: Unknown language `#1'. Either you have
(babel)                misspelled its name, it has not been installed,
(babel)                or you requested it in a previous run. Fix its name,
(babel)                install it or just rerun the file, respectively. In
(babel)                some cases, you may need to remove the aux file
```

The most frequent reason is, by far, the latest (for example, you included spanish, but you realized this language is not used after all, and therefore you removed it from the option list). In most cases, the error vanishes when the document is typeset again, but in more severe ones you will need to remove the aux file.

¹No predefined “axis” for modifiers are provided because languages and their scripts have quite different needs.

²In old versions the error read “You have used an old interface to call babel”, not very helpful.

³In old versions the error read “You haven’t loaded the language LANG yet”.

1.6 Plain

In e-Plain and pdf-Plain, load languages styles with `\input` and then use `\begindocument` (the latter is defined by babel):

```
\input estonian.sty
\begindocument
```

WARNING Not all languages provide a sty file and some of them are not compatible with those formats. Please, refer to [Using babel with Plain](#) for further details.

1.7 Basic language selectors

This section describes the commands to be used in the document to switch the language in multilingual documents. In most cases, only the two basic macros `\selectlanguage` and `\foreignlanguage` are necessary. The environments `otherlanguage`, `otherlanguage*` and `hyphenrules` are auxiliary, and described in the next section. The main language is selected automatically when the document environment begins.

`\selectlanguage` $\{ \langle language \rangle \}$

When a user wants to switch from one language to another he can do so using the macro `\selectlanguage`. This macro takes the language, defined previously by a language definition file, as its argument. It calls several macros that should be defined in the language definition files to activate the special definitions for the language chosen:

```
\selectlanguage{german}
```

This command can be used as environment, too.

NOTE For “historical reasons”, a macro name is converted to a language name without the leading `\`; in other words, `\selectlanguage{\german}` is equivalent to `\selectlanguage{german}`. Using a macro instead of a “real” name is deprecated. **New 3.43** However, if the macro name does not match any language, it will get expanded as expected.

NOTE Bear in mind `\selectlanguage` can be automatically executed, in some cases, in the auxiliary files, at heads and foots, and after the environment `otherlanguage*`.

WARNING If used inside braces there might be some non-local changes, as this would be roughly equivalent to:

```
{\selectlanguage{<inner-language>} ...}\selectlanguage{<outer-language>}
```

If you want a change which is really local, you must enclose this code with an additional grouping level.

WARNING There are a couple of issues related to the way the language information is written to the auxiliary files:

- `\selectlanguage` should not be used inside some boxed environments (like floats or `minipage`) to switch the language if you need the information written to the aux be correctly synchronized. This rarely happens, but if it were the case, you must use `otherlanguage` instead.
- In addition, this macro inserts a `\write` in vertical mode, which may break the vertical spacing in some cases (for example, between lists). **New 3.64** The behavior can be adjusted with `\babeladjust{select.write=<mode>}`, where `<mode>` is `shift` (which shifts the skips down and adds a `\penalty`); `keep` (the default – with it the `\write` and the skips are kept in the order they are written), and `omit` (which may seem a too drastic solution, because nothing is written, but more often than not this command is applied to more or less short texts with no sectioning or similar commands and therefore no language synchronization is necessary).

`\foreignlanguage` [*⟨option-list⟩*]{*⟨language⟩*}{*⟨text⟩*}

The command `\foreignlanguage` takes two arguments; the second argument is a phrase to be typeset according to the rules of the language named in its first one.

This command (1) only switches the extra definitions and the hyphenation rules for the language, *not* the names and dates, (2) does not send information about the language to auxiliary files (i.e., the surrounding language is still in force), and (3) it works even if the language has not been set as package option (but in such a case it only sets the hyphenation patterns and a warning is shown). With the `bidi` option, it also enters in horizontal mode (this is not done always for backwards compatibility), and since it is meant for phrases only the text direction (and not the paragraph one) is set.

New 3.44 As already said, captions and dates are not switched. However, with the optional argument you can switch them, too. So, you can write:

```
\foreignlanguage[date]{polish}{\today}
```

In addition, captions can be switched with `captions` (or both, of course, with `date, captions`). Until 3.43 you had to write something like `{\selectlanguage{..} ..}`, which was not always the most convenient way.

1.8 Auxiliary language selectors

`\begin{otherlanguage}` {*⟨language⟩*} ... **`\end{otherlanguage}`**

The environment `otherlanguage` does basically the same as `\selectlanguage`, except that language change is (mostly) local to the environment.

Actually, there might be some non-local changes, as this environment is roughly equivalent to:

```
\begingroup
\selectlanguage{<inner-language>}
...
\endgroup
\selectlanguage{<outer-language>}
```

If you want a change which is really local, you must enclose this environment with an additional grouping, like braces `{}`.

Spaces after the environment are ignored.

`\begin{otherlanguage*}` [*⟨option-list⟩*]{*⟨language⟩*} ... **`\end{otherlanguage*}`**

Same as `\foreignlanguage` but as environment. Spaces after the environment are *not* ignored.

This environment was originally intended for intermixing left-to-right typesetting with right-to-left typesetting in engines not supporting a change in the writing direction inside a line. However, by default it never complied with the documented behavior and it is just a version as environment of `\foreignlanguage`, except when the option `bidi` is set – in this case, `\foreignlanguage` emits a `\leavevmode`, while `otherlanguage*` does not.

1.9 More on selection

`\babeltags` {*⟨tag1⟩* = *⟨language1⟩*, *⟨tag2⟩* = *⟨language2⟩*, ...}

New 3.9i In multilingual documents with many language-switches the commands above can be cumbersome. With this tool shorter names can be defined. It adds nothing really new – it is just syntactical sugar.

It defines `\text{<tag1>{<text>}}` to be `\foreignlanguage{<language1>}{<text>}`, and `\begin{<tag1>}` to be `\begin{otherlanguage*}{<language1>}`, and so on. Note `\{<tag1>` is also allowed, but remember to set it locally inside a group.

WARNING There is a clear drawback to this feature, namely, the ‘prefix’ `\text...` is heavily overloaded in \TeX and conflicts with existing macros may arise (`\textlatin`, `\textbar`, `\textit`, `\textcolor` and many others). The same applies to environments, because `arabic` conflicts with `\arabic`. Furthermore, and because of this overloading, detecting the language of a chunk of text by external tools can become unfeasible. Except if there is a reason for this ‘syntactical sugar’, the best option is to stick to the default selectors or to define your own alternatives.

EXAMPLE With

```
\babeltags{de = german}
```

you can write

```
text \textde{German text} text
```

and

```
text
\begin{de}
  German text
\end{de}
text
```

NOTE Something like `\babeltags{finnish = finnish}` is legitimate – it defines `\textfinnish` and `\finnish` (and, of course, `\begin{finnish}`).

NOTE Actually, there may be another advantage in the ‘short’ syntax `\text{<tag>}`, namely, it is not affected by `\MakeUppercase` (while `\foreignlanguage` is).

\babelensure `[include=<commands>, exclude=<commands>, fontenc=<encoding>]{<language>}`

New 3.9i Except in a few languages, like `ruussian`, captions and dates are just strings, and do not switch the language. That means you should set it explicitly if you want to use them, or hyphenation (and in some cases the text itself) will be wrong. For example:

```
\foreignlanguage{ruussian}{text \foreignlanguage{polish}{\seename} text}
```

Of course, \TeX can do it for you. To avoid switching the language all the while, `\babelensure` redefines the captions for a given language to wrap them with a selector:

```
\babelensure{polish}
```

By default only the basic captions and `\today` are redefined, but you can add further macros with the key `include` in the optional argument (without commas). Macros not to be modified are listed in `exclude`. You can also enforce a font encoding with the option `fontenc`.⁴ A couple of examples:

```
\babelensure[include=\Today]{spanish}
\babelensure[fontenc=T5]{vietnamese}
```

They are activated when the language is selected (at the `afterextras` event), and it makes some assumptions which could not be fulfilled in some languages. Note also you should include only macros defined by the language, not global macros (eg, \TeX of `\dag`). With `ini` files (see below), captions are ensured by default.

⁴With it, encoded strings may not work as expected.

1.10 Shorthands

A *shorthand* is a sequence of one or two characters that expands to arbitrary TeX code. Shorthands can be used for different kinds of things; for example: (1) in some languages shorthands such as "a are defined to be able to hyphenate the word if the encoding is OT1; (2) in some languages shorthands such as ! are used to insert the right amount of white space; (3) several kinds of discretionary and breaks can be inserted easily with "-", "=", etc. The package inputenc as well as xetex and luatex have alleviated entering non-ASCII characters, but minority languages and some kinds of text can still require characters not directly available on the keyboards (and sometimes not even as separated or precomposed Unicode characters). As to the point 2, now pdfTeX provides \knbcode, and luatex can manipulate the glyph list. Tools for point 3 can be still very useful in general. There are four levels of shorthands: *user*, *language*, *system*, and *language user* (by order of precedence). In most cases, you will use only shorthands provided by languages.

NOTE Keep in mind the following:

1. Activated chars used for two-char shorthands cannot be followed by a closing brace } and the spaces following are gobbled. With one-char shorthands (eg, :), they are preserved.
2. If on a certain level (system, language, user, language user) there is a one-char shorthand, two-char ones starting with that char and on the same level are ignored.
3. Since they are active, a shorthand cannot contain the same character in its definition (except if deactivated with, eg, \string).

TROUBLESHOOTING A typical error when using shorthands is the following:

```
! Argument of \language@active@arg" has an extra }.
```

It means there is a closing brace just after a shorthand, which is not allowed (eg, "}"). Just add {} after (eg, "{}").

`\shorthandon` `{\shorthands-list}`
`\shorthandoff` `*{\shorthands-list}`

It is sometimes necessary to switch a shorthand character off temporarily, because it must be used in an entirely different way. For this purpose, the user commands `\shorthandoff` and `\shorthandon` are provided. They each take a list of characters as their arguments. The command `\shorthandoff` sets the `\catcode` for each of the characters in its argument to other (12); the command `\shorthandon` sets the `\catcode` to active (13). Both commands only work on ‘known’ shorthand characters.

New 3.9a However, `\shorthandoff` does not behave as you would expect with characters like ~ or ^, because they usually are not “other”. For them `\shorthandoff*` is provided, so that with

```
\shorthandoff*{~^}
```

~ is still active, very likely with the meaning of a non-breaking space, and ^ is the superscript character. The catcodes used are those when the shorthands are defined, usually when language files are loaded.

If you do not need shorthands, or prefer an alternative approach of your own, you may want to switch them off with the package option `shorthands=off`, as described below.

WARNING It is worth emphasizing these macros are meant for temporary changes. Whenever possible and if there are not conflicts with other packages, shorthands must be always enabled (or disabled).

`\useshortands` `*{\langle char \rangle}`

The command `\useshortands` initiates the definition of user-defined shorthand sequences. It has one argument, the character that starts these personal shorthands.

New 3.9a User shorthands are not always alive, as they may be deactivated by languages (for example, if you use " for your user shorthands and switch from german to french, they stop working). Therefore, a starred version `\useshortands*{\langle char \rangle}` is provided, which makes sure shorthands are always activated.

Currently, if the package option `shorthands` is used, you must include any character to be activated with `\useshortands`. This restriction will be lifted in a future release.

`\defineshortand` `[\langle language \rangle, \langle language \rangle, ...]{\langle shorthand \rangle}{\langle code \rangle}`

The command `\defineshortand` takes two arguments: the first is a one- or two-character shorthand sequence, and the second is the code the shorthand should expand to.

New 3.9a An optional argument allows to (re)define language and system shorthands (some languages do not activate shorthands, so you may want to add `\languageshortands{\langle lang \rangle}` to the corresponding `\extras{\langle lang \rangle}`, as explained below). By default, user shorthands are (re)defined.

User shorthands override language ones, which in turn override system shorthands.

Language-dependent user shorthands (new in 3.9) take precedence over “normal” user shorthands.

EXAMPLE Let’s assume you want a unified set of shorthand for dictionaries (languages do not define shorthands consistently, and “-”, “\”, “=” have different meanings). You can start with, say:

```
\useshortands*{"}
\defineshortand{"*}{\babelhyphen{soft}}
\defineshortand{"-}{\babelhyphen{hard}}
```

However, the behavior of hyphens is language-dependent. For example, in languages like Polish and Portuguese, a hard hyphen inside compound words are repeated at the beginning of the next line. You can then set:

```
\defineshortand[*polish,*portuguese]{"-}{\babelhyphen{repeat}}
```

Here, options with `*` set a language-dependent user shorthand, which means the generic one above only applies for the rest of languages; without `*` they would (re)define the language shorthands instead, which are overridden by user ones.

Now, you have a single unified shorthand (“-”), with a content-based meaning (‘compound word hyphen’) whose visual behavior is that expected in each context.

`\languageshortands` `{\langle language \rangle}`

The command `\languageshortands` can be used to switch the shorthands on the language level. It takes one argument, the name of a language or none (the latter does what its name suggests).⁵ Note that for this to work the language should have been specified as an option when loading the `babel` package. For example, you can use in english the shorthands defined by `ngerman` with

```
\addto\extrasenglish{\languageshortands{ngerman}}
```

(You may also need to activate them as user shorthands in the preamble with, for example, `\useshortands` or `\useshortands*`.)

⁵Actually, any name not corresponding to a language group does the same as none. However, follow this convention because it might be enforced in future releases of `babel` to catch possible errors.

EXAMPLE Very often, this is a more convenient way to deactivate shorthands than `\shorthandoff`, for example if you want to define a macro to easy typing phonetic characters with `tipa`:

```
\newcommand{\myipa}[1]{\{\language shorthands{none}\tipaencoding#1}}
```

\babelshorthand `{\langle shorthand \rangle}`

With this command you can use a shorthand even if (1) not activated in shorthands (in this case only shorthands for the current language are taken into account, ie, not user shorthands), (2) turned off with `\shorthandoff` or (3) deactivated with the internal `\bbl@deactivate`; for example, `\babelshorthand{"u}` or `\babelshorthand{:}`. (You can conveniently define your own macros, or even your own user shorthands provided they do not overlap.)

EXAMPLE Since by default shorthands are not activated until `\begin{document}`, you may use this macro when defining the `\title` in the preamble:

```
\title{Documento científico\babelshorthand{"-}técnico}
```

For your records, here is a list of shorthands, but you must double check them, as they may change:⁶

Languages with no shorthands Croatian, English (any variety), Indonesian, Hebrew, Interlingua, Irish, Lower Sorbian, Malaysian, North Sami, Romanian, Scottish, Welsh
Languages with only " as defined shorthand character Albanian, Bulgarian, Danish, Dutch, Finnish, German (old and new orthography, also Austrian), Icelandic, Italian, Norwegian, Polish, Portuguese (also Brazilian), Russian, Serbian (with Latin script), Slovene, Swedish, Ukrainian, Upper Sorbian

Basque " ' ~
Breton : ; ? !
Catalan " ' ` ~
Czech " -
Esperanto ^
Estonian " ~
French (all varieties) : ; ? !
Galician " . ' ~ < >
Greek ~
Hungarian ` ~
Kurmanji ^
Latin " ^ =
Slovak " ^ ' -
Spanish " . < > ' ~
Turkish : ! =

In addition, the babel core declares ~ as a one-char shorthand which is let, like the standard ~, to a non breaking space.⁷

\ifbabelshorthand `{\langle character \rangle}{\langle true \rangle}{\langle false \rangle}`

New 3.23 Tests if a character has been made a shorthand.

\aliasshorthand `{\langle original \rangle}{\langle alias \rangle}`

The command `\aliasshorthand` can be used to let another character perform the same functions as the default shorthand character. If one prefers for example to use the

⁶Thanks to Enrico Gregorio

⁷This declaration serves to nothing, but it is preserved for backward compatibility.

character / over " in typing Polish texts, this can be achieved by entering `\aliasshorthand{"}{/}`. For the reasons in the warning below, usage of this macro is not recommended.

NOTE The substitute character must *not* have been declared before as shorthand (in such a case, `\aliasshorthands` is ignored).

EXAMPLE The following example shows how to replace a shorthand by another

```
\aliasshorthand{~}{^}
\AtBeginDocument{\shorthandoff*{~}}
```

WARNING Shorthands remember somehow the original character, and the fallback value is that of the latter. So, in this example, if no shorthand is found, `^` expands to a non-breaking space, because this is the value of `~` (internally, `^` still calls `\active@char~` or `\normal@char~`). Furthermore, if you change the system value of `^` with `\defineshorthand` nothing happens.

1.11 Package options

New 3.9a These package options are processed before language options, so that they are taken into account irrespective of its order. The first three options have been available in previous versions.

KeepShorthandsActive Tells babel not to deactivate shorthands after loading a language file, so that they are also available in the preamble.

activeacute For some languages babel supports this options to set ' as a shorthand in case it is not done by default.

activegrave Same for `.

shorthands= `<char><char>... | off`
The only language shorthands activated are those given, like, eg:

```
\usepackage[esperanto,french,shorthands=:;!]{babel}
```

If ' is included, `activeacute` is set; if ` is included, `activegrave` is set. Active characters (like `~`) should be preceded by `\string` (otherwise they will be expanded by \TeX before they are passed to the package and therefore they will not be recognized); however, `t` is provided for the common case of `~` (as well as `c` for not so common case of the comma). With `shorthands=off` no language shorthands are defined. As some languages use this mechanism for tools not available otherwise, a macro `\babelshorthand` is defined, which allows using them; see above.

safe= `none | ref | bib`
Some \TeX macros are redefined so that using shorthands is safe. With `safe=bib` only `\nocite`, `\bibcite` and `\bibitem` are redefined. With `safe=ref` only `\newlabel`, `\ref` and `\pageref` are redefined (as well as a few macros from `varioref` and `ifthen`). With `safe=none` no macro is redefined. This option is strongly recommended, because a good deal of incompatibilities and errors are related to these redefinitions. As of **New 3.34**, in $\epsilon\TeX$ based engines (ie, almost every engine except the oldest ones) shorthands can be used in these macros (formerly you could not).

math= `active | normal`
Shorthands are mainly intended for text, not for math. By setting this option with the value `normal` they are deactivated in math mode (default is `active`) and things like `#{a'}` (a closing brace after a shorthand) are not a source of trouble anymore.

- config=** *<file>*
Load *<file>*.cfg instead of the default config file `bblopts.cfg` (the file is loaded even with `noconfigs`).
- main=** *<language>*
Sets the main language, as explained above, ie, this language is always loaded last. If it is not given as package or global option, it is added to the list of requested languages.
- headfoot=** *<language>*
By default, headlines and footlines are not touched (only marks), and if they contain language-dependent macros (which is not usual) there may be unexpected results. With this option you may set the language in heads and foots.
- noconfigs** Global and language default config files are not loaded, so you can make sure your document is not spoilt by an unexpected .cfg file. However, if the key `config` is set, this file is loaded.
- showlanguages** Prints to the log the list of languages loaded when the format was created: number (remember dialects can share it), name, hyphenation file and exceptions file.
- nocase** New 3.9l Language settings for uppercase and lowercase mapping (as set by `\SetCase`) are ignored. Use only if there are incompatibilities with other packages.
- silent** New 3.9l No warnings and no *infos* are written to the log file.⁸
- strings=** `generic` | `unicode` | `encoded` | *<label>* | **
Selects the encoding of strings in languages supporting this feature. Predefined labels are `generic` (for traditional T_EX, LICR and ASCII strings), `unicode` (for engines like xetex and luatex) and `encoded` (for special cases requiring mixed encodings). Other allowed values are font encoding codes (T1, T2A, LGR, L7X...), but only in languages supporting them. Be aware with encoded captions are protected, but they work in `\MakeUpper case` and the like (this feature misuses some internal L^AT_EX tools, so use it only as a last resort).
- hyphenmap=** `off` | `first` | `select` | `other` | `other*`
New 3.9g Sets the behavior of case mapping for hyphenation, provided the language defines it.⁹ It can take the following values:
- off** deactivates this feature and no case mapping is applied;
 - first** sets it at the first switching commands in the current or parent scope (typically, when the aux file is first read and at `\begin{document}`}, but also the first `\selectlanguage` in the preamble), and it's the default if a single language option has been stated;¹⁰
 - select** sets it only at `\selectlanguage`;
 - other** also sets it at `other language`;
 - other*** also sets it at `other language*` as well as in heads and foots (if the option `headfoot` is used) and in auxiliary files (ie, at `\select@language`), and it's the default if several language options have been stated. The option `first` can be regarded as an optimized version of `other*` for monolingual documents.¹¹

⁸You can use alternatively the package `silence`.

⁹Turned off in plain.

¹⁰Duplicated options count as several ones.

¹¹Providing `foreign` is pointless, because the case mapping applied is that at the end of the paragraph, but if either xetex or luatex change this behavior it might be added. On the other hand, `other` is provided even if I [JBL] think it isn't really useful, but who knows.

bidi= default | basic | basic-r | bidi-l | bidi-r

New 3.14 Selects the bidi algorithm to be used in luatex and xetex. See sec. 1.24.

layout=

New 3.16 Selects which layout elements are adapted in bidi documents. See sec. 1.24.

provide= *

New 3.49 An alternative to `\babelprovide` for languages passed as options. See section 1.13, which describes also the variants `provide+=` and `provide*=`.

1.12 The base option

With this package option `babel` just loads some basic macros (those in `switch.def`), defines `\AfterBabelLanguage` and exits. It also selects the hyphenation patterns for the last language passed as option (by its name in `language.dat`). There are two main uses: classes and packages, and as a last resort in case there are, for some reason, incompatible languages. It can be used if you just want to select the hyphenation patterns of a single language, too.

\AfterBabelLanguage `{<option-name>}{<code>}`

This command is currently the only provided by `base`. Executes `<code>` when the file loaded by the corresponding package option is finished (at `\ldf@finish`). The setting is global. So

```
\AfterBabelLanguage{french}{...}
```

does ... at the end of `french.ldf`. It can be used in `ldf` files, too, but in such a case the code is executed only if `<option-name>` is the same as `\CurrentOption` (which could not be the same as the option name as set in `\usepackage!`).

EXAMPLE Consider two languages `foo` and `bar` defining the same `\macro` with `\newcommand`. An error is raised if you attempt to load both. Here is a way to overcome this problem:

```
\usepackage[base]{babel}
\AfterBabelLanguage{foo}{%
  \let\macroFoo\macro
  \let\macro\relax}
\usepackage[foo,bar]{babel}
```

NOTE With a recent version of \TeX , an alternative method to execute some code just after an `ldf` file is loaded is with `\AddToHook` and the hook `file/<language>.ldf/after`. `Babel` does not predeclare it, and you have to do it yourself with `\ActivateGenericHook`.

WARNING Currently this option is not compatible with languages loaded on the fly.

1.13 ini files

An alternative approach to define a language (or, more precisely, a *locale*) is by means of an `ini` file. Currently `babel` provides about 250 of these files containing the basic data required for a locale, plus basic templates for 500 about locales.

`ini` files are not meant only for `babel`, and they have been devised as a resource for other packages. To easy interoperability between \TeX and other systems, they are identified with the BCP 47 codes as preferred by the Unicode Common Locale Data Repository, which was used as source for most of the data provided by these files, too (the main exception being the `\...name` strings).

Most of them set the date, and many also the captions (Unicode and LICR). They will be evolving with the time to add more features (something to keep in mind if backward

compatibility is important). The following section shows how to make use of them by means of `\babelprovide`. In other words, `\babelprovide` is mainly meant for auxiliary tasks, and as alternative when the `ldf`, for some reason, does work as expected.

EXAMPLE Although Georgian has its own `ldf` file, here is how to declare this language with an `ini` file in Unicode engines.

LUATEX/XETEX

```
\documentclass{book}

\usepackage{babel}
\babelprovide[import, main]{georgian}

\babelfont{rm}[Renderer=Harfbuzz]{DejaVu Sans}

\begin{document}

\tableofcontents

\chapter{სამზარეულო და სუფრის ტრადიციები}

ქართული ტრადიციული სამზარეულო ერთ-ერთი უმდიდრესია მთელ მსოფლიოში.

\end{document}
```

New 3.49 Alternatively, you can tell `babel` to load all or some languages passed as options with `\babelprovide` and not from the `ldf` file in a few typical cases. Thus, `provide=*` means ‘load the main language with the `\babelprovide` mechanism instead of the `ldf` file’ applying the basic features, which in this case means `import`, `main`. There are (currently) three options:

- `provide=*` is the option just explained, for the main language;
- `provide+=*` is the same for additional languages (the main language is still the `ldf` file);
- `provide*=*` is the same for all languages, ie, main and additional.

EXAMPLE The preamble in the previous example can be more compactly written as:

```
\documentclass{book}
\usepackage[georgian, provide=*]{babel}
\babelfont{rm}[Renderer=Harfbuzz]{DejaVu Sans}
```

Or also:

```
\documentclass[georgian]{book}
\usepackage[provide=*]{babel}
\babelfont{rm}[Renderer=Harfbuzz]{DejaVu Sans}
```

NOTE The `ini` files just define and set some parameters, but the corresponding behavior is not always implemented. Also, there are some limitations in the engines. A few remarks follow (which could no longer be valid when you read this manual, if the packages involved have been updated). The `Harfbuzz` renderer has still some issues, so as a rule of thumb prefer the default renderer, and resort to `Harfbuzz` only if the former does not work for you. Fortunately, fonts can be loaded twice with different renderers; for example:

```
\babelfont[spanish]{rm}{FreeSerif}
\babelfont[hindi]{rm}[Renderer=Harfbuzz]{FreeSerif}
```

Arabic Monolingual documents mostly work in luatex, but it must be fine tuned, particularly math and graphical elements like picture. In xetex babel resorts to the bidi package, which seems to work.

Hebrew Niqqud marks seem to work in both engines, but depending on the font cantillation marks might be misplaced (xetex or luatex with Harfbuzz seems better).

Devanagari In luatex and the the default renderer many fonts work, but some others do not, the main issue being the ‘ra’. You may need to set explicitly the script to either deva or dev2, eg:

```
\newfontscript{Devanagari}{deva}
```

Other Indic scripts are still under development in the default luatex renderer, but should work with Renderer=Harfbuzz. They also work with xetex, although unlike with luatex fine tuning the font behavior is not always possible.

Southeast scripts Thai works in both luatex and xetex, but line breaking differs (rules are hard-coded in xetex, but they can be modified in luatex). Lao seems to work, too, but there are no patterns for the latter in luatex. Khemer clusters are rendered wrongly with the default renderer. The comment about Indic scripts and luatex also applies here. Some quick patterns can help, with something similar to:

```
\babelprovide[import, hyphenrules=+]{lao}
\babelpatterns[lao]{lṇ lṃ lṂ lṁ lṅ lṇ lṅ} % Random
```

East Asia scripts Settings for either Simplified or Traditional should work out of the box, with basic line breaking with any renderer. Although for a few words and shorts texts the ini files should be fine, CJK texts are best set with a dedicated framework (CJK, luatexja, kotex, CTeX, etc.). This is what the class ltjbook does with luatex, which can be used in conjunction with the ldf for japanese, because the following piece of code loads luatexja:

```
\documentclass[japanese]{ltjbook}
\usepackage{babel}
```

Latin, Greek, Cyrillic Combining chars with the default luatex font renderer might be wrong; on the other hand, with the Harfbuzz renderer diacritics are stacked correctly, but many hyphenations points are discarded (this bug is related to kerning, so it depends on the font). With xetex both combining characters and hyphenation work as expected (not quite, but in most cases it works; the problem here are font clusters).

NOTE Wikipedia defines a *locale* as follows: “In computing, a locale is a set of parameters that defines the user’s language, region and any special variant preferences that the user wants to see in their user interface. Usually a locale identifier consists of at least a language code and a country/region code.” Babel is moving gradually from the old and fuzzy concept of *language* to the more modern of *locale*. Note each locale is by itself a separate “language”, which explains why there are so many files. This is on purpose, so that possible variants can be created and/or redefined easily.

Here is the list (u means Unicode captions, and l means LICR captions):

af	Afrikaans ^{ul}	bem	Bemba
agq	Aghem	bez	Bena
ak	Akan	bg	Bulgarian ^{ul}
am	Amharic ^{ul}	bm	Bambara
ar	Arabic ^{ul}	bn	Bangla ^{ul}
ar-DZ	Arabic ^{ul}	bo	Tibetan ^u
ar-MA	Arabic ^{ul}	brx	Bodo
ar-SY	Arabic ^{ul}	bs-Cyrl	Bosnian
as	Assamese	bs-Latn	Bosnian ^{ul}
asa	Asu	bs	Bosnian ^{ul}
ast	Asturian ^{ul}	ca	Catalan ^{ul}
az-Cyrl	Azerbaijani	ce	Chechen
az-Latn	Azerbaijani	cgg	Chiga
az	Azerbaijani ^{ul}	chr	Cherokee
bas	Basaa	ckb	Central Kurdish
be	Belarusian ^{ul}	cop	Coptic

cs	Czech ^{ul}	hsb	Upper Sorbian ^{ul}
cu	Church Slavic	hu	Hungarian ^{ul}
cu-Cyrs	Church Slavic	hy	Armenian ^u
cu-Glag	Church Slavic	ia	Interlingua ^{ul}
cy	Welsh ^{ul}	id	Indonesian ^{ul}
da	Danish ^{ul}	ig	Igbo
dav	Taita	ii	Sichuan Yi
de-AT	German ^{ul}	is	Icelandic ^{ul}
de-CH	German ^{ul}	it	Italian ^{ul}
de	German ^{ul}	ja	Japanese
dje	Zarma	jgo	Ngomba
dsb	Lower Sorbian ^{ul}	jmc	Machame
dua	Duala	ka	Georgian ^{ul}
dyo	Jola-Fonyi	kab	Kabyle
dz	Dzongkha	kam	Kamba
ebu	Embu	kde	Makonde
ee	Ewe	kea	Kabuverdianu
el	Greek ^{ul}	khq	Koyra Chiini
el-polyton	Polytonic Greek ^{ul}	ki	Kikuyu
en-AU	English ^{ul}	kk	Kazakh
en-CA	English ^{ul}	kkj	Kako
en-GB	English ^{ul}	kl	Kalaallisut
en-NZ	English ^{ul}	kln	Kalenjin
en-US	English ^{ul}	km	Khmer
en	English ^{ul}	kn	Kannada ^{ul}
eo	Esperanto ^{ul}	ko	Korean
es-MX	Spanish ^{ul}	kok	Konkani
es	Spanish ^{ul}	ks	Kashmiri
et	Estonian ^{ul}	ksb	Shambala
eu	Basque ^{ul}	ksf	Bafia
ewo	Ewondo	ksh	Colognian
fa	Persian ^{ul}	kw	Cornish
ff	Fulah	ky	Kyrgyz
fi	Finnish ^{ul}	lag	Langi
fil	Filipino	lb	Luxembourgish
fo	Faroese	lg	Ganda
fr	French ^{ul}	lkt	Lakota
fr-BE	French ^{ul}	ln	Lingala
fr-CA	French ^{ul}	lo	Lao ^{ul}
fr-CH	French ^{ul}	lrc	Northern Luri
fr-LU	French ^{ul}	lt	Lithuanian ^{ul}
fur	Friulian ^{ul}	lu	Luba-Katanga
fy	Western Frisian	luo	Luo
ga	Irish ^{ul}	luy	Luyia
gd	Scottish Gaelic ^{ul}	lv	Latvian ^{ul}
gl	Galician ^{ul}	mas	Masai
grc	Ancient Greek ^{ul}	mer	Meru
gsw	Swiss German	mfe	Morisyen
gu	Gujarati	mg	Malagasy
guz	Gusii	mgh	Makhuwa-Meetto
gv	Manx	mgo	Meta'
ha-GH	Hausa	mk	Macedonian ^{ul}
ha-NE	Hausa ^l	ml	Malayalam ^{ul}
ha	Hausa	mn	Mongolian
haw	Hawaiian	mr	Marathi ^{ul}
he	Hebrew ^{ul}	ms-BN	Malay ^l
hi	Hindi ^u	ms-SG	Malay ^l
hr	Croatian ^{ul}	ms	Malay ^{ul}

mt	Maltese	smn	Inari Sami
mua	Mundang	sn	Shona
my	Burmese	so	Somali
mzn	Mazanderani	sq	Albanian ^{ul}
naq	Nama	sr-Cyrl-BA	Serbian ^{ul}
nb	Norwegian Bokmål ^{ul}	sr-Cyrl-ME	Serbian ^{ul}
nd	North Ndebele	sr-Cyrl-XK	Serbian ^{ul}
ne	Nepali	sr-Cyrl	Serbian ^{ul}
nl	Dutch ^{ul}	sr-Latn-BA	Serbian ^{ul}
nmg	Kwasio	sr-Latn-ME	Serbian ^{ul}
nn	Norwegian Nynorsk ^{ul}	sr-Latn-XK	Serbian ^{ul}
nnh	Ngiemboon	sr-Latn	Serbian ^{ul}
nus	Nuer	sr	Serbian ^{ul}
nyn	Nyankole	sv	Swedish ^{ul}
om	Oromo	sw	Swahili
or	Odia	ta	Tamil ^u
os	Ossetic	te	Telugu ^{ul}
pa-Arab	Punjabi	teo	Teso
pa-Guru	Punjabi	th	Thai ^{ul}
pa	Punjabi	ti	Tigrinya
pl	Polish ^{ul}	tk	Turkmen ^{ul}
pms	Piedmontese ^{ul}	to	Tongan
ps	Pashto	tr	Turkish ^{ul}
pt-BR	Portuguese ^{ul}	twq	Tasawaq
pt-PT	Portuguese ^{ul}	tzm	Central Atlas Tamazight
pt	Portuguese ^{ul}	ug	Uyghur
qu	Quechua	uk	Ukrainian ^{ul}
rm	Romansh ^{ul}	ur	Urdu ^{ul}
rn	Rundi	uz-Arab	Uzbek
ro	Romanian ^{ul}	uz-Cyrl	Uzbek
rof	Rombo	uz-Latn	Uzbek
ru	Russian ^{ul}	uz	Uzbek
rw	Kinyarwanda	vai-Latn	Vai
rwk	Rwa	vai-Vaii	Vai
sa-Beng	Sanskrit	vai	Vai
sa-Deva	Sanskrit	vi	Vietnamese ^{ul}
sa-Gujr	Sanskrit	vun	Vunjo
sa-Knda	Sanskrit	wae	Walser
sa-Mlym	Sanskrit	xog	Soga
sa-Telu	Sanskrit	yav	Yangben
sa	Sanskrit	yi	Yiddish
sah	Sakha	yo	Yoruba
saq	Samburu	yue	Cantonese
sbp	Sangu	zgh	Standard Moroccan Tamazight
se	Northern Sami ^{ul}		
seh	Sena	zh-Hans-HK	Chinese
ses	Koyraboro Senni	zh-Hans-MO	Chinese
sg	Sango	zh-Hans-SG	Chinese
shi-Latn	Tachelhit	zh-Hans	Chinese
shi-Tfng	Tachelhit	zh-Hant-HK	Chinese
shi	Tachelhit	zh-Hant-MO	Chinese
si	Sinhala	zh-Hant	Chinese
sk	Slovak ^{ul}	zh	Chinese
sl	Slovenian ^{ul}	zu	Zulu

In some contexts (currently `\babel font`) an ini file may be loaded by its name. Here is the list of the names currently supported. With these languages, `\babel font` loads (if not done before) the language and script names (even if the language is defined as a package option

with an ldf file). These are also the names recognized by \babelprovide with a valueless import.

aghem	chinese-hans-mo
akan	chinese-hans-sg
albanian	chinese-hans
american	chinese-hant-hk
amharic	chinese-hant-mo
ancientgreek	chinese-hant
arabic	chinese-simplified-hongkongsarchina
arabic-algeria	chinese-simplified-macausarchina
arabic-DZ	chinese-simplified-singapore
arabic-morocco	chinese-simplified
arabic-MA	chinese-traditional-hongkongsarchina
arabic-syria	chinese-traditional-macausarchina
arabic-SY	chinese-traditional
armenian	chinese
assamese	churchslavic
asturian	churchslavic-cyrs
asu	churchslavic-oldcyrillic ¹²
australian	churchsslavic-glag
austrian	churchsslavic-glagolitic
azerbaijani-cyrillic	cognian
azerbaijani-cyrl	cornish
azerbaijani-latin	croatian
azerbaijani-latn	czech
azerbaijani	danish
bafia	duala
bambara	dutch
basaa	dzongkha
basque	embu
belarusian	english-au
bemba	english-australia
bena	english-ca
bengali	english-canada
bodo	english-gb
bosnian-cyrillic	english-newzealand
bosnian-cyrl	english-nz
bosnian-latin	english-unitedkingdom
bosnian-latn	english-unitedstates
bosnian	english-us
brazilian	english
breton	esperanto
british	estonian
bulgarian	ewe
burmese	ewondo
canadian	faroeese
cantonese	filipino
catalan	finnish
centralatlastamazight	french-be
centralkurdish	french-belgium
chechen	french-ca
cherokee	french-canada
chiga	french-ch
chinese-hans-hk	french-lu

¹²The name in the CLDR is Old Church Slavonic Cyrillic, but it has been shortened for practical reasons.

french-luxembourg	lowersorbian
french-switzerland	lsorbian
french	lubakatanga
friulian	luo
fulah	luxembourgish
galician	luyia
ganda	macedonian
georgian	machame
german-at	makhuwameetto
german-austria	makonde
german-ch	malagasy
german-switzerland	malay-bn
german	malay-brunei
greek	malay-sg
gujarati	malay-singapore
gusii	malay
hausa-gh	malayalam
hausa-ghana	maltese
hausa-ne	manx
hausa-niger	marathi
hausa	masai
hawaiian	mazanderani
hebrew	meru
hindi	meta
hungarian	mexican
icelandic	mongolian
igbo	morisyen
inarisami	mundang
indonesian	nama
interlingua	nepali
irish	newzealand
italian	ngiemboon
japanese	ngomba
jolafonyi	norsk
kabuverdianu	northernluri
kabyle	northernsami
kako	northndebele
kalaallisut	norwegianbokmal
kalenjin	norwegiannynorsk
kamba	nswissgerman
kannada	nuer
kashmiri	nyankole
kazakh	nynorsk
khmer	occitan
kikuyu	oriya
kinyarwanda	oromo
konkani	ossetic
korean	pashto
koyraborosenni	persian
koyrachiini	piedmontese
kwasio	polish
kyrgyz	polytonicgreek
lakota	portuguese-br
langi	portuguese-brazil
lao	portuguese-portugal
latvian	portuguese-pt
lingala	portuguese
lithuanian	punjabi-arab

punjabi-arabic	soga
punjabi-gurmukhi	somali
punjabi-guru	spanish-mexico
punjabi	spanish-mx
quechua	spanish
romanian	standardmoroccantamazight
romansh	swahili
rombo	swedish
rundi	swissgerman
russian	tachelhit-latin
rwa	tachelhit-latn
sakha	tachelhit-tfng
samburu	tachelhit-tifinagh
samin	tachelhit
sango	taita
sangu	tamil
sanskrit-beng	tasawaq
sanskrit-bengali	telugu
sanskrit-deva	teso
sanskrit-devanagari	thai
sanskrit-gujarati	tibetan
sanskrit-gujr	tigrinya
sanskrit-kannada	tongan
sanskrit-knda	turkish
sanskrit-malayalam	turkmen
sanskrit-mlym	ukenglish
sanskrit-telu	ukrainian
sanskrit-telugu	uppersorbian
sanskrit	urdu
scottishgaelic	usenglish
sena	usorbian
serbian-cyrillic-bosniaherzegovina	uyghur
serbian-cyrillic-kosovo	uzbek-arab
serbian-cyrillic-montenegro	uzbek-arabic
serbian-cyrillic	uzbek-cyrillic
serbian-cyrl-ba	uzbek-cyrl
serbian-cyrl-me	uzbek-latin
serbian-cyrl-xk	uzbek-latn
serbian-cyrl	uzbek
serbian-latin-bosniaherzegovina	vai-latin
serbian-latin-kosovo	vai-latn
serbian-latin-montenegro	vai-vai
serbian-latin	vai-vaii
serbian-latn-ba	vai
serbian-latn-me	vietnam
serbian-latn-xk	vietnamese
serbian-latn	vunjo
serbian	walser
shambala	welsh
shona	westernfrisian
sichuanyi	yangben
sinhala	yiddish
slovak	yoruba
slovene	zarma
slovenian	zulu afrikaans

Modifying and adding values to ini files

New 3.39 There is a way to modify the values of ini files when they get loaded with

`\babelprovide` and `import`. To set, say, `digits.native` in the `numbers` section, use something like `numbers/digits.native=abcdefghijkl`. Keys may be added, too. Without `import` you may modify the identification keys. This can be used to create private variants easily. All you need is to import the same ini file with a different locale name and different parameters.

1.14 Selecting fonts

New 3.15 Babel provides a high level interface on top of `fontspec` to select fonts. There is no need to load `fontspec` explicitly – babel does it for you with the first `\babelfont`.¹³

`\babelfont` `[<language-list>]{<font-family>}[<font-options>]{<font-name>}`

NOTE See the note in the previous section about some issues in specific languages.

The main purpose of `\babelfont` is to define at once in a multilingual document the fonts required by the different languages, with their corresponding language systems (script and language). So, if you load, say, 4 languages, `\babelfont{rm}{FreeSerif}` defines 4 fonts (with their variants, of course), which are switched with the language by babel. It is a tool to make things easier and transparent to the user.

Here *font-family* is `rm`, `sf` or `tt` (or newly defined ones, as explained below), and *font-name* is the same as in `fontspec` and the like.

If no language is given, then it is considered the default font for the family, activated when a language is selected.

On the other hand, if there is one or more languages in the optional argument, the font will be assigned to them, overriding the default one. Alternatively, you may set a font for a script – just precede its name (lowercase) with a star (eg, `*devanagari`). With this optional argument, the font is *not* yet defined, but just predeclared. This means you may define as many fonts as you want ‘just in case’, because if the language is never selected, the corresponding `\babelfont` declaration is just ignored.

Babel takes care of the font language and the font script when languages are selected (as well as the writing direction); see the recognized languages above. In most cases, you will not need *font-options*, which is the same as in `fontspec`, but you may add further key/value pairs if necessary.

EXAMPLE Usage in most cases is very simple. Let us assume you are setting up a document in Swedish, with some words in Hebrew, with a font suited for both languages.

LUATEX/XETEX

```
\documentclass{article}

\usepackage[swedish, bidi=default]{babel}

\babelprovide[import]{hebrew}

\babelfont{rm}{FreeSerif}

\begin{document}

Svenska \foreignlanguage{hebrew}{עִבְרִית} svenska.

\end{document}
```

If on the other hand you have to resort to different fonts, you can replace the red line above with, say:

LUATEX/XETEX

```
\babelfont{rm}{Iwona}
\babelfont[hebrew]{rm}{FreeSerif}
```

¹³See also the package `combofont` for a complementary approach.

`\babelfont` can be used to implicitly define a new font family. Just write its name instead of `rm`, `sf` or `tt`. This is the preferred way to select fonts in addition to the three basic families.

EXAMPLE Here is how to do it:

LUATEX/XETEX

```
\babelfont{kai}{FandolKai}
```

Now, `\kaifamily` and `\kaidefault`, as well as `\textkai` are at your disposal.

NOTE You may load `fontspec` explicitly. For example:

LUATEX/XETEX

```
\usepackage{fontspec}
\newfontscript{Devanagari}{deva}
\babelfont[hindi]{rm}{Shobhika}
```

This makes sure the OpenType script for Devanagari is `deva` and not `dev2`, in case it is not detected correctly. You may also pass some options to `fontspec`: with `silent`, the warnings about unavailable scripts or languages are not shown (they are only really useful when the document format is being set up).

NOTE Directionality is a property affecting margins, indentation, column order, etc., not just text. Therefore, it is under the direct control of the language, which applies both the script and the direction to the text. As a consequence, there is no need to set `Script` when declaring a font with `\babelfont` (nor `Language`). In fact, it is even discouraged.

NOTE `\fontspec` is not touched at all, only the preset font families (`rm`, `sf`, `tt`, and the like). If a language is switched when an *ad hoc* font is active, or you select the font with this command, neither the script nor the language is passed. You must add them by hand. This is by design, for several reasons—for example, each font has its own set of features and a generic setting for several of them can be problematic, and also preserving a “lower-level” font selection is useful.

NOTE The keys `Language` and `Script` just pass these values to the *font*, and do *not* set the script for the *language* (and therefore the writing direction). In other words, the `ini` file or `\babelprovide` provides default values for `\babelfont` if omitted, but the opposite is not true. See the note above for the reasons of this behavior.

WARNING Using `\setxxxxfont` and `\babelfont` at the same time is discouraged, but very often works as expected. However, be aware with `\setxxxxfont` the language system will not be set by `babel` and should be set with `fontspec` if necessary.

TROUBLESHOOTING *Package fontspec Warning: ‘Language ‘LANG’ not available for font ‘FONT’ with script ‘SCRIPT’ ‘Default’ language used instead’.*

This is *not* an error. This warning is shown by `fontspec`, not by `babel`. It can be irrelevant for English, but not for many other languages, including Urdu and Turkish. This is a useful and harmless warning, and if everything is fine with your document the best thing you can do is just to ignore it altogether.

TROUBLESHOOTING *Package babel Info: The following fonts are not babel standard families.*

This is *not* an error. `babel` assumes that if you are using `\babelfont` for a family, very likely you want to define the rest of them. If you don’t, you can find some inconsistencies between families. This checking is done at the beginning of the document, at a point where we cannot know which families will be used.

Actually, there is no real need to use `\babelfont` in a monolingual document, if you set the language system in `\setmainfont` (or not, depending on what you want).

As the message explains, *there is nothing intrinsically wrong* with not defining all the families. In fact, there is nothing intrinsically wrong with not using `\babelfont` at all. But you must be aware that this may lead to some problems.

NOTE `\babelfont` is a high level interface to `fontspec`, and therefore in `xetex` you can apply Mappings. For example, there is a set of [transliterations for Brahmic scripts](#) by Davis M. Jones. After installing them in you distribution, just set the map as you would do with `fontspec`.

1.15 Modifying a language

Modifying the behavior of a language (say, the chapter “caption”), is sometimes necessary, but not always trivial. In the case of caption names a specific macro is provided, because this is perhaps the most frequent change:

`\setlocalecaption` $\{\langle language-name \rangle\}\{\langle caption-name \rangle\}\{\langle string \rangle\}$

New 3.51 Here *caption-name* is the name as string without the trailing name. An example, which also shows caption names are often a stylistic choice, is:

```
\setlocalecaption{english}{contents}{Table of Contents}
```

This works not only with existing caption names, because it also serves to define new ones by setting the *caption-name* to the name of your choice (name will be postpended). Captions so defined or redefined behave with the ‘new way’ described in the following note.

NOTE There are a few alternative methods:

- With data import’ed from ini files, you can modify the values of specific keys, like:

```
\babelprovide[import, captions/listtable = Lista de tablas]{spanish}
```

(In this particular case, instead of the captions group you may need to modify the `captions.licr` one.)

- The ‘old way’, still valid for many languages, to redefine a caption is the following:

```
\addto\captionenglish{%  
  \renewcommand\contentsname{Foo}%  
}
```

As of 3.15, there is no need to hide spaces with % (babel removes them), but it is advisable to do so. This redefinition is not activated until the language is selected.

- The ‘new way’, which is found in bulgarian, azerbaijani, spanish, french, turkish, icelandic, vietnamese and a few more, as well as in languages created with `\babelprovide` and its key `import`, is:

```
\renewcommand\spanishchaptername{Foo}
```

This redefinition is immediate.

NOTE Do *not* redefine a caption in the following way:

```
\AtBeginDocument{\renewcommand\contentsname{Foo}}
```

The changes may be discarded with a language selector, and the original value restored.

Macros to be run when a language is selected can be add to `\extras<lang>`:

```
\addto\extrarussian{\mymacro}
```

There is a counterpart for code to be run when a language is unselected: `\noextras<lang>`.

NOTE These macros (`\captions<lang>`, `\extras<lang>`) may be redefined, but *must not* be used as such – they just pass information to babel, which executes them in the proper context.

Another way to modify a language loaded as a package or class option is by means of `\babelprovide`, described below in depth. So, something like:

```
\usepackage[danish]{babel}
\babelprovide[captions=da, hyphenrules=nohyphenation]{danish}
```

first loads `danish.ldf`, and then redefines the captions for danish (as provided by the `ini` file) and prevents hyphenation. The rest of the language definitions are not touched. Without the optional argument it just loads some additional tools if provided by the `ini` file, like extra counters.

1.16 Creating a language

New 3.10 And what if there is no style for your language or none fits your needs? You may then define quickly a language with the help of the following macro in the preamble (which may be used to modify an existing language, too, as explained in the previous subsection).

\babelprovide [*<options>*]{*<language-name>*}

If the language *<language-name>* has not been loaded as class or package option and there are no *<options>*, it creates an “empty” one with some defaults in its internal structure: the hyphen rules, if not available, are set to the current ones, left and right hyphen mins are set to 2 and 3. In either case, caption, date and language system are not defined. If no `ini` file is imported with `import`, *<language-name>* is still relevant because in such a case the hyphenation and like breaking rules (including those for South East Asian and CJK) are based on it as provided in the `ini` file corresponding to that name; the same applies to OpenType language and script. Conveniently, some options allow to fill the language, and babel warns you about what to do if there is a missing string. Very likely you will find alerts like that in the log file:

```
Package babel Warning: \chaptername not set for 'mylang'. Please,
(babel)                define it after the language has been loaded
(babel)                (typically in the preamble) with:
(babel)                \setlocalecaption{mylang}{chapter}{..}
(babel)                Reported on input line 26.
```

In most cases, you will only need to define a few macros. Note languages loaded on the fly are not yet available in the preamble.

EXAMPLE If you need a language named `arhinish`:

```
\usepackage[danish]{babel}
\babelprovide{arhinish}
\setlocalecaption{arhinish}{chapter}{Chapitula}
\setlocalecaption{arhinish}{refname}{Refirenke}
\renewcommand\arhinishhyphenmins{22}
```

EXAMPLE Locales with names based on BCP 47 codes can be created with something like:

```
\babelprovide[import=en-US]{enUS}
```

Note, however, mixing ways to identify locales can lead to problems. For example, is `yi` the name of the language spoken by the Yi people or is it the code for Yiddish?

The main language is not changed (danish in this example). So, you must add `\selectlanguage{arhinish}` or other selectors where necessary. If the language has been loaded as an argument in `\documentclass` or `\usepackage`, then `\babelprovide` redefines the requested data.

import= *<language-tag>*

New 3.13 Imports data from an ini file, including captions and date (also line breaking rules in newly defined languages). For example:

```
\babelprovide[import=hu]{hungarian}
```

Unicode engines load the UTF-8 variants, while 8-bit engines load the LICR (ie, with macros like `\'` or `\ss`) ones.

New 3.23 It may be used without a value. In such a case, the ini file set in the corresponding `babel-<language>.tex` (where `<language>` is the last argument in `\babelprovide`) is imported. See the list of recognized languages above. So, the previous example can be written:

```
\babelprovide[import]{hungarian}
```

There are about 250 ini files, with data taken from the ldf files and the CLDR provided by Unicode. Not all languages in the latter are complete, and therefore neither are the ini files. A few languages may show a warning about the current lack of suitability of some features.

Besides `\today`, this option defines an additional command for dates: `\<language>date`, which takes three arguments, namely, year, month and day numbers. In fact, `\today` calls `\<language>today`, which in turn calls

`\<language>date{\the\year}{\the\month}{\the\day}`. **New 3.44** More convenient is usually `\localedate`, which prints the date for the current locale.

captions= *<language-tag>*

Loads only the strings. For example:

```
\babelprovide[captions=hu]{hungarian}
```

hyphenrules= *<language-list>*

With this option, with a space-separated list of hyphenation rules, babel assigns to the language the first valid hyphenation rules in the list. For example:

```
\babelprovide[hyphenrules=chavacano spanish italian]{chavacano}
```

If none of the listed hyphenrules exist, the default behavior applies. Note in this example we set `chavacano` as first option – without it, it would select `spanish` even if `chavacano` exists.

A special value is `+`, which allocates a new language (in the \TeX sense). It only makes sense as the last value (or the only one; the subsequent ones are silently ignored). It is mostly useful with `luatex`, because you can add some patterns with `\babelpatterns`, as for example:

```
\babelprovide[hyphenrules=+]{neo}  
\babelpatterns[neo]{a1 e1 i1 o1 u1}
```

In other engines it just suppresses hyphenation (because the pattern list is empty).

New 3.58 Another special value is `unhyphenated`, which activates a line breking mode that allows spaces to be stretched to arbitrary amounts.

main This valueless option makes the language the main one (thus overriding that set when babel is loaded). Only in newly defined languages.

EXAMPLE Let's assume your document (xetex or luatex) is mainly in Polytonic Greek with but with some sections in Italian. Then, the first attempt should be:

```
\usepackage[italian, greek.polutonic]{babel}
```

But if, say, accents in Greek are not shown correctly, you can try

```
\usepackage[italian, polytonicgreek, provide=*]{babel}
```

Remember there is an alternative syntax for the latter:

```
\usepackage[italian]{babel}  
\babelprovide[import, main]{polytonicgreek}
```

Finally, also remember you might not need to load `italian` at all if there are only a few word in this language (see 1.3).

script= $\langle script-name \rangle$

New 3.15 Sets the script name to be used by fontspec (eg, Devanagari). Overrides the value in the ini file. If fontspec does not define it, then babel sets its tag to that provided by the ini file. This value is particularly important because it sets the writing direction, so you must use it if for some reason the default value is wrong.

language= $\langle language-name \rangle$

New 3.15 Sets the language name to be used by fontspec (eg, Hindi). Overrides the value in the ini file. If fontspec does not define it, then babel sets its tag to that provided by the ini file. Not so important, but sometimes still relevant.

alph= $\langle counter-name \rangle$

Assigns to `\alph` that counter. See the next section.

Alph= $\langle counter-name \rangle$

Same for `\Alph`.

A few options (only luatex) set some properties of the writing system used by the language. These properties are *always* applied to the script, no matter which language is active. Although somewhat inconsistent, this makes setting a language up easier in most typical cases.

onchar= ids | fonts

New 3.38 This option is much like an ‘event’ called when a character belonging to the script of this locale is found (as its name implies, it acts on characters, not on spaces). There are currently two ‘actions’, which can be used at the same time (separated by a space): with `ids` the `\language` and the `\localeid` are set to the values of this locale; with `fonts`, the fonts are changed to those of this locale (as set with `\babelfont`). This option is not compatible with `mapfont`. Characters can be added or modified with `\babelcharproperty`.

NOTE An alternative approach with luatex and Harfbuzz is the font option `RawFeature={multiscript=auto}`. It does not switch the babel language and therefore the line breaking rules, but in many cases it can be enough.

intraspace= $\langle base \rangle \langle shrink \rangle \langle stretch \rangle$

Sets the interword space for the writing system of the language, in em units (so, 0 .1 0 is 0em plus .1em). Like `\spaceskip`, the em unit applied is that of the current text (more precisely, the previous glyph). Currently used only in Southeast Asian scripts, like Thai, and CJK.

intrapenalty= $\langle penalty \rangle$

Sets the interword penalty for the writing system of this language. Currently used only in Southeast Asian scripts, like Thai. Ignored if 0 (which is the default value).

transforms= $\langle transform-list \rangle$

See section 1.21.

justification= kashida | elongated | unhyphenated

New 3.59 There are currently three options, mainly for the Arabic script. It sets the linebreaking and justification method, which can be based on the the ARABIC TATWEEL character or in the ‘justification alternatives’ OpenType table (jalt). For an explanation see the [babel site](#).

linebreaking= **New 3.59** Just a synonymous for justification.

mapfont= direction

Assigns the font for the writing direction of this language (only with `bidi=basic`). Whenever possible, instead of this option use `onchar`, based on the script, which usually makes more sense. More precisely, what `mapfont=direction` means is, ‘when a character has the same direction as the script for the “provided” language, then change its font to that set for this language’. There are 3 directions, following the bidi Unicode algorithm, namely, Arabic-like, Hebrew-like and left to right. So, there should be at most 3 directives of this kind.

NOTE (1) If you need shorthands, you can define them with `\usesshorthands` and `\defineshorthand` as described above. (2) Captions and `\today` are “ensured” with `\babelensure` (this is the default in ini-based languages).

1.17 Digits and counters

New 3.20 About thirty ini files define a field named `digits.native`. When it is present, two macros are created: `\<language>digits` and `\<language>counter` (only xetex and luatex). With the first, a string of ‘Latin’ digits are converted to the native digits of that language; the second takes a counter name as argument. With the option `maparabic` in `\babelprovide`, `\arabic` is redefined to produce the native digits (this is done *globally*, to avoid inconsistencies in, for example, page numbering, and note as well dates do not rely on `\arabic`.)

For example:

```
\babelprovide[import]{telugu}
% Or also, if you want:
% \babelprovide[import, maparabic]{telugu}
\babelfont{rm}{Gautami} % With luatex, better with Harfbuzz
\begin{document}
\telugudigits{1234}
\telugucounter{section}
\end{document}
```

Languages providing native digits in all or some variants are:

Arabic	Persian	Lao	Odia	Urdu
Assamese	Gujarati	Northern Luri	Punjabi	Uzbek
Bangla	Hindi	Malayalam	Pashto	Vai
Tibetar	Khmer	Marathi	Tamil	Cantonese
Bodo	Kannada	Burmese	Telugu	Chinese
Central Kurdish	Konkani	Mazanderani	Thai	
Dzongkha	Kashmiri	Nepali	Uyghur	

New 3.30 With `luatex` there is an alternative approach for mapping digits, namely, `mapdigits`. Conversion is based on the language and it is applied to the typeset text (not math, PDF bookmarks, etc.) before bidi and fonts are processed (ie, to the node list as generated by the \TeX code). This means the local digits have the correct bidirectional behavior (unlike `Numbers=Arabic` in `fontspec`, which is not recommended).

NOTE With `xetex` you can use the option `Mapping` when defining a font.

`\localenumeral` $\{\langle style \rangle\}\{\langle number \rangle\}$
`\localecounter` $\{\langle style \rangle\}\{\langle counter \rangle\}$

New 3.41 Many ‘ini’ locale files has been extended with information about non-positional numerical systems, based on those predefined in CSS. They only work with `xetex` and `luatex` and are fully expendable (even inside an unprotected `\edef`). Currently, they are limited to numbers below 10000. There are several ways to use them (for the available styles in each language, see the list below):

- `\localenumeral{\langle style \rangle}\{\langle number \rangle\}`, like `\localenumeral{abjad}{15}`
- `\localecounter{\langle style \rangle}\{\langle counter \rangle\}`, like `\localecounter{lower}{section}`
- In `\babelprovide`, as an argument to the keys `alph` and `Alph`, which redefine what `\alph` and `\Alph` print. For example:

```
\babelprovide[alph=alphabetic]{thai}
```

The styles are:

Ancient Greek `lower.ancient`, `upper.ancient`
Amharic `afar`, `agaw`, `ari`, `blin`, `dizi`, `gedeo`, `gumuz`, `hadiyya`, `harari`, `kaffa`, `kebena`, `kembata`, `konso`, `kunama`, `meen`, `oromo`, `saho`, `sidama`, `silti`, `tigre`, `wolaita`, `yemsa`
Arabic `abjad`, `maghrebi.abjad`
Armenian `lower.letter`, `upper.letter`
Belarusan, Bulgarian, Church Slavic, Macedonian, Serbian `lower`, `upper`
Bengali `alphabetic`
Central Kurdish `alphabetic`
Chinese `cjk-earthly-branch`, `cjk-heavenly-stem`, `circled.ideograph`, `parenthesized.ideograph`, `fullwidth.lower.alpha`, `fullwidth.upper.alpha`
Church Slavic (Glagolitic) `letters`
Coptic `epact`, `lower.letters`
French `date.day` (mainly for internal use).
Georgian `letters`
Greek `lower.modern`, `upper.modern`, `lower.ancient`, `upper.ancient` (all with `keraia`)
Hebrew `letters` (neither `geresh` nor `gershayim yet`)
Hindi `alphabetic`
Italian `lower.legal`, `upper.legal`
Japanese `hiragana`, `hiragana.iroha`, `katakana`, `katakana.iroha`, `circled.katakana`, `informal`, `formal`, `cjk-earthly-branch`, `cjk-heavenly-stem`, `circled.ideograph`, `parenthesized.ideograph`, `fullwidth.lower.alpha`, `fullwidth.upper.alpha`

Khmer consonant
Korean consonant, syllable, hanja.informal, hanja.formal, hangul.formal,
 cjk-earthly-branch, cjk-heavenly-stem, circled.ideograph,
 parenthesized.ideograph, fullwidth.lower.alpha, fullwidth.upper.alpha
Marathi alphabetic
Persian abjad, alphabetic
Russian lower, lower.full, upper, upper.full
Syriac letters
Tamil ancient
Thai alphabetic
Ukrainian lower, lower.full, upper, upper.full

New 3.45 In addition, native digits (in languages defining them) may be printed with the numeral style digits.

1.18 Dates

New 3.45 When the data is taken from an ini file, you may print the date corresponding to the Gregorian calendar and other lunisolar systems with the following command.

\localedate [*<calendar=.., variant=..>*]{*<year>*}{*<month>*}{*<day>*}

By default the calendar is the Gregorian, but an ini file may define strings for other calendars (currently ar, ar-*, he, fa, hi). In the latter case, the three arguments are the year, the month, and the day in those in the corresponding calendar. They are *not* the Gregorian data to be converted (which means, say, 13 is a valid month number with calendar=hebrew and calendar=coptic).

Even with a certain calendar there may be variants. In Kurmanji the default variant prints something like 30. *Çileyä Pêşîn 2019*, but with variant=izafa it prints 31'ê *Çileyä Pêşînê 2019*.

\babelcalendar [*<date>*]{*<calendar>*}{*<year-macro>*}{*<month-macro>*}{*<day-macro>*}

New 3.76 Although calendars aren't the primary concern of babel, the package should be able to, at least, generate correctly the current date in the way users would expect in their own culture. Currently, \localedate can print dates in a few calendars (provided the ini locale file has been imported), but year, month and day had to be entered by hand, which is very inconvenient. With this macro, the current date is converted and stored in the three last arguments, which must be macros. The optional argument converts the given date, in the form '*<year>*-'*<month>*-'*<day>*'. Please, refer to the page on the news for 3.76 in the babel site for further details.

1.19 Accessing language info

\language The control sequence \language contains the name of the current language.

WARNING Due to some internal inconsistencies in catcodes, it should *not* be used to test its value. Use iflang, by Heiko Oberdiek.

\iflanguage {*<language>*}{*<true>*}{*<false>*}

If more than one language is used, it might be necessary to know which language is active at a specific time. This can be checked by a call to \iflanguage, but note here “language” is used in the T_EX sense, as a set of hyphenation patterns, and *not* as its babel name. This macro takes three arguments. The first argument is the name of a language; the second and third arguments are the actions to take if the result of the test is true or false respectively.

\localeinfo `*{⟨field⟩}`

New 3.38 If an ini file has been loaded for the current language, you may access the information stored in it. This macro is fully expandable, and the available fields are:

`name.english` as provided by the Unicode CLDR.

`tag.ini` is the tag of the ini file (the way this file is identified in its name).

`tag.bcp47` is the full BCP 47 tag (see the warning below). This is the value to be used for the ‘real’ provided tag (babel may fill other fields if they are considered necessary).

`language.tag.bcp47` is the BCP 47 language tag.

`tag.opentype` is the tag used by OpenType (usually, but not always, the same as BCP 47).

`script.name`, as provided by the Unicode CLDR.

`script.tag.bcp47` is the BCP 47 tag of the script used by this locale. This is a required field for the fonts to be correctly set up, and therefore it should be always defined.

`script.tag.opentype` is the tag used by OpenType (usually, but not always, the same as BCP 47).

`region.tag.bcp47` is the BCP 47 tag of the region or territory. Defined only if the locale loaded actually contains it (eg, `es-MX` does, but `es` doesn’t), which is how locales behave in the CLDR. **New 3.75**

`variant.tag.bcp47` is the BCP 47 tag of the variant (in the BCP 47 sense, like 1901 for German). **New 3.75**

`extension.⟨s⟩.tag.bcp47` is the BCP 47 value of the extension whose singleton is `⟨s⟩` (currently the recognized singletons are `x`, `t` and `u`). The internal syntax can be somewhat complex, and this feature is still somewhat tentative. An example is `classicalatin` which sets `extension.x.tag.bcp47` to `classic`. **New 3.75**

WARNING **New 3.46** As of version 3.46 `tag.bcp47` returns the full BCP 47 tag. Formerly it returned just the language subtag, which was clearly counterintuitive.

New 3.75 Sometimes, it comes in handy to be able to use `\localeinfo` in an expandable way even if something went wrong (for example, the locale currently active is undefined). For these cases, `localeinfo*` just returns an empty string instead of raising an error. Bear in mind that babel, following the CLDR, may leave the region unset, which means `\getlanguageproperty*`, described below, is the preferred command, so that the existence of a field can be checked before. This also means building a string with the language and the region with `\localeinfo*{language.tab.bcp47}` - `\localeinfo*{region.tab.bcp47}` is not usually a good idea (because of the hyphen).

\getlocaleproperty `*{⟨macro⟩}{⟨locale⟩}{⟨property⟩}`

New 3.42 The value of any locale property as set by the ini files (or added/modified with `\babelprovide`) can be retrieved and stored in a macro with this command. For example, after:

```
\getlocaleproperty\hechap{hebrew}{captions/chapter}
```

the macro `\hechap` will contain the string פרק.

If the key does not exist, the macro is set to `\relax` and an error is raised. **New 3.47** With the starred version no error is raised, so that you can take your own actions with undefined properties.

\localeid Each language in the babel sense has its own unique numeric identifier, which can be retrieved with `\localeid`.

The `\localeid` is not the same as the `\language` identifier, which refers to a set of hyphenation patterns (which, in turn, is just a component of the line breaking algorithm described in the next section). The data about preloaded patterns are stored in an internal macro named `\bbl@languages` (see the code for further details), but note several locales may share a single `\language`, so they are separated concepts. In `luatex`, the `\localeid` is saved in each node (when it makes sense) as an attribute, too.

`\LocaleForEach` `{\code}`

Babel remembers which ini files have been loaded. There is a loop named `\LocaleForEach` to traverse the list, where `#1` is the name of the current item, so that `\LocaleForEach{\message{ **#1** }}` just shows the loaded ini's.

`ensureinfo=off`

New 3.75 Previously, ini files are loaded only with `\babelprovide` and also when languages are selected if there is a `\babelfont` or they have not been explicitly declared. Now the ini files are loaded (and therefore the corresponding data) even if these two conditions are not met (in previous versions you had to enable it with `\BabelEnsureInfo` in the preamble). Because of the way this feature works, problems are very unlikely, but there is switch as a package option to turn the new behavior off (`ensureinfo=off`).

1.20 Hyphenation and line breaking

Babel deals with three kinds of line breaking rules: Western, typically the LGC group, South East Asian, like Thai, and CJK, but support depends on the engine: pdfTeX only deals with the former, xetex also with the second one (although in a limited way), while luatex provides basic rules for the latter, too. With luatex there are also tools for non-standard hyphenation rules, explained in the next section.

`\babelhyphen` `*{\type}`

`\babelhyphen` `*{\text}`

New 3.9a It is customary to classify hyphens in two types: (1) *explicit* or *hard hyphens*, which in T_EX are entered as `-`, and (2) *optional* or *soft hyphens*, which are entered as `\-`. Strictly, a *soft hyphen* is not a hyphen, but just a breaking opportunity or, in T_EX terms, a “discretionary”; a *hard hyphen* is a hyphen with a breaking opportunity after it. A further type is a *non-breaking hyphen*, a hyphen without a breaking opportunity. In T_EX, `-` and `\-` forbid further breaking opportunities in the word. This is the desired behavior very often, but not always, and therefore many languages provide shorthands for these cases. Unfortunately, this has not been done consistently: for example, `-` in Dutch, Portuguese, Catalan or Danish is a hard hyphen, while in German, Spanish, Norwegian, Slovak or Russian is a soft hyphen. Furthermore, some of them even redefine `\-`, so that you cannot insert a soft hyphen without breaking opportunities in the rest of the word. Therefore, some macros are provided with a set of basic “hyphens” which can be used by themselves, to define a user shorthand, or even in language files.

- `\babelhyphen{soft}` and `\babelhyphen{hard}` are self explanatory.
- `\babelhyphen{repeat}` inserts a hard hyphen which is repeated at the beginning of the next line, as done in languages like Polish, Portuguese and Spanish.
- `\babelhyphen{nobreak}` inserts a hard hyphen without a break after it (even if a space follows).
- `\babelhyphen{empty}` inserts a break opportunity without a hyphen at all.
- `\babelhyphen{\text}` is a hard “hyphen” using `\text` instead. A typical case is `\babelhyphen{/}`.

With all of them, hyphenation in the rest of the word is enabled. If you don't want to enable it, there is a starred counterpart: `\babelhyphen*{soft}` (which in most cases is equivalent to the original `\-`), `\babelhyphen*{hard}`, etc.

Note `hard` is also good for isolated prefixes (eg, *anti-*) and `nobreak` for isolated suffixes (eg, *-ism*), but in both cases `\babelhyphen*{nobreak}` is usually better.

There are also some differences with L^AT_EX: (1) the character used is that set for the current font, while in L^AT_EX it is hardwired to `-` (a typical value); (2) the hyphen to be used in fonts with a negative `\hyphenchar` is `-`, like in L^AT_EX, but it can be changed to another value by redefining `\babelnullhyphen`; (3) a break after the hyphen is forbidden if preceded by a glue >0 pt (at the beginning of a word, provided it is not immediately preceded by, say, a parenthesis).

\babelhyphenation [*<language>* , *<language>* , ...] { *<exceptions>* }

New 3.9a Sets hyphenation exceptions for the languages given or, without the optional argument, for *all* languages (eg, proper nouns or common loan words, and of course monolingual documents). Multiple declarations work much like `\hyphenation` (last wins), but language exceptions take precedence over global ones.

It can be used only in the preamble, and exceptions are set when the language is first selected, thus taking into account changes of `\lccodes`'s done in `\extras<lang>` as well as the language-specific encoding (not set in the preamble by default). Multiple `\babelhyphenation`'s are allowed. For example:

```
\babelhyphenation{Wal-hal-la Dar-bhan-ga}
```

Listed words are saved expanded and therefore it relies on the LICR. Of course, it also works without the LICR if the input and the font encodings are the same, like in Unicode based engines.

NOTE Using `\babelhyphenation` with Southeast Asian scripts is mostly pointless. But with `\babelpatterns` (below) you may fine-tune line breaking (only `luatex`). Even if there are no patterns for the language, you can add at least some typical cases.

NOTE To set hyphenation exceptions in the preamble before any language is explicitly set with a selector, use `\babelhyphenation` instead of `\hyphenation`. In the preamble the hyphenation rules are not always fully set up and an error can be raised.

\begin{hyphenrules} { *<language>* } ... **\end{hyphenrules}**

The environment `hyphenrules` can be used to select *only* the hyphenation rules to be used (it can be used as command, too). This can for instance be used to select 'nohyphenation', provided that in `language.dat` the 'language' nohyphenation is defined by loading `zerohyph.tex`. It deactivates language shorthands, too (but not user shorthands). Except for these simple uses, `hyphenrules` is deprecated and other `language*` (the starred version) is preferred, because the former does not take into account possible changes in encodings of characters like, say, ' done by some languages (eg, `italian`, `french`, `ukraineb`).

\babelpatterns [*<language>* , *<language>* , ...] { *<patterns>* }

New 3.9m *In luatex only*,¹⁴ adds or replaces patterns for the languages given or, without the optional argument, for *all* languages. If a pattern for a certain combination already exists, it gets replaced by the new one.

It can be used only in the preamble, and patterns are added when the language is first selected, thus taking into account changes of `\lccodes`'s done in `\extras<lang>` as well as the language-specific encoding (not set in the preamble by default). Multiple `\babelpatterns`'s are allowed.

Listed patterns are saved expanded and therefore it relies on the LICR. Of course, it also works without the LICR if the input and the font encodings are the same, like in Unicode based engines.

New 3.31 (Only `luatex`.) With `\babelprovide` and imported CJK languages, a simple generic line breaking algorithm (push-out-first) is applied, based on a selection of the Unicode rules (**New 3.32** it is disabled in verbatim mode, or more precisely when the `hyphenrules` are set to `nohyphenation`). It can be activated alternatively by setting explicitly the `intraspace`.

New 3.27 Interword spacing for Thai, Lao and Khemer is activated automatically if a language with one of those scripts are loaded with `\babelprovide`. See the sample on the `babel` repository. With both Unicode engines, spacing is based on the "current" em unit (the size of the previous char in `luatex`, and the font size set by the last `\selectfont` in `xetex`).

¹⁴With `luatex` exceptions and patterns can be modified almost freely. However, this is very likely a task for a separate package and `babel` only provides the most basic tools.

1.21 Transforms

Transforms (only luatex) provide a way to process the text on the typesetting level in several language-dependent ways, like non-standard hyphenation, special line breaking rules, script to script conversion, spacing conventions and so on.¹⁵

It currently embraces `\babelprehyphenation` and `\babelposthyphenation`.

New 3.57 Several ini files predefine some transforms. They are activated with the key transforms in `\babelprovide`, either if the locale is being defined with this macro or the languages has been previously loaded as a class or package option, as the following example illustrates:

```
\usepackage[magyar]{babel}
\babelprovide[transforms = digraphs.hyphen]{magyar}
```

New 3.67 Transforms predefined in the ini locale files can be made attribute-dependent, too. When an attribute between parenthesis is inserted subsequent transforms will be assigned to it (up to the list end or another attribute). For example, and provided an attribute called `\withsigmafinal` has been declared:

```
transforms = transliteration.omega (\withsigmafinal) sigma.final
```

This applies `transliteration.omega` always, but `sigma.final` only when `\withsigmafinal` is set.

Here are the transforms currently predefined. (More to follow in future releases.)

Arabic	<code>transliteration.dad</code>	Applies the transliteration system devised by Yannis Haralambous for dad (simple and T _E X-friendly). Not yet complete, but sufficient for most texts.
Croatian	<code>digraphs.ligatures</code>	Ligatures <i>DŽ, Dž, dž, LJ, Lj, lj, NJ, Nj, nj</i> . It assumes they exist. This is not the recommended way to make these transformations (the best way is with OTF features), but it can get you out of a hurry.
Czech, Polish, Portuguese, Slovak, Spanish	<code>hyphen.repeat</code>	Explicit hyphens behave like <code>\babelhyphen{repeat}</code> .
Czech, Polish, Slovak	<code>oneletter.nobreak</code>	Converts a space after a non-syllabic preposition or conjunction into a non-breaking space.
Finnish	<code>prehyphen.nobreak</code>	Line breaks just after hyphens prepended to words are prevented, like in “pakastekaapit ja -arkut”.
Greek	<code>diaeresis.hyphen</code>	Removes the diaeresis above iota and upsilon if hyphenated just before. It works with the three variants.
Greek	<code>transliteration.omega</code>	Although the provided combinations are not the full set, this transform follows the syntax of Omega: = for the circumflex, v for digamma, and so on. For better compatibility with Levy’s system, ~ (as ‘string’) is an alternative to =. ' is tonos in Monotonic Greek, but oxia in Polytonic and Ancient Greek.

¹⁵They are similar in concept, but not the same, as those in Unicode. The main inspiration for this feature is the Omega transformation processes.

Greek	<code>sigma.final</code>	The transliteration system above does not convert the sigma at the end of a word (on purpose). This transform does it. To prevent the conversion (an abbreviation, for example), write "s.
Hindi, Sanskrit	<code>transliteration.hk</code>	The Harvard-Kyoto system to romanize Devanagari.
Hindi, Sanskrit	<code>punctuation.space</code>	Inserts a space before the following four characters: <code>!?:;</code> .
Hungarian	<code>digraphs.hyphen</code>	Hyphenates the long digraphs <i>ccs</i> , <i>ddz</i> , <i>ggy</i> , <i>lly</i> , <i>nny</i> , <i>ssz</i> , <i>tty</i> and <i>zzs</i> as <i>cs-cs</i> , <i>dz-dz</i> , etc.
Indic scripts	<code>danda.nobreak</code>	Prevents a line break before a danda or double danda if there is a space. For Assamese, Bengali, Gujarati, Hindi, Kannada, Malayalam, Marathi, Oriya, Tamil, Telugu.
Latin	<code>digraphs.ligatures</code>	Replaces the groups <i>ae</i> , <i>AE</i> , <i>oe</i> , <i>OE</i> with <i>æ</i> , <i>Æ</i> , <i>œ</i> , <i>Œ</i> .
Latin	<code>letters.noj</code>	Replaces <i>j</i> , <i>J</i> with <i>i</i> , <i>I</i> .
Latin	<code>letters.uv</code>	Replaces <i>v</i> , <i>U</i> with <i>u</i> , <i>V</i> .
Sanskrit	<code>transliteration.iast</code>	The IAST system to romanize Devanagari. ¹⁶
Serbian	<code>transliteration.gajica</code>	(Note serbian with ini files refers to the Cyrillic script, which is here the target.) The standard system devised by Ljudevit Gaj.
Arabic, Persian	<code>kashida.plain</code>	Experimental. A very simple and basic transform for ‘plain’ Arabic fonts, which attempts to distribute the tatwil as evenly as possible (starting at the end of the line). See the news for version 3.59.

`\babelposthyphenation` [*options*]{*hyphenrules-name*}{*lua-pattern*}{*replacement*}

New 3.37-3.39 With *luatex* it is possible to define non-standard hyphenation rules, like *f-f* → *ff-f*, repeated hyphens, ranked ruled (or more precisely, ‘penalized’ hyphenation points), and so on. A few rules are currently provided (see above), but they can be defined as shown in the following example, where `{1}` is the first captured char (between `()` in the pattern):

```
\babelposthyphenation{german}{([fmtrp]) | {1}}
{
  { no = {1}, pre = {1}{1}- }, % Replace first char with disc
  remove,                     % Remove automatic disc (2nd node)
  {}                          % Keep last char, untouched
}
```

In the replacements, a captured char may be mapped to another, too. For example, if the first capture reads `([îû])`, the replacement could be `{1|îû|íú}`, which maps *î* to *í*, and *û* to *ú*, so that the diaeresis is removed.

This feature is activated with the first `\babelposthyphenation` or `\babelprehyphenation`.

New 3.67 With the optional argument you can associate a user defined transform to an attribute, so that it’s active only when it’s set (currently its attribute value is ignored). With this mechanism transforms can be set or unset even in the middle of paragraphs, and applied to single words. To define, set and unset the attribute, the LaTeX kernel provides the macros `\newattribute`, `\setattribute` and `\unsetattribute`. The following example shows how to use it, provided an attribute named `\latinnoj` has been declared:


```
\babelprehyphenation[attribute=\latinnoj]{latin}{ J }{ string = I }
```

See the [babel site](#) for a more detailed description and some examples. It also describes a few additional replacement types (string, penalty).

Although the main purpose of this command is non-standard hyphenation, it may actually be used for other transformations (after hyphenation is applied, so you must take discretionaries into account).

You are limited to substitutions as done by lua, although a future implementation may alternatively accept lpeg.

\babelprehyphenation [*\options*]{*\locale-name*}{*\lua-pattern*}{*\replacement*}

New 3.44-3-52 It is similar to the latter, but (as its name implies) applied before hyphenation, which is particularly useful in transliterations. There are other differences: (1) the first argument is the locale instead of the name of the hyphenation patterns; (2) in the search patterns = has no special meaning, while | stands for an ordinary space; (3) in the replacement, discretionaries are not accepted.

See the description above for the optional argument.

This feature is activated with the first \babelposthyphenation or \babelprehyphenation.

EXAMPLE You can replace a character (or series of them) by another character (or series of them). Thus, to enter ž as zh and š as sh in a newly created locale for transliterated Russian:

```
\babelprovide[hyphenrules=+]{russian-latin} % Create locale
\babelprehyphenation{russian-latin}{([sz])h} % Create rule
{
  string = {1|sz|šž},
  remove
}
```

EXAMPLE The following rule prevent the word “a” from being at the end of a line:

```
\babelprehyphenation{english}{|a|}
{ }, { }, % Keep first space and a
{ insert, penalty = 10000 }, % Insert penalty
{ } % Keep last space
}
```

NOTE With luatex there is another approach to make text transformations, with the function `fonts.handlers.otf.addfeature`, which adds new features to an OTF font (substitution and positioning). These features can be made language-dependent, and babel by default recognizes this setting if the font has been declared with `\babelfont`. The *transforms* mechanism supplements rather than replaces OTF features.

With xetex, where *transforms* are not available, there is still another approach, with font mappings, mainly meant to perform encoding conversions and transliterations. Mappings, however, are linked to fonts, not to languages.

1.22 Selection based on BCP 47 tags

New 3.43 The recommended way to select languages is that described at the beginning of this document. However, BCP 47 tags are becoming customary, particularly in documents (or parts of documents) generated by external sources, and therefore babel will provide a set of tools to select the locales in different situations, adapted to the particular needs of each case. Currently, babel provides autoloading of locales as described in this section. In these contexts autoloading is particularly important because we may not know on beforehand which languages will be requested.

It must be activated explicitly, because it is primarily meant for special tasks. Mapping from BCP 47 codes to locale names are not hardcoded in babel. Instead the data is taken

from the ini files, which means currently about 250 tags are already recognized. Babel performs a simple lookup in the following way: $\text{fr-Latn-FR} \rightarrow \text{fr-Latn} \rightarrow \text{fr-FR} \rightarrow \text{fr}$. Languages with the same resolved name are considered the same. Case is normalized before, so that $\text{fr-latn-fr} \rightarrow \text{fr-Latn-FR}$. If a tag and a name overlap, the tag takes precedence.

Here is a minimal example:

```
\documentclass{article}

\usepackage[danish]{babel}

\babeladjust{
  autoload.bcp47 = on,
  autoload.bcp47.options = import
}

\begin{document}

Chapter in Danish: \chaptername.

\selectlanguage{de-AT}

\localedate{2020}{1}{30}

\end{document}
```

Currently the locales loaded are based on the ini files and decoupled from the main ldf files. This is by design, to ensure code generated externally produces the same result regardless of the languages requested in the document, but an option to use the ldf instead will be added in a future release, because both options make sense depending on the particular needs of each document (there will be some restrictions, however). The behaviour is adjusted with `\babeladjust` with the following parameters:

`autoload.bcp47` with values on and off.

`autoload.bcp47.options`, which are passed to `\babelprovide`; empty by default, but you may add `import` (features defined in the corresponding `babel-...tex` file might not be available).

`autoload.bcp47.prefix`. Although the public name used in selectors is the tag, the internal name will be different and generated by prepending a prefix, which by default is `bcp47-`. You may change it with this key.

New 3.46 If an ldf file has been loaded, you can enable the corresponding language tags as selector names with:

```
\babeladjust{ bcp47.toname = on }
```

(You can deactivate it with off.) So, if `dutch` is one of the package (or class) options, you can write `\selectlanguage{nl}`. Note the language name does not change (in this example is still `dutch`), but you can get it with `\localeinfo` or `\getlanguageproperty`. It must be turned on explicitly for similar reasons to those explained above.

1.23 Selecting scripts

Currently babel provides no standard interface to select scripts, because they are best selected with either `\fontencoding` (low-level) or a language name (high-level). Even the

Latin script may require different encodings (ie, sets of glyphs) depending on the language, and therefore such a switch would be in a sense incomplete.¹⁷ Some languages sharing the same script define macros to switch it (eg, `\textcyrillic`), but be aware they may also set the language to a certain default. Even the babel core defined `\textlatin`, but it was somewhat buggy because in some cases it messed up encodings and fonts (for example, if the main Latin encoding was LY1), and therefore it has been deprecated.¹⁸

`\ensureascii` $\{\langle text \rangle\}$

New 3.9i This macro makes sure $\langle text \rangle$ is typeset with a LICR-savvy encoding in the ASCII range. It is used to redefine `\TeX` and `\LaTeX` so that they are correctly typeset even with LGR or X2 (the complete list is stored in `\BabelNonASCII`, which by default is LGR, X2, OT2, OT3, OT6, LHE, LWN, LMA, LMC, LMS, LMU, but you can modify it). So, in some sense it fixes the bug described in the previous paragraph.

If non-ASCII encodings are not loaded (or no encoding at all), it is no-op (also `\TeX` and `\LaTeX` are not redefined); otherwise, `\ensureascii` switches to the encoding at the beginning of the document if ASCII-savvy, or else the last ASCII-savvy encoding loaded. For example, if you load LY1, LGR, then it is set to LY1, but if you load LY1, T2A it is set to T2A. The symbol encodings TS1, T3, and TS3 are not taken into account, since they are not used for “ordinary” text (they are stored in `\BabelNonText`, used in some special cases when no Latin encoding is explicitly set).

The foregoing rules (which are applied “at begin document”) cover most of the cases. No assumption is made on characters above 127, which may not follow the LICR conventions – the goal is just to ensure most of the ASCII letters and symbols are the right ones.

1.24 Selecting directions

No macros to select the writing direction are provided, either – writing direction is intrinsic to each script and therefore it is best set by the language (which can be a dummy one). Furthermore, there are in fact two right-to-left modes, depending on the language, which differ in the way ‘weak’ numeric characters are ordered (eg, Arabic %123 vs Hebrew 123%).

WARNING The current code for **text** in luatex should be considered essentially stable, but, of course, it is not bug-free and there can be improvements in the future, because setting bidi text has many subtleties (see for example <https://www.w3.org/TR/html-bidi/>). A basic stable version for other engines must wait. This applies to text; there is a basic support for **graphical** elements, including the picture environment (with `pict2e`) and `pfg/tikz`. Also, indexes and the like are under study, as well as math (there are progresses in the latter, including `amsmath` and `mathtools` too, but for example gathered may fail).

An effort is being made to avoid incompatibilities in the future (this one of the reason currently bidi must be explicitly requested as a package option, with a certain bidi model, and also the layout options described below).

WARNING If characters to be mirrored are shown without changes with luatex, try with the following line:

```
\babeladjust{bidi.mirroring=off}
```

There are some package options controlling bidi writing.

bidi= default | basic | basic-r | bidi-l | bidi-r

¹⁷The so-called Unicode fonts do not improve the situation either. So, a font suited for Vietnamese is not necessarily suited for, say, the romanization of Indic languages, and the fact it contains glyphs for Modern Greek does not mean it includes them for Classic Greek.

¹⁸But still defined for backwards compatibility.

New 3.14 Selects the bidi algorithm to be used. With default the bidi mechanism is just activated (by default it is not), but every change must be marked up. In xetex and pdftex this is the only option.

In luatex, `basic-r` provides a simple and fast method for R text, which handles numbers and unmarked L text within an R context many in typical cases. **New 3.19** Finally, `basic` supports both L and R text, and it is the preferred method (support for `basic-r` is currently limited). (They are named `basic` mainly because they only consider the intrinsic direction of scripts and weak directionality.)

New 3.29 In xetex, `bidi-r` and `bidi-l` resort to the package `bidi` (by Vafa Khalighi). Integration is still somewhat tentative, but it mostly works. For RL documents use the former, and for LR ones use the latter.

There are samples on GitHub, under `/required/babel/samples`. See particularly `lua-bidibasic.tex` and `lua-secenum.tex`.

EXAMPLE The following text comes from the Arabic Wikipedia (article about Arabia). Copy-pasting some text from the Wikipedia is a good way to test this feature. Remember `basic` is available in luatex only.

```
\documentclass{article}

\usepackage[bidi=basic]{babel}

\babelprovide[import, main]{arabic}

\babelfont{rm}{FreeSerif}

\begin{document}

    وقد عرفت شبه جزيرة العرب طيلة العصر الهيليني (الاعريقي) بـ
    Arabia أو Aravia (بالاعريقية Ἀραβία)، استخدم الرومان ثلاث
    بادئات بـ“Arabia” على ثلاث مناطق من شبه الجزيرة العربية، إلا أنها
    حقيقةً كانت أكبر مما تعرف عليه اليوم.

\end{document}
```

EXAMPLE With `bidi=basic` both L and R text can be mixed without explicit markup (the latter will be only necessary in some special cases where the Unicode algorithm fails). It is used much like `bidi=basic-r`, but with R text inside L text you may want to map the font so that the correct features are in force. This is accomplished with an option in `\babelprovide`, as illustrated:

```
\documentclass{book}

\usepackage[english, bidi=basic]{babel}

\babelprovide[onchar=ids fonts]{arabic}

\babelfont{rm}{Crimson}
\babelfont[*arabic]{rm}{FreeSerif}

\begin{document}

    Most Arabic speakers consider the two varieties to be two registers
    of one language, although the two registers can be referred to in
    Arabic as فصحى العصر \textit{fuṣḥā l-‘aṣr} (MSA) and
    فصحى التراث \textit{fuṣḥā t-turāth} (CA).

\end{document}
```

In this example, and thanks to `onchar=ids fonts`, any Arabic letter (because the language is `arabic`) changes its font to that set for this language (here defined via `*arabic`, because `Crimson` does not provide Arabic letters).

NOTE Boxes are “black boxes”. Numbers inside an `\hbox` (for example in a `\ref`) do not know anything about the surrounding chars. So, `\ref{A}-\ref{B}` are not rendered in the visual order A-B, but in the wrong one B-A (because the hyphen does not “see” the digits inside the `\hbox`’es). If you need `\ref` ranges, the best option is to define a dedicated macro like this (to avoid explicit direction changes in the body; here `\textthe` must be defined to select the main language):

```
\newcommand\refrange[2]{\babelsublr{\textthe{\ref{#1}}-\textthe{\ref{#2}}}}
```

In the future a more complete method, reading recursively boxed text, may be added.

layout= sectioning | counters | lists | contents | footnotes | captions | columns | graphics | extras

New 3.16 *To be expanded.* Selects which layout elements are adapted in bidi documents, including some text elements (except with options loading the `bidi` package, which provides its own mechanism to control these elements). You may use several options with a dot-separated list (eg, `layout=counters.contents.sectioning`). This list will be expanded in future releases. Note not all options are required by all engines.

sectioning makes sure the sectioning macros are typeset in the main language, but with the title text in the current language (see below `\BabelPatchSection` for further details).

counters required in all engines (except `luatex` with `bidi=basic`) to reorder section numbers and the like (eg, `\subsection`..`\section`); required in `xetex` and `pdftex` for counters in general, as well as in `luatex` with `bidi=default`; required in `luatex` for numeric footnote marks >9 with `bidi=basic-r` (but *not* with `bidi=basic`); note, however, it can depend on the counter format.

With counters, `\arabic` is not only considered L text always (with `\babelsublr`, see below), but also an “isolated” block which does not interact with the surrounding chars. So, while 1.2 in R text is rendered in that order with `bidi=basic` (as a decimal number), in `\arabic{c1}.\arabic{c2}` the visual order is `c2.c1`. Of course, you may always adjust the order by changing the language, if necessary.¹⁹

lists required in `xetex` and `pdftex`, but only in bidirectional (with both R and L paragraphs) documents in `luatex`.

WARNING As of April 2019 there is a bug with `\parshape` in `luatex` (a `TEX` primitive) which makes lists to be horizontally misplaced if they are inside a `\vbox` (like `minipage`) and the current direction is different from the main one. A workaround is to restore the main language before the box and then set the local one inside.

contents required in `xetex` and `pdftex`; in `luatex` toc entries are R by default if the main language is R.

columns required in `xetex` and `pdftex` to reverse the column order (currently only the standard two-column mode); in `luatex` they are R by default if the main language is R (including `multicol`).

footnotes not required in monolingual documents, but it may be useful in bidirectional documents (with both R and L paragraphs) in all engines; you may use alternatively `\BabelFootnote` described below (what this option does exactly is also explained there).

captions is similar to sectioning, but for `\caption`; not required in monolingual documents with `luatex`, but may be required in `xetex` and `pdftex` in some styles (support for the latter two engines is still experimental) **New 3.18** .

tabular required in `luatex` for R `tabular`, so that the first column is the right one (it has been tested only with simple tables, so expect some readjustments in the future); ignored in `pdftex` or `xetex` (which will not support a similar option in the short term). It patches an internal command, so it might be ignored by some packages and classes (or even raise an error). **New 3.18** .

¹⁹Next on the roadmap are counters and numeral systems in general. Expect some minor readjustments.

graphics modifies the picture environment so that the whole figure is L but the text is R. It *does not* work with the standard `picture`, and *pict2e* is required. It attempts to do the same for `pgf/tikz`. Somewhat experimental. **New 3.32** .

extras is used for miscellaneous readjustments which do not fit into the previous groups. Currently redefines in `luatex` `\underline` and `\LaTeXe` **New 3.19** .

EXAMPLE Typically, in an Arabic document you would need:

```
\usepackage[bidi=basic,
             layout=counters.tabular]{babel}
```

\babelsublr `{\langle lr-text \rangle}`

Digits in `pdftex` must be marked up explicitly (unlike `luatex` with `bidi=basic` or `bidi=basic-r` and, usually, `xetex`). This command is provided to set `{\langle lr-text \rangle}` in L mode if necessary. It's intended for what Unicode calls weak characters, because words are best set with the corresponding language. For this reason, there is no `rl` counterpart. Any `\babelsublr` in *explicit* L mode is ignored. However, with `bidi=basic` and *implicit* L, it first returns to R and then switches to explicit L. To clarify this point, consider, in an R context:

```
RTL A ltr text \thechapter{} and still ltr RTL B
```

There are *three* R blocks and *two* L blocks, and the order is *RTL B and still ltr 1 ltr text RTL A*. This is by design to provide the proper behavior in the most usual cases — but if you need to use `\ref` in an L text inside R, the L text must be marked up explicitly; for example:

```
RTL A \foreignlanguage{english}{ltr text \thechapter{} and still ltr} RTL B
```

\BabelPatchSection `{\langle section-name \rangle}`

Mainly for `bidi` text, but it can be useful in other cases. `\BabelPatchSection` and the corresponding option `layout=sectioning` takes a more logical approach (at least in many cases) because it applies the global language to the section format (including the `\chaptername` in `\chapter`), while the section text is still the current language. The latter is passed to `tocs` and `marks`, too, and with `sectioning` in `layout` they both reset the “global” language to the main one, while the text uses the “local” language. With `layout=sectioning` all the standard sectioning commands are redefined (it also “isolates” the page number in heads, for a proper `bidi` behavior), but with this command you can set them individually if necessary (but note then `tocs` and `marks` are not touched).

\BabelFootnote `{\langle cmd \rangle}{\langle local-language \rangle}{\langle before \rangle}{\langle after \rangle}`

New 3.17 Something like:

```
\BabelFootnote{\parsfootnote}{\language}\{(\{)\}
```

defines `\parsfootnote` so that `\parsfootnote{note}` is equivalent to:

```
\footnote{(\foreignlanguage{\language}{note})}
```

but the footnote itself is typeset in the main language (to unify its direction). In addition, `\parsfootnotetext` is defined. The option `footnotes` just does the following:

```

\BabelFootnote{\footnote}{\language}\language}%
\BabelFootnote{\localfootnote}{\language}\language}%
\BabelFootnote{\mainfootnote}{\language}\language}%

```

(which also redefine `\footnotetext` and define `\localfootnotetext` and `\mainfootnotetext`). If the language argument is empty, then no language is selected inside the argument of the footnote. Note this command is available always in bidi documents, even without `layout=footnotes`.

EXAMPLE If you want to preserve directionality in footnotes and there are many footnotes entirely in English, you can define:

```

\BabelFootnote{\enfootnote}{english}\language\language}%

```

It adds a period outside the English part, so that it is placed at the left in the last line. This means the dot the end of the footnote text should be omitted.

1.25 Language attributes

`\languageattribute`

This is a user-level command, to be used in the preamble of a document (after `\usepackage[...]{babel}`), that declares which attributes are to be used for a given language. It takes two arguments: the first is the name of the language; the second, a (list of) attribute(s) to be used. Attributes must be set in the preamble and only once – they cannot be turned on and off. The command checks whether the language is known in this document and whether the attribute(s) are known for this language.

Very often, using a *modifier* in a package option is better.

Several language definition files use their own methods to set options. For example, french uses `\frenchsetup`, magyar (1.5) uses `\magyarOptions`; modifiers provided by spanish have no attribute counterparts. Macros setting options are also used (eg, `\ProsodicMarksOn` in latin).

1.26 Hooks

New 3.9a A hook is a piece of code to be executed at certain events. Some hooks are predefined when `luatex` and `xetex` are used.

New 3.64 This is not the only way to inject code at those points. The events listed below can be used as a hook name in `\AddToHook` in the form `babel/⟨language-name⟩/⟨event-name⟩` (with `*` it's applied to all languages), but there is a limitation, because the parameters passed with the babel mechanism are not allowed. The `\AddToHook` mechanism does *not* replace the current one in 'babel'. Its main advantage is you can reconfigure 'babel' even before loading it. See the example below.

`\AddBabelHook` `[⟨lang⟩]{⟨name⟩}{⟨event⟩}{⟨code⟩}`

The same name can be applied to several events. Hooks with a certain `⟨name⟩` may be enabled and disabled for all defined events with `\EnableBabelHook{⟨name⟩}`, `\DisableBabelHook{⟨name⟩}`. Names containing the string `babel` are reserved (they are used, for example, by `\usesshortands*` to add a hook for the event `afterextras`).

New 3.33 They may be also applied to a specific language with the optional argument; language-specific settings are executed after global ones.

Current events are the following; in some of them you can use one to three \TeX parameters (`#1`, `#2`, `#3`), with the meaning given:

adddialect (language name, dialect name) Used by `luababel.def` to load the patterns if not preloaded.

patterns (language name, language with encoding) Executed just after the `\language` has been set. The second argument has the patterns name actually selected (in the form of either `lang:ENC` or `lang`).

hyphenation (language name, language with encoding) Executed locally just before exceptions given in `\babelhyphenation` are actually set.

defaultcommands Used (locally) in `\StartBabelCommands`.

encodedcommands (input, font encodings) Used (locally) in `\StartBabelCommands`. Both `xetex` and `luatex` make sure the encoded text is read correctly.

stopcommands Used to reset the above, if necessary.

write This event comes just after the switching commands are written to the aux file.

beforeextras Just before executing `\extras<language>`. This event and the next one should not contain language-dependent code (for that, add it to `\extras<language>`).

afterextras Just after executing `\extras<language>`. For example, the following deactivates shorthands in all languages:

```
\AddBabelHook{noshort}{afterextras}{\languageshorthands{none}}
```

stringprocess Instead of a parameter, you can manipulate the macro `\BabelString` containing the string to be defined with `\SetString`. For example, to use an expanded version of the string in the definition, write:

```
\AddBabelHook{myhook}{stringprocess}{%
\protected@edef\BabelString{\BabelString}}
```

initiateactive (char as active, char as other, original char) **New 3.9i** Executed just after a shorthand has been ‘initiated’. The three parameters are the same character with different catcodes: active, other (`\string’ed`) and the original one.

afterreset **New 3.9i** Executed when selecting a language just after `\originalTeX` is run and reset to its base value, before executing `\captions<language>` and `\date<language>`.

Four events are used in `hyphen.cfg`, which are handled in a quite different way for efficiency reasons – unlike the precedent ones, they only have a single hook and replace a default definition.

everylanguage (language) Executed before every language patterns are loaded.

loadkernel (file) By default just defines a few basic commands. It can be used to define different versions of them or to load a file.

loadpatterns (patterns file) Loads the patterns file. Used by `luababel.def`.

loadexceptions (exceptions file) Loads the exceptions file. Used by `luababel.def`.

EXAMPLE The generic unlocalized \TeX hooks are predefined, so that you can write:

```
\AddToHook{babel/*/afterextras}{\frenchspacing}
```

which is executed always after the extras for the language being selected (and just before the non-localized hooks defined with `\AddBabelHook`).

In addition, locale-specific hooks in the form `babel/<language-name>/<event-name>` are *recognized* (executed just before the localized babel hooks), but they are *not predefined*. You have to do it yourself. For example, to set `\frenchspacing` only in bengali:

```
\ActivateGenericHook{babel/bengali/afterextras}
\AddToHook{babel/bengali/afterextras}{\frenchspacing}
```


`\BabelContentsFiles` **New 3.9a** This macro contains a list of “toc” types requiring a command to switch the language. Its default value is `toc`, `lof`, `lot`, but you may redefine it with `\renewcommand` (it’s up to you to make sure no toc type is duplicated).

1.27 Languages supported by babel with ldf files

In the following table most of the languages supported by babel with and .ldf file are listed, together with the names of the option which you can load babel with for each language. Note this list is open and the current options may be different. It does not include ini files.

Afrikaans afrikaans
Azerbaijani azerbaijani
Basque basque
Breton breton
Bulgarian bulgarian
Catalan catalan
Croatian croatian
Czech czech
Danish danish
Dutch dutch
English english, USenglish, american, UKenglish, british, canadian, australian, newzealand
Esperanto esperanto
Estonian estonian
Finnish finnish
French french, francais, canadien, acadian
Galician galician
German austrian, german, germanb, ngerman, naustrian
Greek greek, polutonikogreek
Hebrew hebrew
Icelandic icelandic
Indonesian indonesian (bahasa, indon, bahasai)
Interlingua interlingua
Irish Gaelic irish
Italian italian
Latin latin
Lower Sorbian lowersorbian
Malay malay, melayu (bahasam)
North Sami samin
Norwegian norsk, nynorsk
Polish polish
Portuguese portuguese, brazilian (portuges, brazil)²⁰
Romanian romanian
Russian russian
Scottish Gaelic scottish
Spanish spanish
Slovakian slovak
Slovenian slovene
Swedish swedish
Serbian serbian
Turkish turkish
Ukrainian ukrainian
Upper Sorbian uppersorbian
Welsh welsh

There are more languages not listed above, including hindi, thai, thaicjk, latvian, turkmen, magyar, mongolian, romansh, lithuanian, spanglish, vietnamese, japanese, pinyin, arabic, farsi, ibygreek, bgreek, serbianc, frenchle, ethiopian and friulan.

²⁰The two last name comes from the times when they had to be shortened to 8 characters

Most of them work out of the box, but some may require extra fonts, encoding files, a preprocessor or even a complete framework (like CJK or luatexja). For example, if you have got the velthuis/devnag package, you can create a file with extension .dn:

```
\documentclass{article}
\usepackage[hindi]{babel}
\begin{document}
{\dn devaanaa.m priya.h}
\end{document}
```

Then you preprocess it with devnag $\langle file \rangle$, which creates $\langle file \rangle$.tex; you can then typeset the latter with \LaTeX .

1.28 Unicode character properties in luatex

New 3.32 Part of the babel job is to apply Unicode rules to some script-specific features based on some properties. Currently, they are 3, namely, direction (ie, bidi class), mirroring glyphs, and line breaking for CJK scripts. These properties are stored in lua tables, which you can modify with the following macro (for example, to set them for glyphs in the PUA).

$\backslash\text{babelcharproperty}$ $\{\langle char-code \rangle\}[\langle to-char-code \rangle]\{\langle property \rangle\}\{\langle value \rangle\}$

New 3.32 Here, $\{\langle char-code \rangle\}$ is a number (with \TeX syntax). With the optional argument, you can set a range of values. There are three properties (with a short name, taken from Unicode): direction (bc), mirror (bmg), linebreak (lb). The settings are global, and this command is allowed only in vertical mode (the preamble or between paragraphs). For example:

```
\babelcharproperty{\z}{mirror}{`?}
\babelcharproperty{\-}{direction}{l} % or al, r, en, an, on, et, cs
\babelcharproperty{\`}{linebreak}{cl} % or id, op, cl, ns, ex, in, hy
```

New 3.39 Another property is locale, which adds characters to the list used by onchar in $\backslash\text{babelprovide}$, or, if the last argument is empty, removes them. The last argument is the locale name:

```
\babelcharproperty{`,`}{locale}{english}
```

1.29 Tweaking some features

$\backslash\text{babeladjust}$ $\{\langle key-value-list \rangle\}$

New 3.36 Sometimes you might need to disable some babel features. Currently this macro understands the following keys (and only for luatex), with values on or off: bidi.text, bidi.mirroring, bidi.mapdigits, layout.lists, layout.tabular, linebreak.sea, linebreak.cjk, justify.arabic. For example, you can set $\backslash\text{babeladjust}\{\text{bidi.text}=\text{off}\}$ if you are using an alternative algorithm or with large sections not requiring it. Use with care, because these options do not deactivate other related options (like paragraph direction with bidi.text).

1.30 Tips, workarounds, known issues and notes

- If you use the document class book *and* you use $\backslash\text{ref}$ inside the argument of $\backslash\text{chapter}$ (or just use $\backslash\text{ref}$ inside $\backslash\text{MakeUppercase}$), \LaTeX will keep complaining about an undefined label. To prevent such problems, you can revert to using uppercase labels, you can use $\backslash\text{lowercase}\{\backslash\text{ref}\{\text{foo}\}\}$ inside the argument of $\backslash\text{chapter}$, or, if you will not use shorthands in labels, set the safe option to none or bib.

- Both `ltxdoc` and `babel` use `\AtBeginDocument` to change some catcodes, and `babel` reloads `hline` to make sure `:` has the right one, so if you want to change the catcode of `|` it has to be done using the same method at the proper place, with

```
\AtBeginDocument{\DeleteShortVerb{\|}}
```

before loading `babel`. This way, when the document begins the sequence is (1) make `|` active (`ltxdoc`); (2) make it unactive (your settings); (3) make `babel` shorthands active (`babel`); (4) reload `hline` (`babel`, now with the correct catcodes for `|` and `:`).

- Documents with several input encodings are not frequent, but sometimes are useful. You can set different encodings for different languages as the following example shows:

```
\addto\extrasfrench{\inputencoding{latin1}}
\addto\extrarussian{\inputencoding{koi8-r}}
```

- For the hyphenation to work correctly, `lccodes` cannot change, because \TeX only takes into account the values when the paragraph is hyphenated, i.e., when it has been finished.²¹ So, if you write a chunk of French text with `\foreignlanguage`, the apostrophes might not be taken into account. This is a limitation of \TeX , not of `babel`. Alternatively, you may use `\usesshorthands` to activate `'` and `\defineshorthand`, or redefine `\textquoteright` (the latter is called by the non-ASCII right quote).
- `\bibitem` is out of sync with `\selectlanguage` in the `.aux` file. The reason is `\bibitem` uses `\immediate` (and others, in fact), while `\selectlanguage` doesn't. There is a similar issue with floats, too. There is no known workaround.
- `Babel` does not take into account `\normalsfcodes` and (non-)French spacing is not always properly (un)set by languages. However, problems are unlikely to happen and therefore this part remains untouched in version 3.9 (but it is in the 'to do' list).
- Using a character mathematically active (ie, with math code "8000) as a shorthand can make \TeX enter in an infinite loop in some rare cases. (Another issue in the 'to do' list, although there is a partial solution.)

The following packages can be useful, too (the list is still far from complete):

csquotes Logical markup for quotes.

iflang Tests correctly the current language.

hyphsubst Selects a different set of patterns for a language.

translator An open platform for packages that need to be localized.

siunitx Typesetting of numbers and physical quantities.

biblatex Programmable bibliographies and citations.

bicaption Bilingual captions.

babelbib Multilingual bibliographies.

microtype Adjusts the typesetting according to some languages (kerning and spacing).

Ligatures can be disabled.

substitutefont Combines fonts in several encodings.

mkpattern Generates hyphenation patterns.

tracklang Tracks which languages have been requested.

ucharclasses (xetex) Switches fonts when you switch from one Unicode block to another.

zhspacing Spacing for CJK documents in xetex.

²¹This explains why \LaTeX assumes the lowercase mapping of T1 and does not provide a tool for multiple mappings. Unfortunately, `\savingshyphcodes` is not a solution either, because `lccodes` for hyphenation are frozen in the format and cannot be changed.

1.31 Current and future work

The current work is focused on the so-called complex scripts in luatex. In 8-bit engines, babel provided a basic support for bidi text as part of the style for Hebrew, but it is somewhat unsatisfactory and internally replaces some hardwired commands by other hardwired commands (generic changes would be much better).

Useful additions would be, for example, time, currency, addresses and personal names.²²

But that is the easy part, because they don't require modifying the \LaTeX internals.

Calendars (Arabic, Persian, Indic, etc.) are under study.

Also interesting are differences in the sentence structure or related to it. For example, in Basque the number precedes the name (including chapters), in Hungarian "from (1)" is "(1)-ból", but "from (3)" is "(3)-ból", in Spanish an item labelled "3." may be referred to as either "ítem 3.^o" or "3.^{er} ítem", and so on.

An option to manage bidirectional document layout in luatex (lists, footnotes, etc.) is almost finished, but xetex required more work. Unfortunately, proper support for xetex requires patching somehow lots of macros and packages (and some issues related to `\specials` remain, like color and hyperlinks), so babel resorts to the bidi package (by Vafa Khalighi). See the babel repository for a small example (xe-bidi).

1.32 Tentative and experimental code

See the code section for `\foreignlanguage*` (a new starred version of `\foreignlanguage`). For old an deprecated functions, see the babel site.

Options for locales loaded on the fly

New 3.51 `\babeladjust{ autoload.options = ... }` sets the options when a language is loaded on the fly (by default, no options). A typical value would be `import`, which defines captions, date, numerals, etc., but ignores the code in the tex file (for example, extended numerals in Greek).

Labels

New 3.48 There is some work in progress for babel to deal with labels, both with the relation to captions (chapters, part), and how counters are used to define them. It is still somewhat tentative because it is far from trivial – see the babel site for further details.

2 Loading languages with `language.dat`

\TeX and most engines based on it (pdf \TeX , xetex, $\epsilon\text{-}\TeX$, the main exception being luatex) require hyphenation patterns to be preloaded when a format is created (eg, \LaTeX , Xe \LaTeX , pdf \LaTeX). babel provides a tool which has become standard in many distributions and based on a "configuration file" named `language.dat`. The exact way this file is used depends on the distribution, so please, read the documentation for the latter (note also some distributions generate the file with some tool).

New 3.9q With luatex, however, patterns are loaded on the fly when requested by the language (except the "0th" language, typically english, which is preloaded always).²³ Until 3.9n, this task was delegated to the package `luatex-hyphen`, by Khaled Hosny, Élie Roux, and Manuel Pégourié-Gonnard, and required an extra file named `language.dat.lua`, but now a new mechanism has been devised based solely on `language.dat`. **You must rebuild the formats** if upgrading from a previous version. You may want to have a local `language.dat` for a particular project (for example, a book on Chemistry).²⁴

²²See for example POSIX, ISO 14652 and the Unicode Common Locale Data Repository (CLDR). Those systems, however, have limited application to \TeX because their aim is just to display information and not fine typesetting.

²³This feature was added to 3.9o, but it was buggy. Both 3.9o and 3.9p are deprecated.

²⁴The loader for lua(e)tex is slightly different as it's not based on babel but on `etex.src`. Until 3.9p it just didn't work, but thanks to the new code it works by reloading the data in the babel way, i.e., with `language.dat`.

2.1 Format

In that file the person who maintains a T_EX environment has to record for which languages he has hyphenation patterns *and* in which files these are stored²⁵. When hyphenation exceptions are stored in a separate file this can be indicated by naming that file *after* the file with the hyphenation patterns.

The file can contain empty lines and comments, as well as lines which start with an equals (=) sign. Such a line will instruct L^AT_EX that the hyphenation patterns just processed have to be known under an alternative name. Here is an example:

```
% File      : language.dat
% Purpose   : tell iniTeX what files with patterns to load.
english    english.hyphenations
=british

dutch      hyphen.dutch exceptions.dutch % Nederlands
german     hyphen.ger
```

You may also set the font encoding the patterns are intended for by following the language name by a colon and the encoding code.²⁶ For example:

```
german:T1 hyphenT1.ger
german hyphen.ger
```

With the previous settings, if the encoding when the language is selected is T1 then the patterns in hyphenT1.ger are used, but otherwise use those in hyphen.ger (note the encoding can be set in `\extras{lang}`).

A typical error when using babel is the following:

```
No hyphenation patterns were preloaded for
the language '<lang>' into the format.
Please, configure your TeX system to add them and
rebuild the format. Now I will use the patterns
preloaded for english instead}}
```

It simply means you must reconfigure language.dat, either by hand or with the tools provided by your distribution.

3 The interface between the core of babel and the language definition files

The *language definition files* (ldf) must conform to a number of conventions, because these files have to fill in the gaps left by the common code in babel.def, i.e., the definitions of the macros that produce texts. Also the language-switching possibility which has been built into the babel system has its implications.

The following assumptions are made:

- Some of the language-specific definitions might be used by plain T_EX users, so the files have to be coded so that they can be read by both L^AT_EX and plain T_EX. The current format can be checked by looking at the value of the macro `\fmtname`.
- The common part of the babel system redefines a number of macros and environments (defined previously in the document style) to put in the names of macros that replace the previously hard-wired texts. These macros have to be defined in the language definition files.

²⁵This is because different operating systems sometimes use very different file-naming conventions.

²⁶This is not a new feature, but in former versions it didn't work correctly.

- The language definition files must define five macros, used to activate and deactivate the language-specific definitions. These macros are `\langle lang \rangle hyphenmins`, `\captions\langle lang \rangle`, `\date\langle lang \rangle`, `\extras\langle lang \rangle` and `\noextras\langle lang \rangle` (the last two may be left empty); where `\langle lang \rangle` is either the name of the language definition file or the name of the \LaTeX option that is to be used. These macros and their functions are discussed below. You must define all or none for a language (or a dialect); defining, say, `\date\langle lang \rangle` but not `\captions\langle lang \rangle` does not raise an error but can lead to unexpected results.
- When a language definition file is loaded, it can define `\l@\langle lang \rangle` to be a dialect of `\language0` when `\l@\langle lang \rangle` is undefined.
- Language names must be all lowercase. If an unknown language is selected, babel will attempt setting it after lowercasing its name.
- The semantics of modifiers is not defined (on purpose). In most cases, they will just be simple separated options (eg, spanish), but a language might require, say, a set of options organized as a tree with suboptions (in such a case, the recommended separator is `/`).

Some recommendations:

- The preferred shorthand is `"`, which is not used in \LaTeX (quotes are entered as ``` and `'`). Other good choices are characters which are not used in a certain context (eg, `=` in an ancient language). Note however `=`, `<`, `>`, `:` and the like can be dangerous, because they may be used as part of the syntax of some elements (numeric expressions, key/value pairs, etc.).
- Captions should not contain shorthands or encoding-dependent commands (the latter is not always possible, but should be clearly documented). They should be defined using the LICR. You may also use the new tools for encoded strings, described below.
- Avoid adding things to `\noextras\langle lang \rangle` except for `umlauthigh` and friends, `\bbl@deactivate`, `\bbl@(non)frenchspacing`, and language-specific macros. Use always, if possible, `\bbl@save` and `\bbl@savevariable` (except if you still want to have access to the previous value). Do not reset a macro or a setting to a hardcoded value. Never. Instead save its value in `\extras\langle lang \rangle`.
- Do not switch scripts. If you want to make sure a set of glyphs is used, switch either the font encoding (low-level) or the language (high-level, which in turn may switch the font encoding). Usage of things like `\latintext` is deprecated.²⁷
- Please, for “private” internal macros do not use the `\bbl@` prefix. It is used by babel and it can lead to incompatibilities.

There are no special requirements for documenting your language files. Now they are not included in the base babel manual, so provide a standalone document suited for your needs, as well as other files you think can be useful. A PDF and a “readme” are strongly recommended.

3.1 Guidelines for contributed languages

Currently, the easiest way to contribute a new language is by taking one of the 500 or so `ini` templates available on GitHub as a basis. Just make a pull request or download it and then, after filling the fields, send it to me. Feel free to ask for help or to make feature requests.

As to `ldf` files, now language files are “outsourced” and are located in a separate directory (`/macros/latex/contrib/babel-contrib`), so that they are contributed directly to CTAN (please, do not send to me language styles just to upload them to CTAN).

Of course, placing your style files in this directory is not mandatory, but if you want to do it, here are a few guidelines.

²⁷But not removed, for backward compatibility.

- Do not hesitate stating on the file heads you are the author and the maintainer, if you actually are. There is no need to state the babel maintainer(s) as authors if they have not contributed significantly to your language files.
- Fonts are not strictly part of a language, so they are best placed in the corresponding TeX tree. This includes not only tfm, vf, ps1, ot f, mf files and the like, but also fd ones.
- Font and input encodings are usually best placed in the corresponding tree, too, but sometimes they belong more naturally to the babel style. Note you may also need to define a LICR.
- Babel ldf files may just interface a framework, as it happens often with Oriental languages/scripts. This framework is best placed in its own directory.

The following page provides a starting point for ldf files:

<http://www.texnia.com/incubator.html>. See also

<https://latex3.github.io/babel/guides/list-of-locale-templates.html>.

If you need further assistance and technical advice in the development of language styles, I am willing to help you. And of course, you can make any suggestion you like.

3.2 Basic macros

In the core of the babel system, several macros are defined for use in language definition files. Their purpose is to make a new language known. The first two are related to hyphenation patterns.

\addlanguage The macro `\addlanguage` is a non-outer version of the macro `\newlanguage`, defined in plain.tex version 3.x. Here “language” is used in the TeX sense of set of hyphenation patterns.

\adddialect The macro `\adddialect` can be used when two languages can (or must) use the same hyphenation patterns. This can also be useful for languages for which no patterns are preloaded in the format. In such cases the default behavior of the babel system is to define this language as a ‘dialect’ of the language for which the patterns were loaded as `\language0`. Here “language” is used in the TeX sense of set of hyphenation patterns.

\<lang>hyphenmins The macro `\<lang>hyphenmins` is used to store the values of the `\lefthyphenmin` and `\righthyphenmin`. Redefine this macro to set your own values, with two numbers corresponding to these two parameters. For example:

```
\renewcommand\spanishhyphenmins{34}
```

(Assigning `\lefthyphenmin` and `\righthyphenmin` directly in `\extras<lang>` has no effect.)

\providehyphenmins The macro `\providehyphenmins` should be used in the language definition files to set `\lefthyphenmin` and `\righthyphenmin`. This macro will check whether these parameters were provided by the hyphenation file before it takes any action. If these values have been already set, this command is ignored (currently, default pattern files do *not* set them).

\captions<lang> The macro `\captions<lang>` defines the macros that hold the texts to replace the original hard-wired texts.

\date<lang> The macro `\date<lang>` defines `\today`.

\extras<lang> The macro `\extras<lang>` contains all the extra definitions needed for a specific language. This macro, like the following, is a hook – you can add things to it, but it must not be used directly.

\noextras<lang> Because we want to let the user switch between languages, but we do not know what state TeX might be in after the execution of `\extras<lang>`, a macro that brings TeX into a predefined state is needed. It will be no surprise that the name of this macro is `\noextras<lang>`.

\bbl@declare@ttribute This is a command to be used in the language definition files for declaring a language attribute. It takes three arguments: the name of the language, the attribute to be defined, and the code to be executed when the attribute is to be used.

\main@language To postpone the activation of the definitions needed for a language until the beginning of a

document, all language definition files should use `\main@language` instead of `\selectlanguage`. This will just store the name of the language, and the proper language will be activated at the start of the document.

<code>\ProvidesLanguage</code>	The macro <code>\ProvidesLanguage</code> should be used to identify the language definition files. Its syntax is similar to the syntax of the \TeX command <code>\ProvidesPackage</code> .
<code>\LdfInit</code>	The macro <code>\LdfInit</code> performs a couple of standard checks that must be made at the beginning of a language definition file, such as checking the category code of the <code>@</code> -sign, preventing the <code>.ldf</code> file from being processed twice, etc.
<code>\ldf@quit</code>	The macro <code>\ldf@quit</code> does work needed if a <code>.ldf</code> file was processed earlier. This includes resetting the category code of the <code>@</code> -sign, preparing the language to be activated at <code>\begin{document}</code> time, and ending the input stream.
<code>\ldf@finish</code>	The macro <code>\ldf@finish</code> does work needed at the end of each <code>.ldf</code> file. This includes resetting the category code of the <code>@</code> -sign, loading a local configuration file, and preparing the language to be activated at <code>\begin{document}</code> time.
<code>\loadlocalcfg</code>	After processing a language definition file, \TeX can be instructed to load a local configuration file. This file can, for instance, be used to add strings to <code>\captions{<lang>}</code> to support local document classes. The user will be informed that this configuration file has been loaded. This macro is called by <code>\ldf@finish</code> .
<code>\substitutefontfamily</code>	(Deprecated.) This command takes three arguments, a font encoding and two font family names. It creates a font description file for the first font in the given encoding. This <code>.fd</code> file will instruct \TeX to use a font from the second family when a font from the first family in the given encoding seems to be needed.

3.3 Skeleton

Here is the basic structure of an `ldf` file, with a language, a dialect and an attribute. Strings are best defined using the method explained in sec. 3.8 (babel 3.9 and later).

```
\ProvidesLanguage{<language>}
[2016/04/23 v0.0 <Language> support from the babel system]
\LdfInit{<language>}{captions<language>}

\ifx\undefined\l@<language>
  \nopatterns{<Language>}
  \adddialect\l@<language>0
\fi

\adddialect\l@<dialect>\l@<language>

\bbl@declare@ttribute{<language>}{<attrib>}{%
  \expandafter\addto\expandafter\extras<language>
  \expandafter{\extras<attrib><language>}%
  \let\captions<language>\captions<attrib><language>}

\providehyphenmins{<language>}{\tw@\thr@@}

\StartBabelCommands*{<language>}{captions}
\SetString\chaptername{<chapter name>}
% More strings

\StartBabelCommands*{<language>}{date}
\SetString\monthinname{<name of first month>}
% More strings

\StartBabelCommands*{<dialect>}{captions}
\SetString\chaptername{<chapter name>}
% More strings

\StartBabelCommands*{<dialect>}{date}
\SetString\monthinname{<name of first month>}
```



```
% More strings

\EndBabelCommands

\addto\extras<language>{}
\addto\noextras<language>{}
\let\extras<dialect>\extras<language>
\let\noextras<dialect>\noextras<language>

\ldf@finish{<language>}
```

NOTE If for some reason you want to load a package in your style, you should be aware it cannot be done directly in the ldf file, but it can be delayed with `\AtEndOfPackage`. Macros from external packages can be used *inside* definitions in the ldf itself (for example, `\extras<language>`), but if executed directly, the code must be placed inside `\AtEndOfPackage`. A trivial example illustrating these points is:

```
\AtEndOfPackage{%
  \RequirePackage{dingbat}%      Delay package
  \savebox{\myeye}{\eye{}}%      And direct usage
  \newsavebox{\myeye}
  \newcommand\myanchor{\anchor}% But OK inside command
```

3.4 Support for active characters

In quite a number of language definition files, active characters are introduced. To facilitate this, some support macros are provided.

<code>\initiate@active@char</code>	<p>The internal macro <code>\initiate@active@char</code> is used in language definition files to instruct \TeX to give a character the category code ‘active’. When a character has been made active it will remain that way until the end of the document. Its definition may vary.</p>
<code>\bbl@activate</code> <code>\bbl@deactivate</code>	<p>The command <code>\bbl@activate</code> is used to change the way an active character expands. <code>\bbl@activate</code> ‘switches on’ the active behavior of the character. <code>\bbl@deactivate</code> lets the active character expand to its former (mostly) non-active self.</p>
<code>\declare@shorthand</code>	<p>The macro <code>\declare@shorthand</code> is used to define the various shorthands. It takes three arguments: the name for the collection of shorthands this definition belongs to; the character (sequence) that makes up the shorthand, i.e. <code>~</code> or <code>"a</code>; and the code to be executed when the shorthand is encountered. (It does <i>not</i> raise an error if the shorthand character has not been “initiated”.)</p>
<code>\bbl@add@special</code> <code>\bbl@remove@special</code>	<p>The \TeXbook states: “Plain \TeX includes a macro called <code>\dospecials</code> that is essentially a set macro, representing the set of all characters that have a special category code.” [4, p. 380] It is used to set text ‘verbatim’. To make this work if more characters get a special category code, you have to add this character to the macro <code>\dospecial</code>. \TeX adds another macro called <code>\@sanitize</code> representing the same character set, but without the curly braces. The macros <code>\bbl@add@special<char></code> and <code>\bbl@remove@special<char></code> add and remove the character <code><char></code> to these two sets.</p>

3.5 Support for saving macro definitions

Language definition files may want to *redefine* macros that already exist. Therefore a mechanism for saving (and restoring) the original definition of those macros is provided. We provide two macros for this²⁸.

<code>\babel@save</code>	<p>To save the current meaning of any control sequence, the macro <code>\babel@save</code> is provided. It takes one argument, <code><csname></code>, the control sequence for which the meaning has to be saved.</p>
<code>\babel@savevariable</code>	<p>A second macro is provided to save the current value of a variable. In this context,</p>

²⁸This mechanism was introduced by Bernd Raichle.

anything that is allowed after the `\` the primitive is considered to be a variable. The macro takes one argument, the *variable*.

The effect of the preceding macros is to append a piece of code to the current definition of `\originalTeX`. When `\originalTeX` is expanded, this code restores the previous definition of the control sequence or the previous value of the variable.

3.6 Support for extending macros

`\addto` The macro `\addto{<control sequence>}{<TeX code>}` can be used to extend the definition of a macro. The macro need not be defined (ie, it can be undefined or `\relax`). This macro can, for instance, be used in adding instructions to a macro like `\extrasenglish`. Be careful when using this macro, because depending on the case the assignment can be either global (usually) or local (sometimes). That does not seem very consistent, but this behavior is preserved for backward compatibility. If you are using `etoolbox`, by Philipp Lehman, consider using the tools provided by this package instead of `\addto`.

3.7 Macros common to a number of languages

`\bbl@allowhyphens` In several languages compound words are used. This means that when `TeX` has to hyphenate such a compound word, it only does so at the ‘-’ that is used in such words. To allow hyphenation in the rest of such a compound word, the macro `\bbl@allowhyphens` can be used.

`\allowhyphens` Same as `\bbl@allowhyphens`, but does nothing if the encoding is `T1`. It is intended mainly for characters provided as real glyphs by this encoding but constructed with `\accent` in `OT1`.

Note the previous command (`\bbl@allowhyphens`) has different applications (hyphens and discretionaries) than this one (composite chars). Note also prior to version 3.7, `\allowhyphens` had the behavior of `\bbl@allowhyphens`.

`\set@low@box` For some languages, quotes need to be lowered to the baseline. For this purpose the macro `\set@low@box` is available. It takes one argument and puts that argument in an `\hbox`, at the baseline. The result is available in `\box0` for further processing.

`\save@sf@q` Sometimes it is necessary to preserve the `\spacefactor`. For this purpose the macro `\save@sf@q` is available. It takes one argument, saves the current `spacefactor`, executes the argument, and restores the `spacefactor`.

`\bbl@frenchspacing`
`\bbl@nonfrenchspacing` The commands `\bbl@frenchspacing` and `\bbl@nonfrenchspacing` can be used to properly switch French spacing on and off.

3.8 Encoding-dependent strings

New 3.9a Babel 3.9 provides a way of defining strings in several encodings, intended mainly for `luatex` and `xetex`. This is the only new feature requiring changes in language files if you want to make use of it.

Furthermore, it must be activated explicitly, with the package option `strings`. If there is no `strings`, these blocks are ignored, except `\SetCases` (and except if forced as described below). In other words, the old way of defining/switching strings still works and it’s used by default.

It consist is a series of blocks started with `\StartBabelCommands`. The last block is closed with `\EndBabelCommands`. Each block is a single group (ie, local declarations apply until the next `\StartBabelCommands` or `\EndBabelCommands`). An `ldf` may contain several series of this kind.

Thanks to this new feature, string values and string language switching are not mixed any more. No need of `\addto`. If the language is `french`, just redefine `\frenchchaptername`.

`\StartBabelCommands` `{<language-list>}{<category>}[<selector>]`

The *<language-list>* specifies which languages the block is intended for. A block is taken into account only if the `\CurrentOption` is listed here. Alternatively, you can define `\BabelLanguages` to a comma-separated list of languages to be defined (if undefined,

`\StartBabelCommands` sets it to `\CurrentOption`). You may write `\CurrentOption` as the language, but this is discouraged – a explicit name (or names) is much better and clearer. A “selector” is a name to be used as value in package option strings, optionally followed by extra info about the encodings to be used. The name `unicode` must be used for `xetex` and `luatex` (the key `strings` has also other two special values: `generic` and `encoded`). If a string is set several times (because several blocks are read), the first one takes precedence (ie, it works much like `\providecommand`).

Encoding info is `charset=` followed by a charset, which if given sets how the strings should be translated to the internal representation used by the engine, typically `utf8`, which is the only value supported currently (default is no translations). Note `charset` is applied by `luatex` and `xetex` when reading the file, not when the macro or string is used in the document.

A list of font encodings which the strings are expected to work with can be given after `fontenc=` (separated with spaces, if two or more) – recommended, but not mandatory, although blocks without this key are not taken into account if you have requested `strings=encoded`.

Blocks without a selector are read always if the key `strings` has been used. They provide fallback values, and therefore must be the last blocks; they should be provided always if possible and all strings should be defined somehow inside it; they can be the only blocks (mainly LGC scripts using the LICR). Blocks without a selector can be activated explicitly with `strings=generic` (no block is taken into account except those). With `strings=encoded`, strings in those blocks are set as default (internally, `?`). With `strings=encoded` strings are protected, but they are correctly expanded in `\MakeUppercase` and the like. If there is no key `strings`, string definitions are ignored, but `\SetCases` are still honored (in a encoded way).

The `<category>` is either `captions`, `date` or `extras`. You must stick to these three categories, even if no error is raised when using other name.²⁹ It may be empty, too, but in such a case using `\SetString` is an error (but not `\SetCase`).

```
\StartBabelCommands{language}{captions}
  [unicode, fontenc=TU EU1 EU2, charset=utf8]
\SetString{chaptername}{utf8-string}

\StartBabelCommands{language}{captions}
\SetString{chaptername}{ascii-maybe-LICR-string}

\EndBabelCommands
```

A real example is:

```
\StartBabelCommands{austrian}{date}
  [unicode, fontenc=TU EU1 EU2, charset=utf8]
\SetString\monthiname{Jänner}

\StartBabelCommands{german,austrian}{date}
  [unicode, fontenc=TU EU1 EU2, charset=utf8]
\SetString\monthiiname{März}

\StartBabelCommands{austrian}{date}
\SetString\monthiname{J\"a\"nner}

\StartBabelCommands{german}{date}
\SetString\monthiname{Januar}

\StartBabelCommands{german,austrian}{date}
\SetString\monthiiname{Februar}
\SetString\monthiiname{M\"a\"rz}
```

²⁹In future releases further categories may be added.

```

\SetString\monthivname{April}
\SetString\monthvname{Mai}
\SetString\monthviname{Juni}
\SetString\monthviiname{Juli}
\SetString\monthviiiname{August}
\SetString\monthixname{September}
\SetString\monthxname{Oktober}
\SetString\monthxiname{November}
\SetString\monthxiiname{Dezenber}
\SetString\today{\number\day.~%
\csname month\romannumeral\month name\endcsname\space
\number\year}

\StartBabelCommands{german,austrian}{captions}
\SetString\prefacename{Vorwort}
[etc.]

\EndBabelCommands

```

When used in ldf files, previous values of `\langle category \rangle \langle language \rangle` are overridden, which means the old way to define strings still works and used by default (to be precise, is first set to undefined and then strings are added). However, when used in the preamble or in a package, new settings are added to the previous ones, if the language exists (in the babel sense, ie, if `\date \langle language \rangle` exists).

`\StartBabelCommands` `*{\langle language-list \rangle}{\langle category \rangle}[\langle selector \rangle]`

The starred version just forces strings to take a value – if not set as package option, then the default for the engine is used. This is not done by default to prevent backward incompatibilities, but if you are creating a new language this version is better. It's up to the maintainers of the current languages to decide if using it is appropriate.³⁰

`\EndBabelCommands` Marks the end of the series of blocks.

`\AfterBabelCommands` `{\langle code \rangle}`

The code is delayed and executed at the global scope just after `\EndBabelCommands`.

`\SetString` `{\langle macro-name \rangle}{\langle string \rangle}`

Adds `\langle macro-name \rangle` to the current category, and defines globally `\langle lang-macro-name \rangle` to `\langle code \rangle` (after applying the transformation corresponding to the current charset or defined with the hook `stringprocess`).

Use this command to define strings, without including any “logic” if possible, which should be a separated macro. See the example above for the date.

`\SetStringLoop` `{\langle macro-name \rangle}{\langle string-list \rangle}`

A convenient way to define several ordered names at once. For example, to define `\abmoniname`, `\abmoniiname`, etc. (and similarly with `abday`):

```

\SetStringLoop{abmon#1name}{en,fb,mr,ab,my,jn,jl,ag,sp,oc,nv,dc}
\SetStringLoop{abday#1name}{lu,ma,mi,ju,vi,sa,do}

```

#1 is replaced by the roman numeral.

`\SetCase` `[\langle map-list \rangle]{\langle toupper-code \rangle}{\langle tolower-code \rangle}`

³⁰This replaces in 3.9g a short-lived `\UseStrings` which has been removed because it did not work.

Sets globally code to be executed at `\MakeUppercase` and `\MakeLowercase`. The code would typically be things like `\let\BB\bb` and `\uccode` or `\lccode` (although for the reasons explained above, changes in lc/uc codes may not work). A *map-list* is a series of macros using the internal format of `\@uc1clist` (eg, `\bb\BB\cc\CC`). The mandatory arguments take precedence over the optional one. This command, unlike `\SetString`, is executed always (even without strings), and it is intended for minor readjustments only. For example, as T1 is the default case mapping in \TeX , we can set for Turkish:

```
\StartBabelCommands{turkish}{}[ot1enc, fontenc=OT1]
\SetCase
  {\uccode"10=`I\relax}
  {\lccode`I="10\relax}

\StartBabelCommands{turkish}{}[unicode, fontenc=TU EU1 EU2, charset=utf8]
\SetCase
  {\uccode`i=`İ\relax
   \uccode`ı=`I\relax}
  {\lccode`İ=`i\relax
   \lccode`I=`ı\relax}

\StartBabelCommands{turkish}{}
\SetCase
  {\uccode`i="9D\relax
   \uccode"19=`I\relax}
  {\lccode"9D=`i\relax
   \lccode`I="19\relax}

\EndBabelCommands
```

(Note the mapping for OT1 is not complete.)

`\SetHyphenMap` `{\to-lower-macros}`

New 3.9g Case mapping serves in \TeX for two unrelated purposes: case transforms (upper/lower) and hyphenation. `\SetCase` handles the former, while hyphenation is handled by `\SetHyphenMap` and controlled with the package option `hyphenmap`. So, even if internally they are based on the same \TeX primitive (`\lccode`), `babel` sets them separately. There are three helper macros to be used inside `\SetHyphenMap`:

- `\BabelLower{\uccode}{\lccode}` is similar to `\lccode` but it's ignored if the char has been set and saves the original `\lccode` to restore it when switching the language (except with `hyphenmap=first`).
- `\BabelLowerMM{\uccode-from}{\uccode-to}{\step}{\lccode-from}` loops though the given uppercase codes, using the step, and assigns them the `\lccode`, which is also increased (MM stands for *many-to-many*).
- `\BabelLowerMO{\uccode-from}{\uccode-to}{\step}{\lccode}` loops though the given uppercase codes, using the step, and assigns them the `\lccode`, which is fixed (MO stands for *many-to-one*).

An example is (which is redundant, because these assignments are done by both `luatex` and `xetex`):

```
\SetHyphenMap{\BabelLowerMM{"100}{\lccode"11F}{2}{\lccode"101}}
```

This macro is not intended to fix wrong mappings done by Unicode (which are the default in both `xetex` and `luatex`) – if an assignment is wrong, fix it directly.

3.9 Executing code based on the selector

`\IfBabelSelectorTF` $\{\langle selectors \rangle\}\{\langle true \rangle\}\{\langle false \rangle\}$

New 3.67 Sometimes a different setup is desired depending on the selector used. Values allowed in $\langle selectors \rangle$ are `select`, `other`, `foreign`, `other*` (and also `foreign*` for the tentative starred version), and it can consist of a comma-separated list. For example:

```
\IfBabelSelectorTF{other, other*}{A}{B}
```

is true with these two environment selectors.
Its natural place of use is in hooks or in `\extras $\langle language \rangle$` .

Part II

Source code

`babel` is being developed incrementally, which means parts of the code are under development and therefore incomplete. Only documented features are considered complete. In other words, use `babel` only as documented (except, of course, if you want to explore and test them – you can post suggestions about multilingual issues to kadingira@tug.org on <http://tug.org/mailman/listinfo/kadingira>).

4 Identification and loading of required files

Code documentation is still under revision.

The following description is no longer valid, because `switch` and `plain` have been merged into `babel.def`.

The `babel` package after unpacking consists of the following files:

`switch.def` defines macros to set and switch languages.

`babel.def` defines the rest of macros. It has two parts: a generic one and a second one only for LaTeX.

`babel.sty` is the \LaTeX package, which sets options and loads language styles.

`plain.def` defines some \LaTeX macros required by `babel.def` and provides a few tools for Plain.

`hyphen.cfg` is the file to be used when generating the formats to load hyphenation patterns.

The `babel` installer extends `docstrip` with a few “pseudo-guards” to set “variables” used at installation time. They are used with `<@name@>` at the appropriated places in the source code and shown below with $\langle\langle name \rangle\rangle$. That brings a little bit of literate programming.

5 locale directory

A required component of `babel` is a set of `ini` files with basic definitions for about 200 languages. They are distributed as a separate zip file, not packed as `dtx`. With them, `babel` will fully support Unicode engines.

Most of them are essentially finished (except bugs and mistakes, of course). Some of them are still incomplete (but they will be usable), and there are some omissions (eg, Latin and polytonic Greek, and there are no geographic areas in Spanish). Hindi, French, Occitan and Breton will show a warning related to dates. Not all include LICR variants.

This is a preliminary documentation.

`ini` files contain the actual data; `tex` files are currently just proxies to the corresponding `ini` files.

Most keys are self-explanatory.

`charset` the encoding used in the `ini` file.

`version` of the `ini` file

`level` “version” of the `ini` specification . which keys are available (they may grow in a compatible way) and how they should be read.

`encodings` a descriptive list of font encodings.

`[captions]` section of captions in the file `charset`

`[captions.licr]` same, but in pure ASCII using the LICR

date.long fields are as in the CLDR, but the syntax is different. Anything inside brackets is a date field (eg, MMM for the month name) and anything outside is text. In addition, [] is a non breakable space and [.] is an abbreviation dot.

Keys may be further qualified in a particular language with a suffix starting with a uppercase letter. It can be just a letter (eg, babel.name.A, babel.name.B) or a name (eg, date.long.Nominative, date.long.Formal, but no language is currently using the latter). *Multi-letter* qualifiers are forward compatible in the sense they won't conflict with new "global" keys (which start always with a lowercase case). There is an exception, however: the section counters has been devised to have arbitrary keys, so you can add lowercased keys if you want.

6 Tools

```
1 <<version=3.76.2772>>
2 <<date=2022/06/18>>
```

Do not use the following macros in ldf files. They may change in the future. This applies mainly to those recently added for replacing, trimming and looping. The older ones, like \bbl@afterfi, will not change.

We define some basic macros which just make the code cleaner. \bbl@add is now used internally instead of \addto because of the unpredictable behavior of the latter. Used in babel.def and in babel.sty, which means in L^AT_EX is executed twice, but we need them when defining options and babel.def cannot be load until options have been defined. This does not hurt, but should be fixed somehow.

```
3 <<{*Basic macros}>> ≡
4 \bbl@trace{Basic macros}
5 \def\bbl@stripslash{\expandafter\@gobble\string}
6 \def\bbl@add#1#2{%
7   \bbl@ifunset{\bbl@stripslash#1}%
8   {\def#1{#2}}%
9   {\expandafter\def\expandafter#1\expandafter{#1#2}}%
10 \def\bbl@xin@{\@expandtwoargs\in@}
11 \def\bbl@csarg#1#2{\expandafter#1\csname bbl@#2\endcsname}%
12 \def\bbl@cs#1{\csname bbl@#1\endcsname}
13 \def\bbl@c1#1{\csname bbl@#1\language\endcsname}
14 \def\bbl@loop#1#2#3{\bbl@loop#1{#3}#2,\@nnil,}
15 \def\bbl@loopx#1#2{\expandafter\bbl@loop\expandafter#1\expandafter{#2}}
16 \def\bbl@loop#1#2#3,{%
17   \ifx\@nnil#3\relax\else
18     \def#1{#3}#2\bbl@afterfi\bbl@loop#1{#2}%
19   \fi}
20 \def\bbl@for#1#2#3{\bbl@loopx#1{#2}{\ifx#1\@empty\else#3\fi}}
```

\bbl@add@list This internal macro adds its second argument to a comma separated list in its first argument. When the list is not defined yet (or empty), it will be initiated. It presumes expandable character strings.

```
21 \def\bbl@add@list#1#2{%
22   \edef#1{%
23     \bbl@ifunset{\bbl@stripslash#1}%
24     {}%
25     {\ifx#1\@empty\else#1,\fi}%
26     #2}}
```

\bbl@afterelse \bbl@afterfi Because the code that is used in the handling of active characters may need to look ahead, we take extra care to 'throw' it over the \else and \fi parts of an \if-statement³¹. These macros will break if another \if... \fi statement appears in one of the arguments and it is not enclosed in braces.

```
27 \long\def\bbl@afterelse#1\else#2\fi{\fi#1}
28 \long\def\bbl@afterfi#1\fi{\fi#1}
```

\bbl@exp Now, just syntactical sugar, but it makes partial expansion of some code a lot more simple and readable. Here \ stands for \noexpand, \<.> for \noexpand applied to a built macro name (which does not define the macro if undefined to \relax, because it is created locally), and \[...] for

³¹This code is based on code presented in TUGboat vol. 12, no2, June 1991 in "An expansion Power Lemma" by Sonja Maus.

one-level expansion (where . . is the macro name without the backslash). The result may be followed by extra arguments, if necessary.

```

29 \def\bbl@exp#1{%
30   \begingroup
31     \let\@noexpand
32     \let\<\bbl@exp@en
33     \let\[\bbl@exp@ue
34     \edef\bbl@exp@aux{\endgroup#1}%
35   \bbl@exp@aux}
36 \def\bbl@exp@en#1>{\expandafter\@noexpand\csname#1\endcsname}%
37 \def\bbl@exp@ue#1]{%
38   \unexpanded\expandafter\expandafter\expandafter{\csname#1\endcsname}}%

```

\bbl@trim The following piece of code is stolen (with some changes) from keyval, by David Carlisle. It defines two macros: `\bbl@trim` and `\bbl@trim@def`. The first one strips the leading and trailing spaces from the second argument and then applies the first argument (a macro, `\toks@` and the like). The second one, as its name suggests, defines the first argument as the stripped second argument.

```

39 \def\bbl@tempa#1{%
40   \long\def\bbl@trim##1##2{%
41     \futurelet\bbl@trim@a\bbl@trim@c##2\@nil\@nil#1\@nil\relax{##1}}%
42   \def\bbl@trim@c{%
43     \ifx\bbl@trim@a\@sptoken
44       \expandafter\bbl@trim@b
45     \else
46       \expandafter\bbl@trim@b\expandafter#1%
47     \fi}%
48   \long\def\bbl@trim@b#1##1 \@nil{\bbl@trim@i##1}}
49 \bbl@tempa{ }
50 \long\def\bbl@trim@i#1\@nil#2\relax#3{#3{#1}}
51 \long\def\bbl@trim@def#1{\bbl@trim{\def#1}}

```

\bbl@ifunset To check if a macro is defined, we create a new macro, which does the same as `\ifundefined`. However, in an ϵ -tex engine, it is based on `\ifcsname`, which is more efficient, and does not waste memory.

```

52 \begingroup
53   \gdef\bbl@ifunset#1{%
54     \expandafter\ifx\csname#1\endcsname\relax
55       \expandafter\@firstoftwo
56     \else
57       \expandafter\@secondoftwo
58     \fi}
59 \bbl@ifunset{ifcsname}% TODO. A better test?
60 {}%
61 {\gdef\bbl@ifunset#1{%
62   \ifcsname#1\endcsname
63     \expandafter\ifx\csname#1\endcsname\relax
64       \bbl@afterelse\expandafter\@firstoftwo
65     \else
66       \bbl@afterfi\expandafter\@secondoftwo
67     \fi
68   \else
69     \expandafter\@firstoftwo
70   \fi}}
71 \endgroup

```

\bbl@ifblank A tool from url, by Donald Arseneau, which tests if a string is empty or space. The companion macros tests if a macro is defined with some ‘real’ value, ie, not `\relax` and not empty,

```

72 \def\bbl@ifblank#1{%
73   \bbl@ifblank@i#1\@nil\@nil\@secondoftwo\@firstoftwo\@nil}
74 \long\def\bbl@ifblank@i#1#2\@nil#3#4#5\@nil{#4}
75 \def\bbl@ifset#1#2#3{%
76   \bbl@ifunset{#1}{#3}{\bbl@exp{\@bbl@ifblank{#1}}{#3}{#2}}}

```

For each element in the comma separated <key>=<value> list, execute <code> with #1 and #2 as the key and the value of current item (trimmed). In addition, the item is passed verbatim as #3. With the <key> alone, it passes \@empty (ie, the macro thus named, not an empty argument, which is what you get with <key>= and no value).

```

77 \def\bbl@forkv#1#2{%
78   \def\bbl@kvcmd##1##2##3{#2}%
79   \bbl@kvnext#1,\@nil,}
80 \def\bbl@kvnext#1,{%
81   \ifx\@nil#1\relax\else
82     \bbl@ifblank{#1}{\bbl@forkv@eq#1=\@empty=\@nil{#1}}%
83     \expandafter\bbl@kvnext
84   \fi}
85 \def\bbl@forkv@eq#1=#2=#3\@nil#4{%
86   \bbl@trim@def\bbl@forkv@a{#1}%
87   \bbl@trim{\expandafter\bbl@kvcmd\expandafter{\bbl@forkv@a}}{#2}{#4}}

```

A *for* loop. Each item (trimmed), is #1. It cannot be nested (it's doable, but we don't need it).

```

88 \def\bbl@vforeach#1#2{%
89   \def\bbl@forcmd##1{#2}%
90   \bbl@fornext#1,\@nil,}
91 \def\bbl@fornext#1,{%
92   \ifx\@nil#1\relax\else
93     \bbl@ifblank{#1}{\bbl@trim\bbl@forcmd{#1}}%
94     \expandafter\bbl@fornext
95   \fi}
96 \def\bbl@foreach#1{\expandafter\bbl@vforeach\expandafter{#1}}

```

\bbl@replace Returns implicitly \toks@ with the modified string.

```

97 \def\bbl@replace#1#2#3{% in #1 -> repl #2 by #3
98   \toks@{}%
99   \def\bbl@replace@aux##1#2##2#2{%
100     \ifx\bbl@nil##2%
101       \toks@\expandafter{\the\toks@##1}%
102     \else
103       \toks@\expandafter{\the\toks@##1#3}%
104       \bbl@afterfi
105       \bbl@replace@aux##2#2%
106     \fi}%
107   \expandafter\bbl@replace@aux#1#2\bbl@nil#2%
108   \edef#1{\the\toks@}}

```

An extension to the previous macro. It takes into account the parameters, and it is string based (ie, if you replace elax by ho, then \relax becomes \rho). No checking is done at all, because it is not a general purpose macro, and it is used by babel only when it works (an example where it does *not* work is in \bbl@TG@@date, and also fails if there are macros with spaces, because they are retokenized). It may change! (or even merged with \bbl@replace; I'm not sure ckecking the replacement is really necessary or just paranoia).

```

109 \ifx\detokenize\@undefined\else % Unused macros if old Plain TeX
110   \bbl@exp{\def\\bbl@parsedef##1\detokenize{macro:}}#2->#3\relax{%
111     \def\bbl@tempa{#1}%
112     \def\bbl@tempb{#2}%
113     \def\bbl@tempe{#3}}
114   \def\bbl@sreplace#1#2#3{%
115     \begingroup
116     \expandafter\bbl@parsedef\meaning#1\relax
117     \def\bbl@tempc{#2}%
118     \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
119     \def\bbl@tempd{#3}%
120     \edef\bbl@tempd{\expandafter\strip@prefix\meaning\bbl@tempd}%
121     \bbl@xin{\bbl@tempc}{\bbl@tempe}% If not in macro, do nothing
122     \ifin@
123       \bbl@exp{\bbl@replace\\bbl@tempe{\bbl@tempc}{\bbl@tempd}}%
124       \def\bbl@tempc{Expanded an executed below as 'uplevel'}

```



```

125         \\makeatletter % "internal" macros with @ are assumed
126         \\scantokens{%
127             \bbl@tempa\\@namedef{\bbl@stripslash#1}\bbl@tempb{\bbl@tempe}}%
128         \catcode64=\the\catcode64\relax}% Restore @
129     \else
130         \let\bbl@tempc@empty % Not \relax
131     \fi
132     \bbl@exp{% For the 'uplevel' assignments
133 \endgroup
134     \bbl@tempc}} % empty or expand to set #1 with changes
135 \fi

```

Two further tools. `\bbl@ifsamestring` first expand its arguments and then compare their expansion (sanitized, so that the catcodes do not matter). `\bbl@engine` takes the following values: 0 is pdfTeX, 1 is luatex, and 2 is xetex. You may use the latter it in your language style if you want.

```

136 \def\bbl@ifsamestring#1#2{%
137 \begingroup
138 \protected@edef\bbl@tempb{#1}%
139 \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
140 \protected@edef\bbl@tempc{#2}%
141 \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
142 \ifx\bbl@tempb\bbl@tempc
143     \aftergroup\@firstoftwo
144 \else
145     \aftergroup\@secondoftwo
146 \fi
147 \endgroup}
148 \chardef\bbl@engine=%
149 \ifx\directlua\@undefined
150     \ifx\XeTeXinputencoding\@undefined
151         \z@
152     \else
153         \tw@
154     \fi
155 \else
156     \@ne
157 \fi

```

A somewhat hackish tool (hence its name) to avoid spurious spaces in some contexts.

```

158 \def\bbl@bsphack{%
159 \ifhmode
160     \hskip\z@skip
161     \def\bbl@esphack{\loop\ifdim\lastskip>\z@\unskip\repeat\unskip}%
162 \else
163     \let\bbl@esphack\@empty
164 \fi}

```

Another hackish tool, to apply case changes inside a protected macros. It's based on the internal `\let's` made by `\MakeUppercase` and `\MakeLowercase` between things like `\oe` and `\OE`.

```

165 \def\bbl@cased{%
166 \ifx\oe\OE
167     \expandafter\in@\expandafter
168     {\expandafter\OE\expandafter}\expandafter{\oe}%
169 \ifin@
170     \bbl@afterelse\expandafter\MakeUppercase
171 \else
172     \bbl@afterfi\expandafter\MakeLowercase
173 \fi
174 \else
175     \expandafter\@firstofone
176 \fi}

```

An alternative to `\IfFormatAtLeastTF` for old versions. Temporary.

```

177 \ifx\IfFormatAtLeastTF\@undefined
178   \def\bbl@ifformatlater{\@ifl@t@r\fmtversion}
179 \else
180   \let\bbl@ifformatlater\IfFormatAtLeastTF
181 \fi

```

The following adds some code to `\extras...` both before and after, while avoiding doing it twice. It's somewhat convoluted, to deal with `#`'s. Used to deal with `alph`, `Alph` and `frenchspacing` when there are already changes (with `\babel@save`).

```

182 \def\bbl@extras@wrap#1#2#3{% 1:in-test, 2:before, 3:after
183   \toks@{\expandafter\expandafter\expandafter{%
184     \csname extras\language\endcsname}%
185     \bbl@exp{\in@{#1}}{\the\toks@}}%
186   \ifin@else
187     \@temptokena{#2}%
188     \edef\bbl@tempc{\the\@temptokena\the\toks@}%
189     \toks@\expandafter{\bbl@tempc#3}%
190     \expandafter\edef\csname extras\language\endcsname{\the\toks@}%
191   \fi}
192 </Basic macros>

```

Some files identify themselves with a \TeX macro. The following code is placed before them to define (and then undefine) if not in \TeX .

```

193 <<*Make sure ProvidesFile is defined>> ≡
194 \ifx\ProvidesFile\@undefined
195   \def\ProvidesFile#1[#2 #3 #4]{%
196     \wlog{File: #1 #4 #3 <#2>}%
197     \let\ProvidesFile\@undefined}
198 \fi
199 </Make sure ProvidesFile is defined>

```

6.1 Multiple languages

`\language` Plain \TeX version 3.0 provides the primitive `\language` that is used to store the current language. When used with a pre-3.0 version this function has to be implemented by allocating a counter. The following block is used in `switch.def` and `hyphen.cfg`; the latter may seem redundant, but remember `babel` doesn't require loading `switch.def` in the format.

```

200 <<*Define core switching macros>> ≡
201 \ifx\language\@undefined
202   \csname newcount\endcsname\language
203 \fi
204 </Define core switching macros>

```

`\last@language` Another counter is used to keep track of the allocated languages. \TeX and \LaTeX reserves for this purpose the count 19.

`\addlanguage` This macro was introduced for $\TeX < 2$. Preserved for compatibility.

```

205 <<*Define core switching macros>> ≡
206 \countdef\last@language=19
207 \def\addlanguage{\csname newlanguage\endcsname}
208 </Define core switching macros>

```

Now we make sure all required files are loaded. When the command `\AtBeginDocument` doesn't exist we assume that we are dealing with a plain-based format. In that case the file `plain.def` is needed (which also defines `\AtBeginDocument`, and therefore it is not loaded twice). We need the first part when the format is created, and `\orig@dump` is used as a flag. Otherwise, we need to use the second part, so `\orig@dump` is not defined (`plain.def` undefines it).

Check if the current version of `switch.def` has been previously loaded (mainly, `hyphen.cfg`). If not, load it now. We cannot load `babel.def` here because we first need to declare and process the package options.

6.2 The Package File (LaTeX, babel.sty)

```

209 \*package>
210 \NeedsTeXFormat{LaTeX2e}[2005/12/01]
211 \ProvidesPackage{babel}[\langle date \rangle \langle version \rangle The Babel package]

```

Start with some “private” debugging tool, and then define macros for errors.

```

212 \@ifpackagewith{babel}{debug}
213   {\providecommand\bbl@trace[1]{\message{^^J[ #1 ]}}%
214    \let\bbl@debug\@firstofone
215    \ifx\directlua\@undefined\else
216      \directlua{ Babel = Babel or {}
217        Babel.debug = true }%
218      \input{babel-debug.tex}%
219    \fi}
220 {\providecommand\bbl@trace[1]{}%
221  \let\bbl@debug\@gobble
222  \ifx\directlua\@undefined\else
223    \directlua{ Babel = Babel or {}
224      Babel.debug = false }%
225  \fi}
226 \def\bbl@error#1#2{%
227   \begingroup
228     \def\{\MessageBreak}%
229     \PackageError{babel}{#1}{#2}%
230   \endgroup}
231 \def\bbl@warning#1{%
232   \begingroup
233     \def\{\MessageBreak}%
234     \PackageWarning{babel}{#1}%
235   \endgroup}
236 \def\bbl@infowarn#1{%
237   \begingroup
238     \def\{\MessageBreak}%
239     \GenericWarning
240       {(babel) \@spaces\@spaces\@spaces}%
241       {Package babel Info: #1}%
242   \endgroup}
243 \def\bbl@info#1{%
244   \begingroup
245     \def\{\MessageBreak}%
246     \PackageInfo{babel}{#1}%
247   \endgroup}

```

This file also takes care of a number of compatibility issues with other packages and defines a few additional package options. Apart from all the language options below we also have a few options that influence the behavior of language definition files.

Many of the following options don’t do anything themselves, they are just defined in order to make it possible for babel and language definition files to check if one of them was specified by the user.

But first, include here the *Basic macros* defined above.

```

248 \langle Basic macros \rangle
249 \@ifpackagewith{babel}{silent}
250   {\let\bbl@info\@gobble
251    \let\bbl@infowarn\@gobble
252    \let\bbl@warning\@gobble}
253   {}
254 %
255 \def\AfterBabelLanguage#1{%
256   \global\expandafter\bbl@add\csname#1.ldf-h@k\endcsname}%

```

If the format created a list of loaded languages (in \bbl@languages), get the name of the 0-th to show the actual language used. Also available with base, because it just shows info.

```

257 \ifx\bbl@languages\@undefined\else
258   \begingroup
259     \catcode`\^^I=12

```

```

260 \ifpackagewith{babel}{showlanguages}{%
261 \begingroup
262 \def\bbl@elt#1#2#3#4{\wlog{#2^^I#1^^I#3^^I#4}}}%
263 \wlog{<*languages>}%
264 \bbl@languages
265 \wlog{</languages>}%
266 \endgroup}{%
267 \endgroup
268 \def\bbl@elt#1#2#3#4{%
269 \ifnum#2=\z@
270 \gdef\bbl@nulllanguage{#1}%
271 \def\bbl@elt##1##2##3##4{}}%
272 \fi}%
273 \bbl@languages
274 \fi%

```

6.3 base

The first ‘real’ option to be processed is base, which set the hyphenation patterns then resets `ver@babel.sty` so that \TeX forgets about the first loading. After a subset of `babel.def` has been loaded (the old `switch.def`) and `\AfterBabelLanguage` defined, it exits. Now the base option. With it we can define (and load, with `luatex`) hyphenation patterns, even if we are not interested in the rest of `babel`.

```

275 \bbl@trace{Defining option 'base'}
276 \ifpackagewith{babel}{base}{%
277 \let\bbl@onlyswitch\@empty
278 \let\bbl@provide@locale\relax
279 \input babel.def
280 \let\bbl@onlyswitch\@undefined
281 \ifx\directlua\@undefined
282 \DeclareOption*{\bbl@patterns{\CurrentOption}}%
283 \else
284 \input luababel.def
285 \DeclareOption*{\bbl@patterns@lua{\CurrentOption}}%
286 \fi
287 \DeclareOption{base}{}%
288 \DeclareOption{showlanguages}{}%
289 \ProcessOptions
290 \global\expandafter\let\csname opt@babel.sty\endcsname\relax
291 \global\expandafter\let\csname ver@babel.sty\endcsname\relax
292 \global\let\@ifl@ter@\@ifl@ter
293 \def\@ifl@ter#1#2#3#4#5{\global\let\@ifl@ter\@ifl@ter@}%
294 \endinput}{}%

```

6.4 key=value options and other general option

The following macros extract language modifiers, and only real package options are kept in the option list. Modifiers are saved and assigned to `\BabelModifiers` at `\bbl@load@language`; when no modifiers have been given, the former is `\relax`. How modifiers are handled are left to language styles; they can use `\in@`, loop them with `\@for` or `load keyval`, for example.

```

295 \bbl@trace{key=value and another general options}
296 \bbl@csarg\let{tempa\expandafter}\csname opt@babel.sty\endcsname
297 \def\bbl@tempb#1.#2{% Remove trailing dot
298 #1\ifx\@empty#2\else,\bbl@afterfi\bbl@tempb#2\fi}%
299 \def\bbl@tempd#1.#2\@nnil{% TODO. Refactor lists?
300 \ifx\@empty#2%
301 \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
302 \else
303 \in@{,provide=}{, #1}%
304 \ifin@
305 \edef\bbl@tempc{%
306 \ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.\bbl@tempb#2}%
307 \else

```

```

308 \in@{=}{#1}%
309 \ifin@
310 \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.#2}%
311 \else
312 \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
313 \bbl@csarg\edef{mod@#1}{\bbl@tempb#2}%
314 \fi
315 \fi
316 \fi}
317 \let\bbl@tempc\@empty
318 \bbl@foreach\bbl@tempa{\bbl@tempd#1.\@empty\@nnil}
319 \expandafter\let\csname opt@babel.sty\endcsname\bbl@tempc

```

The next option tells babel to leave shorthand characters active at the end of processing the package. This is *not* the default as it can cause problems with other packages, but for those who want to use the shorthand characters in the preamble of their documents this can help.

```

320 \DeclareOption{KeepShorthandsActive}{}
321 \DeclareOption{activeacute}{}
322 \DeclareOption{activegrave}{}
323 \DeclareOption{debug}{}
324 \DeclareOption{noconfigs}{}
325 \DeclareOption{showlanguages}{}
326 \DeclareOption{silent}{}
327 % \DeclareOption{mono}{}
328 \DeclareOption{shorthands=off}{\bbl@tempa shorthands=\bbl@tempa}
329 \chardef\bbl@iniflag\z@
330 \DeclareOption{provide=*}{\chardef\bbl@iniflag\@ne} % main -> +1
331 \DeclareOption{provide+=*}{\chardef\bbl@iniflag\tw@} % add = 2
332 \DeclareOption{provide*=*}{\chardef\bbl@iniflag\thr@@} % add + main
333 % A separate option
334 \let\bbl@autoload@options\@empty
335 \DeclareOption{provide=@*}{\def\bbl@autoload@options{import}}
336 % Don't use. Experimental. TODO.
337 \newif\ifbbl@single
338 \DeclareOption{selectors=off}{\bbl@singletrue}
339 <More package options>

```

Handling of package options is done in three passes. (I [JBL] am not very happy with the idea, anyway.) The first one processes options which has been declared above or follow the syntax <key>=<value>, the second one loads the requested languages, except the main one if set with the key main, and the third one loads the latter. First, we “flag” valid keys with a nil value.

```

340 \let\bbl@opt@shorthands\@nnil
341 \let\bbl@opt@config\@nnil
342 \let\bbl@opt@main\@nnil
343 \let\bbl@opt@headfoot\@nnil
344 \let\bbl@opt@layout\@nnil
345 \let\bbl@opt@provide\@nnil

```

The following tool is defined temporarily to store the values of options.

```

346 \def\bbl@tempa#1=#2\bbl@tempa{%
347 \bbl@csarg\ifx{opt@#1}\@nnil
348 \bbl@csarg\edef{opt@#1}{#2}%
349 \else
350 \bbl@error
351 {Bad option '#1=#2'. Either you have misspelled the\\%
352 key or there is a previous setting of '#1'. Valid\\%
353 keys are, among others, 'shorthands', 'main', 'bidi',\\%
354 'strings', 'config', 'headfoot', 'safe', 'math'.}%
355 {See the manual for further details.}
356 \fi}

```

Now the option list is processed, taking into account only currently declared options (including those declared with a =), and <key>=<value> options (the former take precedence). Unrecognized options are saved in \bbl@language@opts, because they are language options.

```

357 \let\bbbl@language@opts@empty
358 \DeclareOption*{%
359   \bbbl@xin@{\string=}{\CurrentOption}%
360   \ifin@
361     \expandafter\bbbl@tempa\CurrentOption\bbbl@tempa
362   \else
363     \bbbl@add@list\bbbl@language@opts{\CurrentOption}%
364   \fi}

```

Now we finish the first pass (and start over).

```

365 \ProcessOptions*
366 \ifx\bbbl@opt@provide\@nnil
367   \let\bbbl@opt@provide\@empty %%%% MOVE above
368 \else
369   \chardef\bbbl@iniflag\@ne
370   \bbbl@exp{\bbbl@forkv{\@nameuse{\raw@opt@babel.sty}}}{%
371     \in@{,provide,}{, #1,}%
372     \ifin@
373       \def\bbbl@opt@provide{#2}%
374       \bbbl@replace\bbbl@opt@provide{;}{,}%
375     \fi}
376 \fi
377 %

```

6.5 Conditional loading of shorthands

If there is no `shorthands=<chars>`, the original babel macros are left untouched, but if there is, these macros are wrapped (in `babel.def`) to define only those given.

A bit of optimization: if there is no `shorthands=`, then `\bbbl@ifshorthand` is always true, and it is always false if `shorthands` is empty. Also, some code makes sense only with `shorthands=...`

```

378 \bbbl@trace{Conditional loading of shorthands}
379 \def\bbbl@sh@string#1{%
380   \ifx#1\@empty\else
381     \ifx#1t\string~%
382     \else\ifx#1c\string,%
383     \else\string#1%
384   \fi\fi
385   \expandafter\bbbl@sh@string
386 \fi}
387 \ifx\bbbl@opt@shorthands\@nnil
388   \def\bbbl@ifshorthand#1#2#3{#2}%
389 \else\ifx\bbbl@opt@shorthands\@empty
390   \def\bbbl@ifshorthand#1#2#3{#3}%
391 \else

```

The following macro tests if a shorthand is one of the allowed ones.

```

392 \def\bbbl@ifshorthand#1{%
393   \bbbl@xin@{\string#1}{\bbbl@opt@shorthands}%
394   \ifin@
395     \expandafter\@firstoftwo
396   \else
397     \expandafter\@secondoftwo
398   \fi}

```

We make sure all chars in the string are ‘other’, with the help of an auxiliary macro defined above (which also zaps spaces).

```

399 \edef\bbbl@opt@shorthands{%
400   \expandafter\bbbl@sh@string\bbbl@opt@shorthands\@empty}%

```

The following is ignored with `shorthands=off`, since it is intended to take some additional actions for certain chars.

```

401 \bbbl@ifshorthand{'}%
402 {\PassOptionsToPackage{activeacute}{babel}}{}

```

```

403 \bbl@ifshorthand{`}%
404 {\PassOptionsToPackage{activegrave}{babel}}{}
405 \fi\fi

```

With `headfoot=lang` we can set the language used in heads/foots. For example, in `babel/3796` just adds `headfoot=english`. It misuses `\@resetactivechars` but seems to work.

```

406 \ifx\bbl@opt@headfoot\@nnil\else
407 \g@addto@macro\@resetactivechars{%
408 \set@typeset@protect
409 \expandafter\select@language@x\expandafter{\bbl@opt@headfoot}%
410 \let\protect\noexpand}
411 \fi

```

For the option `safe` we use a different approach – `\bbl@opt@safe` says which macros are redefined (B for bibs and R for refs). By default, both are set.

```

412 \ifx\bbl@opt@safe\@undefined
413 \def\bbl@opt@safe{BR}
414 \fi

```

For layout an auxiliary macro is provided, available for packages and language styles. Optimization: if there is no layout, just do nothing.

```

415 \bbl@trace{Defining IfBabelLayout}
416 \ifx\bbl@opt@layout\@nnil
417 \newcommand\IfBabelLayout[3]{#3}%
418 \else
419 \newcommand\IfBabelLayout[1]{%
420 \expandafter\in@{.#1.}{.\bbl@opt@layout.}%
421 \ifin@
422 \expandafter\@firstoftwo
423 \else
424 \expandafter\@secondoftwo
425 \fi}
426 \fi
427 \</package>
428 \<core>

```

6.6 Interlude for Plain

Because of the way `docstrip` works, we need to insert some code for Plain here. However, the tools provided by the `babel` installer for literate programming makes this section a short interlude, because the actual code is below, tagged as *Emulate LaTeX*.

```

429 \ifx\ldf@quit\@undefined\else
430 \endinput\fi % Same line!
431 \<<Make sure ProvidesFile is defined>>
432 \ProvidesFile{babel.def}[\<date>] \<version> Babel common definitions]
433 \ifx\AtBeginDocument\@undefined % TODO. change test.
434 \<<Emulate LaTeX>>
435 \fi

```

That is all for the moment. Now follows some common stuff, for both Plain and \LaTeX . After it, we will resume the \LaTeX -only stuff.

```

436 \</core>
437 \<*package | core>

```

7 Multiple languages

This is not a separate file (`switch.def`) anymore.

Plain \TeX version 3.0 provides the primitive `\language` that is used to store the current language. When used with a pre-3.0 version this function has to be implemented by allocating a counter.

```

438 \def\bbl@version{\<version>}
439 \def\bbl@date{\<date>}
440 \<<Define core switching macros>>

```

`\adddialect` The macro `\adddialect` can be used to add the name of a dialect or variant language, for which an already defined hyphenation table can be used.

```

441 \def\adddialect#1#2{%
442   \global\chardef#1#2\relax
443   \bbl@usehooks{adddialect}{\{#1\}{#2\}}%
444   \begingroup
445     \count@#1\relax
446     \def\bbl@elt##1##2##3##4{%
447       \ifnum\count@=##2\relax
448         \edef\bbl@tempa{\expandafter\@gobbletwo\string#1}%
449         \bbl@info{Hyphen rules for '\expandafter\@gobble\bbl@tempa'
450           set to \expandafter\string\csname l@##1\endcsname\}%
451           (\string\language\the\count@). Reported}%
452       \def\bbl@elt####1####2####3####4{%
453         \fi}%
454       \bbl@cs{languages}%
455     \endgroup

```

`\bbl@iflanguage` executes code only if the language `l@` exists. Otherwise raises an error.

The argument of `\bbl@fixname` has to be a macro name, as it may get “fixed” if casing (lc/uc) is wrong. It’s an attempt to fix a long-standing bug when `\foreignlanguage` and the like appear in a `\MakeXXXcase`. However, a lowercase form is not imposed to improve backward compatibility (perhaps you defined a language named MYLANG, but unfortunately mixed case names cannot be trapped). Note `l@` is encapsulated, so that its case does not change.

```

456 \def\bbl@fixname#1{%
457   \begingroup
458   \def\bbl@tempe{l@}%
459   \edef\bbl@tempd{\noexpand\@ifundefined{\noexpand\bbl@tempe#1}}%
460   \bbl@tempd
461     {\lowercase\expandafter{\bbl@tempd}%
462     {\uppercase\expandafter{\bbl@tempd}%
463     \@empty
464     {\edef\bbl@tempd{\def\noexpand#1{#1}}%
465     \uppercase\expandafter{\bbl@tempd}}}%
466     {\edef\bbl@tempd{\def\noexpand#1{#1}}%
467     \lowercase\expandafter{\bbl@tempd}}}%
468   \@empty
469   \edef\bbl@tempd{\endgroup\def\noexpand#1{#1}}%
470   \bbl@tempd
471   \bbl@exp{\bbl@usehooks{language}{\{#1\}}}
472 \def\bbl@iflanguage#1{%
473   \@ifundefined{l@#1}{\@nolanerr{#1}\@gobble}\@firstofone}

```

After a name has been ‘fixed’, the selectors will try to load the language. If even the fixed name is not defined, will load it on the fly, either based on its name, or if activated, its BCP47 code.

We first need a couple of macros for a simple BCP 47 look up. It also makes sure, with `\bbl@bcpcase`, casing is the correct one, so that `sr-latn-ba` becomes `fr-Latn-BA`. Note #4 may contain some `\@empty`’s, but they are eventually removed. `\bbl@bcpllookup` either returns the found ini or it is `\relax`.

```

474 \def\bbl@bcpcase#1#2#3#4\@#5{%
475   \ifx\@empty#3%
476     \uppercase{\def#5{#1#2}}%
477   \else
478     \uppercase{\def#5{#1}}%
479     \lowercase{\edef#5{#5#2#3#4}}%
480   \fi}
481 \def\bbl@bcpllookup#1-#2-#3-#4\@{%
482   \let\bbl@bcp\relax
483   \lowercase{\def\bbl@tempa{#1}}%
484   \ifx\@empty#2%
485     \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
486   \else\ifx\@empty#3%
487     \bbl@bcpcase#2\@empty\@empty\@{\bbl@tempb}
488     \IfFileExists{babel-\bbl@tempa-\bbl@tempb.ini}%

```



```

489 \edef\bbl@bcp{\bbl@tempa-\bbl@tempb}}%
490 {}%
491 \ifx\bbl@bcp\relax
492 \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
493 \fi
494 \else
495 \bbl@bcpcase#2\@empty\@empty\@{\bbl@tempb
496 \bbl@bcpcase#3\@empty\@empty\@{\bbl@tempc
497 \IfFileExists{babel-\bbl@tempa-\bbl@tempb-\bbl@tempc.ini}%
498 {\edef\bbl@bcp{\bbl@tempa-\bbl@tempb-\bbl@tempc}}%
499 {}%
500 \ifx\bbl@bcp\relax
501 \IfFileExists{babel-\bbl@tempa-\bbl@tempc.ini}%
502 {\edef\bbl@bcp{\bbl@tempa-\bbl@tempc}}%
503 {}%
504 \fi
505 \ifx\bbl@bcp\relax
506 \IfFileExists{babel-\bbl@tempa-\bbl@tempc.ini}%
507 {\edef\bbl@bcp{\bbl@tempa-\bbl@tempc}}%
508 {}%
509 \fi
510 \ifx\bbl@bcp\relax
511 \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
512 \fi
513 \fi\fi}
514 \let\bbl@initoload\relax
515 \def\bbl@provide@locale{%
516 \ifx\babelprovide\undefined
517 \bbl@error{For a language to be defined on the fly 'base'\\%
518 is not enough, and the whole package must be\\%
519 loaded. Either delete the 'base' option or\\%
520 request the languages explicitly}%
521 {See the manual for further details.}%
522 \fi
523 % TODO. Option to search if loaded, with \LocaleForEach
524 \let\bbl@auxname\language\language % Still necessary. TODO
525 \bbl@ifunset{bbl@bcp@map@\language}{}% Move uplevel??
526 {\edef\language\language{\@nameuse{bbl@bcp@map@\language}}}%
527 \ifbbl@bcpallowed
528 \expandafter\ifx\csname date\language\endcsname\relax
529 \expandafter
530 \bbl@bcplookup\language-\@empty-\@empty-\@empty\@
531 \ifx\bbl@bcp\relax\else % Returned by \bbl@bcplookup
532 \edef\language{\bbl@bcp@prefix\bbl@bcp}%
533 \edef\localename{\bbl@bcp@prefix\bbl@bcp}%
534 \expandafter\ifx\csname date\language\endcsname\relax
535 \let\bbl@initoload\bbl@bcp
536 \bbl@exp{\bbl@babelprovide[\bbl@autoload@bcptoptions]{\language}}%
537 \let\bbl@initoload\relax
538 \fi
539 \bbl@csarg\xdef{bcp@map@\bbl@bcp}{\localename}%
540 \fi
541 \fi
542 \fi
543 \expandafter\ifx\csname date\language\endcsname\relax
544 \IfFileExists{babel-\language.tex}%
545 {\bbl@exp{\bbl@babelprovide[\bbl@autoload@options]{\language}}}%
546 {}%
547 \fi}

```

`\iflanguage` Users might want to test (in a private package for instance) which language is currently active. For this we provide a test macro, `\iflanguage`, that has three arguments. It checks whether the first argument is a known language. If so, it compares the first argument with the value of `\language`.

Then, depending on the result of the comparison, it executes either the second or the third argument.

```

548 \def\iflanguage#1{%
549   \bbl@iflanguage{#1}{%
550     \ifnum\csname l@#1\endcsname=\language
551       \expandafter\@firstoftwo
552     \else
553       \expandafter\@secondoftwo
554     \fi}}

```

7.1 Selecting the language

`\selectlanguage` The macro `\selectlanguage` checks whether the language is already defined before it performs its actual task, which is to update `\language` and activate language-specific definitions.

```

555 \let\bbl@select@type\z@
556 \edef\selectlanguage{%
557   \noexpand\protect
558   \expandafter\noexpand\csname selectlanguage \endcsname}

```

Because the command `\selectlanguage` could be used in a moving argument it expands to `\protect\selectlanguageL`. Therefore, we have to make sure that a macro `\protect` exists. If it doesn't it is `\let` to `\relax`.

```

559 \ifx\@undefined\protect\let\protect\relax\fi

```

The following definition is preserved for backwards compatibility (eg, arabi, koma). It is related to a trick for 2.09, now discarded.

```

560 \let\xstring\string

```

Since version 3.5 babel writes entries to the auxiliary files in order to typeset table of contents etc. in the correct language environment.

`\bbl@pop@language` But when the language change happens *inside* a group the end of the group doesn't write anything to the auxiliary files. Therefore we need TeX's `aftergroup` mechanism to help us. The command `\aftergroup` stores the token immediately following it to be executed when the current group is closed. So we define a temporary control sequence `\bbl@pop@language` to be executed at the end of the group. It calls `\bbl@set@language` with the name of the current language as its argument.

`\bbl@language@stack` The previous solution works for one level of nesting groups, but as soon as more levels are used it is no longer adequate. For that case we need to keep track of the nested languages using a stack mechanism. This stack is called `\bbl@language@stack` and initially empty.

```

561 \def\bbl@language@stack{}

```

When using a stack we need a mechanism to push an element on the stack and to retrieve the information afterwards.

`\bbl@push@language` The stack is simply a list of languagenames, separated with a '+' sign; the push function can be simple:
`\bbl@pop@language`

```

562 \def\bbl@push@language{%
563   \ifx\languagename\@undefined\else
564     \ifx\currentgrouplevel\@undefined
565       \xdef\bbl@language@stack{\languagename+\bbl@language@stack}%
566     \else
567       \ifnum\currentgrouplevel=\z@
568         \xdef\bbl@language@stack{\languagename+}%
569       \else
570         \xdef\bbl@language@stack{\languagename+\bbl@language@stack}%
571       \fi
572     \fi
573   \fi}

```

Retrieving information from the stack is a little bit less simple, as we need to remove the element from the stack while storing it in the macro `\languagename`. For this we first define a helper function.

`\bbl@pop@lang` This macro stores its first element (which is delimited by the ‘+’-sign) in `\language` and stores the rest of the string in `\bbl@language@stack`.

```
574 \def\bbl@pop@lang#1+#2\@@{%
575   \edef\language{#1}%
576   \xdef\bbl@language@stack{#2}}
```

The reason for the somewhat weird arrangement of arguments to the helper function is the fact it is called in the following way. This means that before `\bbl@pop@lang` is executed TeX first *expands* the stack, stored in `\bbl@language@stack`. The result of that is that the argument string of `\bbl@pop@lang` contains one or more language names, each followed by a ‘+’-sign (zero language names won’t occur as this macro will only be called after something has been pushed on the stack).

```
577 \let\bbl@ifrestoring\@secondoftwo
578 \def\bbl@pop@language{%
579   \expandafter\bbl@pop@lang\bbl@language@stack\@@
580   \let\bbl@ifrestoring\@firstoftwo
581   \expandafter\bbl@set@language\expandafter{\language}%
582   \let\bbl@ifrestoring\@secondoftwo}
```

Once the name of the previous language is retrieved from the stack, it is fed to `\bbl@set@language` to do the actual work of switching everything that needs switching.

An alternative way to identify languages (in the babel sense) with a numerical value is introduced in 3.30. This is one of the first steps for a new interface based on the concept of locale, which explains the name of `\localeid`. This means `\l@...` will be reserved for hyphenation patterns (so that two locales can share the same rules).

```
583 \chardef\localeid\z@
584 \def\bbl@id@last{0} % No real need for a new counter
585 \def\bbl@id@assign{%
586   \bbl@ifunset\bbl@id@@\language}%
587   {\count@\bbl@id@last\relax
588    \advance\count@\@ne
589    \bbl@csarg\chardef{id@@\language}\count@
590    \edef\bbl@id@last{\the\count@}%
591    \ifcase\bbl@engine\or
592      \directlua{
593        Babel = Babel or {}
594        Babel.locale_props = Babel.locale_props or {}
595        Babel.locale_props[\bbl@id@last] = {}
596        Babel.locale_props[\bbl@id@last].name = '\language'
597      }%
598    \fi}%
599   {}%
600   \chardef\localeid\bbl@cl{id@}}
```

The unprotected part of `\selectlanguage`.

```
601 \expandafter\def\csname selectlanguage \endcsname#1{%
602   \ifnum\bbl@hymapsel=\@cclv\let\bbl@hymapsel\tw@\fi
603   \bbl@push@language
604   \aftergroup\bbl@pop@language
605   \bbl@set@language{#1}}
```

`\bbl@set@language` The macro `\bbl@set@language` takes care of switching the language environment *and* of writing entries on the auxiliary files. For historical reasons, language names can be either language of `\language`. To catch either form a trick is used, but unfortunately as a side effect the catcodes of letters in `\language` are messed up. This is a bug, but preserved for backwards compatibility. The list of auxiliary files can be extended by redefining `\BabelContentsFiles`, but make sure they are loaded inside a group (as aux, toc, lof, and lot do) or the last language of the document will remain active afterwards.

We also write a command to change the current language in the auxiliary files.

`\bbl@savelastskip` is used to deal with skips before the write whatsit (as suggested by U Fischer). Adapted from `hyperref`, but it might fail, so I’ll consider it a temporary hack, while I study other options (the ideal, but very likely unfeasible except perhaps in `lualatex`, is to avoid the `\write` altogether when not needed).

```

606 \def\BabelContentsFiles{toc,lof,lot}
607 \def\bbl@set@language#1{% from selectlanguage, pop@
608 % The old buggy way. Preserved for compatibility.
609 \edef\language{%
610   \ifnum\escapechar=\expandafter`\string#1\@empty
611   \else\string#1\@empty\fi}%
612 \ifcat\relax\noexpand#1%
613   \expandafter\ifx\csname date\language\endcsname\relax
614     \edef\language{#1}%
615     \let\locale\language
616   \else
617     \bbl@info{Using '\string\language' instead of 'language' is\%
618               deprecated. If what you want is to use a\%
619               macro containing the actual locale, make\%
620               sure it does not not match any language.\%
621               Reported}%
622     \ifx\scantokens\undefined
623       \def\locale{??}%
624     \else
625       \scantokens\expandafter{\expandafter
626         \def\expandafter\locale\expandafter{\language}}%
627     \fi
628   \fi
629 \else
630   \def\locale{#1}% This one has the correct catcodes
631 \fi
632 \select@language{\language}%
633 % write to aux
634 \expandafter\ifx\csname date\language\endcsname\relax\else
635   \if@filesw
636     \ifx\babel@aux\@gobbletwo\else % Set if single in the first, redundant
637       \bbl@savelastskip
638       \protected@write\@auxout{}\{\string\babel@aux{\bbl@auxname}\}%
639       \bbl@restorelastskip
640     \fi
641     \bbl@usehooks{write}\}%
642   \fi
643 \fi}
644 %
645 \let\bbl@restorelastskip\relax
646 \let\bbl@savelastskip\relax
647 %
648 \newif\ifbbl@bcpallowed
649 \bbl@bcpallowedfalse
650 \def\select@language#1{% from set@, babel@aux
651   \ifx\bbl@selectorname\@empty
652     \def\bbl@selectorname{select}%
653   % set hymap
654   \fi
655   \ifnum\bbl@hymapsel=\@cclv\chardef\bbl@hymapsel4\relax\fi
656   % set name
657   \edef\language{#1}%
658   \bbl@fixname\language
659   % TODO. name@map must be here?
660   \bbl@provide@locale
661   \bbl@iflanguage\language{%
662     \expandafter\ifx\csname date\language\endcsname\relax
663     \bbl@error
664       {Unknown language '\language'. Either you have\%
665       misspelled its name, it has not been installed,\%
666       or you requested it in a previous run. Fix its name,\%
667       install it or just rerun the file, respectively. In\%
668       some cases, you may need to remove the aux file}%

```

```

669     {You may proceed, but expect wrong results}%
670   \else
671     % set type
672     \let\bbl@select@type\z@
673     \expandafter\bbl@switch\expandafter{\language}%
674   \fi}}
675 \def\babel@aux#1#2{%
676   \select@language{#1}%
677   \bbl@foreach\BabelContentsFiles{% \relax -> don't assume vertical mode
678     \@writefile{##1}{\babel@toc{#1}{#2}\relax}}}% TODO - plain?
679 \def\babel@toc#1#2{%
680   \select@language{#1}}

```

First, check if the user asks for a known language. If so, update the value of `\language` and call `\originalTeX` to bring \TeX in a certain pre-defined state.

The name of the language is stored in the control sequence `\language`.

Then we have to *redefine* `\originalTeX` to compensate for the things that have been activated. To save memory space for the macro definition of `\originalTeX`, we construct the control sequence name for the `\noextras<lang>` command at definition time by expanding the `\csname` primitive. Now activate the language-specific definitions. This is done by constructing the names of three macros by concatenating three words with the argument of `\selectlanguage`, and calling these macros.

The switching of the values of `\lefthyphenmin` and `\righthyphenmin` is somewhat different. First we save their current values, then we check if `\<lang>hyphenmins` is defined. If it is not, we set default values (2 and 3), otherwise the values in `\<lang>hyphenmins` will be used.

```

681 \newif\ifbbl@usedategroup
682 \def\bbl@switch#1{% from select@, foreign@
683   % make sure there is info for the language if so requested
684   \bbl@ensureinfo{#1}%
685   % restore
686   \originalTeX
687   \expandafter\def\expandafter\originalTeX\expandafter{%
688     \csname noextras#1\endcsname
689     \let\originalTeX\@empty
690     \babel@beginsave}%
691   \bbl@usehooks{afterreset}{}%
692   \languageshorthands{none}%
693   % set the locale id
694   \bbl@id@assign
695   % switch captions, date
696   % No text is supposed to be added here, so we remove any
697   % spurious spaces.
698   \bbl@bspack
699   \ifcase\bbl@select@type
700     \csname captions#1\endcsname\relax
701     \csname date#1\endcsname\relax
702   \else
703     \bbl@xin@{,captions,}{,\bbl@select@opts,}%
704     \ifin@
705       \csname captions#1\endcsname\relax
706     \fi
707     \bbl@xin@{,date,}{,\bbl@select@opts,}%
708     \ifin@ % if \foreign... within \<lang>date
709       \csname date#1\endcsname\relax
710     \fi
711   \fi
712   \bbl@espack
713   % switch extras
714   \bbl@usehooks{beforeextras}{}%
715   \csname extras#1\endcsname\relax
716   \bbl@usehooks{afterextras}{}%
717   % > babel-ensure
718   % > babel-sh-<short>

```

```

719 % > babel-bidi
720 % > babel-fontspec
721 % hyphenation - case mapping
722 \ifcase\bbbl@opt@hyphenmap\or
723   \def\BabelLower##1##2{\lccode##1=##2\relax}%
724   \ifnum\bbbl@hymapsel>4\else
725     \csname\language\name @bbbl@hyphenmap\endcsname
726     \fi
727     \chardef\bbbl@opt@hyphenmap\z@
728 \else
729   \ifnum\bbbl@hymapsel>\bbbl@opt@hyphenmap\else
730     \csname\language\name @bbbl@hyphenmap\endcsname
731     \fi
732 \fi
733 \let\bbbl@hymapsel\@ccclv
734 % hyphenation - select rules
735 \ifnum\csname l@\language\endcsname=\l@unhyphenated
736   \edef\bbbl@tempa{u}%
737 \else
738   \edef\bbbl@tempa{\bbbl@ccl{lnbrk}}%
739 \fi
740 % linebreaking - handle u, e, k (v in the future)
741 \bbbl@xin@{/u}{/\bbbl@tempa}%
742 \ifin@else\bbbl@xin@{/e}{/\bbbl@tempa}\fi % elongated forms
743 \ifin@else\bbbl@xin@{/k}{/\bbbl@tempa}\fi % only kashida
744 \ifin@else\bbbl@xin@{/v}{/\bbbl@tempa}\fi % variable font
745 \ifin@
746   % unhyphenated/kashida/elongated = allow stretching
747   \language\l@unhyphenated
748   \babel@savevariable\emergencystretch
749   \emergencystretch\maxdimen
750   \babel@savevariable\hbadness
751   \hbadness\@M
752 \else
753   % other = select patterns
754   \bbbl@patterns{#1}%
755 \fi
756 % hyphenation - mins
757 \babel@savevariable\lefthyphenmin
758 \babel@savevariable\righthyphenmin
759 \expandafter\ifx\csname #1hyphenmins\endcsname\relax
760   \set@hyphenmins\tw@\thr@@\relax
761 \else
762   \expandafter\expandafter\expandafter\set@hyphenmins
763     \csname #1hyphenmins\endcsname\relax
764 \fi
765 \let\bbbl@selectorname\@empty}

```

`otherlanguage` The `otherlanguage` environment can be used as an alternative to using the `\selectlanguage` declarative command. When you are typesetting a document which mixes left-to-right and right-to-left typesetting you have to use this environment in order to let things work as you expect them to.

The `\ignorespaces` command is necessary to hide the environment when it is entered in horizontal mode.

```

766 \long\def\otherlanguage#1{%
767   \def\bbbl@selectorname{other}%
768   \ifnum\bbbl@hymapsel=\@ccclv\let\bbbl@hymapsel\thr@@\fi
769   \csname selectlanguage \endcsname{#1}%
770   \ignorespaces}

```

The `\endotherlanguage` part of the environment tries to hide itself when it is called in horizontal mode.

```

771 \long\def\endotherlanguage{%

```

```

772 \global\@ignoretrue\ignorespaces}

otherlanguage* The otherlanguage environment is meant to be used when a large part of text from a different
language needs to be typeset, but without changing the translation of words such as ‘figure’. This
environment makes use of \foreign@language.

773 \expandafter\def\csname otherlanguage*\endcsname{%
774 \@ifnextchar[\bbl@otherlanguage@s{\bbl@otherlanguage@s[]}}
775 \def\bbl@otherlanguage@s[#1]#2{%
776 \def\bbl@selectorname{other*}%
777 \ifnum\bbl@hymapset=\@ccclv\chardef\bbl@hymapset4\relax\fi
778 \def\bbl@select@opts{#1}%
779 \foreign@language{#2}}

At the end of the environment we need to switch off the extra definitions. The grouping mechanism
of the environment will take care of resetting the correct hyphenation rules and “extras”.

780 \expandafter\let\csname endotherlanguage*\endcsname\relax

\foreignlanguage The \foreignlanguage command is another substitute for the \selectlanguage command. This
command takes two arguments, the first argument is the name of the language to use for typesetting
the text specified in the second argument.
Unlike \selectlanguage this command doesn’t switch everything, it only switches the hyphenation
rules and the extra definitions for the language specified. It does this within a group and assumes the
\extras<lang> command doesn’t make any \global changes. The coding is very similar to part of
\selectlanguage.
\bbl@beforeforeign is a trick to fix a bug in bidi texts. \foreignlanguage is supposed to be a ‘text’
command, and therefore it must emit a \leavevmode, but it does not, and therefore the indent is
placed on the opposite margin. For backward compatibility, however, it is done only if a right-to-left
script is requested; otherwise, it is no-op.
(3.11) \foreignlanguage* is a temporary, experimental macro for a few lines with a different script
direction, while preserving the paragraph format (thank the braces around \par, things like
\hangindent are not reset). Do not use it in production, because its semantics and its syntax may
change (and very likely will, or even it could be removed altogether). Currently it enters in vmode
and then selects the language (which in turn sets the paragraph direction).
(3.11) Also experimental are the hook foreign and foreign*. With them you can redefine
\BabelText which by default does nothing. Its behavior is not well defined yet. So, use it in
horizontal mode only if you do not want surprises.
In other words, at the beginning of a paragraph \foreignlanguage enters into hmode with the
surrounding lang, and with \foreignlanguage* with the new lang.

781 \providecommand\bbl@beforeforeign{}
782 \edef\foreignlanguage{%
783 \noexpand\protect
784 \expandafter\noexpand\csname foreignlanguage \endcsname}
785 \expandafter\def\csname foreignlanguage \endcsname{%
786 \@ifstar\bbl@foreign@s\bbl@foreign@x}
787 \providecommand\bbl@foreign@x[3][]{%
788 \begingroup
789 \def\bbl@selectorname{foreign}%
790 \def\bbl@select@opts{#1}%
791 \let\BabelText\@firstofone
792 \bbl@beforeforeign
793 \foreign@language{#2}%
794 \bbl@usehooks{foreign}{}%
795 \BabelText{#3}% Now in horizontal mode!
796 \endgroup}
797 \def\bbl@foreign@s#1#2{% TODO - \shapemode, \@setpar, ?\@@par
798 \begingroup
799 {\par}%
800 \def\bbl@selectorname{foreign*}%
801 \let\bbl@select@opts\empty
802 \let\BabelText\@firstofone
803 \foreign@language{#1}%
804 \bbl@usehooks{foreign*}{}%
805 \bbl@dirparastext

```

```

806 \BabelText{#2}% Still in vertical mode!
807 {\par}%
808 \endgroup}

```

`\foreign@language` This macro does the work for `\foreignlanguage` and the other `language*` environment. First we need to store the name of the language and check that it is a known language. Then it just calls `bbl@switch`.

```

809 \def\foreign@language#1{%
810 % set name
811 \edef\language#1}%
812 \ifbbl@usedategroup
813 \bbl@add\bbl@select@opts{,date,}%
814 \bbl@usedategroupfalse
815 \fi
816 \bbl@fixname\language
817 % TODO. name@map here?
818 \bbl@provide@locale
819 \bbl@iflanguage\language{%
820 \expandafter\ifx\csname date\language\endcsname\relax
821 \bbl@warning % TODO - why a warning, not an error?
822 {Unknown language '#1'. Either you have\\%
823 misspelled its name, it has not been installed,\\%
824 or you requested it in a previous run. Fix its name,\\%
825 install it or just rerun the file, respectively. In\\%
826 some cases, you may need to remove the aux file.\\%
827 I'll proceed, but expect wrong results.\\%
828 Reported}%
829 \fi
830 % set type
831 \let\bbl@select@type\@ne
832 \expandafter\bbl@switch\expandafter{\language}}

```

The following macro executes conditionally some code based on the selector being used.

```

833 \def\IfBabelSelectorTF#1{%
834 \bbl@xin@{\bbl@selectorname,}{,\zap@space#1 \@empty,}%
835 \ifin@
836 \expandafter\@firstoftwo
837 \else
838 \expandafter\@secondoftwo
839 \fi}

```

`\bbl@patterns` This macro selects the hyphenation patterns by changing the `\language` register. If special hyphenation patterns are available specifically for the current font encoding, use them instead of the default.

It also sets hyphenation exceptions, but only once, because they are global (here language `\lccode*` has been set, too). `\bbl@hyphenation@` is set to relax until the very first `\babelhyphenation`, so do nothing with this value. If the exceptions for a language (by its number, not its name, so that `:ENC` is taken into account) has been set, then use `\hyphenation` with both global and language exceptions and empty the latter to mark they must not be set again.

```

840 \let\bbl@hyphlist\@empty
841 \let\bbl@hyphenation@relax
842 \let\bbl@pttnlist\@empty
843 \let\bbl@patterns@relax
844 \let\bbl@hymapsel=\cclv
845 \def\bbl@patterns#1{%
846 \language=\expandafter\ifx\csname l@#1:\f@encoding\endcsname\relax
847 \csname l@#1\endcsname
848 \edef\bbl@tempa{#1}%
849 \else
850 \csname l@#1:\f@encoding\endcsname
851 \edef\bbl@tempa{#1:\f@encoding}%
852 \fi
853 \@expandtwoargs\bbl@usehooks{patterns}{#{1}}{\bbl@tempa}}%

```



```

854 % > luatex
855 \@ifundefined{bbl@hyphenation@}{\% Can be \relax!
856   \begingroup
857     \bbl@xin@{\number\language,}{\bbl@hyphlist}%
858     \ifin@else
859       \@expandtwoargs\bbl@usehooks{hyphenation}{\#1}{\bbl@tempa}}%
860       \hyphenation{%
861         \bbl@hyphenation@
862         \@ifundefined{bbl@hyphenation@#1}%
863         \@empty
864         {\space\csname bbl@hyphenation@#1\endcsname}}%
865       \xdef\bbl@hyphlist{\bbl@hyphlist\number\language,}%
866       \fi
867   \endgroup}}

```

`hyphenrules` The environment `hyphenrules` can be used to select *just* the hyphenation rules. This environment does *not* change `\language` and when the hyphenation rules specified were not loaded it has no effect. Note however, `\lcode`'s and font encodings are not set at all, so in most cases you should use `otherlanguage*`.

```

868 \def\hyphenrules#1{%
869   \edef\bbl@tempf{#1}%
870   \bbl@fixname\bbl@tempf
871   \bbl@iflanguage\bbl@tempf{%
872     \expandafter\bbl@patterns\expandafter{\bbl@tempf}%
873     \ifx\languageshorthands\@undefined\else
874       \languageshorthands{none}%
875     \fi
876     \expandafter\ifx\csname\bbl@tempf hyphenmins\endcsname\relax
877       \set@hyphenmins\tw@\thr@@\relax
878     \else
879       \expandafter\expandafter\expandafter\set@hyphenmins
880       \csname\bbl@tempf hyphenmins\endcsname\relax
881     \fi}}
882 \let\endhyphenrules\@empty

```

`\providehyphenmins` The macro `\providehyphenmins` should be used in the language definition files to provide a *default* setting for the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`. If the macro `\(lang)hyphenmins` is already defined this command has no effect.

```

883 \def\providehyphenmins#1#2{%
884   \expandafter\ifx\csname #1hyphenmins\endcsname\relax
885     \@namedef{#1hyphenmins}{#2}%
886   \fi}

```

`\set@hyphenmins` This macro sets the values of `\lefthyphenmin` and `\righthyphenmin`. It expects two values as its argument.

```

887 \def\set@hyphenmins#1#2{%
888   \lefthyphenmin#1\relax
889   \righthyphenmin#2\relax}

```

`\ProvidesLanguage` The identification code for each file is something that was introduced in $\text{\LaTeX 2}_{\epsilon}$. When the command `\ProvidesFile` does not exist, a dummy definition is provided temporarily. For use in the language definition file the command `\ProvidesLanguage` is defined by `babel`. Depending on the format, ie, on if the former is defined, we use a similar definition or not.

```

890 \ifx\ProvidesFile\@undefined
891   \def\ProvidesLanguage#1[#2 #3 #4]{%
892     \wlog{Language: #1 #4 #3 <#2>}%
893   }
894 \else
895   \def\ProvidesLanguage#1{%
896     \begingroup
897     \catcode`\ 10 %
898     \@makeother\%

```

```

899     \@ifnextchar[%]
900     {\@provideslanguage{#1}}{\@provideslanguage{#1}[]}}
901 \def\@provideslanguage#1[#2]{%
902   \wlog{Language: #1 #2}%
903   \expandafter\xdef\csname ver@#1.ldf\endcsname{#2}%
904   \endgroup}
905 \fi

```

`\originalTeX` The macro `\originalTeX` should be known to \TeX at this moment. As it has to be expandable we `\let` it to `\@empty` instead of `\relax`.

```
906 \ifx\originalTeX\undefined\let\originalTeX\@empty\fi
```

Because this part of the code can be included in a format, we make sure that the macro which initializes the save mechanism, `\babel@beginsave`, is not considered to be undefined.

```
907 \ifx\babel@beginsave\undefined\let\babel@beginsave\relax\fi
```

A few macro names are reserved for future releases of babel, which will use the concept of ‘locale’:

```

908 \providecommand\setlocale{%
909   \bbl@error
910   {Not yet available}%
911   {Find an armchair, sit down and wait}}
912 \let\uselocale\setlocale
913 \let\locale\setlocale
914 \let\selectlocale\setlocale
915 \let\textlocale\setlocale
916 \let\textlanguage\setlocale
917 \let\languagetext\setlocale

```

7.2 Errors

`\@nolanerr` The babel package will signal an error when a documents tries to select a language that hasn’t been defined earlier. When a user selects a language for which no hyphenation patterns were loaded into the format he will be given a warning about that fact. We revert to the patterns for `\language=0` in that case. In most formats that will be (US)english, but it might also be empty.

`\@noopterr` When the package was loaded without options not everything will work as expected. An error message is issued in that case.
When the format knows about `\PackageError` it must be $\LaTeX 2_{\epsilon}$, so we can safely use its error handling interface. Otherwise we’ll have to ‘keep it simple’.
Infos are not written to the console, but on the other hand many people think warnings are errors, so a further message type is defined: an important info which is sent to the console.

```

918 \edef\bbl@nulllanguage{\string\language=0}
919 \def\bbl@nocaption{\protect\bbl@nocaption@i}
920 \def\bbl@nocaption@i#1#2{% 1: text to be printed 2: caption macro \langXname
921   \global\@namedef{#2}{\textbf{?#1?}}}%
922   \@nameuse{#2}%
923   \edef\bbl@tempa{#1}%
924   \bbl@sreplace\bbl@tempa{name}{}}%
925   \bbl@warning{% TODO.
926     \@backslashchar#1 not set for '\language'. Please,\\%
927     define it after the language has been loaded\\%
928     (typically in the preamble) with:\\%
929     \string\setlocalecaption{\language}{\bbl@tempa}{..}\\%
930     Reported}}
931 \def\bbl@tentative{\protect\bbl@tentative@i}
932 \def\bbl@tentative@i#1{%
933   \bbl@warning{%
934     Some functions for '#1' are tentative.\\%
935     They might not work as expected and their behavior\\%
936     could change in the future.\\%
937     Reported}}
938 \def\@nolanerr#1{%
939   \bbl@error

```

```

940 {You haven't defined the language '#1' yet.\\%
941 Perhaps you misspelled it or your installation\\%
942 is not complete}%
943 {Your command will be ignored, type <return> to proceed}}
944 \def\@nopatterns#1{%
945 \bbl@warning
946 {No hyphenation patterns were preloaded for\\%
947 the language '#1' into the format.\\%
948 Please, configure your TeX system to add them and\\%
949 rebuild the format. Now I will use the patterns\\%
950 preloaded for \bbl@nulllanguage\space instead}}
951 \let\bbl@usehooks\@gobbletwo
952 \ifx\bbl@onlyswitch\@empty\endinput\fi
953 % Here ended switch.def

Here ended the now discarded switch.def. Here also (currently) ends the base option.

954 \ifx\directlua\@undefined\else
955 \ifx\bbl@luapatterns\@undefined
956 \input luababel.def
957 \fi
958 \fi
959 <Basic macros>
960 \bbl@trace{Compatibility with language.def}
961 \ifx\bbl@languages\@undefined
962 \ifx\directlua\@undefined
963 \openin1 = language.def % TODO. Remove hardcoded number
964 \ifeof1
965 \closein1
966 \message{I couldn't find the file language.def}
967 \else
968 \closein1
969 \begingroup
970 \def\addlanguage#1#2#3#4#5{%
971 \expandafter\ifx\csname lang@#1\endcsname\relax\else
972 \global\expandafter\let\csname l@#1\expandafter\endcsname
973 \csname lang@#1\endcsname
974 \fi}%
975 \def\uselanguage#1{%
976 \input language.def
977 \endgroup
978 \fi
979 \fi
980 \chardef\l@english\z@
981 \fi

```

\addto It takes two arguments, a *<control sequence>* and \TeX -code to be added to the *<control sequence>*. If the *<control sequence>* has not been defined before it is defined now. The control sequence could also expand to `\relax`, in which case a circular definition results. The net result is a stack overflow. Note there is an inconsistency, because the assignment in the last branch is global.

```

982 \def\addto#1#2{%
983 \ifx#1\@undefined
984 \def#1{#2}%
985 \else
986 \ifx#1\relax
987 \def#1{#2}%
988 \else
989 {\toks@\expandafter{#1#2}%
990 \xdef#1{\the\toks@}}%
991 \fi
992 \fi}

```

The macro `\initiate@active@char` below takes all the necessary actions to make its argument a shorthand character. The real work is performed once for each character. But first we define a little tool. TODO. Always used with additional expansions. Move them here? Move the macro to basic?

```

993 \def\bbl@withactive#1#2{%
994   \begingroup
995     \lccode`~=#2\relax
996     \lowercase{\endgroup#1~}}

```

`\bbl@redefine` To redefine a command, we save the old meaning of the macro. Then we redefine it to call the original macro with the ‘sanitized’ argument. The reason why we do it this way is that we don’t want to redefine the \LaTeX macros completely in case their definitions change (they have changed in the past). A macro named `\macro` will be saved new control sequences named `\org@macro`.

```

997 \def\bbl@redefine#1{%
998   \edef\bbl@tempa{\bbl@stripslash#1}%
999   \expandafter\let\csname org@\bbl@tempa\endcsname#1%
1000   \expandafter\def\csname\bbl@tempa\endcsname{
1001   \@onlypreamble\bbl@redefine

```

`\bbl@redefine@long` This version of `\babel@redefine` can be used to redefine `\long` commands such as `\ifthenelse`.

```

1002 \def\bbl@redefine@long#1{%
1003   \edef\bbl@tempa{\bbl@stripslash#1}%
1004   \expandafter\let\csname org@\bbl@tempa\endcsname#1%
1005   \expandafter\long\expandafter\def\csname\bbl@tempa\endcsname{
1006   \@onlypreamble\bbl@redefine@long

```

`\bbl@redefineroobust` For commands that are redefined, but which *might* be robust we need a slightly more intelligent macro. A robust command `foo` is defined to expand to `\protect\foo_`. So it is necessary to check whether `\foo_` exists. The result is that the command that is being redefined is always robust afterwards. Therefore all we need to do now is define `\foo_`.

```

1007 \def\bbl@redefineroobust#1{%
1008   \edef\bbl@tempa{\bbl@stripslash#1}%
1009   \bbl@ifunset{\bbl@tempa\space}%
1010   {\expandafter\let\csname org@\bbl@tempa\endcsname#1%
1011     \bbl@exp{\def\#1{\protect\<\bbl@tempa\space>}}}%
1012   {\bbl@exp{\let\<org@\bbl@tempa>\<\bbl@tempa\space>}}}%
1013   \@namedef{\bbl@tempa\space}%
1014   \@onlypreamble\bbl@redefineroobust

```

7.3 Hooks

Admittedly, the current implementation is a somewhat simplistic and does very little to catch errors, but it is meant for developers, after all. `\bbl@usehooks` is the commands used by `babel` to execute hooks defined for an event.

```

1015 \bbl@trace{Hooks}
1016 \newcommand\AddBabelHook[3][{}]{%
1017   \bbl@ifunset{\bbl@hk@#2}{\EnableBabelHook{#2}}}%
1018   \def\bbl@tempa##1,#3=##2,##3@empty{\def\bbl@tempb{##2}}%
1019   \expandafter\bbl@tempa\bbl@evargs,#3=,\@empty
1020   \bbl@ifunset{\bbl@ev@#2@#3@#1}%
1021     {\bbl@csarg\bbl@add{ev@#3@#1}{\bbl@elth{#2}}}%
1022     {\bbl@csarg\let{ev@#2@#3@#1}\relax}%
1023   \bbl@csarg\newcommand{ev@#2@#3@#1}[\bbl@tempb]}
1024 \newcommand\EnableBabelHook[1]{\bbl@csarg\let{hk@#1}\@firstofone}
1025 \newcommand\DisableBabelHook[1]{\bbl@csarg\let{hk@#1}\@gobble}
1026 \def\bbl@usehooks#1#2{%
1027   \ifx\UseHook\undefined\else\UseHook{babel/*/#1}\fi
1028   \def\bbl@elth##1{%
1029     \bbl@cs{hk@##1}{\bbl@cs{ev@##1@#1@#2}}%
1030     \bbl@cs{ev@#1@}%
1031     \ifx\language\undefined\else % Test required for Plain (?)
1032       \ifx\UseHook\undefined\else\UseHook{babel/\language/#1}\fi
1033       \def\bbl@elth##1{%
1034         \bbl@cs{hk@##1}{\bbl@cl{ev@##1@#1@#2}}%
1035         \bbl@cl{ev@#1}%
1036       \fi}

```

To ensure forward compatibility, arguments in hooks are set implicitly. So, if a further argument is added in the future, there is no need to change the existing code. Note events intended for hyphen.cfg are also loaded (just in case you need them for some reason).

```

1037 \def\bbl@evargs{,% <- don't delete this comma
1038   everylanguage=1,loadkernel=1,loadpatterns=1,loadexceptions=1,%
1039   adddialect=2,patterns=2,defaultcommands=0,encodedcommands=2,write=0,%
1040   beforeextras=0,afterextras=0,stopcommands=0,stringprocess=0,%
1041   hyphenation=2,initiateactive=3,afterreset=0,foreign=0,foreign*=0,%
1042   beforestart=0,language=2}
1043 \ifx\NewHook\undefined\else
1044   \def\bbl@tempa#1=#2\@{\NewHook{babel/#1}}
1045   \bbl@foreach\bbl@evargs{\bbl@tempa#1\@}
1046 \fi

```

\babelensure The user command just parses the optional argument and creates a new macro named `\bbl@e@<language>`. We register a hook at the `afterextras` event which just executes this macro in a “complete” selection (which, if undefined, is `\relax` and does nothing). This part is somewhat involved because we have to make sure things are expanded the correct number of times. The macro `\bbl@e@<language>` contains `\bbl@ensure{<include>}{<exclude>}{<fontenc>}`, which in turn loops over the macros names in `\bbl@captionslist`, excluding (with the help of `\in@`) those in the exclude list. If the fontenc is given (and not `\relax`), the `\fontencoding` is also added. Then we loop over the include list, but if the macro already contains `\foreignlanguage`, nothing is done. Note this macro (1) is not restricted to the preamble, and (2) changes are local.

```

1047 \bbl@trace{Defining babelensure}
1048 \newcommand\babelensure[2][{}% TODO - revise test files
1049   \AddBabelHook{babel-ensure}{afterextras}{%
1050     \ifcase\bbl@select@type
1051       \bbl@cl{e}%
1052     \fi}%
1053 \begingroup
1054   \let\bbl@ens@include\empty
1055   \let\bbl@ens@exclude\empty
1056   \def\bbl@ens@fontenc{\relax}%
1057   \def\bbl@tempb##1{%
1058     \ifx\empty##1\else\noexpand##1\expandafter\bbl@tempb\fi}%
1059   \edef\bbl@tempa{\bbl@tempb##1\empty}%
1060   \def\bbl@tempb##1=#2\@{\@namedef{\bbl@ens@##1}{##2}}%
1061   \bbl@foreach\bbl@tempa{\bbl@tempb##1\@}%
1062   \def\bbl@tempc{\bbl@ensure}%
1063   \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
1064     \expandafter{\bbl@ens@include}}%
1065   \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
1066     \expandafter{\bbl@ens@exclude}}%
1067   \toks@\expandafter{\bbl@tempc}%
1068   \bbl@exp{%
1069 \endgroup
1070 \def<\bbl@e@#2>{\the\toks@{\bbl@ens@fontenc}}}%
1071 \def\bbl@ensure#1#2#3{% 1: include 2: exclude 3: fontenc
1072   \def\bbl@tempb##1{% elt for (excluding) \bbl@captionslist list
1073     \ifx##1\undefined % 3.32 - Don't assume the macro exists
1074       \edef##1{\noexpand\bbl@nocaption
1075         {\bbl@stripslash##1}{\language\bbl@stripslash##1}}%
1076     \fi
1077     \ifx##1\empty\else
1078       \in@{##1}{#2}%
1079     \ifin\else
1080       \bbl@ifunset{\bbl@ensure@\language}%
1081       {\bbl@exp{%
1082         \\DeclareRobustCommand\bbl@ensure@\language>[1]{%
1083           \\foreignlanguage{\language}%
1084           {\ifx\relax#3\else
1085             \\fontencoding{#3}\\selectfont
1086             \fi

```

```

1087          #####1}}}%
1088      {}%
1089      \toks@\expandafter{##1}%
1090      \edef##1{%
1091          \bbl@csarg\noexpand{ensure@\language}%
1092          {\the\toks@}}%
1093      \fi
1094      \expandafter\bbl@tempb
1095      \fi}%
1096      \expandafter\bbl@tempb\bbl@captionslist\today\@empty
1097      \def\bbl@tempa##1{% elt for include list
1098          \ifx##1\@empty\else
1099              \bbl@csarg\in{ensure@\language\expandafter}\expandafter{##1}%
1100              \ifin\else
1101                  \bbl@tempb##1\@empty
1102              \fi
1103              \expandafter\bbl@tempa
1104              \fi}%
1105      \bbl@tempa#1\@empty}
1106      \def\bbl@captionslist{%
1107          \prefacename\refname\abstractname\bibname\chaptername\appendixname
1108          \contentsname\listfigurename\listtablename\indexname\figurename
1109          \tablename\partname\enclname\ccname\headtoname\pagename\seename
1110          \alsoname\proofname\glossaryname}

```

7.4 Setting up language files

`\LdfInit` `\LdfInit` macro takes two arguments. The first argument is the name of the language that will be defined in the language definition file; the second argument is either a control sequence or a string from which a control sequence should be constructed. The existence of the control sequence indicates that the file has been processed before.

At the start of processing a language definition file we always check the category code of the `@`-sign. We make sure that it is a ‘letter’ during the processing of the file. We also save its name as the last called option, even if not loaded.

Another character that needs to have the correct category code during processing of language definition files is the equals sign, ‘=’, because it is sometimes used in constructions with the `\let` primitive. Therefore we store its current catcode and restore it later on.

Now we check whether we should perhaps stop the processing of this file. To do this we first need to check whether the second argument that is passed to `\LdfInit` is a control sequence. We do that by looking at the first token after passing #2 through `string`. When it is equal to `\@backslashchar` we are dealing with a control sequence which we can compare with `\@undefined`.

If so, we call `\ldf@quit` to set the main language, restore the category code of the `@`-sign and call `\endinput`

When #2 was *not* a control sequence we construct one and compare it with `\relax`.

Finally we check `\originalTeX`.

```

1111 \bbl@trace{Macros for setting language files up}
1112 \def\bbl@ldfinit{%
1113     \let\bbl@screset\@empty
1114     \let\BabelStrings\bbl@opt@string
1115     \let\BabelOptions\@empty
1116     \let\BabelLanguages\relax
1117     \ifx\originalTeX\@undefined
1118         \let\originalTeX\@empty
1119     \else
1120         \originalTeX
1121     \fi}
1122 \def\LdfInit#1#2{%
1123     \chardef\atcatcode=\catcode`\@
1124     \catcode`\@=11\relax
1125     \chardef\eqcatcode=\catcode`\=
1126     \catcode`\-=12\relax
1127     \expandafter\if\expandafter\@backslashchar
1128         \expandafter\@car\string#2\@nil

```

```

1129 \ifx#2\@undefined\else
1130 \ldf@quit{#1}%
1131 \fi
1132 \else
1133 \expandafter\ifx\csname#2\endcsname\relax\else
1134 \ldf@quit{#1}%
1135 \fi
1136 \fi
1137 \bbl@ldfinit}

```

`\ldf@quit` This macro interrupts the processing of a language definition file.

```

1138 \def\ldf@quit#1{%
1139 \expandafter\main@language\expandafter{#1}%
1140 \catcode`\@=\atcatcode \let\atcatcode\relax
1141 \catcode`\==\eqcatcode \let\eqcatcode\relax
1142 \endinput}

```

`\ldf@finish` This macro takes one argument. It is the name of the language that was defined in the language definition file.
We load the local configuration file if one is present, we set the main language (taking into account that the argument might be a control sequence that needs to be expanded) and reset the category code of the @-sign.

```

1143 \def\bbl@afterldf#1{% TODO. Merge into the next macro? Unused elsewhere
1144 \bbl@afterlang
1145 \let\bbl@afterlang\relax
1146 \let\BabelModifiers\relax
1147 \let\bbl@screset\relax}%
1148 \def\ldf@finish#1{%
1149 \loadlocalcfg{#1}%
1150 \bbl@afterldf{#1}%
1151 \expandafter\main@language\expandafter{#1}%
1152 \catcode`\@=\atcatcode \let\atcatcode\relax
1153 \catcode`\==\eqcatcode \let\eqcatcode\relax}

```

After the preamble of the document the commands `\LdfInit`, `\ldf@quit` and `\ldf@finish` are no longer needed. Therefore they are turned into warning messages in `LATEX`.

```

1154 \@onlypreamble\LdfInit
1155 \@onlypreamble\ldf@quit
1156 \@onlypreamble\ldf@finish

```

`\main@language` This command should be used in the various language definition files. It stores its argument in `\bbl@main@language`; to be used to switch to the correct language at the beginning of the document.

```

1157 \def\main@language#1{%
1158 \def\bbl@main@language{#1}%
1159 \let\language\bbl@main@language % TODO. Set localename
1160 \bbl@id@assign
1161 \bbl@patterns{\language}}

```

We also have to make sure that some code gets executed at the beginning of the document, either when the aux file is read or, if it does not exist, when the `\AtBeginDocument` is executed. Languages do not set `\pagedir`, so we set here for the whole document to the main `\bodydir`.

```

1162 \def\bbl@beforestart{%
1163 \def\@nolanerr##1{%
1164 \bbl@warning{Undefined language '##1' in aux.\Reported}}%
1165 \bbl@usehooks{beforestart}}%
1166 \global\let\bbl@beforestart\relax}
1167 \AtBeginDocument{%
1168 {\@nameuse{bbl@beforestart}}% Group!
1169 \if@filesw
1170 \providecommand\babel@aux[2]{}%
1171 \immediate\write\mainaux{%
1172 \string\providecommand\string\babel@aux[2]{}%

```

```

1173 \immediate\write\@mainaux{\string\@nameuse{bbl@beforestart}}%
1174 \fi
1175 \expandafter\selectlanguage\expandafter{bbl@main@language}%
1176 \ifbbl@single % must go after the line above.
1177 \renewcommand\selectlanguage[1]{}%
1178 \renewcommand\foreignlanguage[2]{#2}%
1179 \global\let\babel@aux\@gobbletwo % Also as flag
1180 \fi
1181 \ifcase\bbl@engine\or\pagedir\bodydir\fi % TODO - a better place

A bit of optimization. Select in heads/foots the language only if necessary.
1182 \def\select@language@x#1{%
1183 \ifcase\bbl@select@type
1184 \bbl@ifsamestring\languagename{#1}{\select@language{#1}}%
1185 \else
1186 \select@language{#1}%
1187 \fi}

```

7.5 Shorthands

`\bbl@add@special` The macro `\bbl@add@special` is used to add a new character (or single character control sequence) to the macro `\dospecials` (and `\@sanitize` if \LaTeX is used). It is used only at one place, namely when `\initiate@active@char` is called (which is ignored if the char has been made active before). Because `\@sanitize` can be undefined, we put the definition inside a conditional. Items are added to the lists without checking its existence or the original catcode. It does not hurt, but should be fixed. It's already done with `\nfss@catcodes`, added in 3.10.

```

1188 \bbl@trace{Shorhands}
1189 \def\bbl@add@special#1{% 1:a macro like \", \?, etc.
1190 \bbl@add\dospecials{\do#1}% test @sanitize = \relax, for back. compat.
1191 \bbl@ifunset{\@sanitize}{\bbl@add\@sanitize{\@makeother#1}}%
1192 \ifx\nfss@catcodes\undefined\else % TODO - same for above
1193 \begingroup
1194 \catcode`#1\active
1195 \nfss@catcodes
1196 \ifnum\catcode`#1=\active
1197 \endgroup
1198 \bbl@add\nfss@catcodes{\@makeother#1}%
1199 \else
1200 \endgroup
1201 \fi
1202 \fi}

```

`\bbl@remove@special` The companion of the former macro is `\bbl@remove@special`. It removes a character from the set macros `\dospecials` and `\@sanitize`, but it is not used at all in the babel core.

```

1203 \def\bbl@remove@special#1{%
1204 \begingroup
1205 \def\x##1##2{\ifnum`#1=##2\noexpand\@empty
1206 \else\noexpand##1\noexpand##2\fi}%
1207 \def\do{\x\do}%
1208 \def\@makeother{\x\@makeother}%
1209 \edef\x{\endgroup
1210 \def\noexpand\dospecials{\dospecials}%
1211 \expandafter\ifx\cname @sanitize\endcsname\relax\else
1212 \def\noexpand\@sanitize{\@sanitize}%
1213 \fi}%
1214 \x}

```

`\initiate@active@char` A language definition file can call this macro to make a character active. This macro takes one argument, the character that is to be made active. When the character was already active this macro does nothing. Otherwise, this macro defines the control sequence `\normal@char⟨char⟩` to expand to the character in its ‘normal state’ and it defines the active character to expand to `\normal@char⟨char⟩` by default (`⟨char⟩` being the character to be made active). Later its definition can be changed to expand to `\active@char⟨char⟩` by calling `\bbl@activate{⟨char⟩}`.

For example, to make the double quote character active one could have `\initiate@active@char{}` in a language definition file. This defines " as `\active@prefix " \active@char` (where the first " is the character with its original catcode, when the shorthand is created, and `\active@char` is a single token). In protected contexts, it expands to `\protect "` or `\noexpand "` (ie, with the original "); otherwise `\active@char` is executed. This macro in turn expands to `\normal@char` in "safe" contexts (eg, `\label`), but `\user@active` in normal "unsafe" ones. The latter search a definition in the user, language and system levels, in this order, but if none is found, `\normal@char` is used.

However, a deactivated shorthand (with `\bbl@deactivate` is defined as

`\active@prefix "\normal@char`.

The following macro is used to define shorthands in the three levels. It takes 4 arguments: the (string'ed) character, `\<level>@group`, `<level>@active` and `<next-level>@active` (except in system).

```
1215 \def\bbl@active@def#1#2#3#4{%
1216   \@namedef{#3#1}{%
1217     \expandafter\ifx\csname#2@sh@#1\endcsname\relax
1218       \bbl@afterelse\bbl@sh@select#2#1{#3@arg#1}{#4#1}%
1219     \else
1220       \bbl@afterfi\csname#2@sh@#1\endcsname
1221     \fi}%
```

When there is also no current-level shorthand with an argument we will check whether there is a next-level defined shorthand for this active character.

```
1222 \long\@namedef{#3@arg#1}##1{%
1223   \expandafter\ifx\csname#2@sh@#1\string##1\endcsname\relax
1224     \bbl@afterelse\csname#4#1\endcsname##1%
1225   \else
1226     \bbl@afterfi\csname#2@sh@#1\string##1\endcsname
1227   \fi}}%
```

`\initiate@active@char` calls `\@initiate@active@char` with 3 arguments. All of them are the same character with different catcodes: active, other (`\string'ed`) and the original one. This trick simplifies the code a lot.

```
1228 \def\initiate@active@char#1{%
1229   \bbl@ifunset{active@char\string#1}%
1230   {\bbl@withactive
1231     {\expandafter\@initiate@active@char\expandafter}#1\string#1#1}%
1232   {}}
```

The very first thing to do is saving the original catcode and the original definition, even if not active, which is possible (undefined characters require a special treatment to avoid making them `\relax` and preserving some degree of protection).

```
1233 \def\@initiate@active@char#1#2#3{%
1234   \bbl@csarg\edef{oricat@#2}{\catcode`#2=\the\catcode`#2\relax}%
1235   \ifx#1\undefined
1236     \bbl@csarg\def{oridef@#2}{\def#1{\active@prefix#1\@undefined}}%
1237   \else
1238     \bbl@csarg\let{oridef@#2}#1%
1239     \bbl@csarg\edef{oridef@#2}{%
1240       \let\noexpand#1%
1241       \expandafter\noexpand\csname bbl@oridef@#2\endcsname}%
1242   \fi
```

If the character is already active we provide the default expansion under this shorthand mechanism. Otherwise we write a message in the transcript file, and define `\normal@char` (*char*) to expand to the character in its default state. If the character is mathematically active when babel is loaded (for example ') the normal expansion is somewhat different to avoid an infinite loop (but it does not prevent the loop if the mathcode is set to "8000 *a posteriori*").

```
1243 \ifx#1#3\relax
1244   \expandafter\let\csname normal@char#2\endcsname#3%
1245 \else
1246   \bbl@info{Making #2 an active character}%
1247   \ifnum\mathcode`#2=\ifodd\bbl@engine"1000000 \else"8000 \fi
1248   \@namedef{normal@char#2}{%
```

```

1249     \textormath{#3}{\csname bbl@oridef@@#2\endcsname}}%
1250     \else
1251     \namedef{normal@char#2}{#3}%
1252     \fi

```

To prevent problems with the loading of other packages after babel we reset the catcode of the character to the original one at the end of the package and of each language file (except with KeepShorthandsActive). It is re-activate again at \begin{document}. We also need to make sure that the shorthands are active during the processing of the .aux file. Otherwise some citations may give unexpected results in the printout when a shorthand was used in the optional argument of \bibitem for example. Then we make it active (not strictly necessary, but done for backward compatibility).

```

1253     \bbl@restoreactive{#2}%
1254     \AtBeginDocument{%
1255     \catcode`#2\active
1256     \if@filesw
1257     \immediate\write\@mainaux{\catcode`\string#2\active}%
1258     \fi}%
1259     \expandafter\bbl@add@special\csname#2\endcsname
1260     \catcode`#2\active
1261     \fi

```

Now we have set \normal@char{char}, we must define \active@char{char}, to be executed when the character is activated. We define the first level expansion of \active@char{char} to check the status of the @safe@actives flag. If it is set to true we expand to the 'normal' version of this character; otherwise we call \user@active{char} to start the search of a definition in the user, language and system levels (or eventually normal@char{char}).

```

1262     \let\bbl@tempa\@firstoftwo
1263     \if\string^#2%
1264     \def\bbl@tempa{\noexpand\textormath}%
1265     \else
1266     \ifx\bbl@mathnormal\@undefined\else
1267     \let\bbl@tempa\bbl@mathnormal
1268     \fi
1269     \fi
1270     \expandafter\edef\csname active@char#2\endcsname{%
1271     \bbl@tempa
1272     {\noexpand\if@safe@actives
1273     \noexpand\expandafter
1274     \expandafter\noexpand\csname normal@char#2\endcsname
1275     \noexpand\else
1276     \noexpand\expandafter
1277     \expandafter\noexpand\csname bbl@doactive#2\endcsname
1278     \noexpand\fi}%
1279     {\expandafter\noexpand\csname normal@char#2\endcsname}}}%
1280     \bbl@csarg\edef{doactive#2}{%
1281     \expandafter\noexpand\csname user@active#2\endcsname}%

```

We now define the default values which the shorthand is set to when activated or deactivated. It is set to the deactivated form (globally), so that the character expands to

`\active@prefix{char} \normal@char{char}`

(where \active@char{char} is one control sequence!).

```

1282     \bbl@csarg\edef{active@#2}{%
1283     \noexpand\active@prefix\noexpand#1%
1284     \expandafter\noexpand\csname active@char#2\endcsname}%
1285     \bbl@csarg\edef{normal@#2}{%
1286     \noexpand\active@prefix\noexpand#1%
1287     \expandafter\noexpand\csname normal@char#2\endcsname}%
1288     \expandafter\let\expandafter#1\csname bbl@normal@#2\endcsname

```

The next level of the code checks whether a user has defined a shorthand for himself with this character. First we check for a single character shorthand. If that doesn't exist we check for a shorthand with an argument.

```

1289 \bbl@active@def#2\user@group{user@active}{language@active}%
1290 \bbl@active@def#2\language@group{language@active}{system@active}%
1291 \bbl@active@def#2\system@group{system@active}{normal@char}%

```

In order to do the right thing when a shorthand with an argument is used by itself at the end of the line we provide a definition for the case of an empty argument. For that case we let the shorthand character expand to its non-active self. Also, When a shorthand combination such as ' ' ends up in a heading T_EX would see \protect'\protect'. To prevent this from happening a couple of shorthand needs to be defined at user level.

```

1292 \expandafter\edef\csname\user@group @sh@#2@\endcsname
1293   {\expandafter\noexpand\csname normal@char#2\endcsname}%
1294 \expandafter\edef\csname\user@group @sh@#2@\string\protect@\endcsname
1295   {\expandafter\noexpand\csname user@active#2\endcsname}%

```

Finally, a couple of special cases are taken care of. (1) If we are making the right quote (') active we need to change \pr@m@s as well. Also, make sure that a single ' in math mode 'does the right thing'. (2) If we are using the caret (^) as a shorthand character special care should be taken to make sure math still works. Therefore an extra level of expansion is introduced with a check for math mode on the upper level.

```

1296 \if\string'#2%
1297   \let\prim@s\bbl@prim@s
1298   \let\active@math@prime#1%
1299 \fi
1300 \bbl@usehooks{initiateactive}{{#1}{#2}{#3}}

```

The following package options control the behavior of shorthands in math mode.

```

1301 \langle *More package options \rangle \equiv
1302 \DeclareOption{math=active}{}
1303 \DeclareOption{math=normal}{{\def\bbl@mathnormal{\noexpand\textormath}}}
1304 \rangle /More package options \rangle

```

Initiating a shorthand makes active the char. That is not strictly necessary but it is still done for backward compatibility. So we need to restore the original catcode at the end of package *and* the end of the ldf.

```

1305 \ifpackagewith{babel}{KeepShorthandsActive}%
1306   {\let\bbl@restoreactive@gobble}%
1307   {\def\bbl@restoreactive#1{%
1308     \bbl@exp{%
1309       \\\AfterBabelLanguage\\CurrentOption
1310       {\catcode`#1=\the\catcode`#1\relax}%
1311       \\\AtEndOfPackage
1312       {\catcode`#1=\the\catcode`#1\relax}}}%
1313     \AtEndOfPackage{\let\bbl@restoreactive@gobble}}

```

\bbl@sh@select This command helps the shorthand supporting macros to select how to proceed. Note that this macro needs to be expandable as do all the shorthand macros in order for them to work in expansion-only environments such as the argument of \hyphenation.

This macro expects the name of a group of shorthands in its first argument and a shorthand character in its second argument. It will expand to either \bbl@firstcs or \bbl@scndcs. Hence two more arguments need to follow it.

```

1314 \def\bbl@sh@select#1#2{%
1315   \expandafter\ifx\csname#1@sh@#2@sel\endcsname\relax
1316     \bbl@afterelse\bbl@scndcs
1317   \else
1318     \bbl@afterfi\csname#1@sh@#2@sel\endcsname
1319   \fi}

```

\active@prefix The command \active@prefix which is used in the expansion of active characters has a function similar to \OT1-cmd in that it \protects the active character whenever \protect is *not* \@typeset@protect. The \@gobble is needed to remove a token such as \activechar: (when the double colon was the active character to be dealt with). There are two definitions, depending of \ifincsname is available. If there is, the expansion will be more robust.

```

1320 \begin@group

```

```

1321 \bbl@ifunset{ifincsname}% TODO. Ugly. Correct? Only Plain?
1322 {\gdef\active@prefix#1{%
1323   \ifx\protect\@typeset@protect
1324   \else
1325     \ifx\protect\@unexpandable@protect
1326     \noexpand#1%
1327     \else
1328     \protect#1%
1329     \fi
1330   \expandafter\@gobble
1331   \fi}}
1332 {\gdef\active@prefix#1{%
1333   \ifincsname
1334   \string#1%
1335   \expandafter\@gobble
1336   \else
1337     \ifx\protect\@typeset@protect
1338     \else
1339       \ifx\protect\@unexpandable@protect
1340       \noexpand#1%
1341       \else
1342       \protect#1%
1343       \fi
1344       \expandafter\expandafter\expandafter\@gobble
1345       \fi
1346     \fi}}
1347 \endgroup

```

`\if@safe@actives` In some circumstances it is necessary to be able to change the expansion of an active character on the fly. For this purpose the switch `@safe@actives` is available. The setting of this switch should be checked in the first level expansion of `\active@char<char>`.

```

1348 \newif\if@safe@actives
1349 \@safe@activesfalse

```

`\bbl@restore@actives` When the output routine kicks in while the active characters were made “safe” this must be undone in the headers to prevent unexpected typeset results. For this situation we define a command to make them “unsafe” again.

```

1350 \def\bbl@restore@actives{\if@safe@actives\@safe@activesfalse\fi}

```

`\bbl@activate` Both macros take one argument, like `\initiate@active@char`. The macro is used to change the definition of an active character to expand to `\active@char<char>` in the case of `\bbl@activate`, or `\normal@char<char>` in the case of `\bbl@deactivate`.

```

1351 \chardef\bbl@activated\z@
1352 \def\bbl@activate#1{%
1353   \chardef\bbl@activated\@ne
1354   \bbl@withactive{\expandafter\let\expandafter}#1%
1355   \csname bbl@active@\string#1\endcsname}
1356 \def\bbl@deactivate#1{%
1357   \chardef\bbl@activated\tw@
1358   \bbl@withactive{\expandafter\let\expandafter}#1%
1359   \csname bbl@normal@\string#1\endcsname}

```

`\bbl@firstcs` These macros are used only as a trick when declaring shorthands.

```

\bbl@scndcs
1360 \def\bbl@firstcs#1#2{\csname#1\endcsname}
1361 \def\bbl@scndcs#1#2{\csname#2\endcsname}

```

`\declare@shorthand` The command `\declare@shorthand` is used to declare a shorthand on a certain level. It takes three arguments:

1. a name for the collection of shorthands, i.e. ‘system’, or ‘dutch’;
2. the character (sequence) that makes up the shorthand, i.e. `~` or `"a`;
3. the code to be executed when the shorthand is encountered.

The auxiliary macro `\babel@texpdf` improves the interoperativity with `hyperref` and takes 4 arguments: (1) The \TeX code in text mode, (2) the string for `hyperref`, (3) the \TeX code in math mode, and (4), which is currently ignored, but it's meant for a string in math mode, like a minus sign instead of an hyphen (currently `hyperref` doesn't discriminate the mode). This macro may be used in `ldf` files.

```

1362 \def\babel@texpdf#1#2#3#4{%
1363   \ifx\texorpdfstring\undefined
1364     \textormath{#1}{#3}%
1365   \else
1366     \texorpdfstring{\textormath{#1}{#3}}{#2}%
1367     % \texorpdfstring{\textormath{#1}{#3}}{\textormath{#2}{#4}}%
1368   \fi}
1369 %
1370 \def\declare@shorthand#1#2{\@decl@short{#1}#2\@nil}
1371 \def\@decl@short#1#2#3\@nil#4{%
1372   \def\bbl@tempa{#3}%
1373   \ifx\bbl@tempa\empty
1374     \expandafter\let\csname #1@sh@\string#2@sel\endcsname\bbl@scndcs
1375     \bbl@ifunset{#1@sh@\string#2@}{}%
1376     {\def\bbl@tempa{#4}%
1377      \expandafter\ifx\csname#1@sh@\string#2@\endcsname\bbl@tempa
1378      \else
1379        \bbl@info
1380          {Redefining #1 shorthand \string#2\%
1381           in language \CurrentOption}%
1382      \fi}%
1383     \@namedef{#1@sh@\string#2@}{#4}%
1384   \else
1385     \expandafter\let\csname #1@sh@\string#2@sel\endcsname\bbl@firstcs
1386     \bbl@ifunset{#1@sh@\string#2@\string#3@}{}%
1387     {\def\bbl@tempa{#4}%
1388      \expandafter\ifx\csname#1@sh@\string#2@\string#3@\endcsname\bbl@tempa
1389      \else
1390        \bbl@info
1391          {Redefining #1 shorthand \string#2\string#3\%
1392           in language \CurrentOption}%
1393      \fi}%
1394     \@namedef{#1@sh@\string#2@\string#3@}{#4}%
1395   \fi}

```

`\textormath` Some of the shorthands that will be declared by the language definition files have to be usable in both text and mathmode. To achieve this the helper macro `\textormath` is provided.

```

1396 \def\textormath{%
1397   \ifmmode
1398     \expandafter\@secondoftwo
1399   \else
1400     \expandafter\@firstoftwo
1401   \fi}

```

`\user@group` The current concept of ‘shorthands’ supports three levels or groups of shorthands. For each level the name of the level or group is stored in a macro. The default is to have a user group; use language group ‘english’ and have a system group called ‘system’.

```

1402 \def\user@group{user}
1403 \def\language@group{english} % TODO. I don't like defaults
1404 \def\system@group{system}

```

`\usesshorthands` This is the user level macro. It initializes and activates the character for use as a shorthand character (ie, it's active in the preamble). Languages can deactivate shorthands, so a starred version is also provided which activates them always after the language has been switched.

```

1405 \def\usesshorthands{%
1406   \@ifstar\bbl@usesesh@s{\bbl@usesesh@x{}}
1407 \def\bbl@usesesh@s#1{%

```

```

1408 \bbl@usesesh@x
1409 {\AddBabelHook{babel-sh-\string#1}{afterextras}{\bbl@activate{#1}}}%
1410 {#1}}
1411 \def\bbl@usesesh@x#1#2{%
1412 \bbl@ifshorthand{#2}%
1413 {\def\user@group{user}%
1414 \initiate@active@char{#2}%
1415 #1%
1416 \bbl@activate{#2}}%
1417 {\bbl@error
1418 {I can't declare a shorthand turned off (\string#2)}
1419 {Sorry, but you can't use shorthands which have been\\%
1420 turned off in the package options}}}

```

`\defineshorthand` Currently we only support two groups of user level shorthands, named internally `user` and `user@<lang>` (language-dependent user shorthands). By default, only the first one is taken into account, but if the former is also used (in the optional argument of `\defineshorthand`) a new level is inserted for it (`user@generic`, done by `\bbl@set@user@generic`); we make also sure `{}` and `\protect` are taken into account in this new top level.

```

1421 \def\user@language@group{user@\language@group}
1422 \def\bbl@set@user@generic#1#2{%
1423 \bbl@ifunset{user@generic@active#1}%
1424 {\bbl@active@def#1\user@language@group{user@active}{user@generic@active}%
1425 \bbl@active@def#1\user@group{user@generic@active}{language@active}%
1426 \expandafter\edef\csname#2@sh@#1@@\endcsname{%
1427 \expandafter\noexpand\csname normal@char#1\endcsname}%
1428 \expandafter\edef\csname#2@sh@#1@\string\protect@\endcsname{%
1429 \expandafter\noexpand\csname user@active#1\endcsname}}%
1430 \@empty}
1431 \newcommand\defineshorthand[3][user]{%
1432 \edef\bbl@tempa{\zap@space#1 \@empty}%
1433 \bbl@for\bbl@tempb\bbl@tempa{%
1434 \if*\expandafter\@car\bbl@tempb\@nil
1435 \edef\bbl@tempb{user@\expandafter\@gobble\bbl@tempb}%
1436 \@expandtwoargs
1437 \bbl@set@user@generic{\expandafter\string\@car#2\@nil}\bbl@tempb
1438 \fi
1439 \declare@shorthand{\bbl@tempb}{#2}{#3}}}

```

`\languageshorthands` A user level command to change the language from which shorthands are used. Unfortunately, `babel` currently does not keep track of defined groups, and therefore there is no way to catch a possible change in casing to fix it in the same way languages names are fixed. [TODO].

```

1440 \def\languageshorthands#1{\def\language@group{#1}}

```

`\aliasshorthand` First the new shorthand needs to be initialized. Then, we define the new shorthand in terms of the original one, but note with `\aliasshorthands{"}{/}` is `\active@prefix /active@char/`, so we still need to let the latest to `\active@char`.

```

1441 \def\aliasshorthand#1#2{%
1442 \bbl@ifshorthand{#2}%
1443 {\expandafter\ifx\csname active@char\string#2\endcsname\relax
1444 \ifx\document\@notprerr
1445 \@notshorthand{#2}%
1446 \else
1447 \initiate@active@char{#2}%
1448 \expandafter\let\csname active@char\string#2\expandafter\endcsname
1449 \csname active@char\string#1\endcsname
1450 \expandafter\let\csname normal@char\string#2\expandafter\endcsname
1451 \csname normal@char\string#1\endcsname
1452 \bbl@activate{#2}%
1453 \fi
1454 \fi}%
1455 {\bbl@error
1456 {Cannot declare a shorthand turned off (\string#2)}}

```

```

1457     {Sorry, but you cannot use shorthands which have been\\%
1458     turned off in the package options}}

\@notshorthand
1459 \def\@notshorthand#1{%
1460   \bbl@error{%
1461     The character '\string #1' should be made a shorthand character;\\%
1462     add the command \string\usesshorthands\string{#1\string} to
1463     the preamble.\\%
1464     I will ignore your instruction}%
1465   {You may proceed, but expect unexpected results}}

\shorthandon The first level definition of these macros just passes the argument on to \bbl@switch@sh, adding
\shorthandoff \@nil at the end to denote the end of the list of characters.

1466 \newcommand*\shorthandon[1]{\bbl@switch@sh\@ne#1\@nnil}
1467 \DeclareRobustCommand*\shorthandoff{%
1468   \@ifstar{\bbl@shorthandoff\tw@}{\bbl@shorthandoff\z@}}
1469 \def\bbl@shorthandoff#1#2{\bbl@switch@sh#1#2\@nnil}

\bbl@switch@sh The macro \bbl@switch@sh takes the list of characters apart one by one and subsequently switches
the category code of the shorthand character according to the first argument of \bbl@switch@sh.
But before any of this switching takes place we make sure that the character we are dealing with is
known as a shorthand character. If it is, a macro such as \active@char" should exist.
Switching off and on is easy – we just set the category code to ‘other’ (12) and \active. With the
starred version, the original catcode and the original definition, saved in \initiate@active@char,
are restored.

1470 \def\bbl@switch@sh#1#2{%
1471   \ifx#2\@nnil\else
1472     \bbl@ifunset{\bbl@active@\string#2}%
1473     {\bbl@error
1474       {I can't switch '\string#2' on or off--not a shorthand}%
1475       {This character is not a shorthand. Maybe you made\\%
1476         a typing mistake? I will ignore your instruction.}}%
1477     {\ifcase#1%   off, on, off*
1478       \catcode`#2\relax
1479     \or
1480       \catcode`#2\active
1481       \bbl@ifunset{\bbl@shdef@\string#2}%
1482       {}%
1483       {\bbl@withactive{\expandafter\let\expandafter}\#2%
1484         \csname bbl@shdef@\string#2\endcsname
1485         \bbl@csarg\let{shdef@\string#2}\relax}%
1486       \ifcase\bbl@activated\or
1487         \bbl@activate{#2}%
1488       \else
1489         \bbl@deactivate{#2}%
1490       \fi
1491     \or
1492       \bbl@ifunset{\bbl@shdef@\string#2}%
1493       {\bbl@withactive{\bbl@csarg\let{shdef@\string#2}}#2}%
1494       {}%
1495       \csname bbl@oricat@\string#2\endcsname
1496       \csname bbl@oridef@\string#2\endcsname
1497     \fi}%
1498   \bbl@afterfi\bbl@switch@sh#1%
1499   \fi}

Note the value is that at the expansion time; eg, in the preamble shorthands are usually deactivated.

1500 \def\babelshorthand{\active@prefix\babelshorthand\bbl@putsh}
1501 \def\bbl@putsh#1{%
1502   \bbl@ifunset{\bbl@active@\string#1}%
1503   {\bbl@putsh@i#1\@empty\@nnil}%
1504   {\csname bbl@active@\string#1\endcsname}}

```

```

1505 \def\bb1@putsh@i#1#2\@nnil{%
1506   \csname\language@group @sh@\string#1@%
1507     \ifx\@empty#2\else\string#2@\fi\endcsname}
1508 \ifx\bb1@opt@shorthands\@nnil\else
1509   \let\bb1@s@initiate@active@char\initiate@active@char
1510   \def\initiate@active@char#1{%
1511     \bb1@ifshorthand{#1}{\bb1@s@initiate@active@char{#1}}{}}
1512   \let\bb1@s@switch@sh\bb1@switch@sh
1513   \def\bb1@switch@sh#1#2{%
1514     \ifx#2\@nnil\else
1515       \bb1@afterfi
1516       \bb1@ifshorthand{#2}{\bb1@s@switch@sh#1{#2}}{\bb1@switch@sh#1}%
1517     \fi}
1518   \let\bb1@s@activate\bb1@activate
1519   \def\bb1@activate#1{%
1520     \bb1@ifshorthand{#1}{\bb1@s@activate{#1}}{}}
1521   \let\bb1@s@deactivate\bb1@deactivate
1522   \def\bb1@deactivate#1{%
1523     \bb1@ifshorthand{#1}{\bb1@s@deactivate{#1}}{}}
1524 \fi

```

You may want to test if a character is a shorthand. Note it does not test whether the shorthand is on or off.

```

1525 \newcommand\ifbabelshorthand[3]{\bb1@ifunset{bb1@active@\string#1}{#3}{#2}}

```

`\bb1@prim@s` One of the internal macros that are involved in substituting `\prime` for each right quote in
`\bb1@pr@m@s` mathmode is `\prim@s`. This checks if the next character is a right quote. When the right quote is active, the definition of this macro needs to be adapted to look also for an active right quote; the hat could be active, too.

```

1526 \def\bb1@prim@s{%
1527   \prime\futurelet\@let@token\bb1@pr@m@s}
1528 \def\bb1@if@primes#1#2{%
1529   \ifx#1\@let@token
1530     \expandafter\@firstoftwo
1531   \else\ifx#2\@let@token
1532     \bb1@afterelse\expandafter\@firstoftwo
1533   \else
1534     \bb1@afterfi\expandafter\@secondoftwo
1535   \fi\fi}
1536 \begingroup
1537 \catcode`\^=7 \catcode`\*= \active \lccode`\*=`^
1538 \catcode`\'=12 \catcode`\`= \active \lccode`\`= ` '
1539 \lowercase{%
1540   \gdef\bb1@pr@m@s{%
1541     \bb1@if@primes""%
1542     \pr@@@s
1543     {\bb1@if@primes*\^*\pr@@@t\egroup}}
1544 \endgroup

```

Usually the `~` is active and expands to `\penalty\@M_{}`. When it is written to the `.aux` file it is written expanded. To prevent that and to be able to use the character `~` as a start character for a shorthand, it is redefined here as a one character shorthand on system level. The system declaration is in most cases redundant (when `~` is still a non-break space), and in some cases is inconvenient (if `~` has been redefined); however, for backward compatibility it is maintained (some existing documents may rely on the `babel` value).

```

1545 \initiate@active@char{~}
1546 \declare@shorthand{system}{~}{\leavevmode\nobreak\ }
1547 \bb1@activate{~}

```

`\OT1dpos` The position of the double quote character is different for the OT1 and T1 encodings. It will later be
`\T1dpos` selected using the `\f@encoding` macro. Therefore we define two macros here to store the position of the character in these encodings.

```

1548 \expandafter\def\csname OT1dpos\endcsname{127}
1549 \expandafter\def\csname T1dpos\endcsname{4}

```


When the macro `\f@encoding` is undefined (as it is in plain $\text{T}_{\text{E}}\text{X}$) we define it here to expand to `OT1`

```
1550 \ifx\f@encoding\undefined
1551   \def\f@encoding{OT1}
1552 \fi
```

7.6 Language attributes

Language attributes provide a means to give the user control over which features of the language definition files he wants to enable.

`\languageattribute` The macro `\languageattribute` checks whether its arguments are valid and then activates the selected language attribute. First check whether the language is known, and then process each attribute in the list.

```
1553 \bbl@trace{Language attributes}
1554 \newcommand\languageattribute[2]{%
1555   \def\bbl@tempc{#1}%
1556   \bbl@fixname\bbl@tempc
1557   \bbl@iflanguage\bbl@tempc{%
1558     \bbl@vforeach{#2}{%
```

We want to make sure that each attribute is selected only once; therefore we store the already selected attributes in `\bbl@known@attrs`. When that control sequence is not yet defined this attribute is certainly not selected before.

```
1559     \ifx\bbl@known@attrs\undefined
1560       \in@false
1561     \else
1562       \bbl@xin@{,\bbl@tempc-##1,}{,\bbl@known@attrs,}%
1563     \fi
1564     \ifin@
1565       \bbl@warning{%
1566         You have more than once selected the attribute '##1'\%
1567         for language #1. Reported}%
1568     \else
```

When we end up here the attribute is not selected before. So, we add it to the list of selected attributes and execute the associated $\text{T}_{\text{E}}\text{X}$ -code.

```
1569       \bbl@exp{%
1570         \\bbl@add@list\\bbl@known@attrs{\bbl@tempc-##1}}%
1571       \edef\bbl@tempa{\bbl@tempc-##1}%
1572       \expandafter\bbl@ifknown@trib\expandafter{\bbl@tempa}\bbl@attributes%
1573       {\csname\bbl@tempc @attr##1\endcsname}%
1574       {\@attrerr{\bbl@tempc}{##1}}%
1575       \fi}}%
1576 \@onlypreamble\languageattribute
```

The error text to be issued when an unknown attribute is selected.

```
1577 \newcommand*{\@attrerr}[2]{%
1578   \bbl@error
1579   {The attribute #2 is unknown for language #1.}%
1580   {Your command will be ignored, type <return> to proceed}}
```

`\bbl@declare@ttribute` This command adds the new language/attribute combination to the list of known attributes. Then it defines a control sequence to be executed when the attribute is used in a document. The result of this should be that the macro `\extras...` for the current language is extended, otherwise the attribute will not work as its code is removed from memory at `\begin{document}`.

```
1581 \def\bbl@declare@ttribute#1#2#3{%
1582   \bbl@xin@{,#2,}{,\BabelModifiers,}%
1583   \ifin@
1584     \AfterBabelLanguage{#1}{\languageattribute{#1}{#2}}%
1585   \fi
1586   \bbl@add@list\bbl@attributes{#1-#2}%
1587   \expandafter\def\csname#1@attr#2\endcsname{#3}}
```

`\bbl@ifattributeset` This internal macro has 4 arguments. It can be used to interpret \TeX code based on whether a certain attribute was set. This command should appear inside the argument to `\AtBeginDocument` because the attributes are set in the document preamble, *after* `babel` is loaded. The first argument is the language, the second argument the attribute being checked, and the third and fourth arguments are the true and false clauses.

```

1588 \def\bbl@ifattributeset#1#2#3#4{%
1589   \ifx\bbl@known@attrs\@undefined
1590     \in@false
1591   \else
1592     \bbl@xin@{,#1-#2,}{,\bbl@known@attrs,}%
1593   \fi
1594   \ifin@
1595     \bbl@afterelse#3%
1596   \else
1597     \bbl@afterfi#4%
1598   \fi}

```

`\bbl@ifknown@ttrib` An internal macro to check whether a given language/attribute is known. The macro takes 4 arguments, the language/attribute, the attribute list, the \TeX -code to be executed when the attribute is known and the \TeX -code to be executed otherwise. We first assume the attribute is unknown. Then we loop over the list of known attributes, trying to find a match.

```

1599 \def\bbl@ifknown@ttrib#1#2{%
1600   \let\bbl@tempa\@secondoftwo
1601   \bbl@loopx\bbl@tempb{#2}{%
1602     \expandafter\in@\expandafter{\expandafter,\bbl@tempb,}{,#1,}%
1603   \ifin@
1604     \let\bbl@tempa\@firstoftwo
1605   \else
1606   \fi}%
1607   \bbl@tempa}

```

`\bbl@clear@ttribs` This macro removes all the attribute code from \TeX 's memory at `\begin{document}` time (if any is present).

```

1608 \def\bbl@clear@ttribs{%
1609   \ifx\bbl@attributes\@undefined\else
1610     \bbl@loopx\bbl@tempa{\bbl@attributes}{%
1611       \expandafter\bbl@clear@ttrib\bbl@tempa.
1612     }%
1613     \let\bbl@attributes\@undefined
1614   \fi}
1615 \def\bbl@clear@ttrib#1-#2.{%
1616   \expandafter\let\csname#1@attr#2\endcsname\@undefined}
1617 \AtBeginDocument{\bbl@clear@ttribs}

```

7.7 Support for saving macro definitions

To save the meaning of control sequences using `\babel@save`, we use temporary control sequences. To save hash table entries for these control sequences, we don't use the name of the control sequence to be saved to construct the temporary name. Instead we simply use the value of a counter, which is reset to zero each time we begin to save new values. This works well because we release the saved meanings before we begin to save a new set of control sequence meanings (see `\selectlanguage` and `\originalTeX`). Note undefined macros are not undefined any more when saved – they are *\relax'ed*.

`\babel@savecnt` The initialization of a new save cycle: reset the counter to zero.
`\babel@beginsave`

```

1618 \bbl@trace{Macros for saving definitions}
1619 \def\babel@beginsave{\babel@savecnt\z@}

```

Before it's forgotten, allocate the counter and initialize all.

```

1620 \newcount\babel@savecnt
1621 \babel@beginsave

```

`\babel@save` The macro `\babel@save⟨csize⟩` saves the current meaning of the control sequence `⟨csize⟩` to `\originalTeX`³². To do this, we let the current meaning to a temporary control sequence, the restore commands are appended to `\originalTeX` and the counter is incremented. The macro `\babel@savevariable⟨variable⟩` saves the value of the variable. `⟨variable⟩` can be anything allowed after the `\the` primitive.

```

1622 \def\babel@save#1{%
1623   \expandafter\let\csname babel@number\babel@savecnt\endcsname#1\relax
1624   \toks@\expandafter{\originalTeX\let#1=}%
1625   \bbl@exp{%
1626     \def\originalTeX{\the\toks@\<babel@number\babel@savecnt>\relax}}%
1627   \advance\babel@savecnt\@ne}
1628 \def\babel@savevariable#1{%
1629   \toks@\expandafter{\originalTeX #1=}%
1630   \bbl@exp{\def\originalTeX{\the\toks@\the#1\relax}}}
```

`\bbl@frenchspacing` Some languages need to have `\frenchspacing` in effect. Others don't want that. The command `\bbl@frenchspacing` switches it on when it isn't already in effect and `\bbl@nonfrenchspacing` switches it off if necessary. A more refined way to switch the catcodes is done with ini files. Here an auxiliary macro is defined, but the main part is in `\babelprovide`. This new method should be ideally the default one.

```

1631 \def\bbl@frenchspacing{%
1632   \ifnum\the\scode`\.=\@m
1633     \let\bbl@nonfrenchspacing\relax
1634   \else
1635     \frenchspacing
1636     \let\bbl@nonfrenchspacing\nonfrenchspacing
1637   \fi}
1638 \let\bbl@nonfrenchspacing\nonfrenchspacing
1639 \let\bbl@elt\relax
1640 \edef\bbl@fs@chars{%
1641   \bbl@elt{\string.}\@m{3000}\bbl@elt{\string?}\@m{3000}%
1642   \bbl@elt{\string!}\@m{3000}\bbl@elt{\string:}\@m{2000}%
1643   \bbl@elt{\string;}\@m{1500}\bbl@elt{\string,}\@m{1250}}
1644 \def\bbl@pre@fs{%
1645   \def\bbl@elt##1##2##3{\scode`##1=\the\scode`##1\relax}%
1646   \edef\bbl@save@sfcodes{\bbl@fs@chars}}%
1647 \def\bbl@post@fs{%
1648   \bbl@save@sfcodes
1649   \edef\bbl@tempa{\bbl@cl{frspc}}%
1650   \edef\bbl@tempa{\expandafter\@car\bbl@tempa\@nil}%
1651   \if u\bbl@tempa      % do nothing
1652   \else\if n\bbl@tempa % non french
1653     \def\bbl@elt##1##2##3{%
1654       \ifnum\scode`##1=##2\relax
1655       \babel@savevariable{\scode`##1}%
1656       \scode`##1=##3\relax
1657     \fi}%
1658     \bbl@fs@chars
1659   \else\if y\bbl@tempa % french
1660     \def\bbl@elt##1##2##3{%
1661       \ifnum\scode`##1=##3\relax
1662       \babel@savevariable{\scode`##1}%
1663       \scode`##1=##2\relax
1664     \fi}%
1665     \bbl@fs@chars
1666   \fi\fi\fi}
```

7.8 Short tags

`\babeltags` This macro is straightforward. After zapping spaces, we loop over the list and define the macros `\text⟨tag⟩` and `\⟨tag⟩`. Definitions are first expanded so that they don't contain `\csize` but the

³²`\originalTeX` has to be expandable, i.e. you shouldn't let it to `\relax`.

actual macro.

```

1667 \bbl@trace{Short tags}
1668 \def\babeltags#1{%
1669   \edef\bbl@tempa{\zap@space#1 \@empty}%
1670   \def\bbl@tempb##1=##2\@{%
1671     \edef\bbl@tempc{%
1672       \noexpand\newcommand
1673       \expandafter\noexpand\csname ##1\endcsname{%
1674         \noexpand\protect
1675         \expandafter\noexpand\csname otherlanguage*\endcsname{##2}}
1676       \noexpand\newcommand
1677       \expandafter\noexpand\csname text##1\endcsname{%
1678         \noexpand\foreignlanguage{##2}}
1679     \bbl@tempc}%
1680   \bbl@for\bbl@tempa\bbl@tempa{%
1681     \expandafter\bbl@tempb\bbl@tempa\@{}}

```

7.9 Hyphens

`\babelhyphenation` This macro saves hyphenation exceptions. Two macros are used to store them: `\bbl@hyphenation@` for the global ones and `\bbl@hyphenation<lang>` for language ones. See `\bbl@patterns` above for further details. We make sure there is a space between words when multiple commands are used.

```

1682 \bbl@trace{Hyphens}
1683 \@onlypreamble\babelhyphenation
1684 \AtEndOfPackage{%
1685   \newcommand\babelhyphenation[2][\@empty]{%
1686     \ifx\bbl@hyphenation@relax
1687       \let\bbl@hyphenation@\@empty
1688     \fi
1689     \ifx\bbl@hyphlist\@empty\else
1690       \bbl@warning{%
1691         You must not intermingle \string\selectlanguage\space and\\%
1692         \string\babelhyphenation\space or some exceptions will not\\%
1693         be taken into account. Reported}%
1694     \fi
1695     \ifx\@empty#1%
1696       \protected@edef\bbl@hyphenation@{\bbl@hyphenation@\space#2}%
1697     \else
1698       \bbl@vforeach{#1}{%
1699         \def\bbl@tempa{##1}%
1700         \bbl@fixname\bbl@tempa
1701         \bbl@iflanguage\bbl@tempa{%
1702           \bbl@csarg\protected@edef{hyphenation@\bbl@tempa}{%
1703             \bbl@ifunset{bbl@hyphenation@\bbl@tempa}%
1704             {}%
1705             {\csname bbl@hyphenation@\bbl@tempa\endcsname\space}%
1706             #2}}}%
1707       \fi}}

```

`\bbl@allowhyphens` This macro makes hyphenation possible. Basically its definition is nothing more than `\nobreak \hskip 0pt plus 0pt`³³.

```

1708 \def\bbl@allowhyphens{\ifvmode\else\nobreak\hskip\z@skip\fi}
1709 \def\bbl@t@one{T1}
1710 \def\allowhyphens{\ifx\cf@encoding\bbl@t@one\else\bbl@allowhyphens\fi}

```

`\babelhyphen` Macros to insert common hyphens. Note the space before `@` in `\babelhyphen`. Instead of protecting it with `\DeclareRobustCommand`, which could insert a `\relax`, we use the same procedure as shorthands, with `\active@prefix`.

```

1711 \newcommand\babelnullhyphen{\char\hyphenchar\font}
1712 \def\babelhyphen{\active@prefix\babelhyphen\bbl@hyphen}

```

³³ \TeX begins and ends a word for hyphenation at a glue node. The penalty prevents a linebreak at this glue node.

```

1713 \def\bbl@hyphen{%
1714   \@ifstar{\bbl@hyphen@i @}{\bbl@hyphen@i \@empty}}
1715 \def\bbl@hyphen@i#1#2{%
1716   \bbl@ifunset{\bbl@hy@#1#2\@empty}%
1717   {\csname bbl@#1usehyphen\endcsname{\discretionary{#2}{}{#2}}}%
1718   {\csname bbl@hy@#1#2\@empty\endcsname}}

```

The following two commands are used to wrap the “hyphen” and set the behavior of the rest of the word – the version with a single @ is used when further hyphenation is allowed, while that with @@ if no more hyphens are allowed. In both cases, if the hyphen is preceded by a positive space, breaking after the hyphen is disallowed.

There should not be a discretionary after a hyphen at the beginning of a word, so it is prevented if preceded by a skip. Unfortunately, this does handle cases like “(-suffix)”. \nobreak is always preceded by \leavevmode, in case the shorthand starts a paragraph.

```

1719 \def\bbl@usehyphen#1{%
1720   \leavevmode
1721   \ifdim\lastskip>\z@\mbox{#1}\else\nobreak#1\fi
1722   \nobreak\hskip\z@skip}
1723 \def\bbl@@usehyphen#1{%
1724   \leavevmode\ifdim\lastskip>\z@\mbox{#1}\else#1\fi}

```

The following macro inserts the hyphen char.

```

1725 \def\bbl@hyphenchar{%
1726   \ifnum\hyphenchar\font=\m@ne
1727     \babe\nullhyphen
1728   \else
1729     \char\hyphenchar\font
1730   \fi}

```

Finally, we define the hyphen “types”. Their names will not change, so you may use them in ldf’s. After a space, the \mbox in \bbl@hy@nobreak is redundant.

```

1731 \def\bbl@hy@soft{\bbl@usehyphen{\discretionary{\bbl@hyphenchar}{}}{}}
1732 \def\bbl@hy@@soft{\bbl@@usehyphen{\discretionary{\bbl@hyphenchar}{}}{}}
1733 \def\bbl@hy@hard{\bbl@usehyphen\bbl@hyphenchar}
1734 \def\bbl@hy@@hard{\bbl@@usehyphen\bbl@hyphenchar}
1735 \def\bbl@hy@nobreak{\bbl@usehyphen{\mbox{\bbl@hyphenchar}}}
1736 \def\bbl@hy@@nobreak{\mbox{\bbl@hyphenchar}}
1737 \def\bbl@hy@repeat{%
1738   \bbl@usehyphen{%
1739     \discretionary{\bbl@hyphenchar}{\bbl@hyphenchar}{\bbl@hyphenchar}}
1740 \def\bbl@hy@@repeat{%
1741   \bbl@@usehyphen{%
1742     \discretionary{\bbl@hyphenchar}{\bbl@hyphenchar}{\bbl@hyphenchar}}
1743 \def\bbl@hy@empty{\hskip\z@skip}
1744 \def\bbl@hy@@empty{\discretionary{}{}{}}

```

`\bbl@disc` For some languages the macro `\bbl@disc` is used to ease the insertion of discretionaries for letters that behave ‘abnormally’ at a breakpoint.

```

1745 \def\bbl@disc#1#2{\nobreak\discretionary{#2-}{}{#1}\bbl@allowhyphens}

```

7.10 Multiencoding strings

The aim following commands is to provide a common interface for strings in several encodings. They also contains several hooks which can be used by luatex and xetex. The code is organized here with pseudo-guards, so we start with the basic commands.

Tools But first, a couple of tools. The first one makes global a local variable. This is not the best solution, but it works.

```

1746 \bbl@trace{Multiencoding strings}
1747 \def\bbl@tglobal#1{\global\let#1#1}
1748 \def\bbl@recatcode#1{% TODO. Used only once?
1749   \@tempcnta="7F
1750   \def\bbl@tempa{%

```

```

1751 \ifnum\@tempcnta>"FF\else
1752 \catcode\@tempcnta=#1\relax
1753 \advance\@tempcnta\@ne
1754 \expandafter\bb1@tempa
1755 \fi}%
1756 \bb1@tempa}

```

The second one. We need to patch `\@uclclist`, but it is done once and only if `\SetCase` is used or if strings are encoded. The code is far from satisfactory for several reasons, including the fact `\@uclclist` is not a list any more. Therefore a package option is added to ignore it. Instead of gobbling the macro getting the next two elements (usually `\reserved@a`), we pass it as argument to `\bb1@ucllc`. The parser is restarted inside `\<lang>\bb1@ucllc` because we do not know how many expansions are necessary (depends on whether strings are encoded). The last part is tricky – when uppercasing, we have:

```
\let\bb1@tolower\@empty\bb1@toupper\@empty
```

and starts over (and similarly when lowercasing).

```

1757 \ifpackagewith{babel}{nocase}%
1758 {\let\bb1@patchucllc\relax}%
1759 {\def\bb1@patchucllc{%
1760 \global\let\bb1@patchucllc\relax
1761 \g@addto@macro\@uclclist{\reserved@b{\reserved@b\bb1@ucllc}}%
1762 \gdef\bb1@ucllc##1{%
1763 \let\bb1@encoded\bb1@encoded@ucllc
1764 \bb1@ifunset{\language @bb1@ucllc}% and resumes it
1765 {##1}%
1766 {\let\bb1@tempa##1\relax % Used by LANG@bb1@ucllc
1767 \csname\language @bb1@ucllc\endcsname}%
1768 {\bb1@tolower\@empty}\bb1@toupper\@empty}}%
1769 \gdef\bb1@tolower{\csname\language @bb1@lc\endcsname}%
1770 \gdef\bb1@toupper{\csname\language @bb1@uc\endcsname}}%
1771 <<(*More package options)>> ≡
1772 \DeclareOption{nocase}{}
1773 <</More package options>>

```

The following package options control the behavior of `\SetString`.

```

1774 <<(*More package options)>> ≡
1775 \let\bb1@opt@strings\@nnil % accept strings=value
1776 \DeclareOption{strings}{\def\bb1@opt@strings{\BabelStringsDefault}}
1777 \DeclareOption{strings=encoded}{\let\bb1@opt@strings\relax}
1778 \def\BabelStringsDefault{generic}
1779 <</More package options>>

```

Main command This is the main command. With the first use it is redefined to omit the basic setup in subsequent blocks. We make sure strings contain actual letters in the range 128-255, not active characters.

```

1780 \@onlypreamble\StartBabelCommands
1781 \def\StartBabelCommands{%
1782 \begingroup
1783 \bb1@recatcode{11}%
1784 <<Macros local to BabelCommands>>
1785 \def\bb1@provstring##1##2{%
1786 \providecommand##1{##2}%
1787 \bb1@tglobal##1}%
1788 \global\let\bb1@scafter\@empty
1789 \let\StartBabelCommands\bb1@startcmds
1790 \ifx\BabelLanguages\relax
1791 \let\BabelLanguages\CurrentOption
1792 \fi
1793 \begingroup
1794 \let\bb1@screset\@nnil % local flag - disable 1st stopcommands

```

```

1795 \StartBabelCommands}
1796 \def\bb1@startcmds{%
1797   \ifx\bb1@screset\@nnil\else
1798     \bb1@usehooks{stopcommands}}}%
1799 \fi
1800 \endgroup
1801 \begingroup
1802 \@ifstar
1803   {\ifx\bb1@opt@strings\@nnil
1804     \let\bb1@opt@strings\BabelStringsDefault
1805     \fi
1806     \bb1@startcmds@i}%
1807   \bb1@startcmds@i}
1808 \def\bb1@startcmds@i#1#2{%
1809   \edef\bb1@L{\zap@space#1 \@empty}%
1810   \edef\bb1@G{\zap@space#2 \@empty}%
1811   \bb1@startcmds@ii}
1812 \let\bb1@startcommands\StartBabelCommands

```

Parse the encoding info to get the label, input, and font parts.

Select the behavior of \SetString. There are two main cases, depending of if there is an optional argument: without it and strings=encoded, strings are defined always; otherwise, they are set only if they are still undefined (ie, fallback values). With labelled blocks and strings=encoded, define the strings, but with another value, define strings only if the current label or font encoding is the value of strings; otherwise (ie, no strings or a block whose label is not in strings=) do nothing.

We presume the current block is not loaded, and therefore set (above) a couple of default values to gobble the arguments. Then, these macros are redefined if necessary according to several parameters.

```

1813 \newcommand\bb1@startcmds@ii[1][\@empty]{%
1814   \let\SetString\@gobbletwo
1815   \let\bb1@stringdef\@gobbletwo
1816   \let\AfterBabelCommands\@gobble
1817   \ifx\@empty#1%
1818     \def\bb1@sc@label{generic}%
1819     \def\bb1@encstring###1##2{%
1820       \ProvideTextCommandDefault##1{##2}%
1821       \bb1@tglobal##1%
1822       \expandafter\bb1@tglobal\curname\string? \string##1\endcurname}%
1823     \let\bb1@sctest\in@true
1824   \else
1825     \let\bb1@sc@charset\space % <- zapped below
1826     \let\bb1@sc@fontenc\space % <- " "
1827     \def\bb1@tempa##1=##2\@nil{%
1828       \bb1@csarg\edef{sc@\zap@space##1 \@empty}{##2 }}%
1829     \bb1@vforeach{label=#1}{\bb1@tempa##1\@nil}%
1830     \def\bb1@tempa##1 ##2{% space -> comma
1831       ##1%
1832       \ifx\@empty##2\else\ifx,##1,\else,\fi\bb1@afterfi\bb1@tempa##2\fi}%
1833     \edef\bb1@sc@fontenc{\expandafter\bb1@tempa\bb1@sc@fontenc\@empty}%
1834     \edef\bb1@sc@label{\expandafter\zap@space\bb1@sc@label\@empty}%
1835     \edef\bb1@sc@charset{\expandafter\zap@space\bb1@sc@charset\@empty}%
1836     \def\bb1@encstring###1##2{%
1837       \bb1@foreach\bb1@sc@fontenc{%
1838         \bb1@ifunset{T@####1}%
1839         }%
1840         {\ProvideTextCommand##1{####1}{##2}%
1841         \bb1@tglobal##1%
1842         \expandafter
1843         \bb1@tglobal\curname####1\string##1\endcurname}}}%
1844     \def\bb1@sctest{%
1845       \bb1@xin@{\bb1@opt@strings,}{,\bb1@sc@label,\bb1@sc@fontenc,}}%
1846   \fi
1847   \ifx\bb1@opt@strings\@nnil % ie, no strings key -> defaults

```

```

1848 \else\ifx\bbbl@opt@strings\relax % ie, strings=encoded
1849 \let\AfterBabelCommands\bbbl@aftercmds
1850 \let\SetString\bbbl@setstring
1851 \let\bbbl@stringdef\bbbl@encstring
1852 \else % ie, strings=value
1853 \bbbl@sctest
1854 \ifin@
1855 \let\AfterBabelCommands\bbbl@aftercmds
1856 \let\SetString\bbbl@setstring
1857 \let\bbbl@stringdef\bbbl@provstring
1858 \fi\fi\fi
1859 \bbbl@scswitch
1860 \ifx\bbbl@G\empty
1861 \def\SetString##1##2{%
1862 \bbbl@error{Missing group for string \string##1}%
1863 {You must assign strings to some category, typically\\%
1864 captions or extras, but you set none}}%
1865 \fi
1866 \ifx\@empty#1%
1867 \bbbl@usehooks{defaultcommands}{}%
1868 \else
1869 \@expandtwoargs
1870 \bbbl@usehooks{encodedcommands}{\bbbl@sc@charset}{\bbbl@sc@fontenc}}%
1871 \fi}

```

There are two versions of `\bbbl@scswitch`. The first version is used when ldfs are read, and it makes sure `\group\language` is reset, but only once (`\bbbl@screset` is used to keep track of this). The second version is used in the preamble and packages loaded after babel and does nothing. The macro `\bbbl@forlang` loops `\bbbl@L` but its body is executed only if the value is in `\BabelLanguages` (inside babel) or `\date\language` is defined (after babel has been loaded). There are also two version of `\bbbl@forlang`. The first one skips the current iteration if the language is not in `\BabelLanguages` (used in ldfs), and the second one skips undefined languages (after babel has been loaded).

```

1872 \def\bbbl@forlang#1#2{%
1873 \bbbl@for#1\bbbl@L{%
1874 \bbbl@xin@{, #1, }, \BabelLanguages,}%
1875 \ifin@#2\relax\fi}}
1876 \def\bbbl@scswitch{%
1877 \bbbl@forlang\bbbl@tempa{%
1878 \ifx\bbbl@G\empty\else
1879 \ifx\SetString\gobbletwo\else
1880 \edef\bbbl@GL{\bbbl@G\bbbl@tempa}%
1881 \bbbl@xin@{, \bbbl@GL, }, \bbbl@screset,}%
1882 \ifin@\else
1883 \global\expandafter\let\csname\bbbl@GL\endcsname\@undefined
1884 \xdef\bbbl@screset{\bbbl@screset, \bbbl@GL}%
1885 \fi
1886 \fi
1887 \fi}}
1888 \AtEndOfPackage{%
1889 \def\bbbl@forlang#1#2{\bbbl@for#1\bbbl@L{\bbbl@ifunset{date#1}{}{#2}}}%
1890 \let\bbbl@scswitch\relax}
1891 \@onlypreamble\EndBabelCommands
1892 \def\EndBabelCommands{%
1893 \bbbl@usehooks{stopcommands}{}%
1894 \endgroup
1895 \endgroup
1896 \bbbl@scafter}
1897 \let\bbbl@endcommands\EndBabelCommands

```

Now we define commands to be used inside `\StartBabelCommands`.

Strings The following macro is the actual definition of `\SetString` when it is “active”

First save the “switcher”. Create it if undefined. Strings are defined only if undefined (ie, like `\providescommand`). With the event `stringprocess` you can preprocess the string by manipulating the value of `\BabelString`. If there are several hooks assigned to this event, preprocessing is done in the same order as defined. Finally, the string is set.

```

1898 \def\bbl@setstring#1#2{% eg, \prefacename{<string>}
1899   \bbl@forlang\bbl@tempa{%
1900     \edef\bbl@LC{\bbl@tempa\bbl@stripslash#1}%
1901     \bbl@ifunset{\bbl@LC}% eg, \germanchaptername
1902       {\bbl@exp{%
1903         \global\bbbl@add\<\bbl@G\bbl@tempa>{\bbbl@scset\#1\<\bbl@LC>}}}%
1904       }%
1905     \def\BabelString{#2}%
1906     \bbl@usehooks{stringprocess}}}%
1907   \expandafter\bbl@stringdef
1908     \csname\bbl@LC\expandafter\endcsname\expandafter{\BabelString}}}
```

Now, some additional stuff to be used when encoded strings are used. Captions then include `\bbl@encoded` for string to be expanded in case transformations. It is `\relax` by default, but in `\MakeUppercase` and `\MakeLowercase` its value is a modified expandable `\@changed@cmd`.

```

1909 \ifx\bbl@opt@strings\relax
1910   \def\bbl@scset#1#2{\def#1{\bbl@encoded#2}}
1911   \bbl@patchuclc
1912   \let\bbl@encoded\relax
1913   \def\bbl@encoded@uclc#1{%
1914     \@inmathwarn#1%
1915     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
1916       \expandafter\ifx\csname ?\string#1\endcsname\relax
1917         \TextSymbolUnavailable#1%
1918       \else
1919         \csname ?\string#1\endcsname
1920       \fi
1921     \else
1922       \csname\cf@encoding\string#1\endcsname
1923     \fi}
1924 \else
1925   \def\bbl@scset#1#2{\def#1{#2}}
1926 \fi
```

Define `\SetStringLoop`, which is actually set inside `\StartBabelCommands`. The current definition is somewhat complicated because we need a count, but `\count@` is not under our control (remember `\SetString` may call hooks). Instead of defining a dedicated count, we just “pre-expand” its value.

```

1927 <<{*Macros local to BabelCommands}>> ≡
1928 \def\SetStringLoop##1##2{%
1929   \def\bbl@templ####1{\expandafter\noexpand\csname##1\endcsname}%
1930   \count@\z@
1931   \bbl@loop\bbl@tempa{##2}{% empty items and spaces are ok
1932     \advance\count@\@ne
1933     \toks@\expandafter{\bbl@tempa}%
1934     \bbl@exp{%
1935       \SetString\bbl@templ{\romannumeral\count@}{\the\toks@}%
1936       \count@=\the\count@\relax}}}%
1937 <</Macros local to BabelCommands>>
```

Delaying code Now the definition of `\AfterBabelCommands` when it is activated.

```

1938 \def\bbl@aftercmds#1{%
1939   \toks@\expandafter{\bbl@scafter#1}%
1940   \xdef\bbl@scafter{\the\toks@}}
```

Case mapping The command `\SetCase` provides a way to change the behavior of `\MakeUppercase` and `\MakeLowercase`. `\bbl@tempa` is set by the patched `\@uclclist` to the parsing command.

```

1941 <<{*Macros local to BabelCommands}>> ≡
```

```

1942 \newcommand\SetCase[3][]{%
1943   \bbl@patchuclc
1944   \bbl@forlang\bbl@tempa{%
1945     \expandafter\bbl@encstring
1946     \csname\bbl@tempa @bbl@uclc\endcsname{\bbl@tempa##1}%
1947     \expandafter\bbl@encstring
1948     \csname\bbl@tempa @bbl@uc\endcsname{##2}%
1949     \expandafter\bbl@encstring
1950     \csname\bbl@tempa @bbl@lc\endcsname{##3}}}%
1951 \</Macros local to BabelCommands>

```

Macros to deal with case mapping for hyphenation. To decide if the document is monolingual or multilingual, we make a rough guess – just see if there is a comma in the languages list, built in the first pass of the package options.

```

1952 \<(*Macros local to BabelCommands)> ≡
1953 \newcommand\SetHyphenMap[1]{%
1954   \bbl@forlang\bbl@tempa{%
1955     \expandafter\bbl@stringdef
1956     \csname\bbl@tempa @bbl@hyphenmap\endcsname{##1}}}%
1957 \</Macros local to BabelCommands>

```

There are 3 helper macros which do most of the work for you.

```

1958 \newcommand\BabelLower[2]{% one to one.
1959   \ifnum\lccode#1=#2\else
1960     \babel@savevariable{\lccode#1}%
1961     \lccode#1=#2\relax
1962   \fi}
1963 \newcommand\BabelLowerMM[4]{% many-to-many
1964   \@tempcnta=#1\relax
1965   \@tempcntb=#4\relax
1966   \def\bbl@tempa{%
1967     \ifnum\@tempcnta>#2\else
1968       \@expandtwoargs\BabelLower{\the\@tempcnta}{\the\@tempcntb}%
1969       \advance\@tempcnta#3\relax
1970       \advance\@tempcntb#3\relax
1971       \expandafter\bbl@tempa
1972     \fi}%
1973   \bbl@tempa}
1974 \newcommand\BabelLowerMO[4]{% many-to-one
1975   \@tempcnta=#1\relax
1976   \def\bbl@tempa{%
1977     \ifnum\@tempcnta>#2\else
1978       \@expandtwoargs\BabelLower{\the\@tempcnta}{#4}%
1979       \advance\@tempcnta#3
1980       \expandafter\bbl@tempa
1981     \fi}%
1982   \bbl@tempa}

```

The following package options control the behavior of hyphenation mapping.

```

1983 \<(*More package options)> ≡
1984 \DeclareOption{hyphenmap=off}{\chardef\bbl@opt@hyphenmap\z@}
1985 \DeclareOption{hyphenmap=first}{\chardef\bbl@opt@hyphenmap\@ne}
1986 \DeclareOption{hyphenmap=select}{\chardef\bbl@opt@hyphenmap\tw@}
1987 \DeclareOption{hyphenmap=other}{\chardef\bbl@opt@hyphenmap\thr@@}
1988 \DeclareOption{hyphenmap=other*}{\chardef\bbl@opt@hyphenmap4\relax}
1989 \</More package options>

```

Initial setup to provide a default behavior if hyphenmap is not set.

```

1990 \AtEndOfPackage{%
1991   \ifx\bbl@opt@hyphenmap\undefined
1992     \bbl@xin@{,}{\bbl@language@opts}%
1993     \chardef\bbl@opt@hyphenmap\ifin@4\else\@ne\fi
1994   \fi}

```

This sections ends with a general tool for resetting the caption names with a unique interface. With the old way, which mixes the switcher and the string, we convert it to the new one, which separates these two steps.

```

1995 \newcommand\setlocalecaption{% TODO. Catch typos. What about ensure?
1996 \@ifstar\bbl@setcaption@s\bbl@setcaption@x}
1997 \def\bbl@setcaption@x#1#2#3{% language caption-name string
1998 \bbl@trim@def\bbl@tempa{#2}%
1999 \bbl@xin@{.template}{\bbl@tempa}%
2000 \ifin@
2001 \bbl@ini@captions@template{#3}{#1}%
2002 \else
2003 \edef\bbl@tempd{%
2004 \expandafter\expandafter\expandafter
2005 \strip@prefix\expandafter\meaning\csname captions#1\endcsname}%
2006 \bbl@xin@
2007 {\expandafter\string\csname #2name\endcsname}%
2008 {\bbl@tempd}%
2009 \ifin@ % Renew caption
2010 \bbl@xin@{\string\bbl@scset}{\bbl@tempd}%
2011 \ifin@
2012 \bbl@exp{%
2013 \\\bbl@ifsamestring{\bbl@tempa}{\language name}%
2014 {\\\bbl@scset\<#2name>\<#1#2name>}%
2015 {}}%
2016 \else % Old way converts to new way
2017 \bbl@ifunset{#1#2name}%
2018 {\bbl@exp{%
2019 \\\bbl@add\<captions#1>{\def\<#2name>{\<#1#2name>}}%
2020 \\\bbl@ifsamestring{\bbl@tempa}{\language name}%
2021 {\def\<#2name>{\<#1#2name>}}%
2022 {}}}%
2023 {}}%
2024 \fi
2025 \else
2026 \bbl@xin@{\string\bbl@scset}{\bbl@tempd}% New
2027 \ifin@ % New way
2028 \bbl@exp{%
2029 \\\bbl@add\<captions#1>{\\\bbl@scset\<#2name>\<#1#2name>}%
2030 \\\bbl@ifsamestring{\bbl@tempa}{\language name}%
2031 {\\\bbl@scset\<#2name>\<#1#2name>}%
2032 {}}%
2033 \else % Old way, but defined in the new way
2034 \bbl@exp{%
2035 \\\bbl@add\<captions#1>{\def\<#2name>{\<#1#2name>}}%
2036 \\\bbl@ifsamestring{\bbl@tempa}{\language name}%
2037 {\def\<#2name>{\<#1#2name>}}%
2038 {}}%
2039 \fi%
2040 \fi
2041 \@namedef{#1#2name}{#3}%
2042 \toks@\expandafter{\bbl@captionslist}%
2043 \bbl@exp{\\\in@{\<#2name>}{\the\toks@}}%
2044 \ifin@\else
2045 \bbl@exp{\\\bbl@add\\bbl@captionslist{\<#2name>}}%
2046 \bbl@tglobal\bbl@captionslist
2047 \fi
2048 \fi}
2049 % \def\bbl@setcaption@s#1#2#3{} % TODO. Not yet implemented

```

7.11 Macros common to a number of languages

`\set@low@box` The following macro is used to lower quotes to the same level as the comma. It prepares its argument in box register 0.

```
2050 \bbl@trace{Macros related to glyphs}
2051 \def\set@low@box#1{\setbox\tw@hbox{,}\setbox\z@hbox{#1}%
2052   \dimen\z@ht\z@ \advance\dimen\z@ -\ht\tw@%
2053   \setbox\z@hbox{\lower\dimen\z@ \box\z@}\ht\z@ht\tw@ \dp\z@dp\tw@}
```

`\save@sf@q` The macro `\save@sf@q` is used to save and reset the current space factor.

```
2054 \def\save@sf@q#1{\leavevmode
2055   \begingroup
2056   \edef\@SF{\spacefactor\the\spacefactor}#1\@SF
2057   \endgroup}
```

7.12 Making glyphs available

This section makes a number of glyphs available that either do not exist in the OT1 encoding and have to be ‘faked’, or that are not accessible through T1enc.def.

7.12.1 Quotation marks

`\quotedblbase` In the T1 encoding the opening double quote at the baseline is available as a separate character, accessible via `\quotedblbase`. In the OT1 encoding it is not available, therefore we make it available by lowering the normal open quote character to the baseline.

```
2058 \ProvideTextCommand{\quotedblbase}{OT1}{%
2059   \save@sf@q{\set@low@box{\textquotedblright\}%
2060     \box\z@\kern-.04em\bbl@allowhyphens}}
```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```
2061 \ProvideTextCommandDefault{\quotedblbase}{%
2062   \UseTextSymbol{OT1}{\quotedblbase}}
```

`\quotesinglbase` We also need the single quote character at the baseline.

```
2063 \ProvideTextCommand{\quotesinglbase}{OT1}{%
2064   \save@sf@q{\set@low@box{\textquoteright\}%
2065     \box\z@\kern-.04em\bbl@allowhyphens}}
```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```
2066 \ProvideTextCommandDefault{\quotesinglbase}{%
2067   \UseTextSymbol{OT1}{\quotesinglbase}}
```

`\guillemetleft` `\guillemetright` The guillemet characters are not available in OT1 encoding. They are faked. (Wrong names with o preserved for compatibility.)

```
2068 \ProvideTextCommand{\guillemetleft}{OT1}{%
2069   \ifmmode
2070     \ll
2071   \else
2072     \save@sf@q{\nobreak
2073       \raise.2ex\hbox{$\scriptscriptstyle\ll$}\bbl@allowhyphens}%
2074     \fi}
2075 \ProvideTextCommand{\guillemetright}{OT1}{%
2076   \ifmmode
2077     \gg
2078   \else
2079     \save@sf@q{\nobreak
2080       \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
2081     \fi}
2082 \ProvideTextCommand{\guillemotleft}{OT1}{%
2083   \ifmmode
2084     \ll
2085   \else
```

```

2086 \save@sf@q{\nobreak
2087 \raise.2ex\hbox{$\scriptscriptstyle\l1$}\bbl@allowhyphens}%
2088 \fi}
2089 \ProvideTextCommand{\guillemotright}{OT1}{%
2090 \ifmmode
2091 \gg
2092 \else
2093 \save@sf@q{\nobreak
2094 \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
2095 \fi}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2096 \ProvideTextCommandDefault{\guillemotleft}{%
2097 \UseTextSymbol{OT1}{\guillemotleft}}
2098 \ProvideTextCommandDefault{\guillemotright}{%
2099 \UseTextSymbol{OT1}{\guillemotright}}
2100 \ProvideTextCommandDefault{\guillemotleft}{%
2101 \UseTextSymbol{OT1}{\guillemotleft}}
2102 \ProvideTextCommandDefault{\guillemotright}{%
2103 \UseTextSymbol{OT1}{\guillemotright}}

```

`\guilsinglleft` The single guillemets are not available in OT1 encoding. They are faked.
`\guilsinglright`

```

2104 \ProvideTextCommand{\guilsinglleft}{OT1}{%
2105 \ifmmode
2106 <%
2107 \else
2108 \save@sf@q{\nobreak
2109 \raise.2ex\hbox{$\scriptscriptstyle<$}\bbl@allowhyphens}%
2110 \fi}
2111 \ProvideTextCommand{\guilsinglright}{OT1}{%
2112 \ifmmode
2113 >%
2114 \else
2115 \save@sf@q{\nobreak
2116 \raise.2ex\hbox{$\scriptscriptstyle>$}\bbl@allowhyphens}%
2117 \fi}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2118 \ProvideTextCommandDefault{\guilsinglleft}{%
2119 \UseTextSymbol{OT1}{\guilsinglleft}}
2120 \ProvideTextCommandDefault{\guilsinglright}{%
2121 \UseTextSymbol{OT1}{\guilsinglright}}

```

7.12.2 Letters

`\ij` The dutch language uses the letter ‘ij’. It is available in T1 encoded fonts, but not in the OT1 encoded
`\IJ` fonts. Therefore we fake it for the OT1 encoding.

```

2122 \DeclareTextCommand{\ij}{OT1}{%
2123 i\kern-0.02em\bbl@allowhyphens j}
2124 \DeclareTextCommand{\IJ}{OT1}{%
2125 I\kern-0.02em\bbl@allowhyphens J}
2126 \DeclareTextCommand{\ij}{T1}{\char188}
2127 \DeclareTextCommand{\IJ}{T1}{\char156}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2128 \ProvideTextCommandDefault{\ij}{%
2129 \UseTextSymbol{OT1}{\ij}}
2130 \ProvideTextCommandDefault{\IJ}{%
2131 \UseTextSymbol{OT1}{\IJ}}

```

`\dj` The croatian language needs the letters `\dj` and `\DJ`; they are available in the T1 encoding, but not in
`\DJ` the OT1 encoding by default.

Some code to construct these glyphs for the OT1 encoding was made available to me by Stipčević Mario, (stipcevic@olimp.irb.hr).

```

2132 \def\crrtic@{\hrule height0.1ex width0.3em}
2133 \def\crttic@{\hrule height0.1ex width0.33em}
2134 \def\ddj@{%
2135   \setbox0\hbox{d}\dimen@=\ht0
2136   \advance\dimen@1ex
2137   \dimen@.45\dimen@
2138   \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
2139   \advance\dimen@ii.5ex
2140   \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crrtic@}}}}
2141 \def\DDJ@{%
2142   \setbox0\hbox{D}\dimen@=.55\ht0
2143   \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
2144   \advance\dimen@ii.15ex %           correction for the dash position
2145   \advance\dimen@ii-.15\fontdimen7\font % correction for cmtt font
2146   \dimen\thr@@\expandafter\rem@pt\the\fontdimen7\font\dimen@
2147   \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crttic@}}}}
2148 %
2149 \DeclareTextCommand{\dj}{OT1}{\ddj@ d}
2150 \DeclareTextCommand{\DJ}{OT1}{\DDJ@ D}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2151 \ProvideTextCommandDefault{\dj}{%
2152   \UseTextSymbol{OT1}{\dj}}
2153 \ProvideTextCommandDefault{\DJ}{%
2154   \UseTextSymbol{OT1}{\DJ}}

```

\SS For the T1 encoding \SS is defined and selects a specific glyph from the font, but for other encodings it is not available. Therefore we make it available here.

```

2155 \DeclareTextCommand{\SS}{OT1}{\SS}
2156 \ProvideTextCommandDefault{\SS}{\UseTextSymbol{OT1}{\SS}}

```

7.12.3 Shorthands for quotation marks

Shorthands are provided for a number of different quotation marks, which make them usable both outside and inside mathmode. They are defined with \ProvideTextCommandDefault, but this is very likely not required because their definitions are based on encoding-dependent macros.

\glq The ‘german’ single quotes.

```

\grq
2157 \ProvideTextCommandDefault{\glq}{%
2158   \textormath{\quotesinglbase}{\mbox{\quotesinglbase}}}

```

The definition of \grq depends on the fontencoding. With T1 encoding no extra kerning is needed.

```

2159 \ProvideTextCommand{\grq}{T1}{%
2160   \textormath{\kern\z@\textquoteleft}{\mbox{\textquoteleft}}}
2161 \ProvideTextCommand{\grq}{TU}{%
2162   \textormath{\textquoteleft}{\mbox{\textquoteleft}}}
2163 \ProvideTextCommand{\grq}{OT1}{%
2164   \save@sf@q{\kern-.0125em
2165     \textormath{\textquoteleft}{\mbox{\textquoteleft}}}%
2166     \kern.07em\relax}}
2167 \ProvideTextCommandDefault{\grq}{\UseTextSymbol{OT1}{\grq}}

```

\glqq The ‘german’ double quotes.

```

\grqq
2168 \ProvideTextCommandDefault{\glqq}{%
2169   \textormath{\quotedblbase}{\mbox{\quotedblbase}}}

```

The definition of \grqq depends on the fontencoding. With T1 encoding no extra kerning is needed.

```

2170 \ProvideTextCommand{\grqq}{T1}{%
2171   \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}
2172 \ProvideTextCommand{\grqq}{TU}{%
2173   \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}

```

```

2174 \ProvideTextCommand{\grqq}{OT1}{%
2175   \save@sf@q{\kern-.07em
2176     \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}%
2177     \kern.07em\relax}}
2178 \ProvideTextCommandDefault{\grqq}{\UseTextSymbol{OT1}\grqq}

```

\flq The ‘french’ single guillemets.

```

\frq
2179 \ProvideTextCommandDefault{\flq}{%
2180   \textormath{\guilsinglleft}{\mbox{\guilsinglleft}}}
2181 \ProvideTextCommandDefault{\frq}{%
2182   \textormath{\guilsinglright}{\mbox{\guilsinglright}}}

```

\flqq The ‘french’ double guillemets.

```

\frqq
2183 \ProvideTextCommandDefault{\flqq}{%
2184   \textormath{\guillemetleft}{\mbox{\guillemetleft}}}
2185 \ProvideTextCommandDefault{\frqq}{%
2186   \textormath{\guillemetright}{\mbox{\guillemetright}}}

```

7.12.4 Umlauts and tremas

The command \~ needs to have a different effect for different languages. For German for instance, the ‘umlaut’ should be positioned lower than the default position for placing it over the letters a, o, u, A, O and U. When placed over an e, i, E or I it can retain its normal position. For Dutch the same glyph is always placed in the lower position.

\umlauthigh To be able to provide both positions of \~ we provide two commands to switch the positioning, the default will be \umlauthigh (the normal positioning).

```

2187 \def\umlauthigh{%
2188   \def\bbl@umlauta##1{\leavevmode\bgroup%
2189     \expandafter\accent\csname\fontencoding dqpos\endcsname
2190     ##1\bbl@allowhyphens\egroup}%
2191   \let\bbl@umlaute\bbl@umlauta}
2192 \def\umlautlow{%
2193   \def\bbl@umlauta{\protect\lower@umlaut}}
2194 \def\umlautelow{%
2195   \def\bbl@umlaute{\protect\lower@umlaut}}
2196 \umlauthigh

```

\lower@umlaut The command \lower@umlaut is used to position the \~ closer to the letter.

We want the umlaut character lowered, nearer to the letter. To do this we need an extra *<dimen>* register.

```

2197 \expandafter\ifx\csname U@D\endcsname\relax
2198   \csname newdimen\endcsname\U@D
2199 \fi

```

The following code fools T_EX’s make_accent procedure about the current x-height of the font to force another placement of the umlaut character. First we have to save the current x-height of the font, because we’ll change this font dimension and this is always done globally.

Then we compute the new x-height in such a way that the umlaut character is lowered to the base character. The value of .45ex depends on the METAFONT parameters with which the fonts were built. (Just try out, which value will look best.) If the new x-height is too low, it is not changed. Finally we call the \accent primitive, reset the old x-height and insert the base character in the argument.

```

2200 \def\lower@umlaut#1{%
2201   \leavevmode\bgroup
2202     \U@D 1ex%
2203     {\setbox\z@\hbox{%
2204       \expandafter\char\csname\fontencoding dqpos\endcsname}%
2205       \dimen@ -.45ex\advance\dimen@\ht\z@
2206       \ifdim 1ex<\dimen@ \fontdimen5\font\dimen@ \fi}%
2207     \expandafter\accent\csname\fontencoding dqpos\endcsname
2208     \fontdimen5\font\U@D #1%
2209   \egroup}

```

For all vowels we declare `\` to be a composite command which uses `\bbl@umlauta` or `\bbl@umlaute` to position the umlaut character. We need to be sure that these definitions override the ones that are provided when the package `fontenc` with option `OT1` is used. Therefore these declarations are postponed until the beginning of the document. Note these definitions only apply to some languages, but `babel` sets them for *all* languages – you may want to redefine `\bbl@umlauta` and/or `\bbl@umlaute` for a language in the corresponding `ldf` (using the `babel` switching mechanism, of course).

```

2210 \AtBeginDocument{%
2211   \DeclareTextCompositeCommand{\}{OT1}{a}{\bbl@umlauta{a}}%
2212   \DeclareTextCompositeCommand{\}{OT1}{e}{\bbl@umlaute{e}}%
2213   \DeclareTextCompositeCommand{\}{OT1}{i}{\bbl@umlaute{i}}%
2214   \DeclareTextCompositeCommand{\}{OT1}{\i}{\bbl@umlaute{i}}%
2215   \DeclareTextCompositeCommand{\}{OT1}{o}{\bbl@umlauta{o}}%
2216   \DeclareTextCompositeCommand{\}{OT1}{u}{\bbl@umlauta{u}}%
2217   \DeclareTextCompositeCommand{\}{OT1}{A}{\bbl@umlauta{A}}%
2218   \DeclareTextCompositeCommand{\}{OT1}{E}{\bbl@umlaute{E}}%
2219   \DeclareTextCompositeCommand{\}{OT1}{I}{\bbl@umlaute{I}}%
2220   \DeclareTextCompositeCommand{\}{OT1}{O}{\bbl@umlauta{O}}%
2221   \DeclareTextCompositeCommand{\}{OT1}{U}{\bbl@umlauta{U}}%

```

Finally, make sure the default hyphenrules are defined (even if empty). For internal use, another empty `\language` is defined. Currently used in Amharic.

```

2222 \ifx\l@english\undefined
2223   \chardef\l@english\z@
2224 \fi
2225 % The following is used to cancel rules in ini files (see Amharic).
2226 \ifx\l@unhyphenated\undefined
2227   \newlanguage\l@unhyphenated
2228 \fi

```

7.13 Layout

Layout is mainly intended to set bidi documents, but there is at least a tool useful in general.

```

2229 \bbl@trace{Bidi layout}
2230 \providecommand\IfBabelLayout[3]{#3}%
2231 \newcommand\BabelPatchSection[1]{%
2232   \@ifundefined{#1}{}{%
2233     \bbl@exp{\let\<bbl@ss@#1>\<#1>}%
2234     \@namedef{#1}{%
2235       \@ifstar{\bbl@presec@s{#1}}%
2236       {\@dblarg{\bbl@presec@x{#1}}}}%
2237 \def\bbl@presec@x#1[#2]#3{%
2238   \bbl@exp{%
2239     \\\select@language@x{\bbl@main@language}%
2240     \\\bbl@cs{sspre@#1}%
2241     \\\bbl@cs{ss@#1}%
2242     [\\\foreignlanguage{\language}{\unexpanded{#2}}}%
2243     {\\\foreignlanguage{\language}{\unexpanded{#3}}}%
2244     \\\select@language@x{\language}}%
2245 \def\bbl@presec@s#1#2{%
2246   \bbl@exp{%
2247     \\\select@language@x{\bbl@main@language}%
2248     \\\bbl@cs{sspre@#1}%
2249     \\\bbl@cs{ss@#1}*%
2250     [\\\foreignlanguage{\language}{\unexpanded{#2}}}%
2251     \\\select@language@x{\language}}%
2252 \IfBabelLayout{sectioning}%
2253   {\BabelPatchSection{part}%
2254    \BabelPatchSection{chapter}%
2255    \BabelPatchSection{section}%
2256    \BabelPatchSection{subsection}%
2257    \BabelPatchSection{subsubsection}%
2258    \BabelPatchSection{paragraph}%

```



```

2259 \BabelPatchSection{subparagraph}%
2260 \def\babel@toc#1{%
2261 \select@language@x{\bbl@main@language}}{}
2262 \IfBabelLayout{captions}%
2263 {\BabelPatchSection{caption}}{}

```

7.14 Load engine specific macros

```

2264 \bbl@trace{Input engine specific macros}
2265 \ifcase\bbl@engine
2266 \input txtbabel.def
2267 \or
2268 \input luababel.def
2269 \or
2270 \input xebabel.def
2271 \fi

```

7.15 Creating and modifying languages

`\babelprovide` is a general purpose tool for creating and modifying languages. It creates the language infrastructure, and loads, if requested, an ini file. It may be used in conjunction to previously loaded ldf files.

```

2272 \bbl@trace{Creating languages and reading ini files}
2273 \let\bbl@extend@ini\@gobble
2274 \newcommand\babelprovide[2][{}]{%
2275 \let\bbl@savelangname\language
2276 \edef\bbl@savelocaleid{\the\localeid}%
2277 % Set name and locale id
2278 \edef\language{#2}%
2279 \bbl@id@assign
2280 % Initialize keys
2281 \let\bbl@KVP@captions\@nil
2282 \let\bbl@KVP@date\@nil
2283 \let\bbl@KVP@import\@nil
2284 \let\bbl@KVP@main\@nil
2285 \let\bbl@KVP@script\@nil
2286 \let\bbl@KVP@language\@nil
2287 \let\bbl@KVP@hyphenrules\@nil
2288 \let\bbl@KVP@linebreaking\@nil
2289 \let\bbl@KVP@justification\@nil
2290 \let\bbl@KVP@mapfont\@nil
2291 \let\bbl@KVP@maparabic\@nil
2292 \let\bbl@KVP@mapdigits\@nil
2293 \let\bbl@KVP@intraspace\@nil
2294 \let\bbl@KVP@intrapenalty\@nil
2295 \let\bbl@KVP@onchar\@nil
2296 \let\bbl@KVP@transforms\@nil
2297 \global\let\bbl@release@transforms\@empty
2298 \let\bbl@KVP@alph\@nil
2299 \let\bbl@KVP@Alph\@nil
2300 \let\bbl@KVP@labels\@nil
2301 \bbl@csarg\let{KVP@labels*}\@nil
2302 \let\bbl@KVP@calendar\@nil
2303 \let\bbl@calendars\@empty
2304 \global\let\bbl@inidata\@empty
2305 \global\let\bbl@extend@ini\@gobble
2306 \gdef\bbl@key@list{;}%
2307 \bbl@forkv{#1}{% TODO - error handling
2308 \in@{/}{##1}%
2309 \ifin@
2310 \global\let\bbl@extend@ini\bbl@extend@ini@aux
2311 \bbl@renewinikey##1\@{##2}%
2312 \else

```

```

2313     \bbl@csarg\def{KVP@##1}{##2}%
2314     \fi}%
2315     \chardef\bbl@howloaded=% 0:none; 1:ldf without ini; 2:ini
2316     \bbl@ifunset{date#2}\z@{\bbl@ifunset{\bbl@llevel@#2}\@ne\tw@}%
2317     % == init ==
2318     \ifx\bbl@screset\@undefined
2319         \bbl@ldfinit
2320     \fi
2321     % ==
2322     \let\bbl@lbkflag\relax % \@empty = do setup linebreak
2323     \ifcase\bbl@howloaded
2324         \let\bbl@lbkflag\@empty % new
2325     \else
2326         \ifx\bbl@KVP@hyphenrules\@nil\else
2327             \let\bbl@lbkflag\@empty
2328         \fi
2329         \ifx\bbl@KVP@import\@nil\else
2330             \let\bbl@lbkflag\@empty
2331         \fi
2332     \fi
2333     % == import, captions ==
2334     \ifx\bbl@KVP@import\@nil\else
2335         \bbl@exp{\@bbl@ifblank{\bbl@KVP@import}}%
2336         {\ifx\bbl@initload\relax
2337             \begingroup
2338                 \def\BabelBeforeIni##1##2{\gdef\bbl@KVP@import{##1}\endinput}%
2339                 \bbl@input@texini{#2}%
2340             \endgroup
2341         \else
2342             \xdef\bbl@KVP@import{\bbl@initload}%
2343         \fi}%
2344     {}%
2345 \fi
2346 \ifx\bbl@KVP@captions\@nil
2347     \let\bbl@KVP@captions\bbl@KVP@import
2348 \fi
2349 % ==
2350 \ifx\bbl@KVP@transforms\@nil\else
2351     \bbl@replace\bbl@KVP@transforms{ }{,}%
2352 \fi
2353 % == Load ini ==
2354 \ifcase\bbl@howloaded
2355     \bbl@provide@new{#2}%
2356 \else
2357     \bbl@ifblank{#1}%
2358     {}% With \bbl@load@basic below
2359     {\bbl@provide@renew{#2}}%
2360 \fi
2361 % Post tasks
2362 % -----
2363 % == subsequent calls after the first provide for a locale ==
2364 \ifx\bbl@inidata\@empty\else
2365     \bbl@extend@ini{#2}%
2366 \fi
2367 % == ensure captions ==
2368 \ifx\bbl@KVP@captions\@nil\else
2369     \bbl@ifunset{\bbl@extracaps@#2}%
2370     {\bbl@exp{\@babelensure[exclude=\@today]{#2}}}%
2371     {\bbl@exp{\@babelensure[exclude=\@today,
2372         include=[\bbl@extracaps@#2]]{#2}}}%
2373     \bbl@ifunset{\bbl@ensure@\language}%
2374     {\bbl@exp{%
2375         \\\DeclareRobustCommand\<bbl@ensure@\language>[1]{%

```

```

2376         \\foreignlanguage{\language}%
2377         {###1}}}%
2378     }%
2379     \bbl@exp{%
2380         \\bbl@toggle\<bbl@ensure@\language>%
2381         \\bbl@toggle\<bbl@ensure@\language\space>}%
2382     \fi
2383     % ==
2384     % At this point all parameters are defined if 'import'. Now we
2385     % execute some code depending on them. But what about if nothing was
2386     % imported? We just set the basic parameters, but still loading the
2387     % whole ini file.
2388     \bbl@load@basic{#2}%
2389     % == script, language ==
2390     % Override the values from ini or defines them
2391     \ifx\bbl@KVP@script\@nil\else
2392         \bbl@csarg\edef{sname@#2}{\bbl@KVP@script}%
2393     \fi
2394     \ifx\bbl@KVP@language\@nil\else
2395         \bbl@csarg\edef{lname@#2}{\bbl@KVP@language}%
2396     \fi
2397     \ifcase\bbl@engine\or
2398         \bbl@ifunset{bbl@chrng@\language}{}%
2399         {\directlua{
2400             Babel.set_chranges_b('\bbl@cl{sbc}', '\bbl@cl{chrng}') }}%
2401     \fi
2402     % == onchar ==
2403     \ifx\bbl@KVP@onchar\@nil\else
2404         \bbl@luahyphenate
2405         \bbl@exp{%
2406             \\AddToHook{env/document/before}{\\select@language{#2}}}%
2407         \directlua{
2408             if Babel.locale_mapped == nil then
2409                 Babel.locale_mapped = true
2410                 Babel.linebreaking.add_before(Babel.locale_map)
2411                 Babel.loc_to_scr = {}
2412                 Babel.chr_to_loc = Babel.chr_to_loc or {}
2413             end}%
2414         \bbl@xin@{ ids }{ \bbl@KVP@onchar\space}%
2415         \ifin@
2416             \ifx\bbl@starthyphens\undefined % Needed if no explicit selection
2417                 \AddBabelHook{babel-onchar}{beforestart}{\bbl@starthyphens}%
2418             \fi
2419             \bbl@exp{\\bbl@add\\bbl@starthyphens
2420                 {\bbl@patterns@lua{\language}}}%
2421             % TODO - error/warning if no script
2422             \directlua{
2423                 if Babel.script_blocks['\bbl@cl{sbc}'] then
2424                     Babel.loc_to_scr[\the\localeid] =
2425                         Babel.script_blocks['\bbl@cl{sbc}']
2426                     Babel.locale_props[\the\localeid].lc = \the\localeid\space
2427                     Babel.locale_props[\the\localeid].lg = \the\@nameuse{1@\language}\space
2428                 end
2429             }%
2430         \fi
2431         \bbl@xin@{ fonts }{ \bbl@KVP@onchar\space}%
2432         \ifin@
2433             \bbl@ifunset{bbl@lsys@\language}{\bbl@provide@lsys{\language}}{}%
2434             \bbl@ifunset{bbl@wdir@\language}{\bbl@provide@dirs{\language}}{}%
2435             \directlua{
2436                 if Babel.script_blocks['\bbl@cl{sbc}'] then
2437                     Babel.loc_to_scr[\the\localeid] =
2438                         Babel.script_blocks['\bbl@cl{sbc}']

```

```

2439     end}%
2440     \ifx\bbbl@mapselect\undefined % TODO. almost the same as mapfont
2441     \AtBeginDocument{%
2442         \bbbl@patchfont{\bbbl@mapselect}}%
2443         {\selectfont}}%
2444     \def\bbbl@mapselect{%
2445         \let\bbbl@mapselect\relax
2446         \edef\bbbl@prefontid{\fontid\font}}%
2447     \def\bbbl@mapdir##1{%
2448         {\def\language{##1}%
2449         \let\bbbl@ifrestoring\@firstoftwo % To avoid font warning
2450         \bbbl@switchfont
2451         \ifnum\fontid\font>\z@ % A hack, for the pgf nullfont hack
2452             \directlua{
2453                 Babel.locale_props[\the\csname bbl@id@##1\endcsname]%
2454                 ['\bbbl@prefontid'] = \fontid\font\space}%
2455             \fi}}%
2456     \fi
2457     \bbbl@exp{\bbbl@add\bbbl@mapselect{\bbbl@mapdir{\language}}}%
2458     \fi
2459     % TODO - catch non-valid values
2460 \fi
2461 % == mapfont ==
2462 % For bidi texts, to switch the font based on direction
2463 \ifx\bbbl@KVP@mapfont\@nil\else
2464     \bbbl@ifsamestring{\bbbl@KVP@mapfont}{direction}}%
2465     {\bbbl@error{Option '\bbbl@KVP@mapfont' unknown for\%
2466         mapfont. Use 'direction'.%
2467         {See the manual for details.}}}%
2468     \bbbl@ifunset{\bbbl@lsys\language}{\bbbl@provide@lsys\language}}%
2469     \bbbl@ifunset{\bbbl@wdir\language}{\bbbl@provide@dirs\language}}%
2470 \ifx\bbbl@mapselect\undefined % TODO. See onchar.
2471     \AtBeginDocument{%
2472         \bbbl@patchfont{\bbbl@mapselect}}%
2473         {\selectfont}}%
2474     \def\bbbl@mapselect{%
2475         \let\bbbl@mapselect\relax
2476         \edef\bbbl@prefontid{\fontid\font}}%
2477     \def\bbbl@mapdir##1{%
2478         {\def\language{##1}%
2479         \let\bbbl@ifrestoring\@firstoftwo % avoid font warning
2480         \bbbl@switchfont
2481         \directlua{Babel.fontmap
2482             [\the\csname bbl@wdir@##1\endcsname]%
2483             [\bbbl@prefontid]=\fontid\font}}}%
2484     \fi
2485     \bbbl@exp{\bbbl@add\bbbl@mapselect{\bbbl@mapdir{\language}}}%
2486     \fi
2487 % == Line breaking: intraspace, intrapenalty ==
2488 % For CJK, East Asian, Southeast Asian, if interspace in ini
2489 \ifx\bbbl@KVP@intraspace\@nil\else % We can override the ini or set
2490     \bbbl@csarg\edef{intsp@#2}{\bbbl@KVP@intraspace}%
2491 \fi
2492 \bbbl@provide@intraspace
2493 % == Line breaking: CJK quotes ==
2494 \ifcase\bbbl@engine\or
2495     \bbbl@xin@{/c}{\bbbl@c1\lnbrk}}%
2496 \ifin@
2497     \bbbl@ifunset{\bbbl@quote\language}}%
2498     {\directlua{
2499         Babel.locale_props[\the\localeid].cjk_quotes = {}
2500         local cs = 'op'
2501         for c in string.utfvalues(

```

```

2502         [[\csname bbl@quote@\language\endcsname]] do
2503         if Babel.cjk_characters[c].c == 'qu' then
2504             Babel.locale_props[\the\localeid].cjk_quotes[c] = cs
2505         end
2506         cs = ( cs == 'op') and 'cl' or 'op'
2507     end
2508 }}%
2509 \fi
2510 \fi
2511 % == Line breaking: justification ==
2512 \ifx\bbl@KVP@justification\@nil\else
2513     \let\bbl@KVP@linebreaking\bbl@KVP@justification
2514 \fi
2515 \ifx\bbl@KVP@linebreaking\@nil\else
2516     \bbl@xin@{\bbl@KVP@linebreaking,}{,elongated,kashida,cjk,unhyphenated,}%
2517     \ifin@
2518         \bbl@csarg\xdef
2519             {\lnbrk@\language}{\expandafter\@car\bbl@KVP@linebreaking\@nil}%
2520     \fi
2521 \fi
2522 \bbl@xin@{/e}{/\bbl@cl{\lnbrk}}}%
2523 \ifin@else\bbl@xin@{/k}{/\bbl@cl{\lnbrk}}\fi
2524 \ifin@\bbl@arabicjust\fi
2525 % == Line breaking: hyphenate.other.(locale|script) ==
2526 \ifx\bbl@lbcflag\@empty
2527     \bbl@ifunset{\bbl@hyotl@\language}{}%
2528     {\bbl@csarg\bbl@replace{\hyotl@\language}{ }{,}}%
2529     \bbl@startcommands*\language}%
2530     \bbl@csarg\bbl@foreach{\hyotl@\language}{%
2531         \ifcase\bbl@engine
2532             \ifnum##1<257
2533                 \SetHyphenMap{\BabelLower{##1}{##1}}%
2534             \fi
2535             \else
2536                 \SetHyphenMap{\BabelLower{##1}{##1}}%
2537             \fi}%
2538     \bbl@endcommands}%
2539 \bbl@ifunset{\bbl@hyots@\language}{}%
2540 {\bbl@csarg\bbl@replace{\hyots@\language}{ }{,}}%
2541 \bbl@csarg\bbl@foreach{\hyots@\language}{%
2542     \ifcase\bbl@engine
2543         \ifnum##1<257
2544             \global\lccode##1=##1\relax
2545         \fi
2546         \else
2547             \global\lccode##1=##1\relax
2548         \fi}%
2549 \fi
2550 % == Counters: maparabic ==
2551 % Native digits, if provided in ini (TeX level, xe and lua)
2552 \ifcase\bbl@engine\else
2553     \bbl@ifunset{\bbl@dgnat@\language}{}%
2554     {\expandafter\ifx\csname bbl@dgnat@\language\endcsname\@empty\else
2555         \expandafter\expandafter\expandafter
2556         \bbl@setdigits\csname bbl@dgnat@\language\endcsname
2557         \ifx\bbl@KVP@maparabic\@nil\else
2558             \ifx\bbl@latinarabic\@undefined
2559                 \expandafter\let\expandafter\@arabic
2560                 \csname bbl@counter@\language\endcsname
2561             \else % ie, if layout=counters, which redefines \@arabic
2562                 \expandafter\let\expandafter\bbl@latinarabic
2563                 \csname bbl@counter@\language\endcsname
2564             \fi

```

```

2565     \fi
2566     \fi}%
2567 \fi
2568 % == Counters: mapdigits ==
2569 % Native digits (lua level).
2570 \ifodd\bbbl@engine
2571     \ifx\bbbl@KVP@mapdigits\@nil\else
2572         \bbbl@ifunset{bbbl@dgnat@\languagename}{}%
2573         {\RequirePackage{luatexbase}%
2574         \bbbl@activate@preotf
2575         \directlua{
2576             Babel = Babel or {}   %% -> presets in luababel
2577             Babel.digits_mapped = true
2578             Babel.digits = Babel.digits or {}
2579             Babel.digits[\the\localeid] =
2580                 table.pack(string.utfvalue('\bbbl@cl{dgnat}'))
2581             if not Babel.numbers then
2582                 function Babel.numbers(head)
2583                     local LOCALE = Babel.attr_locale
2584                     local GLYPH = node.id'glyph'
2585                     local inmath = false
2586                     for item in node.traverse(head) do
2587                         if not inmath and item.id == GLYPH then
2588                             local temp = node.get_attribute(item, LOCALE)
2589                             if Babel.digits[temp] then
2590                                 local chr = item.char
2591                                 if chr > 47 and chr < 58 then
2592                                     item.char = Babel.digits[temp][chr-47]
2593                                 end
2594                             end
2595                         elseif item.id == node.id'math' then
2596                             inmath = (item.subtype == 0)
2597                         end
2598                     end
2599                     return head
2600                 end
2601             end
2602         } }%
2603     \fi
2604 \fi
2605 % == Counters: alph, Alph ==
2606 % What if extras<lang> contains a \babel@save\@alph? It won't be
2607 % restored correctly when exiting the language, so we ignore
2608 % this change with the \bbbl@alph@saved trick.
2609 \ifx\bbbl@KVP@alph\@nil\else
2610     \bbbl@extras@wrap{\bbbl@alph@saved}%
2611     {\let\bbbl@alph@saved\@alph}%
2612     {\let\@alph\bbbl@alph@saved
2613     \babel@save\@alph}%
2614     \bbbl@exp{%
2615         \bbbl@add<extras\languagename>{%
2616             \let\@alph\<bbbl@cntr@bbbl@KVP@alph @\languagename>}}%
2617 \fi
2618 \ifx\bbbl@KVP@Alph\@nil\else
2619     \bbbl@extras@wrap{\bbbl@Alph@saved}%
2620     {\let\bbbl@Alph@saved\@Alph}%
2621     {\let\@Alph\bbbl@Alph@saved
2622     \babel@save\@Alph}%
2623     \bbbl@exp{%
2624         \bbbl@add<extras\languagename>{%
2625             \let\@Alph\<bbbl@cntr@bbbl@KVP@Alph @\languagename>}}%
2626 \fi
2627 % == Calendars ==

```

```

2628 \ifx\bb1@KVP@calendar\@nil
2629 \edef\bb1@KVP@calendar{\bb1@cl{calpr}}}%
2630 \fi
2631 \def\bb1@tempe##1 ##2\@{% Get first calendar
2632 \def\bb1@tempa{##1}}}%
2633 \bb1@exp{\bb1@tempe\bb1@KVP@calendar\space\@}%
2634 \def\bb1@tempe##1.##2.##3\@{%
2635 \def\bb1@tempc{##1}}}%
2636 \def\bb1@tempb{##2}}}%
2637 \expandafter\bb1@tempe\bb1@tempa..\@%
2638 \bb1@csarg\edef{calpr\@language}%
2639 \ifx\bb1@tempc\@empty\else
2640 calendar=\bb1@tempc
2641 \fi
2642 \ifx\bb1@tempb\@empty\else
2643 ,variant=\bb1@tempb
2644 \fi}
2645 % == require.babel in ini ==
2646 % To load or reload the babel-*.tex, if require.babel in ini
2647 \ifx\bb1@beforestart\relax\else % But not in doc aux or body
2648 \bb1@ifunset{\bb1@rqtex\@language}%
2649 {\expandafter\ifx\csname \bb1@rqtex\@language\endcsname\@empty\else
2650 \let\BabelBeforeIni\@gobbletwo
2651 \chardef\atcatcode=\catcode\@
2652 \catcode\@=11\relax
2653 \bb1@input\@texini{\bb1@cs{rqtex\@language}}}%
2654 \catcode\@=\atcatcode
2655 \let\atcatcode\relax
2656 \global\bb1@csarg\let{rqtex\@language}\relax
2657 \fi}%
2658 \bb1@foreach\bb1@calendars{%
2659 \bb1@ifunset{\bb1@ca##1}%
2660 \chardef\atcatcode=\catcode\@
2661 \catcode\@=11\relax
2662 \InputIfFileExists{babel-ca-##1.tex}{}}}%
2663 \catcode\@=\atcatcode
2664 \let\atcatcode\relax}%
2665 {}}%
2666 \fi
2667 % == frenchspacing ==
2668 \ifcase\bb1@howloaded\in@true\else\in@false\fi
2669 \ifin@else\bb1@xin@{typography/frenchspacing}{\bb1@key@list}\fi
2670 \ifin@
2671 \bb1@extras@wrap{\bb1@pre@fs}%
2672 {\bb1@pre@fs}%
2673 {\bb1@post@fs}%
2674 \fi
2675 % == Release saved transforms ==
2676 \bb1@release@transforms\relax % \relax closes the last item.
2677 % == main ==
2678 \ifx\bb1@KVP@main\@nil % Restore only if not 'main'
2679 \let\@language\bb1@savelangname
2680 \chardef\@localeid\bb1@savelocaleid\relax
2681 \fi}

```

Depending on whether or not the language exists (based on \date<language>), we define two macros. Remember \bb1@startcommands opens a group.

```

2682 \def\bb1@provide@new#1{%
2683 \namedef{date#1}}}% marks lang exists - required by \StartBabelCommands
2684 \namedef{extras#1}}}%
2685 \namedef{noextras#1}}}%
2686 \bb1@startcommands*{#1}{captions}%
2687 \ifx\bb1@KVP@captions\@nil % and also if import, implicit

```

```

2688 \def\bbl@tempb##1{%          elt for \bbl@captionslist
2689 \ifx##1\@empty\else
2690 \bbl@exp{%
2691 \\\SetString\\##1{%
2692 \\\bbl@nocaption{\bbl@stripslash##1}{#1\bbl@stripslash##1}}}%
2693 \expandafter\bbl@tempb
2694 \fi}%
2695 \expandafter\bbl@tempb\bbl@captionslist\@empty
2696 \else
2697 \ifx\bbl@initoload\relax
2698 \bbl@read@ini{\bbl@KVP@captions}2% % Here letters cat = 11
2699 \else
2700 \bbl@read@ini{\bbl@initoload}2% % Same
2701 \fi
2702 \fi
2703 \StartBabelCommands*{#1}{date}%
2704 \ifx\bbl@KVP@import\@nil
2705 \bbl@exp{%
2706 \\\SetString\\today{\\bbl@nocaption{today}{#1today}}}%
2707 \else
2708 \bbl@savetoday
2709 \bbl@savestate
2710 \fi
2711 \bbl@endcommands
2712 \bbl@load@basic{#1}%
2713 % == hyphenmins == (only if new)
2714 \bbl@exp{%
2715 \gdef\<#1hyphenmins>{%
2716 {\bbl@ifunset{\bbl@lftm@#1}{2}{\bbl@cs{lftm@#1}}}%
2717 {\bbl@ifunset{\bbl@rgtm@#1}{3}{\bbl@cs{rgtm@#1}}}%
2718 % == hyphenrules (also in renew) ==
2719 \bbl@provide@hyphens{#1}%
2720 \ifx\bbl@KVP@main\@nil\else
2721 \expandafter\main@language\expandafter{#1}%
2722 \fi}
2723 %
2724 \def\bbl@provide@renew#1{%
2725 \ifx\bbl@KVP@captions\@nil\else
2726 \StartBabelCommands*{#1}{captions}%
2727 \bbl@read@ini{\bbl@KVP@captions}2% % Here all letters cat = 11
2728 \EndBabelCommands
2729 \fi
2730 \ifx\bbl@KVP@import\@nil\else
2731 \StartBabelCommands*{#1}{date}%
2732 \bbl@savetoday
2733 \bbl@savestate
2734 \EndBabelCommands
2735 \fi
2736 % == hyphenrules (also in new) ==
2737 \ifx\bbl@lbfkflag\@empty
2738 \bbl@provide@hyphens{#1}%
2739 \fi}

```

Load the basic parameters (ids, typography, counters, and a few more), while captions and dates are left out. But it may happen some data has been loaded before automatically, so we first discard the saved values. (TODO. But preserving previous values would be useful.)

```

2740 \def\bbl@load@basic#1{%
2741 \ifcase\bbl@howloaded\or\or
2742 \ifcase\csname bbl@llevel@\language\endcsname
2743 \bbl@csarg\let{lname@\language}\relax
2744 \fi
2745 \fi
2746 \bbl@ifunset{\bbl@lname@#1}%

```



```

2747   {\def\BabelBeforeIni##1##2{%
2748     \begingroup
2749       \let\bbl@ini@captions@aux\@gobbles
2750       \def\bbl@inidate####1.####2.####3.####4\relax####5####6}%
2751       \bbl@read@ini{##1}%
2752       \ifx\bbl@initoload\relax\endinput\fi
2753     \endgroup}%
2754   \begingroup      % boxed, to avoid extra spaces:
2755     \ifx\bbl@initoload\relax
2756       \bbl@input@texini{##1}%
2757     \else
2758       \setbox\z@\hbox{\BabelBeforeIni\{bbl@initoload\}}%
2759     \fi
2760   \endgroup}%
2761   {}%

```

```

2762 \def\bbl@provide@hyphens#1{%
2763   \let\bbl@tempa\relax
2764   \ifx\bbl@KVP@hyphenrules\@nil\else
2765     \bbl@replace\bbl@KVP@hyphenrules{ }{,}%
2766     \bbl@foreach\bbl@KVP@hyphenrules{%
2767       \ifx\bbl@tempa\relax      % if not yet found
2768         \bbl@ifsamestring{##1}{+}%
2769         {{\bbl@exp{\addlanguage\<##1>}}}%
2770         {}}%
2771       \bbl@ifunset{l@##1}%
2772       {}}%
2773       {\bbl@exp{\let\bbl@tempa\<l@##1>}}}%
2774     \fi}%
2775 \fi
2776 \ifx\bbl@tempa\relax %           if no opt or no language in opt found
2777   \ifx\bbl@KVP@import\@nil
2778     \ifx\bbl@initoload\relax\else
2779       \bbl@exp{%
2780         and hyphenrules is not empty
2781         \\bbl@ifblank{\bbl@cs{hyphr@#1}}%
2782         {}}%
2783       {\let\\bbl@tempa\<l@\bbl@cl{hyphr}>}}%
2784     \fi
2785   \else % if importing
2786     \bbl@exp{%
2787       and hyphenrules is not empty
2788       \\bbl@ifblank{\bbl@cs{hyphr@#1}}%
2789       {}}%
2790     {\let\\bbl@tempa\<l@\bbl@cl{hyphr}>}}%
2791 \fi
2792 \bbl@ifunset\bbl@tempa{%
2793   ie, relax or undefined
2794   {\bbl@ifunset{l@#1}%
2795     no hyphenrules found - fallback
2796     {\bbl@exp{\adddialect\<#1>\language}}%
2797     {}}%
2798     so, l@<lang> is ok - nothing to do
2799   {\bbl@exp{\adddialect\<#1>\bbl@tempa}}}% found in opt list or ini

```

```

2796 \def\bbl@input@texini#1{%
2797   \bbl@bsphack
2798     \bbl@exp{%
2799       \catcode`\\%=14 \catcode`\\|=0
2800       \catcode`\\|={1} \catcode`\\|=2
2801       \lowercase{\|InputIfFileExists{babel-#1.tex}{}}}%
2802       \catcode`\\%= \the\catcode`\\%\relax
2803       \catcode`\\|= \the\catcode`\\|\relax
2804       \catcode`\\|={ \the\catcode`\\|\relax
2805       \catcode`\\|= \the\catcode`\\|\relax}%
2806   \bbl@esphack}

```

The following macros read and store ini files (but don't process them). For each line, there are 3 possible actions: ignore if starts with ;, switch section if starts with [, and store otherwise. There are used in the first step of \bbl@read@ini.

```

2807 \def\bbl@inline#1\bbl@inline{%
2808   \@ifnextchar[\bbl@inisect{\@ifnextchar\bbl@iniskip\bbl@inistore}#1\@@}% ]
2809 \def\bbl@inisect[#1]#2\@@{\def\bbl@section{#1}}
2810 \def\bbl@iniskip#1\@@{%      if starts with ;
2811 \def\bbl@inistore#1=#2\@@{%   full (default)
2812   \bbl@trim@def\bbl@tempa{#1}%
2813   \bbl@trim\toks@{#2}%
2814   \bbl@xin@{\bbl@section/\bbl@tempa;}{\bbl@key@list}%
2815   \ifin@ \else
2816     \bbl@exp{%
2817       \\g@addto@macro\\bbl@inidata{%
2818         \\bbl@elt{\bbl@section}{\bbl@tempa}{\the\toks@}}}%
2819   \fi}
2820 \def\bbl@inistore@min#1=#2\@@{% minimal (maybe set in \bbl@read@ini)
2821   \bbl@trim@def\bbl@tempa{#1}%
2822   \bbl@trim\toks@{#2}%
2823   \bbl@xin@{.identification.}{.\bbl@section.}%
2824   \ifin@
2825     \bbl@exp{\\g@addto@macro\\bbl@inidata{%
2826       \\bbl@elt{identification}{\bbl@tempa}{\the\toks@}}}%
2827   \fi}

```

Now, the 'main loop', which **must be executed inside a group**. At this point, \bbl@inidata may contain data declared in \babelprovide, with 'slashed' keys. There are 3 steps: first read the ini file and store it; then traverse the stored values, and process some groups if required (date, captions, labels, counters); finally, 'export' some values by defining global macros (identification, typography, characters, numbers). The second argument is 0 when called to read the minimal data for fonts; with \babelprovide it's either 1 or 2.

```

2828 \ifx\bbl@readstream\undefined
2829   \csname newread\endcsname\bbl@readstream
2830 \fi
2831 \def\bbl@read@ini#1#2{%
2832   \global\let\bbl@extend@ini\@gobble
2833   \openin\bbl@readstream=babel-#1.ini
2834   \ifeof\bbl@readstream
2835     \bbl@error
2836     {There is no ini file for the requested language\\%
2837     (#1: \language). Perhaps you misspelled it or your\\%
2838     installation is not complete.}%
2839     {Fix the name or reinstall babel.}%
2840   \else
2841     % == Store ini data in \bbl@inidata ==
2842     \catcode\`|=12 \catcode\`=12 \catcode\`==12 \catcode\`&=12
2843     \catcode\`;=12 \catcode\`=12 \catcode\`%=14 \catcode\`-=12
2844     \bbl@info{Importing
2845       \ifcase#2font and identification \or basic \fi
2846       data for \language\\%
2847       from babel-#1.ini. Reported}%
2848     \ifnum#2=\z@
2849       \global\let\bbl@inidata\@empty
2850       \let\bbl@inistore\bbl@inistore@min % Remember it's local
2851     \fi
2852     \def\bbl@section{identification}%
2853     \bbl@exp{\\bbl@inistore tag.ini=#1\\@@}%
2854     \bbl@inistore load.level=#2\@@
2855     \loop
2856     \if T\ifeof\bbl@readstream F\fi T\relax % Trick, because inside \loop
2857       \endlinechar\m@ne
2858       \read\bbl@readstream to \bbl@line
2859       \endlinechar\^^M

```

```

2860     \ifx\bbbl@line\@empty\else
2861     \expandafter\bbbl@iniline\bbbl@line\bbbl@iniline
2862     \fi
2863     \repeat
2864     % == Process stored data ==
2865     \bbbl@csarg\xdef{lini@\languagename}{#1}%
2866     \bbbl@read@ini@aux
2867     % == 'Export' data ==
2868     \bbbl@ini@exports{#2}%
2869     \global\bbbl@csarg\let{inidata@\languagename}\bbbl@inidata
2870     \global\let\bbbl@inidata\@empty
2871     \bbbl@exp{\bbbl@add@list\bbbl@ini@loaded{\languagename}}%
2872     \bbbl@tglobal\bbbl@ini@loaded
2873 \fi}
2874 \def\bbbl@read@ini@aux{%
2875   \let\bbbl@savestrings\@empty
2876   \let\bbbl@savetoday\@empty
2877   \let\bbbl@savestate\@empty
2878   \def\bbbl@elt##1##2##3{%
2879     \def\bbbl@section{##1}%
2880     \in@{=date.}{=##1}% Find a better place
2881     \ifin@
2882       \bbbl@ifunset{bbbl@inikv@##1}%
2883       {\bbbl@ini@calendar{##1}}%
2884       {}%
2885     \fi
2886     \in@{=identification/extension.}{=##1/##2}%
2887     \ifin@
2888       \bbbl@ini@extension{##2}%
2889     \fi
2890     \bbbl@ifunset{bbbl@inikv@##1}{}%
2891     {\csname bbbl@inikv@##1\endcsname{##2}{##3}}%
2892     \bbbl@inidata}

```

A variant to be used when the ini file has been already loaded, because it's not the first \babelprovide for this language.

```

2893 \def\bbbl@extend@ini@aux#1{%
2894   \bbbl@startcommands*{#1}{captions}%
2895   % Activate captions/... and modify exports
2896   \bbbl@csarg\def{inikv@captions.licr}##1##2{%
2897     \setlocalecaption{#1}{##1}{##2}%
2898     \def\bbbl@inikv@captions##1##2{%
2899       \bbbl@ini@captions@aux{##1}{##2}%
2900     \def\bbbl@stringdef##1##2{\gdef##1{##2}}%
2901     \def\bbbl@exportkey##1##2##3{%
2902       \bbbl@ifunset{bbbl@kv@##2}{}%
2903       {\expandafter\ifx\csname bbbl@kv@##2\endcsname\@empty\else
2904         \bbbl@exp{\global\let\<bbbl@##1@\languagename>\<bbbl@kv@##2>}%
2905       \fi}}%
2906   % As with \bbbl@read@ini, but with some changes
2907   \bbbl@read@ini@aux
2908   \bbbl@ini@exports\tw@
2909   % Update inidata@lang by pretending the ini is read.
2910   \def\bbbl@elt##1##2##3{%
2911     \def\bbbl@section{##1}%
2912     \bbbl@iniline##2=##3\bbbl@iniline}%
2913     \csname bbbl@inidata@#1\endcsname
2914     \global\bbbl@csarg\let{inidata@#1}\bbbl@inidata
2915   \StartBabelCommands*{#1}{date}% And from the import stuff
2916   \def\bbbl@stringdef##1##2{\gdef##1{##2}}%
2917   \bbbl@savetoday
2918   \bbbl@savestate
2919   \bbbl@endcommands}

```

A somewhat hackish tool to handle calendar sections. TODO. To be improved.

```

2920 \def\bbbl@ini@calendar#1{%
2921 \lowercase{\def\bbbl@tempa{=#1=}}%
2922 \bbbl@replace\bbbl@tempa{=date.gregorian}{}%
2923 \bbbl@replace\bbbl@tempa{=date.}{}%
2924 \in@{.licr=}{#1=}%
2925 \ifin@
2926 \ifcase\bbbl@engine
2927 \bbbl@replace\bbbl@tempa{.licr=}{}%
2928 \else
2929 \let\bbbl@tempa\relax
2930 \fi
2931 \fi
2932 \ifx\bbbl@tempa\relax\else
2933 \bbbl@replace\bbbl@tempa{=}{}%
2934 \ifx\bbbl@tempa\empty\else
2935 \xdef\bbbl@calendars{,\bbbl@tempa}%
2936 \fi
2937 \bbbl@exp{%
2938 \def\<bbbl@inikv@#1>####1####2{%
2939 \\\bbbl@inidate####1...\relax{####2}{\bbbl@tempa}}}%
2940 \fi}

```

A key with a slash in \babelprovide replaces the value in the ini file (which is ignored altogether). The mechanism is simple (but suboptimal): add the data to the ini one (at this point the ini file has not yet been read), and define a dummy macro. When the ini file is read, just skip the corresponding key and reset the macro (in \bbbl@inistore above).

```

2941 \def\bbbl@renewinikey#1/#2\@#3{%
2942 \edef\bbbl@tempa{\zap@space #1 \@empty}% section
2943 \edef\bbbl@tempb{\zap@space #2 \@empty}% key
2944 \bbbl@trim\toks@{#3}% value
2945 \bbbl@exp{%
2946 \edef\bbbl@key@list{\bbbl@key@list \bbbl@tempa/\bbbl@tempb;}%
2947 \\\g@addto@macro\bbbl@inidata{%
2948 \\\bbbl@elt{\bbbl@tempa}{\bbbl@tempb}{\the\toks@}}}%

```

The previous assignments are local, so we need to export them. If the value is empty, we can provide a default value.

```

2949 \def\bbbl@exportkey#1#2#3{%
2950 \bbbl@ifunset{\bbbl@kv@#2}%
2951 {\bbbl@csarg\gdef{#1@\language@}{#3}}%
2952 {\expandafter\ifx\csname \bbbl@kv@#2\endcsname\empty
2953 \bbbl@csarg\gdef{#1@\language@}{#3}%
2954 \else
2955 \bbbl@exp{\global\let\<bbbl@#1@\language@>\<bbbl@kv@#2>}%
2956 \fi}}

```

Key-value pairs are treated differently depending on the section in the ini file. The following macros are the readers for identification and typography. Note \bbbl@ini@exports is called always (via \bbbl@inisec), while \bbbl@after@ini must be called explicitly after \bbbl@read@ini if necessary.

```

2957 \def\bbbl@iniwarning#1{%
2958 \bbbl@ifunset{\bbbl@kv@identification.warning#1}{}%
2959 {\bbbl@warning{%
2960 From babel-\bbbl@cs{lini@\language@}.ini:\%
2961 \bbbl@cs{kv@identification.warning#1}\%
2962 Reported }}}
2963 %
2964 \let\bbbl@release@transforms\empty

```

BCP 47 extensions are separated by a single letter (eg, latin-x-medieval. The following macro handles this special case to create correctly the correspondig info.

```

2965 \def\bbbl@ini@extension#1{%
2966 \def\bbbl@tempa{#1}%

```

```

2967 \bbl@replace\bbl@tempa{extension.}{}%
2968 \bbl@replace\bbl@tempa{.tag.bcp47}{}%
2969 \bbl@ifunset\bbl@info@#1}%
2970   {\bbl@csarg\xdef{info@#1}{ext/\bbl@tempa}%
2971     \bbl@exp{%
2972       \\g@addto@macro\\bbl@moreinfo{%
2973         \\bbl@exportkey{ext/\bbl@tempa}{identification.#1}{}}}%
2974   {}}
2975 \let\bbl@moreinfo\@empty
2976 %
2977 \def\bbl@ini@exports#1{%
2978   % Identification always exported
2979   \bbl@iniwarning{}%
2980   \ifcase\bbl@engine
2981     \bbl@iniwarning{.pdflatex}%
2982   \or
2983     \bbl@iniwarning{.lua\latex}%
2984   \or
2985     \bbl@iniwarning{.xel\latex}%
2986   \fi%
2987   \bbl@exportkey{llevel}{identification.load.level}{}%
2988   \bbl@exportkey{elname}{identification.name.english}{}%
2989   \bbl@exp{\\bbl@exportkey{lname}{identification.name.opentype}%
2990     {\csname bbl@elname@\language\endcsname}}%
2991   \bbl@exportkey{tbcp}{identification.tag.bcp47}{}%
2992   \bbl@exportkey{lbcpl}{identification.language.tag.bcp47}{}%
2993   \bbl@exportkey{lotf}{identification.tag.opentype}{dflt}%
2994   \bbl@exportkey{esname}{identification.script.name}{}%
2995   \bbl@exp{\\bbl@exportkey{sname}{identification.script.name.opentype}%
2996     {\csname bbl@esname@\language\endcsname}}%
2997   \bbl@exportkey{sbcpl}{identification.script.tag.bcp47}{}%
2998   \bbl@exportkey{sotf}{identification.script.tag.opentype}{DFLT}%
2999   \bbl@exportkey{rbcp}{identification.region.tag.bcp47}{}%
3000   \bbl@exportkey{vbcp}{identification.variant.tag.bcp47}{}%
3001   \bbl@moreinfo
3002   % Also maps bcp47 -> language
3003   \ifbbl@bcptoname
3004     \bbl@csarg\xdef{bcp@map@\bbl@cl{tbcp}}{\language}%
3005   \fi
3006   % Conditional
3007   \ifnum#1>\z@           % 0 = only info, 1, 2 = basic, (re)new
3008     \bbl@exportkey{calpr}{date.calendar.preferred}{}%
3009     \bbl@exportkey{lnbrk}{typography.linebreaking}{h}%
3010     \bbl@exportkey{hyphr}{typography.hyphenrules}{}%
3011     \bbl@exportkey{lftm}{typography.lefthyphenmin}{2}%
3012     \bbl@exportkey{rgthm}{typography.righthyphenmin}{3}%
3013     \bbl@exportkey{prehc}{typography.prehyphenchar}{}%
3014     \bbl@exportkey{hyotl}{typography.hyphenate.other.locale}{}%
3015     \bbl@exportkey{hyots}{typography.hyphenate.other.script}{}%
3016     \bbl@exportkey{intsp}{typography.intraspaces}{}%
3017     \bbl@exportkey{frspc}{typography.frenchspacing}{u}%
3018     \bbl@exportkey{chrng}{characters.ranges}{}%
3019     \bbl@exportkey{quote}{characters.delimiters.quotes}{}%
3020     \bbl@exportkey{dgnat}{numbers.digits.native}{}%
3021     \ifnum#1=\tw@       % only (re)new
3022       \bbl@exportkey{rqtex}{identification.require.babel}{}%
3023       \bbl@to@global\bbl@savetoday
3024       \bbl@to@global\bbl@savestate
3025       \bbl@savestrings
3026     \fi
3027   \fi}

```

A shared handler for key=val lines to be stored in \bbl@kv@<section>.<key>.

```

3028 \def\bbl@inikv#1#2{%      key=value
3029 \toks@{#2}%              This hides #'s from ini values
3030 \bbl@csarg\edef{kv@\bbl@section.#1}{\the\toks@}}

```

By default, the following sections are just read. Actions are taken later.

```

3031 \let\bbl@inikv@identification\bbl@inikv
3032 \let\bbl@inikv@date\bbl@inikv
3033 \let\bbl@inikv@typography\bbl@inikv
3034 \let\bbl@inikv@characters\bbl@inikv
3035 \let\bbl@inikv@numbers\bbl@inikv

```

Additive numerals require an additional definition. When .1 is found, two macros are defined – the basic one, without .1 called by \localenumerals, and another one preserving the trailing .1 for the ‘units’.

```

3036 \def\bbl@inikv@counters#1#2{%
3037 \bbl@ifsamestring{#1}{digits}%
3038 {\bbl@error{The counter name 'digits' is reserved for mapping\\%
3039 decimal digits}%
3040 {Use another name.}}%
3041 }%
3042 \def\bbl@tempc{#1}%
3043 \bbl@trim@def{\bbl@tempb*}{#2}%
3044 \in@{.1$}{#1$}%
3045 \ifin@
3046 \bbl@replace\bbl@tempc{.1}{}%
3047 \bbl@csarg\protected@xdef{cntr@\bbl@tempc @\language}%
3048 \noexpand\bbl@alphanumeric{\bbl@tempc}%
3049 \fi
3050 \in@{.F.}{#1}%
3051 \ifin@else\in@{.S.}{#1}\fi
3052 \ifin@
3053 \bbl@csarg\protected@xdef{cntr@#1@\language}{\bbl@tempb*}%
3054 \else
3055 \toks@{}% Required by \bbl@buildifcase, which returns \bbl@tempa
3056 \expandafter\bbl@buildifcase\bbl@tempb* \ \ % Space after \
3057 \bbl@csarg\global\expandafter\let{cntr@#1@\language}\bbl@tempa
3058 \fi}

```

Now captions and captions.licr, depending on the engine. And below also for dates. They rely on a few auxiliary macros. It is expected the ini file provides the complete set in Unicode and LICR, in that order.

```

3059 \ifcase\bbl@engine
3060 \bbl@csarg\def{inikv@captions.licr}#1#2{%
3061 \bbl@ini@captions@aux{#1}{#2}}
3062 \else
3063 \def\bbl@inikv@captions#1#2{%
3064 \bbl@ini@captions@aux{#1}{#2}}
3065 \fi

```

The auxiliary macro for captions define \<caption>name.

```

3066 \def\bbl@ini@captions@template#1#2{% string language tempa=capt-name
3067 \bbl@replace\bbl@tempa{.template}{}%
3068 \def\bbl@toreplace{#1}{}%
3069 \bbl@replace\bbl@toreplace{[ ]}{\nobreakspace{}}%
3070 \bbl@replace\bbl@toreplace{[{}]{\csname}%
3071 \bbl@replace\bbl@toreplace{[{}]{\csname the}%
3072 \bbl@replace\bbl@toreplace{[{}]{\name\endcsname{}}}%
3073 \bbl@replace\bbl@toreplace{[{}]{\endcsname{}}}%
3074 \bbl@xin@{\bbl@tempa,}{chapter,appendix,part,}%
3075 \ifin@
3076 \nameuse{bbl@patch\bbl@tempa}%
3077 \global\bbl@csarg\let{\bbl@tempa fmt@#2}\bbl@toreplace
3078 \fi
3079 \bbl@xin@{\bbl@tempa,}{figure,table,}%

```

```

3080 \ifin@
3081 \toks@{\expandafter{\bbl@toreplace}%
3082 \bbl@exp{\gdef\<fnum@\bbl@tempa>{\the\toks@}}}%
3083 \fi}
3084 \def\bbl@ini@captions@aux#1#2{%
3085 \bbl@trim@def\bbl@tempa{#1}%
3086 \bbl@xin@{.template}{\bbl@tempa}%
3087 \ifin@
3088 \bbl@ini@captions@template{#2}\language\name
3089 \else
3090 \bbl@ifblank{#2}%
3091 {\bbl@exp{%
3092 \toks@{\bbl@nocaption{\bbl@tempa}{\language\name\bbl@tempa name}}}%
3093 {\bbl@trim\toks@{#2}}}%
3094 \bbl@exp{%
3095 \bbl@add\bbl@savestrings{%
3096 \SetString\<\bbl@tempa name>{\the\toks@}}}%
3097 \toks@{\expandafter\bbl@captionslist}%
3098 \bbl@exp{\in@{\<\bbl@tempa name>{\the\toks@}}}%
3099 \ifin@ \else
3100 \bbl@exp{%
3101 \bbl@add\<\bbl@extracaps@\language\name>{\<\bbl@tempa name>}%
3102 \bbl@to\global\<\bbl@extracaps@\language\name>}%
3103 \fi
3104 \fi}

```

Labels. Captions must contain just strings, no format at all, so there is new group in ini files.

```

3105 \def\bbl@list@the{%
3106 part,chapter,section,subsection,subsubsection,paragraph,%
3107 subparagraph,enumi,enumii,enumiii,enumiv,equation,figure,%
3108 table,page,footnote,mpfootnote,mpfn}
3109 \def\bbl@map@cnt#1{% #1:roman,etc, // #2:enumi,etc
3110 \bbl@ifunset{bbl@map@#1@\language\name}%
3111 {\@nameuse{#1}}%
3112 {\@nameuse{bbl@map@#1@\language\name}}}
3113 \def\bbl@inikv@labels#1#2{%
3114 \in@{.map}{#1}%
3115 \ifin@
3116 \ifx\bbl@KVP@labels\@nil\else
3117 \bbl@xin@{ map }{\bbl@KVP@labels\space}%
3118 \ifin@
3119 \def\bbl@tempc{#1}%
3120 \bbl@replace\bbl@tempc{.map}{}%
3121 \in@{,#2,}{,arabic,roman,Roman,alph,Alph,fnsymbol,}%
3122 \bbl@exp{%
3123 \gdef\<\bbl@map@\bbl@tempc @\language\name>%
3124 {\ifin@<#2>\else\\localecounter{#2}\fi}}%
3125 \bbl@foreach\bbl@list@the{%
3126 \bbl@ifunset{the##1}{}%
3127 {\bbl@exp{\let\bbl@tempd\<the##1>}%
3128 \bbl@exp{%
3129 \bbl@sreplace\<the##1>%
3130 {\<\bbl@tempc>{##1}}{\bbl@map@cnt{\bbl@tempc}{##1}}}%
3131 \bbl@sreplace\<the##1>%
3132 {\<\@empty @\bbl@tempc>\<c@##1>}{\bbl@map@cnt{\bbl@tempc}{##1}}}%
3133 \expandafter\ifx\csname the##1\endcsname\bbl@tempd\else
3134 \toks@{\expandafter\expandafter\expandafter{%
3135 \csname the##1\endcsname}%
3136 \expandafter\xdef\csname the##1\endcsname{\the\toks@}}%
3137 \fi}}%
3138 \fi
3139 \fi
3140 %

```

```

3141 \else
3142 %
3143 % The following code is still under study. You can test it and make
3144 % suggestions. Eg, enumerate.2 = ([enumi]).([enumii]). It's
3145 % language dependent.
3146 \in@{enumerate.}{#1}%
3147 \ifin@
3148   \def\bbl@tempa{#1}%
3149   \bbl@replace\bbl@tempa{enumerate.}{}%
3150   \def\bbl@toreplace{#2}%
3151   \bbl@replace\bbl@toreplace{[ ]}{\nobreakspace}%
3152   \bbl@replace\bbl@toreplace{[]}{\cename the}%
3153   \bbl@replace\bbl@toreplace{[]}{\endcsname}%
3154   \toks@ \expandafter\bbl@toreplace}%
3155   % TODO. Execute only once:
3156   \bbl@exp{%
3157     \\\bbl@add\<extras\language\>%
3158     \\\babel@save\<labelenum\romannumeral\bbl@tempa>%
3159     \def\<labelenum\romannumeral\bbl@tempa>\the\toks@}%
3160     \\\bbl@tglobal\<extras\language\>%
3161   \fi
3162 \fi}

```

To show correctly some captions in a few languages, we need to patch some internal macros, because the order is hardcoded. For example, in Japanese the chapter number is surrounded by two string, while in Hungarian is placed after. These replacement works in many classes, but not all. Actually, the following lines are somewhat tentative.

```

3163 \def\bbl@chapttype{chapter}
3164 \ifx\@makechapterhead\@undefined
3165   \let\bbl@patchchapter\relax
3166 \else\ifx\thechapter\@undefined
3167   \let\bbl@patchchapter\relax
3168 \else\ifx\ps@headings\@undefined
3169   \let\bbl@patchchapter\relax
3170 \else
3171   \def\bbl@patchchapter{%
3172     \global\let\bbl@patchchapter\relax
3173     \gdef\bbl@chfmt{%
3174       \bbl@ifunset\bbl@bbl@chapttype fmt@\language}%
3175       {\@chapapp\space\thechapter}
3176       {\@nameuse\bbl@bbl@chapttype fmt@\language}}
3177   \bbl@add\appendix{\def\bbl@chapttype{appendix}}% Not harmful, I hope
3178   \bbl@sreplace\ps@headings{\@chapapp\ \thechapter}{\bbl@chfmt}%
3179   \bbl@sreplace\chaptermark{\@chapapp\ \thechapter}{\bbl@chfmt}%
3180   \bbl@sreplace\@makechapterhead{\@chapapp\space\thechapter}{\bbl@chfmt}%
3181   \bbl@tglobal\appendix
3182   \bbl@tglobal\ps@headings
3183   \bbl@tglobal\chaptermark
3184   \bbl@tglobal\@makechapterhead}
3185   \let\bbl@patchappendix\bbl@patchchapter
3186 \fi\fi\fi
3187 \ifx\@part\@undefined
3188   \let\bbl@patchpart\relax
3189 \else
3190   \def\bbl@patchpart{%
3191     \global\let\bbl@patchpart\relax
3192     \gdef\bbl@partformat{%
3193       \bbl@ifunset\bbl@partfmt@\language}%
3194       {\partname\nobreakspace\thepart}
3195       {\@nameuse\bbl@partfmt@\language}}
3196   \bbl@sreplace\@part{\partname\nobreakspace\thepart}{\bbl@partformat}%
3197   \bbl@tglobal\@part}
3198 \fi

```


Date. Arguments (year, month, day) are *not* protected, on purpose. In \today, arguments are always gregorian, and therefore always converted with other calendars – @today works as an internal tag to force conversion if necessary in this particular case (it's *not* a user interface). TODO. Document

```

3199 % Arguments are _not_ protected.
3200 \let\bbl@calendar\@empty
3201 \DeclareRobustCommand\localedate[1][\bbl@localedate{#1}]
3202 \def\bbl@localedate#1#2#3#4{%
3203   \begingroup
3204     \edef\bbl@they{#2}%
3205     \edef\bbl@them{#3}%
3206     \edef\bbl@thed{#4}%
3207     \edef\bbl@tempe{%
3208       \bbl@ifunset\bbl@calpr@\language\name{}{\bbl@cl{calpr}},%
3209       #1}%
3210     \bbl@replace\bbl@tempe{ }{}%
3211     \bbl@replace\bbl@tempe{convert}{convert=}%
3212     \let\bbl@ld@calendar\@empty
3213     \let\bbl@ld@variant\@empty
3214     \let\bbl@ld@convert\relax
3215     \def\bbl@tempb##1=##2\@{\@namedef\bbl@ld@##1}{##2}}%
3216     \bbl@foreach\bbl@tempe{\bbl@tempb##1\@}%
3217     \bbl@replace\bbl@ld@calendar{gregorian}{}%
3218     \ifx\bbl@ld@calendar\@empty\else
3219       \ifx\bbl@ld@convert\relax\else
3220         \babelcalendar[\bbl@they-\bbl@them-\bbl@thed]%
3221         {\bbl@ld@calendar}\bbl@they\bbl@them\bbl@thed
3222       \fi
3223     \fi
3224     \@nameuse\bbl@precalendar}% Remove, eg, +, -civil (-ca-islamic)
3225     \edef\bbl@calendar{% Used in \month..., too
3226       \bbl@ld@calendar
3227       \ifx\bbl@ld@variant\@empty\else
3228         .\bbl@ld@variant
3229       \fi}%
3230     \bbl@cased
3231     {\@nameuse\bbl@date@\language\name @\bbl@calendar}%
3232     \bbl@they\bbl@them\bbl@thed}%
3233   \endgroup}
3234 % eg: 1=months, 2=wide, 3=1, 4=dummy, 5=value, 6=calendar
3235 \def\bbl@inidate#1.#2.#3.#4\relax#5#6{% TODO - ignore with 'captions'
3236   \bbl@trim@def\bbl@tempa{#1.#2}%
3237   \bbl@ifsamestring{\bbl@tempa}{months.wide}%           to savedate
3238   {\bbl@trim@def\bbl@tempa{#3}%
3239     \bbl@trim\toks@{#5}%
3240     \@temptokena\expandafter{\bbl@savestate}%
3241     \bbl@exp{% Reverse order - in ini last wins
3242       \def\\bbl@savestate{%
3243         \\SetString\<month\romannumeral\bbl@tempa#6name>{\the\toks@}%
3244         \the\@temptokena}}}%
3245     {\bbl@ifsamestring{\bbl@tempa}{date.long}%           defined now
3246       {\lowercase{\def\bbl@tempb{#6}}%
3247         \bbl@trim@def\bbl@toreplace{#5}%
3248         \bbl@TG@@date
3249         \global\bbl@csarg\let{date@\language\name @\bbl@tempb}\bbl@toreplace
3250         \ifx\bbl@savestate\@empty
3251           \bbl@exp{% TODO. Move to a better place.
3252             \\AfterBabelCommands{%
3253               \def\<\language\name date>{\protect\<\language\name date >}%
3254               \newcommand\<\language\name date >[4][\{
3255                 \\bbl@usedategroupttrue
3256                 \<bbl@ensure@\language\name>{%
3257                   \\localedate[#####1]{#####2}{#####3}{#####4}}}%
3258               \def\\bbl@savestate{%

```

```

3259          \\\SetString\\today{%
3260          \<\language name date>[convert]%
3261          {\the\year}{\the\month}{\the\day}}}%
3262          \fi}%
3263          {}}}

```

Dates will require some macros for the basic formatting. They may be redefined by language, so “semi-public” names (camel case) are used. Oddly enough, the CLDR places particles like “de” inconsistently in either in the date or in the month name. Note after \bbl@replace \toks@ contains the resulting string, which is used by \bbl@replace@finish@iii (this implicit behavior doesn’t seem a good idea, but it’s efficient).

```

3264 \let\bbl@calendar\@empty
3265 \newcommand\babelcalendar[2][\the\year-\the\month-\the\day]{%
3266   \@nameuse{\bbl@ca#2}#1\@}
3267 \newcommand\BabelDateSpace{\nobreakspace}
3268 \newcommand\BabelDateDot{. \@} % TODO. \let instead of repeating
3269 \newcommand\BabelDated[1]{\number#1}
3270 \newcommand\BabelDatedd[1]{\ifnum#1<10 0\fi\number#1}
3271 \newcommand\BabelDateM[1]{\number#1}
3272 \newcommand\BabelDateMM[1]{\ifnum#1<10 0\fi\number#1}
3273 \newcommand\BabelDateMMM[1]{\number#1}
3274 \csname month\romannumeral#1\bbl@calendar name\endcsname}%
3275 \newcommand\BabelDatey[1]{\number#1}%
3276 \newcommand\BabelDateyy[1]{\number#1}%
3277 \ifnum#1<10 0\number#1 %
3278 \else\ifnum#1<100 \number#1 %
3279 \else\ifnum#1<1000 \expandafter\@gobble\number#1 %
3280 \else\ifnum#1<10000 \expandafter\@gobbletwo\number#1 %
3281 \else
3282   \bbl@error
3283   {Currently two-digit years are restricted to the\
3284     range 0-9999.}%
3285   {There is little you can do. Sorry.}%
3286   \fi\fi\fi\fi}
3287 \newcommand\BabelDateyyyy[1]{\number#1} % TODO - add leading 0
3288 \def\bbl@replace@finish@iii#1{%
3289   \bbl@exp{\def\#1####1####2####3{\the\toks@}}
3290   \def\bbl@TG@date{%
3291     \bbl@replace\bbl@toreplace{[ ]}{\BabelDateSpace}}%
3292     \bbl@replace\bbl@toreplace{[. ]}{\BabelDateDot}}%
3293     \bbl@replace\bbl@toreplace{[d]}{\BabelDated{####3}}%
3294     \bbl@replace\bbl@toreplace{[dd]}{\BabelDatedd{####3}}%
3295     \bbl@replace\bbl@toreplace{[M]}{\BabelDateM{####2}}%
3296     \bbl@replace\bbl@toreplace{[MM]}{\BabelDateMM{####2}}%
3297     \bbl@replace\bbl@toreplace{[MMM]}{\BabelDateMMM{####2}}%
3298     \bbl@replace\bbl@toreplace{[y]}{\BabelDatey{####1}}%
3299     \bbl@replace\bbl@toreplace{[yy]}{\BabelDateyy{####1}}%
3300     \bbl@replace\bbl@toreplace{[yyyy]}{\BabelDateyyyy{####1}}%
3301     \bbl@replace\bbl@toreplace{[y]}{\bbl@datecctr[####1]}%
3302     \bbl@replace\bbl@toreplace{[m]}{\bbl@datecctr[####2]}%
3303     \bbl@replace\bbl@toreplace{[d]}{\bbl@datecctr[####3]}%
3304     \bbl@replace@finish@iii\bbl@toreplace}
3305 \def\bbl@datecctr{\expandafter\bbl@xdatecctr\expandafter}
3306 \def\bbl@xdatecctr[#1|#2]{\localenumeral{#2}{#1}}

```

Transforms.

```

3307 \let\bbl@release@transforms\@empty
3308 \@namedef{\bbl@inikv@transforms.prehyphenation}{%
3309   \bbl@transforms\babelprehyphenation}
3310 \@namedef{\bbl@inikv@transforms.posthyphenation}{%
3311   \bbl@transforms\babelposthyphenation}
3312 \def\bbl@transforms@aux#1#2#3#4,#5\relax{%
3313   #1[#2]{#3}{#4}{#5}}
3314 \begingroup % A hack. TODO. Don't require an specific order

```

```

3315 \catcode\%=12
3316 \catcode\&=14
3317 \gdef\bbl@transforms#1#2#3{&%
3318   \ifx\bbl@KVP@transforms\@nil\else
3319     \directlua{
3320       local str = [=[#2]=]
3321       str = str:gsub('%.%d+%.%d+$', '')
3322       tex.print([[def\string\babeltempa{]] .. str .. [[]]])
3323     }&%
3324     \bbl@xin@{,\babeltempa,}{,\bbl@KVP@transforms,}&%
3325     \ifin@
3326       \in@{.0$}{#2$}&%
3327     \ifin@
3328       \directlua{
3329         local str = string.match([[ \bbl@KVP@transforms]],
3330           '%(([^%(-)]%)[^%)]-\babeltempa')
3331         if str == nil then
3332           tex.print([[def\string\babeltempb{]])
3333         else
3334           tex.print([[def\string\babeltempb{,attribute=]] .. str .. [[]]])
3335         end
3336       }
3337       \toks@{#3}&%
3338       \bbl@exp{&%
3339         \\g@addto@macro\\bbl@release@transforms{&%
3340           \relax &% Closes previous \bbl@transforms@aux
3341           \\bbl@transforms@aux
3342           \\#1{label=\babeltempa\babeltempb}{\language}\the\toks@}}&%
3343       \else
3344         \g@addto@macro\bbl@release@transforms{, {#3}}&%
3345       \fi
3346     \fi
3347   \fi}
3348 \endgroup

```

Language and Script values to be used when defining a font or setting the direction are set with the following macros.

```

3349 \def\bbl@provide@lsys#1{%
3350   \bbl@ifunset{bbl@lname@#1}%
3351     {\bbl@load@info{#1}}%
3352   {%
3353     \bbl@csarg\let{lsys@#1}\@empty
3354     \bbl@ifunset{bbl@sname@#1}{\bbl@csarg\gdef{sname@#1}{Default}}}%
3355     \bbl@ifunset{bbl@sotf@#1}{\bbl@csarg\gdef{sotf@#1}{DFLT}}}%
3356     \bbl@csarg\bbl@add@list{lsys@#1}{Script=\bbl@cs{sname@#1}}%
3357     \bbl@ifunset{bbl@lname@#1}{%
3358       {\bbl@csarg\bbl@add@list{lsys@#1}{Language=\bbl@cs{lname@#1}}}%
3359     \ifcase\bbl@engine\or
3360       \bbl@ifunset{bbl@prehc@#1}{%
3361         {\bbl@exp{\\bbl@ifblank{\bbl@cs{prehc@#1}}}%
3362         }%
3363         {\ifx\bbl@xenohyph\@undefined
3364           \let\bbl@xenohyph\bbl@xenohyph@d
3365           \ifx\AtBeginDocument\@notprerr
3366             \expandafter\@secondoftwo % to execute right now
3367           \fi
3368           \AtBeginDocument{%
3369             \bbl@patchfont{\bbl@xenohyph}%
3370             \expandafter\selectlanguage\expandafter{\language}%
3371           \fi}}%
3372       \fi
3373     \bbl@csarg\bbl@to@global{lsys@#1}}
3374 \def\bbl@xenohyph@d{%

```

```

3375 \bbl@ifset{\bbl@prehc@\language\name}%
3376   {\ifnum\hyphenchar\font=\defaultshyphenchar
3377     \iffontchar\font\bbl@cl{prehc}\relax
3378     \hyphenchar\font\bbl@cl{prehc}\relax
3379     \else\iffontchar\font"200B
3380       \hyphenchar\font"200B
3381     \else
3382       \bbl@warning
3383       {Neither 0 nor ZERO WIDTH SPACE are available\\%
3384         in the current font, and therefore the hyphen\\%
3385         will be printed. Try changing the fontspec's\\%
3386         'HyphenChar' to another value, but be aware\\%
3387         this setting is not safe (see the manual)}%
3388       \hyphenchar\font\defaultshyphenchar
3389     \fi\fi
3390   \fi}%
3391   {\hyphenchar\font\defaultshyphenchar}}
3392 % \fi}

```

```

3393 \def\bbl@load@info#1{%
3394   \def\BabelBeforeIni##1##2{%
3395     \begingroup
3396       \bbl@read@ini{##1}0%
3397       \endinput           % babel- .tex may contain onlypreamble's
3398       \endgroup}%        boxed, to avoid extra spaces:
3399   {\bbl@input@texini{#1}}}
```

[illegible]

```
3430 \bbl@tempa}
```

Alphabetic counters must be converted from a space separated list to an \ifcase structure.

```
3431 \def\bbl@buildifcase#1 {% Returns \bbl@tempa, requires \toks@={}%
3432 \ifx\#1% % \ before, in case #1 is multiletter
3433 \bbl@exp{%
3434 \def\#1\bbl@tempa###1{%
3435 \<ifcase>###1\space\the\toks@\<else>\@ctrerr\<fi>}%
3436 \else
3437 \toks@\expandafter{\the\toks@\or #1}%
3438 \expandafter\bbl@buildifcase
3439 \fi}
```

The code for additive counters is somewhat tricky and it's based on the fact the arguments just before @@ collects digits which have been left 'unused' in previous arguments, the first of them being the number of digits in the number to be converted. This explains the reverse set 76543210. Digits above 10000 are not handled yet. When the key contains the subkey .F., the number after is treated as an special case, for a fixed form (see babel-he.ini, for example).

```
3440 \newcommand\localenumeral[2]{\bbl@cs{cntr@#1@language}{#2}}
3441 \def\bbl@localecntr#1#2{\localenumeral{#2}{#1}}
3442 \newcommand\localecounter[2]{%
3443 \expandafter\bbl@localecntr
3444 \expandafter{\number\csname c@#2\endcsname}{#1}}
3445 \def\bbl@alphanumeric#1#2{%
3446 \expandafter\bbl@alphanumeric@i\number#2 76543210\@@{#1}}
3447 \def\bbl@alphanumeric@i#1#2#3#4#5#6#7#8\@@#9{%
3448 \ifcase\@car#8\@nil\or % Currenty <10000, but prepared for bigger
3449 \bbl@alphanumeric@ii{#9}000000#1\or
3450 \bbl@alphanumeric@ii{#9}00000#1#2\or
3451 \bbl@alphanumeric@ii{#9}0000#1#2#3\or
3452 \bbl@alphanumeric@ii{#9}000#1#2#3#4\else
3453 \bbl@alphanum@invalid{>9999}%
3454 \fi}
3455 \def\bbl@alphanumeric@ii#1#2#3#4#5#6#7#8{%
3456 \bbl@ifunset{bbl@cntr@#1.F.\number#5#6#7#8@language}%
3457 {\bbl@cs{cntr@#1.4@language}{#5}%
3458 \bbl@cs{cntr@#1.3@language}{#6}%
3459 \bbl@cs{cntr@#1.2@language}{#7}%
3460 \bbl@cs{cntr@#1.1@language}{#8}%
3461 \ifnum#6#7#8>\z@ % TODO. An ad hoc rule for Greek. Ugly.
3462 \bbl@ifunset{bbl@cntr@#1.S.321@language}{}%
3463 {\bbl@cs{cntr@#1.S.321@language}{}}%
3464 \fi}%
3465 {\bbl@cs{cntr@#1.F.\number#5#6#7#8@language}}}%
3466 \def\bbl@alphanum@invalid#1{%
3467 \bbl@error{Alphabetic numeral too large (#1)}%
3468 {Currently this is the limit.}}
```

The information in the identification section can be useful, so the following macro just exposes it with a user command.

```
3469 \def\bbl@localeinfo#1#2{%
3470 \bbl@ifunset{bbl@info@#2}{#1}%
3471 {\bbl@ifunset{bbl@csname bbl@info@#2\endcsname @language}{#1}%
3472 {\bbl@cs{csname bbl@info@#2\endcsname @language}}}%
3473 \newcommand\localeinfo[1]{%
3474 \ifx*#1\empty % TODO. A bit hackish to make it expandable.
3475 \bbl@afterelse\bbl@localeinfo{}%
3476 \else
3477 \bbl@localeinfo
3478 {\bbl@error{I've found no info for the current locale.\%
3479 The corresponding ini file has not been loaded\%
3480 Perhaps it doesn't exist}%
3481 {See the manual for details.}}%
3482 {#1}%
```

```

3483 \fi}
3484 % \@namedef{bbl@info@name.locale}{lcname}
3485 \@namedef{bbl@info@tag.ini}{lini}
3486 \@namedef{bbl@info@name.english}{elname}
3487 \@namedef{bbl@info@name.opentype}{lname}
3488 \@namedef{bbl@info@tag.bcp47}{tbc}
3489 \@namedef{bbl@info@language.tag.bcp47}{lbc}
3490 \@namedef{bbl@info@tag.opentype}{lotf}
3491 \@namedef{bbl@info@script.name}{esname}
3492 \@namedef{bbl@info@script.name.opentype}{sname}
3493 \@namedef{bbl@info@script.tag.bcp47}{sbc}
3494 \@namedef{bbl@info@script.tag.opentype}{sotf}
3495 \@namedef{bbl@info@region.tag.bcp47}{rbcp}
3496 \@namedef{bbl@info@variant.tag.bcp47}{vbc}
3497 % Extensions are dealt with in a special way
3498 % Now, an internal \LaTeX{} macro:
3499 \providecommand\BCPdata[1]{\localeinfo*{#1.tag.bcp47}}

```

With version 3.75 \BabelEnsureInfo is executed always, but there is an option to disable it.

```

3500 <<More package options>> ≡
3501 \DeclareOption{ensureinfo=off}{}
3502 <</More package options>>
3503 %
3504 \let\bbl@ensureinfo\@gobble
3505 \newcommand\BabelEnsureInfo{%
3506   \ifx\InputIfFileExists\@undefined\else
3507     \def\bbl@ensureinfo##1{%
3508       \bbl@ifunset{bbl@lname@##1}{\bbl@load@info{##1}}{}}%
3509   \fi
3510   \bbl@foreach\bbl@loaded{%
3511     \def\language{##1}%
3512     \bbl@ensureinfo{##1}}}%
3513 \ifpackagewith{babel}{ensureinfo=off}{}%
3514 {\AtEndOfPackage{% Test for plain.
3515   \ifx\@undefined\bbl@loaded\else\BabelEnsureInfo\fi}}

```

More general, but non-expandable, is \getlocaleproperty. To inspect every possible loaded ini, we define \LocaleForEach, where \bbl@ini@loaded is a comma-separated list of locales, built by \bbl@read@ini.

```

3516 \newcommand\getlocaleproperty{%
3517   \ifstar\bbl@getproperty@s\bbl@getproperty@x}
3518 \def\bbl@getproperty@s#1#2#3{%
3519   \let#1\relax
3520   \def\bbl@elt##1##2##3{%
3521     \bbl@ifsamestring{##1/##2}{##3}%
3522     {\providecommand#1{##3}%
3523     \def\bbl@elt####1####2####3{}}}%
3524   {}}%
3525   \bbl@cs{inidata@#2}}%
3526 \def\bbl@getproperty@x#1#2#3{%
3527   \bbl@getproperty@s{#1}{#2}{#3}%
3528   \ifx#1\relax
3529     \bbl@error
3530     {Unknown key for locale '#2':\%
3531     #3\%
3532     \string#1 will be set to \relax}%
3533     {Perhaps you misspelled it.}%
3534   \fi}
3535 \let\bbl@ini@loaded\@empty
3536 \newcommand\LocaleForEach{\bbl@foreach\bbl@ini@loaded}

```

8 Adjusting the Babel bahavior

A generic high level inteface is provided to adjust some global and general settings.

```
3537 \newcommand\babeladjust[1]{% TODO. Error handling.
3538   \bbl@forkv{#1}{%
3539     \bbl@ifunset{bbl@ADJ@##1@##2}%
3540     {\bbl@cs{ADJ@##1}{##2}}%
3541     {\bbl@cs{ADJ@##1@##2}}}
3542 %
3543 \def\bbl@adjust@lua#1#2{%
3544   \ifvmode
3545     \ifnum\currentgrouplevel=\z@
3546       \directlua{ Babel.#2 }%
3547       \expandafter\expandafter\expandafter\@gobble
3548     \fi
3549   \fi
3550   {\bbl@error   % The error is gobbled if everything went ok.
3551     {Currently, #1 related features can be adjusted only\\%
3552       in the main vertical list.}%
3553     {Maybe things change in the future, but this is what it is.}}}
3554 \@namedef{bbl@ADJ@bidi.mirroring@on}{%
3555   \bbl@adjust@lua{bidi}{mirroring_enabled=true}}
3556 \@namedef{bbl@ADJ@bidi.mirroring@off}{%
3557   \bbl@adjust@lua{bidi}{mirroring_enabled=false}}
3558 \@namedef{bbl@ADJ@bidi.text@on}{%
3559   \bbl@adjust@lua{bidi}{bidi_enabled=true}}
3560 \@namedef{bbl@ADJ@bidi.text@off}{%
3561   \bbl@adjust@lua{bidi}{bidi_enabled=false}}
3562 \@namedef{bbl@ADJ@bidi.mapdigits@on}{%
3563   \bbl@adjust@lua{bidi}{digits_mapped=true}}
3564 \@namedef{bbl@ADJ@bidi.mapdigits@off}{%
3565   \bbl@adjust@lua{bidi}{digits_mapped=false}}
3566 %
3567 \@namedef{bbl@ADJ@linebreak.sea@on}{%
3568   \bbl@adjust@lua{linebreak}{sea_enabled=true}}
3569 \@namedef{bbl@ADJ@linebreak.sea@off}{%
3570   \bbl@adjust@lua{linebreak}{sea_enabled=false}}
3571 \@namedef{bbl@ADJ@linebreak.cjk@on}{%
3572   \bbl@adjust@lua{linebreak}{cjk_enabled=true}}
3573 \@namedef{bbl@ADJ@linebreak.cjk@off}{%
3574   \bbl@adjust@lua{linebreak}{cjk_enabled=false}}
3575 \@namedef{bbl@ADJ@justify.arabic@on}{%
3576   \bbl@adjust@lua{linebreak}{arabic.justify_enabled=true}}
3577 \@namedef{bbl@ADJ@justify.arabic@off}{%
3578   \bbl@adjust@lua{linebreak}{arabic.justify_enabled=false}}
3579 %
3580 \def\bbl@adjust@layout#1{%
3581   \ifvmode
3582     #1%
3583     \expandafter\expandafter\@gobble
3584   \fi
3585   {\bbl@error   % The error is gobbled if everything went ok.
3586     {Currently, layout related features can be adjusted only\\%
3587       in vertical mode.}%
3588     {Maybe things change in the future, but this is what it is.}}}
3589 \@namedef{bbl@ADJ@layout.tabular@on}{%
3590   \bbl@adjust@layout{\let\@tabular\bbl@NL@tabular}}
3591 \@namedef{bbl@ADJ@layout.tabular@off}{%
3592   \bbl@adjust@layout{\let\@tabular\bbl@OL@tabular}}
3593 \@namedef{bbl@ADJ@layout.lists@on}{%
3594   \bbl@adjust@layout{\let\list\bbl@NL@list}}
3595 \@namedef{bbl@ADJ@layout.lists@off}{%
3596   \bbl@adjust@layout{\let\list\bbl@OL@list}}
```

```

3597 \@namedef{bbl@ADJ@hyphenation.extra@on}{%
3598   \bbl@activateposthyphen}
3599 %
3600 \@namedef{bbl@ADJ@autoload.bcp47@on}{%
3601   \bbl@bcpallowedtrue}
3602 \@namedef{bbl@ADJ@autoload.bcp47@off}{%
3603   \bbl@bcpallowedfalse}
3604 \@namedef{bbl@ADJ@autoload.bcp47.prefix}#1{%
3605   \def\bbl@bcp@prefix{#1}}
3606 \def\bbl@bcp@prefix{bcp47-}
3607 \@namedef{bbl@ADJ@autoload.options}#1{%
3608   \def\bbl@autoload@options{#1}}
3609 \let\bbl@autoload@bcptoptions\empty
3610 \@namedef{bbl@ADJ@autoload.bcp47.options}#1{%
3611   \def\bbl@autoload@bcptoptions{#1}}
3612 \newif\ifbbl@bcptname
3613 \@namedef{bbl@ADJ@bcp47.toname@on}{%
3614   \bbl@bcptnametrue}
3615   \BabelEnsureInfo}
3616 \@namedef{bbl@ADJ@bcp47.toname@off}{%
3617   \bbl@bcptnamefalse}
3618 \@namedef{bbl@ADJ@prehyphenation.disable@nohyphenation}{%
3619   \directlua{ Babel.ignore_pre_char = function(node)
3620     return (node.lang == \the\csname l@nohyphenation\endcsname)
3621   end }}
3622 \@namedef{bbl@ADJ@prehyphenation.disable@off}{%
3623   \directlua{ Babel.ignore_pre_char = function(node)
3624     return false
3625   end }}
3626 \@namedef{bbl@ADJ@select.write@shift}{%
3627   \let\bbl@restorelastskip\relax
3628   \def\bbl@savelastskip{%
3629     \let\bbl@restorelastskip\relax
3630     \ifvmode
3631       \ifdim\lastskip=\z@
3632         \let\bbl@restorelastskip\nobreak
3633       \else
3634         \bbl@exp{%
3635           \def\\bbl@restorelastskip{%
3636             \skip@=\the\lastskip
3637             \\nobreak \vskip-\skip@ \vskip\skip@}}%
3638       \fi
3639     \fi}}
3640 \@namedef{bbl@ADJ@select.write@keep}{%
3641   \let\bbl@restorelastskip\relax
3642   \let\bbl@savelastskip\relax}
3643 \@namedef{bbl@ADJ@select.write@omit}{%
3644   \let\bbl@restorelastskip\relax
3645   \def\bbl@savelastskip##1\bbl@restorelastskip{}}

```

As the final task, load the code for lua. TODO: use babel name, override

```

3646 \ifx\directlua\undefined\else
3647   \ifx\bbl@luapatterns\undefined
3648     \input luababel.def
3649   \fi
3650 \fi

```

Continue with \LaTeX .

```

3651 </package | core>
3652 <*package>

```

8.1 Cross referencing macros

The \LaTeX book states:

The *key* argument is any sequence of letters, digits, and punctuation symbols; upper- and lowercase letters are regarded as different.

When the above quote should still be true when a document is typeset in a language that has active characters, special care has to be taken of the category codes of these characters when they appear in an argument of the cross referencing macros.

When a cross referencing command processes its argument, all tokens in this argument should be character tokens with category ‘letter’ or ‘other’.

The following package options control which macros are to be redefined.

```
3653 <(*More package options)> ≡
3654 \DeclareOption{safe=none}{\let\bbl@opt@safe\empty}
3655 \DeclareOption{safe=bib}{\def\bbl@opt@safe{B}}
3656 \DeclareOption{safe=ref}{\def\bbl@opt@safe{R}}
3657 \DeclareOption{safe=refbib}{\def\bbl@opt@safe{BR}}
3658 \DeclareOption{safe=bibref}{\def\bbl@opt@safe{BR}}
3659 <(/More package options)>
```

\@newl@bel First we open a new group to keep the changed setting of `\protect` local and then we set the `@safe@actives` switch to true to make sure that any shorthand that appears in any of the arguments immediately expands to its non-active self.

```
3660 \bbl@trace{Cross referencing macros}
3661 \ifx\bbl@opt@safe\empty\else % ie, if 'ref' and/or 'bib'
3662   \def\@newl@bel#1#2#3{%
3663     \@safe@activetrue
3664     \bbl@ifunset{#1@#2}%
3665     \relax
3666     {\gdef\@multiplelabels{%
3667       \@latex@warning@no@line{There were multiply-defined labels}}%
3668       \@latex@warning@no@line{Label `#2' multiply defined}}%
3669     \global\@namedef{#1@#2}{#3}}}
```

\@testdef An internal ~~TeX~~ macro used to test if the labels that have been written on the .aux file have changed. It is called by the `\enddocument` macro.

```
3670 \CheckCommand*\@testdef[3]{%
3671   \def\reserved@a{#3}%
3672   \expandafter\ifx\csname#1@#2\endcsname\reserved@a
3673   \else
3674   \@tempwattrue
3675   \fi}
```

Now that we made sure that `\@testdef` still has the same definition we can rewrite it. First we make the shorthands ‘safe’. Then we use `\bbl@tempa` as an ‘alias’ for the macro that contains the label which is being checked. Then we define `\bbl@tempb` just as `\@newl@bel` does it. When the label is defined we replace the definition of `\bbl@tempa` by its meaning. If the label didn’t change, `\bbl@tempa` and `\bbl@tempb` should be identical macros.

```
3676 \def\@testdef#1#2#3{% TODO. With @samestring?
3677   \@safe@activetrue
3678   \expandafter\let\expandafter\bbl@tempa\csname #1@#2\endcsname
3679   \def\bbl@tempb{#3}%
3680   \@safe@activesfalse
3681   \ifx\bbl@tempa\relax
3682   \else
3683     \edef\bbl@tempa{\expandafter\strip@prefix\meaning\bbl@tempa}%
3684     \fi
3685     \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
3686     \ifx\bbl@tempa\bbl@tempb
3687     \else
3688     \@tempwattrue
3689     \fi
3690 \fi}
```

\ref The same holds for the macro `\ref` that references a label and `\pageref` to reference a page. We make them robust as well (if they weren’t already) to prevent problems if they should become expanded at the wrong moment.

```

3691 \bbl@xin@{R}\bbl@opt@safe
3692 \ifin@
3693 \edef\bbl@tempc{\expandafter\string\csname ref code\endcsname}%
3694 \bbl@xin@{\expandafter\strip@prefix\meaning\bbl@tempc}%
3695 {\expandafter\strip@prefix\meaning\ref}%
3696 \ifin@
3697 \bbl@redefine\@kernel@ref#1{%
3698 \@safe@activetrue\org@@kernel@ref{#1}\@safe@activesfalse}
3699 \bbl@redefine\@kernel@pageref#1{%
3700 \@safe@activetrue\org@@kernel@pageref{#1}\@safe@activesfalse}
3701 \bbl@redefine\@kernel@sref#1{%
3702 \@safe@activetrue\org@@kernel@sref{#1}\@safe@activesfalse}
3703 \bbl@redefine\@kernel@spageref#1{%
3704 \@safe@activetrue\org@@kernel@spageref{#1}\@safe@activesfalse}
3705 \else
3706 \bbl@redefineroast\ref#1{%
3707 \@safe@activetrue\org@ref{#1}\@safe@activesfalse}
3708 \bbl@redefineroast\pageref#1{%
3709 \@safe@activetrue\org@pageref{#1}\@safe@activesfalse}
3710 \fi
3711 \else
3712 \let\org@ref\ref
3713 \let\org@pageref\pageref
3714 \fi

```

`\@citex` The macro used to cite from a bibliography, `\cite`, uses an internal macro, `\@citex`. It is this internal macro that picks up the argument(s), so we redefine this internal macro and leave `\cite` alone. The first argument is used for typesetting, so the shorthands need only be deactivated in the second argument.

```

3715 \bbl@xin@{B}\bbl@opt@safe
3716 \ifin@
3717 \bbl@redefine\@citex[#1]#2{%
3718 \@safe@activetrue\edef\@tempa{#2}\@safe@activesfalse
3719 \org@@citex[#1]{\@tempa}}

```

Unfortunately, the packages `natbib` and `cite` need a different definition of `\@citex`... To begin with, `natbib` has a definition for `\@citex` with *three* arguments... We only know that a package is loaded when `\begin{document}` is executed, so we need to postpone the different redefinition.

```

3720 \AtBeginDocument{%
3721 \@ifpackageloaded{natbib}{%

```

Notice that we use `\def` here instead of `\bbl@redefine` because `\org@@citex` is already defined and we don't want to overwrite that definition (it would result in parameter stack overflow because of a circular definition).

(Recent versions of `natbib` change dynamically `\@citex`, so PR4087 doesn't seem fixable in a simple way. Just load `natbib` before.)

```

3722 \def\@citex[#1][#2]#3{%
3723 \@safe@activetrue\edef\@tempa{#3}\@safe@activesfalse
3724 \org@@citex[#1][#2]{\@tempa}}%
3725 }{}

```

The package `cite` has a definition of `\@citex` where the shorthands need to be turned off in both arguments.

```

3726 \AtBeginDocument{%
3727 \@ifpackageloaded{cite}{%
3728 \def\@citex[#1]#2{%
3729 \@safe@activetrue\org@@citex[#1][#2]\@safe@activesfalse}%
3730 }{}

```

`\nocite` The macro `\nocite` which is used to instruct BiBTeX to extract uncited references from the database.

```

3731 \bbl@redefine\nocite#1{%
3732 \@safe@activetrue\org@nocite{#1}\@safe@activesfalse}

```

`\bibcite` The macro that is used in the .aux file to define citation labels. When packages such as natbib or cite are not loaded its second argument is used to typeset the citation label. In that case, this second argument can contain active characters but is used in an environment where `\@safe@activetrue` is in effect. This switch needs to be reset inside the `\hbox` which contains the citation label. In order to determine during .aux file processing which definition of `\bibcite` is needed we define `\bibcite` in such a way that it redefines itself with the proper definition. We call `\bbl@cite@choice` to select the proper definition for `\bibcite`. This new definition is then activated.

```
3733 \bbl@redefine\bibcite{%
3734   \bbl@cite@choice
3735   \bibcite}
```

`\bbl@bibcite` The macro `\bbl@bibcite` holds the definition of `\bibcite` needed when neither natbib nor cite is loaded.

```
3736 \def\bbl@bibcite#1#2{%
3737   \org@bibcite{#1}{\@safe@activesfalse#2}}
```

`\bbl@cite@choice` The macro `\bbl@cite@choice` determines which definition of `\bibcite` is needed. First we give `\bibcite` its default definition.

```
3738 \def\bbl@cite@choice{%
3739   \global\let\bibcite\bbl@bibcite
3740   \@ifpackageloaded{natbib}{\global\let\bibcite\org@bibcite}{}%
3741   \@ifpackageloaded{cite}{\global\let\bibcite\org@bibcite}{}%
3742   \global\let\bbl@cite@choice\relax}
```

When a document is run for the first time, no .aux file is available, and `\bibcite` will not yet be properly defined. In this case, this has to happen before the document starts.

```
3743 \AtBeginDocument{\bbl@cite@choice}
```

`\@bibitem` One of the two internal \TeX macros called by `\bibitem` that write the citation label on the .aux file.

```
3744 \bbl@redefine\@bibitem#1{%
3745   \@safe@activetrue\org@bibitem{#1}\@safe@activesfalse}
3746 \else
3747   \let\org@nocite\nocite
3748   \let\org@@citex\@citex
3749   \let\org@bibcite\bibcite
3750   \let\org@@bibitem\@bibitem
3751 \fi
```

8.2 Marks

`\markright` Because the output routine is asynchronous, we must pass the current language attribute to the head lines. To achieve this we need to adapt the definition of `\markright` and `\markboth` somewhat. However, headlines and footlines can contain text outside marks; for that we must take some actions in the output routine if the 'headfoot' options is used.

We need to make some redefinitions to the output routine to avoid an endless loop and to correctly handle the page number in bidi documents.

```
3752 \bbl@trace{Marks}
3753 \IfBabelLayout{sectioning}
3754   {\ifx\bbl@opt@headfoot\@nnil
3755     \g@addto@macro\@resetactivechars{%
3756       \set@typeset@protect
3757       \expandafter\select@language\x\expandafter{\bbl@main@language}%
3758       \let\protect\noexpand
3759       \ifcase\bbl@bidimode\else % Only with bidi. See also above
3760         \edef\thepage{%
3761           \noexpand\babelsublr{\unexpanded\expandafter{\thepage}}}%
3762       \fi}%
3763   \fi}
3764 {\ifbbl@single\else
3765   \bbl@ifunset{markright }{\bbl@redefine\bbl@redefineroobust
3766     \markright#1{%
3767       \bbl@ifblank{#1}%
```

```

3768      {\org@markright{}}}%
3769      {\toks@{#1}}%
3770      \bbl@exp{%
3771          \\\org@markright{\\protect\\foreignlanguage{\language\language}%
3772              {\protect\\bbl@restore@actives\the\toks@}}}%
\markboth The definition of \markboth is equivalent to that of \markright, except that we need two token
\@mkboth registers. The documentclasses report and book define and set the headings for the page. While
doing so they also store a copy of \markboth in \@mkboth. Therefore we need to check whether
\@mkboth has already been set. If so we need to do that again with the new definition of \markboth.
(As of Oct 2019, LATEX stores the definition in an intermediate macro, so it's not necessary anymore,
but it's preserved for older versions.)
3773      \ifx\@mkboth\markboth
3774          \def\bbl@tempc{\let\@mkboth\markboth}
3775      \else
3776          \def\bbl@tempc{
3777              \fi
3778              \bbl@ifunset{markboth } \bbl@redefine\bbl@redefineroobust
3779              \markboth#1#2{%
3780                  \protected@edef\bbl@tempb##1{%
3781                      \protect\foreignlanguage
3782                      {\language\language}{\protect\bbl@restore@actives##1}}%
3783                  \bbl@ifblank{#1}%
3784                  {\toks@{}}%
3785                  {\toks@\expandafter{\bbl@tempb{#1}}}%
3786                  \bbl@ifblank{#2}%
3787                  {\@temptokena{}}%
3788                  {\@temptokena\expandafter{\bbl@tempb{#2}}}%
3789                  \bbl@exp{\\org@markboth{\the\toks@}{\the\@temptokena}}%
3790                  \bbl@tempc
3791              \fi} % end ifbbl@single, end \IfBabelLayout

```

8.3 Preventing clashes with other packages

8.3.1 ifthen

`\ifthenelse` Sometimes a document writer wants to create a special effect depending on the page a certain fragment of text appears on. This can be achieved by the following piece of code:

```

\ifthenelse{\isodd{\pageref{some:label}}}{
    {code for odd pages}
}{
    {code for even pages}
}

```

In order for this to work the argument of `\isodd` needs to be fully expandable. With the above redefinition of `\pageref` it is not in the case of this example. To overcome that, we add some code to the definition of `\ifthenelse` to make things work.

We want to revert the definition of `\pageref` and `\ref` to their original definition for the first argument of `\ifthenelse`, so we first need to store their current meanings.

Then we can set the `\@safe@actives` switch and call the original `\ifthenelse`. In order to be able to use shorthands in the second and third arguments of `\ifthenelse` the resetting of the switch *and* the definition of `\pageref` happens inside those arguments.

```

3792 \bbl@trace{Preventing clashes with other packages}
3793 \ifx\org@ref\undefined\else
3794     \bbl@xin@{R}\bbl@opt@safe
3795     \ifin@
3796         \AtBeginDocument{%
3797             \@ifpackageloaded{ifthen}{%
3798                 \bbl@redefine@long\ifthenelse#1#2#3{%
3799                     \let\bbl@temp@pref\pageref
3800                     \let\pageref\org@pageref
3801                     \let\bbl@temp@ref\ref
3802                     \let\ref\org@ref

```

```

3803         \@safe@activetrue
3804         \org@ifthenelse{#1}%
3805         {\let\pageref\bbl@temp@pref
3806          \let\ref\bbl@temp@ref
3807          \@safe@activesfalse
3808          #2}%
3809         {\let\pageref\bbl@temp@pref
3810          \let\ref\bbl@temp@ref
3811          \@safe@activesfalse
3812          #3}%
3813     }%
3814 }{}%
3815 }
3816 \fi

```

8.3.2 varioref

`\@vpageref` When the package `varioref` is in use we need to modify its internal command `\@vpageref` in order
`\vrefpagemum` to prevent problems when an active character ends up in the argument of `\vref`. The same needs to
`\Ref` happen for `\vrefpagemum`.

```

3817 \AtBeginDocument{%
3818     \@ifpackageloaded{varioref}{%
3819         \bbl@redefine\@vpageref#1[#2]#3{%
3820             \@safe@activetrue
3821             \org@@@vpageref{#1}#2#3}%
3822             \@safe@activesfalse}%
3823         \bbl@redefine\vrefpagemum#1#2{%
3824             \@safe@activetrue
3825             \org@vrefpagemum{#1}#2}%
3826             \@safe@activesfalse}%

```

The package `varioref` defines `\Ref` to be a robust command which uppercases the first character of the reference text. In order to be able to do that it needs to access the expandable form of `\ref`. So we employ a little trick here. We redefine the (internal) command `\Ref␣` to call `\org@ref` instead of `\ref`. The disadvantage of this solution is that whenever the definition of `\Ref` changes, this definition needs to be updated as well.

```

3827     \expandafter\def\csname Ref\endcsname#1{%
3828         \protected@edef\@tempa{\org@ref{#1}}\expandafter\MakeUppercase\@tempa}
3829     }{}%
3830 }
3831 \fi

```

8.3.3 hline

`\hline` Delaying the activation of the shorthand characters has introduced a problem with the `hline` package. The reason is that it uses the ‘:’ character which is made active by the french support in `babel`. Therefore we need to *reload* the package when the ‘:’ is an active character. Note that this happens *after* the category code of the @-sign has been changed to other, so we need to temporarily change it to letter again.

```

3832 \AtEndOfPackage{%
3833     \AtBeginDocument{%
3834         \@ifpackageloaded{hline}%
3835         {\expandafter\ifx\csname normal@char\string\endcsname\relax
3836          \else
3837              \makeatletter
3838              \def\@currname{hline}\input{hline.sty}\makeatother
3839              \fi}%
3840         {}}}

```

`\substitutefontfamily` Deprecated. Use the tools provided by \TeX . The command `\substitutefontfamily` creates an `.fd` file on the fly. The first argument is an encoding mnemonic, the second and third arguments are font family names.

```

3841 \def\substitutefontfamily#1#2#3{%
3842   \lowercase{\immediate\openout15=#1#2.fd\relax}%
3843   \immediate\write15{%
3844     \string\ProvidesFile{#1#2.fd}%
3845     [\the\year/\two@digits{\the\month}/\two@digits{\the\day}
3846     \space generated font description file]^^J
3847     \string\DeclareFontFamily{#1}{#2}{^^J
3848     \string\DeclareFontShape{#1}{#2}{m}{n}{<->ssub * #3/m/n}{^^J
3849     \string\DeclareFontShape{#1}{#2}{m}{it}{<->ssub * #3/m/it}{^^J
3850     \string\DeclareFontShape{#1}{#2}{m}{sl}{<->ssub * #3/m/sl}{^^J
3851     \string\DeclareFontShape{#1}{#2}{m}{sc}{<->ssub * #3/m/sc}{^^J
3852     \string\DeclareFontShape{#1}{#2}{b}{n}{<->ssub * #3/bx/n}{^^J
3853     \string\DeclareFontShape{#1}{#2}{b}{it}{<->ssub * #3/bx/it}{^^J
3854     \string\DeclareFontShape{#1}{#2}{b}{sl}{<->ssub * #3/bx/sl}{^^J
3855     \string\DeclareFontShape{#1}{#2}{b}{sc}{<->ssub * #3/bx/sc}{^^J
3856     }%
3857   \closeout15
3858 }
3859 \@onlypreamble\substitutefontfamily

```

8.4 Encoding and fonts

Because documents may use non-ASCII font encodings, we make sure that the logos of \TeX and \LaTeX always come out in the right encoding. There is a list of non-ASCII encodings. Requested encodings are currently stored in `\fontenc@load@list`. If a non-ASCII has been loaded, we define versions of `\TeX` and `\LaTeX` for them using `\ensureascii`. The default ASCII encoding is set, too (in reverse order): the “main” encoding (when the document begins), the last loaded, or OT1.

`\ensureascii`

```

3860 \bbl@trace{Encoding and fonts}
3861 \newcommand\BabelNonASCII{LGR,X2,OT2,OT3,OT6,LHE,LWN,LMA,LMC,LMS,LMU}
3862 \newcommand\BabelNonText{TS1,T3,TS3}
3863 \let\org@TeX\TeX
3864 \let\org@LaTeX\LaTeX
3865 \let\ensureascii@firstofone
3866 \AtBeginDocument{%
3867   \def\@elt#1{,#1,}%
3868   \edef\bbl@tempa{\expandafter\@gobbletwo\fontenc@load@list}%
3869   \let\@elt\relax
3870   \let\bbl@tempb\empty
3871   \def\bbl@tempc{OT1}%
3872   \bbl@foreach\BabelNonASCII{% LGR loaded in a non-standard way
3873     \bbl@ifunset{T#1}{\def\bbl@tempb{#1}}}%
3874   \bbl@foreach\bbl@tempa{%
3875     \bbl@xin@{#1}{\BabelNonASCII}%
3876     \ifin@
3877       \def\bbl@tempb{#1}% Store last non-ascii
3878     \else\bbl@xin@{#1}{\BabelNonText}% Pass
3879     \ifin@
3880       \def\bbl@tempc{#1}% Store last ascii
3881     \fi
3882   \fi}%
3883   \ifx\bbl@tempb\empty\else
3884     \bbl@xin@{,\cf@encoding,}{,\BabelNonASCII,\BabelNonText,}%
3885     \ifin@
3886       \edef\bbl@tempc{\cf@encoding}% The default if ascii wins
3887     \fi
3888     \edef\ensureascii#1{%
3889       {\noexpand\fontencoding{\bbl@tempc}\noexpand\selectfont#1}}%
3890     \DeclareTextCommandDefault{\TeX}{\ensureascii{\org@TeX}}%
3891     \DeclareTextCommandDefault{\LaTeX}{\ensureascii{\org@LaTeX}}%
3892   \fi}

```

Now comes the old deprecated stuff (with a little change in 3.9l, for fontspec). The first thing we need to do is to determine, at `\begin{document}`, which latin fontencoding to use.

`\latinencoding` When text is being typeset in an encoding other than ‘latin’ (OT1 or T1), it would be nice to still have Roman numerals come out in the Latin encoding. So we first assume that the current encoding at the end of processing the package is the Latin encoding.

```
3893 \AtEndOfPackage{\edef\latinencoding{\cf@encoding}}
```

But this might be overruled with a later loading of the package fontenc. Therefore we check at the execution of `\begin{document}` whether it was loaded with the T1 option. The normal way to do this (using `\ifpackageloaded`) is disabled for this package. Now we have to revert to parsing the internal macro `\@filelist` which contains all the filenames loaded.

```
3894 \AtBeginDocument{%
3895   \ifpackageloaded{fontspec}%
3896     {\xdef\latinencoding{%
3897       \ifx\UTFencname\@undefined
3898         EU\ifcase\bbl@engine\or2\or1\fi
3899       \else
3900         \UTFencname
3901       \fi}}%
3902   {\gdef\latinencoding{OT1}%
3903     \ifx\cf@encoding\bbl@t@one
3904       \xdef\latinencoding{\bbl@t@one}%
3905     \else
3906       \def@elt#1{,#1,}%
3907       \edef\bbl@tempa{\expandafter\@gobbletwo\@fontenc@load@list}%
3908       \let@elt\relax
3909       \bbl@xin@{,T1,}\bbl@tempa
3910       \ifin@
3911         \xdef\latinencoding{\bbl@t@one}%
3912       \fi
3913     \fi}}
```

`\latintext` Then we can define the command `\latintext` which is a declarative switch to a latin font-encoding. Usage of this macro is deprecated.

```
3914 \DeclareRobustCommand{\latintext}{%
3915   \fontencoding{\latinencoding}\selectfont
3916   \def\encodingdefault{\latinencoding}}
```

`\textlatin` This command takes an argument which is then typeset using the requested font encoding. In order to avoid many encoding switches it operates in a local scope.

```
3917 \ifx\@undefined\DeclareTextFontCommand
3918   \DeclareRobustCommand{\textlatin}[1]{\leavevmode{\latintext #1}}
3919 \else
3920   \DeclareTextFontCommand{\textlatin}{\latintext}
3921 \fi
```

For several functions, we need to execute some code with `\selectfont`. With \TeX 2021-06-01, there is a hook for this purpose, but in older versions the \TeX command is patched (the latter solution will be eventually removed).

```
3922 \def\bbl@patchfont#1{\AddToHook{selectfont}{#1}}
```

8.5 Basic bidi support

Work in progress. This code is currently placed here for practical reasons. It will be moved to the correct place soon, I hope.

It is loosely based on `rlbabel.def`, but most of it has been developed from scratch. This babel module (by Johannes Braams and Boris Lavva) has served the purpose of typesetting R documents for two decades, and despite its flaws I think it is still a good starting point (some parts have been copied here almost verbatim), partly thanks to its simplicity. I’ve also looked at ARABI (by Youssef Jabri), which is compatible with babel.

There are two ways of modifying macros to make them “bidi”, namely, by patching the internal low-level macros (which is what I have done with lists, columns, counters, tocs, much like `rlbabel` did), and by introducing a “middle layer” just below the user interface (sectioning, footnotes).

- pdf_{tex} provides a minimal support for bidi text, and it must be done by hand. Vertical typesetting is not possible.
- x_{etex} is somewhat better, thanks to its font engine (even if not always reliable) and a few additional tools. However, very little is done at the paragraph level. Another challenging problem is text direction does not honour \TeX grouping.
- lua_{tex} can provide the most complete solution, as we can manipulate almost freely the node list, the generated lines, and so on, but bidi text does not work out of the box and some development is necessary. It also provides tools to properly set left-to-right and right-to-left page layouts. As Lua \TeX -ja shows, vertical typesetting is possible, too.

```

3923 \bbl@trace{Loading basic (internal) bidi support}
3924 \ifodd\bbl@engine
3925 \else % TODO. Move to txtbabel
3926   \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200
3927     \bbl@error
3928     {The bidi method 'basic' is available only in\\%
3929     luatex. I'll continue with 'bidi=default', so\\%
3930     expect wrong results}%
3931     {See the manual for further details.}%
3932     \let\bbl@beforeforeign\leavevmode
3933     \AtEndOfPackage{%
3934       \EnableBabelHook{babel-bidi}%
3935       \bbl@xebidipar}
3936   \fi\fi
3937   \def\bbl@loadxebidi#1{%
3938     \ifx\RTLfootnotetext\@undefined
3939       \AtEndOfPackage{%
3940         \EnableBabelHook{babel-bidi}%
3941         \ifx\fontspec\@undefined
3942           \bbl@loadfontspec % bidi needs fontspec
3943         \fi
3944         \usepackage#1{bidi}}%
3945     \fi}
3946   \ifnum\bbl@bidimode>200
3947     \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
3948       \bbl@tentative{bidi=bidi}
3949       \bbl@loadxebidi{}
3950     \or
3951       \bbl@loadxebidi{[rldocument]}
3952     \or
3953       \bbl@loadxebidi{}
3954     \fi
3955   \fi
3956 \fi
3957 % TODO? Separate:
3958 \ifnum\bbl@bidimode=\@ne
3959   \let\bbl@beforeforeign\leavevmode
3960   \ifodd\bbl@engine
3961     \newattribute\bbl@attr@dir
3962     \directlua{ Babel.attr_dir = luatexbase.registernumber'bbl@attr@dir' }
3963     \bbl@exp{\output{\bodydir\pagedir\the\output}}
3964   \fi
3965   \AtEndOfPackage{%
3966     \EnableBabelHook{babel-bidi}%
3967     \ifodd\bbl@engine\else
3968       \bbl@xebidipar
3969     \fi}
3970 \fi

```

Now come the macros used to set the direction when a language is switched. First the (mostly) common macros.

```

3971 \bbl@trace{Macros to switch the text direction}
3972 \def\bbl@alscripts{,Arabic,Syriac,Thaana,}

```



```

3973 \def\bb@l@rscripts{% TODO. Base on codes ??
3974   ,Imperial Aramaic,Avestan,Cypriot,Hatran,Hebrew,%
3975   Old Hungarian,Old Hungarian,Lydian,Mandaean,Manichaeen,%
3976   Manichaeen,Meroitic Cursive,Meroitic,Old North Arabian,%
3977   Nabataean,N'Ko,Orkhon,Palmyrene,Inscriptional Pahlavi,%
3978   Psalter Pahlavi,Phoenician,Inscriptional Parthian,Samaritan,%
3979   Old South Arabian,}%
3980 \def\bb@l@provide@dirs#1{%
3981   \bb@l@xin@{\csname bbl@sname@#1\endcsname}{\bb@l@alscripts\bb@l@rscripts}%
3982   \ifin@
3983     \global\bb@l@csarg\chardef{wdir@#1}\@ne
3984     \bb@l@xin@{\csname bbl@sname@#1\endcsname}{\bb@l@alscripts}%
3985     \ifin@
3986       \global\bb@l@csarg\chardef{wdir@#1}\tw@ % useless in xetex
3987     \fi
3988   \else
3989     \global\bb@l@csarg\chardef{wdir@#1}\z@
3990   \fi
3991   \ifodd\bb@l@engine
3992     \bb@l@csarg\ifcase{wdir@#1}%
3993       \directlua{ Babel.locale_props[\the\localeid].texmdir = 'l' }%
3994     \or
3995       \directlua{ Babel.locale_props[\the\localeid].texmdir = 'r' }%
3996     \or
3997       \directlua{ Babel.locale_props[\the\localeid].texmdir = 'al' }%
3998     \fi
3999   \fi}
4000 \def\bb@l@switchdir{%
4001   \bb@l@ifunset{\bb@l@sys@\languagename}{\bb@l@provide@lsys{\languagename}}{}%
4002   \bb@l@ifunset{\bb@l@wdir@\languagename}{\bb@l@provide@dirs{\languagename}}{}%
4003   \bb@l@exp{\bb@l@setdirs\bb@l@cl{wdir}}}%
4004 \def\bb@l@setdirs#1{% TODO - math
4005   \ifcase\bb@l@select@type % TODO - strictly, not the right test
4006     \bb@l@bodydir{#1}%
4007     \bb@l@paddir{#1}%
4008   \fi
4009   \bb@l@texmdir{#1}}
4010 % TODO. Only if \bb@l@bidimode > 0?:
4011 \AddBabelHook{babel-bidi}{afterextras}{\bb@l@switchdir}
4012 \DisableBabelHook{babel-bidi}

```

Now the engine-dependent macros. TODO. Must be moved to the engine files.

```

4013 \ifodd\bb@l@engine % luatex=1
4014 \else % pdftex=0, xetex=2
4015   \newcount\bb@l@dirlevel
4016   \chardef\bb@l@thetexmdir\z@
4017   \chardef\bb@l@thepaddir\z@
4018   \def\bb@l@texmdir#1{%
4019     \ifcase#1\relax
4020       \chardef\bb@l@thetexmdir\z@
4021       \bb@l@texmdir@i\beginL\endL
4022     \else
4023       \chardef\bb@l@thetexmdir\@ne
4024       \bb@l@texmdir@i\beginR\endR
4025     \fi}
4026   \def\bb@l@texmdir@i#1#2{%
4027     \ifhmode
4028       \ifnum\currentgrouplevel>\z@
4029         \ifnum\currentgrouplevel=\bb@l@dirlevel
4030           \bb@l@error{Multiple bidi settings inside a group}%
4031           {I'll insert a new group, but expect wrong results.}%
4032           \bgroup\aftergroup#2\aftergroup\egroup
4033         \else

```

```

4034 \ifcase\currentgroup\type\or % 0 bottom
4035 \aftergroup#2% 1 simple {}
4036 \or
4037 \bgroup\aftergroup#2\aftergroup\egroup % 2 hbox
4038 \or
4039 \bgroup\aftergroup#2\aftergroup\egroup % 3 adj hbox
4040 \or\or\or % vbox vtop align
4041 \or
4042 \bgroup\aftergroup#2\aftergroup\egroup % 7 noalign
4043 \or\or\or\or\or\or % output math disc insert vcent mathchoice
4044 \or
4045 \aftergroup#2% 14 \begingroup
4046 \else
4047 \bgroup\aftergroup#2\aftergroup\egroup % 15 adj
4048 \fi
4049 \fi
4050 \bbl@dirlevel\currentgrouplevel
4051 \fi
4052 #1%
4053 \fi}
4054 \def\bbl@pardir#1{\chardef\bbl@thepardir#1\relax}
4055 \let\bbl@bodydir\@gobble
4056 \let\bbl@pagedir\@gobble
4057 \def\bbl@dirparastext{\chardef\bbl@thepardir\bbl@thetextdir}

```

The following command is executed only if there is a right-to-left script (once). It activates the `\everypar` hack for xetex, to properly handle the par direction. Note text and par dirs are decoupled to some extent (although not completely).

```

4058 \def\bbl@xebidipar{%
4059 \let\bbl@xebidipar\relax
4060 \TeXeTstate\@ne
4061 \def\bbl@xeverypar{%
4062 \ifcase\bbl@thepardir
4063 \ifcase\bbl@thetextdir\else\beginR\fi
4064 \else
4065 {\setbox\z@\lastbox\beginR\box\z@}%
4066 \fi}%
4067 \let\bbl@severypar\everypar
4068 \newtoks\everypar
4069 \everypar=\bbl@severypar
4070 \bbl@severypar{\bbl@xeverypar\the\everypar}}
4071 \ifnum\bbl@bidimode>200
4072 \let\bbl@textdir\i\@gobbletwo
4073 \let\bbl@xebidipar\@empty
4074 \AddBabelHook{bidi}{foreign}{%
4075 \def\bbl@tempa{\def\BabelText####1}%
4076 \ifcase\bbl@thetextdir
4077 \expandafter\bbl@tempa\expandafter{\BabelText{\LR{####1}}}%
4078 \else
4079 \expandafter\bbl@tempa\expandafter{\BabelText{\RL{####1}}}%
4080 \fi}
4081 \def\bbl@pardir#1{\ifcase#1\relax\setLR\else\setRL\fi}
4082 \fi
4083 \fi

```

A tool for weak L (mainly digits). We also disable warnings with hyperref.

```

4084 \DeclareRobustCommand\babelsublr[1]{\leavevmode{\bbl@textdir\z@#1}}
4085 \AtBeginDocument{%
4086 \ifx\pdfstringdefDisableCommands\undefined\else
4087 \ifx\pdfstringdefDisableCommands\relax\else
4088 \pdfstringdefDisableCommands{\let\babelsublr\@firstofone}%
4089 \fi
4090 \fi}

```

8.6 Local Language Configuration

`\loadlocalcfg` At some sites it may be necessary to add site-specific actions to a language definition file. This can be done by creating a file with the same name as the language definition file, but with the extension `.cfg`. For instance the file `norsk.cfg` will be loaded when the language definition file `norsk.ldf` is loaded.

For plain-based formats we don't want to override the definition of `\loadlocalcfg` from `plain.def`.

```
4091 \bbl@trace{Local Language Configuration}
4092 \ifx\loadlocalcfg\undefined
4093   \@ifpackagewith{babel}{noconfigs}%
4094   {\let\loadlocalcfg@gobble}%
4095   {\def\loadlocalcfg#1{%
4096     \InputIfFileExists{#1.cfg}%
4097     {\typeout{*****^J%
4098               * Local config file #1.cfg used^^J%
4099               *}}%
4100     \@empty}}
4101 \fi
```

8.7 Language options

Languages are loaded when processing the corresponding option *except* if a main language has been set. In such a case, it is not loaded until all options has been processed. The following macro inputs the `ldf` file and does some additional checks (`\input` works, too, but possible errors are not caught).

```
4102 \bbl@trace{Language options}
4103 \let\bbl@afterlang\relax
4104 \let\BabelModifiers\relax
4105 \let\bbl@loaded\@empty
4106 \def\bbl@load@language#1{%
4107   \InputIfFileExists{#1.ldf}%
4108   {\edef\bbl@loaded{\CurrentOption
4109     \ifx\bbl@loaded\@empty\else,\bbl@loaded\fi}%
4110     \expandafter\let\expandafter\bbl@afterlang
4111       \csname\CurrentOption.ldf-h@@k\endcsname
4112     \expandafter\let\expandafter\BabelModifiers
4113       \csname\bbl@mod@\CurrentOption\endcsname}%
4114   {\bbl@error{%
4115     Unknown option '\CurrentOption'. Either you misspelled it\\%
4116     or the language definition file \CurrentOption.ldf was not found}%
4117     Valid options are, among others: shorthands=, KeepShorthandsActive,\%
4118     activeacute, activegrave, noconfigs, safe=, main=, math=\%
4119     headfoot=, strings=, config=, hyphenmap=, or a language name.}}}
```

Now, we set a few language options whose names are different from `ldf` files. These declarations are preserved for backwards compatibility, but they must be eventually removed. Use proxy files instead.

```
4120 \def\bbl@try@load@lang#1#2#3{%
4121   \IfFileExists{\CurrentOption.ldf}%
4122   {\bbl@load@language{\CurrentOption}}%
4123   {\#1\bbl@load@language{\#2}\#3}}
4124 %
4125 \DeclareOption{hebrew}{%
4126   \input{rlbabel.def}%
4127   \bbl@load@language{hebrew}}
4128 \DeclareOption{hungarian}{\bbl@try@load@lang{}{magyar}{}}
4129 \DeclareOption{lowersorbian}{\bbl@try@load@lang{}{lsorbian}{}}
4130 \DeclareOption{nynorsk}{\bbl@try@load@lang{}{norsk}{}}
4131 \DeclareOption{polutonikogreek}{%
4132   \bbl@try@load@lang{}{greek}{\languageattribute{greek}{polutoniko}}}
4133 \DeclareOption{russian}{\bbl@try@load@lang{}{russianb}{}}
4134 \DeclareOption{ukrainian}{\bbl@try@load@lang{}{ukraineb}{}}
4135 \DeclareOption{uppersorbian}{\bbl@try@load@lang{}{usorbian}{}}
```

Another way to extend the list of ‘known’ options for babel was to create the file `bblopts.cfg` in which one can add option declarations. However, this mechanism is deprecated – if you want an alternative name for a language, just create a new `.ldf` file loading the actual one. You can also set the name of the file with the package option `config=<name>`, which will load `<name>.cfg` instead.

```

4136 \ifx\bbbl@opt@config\@nnil
4137   \@ifpackagewith{babel}{noconfigs}}{}%
4138   {\InputIfFileExists{bblopts.cfg}%
4139     {\typeout{*****^J%
4140               * Local config file bblopts.cfg used^^J%
4141               *}}}%
4142   {}}%
4143 \else
4144   \InputIfFileExists{\bbbl@opt@config.cfg}%
4145   {\typeout{*****^J%
4146             * Local config file \bbbl@opt@config.cfg used^^J%
4147             *}}%
4148   {\bbbl@error{%
4149     Local config file '\bbbl@opt@config.cfg' not found}{%
4150     Perhaps you misspelled it.}}%
4151 \fi

```

Recognizing global options in packages not having a closed set of them is not trivial, as for them to be processed they must be defined explicitly. So, package options not yet taken into account and stored in `bbbl@language@opts` are assumed to be languages. If not declared above, the names of the option and the file are the same. We first pre-process the class and package options to determine the main language, which is processed in the third ‘main’ pass, *except* if all files are `ldf` and there is no main key. In the latter case (`\bbbl@opt@main` is still `\@nnil`), the traditional way to set the main language is kept — the last loaded is the main language.

```

4152 \ifx\bbbl@opt@main\@nnil
4153   \ifnum\bbbl@iniflag>\z@ % if all ldf's: set implicitly, no main pass
4154     \let\bbbl@tempb\@empty
4155     \edef\bbbl@tempa{\@classoptionslist,\bbbl@language@opts}%
4156     \bbbl@foreach\bbbl@tempa{\edef\bbbl@tempb{#1,\bbbl@tempb}}}%
4157     \bbbl@foreach\bbbl@tempb{% \bbbl@tempb is a reversed list
4158       \ifx\bbbl@opt@main\@nnil % ie, if not yet assigned
4159         \ifodd\bbbl@iniflag % = *=
4160           \IfFileExists{babel-#1.tex}{\def\bbbl@opt@main{#1}}}%
4161         \else % n +=
4162           \IfFileExists{#1.ldf}{\def\bbbl@opt@main{#1}}}%
4163       \fi
4164     \fi}%
4165 \fi
4166 \else
4167   \bbbl@info{Main language set with 'main='. Except if you have\\
4168             problems, prefer the default mechanism for setting\\
4169             the main language. Reported}
4170 \fi

```

A few languages are still defined explicitly. They are stored in case they are needed in the ‘main’ pass (the value can be `\relax`).

```

4171 \ifx\bbbl@opt@main\@nnil\else
4172   \bbbl@csarg\let\loadmain\expandafter\csname ds@\bbbl@opt@main\endcsname
4173   \expandafter\let\csname ds@\bbbl@opt@main\endcsname\relax
4174 \fi

```

Now define the corresponding loaders. With package options, assume the language exists. With class options, check if the option is a language by checking if the correspondin file exists.

```

4175 \bbbl@foreach\bbbl@language@opts{%
4176   \def\bbbl@tempa{#1}%
4177   \ifx\bbbl@tempa\bbbl@opt@main\else
4178     \ifnum\bbbl@iniflag<\tw@ % 0 0 (other = ldf)
4179       \bbbl@ifunset{ds@#1}%
4180       {\DeclareOption{#1}{\bbbl@load@language{#1}}}%

```

```

4181     }%
4182     \else % + * (other = ini)
4183         \DeclareOption{#1}{%
4184             \bbl@ldfinit
4185             \babelprovide[import]{#1}%
4186             \bbl@afterldf{}}%
4187     \fi
4188 \fi}
4189 \bbl@foreach\@classoptionslist{%
4190     \def\bbl@tempa{#1}%
4191     \ifx\bbl@tempa\bbl@opt@main\else
4192         \ifnum\bbl@iniflag<\tw@ % 0 0 (other = ldf)
4193             \bbl@ifunset{ds@#1}%
4194             {\IfFileExists{#1.ldf}%
4195              {\DeclareOption{#1}{\bbl@load@language{#1}}}%
4196              {}}%
4197         }%
4198     \else % + * (other = ini)
4199         \IfFileExists{babel-#1.tex}%
4200         {\DeclareOption{#1}{%
4201             \bbl@ldfinit
4202             \babelprovide[import]{#1}%
4203             \bbl@afterldf{}}}%
4204         {}}%
4205     \fi
4206 \fi}

```

And we are done, because all options for this pass has been declared. Those already processed in the first pass are just ignored.

The options have to be processed in the order in which the user specified them (but remember class options are processed before):

```

4207 \def\AfterBabelLanguage#1{%
4208     \bbl@ifsamestring\CurrentOption{#1}{\global\bbl@add\bbl@afterlang{}}
4209 \DeclareOption*{
4210 \ProcessOptions*

```

This finished the second pass. Now the third one begins, which loads the main language set with the key main. A warning is raised if the main language is not the same as the last named one, or if the value of the key main is not a language. With some options in provide, the package luatexbase is loaded (and immediately used), and therefore \babelprovide can't go inside a \DeclareOption; this explains why it's executed directly, with a dummy declaration. Then all languages have been loaded, so we deactivate \AfterBabelLanguage.

```

4211 \bbl@trace{Option 'main'}
4212 \ifx\bbl@opt@main\@nnil
4213     \edef\bbl@tempa{\@classoptionslist,\bbl@language@opts}
4214     \let\bbl@tempc\@empty
4215     \bbl@for\bbl@tempb\bbl@tempa{%
4216         \bbl@xin@{,\bbl@tempb,}{,\bbl@loaded,}%
4217         \ifin@ \edef\bbl@tempc{\bbl@tempb}\fi}
4218     \def\bbl@tempa#1,#2\@nnil{\def\bbl@tempb{#1}}
4219     \expandafter\bbl@tempa\bbl@loaded,\@nnil
4220     \ifx\bbl@tempb\bbl@tempc\else
4221         \bbl@warning{%
4222             Last declared language option is '\bbl@tempc',\%
4223             but the last processed one was '\bbl@tempb'.\%
4224             The main language can't be set as both a global\%
4225             and a package option. Use 'main=\bbl@tempc' as\%
4226             option. Reported}
4227     \fi
4228 \else
4229     \ifodd\bbl@iniflag % case 1,3 (main is ini)
4230         \bbl@ldfinit
4231         \let\CurrentOption\bbl@opt@main
4232         \bbl@exp{% \bbl@opt@provide = empty if *

```

```

4233     \\\babelprovide[\bbl@opt@provide,import,main]{\bbl@opt@main}}%
4234     \bbl@afterldf{}
4235     \DeclareOption{\bbl@opt@main}{}
4236 \else % case 0,2 (main is ldf)
4237     \ifx\bbl@loadmain\relax
4238         \DeclareOption{\bbl@opt@main}{\bbl@load@language{\bbl@opt@main}}
4239     \else
4240         \DeclareOption{\bbl@opt@main}{\bbl@loadmain}
4241     \fi
4242     \ExecuteOptions{\bbl@opt@main}
4243     \@namedef{ds@\bbl@opt@main}{}%
4244 \fi
4245 \DeclareOption*{}
4246 \ProcessOptions*
4247 \fi
4248 \def\AfterBabelLanguage{%
4249     \bbl@error
4250     {Too late for \string\AfterBabelLanguage}%
4251     {Languages have been loaded, so I can do nothing}}

    In order to catch the case where the user didn't specify a language we check whether
    \bbl@main@language, has become defined. If not, the nil language is loaded.

4252 \ifx\bbl@main@language\@undefined
4253     \bbl@info{%
4254         You haven't specified a language. I'll use 'nil'\%
4255         as the main language. Reported}
4256     \bbl@load@language{nil}
4257 \fi
4258 \</package>

```

9 The kernel of Babel (babel.def, common)

The kernel of the babel system is currently stored in babel.def. The file babel.def contains most of the code. The file hyphen.cfg is a file that can be loaded into the format, which is necessary when you want to be able to switch hyphenation patterns.

Because plain T_EX users might want to use some of the features of the babel system too, care has to be taken that plain T_EX can process the files. For this reason the current format will have to be checked in a number of places. Some of the code below is common to plain T_EX and L^AT_EX, some of it is for the L^AT_EX case only.

Plain formats based on etex (etex, xetex, luatex) don't load hyphen.cfg but etex.src, which follows a different naming convention, so we need to define the babel names. It presumes language.def exists and it is the same file used when formats were created.

A proxy file for switch.def

```

4259 \<*kernel>
4260 \let\bbl@onlyswitch\@empty
4261 \input babel.def
4262 \let\bbl@onlyswitch\@undefined
4263 \</kernel>
4264 \<*patterns>

```

10 Loading hyphenation patterns

The following code is meant to be read by iniT_EX because it should instruct T_EX to read hyphenation patterns. To this end the docstrip option patterns is used to include this code in the file hyphen.cfg. Code is written with lower level macros.

```

4265 \<Make sure ProvidesFile is defined>
4266 \ProvidesFile{hyphen.cfg}[\<<date>>\<<version>>\<Babel hyphens>]
4267 \xdef\bbl@format{\jobname}
4268 \def\bbl@version{\<<version>>}
4269 \def\bbl@date{\<<date>>}
4270 \ifx\AtBeginDocument\@undefined

```

```

4271 \def\@empty{}
4272 \fi
4273 \(\Define core switching macros\)
```

`\process@line` Each line in the file `language.dat` is processed by `\process@line` after it is read. The first thing this macro does is to check whether the line starts with `=`. When the first token of a line is an `=`, the macro `\process@synonym` is called; otherwise the macro `\process@language` will continue.

```

4274 \def\process@line#1#2 #3 #4 {%
4275   \ifx=#1%
4276     \process@synonym{#2}%
4277   \else
4278     \process@language{#1#2}{#3}{#4}%
4279   \fi
4280   \ignorespaces}
```

`\process@synonym` This macro takes care of the lines which start with an `=`. It needs an empty token register to begin with. `\bbl@languages` is also set to empty.

```

4281 \toks@{}
4282 \def\bbl@languages{}
```

When no languages have been loaded yet, the name following the `=` will be a synonym for hyphenation register 0. So, it is stored in a token register and executed when the first pattern file has been processed. (The `\relax` just helps to the `\if` below catching synonyms without a language.) Otherwise the name will be a synonym for the language loaded last. We also need to copy the hyphenmin parameters for the synonym.

```

4283 \def\process@synonym#1{%
4284   \ifnum\last@language=\m@ne
4285     \toks@\expandafter{\the\toks@\relax\process@synonym{#1}}%
4286   \else
4287     \expandafter\chardef\csname l@#1\endcsname\last@language
4288     \wlog{\string\l@#1=\string\language\the\last@language}%
4289     \expandafter\let\csname #1hyphenmins\expandafter\endcsname
4290       \csname\language\hyphenmins\endcsname
4291     \let\bbl@elt\relax
4292     \edef\bbl@languages{\bbl@languages\bbl@elt{#1}{\the\last@language}{}}%
4293   \fi}
```

`\process@language` The macro `\process@language` is used to process a non-empty line from the ‘configuration file’. It has three arguments, each delimited by white space. The first argument is the ‘name’ of a language; the second is the name of the file that contains the patterns. The optional third argument is the name of a file containing hyphenation exceptions.

The first thing to do is call `\addlanguage` to allocate a pattern register and to make that register ‘active’. Then the pattern file is read.

For some hyphenation patterns it is needed to load them with a specific font encoding selected. This can be specified in the file `language.dat` by adding for instance ‘:T1’ to the name of the language.

The macro `\bbl@get@enc` extracts the font encoding from the language name and stores it in `\bbl@hyph@enc`. The latter can be used in hyphenation files if you need to set a behavior depending on the given encoding (it is set to empty if no encoding is given).

Pattern files may contain assignments to `\lefthyphenmin` and `\righthyphenmin`. T_EX does not keep track of these assignments. Therefore we try to detect such assignments and store them in the `\langhyphenmins` macro. When no assignments were made we provide a default setting.

Some pattern files contain changes to the `\lccode` `\uccode` arrays. Such changes should remain local to the language; therefore we process the pattern file in a group; the `\patterns` command acts globally so its effect will be remembered.

Then we globally store the settings of `\lefthyphenmin` and `\righthyphenmin` and close the group.

When the hyphenation patterns have been processed we need to see if a file with hyphenation exceptions needs to be read. This is the case when the third argument is not empty and when it does not contain a space token. (Note however there is no need to save hyphenation exceptions into the format.)

`\bbl@languages` saves a snapshot of the loaded languages in the form

`\bbl@elt{(language-name)}{(number)}{(patterns-file)}{(exceptions-file)}`. Note the last 2

arguments are empty in ‘dialects’ defined in `language.dat` with `=`. Note also the language name can have encoding info.

Finally, if the counter `\language` is equal to zero we execute the synonyms stored.

```

4294 \def\process@language#1#2#3{%
4295   \expandafter\addlanguage\csname l@#1\endcsname
4296   \expandafter\language\csname l@#1\endcsname
4297   \edef\language{#1}%
4298   \bbl@hook@everylanguage{#1}%
4299   % > luatex
4300   \bbl@get@enc#1::\@@@
4301   \begingroup
4302     \lefthyphenmin@m@ne
4303     \bbl@hook@loadpatterns{#2}%
4304     % > luatex
4305     \ifnum\lefthyphenmin=\m@ne
4306     \else
4307       \expandafter\xdef\csname #1hyphenmins\endcsname{%
4308         \the\lefthyphenmin\the\righthyphenmin}%
4309     \fi
4310   \endgroup
4311   \def\bbl@tempa{#3}%
4312   \ifx\bbl@tempa\@empty\else
4313     \bbl@hook@loadexceptions{#3}%
4314     % > luatex
4315   \fi
4316   \let\bbl@elt\relax
4317   \edef\bbl@languages{%
4318     \bbl@languages\bbl@elt{#1}{\the\language}{#2}{\bbl@tempa}}%
4319   \ifnum\the\language=\z@
4320     \expandafter\ifx\csname #1hyphenmins\endcsname\relax
4321       \set@hyphenmins\tw@\thr@@\relax
4322     \else
4323       \expandafter\expandafter\expandafter\set@hyphenmins
4324       \csname #1hyphenmins\endcsname
4325     \fi
4326     \the\toks@
4327     \toks@{}%
4328   \fi}

```

`\bbl@get@enc` The macro `\bbl@get@enc` extracts the font encoding from the language name and stores it in `\bbl@hyph@enc`. It uses delimited arguments to achieve this.

```

4329 \def\bbl@get@enc#1:#2:#3\@@@{\def\bbl@hyph@enc{#2}}

```

Now, hooks are defined. For efficiency reasons, they are dealt here in a special way. Besides `luatex`, format-specific configuration files are taken into account. `loadkernel` currently loads nothing, but define some basic macros instead.

```

4330 \def\bbl@hook@everylanguage#1{}
4331 \def\bbl@hook@loadpatterns#1{\input #1\relax}
4332 \let\bbl@hook@loadexceptions\bbl@hook@loadpatterns
4333 \def\bbl@hook@loadkernel#1{%
4334   \def\addlanguage{\csname newlanguage\endcsname}%
4335   \def\adddialect##1##2{%
4336     \global\chardef##1##2\relax
4337     \wlog{\string##1 = a dialect from \string\language##2}}%
4338   \def\iflanguage##1{%
4339     \expandafter\ifx\csname l@##1\endcsname\relax
4340       \@nolanerr{##1}%
4341     \else
4342       \ifnum\csname l@##1\endcsname=\language
4343         \expandafter\expandafter\expandafter\@firstoftwo
4344       \else
4345         \expandafter\expandafter\expandafter\@secondoftwo
4346       \fi
4347   \fi}%

```



```

4348 \def\providehyphenmins##1##2{%
4349   \expandafter\ifx\csname ##1hyphenmins\endcsname\relax
4350     \@namedef{##1hyphenmins}{##2}%
4351   \fi}%
4352 \def\set@hyphenmins##1##2{%
4353   \lefthyphenmin##1\relax
4354   \righthyphenmin##2\relax}%
4355 \def\selectlanguage{%
4356   \errhelp{Selecting a language requires a package supporting it}%
4357   \errmessage{Not loaded}}%
4358 \let\foreignlanguage\selectlanguage
4359 \let\otherlanguage\selectlanguage
4360 \expandafter\let\csname otherlanguage*\endcsname\selectlanguage
4361 \def\bbl@usehooks##1##2{% TODO. Temporary!!
4362 \def\setlocale{%
4363   \errhelp{Find an armchair, sit down and wait}%
4364   \errmessage{Not yet available}}%
4365 \let\uselocale\setlocale
4366 \let\locale\setlocale
4367 \let\selectlocale\setlocale
4368 \let\localename\setlocale
4369 \let\textlocale\setlocale
4370 \let\textlanguage\setlocale
4371 \let\languagetext\setlocale}
4372 \begingroup
4373 \def\AddBabelHook#1#2{%
4374   \expandafter\ifx\csname bbl@hook@#2\endcsname\relax
4375     \def\next{\toks1}%
4376   \else
4377     \def\next{\expandafter\gdef\csname bbl@hook@#2\endcsname####1}%
4378   \fi
4379   \next}
4380 \ifx\directlua\@undefined
4381   \ifx\XeTeXinputencoding\@undefined\else
4382     \input xebabel.def
4383   \fi
4384 \else
4385   \input luababel.def
4386 \fi
4387 \openin1 = babel-\bbl@format.cfg
4388 \ifeof1
4389 \else
4390   \input babel-\bbl@format.cfg\relax
4391 \fi
4392 \closein1
4393 \endgroup
4394 \bbl@hook@loadkernel{switch.def}

```

`\readconfigfile` The configuration file can now be opened for reading.

```

4395 \openin1 = language.dat

```

See if the file exists, if not, use the default hyphenation file `hyphen.tex`. The user will be informed about this.

```

4396 \def\languagename{english}%
4397 \ifeof1
4398   \message{I couldn't find the file language.dat,\space
4399           I will try the file hyphen.tex}
4400   \input hyphen.tex\relax
4401   \chardef\l@english\z@
4402 \else

```

Pattern registers are allocated using count register `\last@language`. Its initial value is 0. The definition of the macro `\newlanguage` is such that it first increments the count register and then

defines the language. In order to have the first patterns loaded in pattern register number 0 we initialize `\last@language` with the value `-1`.

```
4403 \last@language\m@ne
```

We now read lines from the file until the end is found. While reading from the input, it is useful to switch off recognition of the end-of-line character. This saves us stripping off spaces from the contents of the control sequence.

```
4404 \loop
4405   \endlinechar\m@ne
4406   \read1 to \bbl@line
4407   \endlinechar`^^M
```

If the file has reached its end, exit from the loop here. If not, empty lines are skipped. Add 3 space characters to the end of `\bbl@line`. This is needed to be able to recognize the arguments of `\process@line` later on. The default language should be the very first one.

```
4408   \if T\ifeof1F\fi T\relax
4409   \ifx\bbl@line\@empty\else
4410     \edef\bbl@line{\bbl@line\space\space\space}%
4411     \expandafter\process@line\bbl@line\relax
4412   \fi
4413 \repeat
```

Check for the end of the file. We must reverse the test for `\ifeof` without `\else`. Then reactivate the default patterns, and close the configuration file.

```
4414 \begingroup
4415   \def\bbl@elt#1#2#3#4{%
4416     \global\language=#2\relax
4417     \gdef\language#1}%
4418   \def\bbl@elt##1##2##3##4{}}%
4419   \bbl@languages
4420 \endgroup
4421 \fi
4422 \closein1
```

We add a message about the fact that babel is loaded in the format and with which language patterns to the `\everyjob` register.

```
4423 \if/\the\toks@/\else
4424   \errhelp{language.dat loads no language, only synonyms}
4425   \errmessage{Orphan language synonym}
4426 \fi
```

Also remove some macros from memory and raise an error if `\toks@` is not empty. Finally load `switch.def`, but the latter is not required and the line inputting it may be commented out.

```
4427 \let\bbl@line\@undefined
4428 \let\process@line\@undefined
4429 \let\process@synonym\@undefined
4430 \let\process@language\@undefined
4431 \let\bbl@get@enc\@undefined
4432 \let\bbl@hyph@enc\@undefined
4433 \let\bbl@tempa\@undefined
4434 \let\bbl@hook@loadkernel\@undefined
4435 \let\bbl@hook@everylanguage\@undefined
4436 \let\bbl@hook@loadpatterns\@undefined
4437 \let\bbl@hook@loadexceptions\@undefined
4438 \</patterns>
```

Here the code for `iniTeX` ends.

11 Font handling with fontspec

Add the bidi handler just before `luaotfload`, which is loaded by default by LaTeX. Just in case, consider the possibility it has not been loaded. First, a couple of definitions related to bidi [misplaced].

```
4439 <<(*More package options)>> ≡
```

```

4440 \chardef\bb1@bidimode\z@
4441 \DeclareOption{bidi=default}{\chardef\bb1@bidimode=\@ne}
4442 \DeclareOption{bidi=basic}{\chardef\bb1@bidimode=101 }
4443 \DeclareOption{bidi=basic-r}{\chardef\bb1@bidimode=102 }
4444 \DeclareOption{bidi=bidi}{\chardef\bb1@bidimode=201 }
4445 \DeclareOption{bidi=bidi-r}{\chardef\bb1@bidimode=202 }
4446 \DeclareOption{bidi=bidi-l}{\chardef\bb1@bidimode=203 }
4447 <</More package options>>

```

With explicit languages, we could define the font at once, but we don't. Just wait and see if the language is actually activated. `bb1@font` replaces hardcoded font names inside `\.family` by the corresponding macro `\.default`.

At the time of this writing, `fontspec` shows a warning about there are languages not available, which some people think refers to `babel`, even if there is nothing wrong. Here is hack to patch `fontspec` to avoid the misleading message, which is replaced by a more explanatory one.

```

4448 <<{*Font selection}>> ≡
4449 \bb1@trace{Font handling with fontspec}
4450 \ifx\ExplSyntaxOn\@undefined\else
4451   \ExplSyntaxOn
4452   \catcode`\ =10
4453   \def\bb1@loadfontspec{%
4454     \usepackage{fontspec}% TODO. Apply patch always
4455     \expandafter
4456     \def\csname msg~text~>~fontspec/language-not-exist\endcsname##1##2##3##4{%
4457       Font '\l_fontspec_fontname_tl' is using the\\%
4458       default features for language '##1'.\\%
4459       That's usually fine, because many languages\\%
4460       require no specific features, but if the output is\\%
4461       not as expected, consider selecting another font.}
4462     \expandafter
4463     \def\csname msg~text~>~fontspec/no-script\endcsname##1##2##3##4{%
4464       Font '\l_fontspec_fontname_tl' is using the\\%
4465       default features for script '##2'.\\%
4466       That's not always wrong, but if the output is\\%
4467       not as expected, consider selecting another font.}}
4468   \ExplSyntaxOff
4469 \fi
4470 \@onlypreamble\babelfont
4471 \newcommand\babelfont[2][{}]{% 1=langs/scripts 2=fam
4472   \bb1@foreach{#1}{%
4473     \expandafter\ifx\csname date##1\endcsname\relax
4474       \IfFileExists{babel-##1.tex}%
4475       {\babelprovide{##1}}%
4476     }%
4477   \fi}%
4478 \edef\bb1@tempa{#1}%
4479 \def\bb1@tempb{#2}% Used by \bb1@bblfont
4480 \ifx\fontspec\@undefined
4481   \bb1@loadfontspec
4482 \fi
4483 \EnableBabelHook{babel-fontspec}% Just calls \bb1@switchfont
4484 \bb1@bblfont}
4485 \newcommand\bb1@bblfont[2][{}]{% 1=features 2=fontname, @font=rm|sf|tt
4486   \bb1@ifunset{\bb1@tempb family}%
4487   {\bb1@providefam{\bb1@tempb}}%
4488   {}%
4489   % For the default font, just in case:
4490   \bb1@ifunset{\bb1@sys\languagename}{\bb1@provide@sys{\languagename}}{%
4491     \expandafter\bb1@ifblank\expandafter{\bb1@tempa}%
4492     {\bb1@csarg\edef{\bb1@tempb dflt@}{<{#1}{#2}}% save \bb1@rmdflt@
4493     \bb1@exp{%
4494       \let\<\bb1@tempb dflt@\languagename>\<\bb1@tempb dflt@>%
4495       \bb1@font@set\<\bb1@tempb dflt@\languagename>%

```

```

4496             \<\bbl@tempb default>\<\bbl@tempb family>}}%
4497     {\bbl@foreach\bbl@tempa{% ie bbl@rmdflt@lang / *scrt
4498       \bbl@csarg\def{\bbl@tempb dflt###1}{<{#1}{#2}}}}%

```

If the family in the previous command does not exist, it must be defined. Here is how:

```

4499 \def\bbl@providfam#1{%
4500   \bbl@exp{%
4501     \\\newcommand\<#1default>{% Just define it
4502       \\\bbl@add@list\\bbl@font@fams{#1}%
4503       \\\DeclareRobustCommand\<#1family>{%
4504         \\\not@math@alphabet\<#1family>\relax
4505         % \\\prepare@family@series@update{#1}\<#1default>% TODO. Fails
4506         \\\fontfamily\<#1default>%
4507         \<ifx>\\UseHooks\\@undefined\<else>\\UseHook{#1family}\<fi>%
4508         \\\selectfont}%
4509       \\\DeclareTextFontCommand{\<text#1>}{\<#1family>}}%

```

The following macro is activated when the hook babel-fontspec is enabled. But before, we define a macro for a warning, which sets a flag to avoid duplicate them.

```

4510 \def\bbl@nostdfont#1{%
4511   \bbl@ifunset{\bbl@WFF@f@family}%
4512   {\bbl@csarg\gdef{\bbl@WFF@f@family}}% Flag, to avoid dupl warns
4513   \bbl@infowarn{The current font is not a babel standard family:\%
4514     #1%
4515     \fontname\font\\%
4516     There is nothing intrinsically wrong with this warning, and\\%
4517     you can ignore it altogether if you do not need these\\%
4518     families. But if they are used in the document, you should be\\%
4519     aware 'babel' will no set Script and Language for them, so\\%
4520     you may consider defining a new family with \string\babelfont.\\%
4521     See the manual for further details about \string\babelfont.\\%
4522     Reported}}
4523   }%
4524   \gdef\bbl@switchfont{%
4525     \bbl@ifunset{\bbl@lsys@language}{\bbl@provide@lsys{language}}}%
4526     \bbl@exp{% eg Arabic -> arabic
4527       \lowercase{\edef\\bbl@tempa{\bbl@cl{sname}}}%
4528       \bbl@foreach\bbl@font@fams{%
4529         \bbl@ifunset{\bbl@##1dflt@language}% (1) language?
4530         {\bbl@ifunset{\bbl@##1dflt@*\bbl@tempa}% (2) from script?
4531           {\bbl@ifunset{\bbl@##1dflt@}% 2=F - (3) from generic?
4532             }% 123=F - nothing!
4533             {\bbl@exp{% 3=T - from generic
4534               \global\let\<bbl@##1dflt@language>%
4535                 \<bbl@##1dflt@>}}}%
4536             {\bbl@exp{% 2=T - from script
4537               \global\let\<bbl@##1dflt@language>%
4538                 \<bbl@##1dflt@*\bbl@tempa>}}}%
4539             }% 1=T - language, already defined
4540       \def\bbl@tempa{\bbl@nostdfont}}%
4541       \bbl@foreach\bbl@font@fams{% don't gather with prev for
4542         \bbl@ifunset{\bbl@##1dflt@language}%
4543         {\bbl@cs{famrst@##1}%
4544           \global\bbl@csarg\let{famrst@##1}\relax}%
4545         {\bbl@exp{% order is relevant. TODO: but sometimes wrong!
4546           \\\bbl@add\\originalTeX{%
4547             \\\bbl@font@rst{\bbl@cl{##1dflt}}%
4548             \<##1default>\<##1family>{##1}}%
4549           \\\bbl@font@set\<bbl@##1dflt@language>% the main part!
4550           \<##1default>\<##1family>}}}%
4551       \bbl@ifrestoring{\bbl@tempa}%

```

The following is executed at the beginning of the aux file or the document to warn about fonts not defined with \babelfont.

```

4552 \ifx\fbfamily\undefined\else % if latex
4553 \ifcase\bb1@engine % if pdftex
4554 \let\bb1@ckeckstdfonts\relax
4555 \else
4556 \def\bb1@ckeckstdfonts{%
4557 \begingroup
4558 \global\let\bb1@ckeckstdfonts\relax
4559 \let\bb1@tempa\empty
4560 \bb1@foreach\bb1@font@fams{%
4561 \bb1@ifunset{\bb1##1dflt@}%
4562 {\@nameuse{##1family}%
4563 \bb1@csarg\gdef{WFF@fbfamily}}}% Flag
4564 \bb1@exp{\bb1@add\bb1@tempa{* \<##1family>= fbfamily\\}%
4565 \space\space\fontname\font\\}%
4566 \bb1@csarg\xdef{##1dflt@}{fbfamily}%
4567 \expandafter\xdef\csname ##1default\endcsname{fbfamily}%
4568 {}}%
4569 \ifx\bb1@tempa\empty\else
4570 \bb1@infowarn{The following font families will use the default\\%
4571 settings for all or some languages:\\%
4572 \bb1@tempa
4573 There is nothing intrinsically wrong with it, but\\%
4574 'babel' will no set Script and Language, which could\\%
4575 be relevant in some languages. If your document uses\\%
4576 these families, consider redefining them with \string\babelfont.\\%
4577 Reported}%
4578 \fi
4579 \endgroup}
4580 \fi
4581 \fi

```

Now the macros defining the font with fontspec.

When there are repeated keys in fontspec, the last value wins. So, we just place the ini settings at the beginning, and user settings will take precedence. We must deactivate temporarily `\bb1@mapselect` because `\selectfont` is called internally when a font is defined.

```

4582 \def\bb1@font@set#1#2#3{% eg \bb1@rmdflt@lang \rmdefault \rmfamily
4583 \bb1@xin@{<>}{#1}%
4584 \ifin@
4585 \bb1@exp{\bb1@fontspec@set\#1\expandafter\@gobbletwo#1\#3}%
4586 \fi
4587 \bb1@exp{%
4588 \def\#2{#1}% eg, \rmdefault{\bb1@rmdflt@lang}
4589 \bb1@ifsamestring{#2}{fbfamily}%
4590 {\#3%
4591 \bb1@ifsamestring{fbseries}{bfdefault}{\bfseries}}}%
4592 \let\bb1@tempa\relax}%
4593 {}}
4594 % TODO - next should be global?, but even local does its job. I'm
4595 % still not sure -- must investigate:
4596 \def\bb1@fontspec@set#1#2#3#4{% eg \bb1@rmdflt@lang fnt-opt fnt-nme \xxfamily
4597 \let\bb1@tempe\bb1@mapselect
4598 \let\bb1@mapselect\relax
4599 \let\bb1@temp@fam#4% eg, 'rmfamily', to be restored below
4600 \let#4\empty % Make sure \renewfontfamily is valid
4601 \bb1@exp{%
4602 \let\bb1@temp@pfam\<\bb1@stripslash#4\space>% eg, 'rmfamily '
4603 \<keys_if_exist:nnF>{fontspec-opentype}{Script/\bb1@cl{sname}}}%
4604 {\newfontscript{\bb1@cl{sname}}{\bb1@cl{sotf}}}%
4605 \<keys_if_exist:nnF>{fontspec-opentype}{Language/\bb1@cl{lname}}}%
4606 {\newfontlanguage{\bb1@cl{lname}}{\bb1@cl{lotf}}}%
4607 \renewfontfamily\#4%
4608 [\bb1@cl{lsys},#2]{#3}% ie \bb1@exp{..}{#3}
4609 \begingroup

```

```

4610      #4%
4611      \xdef#1{\f@family}%      eg, \bbl@rmdflt@lang{FreeSerif(0)}
4612 \endgroup
4613 \let#4\bbl@temp@fam
4614 \bbl@exp{\let\<\bbl@stripslash#4\space>}\bbl@temp@pfam
4615 \let\bbl@mapselect\bbl@tempe}%

```

font@rst and famrst are only used when there is no global settings, to save and restore de previous families. Not really necessary, but done for optimization.

```

4616 \def\bbl@font@rst#1#2#3#4{%
4617 \bbl@csarg\def{famrst@#4}{\bbl@font@set{#1}#2#3}}

```

The default font families. They are eurocentric, but the list can be expanded easily with \babelfont.

```

4618 \def\bbl@font@fams{rm,sf,tt}

```

The old tentative way. Short and preverved for compatibility, but deprecated. Note there is no direct alternative for \babelFSfeatures. The reason in explained in the user guide, but essentially – that was not the way to go :-).

```

4619 \newcommand\babelFSstore[2][{}]{%
4620 \bbl@ifblank{#1}%
4621 {\bbl@csarg\def{sname@#2}{Latin}}%
4622 {\bbl@csarg\def{sname@#2}{#1}}%
4623 \bbl@provide@dirs{#2}%
4624 \bbl@csarg\ifnum{wdir@#2}>\z@
4625 \let\bbl@beforeforeign\leavevmode
4626 \EnableBabelHook{babel-bidi}%
4627 \fi
4628 \bbl@foreach{#2}{%
4629 \bbl@FSstore{##1}{rm}\rmdefault\bbl@save@rmdefault
4630 \bbl@FSstore{##1}{sf}\sfdefault\bbl@save@sfdefault
4631 \bbl@FSstore{##1}{tt}\ttdefault\bbl@save@ttdefault}}
4632 \def\bbl@FSstore#1#2#3#4{%
4633 \bbl@csarg\edef{#2default#1}{#3}%
4634 \expandafter\addto\csname extras#1\endcsname{%
4635 \let#4#3%
4636 \ifx#3\f@family
4637 \edef#3{\csname bbl@#2default#1\endcsname}%
4638 \fontfamily{#3}\selectfont
4639 \else
4640 \edef#3{\csname bbl@#2default#1\endcsname}%
4641 \fi}%
4642 \expandafter\addto\csname noextras#1\endcsname{%
4643 \ifx#3\f@family
4644 \fontfamily{#4}\selectfont
4645 \fi
4646 \let#3#4}}
4647 \let\bbl@langfeatures\@empty
4648 \def\babelFSfeatures{% make sure \fontspec is redefined once
4649 \let\bbl@ori@fontspec\fontspec
4650 \renewcommand\fontspec[1][{}]{%
4651 \bbl@ori@fontspec[\bbl@langfeatures##1]}
4652 \let\babelFSfeatures\bbl@FSfeatures
4653 \babelFSfeatures}
4654 \def\bbl@FSfeatures#1#2{%
4655 \expandafter\addto\csname extras#1\endcsname{%
4656 \babel@save\bbl@langfeatures
4657 \edef\bbl@langfeatures{#2,}}%
4658 </Font selection>

```

12 Hooks for XeTeX and LuaTeX

12.1 XeTeX

Unfortunately, the current encoding cannot be retrieved and therefore it is reset always to utf8, which seems a sensible default.

```
4659 <{*Footnote changes}> ≡
4660 \bbl@trace{Bidi footnotes}
4661 \ifnum\bbl@bidimode>\z@
4662   \def\bbl@footnote#1#2#3{%
4663     \ifnextchar[%
4664       {\bbl@footnote@o{#1}{#2}{#3}}%
4665       {\bbl@footnote@x{#1}{#2}{#3}}}
4666   \long\def\bbl@footnote@x#1#2#3#4{%
4667     \bgroup
4668     \select@language@x{\bbl@main@language}%
4669     \bbl@fn@footnote{#2#1{\ignorespaces#4}#3}%
4670     \egroup}
4671   \long\def\bbl@footnote@o#1#2#3[#4]#5{%
4672     \bgroup
4673     \select@language@x{\bbl@main@language}%
4674     \bbl@fn@footnote[#4]{#2#1{\ignorespaces#5}#3}%
4675     \egroup}
4676   \def\bbl@footnotetext#1#2#3{%
4677     \ifnextchar[%
4678       {\bbl@footnotetext@o{#1}{#2}{#3}}%
4679       {\bbl@footnotetext@x{#1}{#2}{#3}}}
4680   \long\def\bbl@footnotetext@x#1#2#3#4{%
4681     \bgroup
4682     \select@language@x{\bbl@main@language}%
4683     \bbl@fn@footnotetext{#2#1{\ignorespaces#4}#3}%
4684     \egroup}
4685   \long\def\bbl@footnotetext@o#1#2#3[#4]#5{%
4686     \bgroup
4687     \select@language@x{\bbl@main@language}%
4688     \bbl@fn@footnotetext[#4]{#2#1{\ignorespaces#5}#3}%
4689     \egroup}
4690   \def\BabelFootnote#1#2#3#4{%
4691     \ifx\bbl@fn@footnote\undefined
4692       \let\bbl@fn@footnote\footnote
4693     \fi
4694     \ifx\bbl@fn@footnotetext\undefined
4695       \let\bbl@fn@footnotetext\footnotetext
4696     \fi
4697     \bbl@ifblank{#2}%
4698     {\def#1{\bbl@footnote{\@firstofone}{#3}{#4}}
4699      \namedef{\bbl@stripslash#1text}%
4700      {\bbl@footnotetext{\@firstofone}{#3}{#4}}}%
4701     {\def#1{\bbl@exp{\bbl@footnote{\foreignlanguage{#2}}}{#3}{#4}}%
4702      \namedef{\bbl@stripslash#1text}%
4703      {\bbl@exp{\bbl@footnotetext{\foreignlanguage{#2}}}{#3}{#4}}}%
4704   \fi
4705 <{/Footnote changes}>
```

Now, the code.

```
4706 <{*xetex}>
4707 \def\BabelStringsDefault{unicode}
4708 \let\xebbl@stop\relax
4709 \AddBabelHook{xetex}{encodedcommands}{%
4710   \def\bbl@tempa{#1}%
4711   \ifx\bbl@tempa\empty
4712     \XeTeXinputencoding"bytes"%
4713   \else
```

```

4714 \XeTeXinputencoding"#1"%
4715 \fi
4716 \def\xebbl@stop{\XeTeXinputencoding"utf8"}}
4717 \AddBabelHook{xetex}{stopcommands}{%
4718 \xebbl@stop
4719 \let\xebbl@stop\relax}
4720 \def\bbl@intraspace#1 #2 #3\@@{%
4721 \bbl@csarg\gdef{xeisp@\language}%
4722 {\XeTeXlinebreakskip #1em plus #2em minus #3em\relax}}
4723 \def\bbl@intrapenalty#1\@@{%
4724 \bbl@csarg\gdef{xeipn@\language}%
4725 {\XeTeXlinebreakpenalty #1\relax}}
4726 \def\bbl@provide@intraspace{%
4727 \bbl@xin@{/s}{/bbl@cl{lnbrk}}}%
4728 \ifin@else\bbl@xin@{/c}{/bbl@cl{lnbrk}}\fi
4729 \ifin@
4730 \bbl@ifunset{bbl@intsp@\language}{%
4731 {\expandafter\ifx\csname bbl@intsp@\language\endcsname\@empty\else
4732 \ifx\bbl@KVP@intraspace\@nil
4733 \bbl@exp{%
4734 \bbl@intraspace\bbl@cl{intsp}\@@}%
4735 \fi
4736 \ifx\bbl@KVP@intrapenalty\@nil
4737 \bbl@intrapenalty0\@@
4738 \fi
4739 \fi
4740 \ifx\bbl@KVP@intraspace\@nil\else % We may override the ini
4741 \expandafter\bbl@intraspace\bbl@KVP@intraspace\@@
4742 \fi
4743 \ifx\bbl@KVP@intrapenalty\@nil\else
4744 \expandafter\bbl@intrapenalty\bbl@KVP@intrapenalty\@@
4745 \fi
4746 \bbl@exp{%
4747 % TODO. Execute only once (but redundant):
4748 \bbl@add<extras\language>%
4749 \XeTeXlinebreaklocale "\bbl@cl{tbcpr}"%
4750 \<bbl@xeisp@\language>%
4751 \<bbl@xeipn@\language>%
4752 \bbl@toglobal\<extras\language>%
4753 \bbl@add<noextras\language>%
4754 \XeTeXlinebreaklocale "en"%
4755 \bbl@toglobal\<noextras\language>%
4756 \ifx\bbl@ispace\@undefined
4757 \gdef\bbl@ispace{\bbl@cl{xeisp}}%
4758 \ifx\AtBeginDocument\@notprerr
4759 \expandafter\@secondoftwo % to execute right now
4760 \fi
4761 \AtBeginDocument{\bbl@patchfont{\bbl@ispace}}%
4762 \fi}%
4763 \fi}
4764 \ifx\DisableBabelHook\@undefined\endinput\fi
4765 \AddBabelHook{babel-fontspec}{afterextras}{\bbl@switchfont}
4766 \AddBabelHook{babel-fontspec}{beforestart}{\bbl@ckeckstdfonts}
4767 \DisableBabelHook{babel-fontspec}
4768 <<Font selection>>
4769 \input txtbabel.def
4770 </xetex>

```

12.2 Layout

In progress.

Note elements like headlines and margins can be modified easily with packages like fancyhdr, typearea or titles, and geometry.

`\bbl@startskip` and `\bbl@endskip` are available to package authors. Thanks to the \TeX expansion mechanism the following constructs are valid: `\adim\bbl@startskip`, `\advance\bbl@startskip\adim`, `\bbl@startskip\adim`. Consider `txtbabel` as a shorthand for *tex-xet babel*, which is the bidi model in both `pdfTeX` and `xetex`.

```

4771 \*texet
4772 \providecommand\bbl@provide@intraspace{}
4773 \bbl@trace{Redefinitions for bidi layout}
4774 \def\bbl@sspre@caption{%
4775   \bbl@exp{\everyhbox{\bbl@textdir\bbl@cs{wdir@\bbl@main@language}}}}
4776 \ifx\bbl@opt@layout\@nnil\endinput\fi % No layout
4777 \def\bbl@startskip{\ifcase\bbl@thepardir\leftskip\else\rightskip\fi}
4778 \def\bbl@endskip{\ifcase\bbl@thepardir\rightskip\else\leftskip\fi}
4779 \ifx\bbl@beforeforeign\leavevmode % A poor test for bidi=
4780   \def\@hangfrom#1{%
4781     \setbox\@tempboxa\hbox{#1}}%
4782     \hangindent\ifcase\bbl@thepardir\wd\@tempboxa\else-\wd\@tempboxa\fi
4783     \noindent\box\@tempboxa}
4784 \def\raggedright{%
4785   \let\@centercr
4786   \bbl@startskip\z@skip
4787   \@rightskip\@flushglue
4788   \bbl@endskip\@rightskip
4789   \parindent\z@
4790   \parfillskip\bbl@startskip}
4791 \def\raggedleft{%
4792   \let\@centercr
4793   \bbl@startskip\@flushglue
4794   \bbl@endskip\z@skip
4795   \parindent\z@
4796   \parfillskip\bbl@endskip}
4797 \fi
4798 \IfBabelLayout{lists}
4799   {\bbl@sreplace\list
4800     {\@totalleftmargin\leftmargin}{\@totalleftmargin\bbl@listleftmargin}%
4801     \def\bbl@listleftmargin{%
4802       \ifcase\bbl@thepardir\leftmargin\else\rightmargin\fi}%
4803     \ifcase\bbl@engine
4804       \def\labelenumii{}\theenumii{}\pdfTeX doesn't reverse ()
4805       \def\p@enumiii{\p@enumii}\theenumii{}\fi
4806     \bbl@sreplace\@verbatim
4807       {\leftskip\@totalleftmargin}%
4808       {\bbl@startskip\textwidth
4809         \advance\bbl@startskip-\linewidth}%
4810       \bbl@sreplace\@verbatim
4811         {\rightskip\z@skip}%
4812         {\bbl@endskip\z@skip}}%
4813   {}
4814 {}
4815 \IfBabelLayout{contents}
4816   {\bbl@sreplace\@dottedtocline{\leftskip}{\bbl@startskip}%
4817     \bbl@sreplace\@dottedtocline{\rightskip}{\bbl@endskip}}
4818 {}
4819 \IfBabelLayout{columns}
4820   {\bbl@sreplace\@outputdblcol{\hb@xt@\textwidth}{\bbl@outputbox}%
4821     \def\bbl@outputbox#1{%
4822       \hb@xt@\textwidth{%
4823         \hskip\columnwidth
4824         \hfil
4825         {\normalcolor\vrule \@width\columnseprule}%
4826         \hfil
4827         \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
4828         \hskip-\textwidth
4829         \hb@xt@\columnwidth{\box\@outputbox \hss}%

```

```

4830      \hskip\columnsep
4831      \hskip\columnwidth}}}%
4832  {}
4833  <Footnote changes>
4834  \IfBabelLayout{footnotes}%
4835  {\BabelFootnote\footnote\language\language{}{}}%
4836  \BabelFootnote\localfootnote\language\language{}{}}%
4837  \BabelFootnote\mainfootnote{}{}}{}
4838  {}

```

Implicitly reverses sectioning labels in bidi=basic, because the full stop is not in contact with L numbers any more. I think there must be a better way.

```

4839 \IfBabelLayout{counters}%
4840 {\let\bbl@latinarabic=@arabic
4841  \def\@arabic#1{\babelsublr{\bbl@latinarabic#1}}}%
4842  \let\bbl@asciroman=@roman
4843  \def\@roman#1{\babelsublr{\ensureascii{\bbl@asciroman#1}}}%
4844  \let\bbl@asciiRoman=@Roman
4845  \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asciiRoman#1}}}}{}
4846 />texet

```

12.3 LuaTeX

The loader for luatex is based solely on language.dat, which is read on the fly. The code shouldn't be executed when the format is build, so we check if \AddBabelHook is defined. Then comes a modified version of the loader in hyphen.cfg (without the hyphenmins stuff, which is under the direct control of babel).

The names \l@<language> are defined and take some value from the beginning because all ldf files assume this for the corresponding language to be considered valid, but patterns are not loaded (except the first one). This is done later, when the language is first selected (which usually means when the ldf finishes). If a language has been loaded, \bbl@hyphendata@<num> exists (with the names of the files read).

The default setup preloads the first language into the format. This is intended mainly for 'english', so that it's available without further intervention from the user. To avoid duplicating it, the following rule applies: if the "0th" language and the first language in language.dat have the same name then just ignore the latter. If there are new synonymous, they are added, but note if the language patterns have not been preloaded they won't at run time.

Other preloaded languages could be read twice, if they have been preloaded into the format. This is not optimal, but it shouldn't happen very often – with luatex patterns are best loaded when the document is typeset, and the "0th" language is preloaded just for backwards compatibility.

As of 1.1b, lua(e)tex is taken into account. Formerly, loading of patterns on the fly didn't work in this format, but with the new loader it does. Unfortunately, the format is not based on babel, and data could be duplicated, because languages are reassigned above those in the format (nothing serious, anyway). Note even with this format language.dat is used (under the principle of a single source), instead of language.def.

Of course, there is room for improvements, like tools to read and reassign languages, which would require modifying the language list, and better error handling.

We need catcode tables, but no format (targeted by babel) provide a command to allocate them (although there are packages like ctablestack). FIX - This isn't true anymore. For the moment, a dangerous approach is used - just allocate a high random number and cross the fingers. To complicate things, etex.sty changes the way languages are allocated.

This files is read at three places: (1) when plain.def, babel.sty starts, to read the list of available languages from language.dat (for the base option); (2) at hyphen.cfg, to modify some macros; (3) in the middle of plain.def and babel.sty, by babel.def, with the commands and other definitions for luatex (eg, \babelpatterns).

```

4847 <*luatex>
4848 \ifx\AddBabelHook\undefined % When plain.def, babel.sty starts
4849 \bbl@trace{Read language.dat}
4850 \ifx\bbl@readstream\undefined
4851  \csname newread\endcsname\bbl@readstream
4852 \fi
4853 \begingroup
4854  \toks@{}

```

```

4855 \count@\z@ % 0=start, 1=0th, 2=normal
4856 \def\bbl@process@line#1#2 #3 #4 {%
4857   \ifx=#1%
4858     \bbl@process@synonym{#2}%
4859   \else
4860     \bbl@process@language{#1#2}{#3}{#4}%
4861   \fi
4862   \ignorespaces}
4863 \def\bbl@manylang{%
4864   \ifnum\bbl@last>\@ne
4865     \bbl@info{Non-standard hyphenation setup}%
4866   \fi
4867   \let\bbl@manylang\relax}
4868 \def\bbl@process@language#1#2#3{%
4869   \ifcase\count@
4870     \@ifundefined{zth@#1}{\count@\tw@}{\count@\@ne}%
4871   \or
4872     \count@\tw@
4873   \fi
4874   \ifnum\count@=\tw@
4875     \expandafter\addlanguage\csname l@#1\endcsname
4876     \language\allocationnumber
4877     \chardef\bbl@last\allocationnumber
4878     \bbl@manylang
4879     \let\bbl@elt\relax
4880     \xdef\bbl@languages{%
4881       \bbl@languages\bbl@elt{#1}{\the\language}{#2}{#3}}%
4882   \fi
4883   \the\toks@
4884   \toks@{}}
4885 \def\bbl@process@synonym@aux#1#2{%
4886   \global\expandafter\chardef\csname l@#1\endcsname#2\relax
4887   \let\bbl@elt\relax
4888   \xdef\bbl@languages{%
4889     \bbl@languages\bbl@elt{#1}{#2}{}}}%
4890 \def\bbl@process@synonym#1{%
4891   \ifcase\count@
4892     \toks@\expandafter{\the\toks@\relax\bbl@process@synonym{#1}}%
4893   \or
4894     \@ifundefined{zth@#1}{\bbl@process@synonym@aux{#1}{0}}}%
4895   \else
4896     \bbl@process@synonym@aux{#1}{\the\bbl@last}%
4897   \fi}
4898 \ifx\bbl@languages\@undefined % Just a (sensible?) guess
4899   \chardef\l@english\z@
4900   \chardef\l@USenglish\z@
4901   \chardef\bbl@last\z@
4902   \global\@namedef{bbl@hyphendata@0}{\hyphen.tex{}}
4903   \gdef\bbl@languages{%
4904     \bbl@elt{english}{0}{\hyphen.tex{}}%
4905     \bbl@elt{USenglish}{0}{}}
4906 \else
4907   \global\let\bbl@languages@format\bbl@languages
4908   \def\bbl@elt#1#2#3#4{% Remove all except language 0
4909     \ifnum#2>\z@ \else
4910       \noexpand\bbl@elt{#1}{#2}{#3}{#4}%
4911     \fi}%
4912   \xdef\bbl@languages{\bbl@languages}%
4913   \fi
4914   \def\bbl@elt#1#2#3#4{\@namedef{zth@#1}} % Define flags
4915   \bbl@languages
4916   \openin\bbl@readstream=language.dat
4917   \ifeof\bbl@readstream

```

```

4918 \bbl@warning{I couldn't find language.dat. No additional\\%
4919 patterns loaded. Reported}%
4920 \else
4921 \loop
4922 \endlinechar\m@ne
4923 \read\bbl@readstream to \bbl@line
4924 \endlinechar\^^M
4925 \if T\ifeof\bbl@readstream F\fi T\relax
4926 \ifx\bbl@line\empty\else
4927 \edef\bbl@line{\bbl@line\space\space\space}%
4928 \expandafter\bbl@process@line\bbl@line\relax
4929 \fi
4930 \repeat
4931 \fi
4932 \endgroup
4933 \bbl@trace{Macros for reading patterns files}
4934 \def\bbl@get@enc#1:#2:#3\@@@{\def\bbl@hyph@enc{#2}}
4935 \ifx\babelcatcodetablenum\undefined
4936 \ifx\newcatcodetable\undefined
4937 \def\babelcatcodetablenum{5211}
4938 \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
4939 \else
4940 \newcatcodetable\babelcatcodetablenum
4941 \newcatcodetable\bbl@pattcodes
4942 \fi
4943 \else
4944 \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
4945 \fi
4946 \def\bbl@luapatterns#1#2{%
4947 \bbl@get@enc#1::\@@@
4948 \setbox\z@\hbox\bgroup
4949 \begingroup
4950 \savecatcodetable\babelcatcodetablenum\relax
4951 \initcatcodetable\bbl@pattcodes\relax
4952 \catcodetable\bbl@pattcodes\relax
4953 \catcode`\#=6 \catcode`\$=3 \catcode`\&=4 \catcode`\^=7
4954 \catcode`\_ =8 \catcode`\{=1 \catcode`\}=2 \catcode`\~ =13
4955 \catcode`\@=11 \catcode`\^^I=10 \catcode`\^^J=12
4956 \catcode`\<=12 \catcode`\>=12 \catcode`\*=12 \catcode`\.=12
4957 \catcode`\-=12 \catcode`\/=12 \catcode`\[=12 \catcode`\]=12
4958 \catcode`\'=12 \catcode`\'=12 \catcode`\`=12
4959 \input #1\relax
4960 \catcodetable\babelcatcodetablenum\relax
4961 \endgroup
4962 \def\bbl@tempa{#2}%
4963 \ifx\bbl@tempa\empty\else
4964 \input #2\relax
4965 \fi
4966 \egroup}%
4967 \def\bbl@patterns@lua#1{%
4968 \language=\expandafter\ifx\csname l@#1:\f@encoding\endcsname\relax
4969 \csname l@#1\endcsname
4970 \edef\bbl@tempa{#1}%
4971 \else
4972 \csname l@#1:\f@encoding\endcsname
4973 \edef\bbl@tempa{#1:\f@encoding}%
4974 \fi\relax
4975 \@namedef{lu@texhyphen@loaded@the\language}{}% Temp
4976 \@ifundefined{bbl@hyphendata@the\language}%
4977 {\def\bbl@elt##1##2##3##4{%
4978 \ifnum##2=\csname l@bbl@tempa\endcsname % #2=spanish, dutch:OT1...
4979 \def\bbl@tempb{##3}%
4980 \ifx\bbl@tempb\empty\else % if not a synonymous

```

```

4981         \def\bbl@tempc{{##3}{##4}}%
4982         \fi
4983         \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
4984         \fi}%
4985     \bbl@languages
4986     \@ifundefined{bbl@hyphendata@the\language}%
4987     {\bbl@info{No hyphenation patterns were set for\%
4988         language '\bbl@tempa'. Reported}}%
4989     {\expandafter\expandafter\expandafter\bbl@luapatterns
4990         \csname bbl@hyphendata@the\language\endcsname}}}%
4991 \endinput\fi
4992 % Here ends \ifx\AddBabelHook\@undefined
4993 % A few lines are only read by hyphen.cfg
4994 \ifx\DisableBabelHook\@undefined
4995     \AddBabelHook{luatex}{everylanguage}{%
4996         \def\process@language##1##2##3{%
4997             \def\process@line####1####2 ####3 ####4 {}}%
4998     \AddBabelHook{luatex}{loadpatterns}{%
4999         \input #1\relax
5000         \expandafter\gdef\csname bbl@hyphendata@the\language\endcsname
5001             {{#1}}}%
5002     \AddBabelHook{luatex}{loadexceptions}{%
5003         \input #1\relax
5004         \def\bbl@tempb##1##2{{##1}{#1}}%
5005         \expandafter\xdef\csname bbl@hyphendata@the\language\endcsname
5006             {\expandafter\expandafter\expandafter\bbl@tempb
5007                 \csname bbl@hyphendata@the\language\endcsname}}%
5008 \endinput\fi
5009 % Here stops reading code for hyphen.cfg
5010 % The following is read the 2nd time it's loaded
5011 \begingroup % TODO - to a lua file
5012 \catcode`\%=12
5013 \catcode`\'=12
5014 \catcode`\\"=12
5015 \catcode`\:=12
5016 \directlua{
5017     Babel = Babel or {}
5018     function Babel.bytes(line)
5019         return line:gsub("(.)",
5020             function (chr) return unicode.utf8.char(string.byte(chr)) end)
5021     end
5022     function Babel.begin_process_input()
5023         if luatexbase and luatexbase.add_to_callback then
5024             luatexbase.add_to_callback('process_input_buffer',
5025                 Babel.bytes, 'Babel.bytes')
5026         else
5027             Babel.callback = callback.find('process_input_buffer')
5028             callback.register('process_input_buffer', Babel.bytes)
5029         end
5030     end
5031     function Babel.end_process_input ()
5032         if luatexbase and luatexbase.remove_from_callback then
5033             luatexbase.remove_from_callback('process_input_buffer', 'Babel.bytes')
5034         else
5035             callback.register('process_input_buffer', Babel.callback)
5036         end
5037     end
5038     function Babel.addpatterns(pp, lg)
5039         local lg = lang.new(lg)
5040         local pats = lang.patterns(lg) or ''
5041         lang.clear_patterns(lg)
5042         for p in pp:gmatch('[^%s]+') do
5043             ss = ''

```

```

5044     for i in string.utfcharacters(p:gsub('%d', '')) do
5045         ss = ss .. '%d?' .. i
5046     end
5047     ss = ss:gsub('^%d%?%.', '%%.') .. '%d?'
5048     ss = ss:gsub('%.%d%?$', '%%.')
5049     pats, n = pats:gsub('%s' .. ss .. '%s', ' ' .. p .. ' ')
5050     if n == 0 then
5051         tex.sprint(
5052             [[\string\csname\space bbl@info\endcsname{New pattern: }]]
5053             .. p .. [[{}]])
5054         pats = pats .. ' ' .. p
5055     else
5056         tex.sprint(
5057             [[\string\csname\space bbl@info\endcsname{Renew pattern: }]]
5058             .. p .. [[{}]])
5059     end
5060 end
5061 lang.patterns(lg, pats)
5062 end
5063 function Babel.hlist_has_bidi(head)
5064     local has_bidi = false
5065     for item in node.traverse(head) do
5066         if item.id == node.id'glyph' then
5067             local itemchar = item.char
5068             local chardata = Babel.characters[itemchar]
5069             local dir = chardata and chardata.d or nil
5070             if not dir then
5071                 for nn, et in ipairs(Babel.ranges) do
5072                     if itemchar < et[1] then
5073                         break
5074                     elseif itemchar <= et[2] then
5075                         dir = et[3]
5076                         break
5077                     end
5078                 end
5079             end
5080             if dir and (dir == 'al' or dir == 'r') then
5081                 has_bidi = true
5082             end
5083         end
5084     end
5085     return has_bidi
5086 end
5087 function Babel.set_chrnges_b (script, chrng)
5088     if chrng == '' then return end
5089     texio.write('Replacing ' .. script .. ' script ranges')
5090     Babel.script_blocks[script] = {}
5091     for s, e in string.gmatch(chrng..' ', '(-)%.%(-)%s') do
5092         table.insert(
5093             Babel.script_blocks[script], {tonumber(s,16), tonumber(e,16)})
5094     end
5095 end
5096 }
5097 \endgroup
5098 \ifx\newattribute\undefined\else
5099     \newattribute\bbl@attr@locale
5100     \directlua{ Babel.attr_locale = luatexbase.registernumber'bbl@attr@locale' }
5101     \AddBabelHook{luatex}{beforeextras}{%
5102         \setattribute\bbl@attr@locale\localeid}
5103 \fi
5104 \def\BabelStringsDefault{unicode}
5105 \let\luabbbl@stop\relax
5106 \AddBabelHook{luatex}{encodedcommands}{%

```

```

5107 \def\bbl@tempa{utf8}\def\bbl@tempb{#1}%
5108 \ifx\bbl@tempa\bbl@tempb\else
5109   \directlua{Babel.begin_process_input()}%
5110   \def\luabbbl@stop{%
5111     \directlua{Babel.end_process_input()}}%
5112 \fi}%
5113 \AddBabelHook{luatex}{stopcommands}{%
5114   \luabbbl@stop
5115   \let\luabbbl@stop\relax}
5116 \AddBabelHook{luatex}{patterns}{%
5117   \@ifundefined{bbl@hyphendata@the\language}%
5118   {\def\bbl@elt##1##2##3##4{%
5119     \ifnum##2=\csname l@##2\endcsname % #2=spanish, dutch:OT1...
5120     \def\bbl@tempb{##3}%
5121     \ifx\bbl@tempb\empty\else % if not a synonymous
5122       \def\bbl@tempc{##3}{##4}}%
5123     \fi
5124     \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
5125     \fi}%
5126   \bbl@languages
5127   \@ifundefined{bbl@hyphendata@the\language}%
5128   {\bbl@info{No hyphenation patterns were set for\%
5129     language '#2'. Reported}}%
5130   {\expandafter\expandafter\expandafter\bbl@luapatterns
5131     \csname bbl@hyphendata@the\language\endcsname}}}%
5132 \@ifundefined{bbl@patterns@}{}%
5133 \begingroup
5134   \bbl@xin@{,\number\language,}{,\bbl@pttnlist}%
5135   \ifin@velse
5136     \ifx\bbl@patterns@\empty\else
5137       \directlua{ Babel.addpatterns(
5138         [[\bbl@patterns@]], \number\language) }%
5139       \fi
5140       \@ifundefined{bbl@patterns@#1}%
5141       {\empty
5142         {\directlua{ Babel.addpatterns(
5143           [[\space\csname bbl@patterns@#1\endcsname]],
5144           \number\language) }}%
5145         \xdef\bbl@pttnlist{\bbl@pttnlist\number\language,}%
5146         \fi
5147       \endgroup}%
5148 \bbl@exp{%
5149   \bbl@ifunset{bbl@prehc@\languagename}{}%
5150   {\bbl@ifblank{\bbl@cs{prehc@\languagename}}}%
5151   {\prehyphenchar=\bbl@cl{prehc}\relax}}}%

```

`\babelpatterns` This macro adds patterns. Two macros are used to store them: `\bbl@patterns@` for the global ones and `\bbl@patterns@<lang>` for language ones. We make sure there is a space between words when multiple commands are used.

```

5152 \@onlypreamble\babelpatterns
5153 \AtEndOfPackage{%
5154   \newcommand\babelpatterns[2][\empty]{%
5155     \ifx\bbl@patterns@\relax
5156       \let\bbl@patterns@\empty
5157     \fi
5158     \ifx\bbl@pttnlist@\empty\else
5159       \bbl@warning{%
5160         You must not intermingle \string\selectlanguage\space and\%
5161         \string\babelpatterns\space or some patterns will not\%
5162         be taken into account. Reported}%
5163       \fi
5164     \ifx\@empty#1%
5165       \protected@edef\bbl@patterns@{\bbl@patterns@\space#2}%

```

```

5166 \else
5167 \edef\bbl@tempb{\zap@space#1 \@empty}%
5168 \bbl@for\bbl@tempa\bbl@tempb{%
5169 \bbl@fixname\bbl@tempa
5170 \bbl@iflanguage\bbl@tempa{%
5171 \bbl@csarg\protected@edef{patterns@\bbl@tempa}{%
5172 \@ifundefined{bbl@patterns@\bbl@tempa}%
5173 \@empty
5174 {\csname bbl@patterns@\bbl@tempa\endcsname\space}%
5175 #2}}}%
5176 \fi}}

```

12.4 Southeast Asian scripts

First, some general code for line breaking, used by `\babelposthyphenation`. Replace regular (ie, implicit) discretionaries by spaceskips, based on the previous glyph (which I think makes sense, because the hyphen and the previous char go always together). Other discretionaries are not touched. See Unicode UAX 14.

```

5177% TODO - to a lua file
5178 \directlua{
5179   Babel = Babel or {}
5180   Babel.linebreaking = Babel.linebreaking or {}
5181   Babel.linebreaking.before = {}
5182   Babel.linebreaking.after = {}
5183   Babel.locale = {} % Free to use, indexed by \localeid
5184   function Babel.linebreaking.add_before(func)
5185     tex.print([[noexpand\csname bbl@luahyphenate\endcsname]])
5186     table.insert(Babel.linebreaking.before, func)
5187   end
5188   function Babel.linebreaking.add_after(func)
5189     tex.print([[noexpand\csname bbl@luahyphenate\endcsname]])
5190     table.insert(Babel.linebreaking.after, func)
5191   end
5192 }
5193 \def\bbl@intraspace#1 #2 #3\@@{%
5194   \directlua{
5195     Babel = Babel or {}
5196     Babel.intraspaces = Babel.intraspaces or {}
5197     Babel.intraspaces['\csname bbl@sbc@language\endcsname'] = %
5198       {b = #1, p = #2, m = #3}
5199     Babel.locale_props[\the\localeid].intraspace = %
5200       {b = #1, p = #2, m = #3}
5201   }}
5202 \def\bbl@intrapenalty#1\@@{%
5203   \directlua{
5204     Babel = Babel or {}
5205     Babel.intrapenalties = Babel.intrapenalties or {}
5206     Babel.intrapenalties['\csname bbl@sbc@language\endcsname'] = #1
5207     Babel.locale_props[\the\localeid].intrapenalty = #1
5208   }}
5209 \begingroup
5210 \catcode`\%=12
5211 \catcode`\^=14
5212 \catcode`\'=12
5213 \catcode`\~=12
5214 \gdef\bbl@seaintraspace{^
5215   \let\bbl@seaintraspace\relax
5216   \directlua{
5217     Babel = Babel or {}
5218     Babel.sea_enabled = true
5219     Babel.sea_ranges = Babel.sea_ranges or {}
5220     function Babel.set_chranges (script, chrng)
5221       local c = 0

```



```

5222     for s, e in string.gmatch(chrng..' ', '(.-%.(-)%s') do
5223         Babel.sea_ranges[script..c]={tonumber(s,16), tonumber(e,16)}
5224         c = c + 1
5225     end
5226 end
5227 function Babel.sea_disc_to_space (head)
5228     local sea_ranges = Babel.sea_ranges
5229     local last_char = nil
5230     local quad = 655360      ^% 10 pt = 655360 = 10 * 65536
5231     for item in node.traverse(head) do
5232         local i = item.id
5233         if i == node.id'glyph' then
5234             last_char = item
5235         elseif i == 7 and item.subtype == 3 and last_char
5236             and last_char.char > 0x0C99 then
5237             quad = font.getfont(last_char.font).size
5238             for lg, rg in pairs(sea_ranges) do
5239                 if last_char.char > rg[1] and last_char.char < rg[2] then
5240                     lg = lg:sub(1, 4)  ^% Remove trailing number of, eg, Cyril1
5241                     local intraspace = Babel.intraspaces[lg]
5242                     local intrapenalty = Babel.intrapenalties[lg]
5243                     local n
5244                     if intrapenalty ~= 0 then
5245                         n = node.new(14, 0)      ^% penalty
5246                         n.penalty = intrapenalty
5247                         node.insert_before(head, item, n)
5248                     end
5249                     n = node.new(12, 13)      ^% (glue, spaceskip)
5250                     node.setglue(n, intraspace.b * quad,
5251                                 intraspace.p * quad,
5252                                 intraspace.m * quad)
5253                     node.insert_before(head, item, n)
5254                     node.remove(head, item)
5255                 end
5256             end
5257         end
5258     end
5259 end
5260 }^^
5261 \bbl@luahyphenate}

```

12.5 CJK line breaking

Minimal line breaking for CJK scripts, mainly intended for simple documents and short texts as a secondary language. Only line breaking, with a little stretching for justification, without any attempt to adjust the spacing. It is based on (but does not strictly follow) the Unicode algorithm.

We first need a little table with the corresponding line breaking properties. A few characters have an additional key for the width (fullwidth vs. halfwidth), not yet used. There is a separate file, defined below.

```

5262 \catcode`\%=14
5263 \gdef\bbl@cjkintraspaces{%
5264     \let\bbl@cjkintraspaces\relax
5265     \directlua{
5266         Babel = Babel or {}
5267         require('babel-data-cjk.lua')
5268         Babel.cjk_enabled = true
5269         function Babel.cjk_linebreak(head)
5270             local GLYPH = node.id'glyph'
5271             local last_char = nil
5272             local quad = 655360      % 10 pt = 655360 = 10 * 65536
5273             local last_class = nil
5274             local last_lang = nil
5275

```

```

5276     for item in node.traverse(head) do
5277         if item.id == GLYPH then
5278
5279             local lang = item.lang
5280
5281             local LOCALE = node.get_attribute(item,
5282                 Babel.attr_locale)
5283             local props = Babel.locale_props[LOCALE]
5284
5285             local class = Babel.cjk_class[item.char].c
5286
5287             if props.cjk_quotes and props.cjk_quotes[item.char] then
5288                 class = props.cjk_quotes[item.char]
5289             end
5290
5291             if class == 'cp' then class = 'cl' end % ]] as CL
5292             if class == 'id' then class = 'I' end
5293
5294             local br = 0
5295             if class and last_class and Babel.cjk_breaks[last_class][class] then
5296                 br = Babel.cjk_breaks[last_class][class]
5297             end
5298
5299             if br == 1 and props.linebreak == 'c' and
5300                 lang ~= \the\l@nohyphenation\space and
5301                 last_lang ~= \the\l@nohyphenation then
5302                 local intrapenalty = props.intrapenalty
5303                 if intrapenalty ~= 0 then
5304                     local n = node.new(14, 0)      % penalty
5305                     n.penalty = intrapenalty
5306                     node.insert_before(head, item, n)
5307                 end
5308                 local intraspace = props.intraspace
5309                 local n = node.new(12, 13)        % (glue, spaceskip)
5310                 node.setglue(n, intraspace.b * quad,
5311                     intraspace.p * quad,
5312                     intraspace.m * quad)
5313                 node.insert_before(head, item, n)
5314             end
5315
5316             if font.getfont(item.font) then
5317                 quad = font.getfont(item.font).size
5318             end
5319             last_class = class
5320             last_lang = lang
5321         else % if penalty, glue or anything else
5322             last_class = nil
5323         end
5324     end
5325     lang.hyphenate(head)
5326 end
5327 }%
5328 \bbl@luahyphenate}
5329 \gdef\bbl@luahyphenate{%
5330 \let\bbl@luahyphenate\relax
5331 \directlua{
5332     luatexbase.add_to_callback('hyphenate',
5333     function (head, tail)
5334         if Babel.linebreaking.before then
5335             for k, func in ipairs(Babel.linebreaking.before) do
5336                 func(head)
5337             end
5338         end

```

```

5339     if Babel.cjk_enabled then
5340       Babel.cjk_linebreak(head)
5341     end
5342     lang.hyphenate(head)
5343     if Babel.linebreaking.after then
5344       for k, func in ipairs(Babel.linebreaking.after) do
5345         func(head)
5346       end
5347     end
5348     if Babel.sea_enabled then
5349       Babel.sea_disc_to_space(head)
5350     end
5351   end,
5352   'Babel.hyphenate')
5353 }
5354 }
5355 \endgroup
5356 \def\bbl@provide@intraspace{%
5357   \bbl@ifunset\bbl@intsp@\languagename{}}%
5358   {\expandafter\ifx\csname bbl@intsp@\languagename\endcsname\@empty\else
5359     \bbl@xin@{/c}{/\bbl@cl{lnbrk}}}%
5360     \ifin@           % cjk
5361     \bbl@cjk@intraspace
5362     \directlua{
5363       Babel = Babel or {}
5364       Babel.locale_props = Babel.locale_props or {}
5365       Babel.locale_props[\the\localeid].linebreak = 'c'
5366     }%
5367     \bbl@exp{\\bbl@intraspace\bbl@cl{intsp}\\@}%
5368     \ifx\bbl@KVP@intrapenalty\@nil
5369       \bbl@intrapenalty0\@@
5370     \fi
5371   \else           % sea
5372     \bbl@sea@intraspace
5373     \bbl@exp{\\bbl@intraspace\bbl@cl{intsp}\\@}%
5374     \directlua{
5375       Babel = Babel or {}
5376       Babel.sea_ranges = Babel.sea_ranges or {}
5377       Babel.set_chranges('bbl@cl{sbc}',
5378         'bbl@cl{chrng}')
5379     }%
5380     \ifx\bbl@KVP@intrapenalty\@nil
5381       \bbl@intrapenalty0\@@
5382     \fi
5383   \fi
5384 \fi
5385 \ifx\bbl@KVP@intrapenalty\@nil\else
5386   \expandafter\bbl@intrapenalty\bbl@KVP@intrapenalty\@@
5387 \fi}}

```

12.6 Arabic justification

```

5388 \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200
5389 \def\bblar@chars{%
5390   0628,0629,062A,062B,062C,062D,062E,062F,0630,0631,0632,0633,%
5391   0634,0635,0636,0637,0638,0639,063A,063B,063C,063D,063E,063F,%
5392   0640,0641,0642,0643,0644,0645,0646,0647,0649}
5393 \def\bblar@elongated{%
5394   0626,0628,062A,062B,0633,0634,0635,0636,063B,%
5395   063C,063D,063E,063F,0641,0642,0643,0644,0646,%
5396   0649,064A}
5397 \begin{group}
5398   \catcode`_ =11 \catcode`:=11

```

```

5399 \gdef\bblar@nofswarn{\gdef\msg_warning:nx##1##2##3{}}
5400 \endgroup
5401 \gdef\bbl@arabicjust{%
5402   \let\bbl@arabicjust\relax
5403   \newattribute\bblar@kashida
5404   \directlua{ Babel.attr_kashida = luatexbase.registernumber'bblar@kashida' }%
5405   \bblar@kashida=\z@
5406   \bbl@patchfont{{\bbl@parsejalt}}%
5407   \directlua{
5408     Babel.arabic.elong_map = Babel.arabic.elong_map or {}
5409     Babel.arabic.elong_map[\the\localeid] = {}
5410     luatexbase.add_to_callback('post_linebreak_filter',
5411       Babel.arabic.justify, 'Babel.arabic.justify')
5412     luatexbase.add_to_callback('hpack_filter',
5413       Babel.arabic.justify_hbox, 'Babel.arabic.justify_hbox')
5414   }}%
5415 % Save both node lists to make replacement. TODO. Save also widths to
5416 % make computations
5417 \def\bblar@fetchjalt#1#2#3#4{%
5418   \bbl@exp{\bbl@foreach{#1}}{%
5419     \bbl@ifunset{bblar@JE@##1}%
5420     {\setbox\z@\hbox{^^^^200d\char"##1#2}}%
5421     {\setbox\z@\hbox{^^^^200d\char"\@nameuse{bblar@JE@##1}#2}}%
5422     \directlua{%
5423       local last = nil
5424       for item in node.traverse(tex.box[0].head) do
5425         if item.id == node.id'glyph' and item.char > 0x600 and
5426           not (item.char == 0x200D) then
5427           last = item
5428         end
5429       end
5430       Babel.arabic.#3['##1#4'] = last.char
5431     }}%
5432 % Brute force. No rules at all, yet. The ideal: look at jalt table. And
5433 % perhaps other tables (falt?, csw?). What about kaf? And diacritic
5434 % positioning?
5435 \gdef\bbl@parsejalt{%
5436   \ifx\addfontfeature\@undefined\else
5437     \bbl@xin@{/e}{/\bbl@c1{lbrk}}%
5438     \ifin@
5439       \directlua{%
5440         if Babel.arabic.elong_map[\the\localeid][\fontid\font] == nil then
5441           Babel.arabic.elong_map[\the\localeid][\fontid\font] = {}
5442           tex.print([[string\csname\space bbl@parsejalti\endcsname]])
5443         end
5444       }%
5445     \fi
5446   \fi}
5447 \gdef\bbl@parsejalti{%
5448   \begingroup
5449     \let\bbl@parsejalt\relax % To avoid infinite loop
5450     \edef\bbl@tempb{\fontid\font}%
5451     \bblar@nofswarn
5452     \bblar@fetchjalt\bblar@elongated{}{from}}%
5453     \bblar@fetchjalt\bblar@chars{^^^^064a}{from}{a}% Alef maksura
5454     \bblar@fetchjalt\bblar@chars{^^^^0649}{from}{y}% Yeh
5455     \addfontfeature{RawFeature=+jalt}%
5456     % \@namedef{bblar@JE@0643}{06AA}% todo: catch medial kaf
5457     \bblar@fetchjalt\bblar@elongated{}{dest}}%
5458     \bblar@fetchjalt\bblar@chars{^^^^064a}{dest}{a}%
5459     \bblar@fetchjalt\bblar@chars{^^^^0649}{dest}{y}%
5460     \directlua{%
5461       for k, v in pairs(Babel.arabic.from) do

```

```

5462         if Babel.arabic.dest[k] and
5463             not (Babel.arabic.from[k] == Babel.arabic.dest[k]) then
5464             Babel.arabic.elong_map[\the\localeid][\bbl@tempb]
5465             [Babel.arabic.from[k]] = Babel.arabic.dest[k]
5466         end
5467     end
5468 }%
5469 \endgroup}
5470 %
5471 \begingroup
5472 \catcode`#=11
5473 \catcode`~=11
5474 \directlua{
5475
5476 Babel.arabic = Babel.arabic or {}
5477 Babel.arabic.from = {}
5478 Babel.arabic.dest = {}
5479 Babel.arabic.justify_factor = 0.95
5480 Babel.arabic.justify_enabled = true
5481
5482 function Babel.arabic.justify(head)
5483     if not Babel.arabic.justify_enabled then return head end
5484     for line in node.traverse_id(node.id'hlist', head) do
5485         Babel.arabic.justify_hlist(head, line)
5486     end
5487     return head
5488 end
5489
5490 function Babel.arabic.justify_hbox(head, gc, size, pack)
5491     local has_inf = false
5492     if Babel.arabic.justify_enabled and pack == 'exactly' then
5493         for n in node.traverse_id(12, head) do
5494             if n.stretch_order > 0 then has_inf = true end
5495         end
5496         if not has_inf then
5497             Babel.arabic.justify_hlist(head, nil, gc, size, pack)
5498         end
5499     end
5500     return head
5501 end
5502
5503 function Babel.arabic.justify_hlist(head, line, gc, size, pack)
5504     local d, new
5505     local k_list, k_item, pos_inline
5506     local width, width_new, full, k_curr, wt_pos, goal, shift
5507     local subst_done = false
5508     local elong_map = Babel.arabic.elong_map
5509     local last_line
5510     local GLYPH = node.id'glyph'
5511     local KASHIDA = Babel.attr_kashida
5512     local LOCALE = Babel.attr_locale
5513
5514     if line == nil then
5515         line = {}
5516         line.glue_sign = 1
5517         line.glue_order = 0
5518         line.head = head
5519         line.shift = 0
5520         line.width = size
5521     end
5522
5523     % Exclude last line. todo. But-- it discards one-word lines, too!
5524     % ? Look for glue = 12:15

```

```

5525 if (line.glue_sign == 1 and line.glue_order == 0) then
5526     elongs = {}      % Stores elongated candidates of each line
5527     k_list = {}      % And all letters with kashida
5528     pos_inline = 0   % Not yet used
5529
5530     for n in node.traverse_id(GLYPH, line.head) do
5531         pos_inline = pos_inline + 1 % To find where it is. Not used.
5532
5533         % Elongated glyphs
5534         if elong_map then
5535             local locale = node.get_attribute(n, LOCALE)
5536             if elong_map[locale] and elong_map[locale][n.font] and
5537                 elong_map[locale][n.font][n.char] then
5538                 table.insert(elongs, {node = n, locale = locale} )
5539                 node.set_attribute(n.prev, KASHIDA, 0)
5540             end
5541         end
5542
5543         % Tatwil
5544         if Babel.kashida_wts then
5545             local k_wt = node.get_attribute(n, KASHIDA)
5546             if k_wt > 0 then % todo. parameter for multi inserts
5547                 table.insert(k_list, {node = n, weight = k_wt, pos = pos_inline})
5548             end
5549         end
5550
5551     end % of node.traverse_id
5552
5553     if #elongs == 0 and #k_list == 0 then goto next_line end
5554     full = line.width
5555     shift = line.shift
5556     goal = full * Babel.arabic.justify_factor % A bit crude
5557     width = node.dimensions(line.head)      % The 'natural' width
5558
5559     % == Elongated ==
5560     % Original idea taken from 'chickenize'
5561     while (#elongs > 0 and width < goal) do
5562         subst_done = true
5563         local x = #elongs
5564         local curr = elongs[x].node
5565         local oldchar = curr.char
5566         curr.char = elong_map[elongs[x].locale][curr.font][curr.char]
5567         width = node.dimensions(line.head) % Check if the line is too wide
5568         % Substitute back if the line would be too wide and break:
5569         if width > goal then
5570             curr.char = oldchar
5571             break
5572         end
5573         % If continue, pop the just substituted node from the list:
5574         table.remove(elongs, x)
5575     end
5576
5577     % == Tatwil ==
5578     if #k_list == 0 then goto next_line end
5579
5580     width = node.dimensions(line.head)      % The 'natural' width
5581     k_curr = #k_list
5582     wt_pos = 1
5583
5584     while width < goal do
5585         subst_done = true
5586         k_item = k_list[k_curr].node
5587         if k_list[k_curr].weight == Babel.kashida_wts[wt_pos] then

```

```

5588     d = node.copy(k_item)
5589     d.char = 0x0640
5590     line.head, new = node.insert_after(line.head, k_item, d)
5591     width_new = node.dimensions(line.head)
5592     if width > goal or width == width_new then
5593         node.remove(line.head, new) % Better compute before
5594         break
5595     end
5596     width = width_new
5597 end
5598 if k_curr == 1 then
5599     k_curr = #k_list
5600     wt_pos = (wt_pos >= table.getn(Babel.kashida_wts)) and 1 or wt_pos+1
5601 else
5602     k_curr = k_curr - 1
5603 end
5604 end
5605
5606 ::next_line::
5607
5608 % Must take into account marks and ins, see luatex manual.
5609 % Have to be executed only if there are changes. Investigate
5610 % what's going on exactly.
5611 if subst_done and not gc then
5612     d = node.hpack(line.head, full, 'exactly')
5613     d.shift = shift
5614     node.insert_before(head, line, d)
5615     node.remove(head, line)
5616 end
5617 end % if process line
5618 end
5619 }
5620 \endgroup
5621 \fi\fi % Arabic just block

```

12.7 Common stuff

```

5622 \AddBabelHook{babel-fontspec}{afterextras}{\bbl@switchfont}
5623 \AddBabelHook{babel-fontspec}{beforestart}{\bbl@cckstdfont}
5624 \DisableBabelHook{babel-fontspec}
5625 <{Font selection}>

```

12.8 Automatic fonts and ids switching

After defining the blocks for a number of scripts (must be extended and very likely fine tuned), we define a short function which just traverse the node list to carry out the replacements. The table `loc_to_scr` gets the locale form a script range (note the locale is the key, and that there is an intermediate table built on the fly for optimization). This locale is then used to get the `\language` and the `\localeid` as stored in `locale_props`, as well as the font (as requested). In the latter table a key starting with `/` maps the font from the global one (the key) to the local one (the value). Maths are skipped and discretionaries are handled in a special way.

```

5626 % TODO - to a lua file
5627 \directlua{
5628 Babel.script_blocks = {
5629   ['dflt'] = {},
5630   ['Arab'] = {{0x0600, 0x06FF}, {0x08A0, 0x08FF}, {0x0750, 0x077F},
5631               {0xFE70, 0xFEFF}, {0xFB50, 0xFDFF}, {0x1EE00, 0x1EEFF}},
5632   ['Armn'] = {{0x0530, 0x058F}},
5633   ['Beng'] = {{0x0980, 0x09FF}},
5634   ['Cher'] = {{0x13A0, 0x13FF}, {0xAB70, 0xABBF}},
5635   ['Copt'] = {{0x03E2, 0x03EF}, {0x2C80, 0x2CFF}, {0x102E0, 0x102FF}},
5636   ['Cyr1'] = {{0x0400, 0x04FF}, {0x0500, 0x052F}, {0x1C80, 0x1C8F},
5637               {0x2DE0, 0x2DFF}, {0xA640, 0xA69F}},
5638   ['Deva'] = {{0x0900, 0x097F}, {0xA8E0, 0xA8FF}},

```

```

5639 ['Ethi'] = {{0x1200, 0x137F}, {0x1380, 0x139F}, {0x2D80, 0x2DDF},
5640           {0xAB00, 0xAB2F}},
5641 ['Geor'] = {{0x10A0, 0x10FF}, {0x2D00, 0x2D2F}},
5642 % Don't follow strictly Unicode, which places some Coptic letters in
5643 % the 'Greek and Coptic' block
5644 ['Grek'] = {{0x0370, 0x03E1}, {0x03F0, 0x03FF}, {0x1F00, 0x1FFF}},
5645 ['Hans'] = {{0x2E80, 0x2EFF}, {0x3000, 0x303F}, {0x31C0, 0x31EF},
5646           {0x3300, 0x33FF}, {0x3400, 0x4DBF}, {0x4E00, 0x9FFF},
5647           {0xF900, 0xFAFF}, {0xFE30, 0xFE4F}, {0xFF00, 0xFFEF},
5648           {0x20000, 0x2A6DF}, {0x2A700, 0x2B73F},
5649           {0x2B740, 0x2B81F}, {0x2B820, 0x2CEAF},
5650           {0x2CEB0, 0x2EBEF}, {0x2F800, 0x2FA1F}},
5651 ['Hebr'] = {{0x0590, 0x05FF}},
5652 ['Jpan'] = {{0x3000, 0x303F}, {0x3040, 0x309F}, {0x30A0, 0x30FF},
5653           {0x4E00, 0x9FAF}, {0xFF00, 0xFFEF}},
5654 ['Khmr'] = {{0x1780, 0x17FF}, {0x19E0, 0x19FF}},
5655 ['Knda'] = {{0x0C80, 0x0CFF}},
5656 ['Kore'] = {{0x1100, 0x11FF}, {0x3000, 0x303F}, {0x3130, 0x318F},
5657           {0x4E00, 0x9FAF}, {0xA960, 0xA97F}, {0xAC00, 0xD7AF},
5658           {0xD7B0, 0xD7FF}, {0xFF00, 0xFFEF}},
5659 ['Lao'] = {{0x0E80, 0x0EFF}},
5660 ['Latn'] = {{0x0000, 0x007F}, {0x0080, 0x00FF}, {0x0100, 0x017F},
5661           {0x0180, 0x024F}, {0x1E00, 0x1EFF}, {0x2C60, 0x2C7F},
5662           {0xA720, 0xA7FF}, {0xAB30, 0xAB6F}},
5663 ['Mahj'] = {{0x11150, 0x1117F}},
5664 ['Mlym'] = {{0x0D00, 0x0D7F}},
5665 ['Mymr'] = {{0x1000, 0x109F}, {0xAA60, 0xAA7F}, {0xA9E0, 0xA9FF}},
5666 ['Orya'] = {{0x0B00, 0x0B7F}},
5667 ['Sinh'] = {{0x0D80, 0x0DFF}, {0x111E0, 0x111FF}},
5668 ['Sycr'] = {{0x0700, 0x074F}, {0x0860, 0x086F}},
5669 ['Taml'] = {{0x0B80, 0x0BFF}},
5670 ['Telu'] = {{0x0C00, 0x0C7F}},
5671 ['Tfng'] = {{0x2D30, 0x2D7F}},
5672 ['Thai'] = {{0x0E00, 0x0E7F}},
5673 ['Tibt'] = {{0x0F00, 0x0FFF}},
5674 ['Vaii'] = {{0xA500, 0xA63F}},
5675 ['Yiii'] = {{0xA000, 0xA48F}, {0xA490, 0xA4CF}}
5676 }
5677
5678 Babel.script_blocks.Cyrs = Babel.script_blocks.Cyrl
5679 Babel.script_blocks.Hant = Babel.script_blocks.Hans
5680 Babel.script_blocks.Kana = Babel.script_blocks.Jpan
5681
5682 function Babel.locale_map(head)
5683   if not Babel.locale_mapped then return head end
5684
5685   local LOCALE = Babel.attr_locale
5686   local GLYPH = node.id('glyph')
5687   local inmath = false
5688   local toloc_save
5689   for item in node.traverse(head) do
5690     local toloc
5691     if not inmath and item.id == GLYPH then
5692       % Optimization: build a table with the chars found
5693       if Babel.chr_to_loc[item.char] then
5694         toloc = Babel.chr_to_loc[item.char]
5695       else
5696         for lc, maps in pairs(Babel.loc_to_scr) do
5697           for _, rg in pairs(maps) do
5698             if item.char >= rg[1] and item.char <= rg[2] then
5699               Babel.chr_to_loc[item.char] = lc
5700             break
5701           end
5702         end
5703       end
5704     end
5705     toloc_save = toloc
5706   end
5707   return head

```



```

5702         end
5703     end
5704 end
5705 end
5706 % Now, take action, but treat composite chars in a different
5707 % fashion, because they 'inherit' the previous locale. Not yet
5708 % optimized.
5709 if not toloc and
5710     (item.char >= 0x0300 and item.char <= 0x036F) or
5711     (item.char >= 0x1AB0 and item.char <= 0x1AFF) or
5712     (item.char >= 0x1DC0 and item.char <= 0x1DFF) then
5713     toloc = toloc_save
5714 end
5715 if toloc and toloc > -1 then
5716     if Babel.locale_props[toloc].lg then
5717         item.lang = Babel.locale_props[toloc].lg
5718         node.set_attribute(item, LOCALE, toloc)
5719     end
5720     if Babel.locale_props[toloc]['/'..item.font] then
5721         item.font = Babel.locale_props[toloc]['/'..item.font]
5722     end
5723     toloc_save = toloc
5724 end
5725 elseif not inmath and item.id == 7 then
5726     item.replace = item.replace and Babel.locale_map(item.replace)
5727     item.pre      = item.pre and Babel.locale_map(item.pre)
5728     item.post     = item.post and Babel.locale_map(item.post)
5729 elseif item.id == node.id'math' then
5730     inmath = (item.subtype == 0)
5731 end
5732 end
5733 return head
5734 end
5735 }

```

The code for `\babelcharproperty` is straightforward. Just note the modified lua table can be different.

```

5736 \newcommand\babelcharproperty[1]{%
5737   \count@=#1\relax
5738   \ifvmode
5739     \expandafter\babel@chprop
5740   \else
5741     \babel@error{\string\babelcharproperty\space can be used only in\%
5742       vertical mode (preamble or between paragraphs)}%
5743     {See the manual for futher info}%
5744   \fi}
5745 \newcommand\babel@chprop[3][\the\count@]{%
5746   \@tempcnta=#1\relax
5747   \babel@ifunset{\babel@chprop@#2}%
5748   {\babel@error{No property named '#2'. Allowed values are\%
5749     direction (bc), mirror (bmg), and linebreak (lb)}%
5750     {See the manual for futher info}}%
5751   }%
5752   \loop
5753     \babel@cs{\babel@chprop@#2}{#3}%
5754     \ifnum\count@<\@tempcnta
5755       \advance\count@\@ne
5756     \repeat}
5757 \def\babel@chprop@direction#1{%
5758   \directlua{
5759     Babel.characters[\the\count@] = Babel.characters[\the\count@] or {}
5760     Babel.characters[\the\count@]['d'] = '#1'
5761   }}

```

```

5762 \let\bbl@chprop@bc\bbl@chprop@direction
5763 \def\bbl@chprop@mirror#1{%
5764   \directlua{
5765     Babel.characters[\the\count@] = Babel.characters[\the\count@] or {}
5766     Babel.characters[\the\count@]['m'] = '\number#1'
5767   }}
5768 \let\bbl@chprop@bmg\bbl@chprop@mirror
5769 \def\bbl@chprop@linebreak#1{%
5770   \directlua{
5771     Babel.cjk_characters[\the\count@] = Babel.cjk_characters[\the\count@] or {}
5772     Babel.cjk_characters[\the\count@]['c'] = '#1'
5773   }}
5774 \let\bbl@chprop@lb\bbl@chprop@linebreak
5775 \def\bbl@chprop@locale#1{%
5776   \directlua{
5777     Babel.chr_to_loc = Babel.chr_to_loc or {}
5778     Babel.chr_to_loc[\the\count@] =
5779       \bbl@ifblank{#1}{-1000}{\the\bbl@cs{id@#1}}\space
5780   }}

```

Post-handling hyphenation patterns for non-standard rules, like ff to ff-f. There are still some issues with speed (not very slow, but still slow). The Lua code is below.

```

5781 \directlua{
5782   Babel.nohyphenation = \the\l@nohyphenation
5783 }

```

Now the T_EX high level interface, which requires the function defined above for converting strings to functions returning a string. These functions handle the {*n*} syntax. For example, pre={1}{1}- becomes function(*m*) return *m*[1]..*m*[1]..'-' end, where *m* are the matches returned after applying the pattern. With a mapped capture the functions are similar to function(*m*) return Babel.capt_map(*m*[1],1) end, where the last argument identifies the mapping to be applied to *m*[1]. The way it is carried out is somewhat tricky, but the effect is not dissimilar to lua load – save the code as string in a TeX macro, and expand this macro at the appropriate place. As \directlua does not take into account the current catcode of @, we just avoid this character in macro names (which explains the internal group, too).

```

5784 \begingroup
5785 \catcode`\~ = 12
5786 \catcode`\% = 12
5787 \catcode`\& = 14
5788 \catcode`\| = 12
5789 \gdef\babelprehyphenation{%&
5790   \@ifnextchar[{\bbl@settransform{0}}{\bbl@settransform{0}}{]}
5791 \gdef\babelposthyphenation{%&
5792   \@ifnextchar[{\bbl@settransform{1}}{\bbl@settransform{1}}{]}
5793 \gdef\bbl@settransform#1[#2]#3#4#5{%&
5794   \ifcase#1
5795     \bbl@activateprehyphen
5796   \else
5797     \bbl@activateposthyphen
5798   \fi
5799 \begingroup
5800   \def\babeltempa{\bbl@add@list\babeltempb}%&
5801   \let\babeltempb\@empty
5802   \def\bbl@tempa{#5}%&
5803   \bbl@replace\bbl@tempa{,}{ ,}%& TODO. Ugly trick to preserve {}
5804   \expandafter\bbl@foreach\expandafter{\bbl@tempa}{%&
5805     \bbl@ifsamestring{##1}{remove}%&
5806     {\bbl@add@list\babeltempb{nil}}}%&
5807   {\directlua{
5808     local rep = {[#1]}
5809     rep = rep:gsub('^%s*(remove)%s*$', 'remove = true')
5810     rep = rep:gsub('^%s*(insert)%s*', 'insert = true, ')
5811     rep = rep:gsub('(string)%s*=%s*([%s,]*)', Babel.capture_func)
5812     if #1 == 0 then

```

```

5813         rep = rep:gsub('(space)%s*=%s*([%d%.]+)%s+([%d%.]+)%s+([%d%.]+)',
5814         'space = {' .. '%2, %3, %4' .. '}')
5815         rep = rep:gsub('(spacefactor)%s*=%s*([%d%.]+)%s+([%d%.]+)%s+([%d%.]+)',
5816         'spacefactor = {' .. '%2, %3, %4' .. '}')
5817         rep = rep:gsub('(kashida)%s*=%s*([^\s,]*)', Babel.capture_kashida)
5818     else
5819         rep = rep:gsub('(no)%s*=%s*([^\s,]*)', Babel.capture_func)
5820         rep = rep:gsub('(pre)%s*=%s*([^\s,]*)', Babel.capture_func)
5821         rep = rep:gsub('(post)%s*=%s*([^\s,]*)', Babel.capture_func)
5822     end
5823     tex.print([[string\babeltempa{[]} .. rep .. [{}]])
5824     }&%
5825 \let\bbl@kv@attribute\relax
5826 \let\bbl@kv@label\relax
5827 \bbl@forkv{#2}{\bbl@csarg\edef{kv@##1}{##2}}&%
5828 \ifx\bbl@kv@attribute\relax\else
5829     \edef\bbl@kv@attribute{\expandafter\bbl@stripslash\bbl@kv@attribute}&%
5830 \fi
5831 \directlua{
5832     local lbkr = Babel.linebreaking.replacements[#1]
5833     local u = unicode.utf8
5834     local id, attr, label
5835     if #1 == 0 then
5836         id = \the\csname bbl@id@#3\endcsname\space
5837     else
5838         id = \the\csname l@#3\endcsname\space
5839     end
5840     \ifx\bbl@kv@attribute\relax
5841         attr = -1
5842     \else
5843         attr = luatexbase.registernumber'\bbl@kv@attribute'
5844     \fi
5845     \ifx\bbl@kv@label\relax\else    %% Same refs:
5846         label = [==[\bbl@kv@label]==]
5847     \fi
5848     %% Convert pattern:
5849     local patt = string.gsub([==[#4]==], '%s', '')
5850     if #1 == 0 then
5851         patt = string.gsub(patt, '|', ' ')
5852     end
5853     if not u.find(patt, '()', nil, true) then
5854         patt = '()' .. patt .. '()'
5855     end
5856     if #1 == 1 then
5857         patt = string.gsub(patt, '%(%)^', '^()')
5858         patt = string.gsub(patt, '%$%(%)', '()$')
5859     end
5860     patt = u.gsub(patt, '{(.)}',
5861         function (n)
5862             return '%' .. (tonumber(n) and (tonumber(n)+1) or n)
5863         end)
5864     patt = u.gsub(patt, '{(%x%x%x%x+)}',
5865         function (n)
5866             return u.gsub(u.char(tonumber(n, 16)), '(%p)', '%%1')
5867         end)
5868     lbkr[id] = lbkr[id] or {}
5869     table.insert(lbkr[id],
5870         { label=label, attr=attr, pattern=patt, replace={\babeltempb} })
5871     }&%
5872 \endgroup}
5873 \endgroup
5874 \def\bbl@activateposthyphen{%
5875     \let\bbl@activateposthyphen\relax

```

```

5876 \directlua{
5877     require('babel-transforms.lua')
5878     Babel.linebreaking.add_after(Babel.post_hyphenate_replace)
5879 }}
5880 \def\bbl@activateprehyphen{%
5881     \let\bbl@activateprehyphen\relax
5882     \directlua{
5883         require('babel-transforms.lua')
5884         Babel.linebreaking.add_before(Babel.pre_hyphenate_replace)
5885     }}

```

12.9 Bidi

As a first step, add a handler for bidi and digits (and potentially other processes) just before luaotfload is applied, which is loaded by default by L^AT_EX. Just in case, consider the possibility it has not been loaded.

```

5886 \def\bbl@activate@preotf{%
5887     \let\bbl@activate@preotf\relax % only once
5888     \directlua{
5889         Babel = Babel or {}
5890         %
5891         function Babel.pre_otfload_v(head)
5892             if Babel.numbers and Babel.digits_mapped then
5893                 head = Babel.numbers(head)
5894             end
5895             if Babel.bidi_enabled then
5896                 head = Babel.bidi(head, false, dir)
5897             end
5898             return head
5899         end
5900         %
5901         function Babel.pre_otfload_h(head, gc, sz, pt, dir)
5902             if Babel.numbers and Babel.digits_mapped then
5903                 head = Babel.numbers(head)
5904             end
5905             if Babel.bidi_enabled then
5906                 head = Babel.bidi(head, false, dir)
5907             end
5908             return head
5909         end
5910         %
5911         luatexbase.add_to_callback('pre_linebreak_filter',
5912             Babel.pre_otfload_v,
5913             'Babel.pre_otfload_v',
5914             luatexbase.priority_in_callback('pre_linebreak_filter',
5915                 'luaotfload.node_processor') or nil)
5916         %
5917         luatexbase.add_to_callback('hpack_filter',
5918             Babel.pre_otfload_h,
5919             'Babel.pre_otfload_h',
5920             luatexbase.priority_in_callback('hpack_filter',
5921                 'luaotfload.node_processor') or nil)
5922     }}

```

The basic setup. The output is modified at a very low level to set the `\bodydir` to the `\pagedir`. Sadly, we have to deal with boxes in math with basic, so the `\bbl@mathboxdir` hack is activated every math with the package option `bidi=`.

```

5923 \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200
5924     \let\bbl@beforeforeign\leavevmode
5925     \AtEndOfPackage{\EnableBabelHook{babel-bidi}}
5926     \RequirePackage{luatexbase}
5927     \bbl@activate@preotf
5928     \directlua{

```

```

5929     require('babel-data-bidi.lua')
5930     \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
5931         require('babel-bidi-basic.lua')
5932     \or
5933         require('babel-bidi-basic-r.lua')
5934     \fi}
5935 % TODO - to locale_props, not as separate attribute
5936 \newattribute\bbl@attr@dir
5937 \directlua{ Babel.attr_dir = luatexbase.registernumber'bbl@attr@dir' }
5938 % TODO. I don't like it, hackish:
5939 \bbl@exp{\output{\bodydir\pagedir\the\output}}
5940 \AtEndOfPackage{\EnableBabelHook{babel-bidi}}
5941 \fi\fi
5942 \chardef\bbl@thetextdir\z@
5943 \chardef\bbl@thepardir\z@
5944 \def\bbl@getluadir#1{%
5945     \directlua{
5946         if tex.#1dir == 'TLT' then
5947             tex.sprint('0')
5948         elseif tex.#1dir == 'TRT' then
5949             tex.sprint('1')
5950         end}}
5951 \def\bbl@setluadir#1#2#3{% 1=text/par.. 2=\textdir.. 3=0 lr/1 rl
5952     \ifcase#3\relax
5953         \ifcase\bbl@getluadir{#1}\relax\else
5954             #2 TLT\relax
5955         \fi
5956     \else
5957         \ifcase\bbl@getluadir{#1}\relax
5958             #2 TRT\relax
5959         \fi
5960     \fi}
5961 \def\bbl@thedir{0}
5962 \def\bbl@textdir#1{%
5963     \bbl@setluadir{text}\textdir{#1}%
5964     \chardef\bbl@thetextdir#1\relax
5965     \edef\bbl@thedir{\the\numexpr\bbl@thepardir*3+#1}%
5966     \setattribute\bbl@attr@dir{\numexpr\bbl@thepardir*3+#1}}
5967 \def\bbl@pardir#1{%
5968     \bbl@setluadir{par}\pardir{#1}%
5969     \chardef\bbl@thepardir#1\relax}
5970 \def\bbl@bodydir{\bbl@setluadir{body}\bodydir}
5971 \def\bbl@pagedir{\bbl@setluadir{page}\pagedir}
5972 \def\bbl@dirparastext{\pardir\the\textdir\relax}%    %%%
5973 %
5974 \ifnum\bbl@bidimode>\z@
5975     \def\bbl@insidemath{0}%
5976     \def\bbl@everymath{\def\bbl@insidemath{1}}
5977     \def\bbl@everydisplay{\def\bbl@insidemath{2}}
5978     \frozen@everymath\expandafter{%
5979         \expandafter\bbl@everymath\the\frozen@everymath}
5980     \frozen@everydisplay\expandafter{%
5981         \expandafter\bbl@everydisplay\the\frozen@everydisplay}
5982     \AtBeginDocument{
5983         \directlua{
5984             function Babel.math_box_dir(head)
5985                 if not (token.get_macro('bbl@insidemath') == '0') then
5986                     if Babel.hlist_has_bidi(head) then
5987                         local d = node.new(node.id'dir')
5988                         d.dir = '+TRT'
5989                         node.insert_before(head, node.has_glyph(head), d)
5990                         for item in node.traverse(head) do
5991                             node.set_attribute(item,

```

```

5992         Babel.attr_dir, token.get_macro('bbl@thedir'))
5993     end
5994 end
5995 end
5996 return head
5997 end
5998 luatexbase.add_to_callback("hpack_filter", Babel.math_box_dir,
5999     "Babel.math_box_dir", 0)
6000 }}%
6001 \fi

```

12.10 Layout

Unlike xetex, luatex requires only minimal changes for right-to-left layouts, particularly in monolingual documents (the engine itself reverses boxes – including column order or headings –, margins, etc.) with `bidi=basic`, without having to patch almost any macro where text direction is relevant.

`\@hangfrom` is useful in many contexts and it is redefined always with the layout option.

There are, however, a number of issues when the text direction is not the same as the box direction (as set by `\bodydir`), and when `\parbox` and `\hangindent` are involved. Fortunately, latest releases of luatex simplify a lot the solution with `\shapemode`.

With the issue #15 I realized commands are best patched, instead of redefined. With a few lines, a modification could be applied to several classes and packages. Now, `tabular` seems to work (at least in simple cases) with `array`, `tabularx`, `hline`, `colortbl`, `longtable`, `booktabs`, etc. However, `dcolumn` still fails.

```

6002 \bbl@trace{Redefinitions for bidi layout}
6003 %
6004 <<(*More package options)>> ≡
6005 \chardef\bbl@eqnpos\z@
6006 \DeclareOption{leqno}{\chardef\bbl@eqnpos\@ne}
6007 \DeclareOption{fleqn}{\chardef\bbl@eqnpos\tw@}
6008 <</More package options>>
6009 %
6010 \def\BabelNoAMSMath{\let\bbl@noamsmath\relax}
6011 \ifnum\bbl@bidimode>\z@
6012   \ifx\matheqdirmode\undefined\else
6013     \matheqdirmode\@ne
6014   \fi
6015   \let\bbl@eqnodir\relax
6016   \def\bbl@eqdel{()}
6017   \def\bbl@eqnum{%
6018     {\normalfont\normalcolor
6019       \expandafter\@firstoftwo\bbl@eqdel
6020       \theequation
6021       \expandafter\@secondoftwo\bbl@eqdel}}
6022   \def\bbl@puteqno#1{\leqno\hbox{#1}}
6023   \def\bbl@putleqno#1{\leqno\hbox{#1}}
6024   \def\bbl@eqno@flip#1{%
6025     \ifdim\predisplaysize=-\maxdimen
6026       \leqno
6027       \hb@xt@.01pt{\hb@xt@\displaywidth{\hss{#1}}\hss}%
6028     \else
6029       \leqno\hbox{#1}%
6030     \fi}
6031   \def\bbl@leqno@flip#1{%
6032     \ifdim\predisplaysize=-\maxdimen
6033       \leqno
6034       \hb@xt@.01pt{\hss\hb@xt@\displaywidth{{#1}\hss}}%
6035     \else
6036       \leqno\hbox{#1}%
6037     \fi}
6038   \AtBeginDocument{%
6039     \ifx\maketag@@@\undefined % Normal equation, eqnarray

```

```

6040 \AddToHook{env/equation/begin}{%
6041   \ifnum\bb1@thetextdir>\z@
6042     \let\@eqnnum\bb1@eqnum
6043     \edef\bb1@eqnodir{\noexpand\bb1@textdir{\the\bb1@thetextdir}}%
6044     \chardef\bb1@thetextdir\z@
6045     \bb1@add\normalfont{\bb1@eqnodir}%
6046     \ifcase\bb1@eqnpos
6047       \let\bb1@puteqno\bb1@eqno@flip
6048     \or
6049       \let\bb1@puteqno\bb1@leqno@flip
6050     \fi
6051   \fi}%
6052 \ifnum\bb1@eqnpos=\tw@%else
6053   \def\endequation{\bb1@puteqno{\@eqnnum}$$\@ignoretrue}%
6054 \fi
6055 \AddToHook{env/eqnarray/begin}{%
6056   \ifnum\bb1@thetextdir>\z@
6057     \edef\bb1@eqnodir{\noexpand\bb1@textdir{\the\bb1@thetextdir}}%
6058     \chardef\bb1@thetextdir\z@
6059     \bb1@add\normalfont{\bb1@eqnodir}%
6060     \ifnum\bb1@eqnpos=\@ne
6061       \def\@eqnnum{%
6062         \setbox\z@\hbox{\bb1@eqnum}%
6063         \hbox to 0.01pt{\hss\hbox to\displaywidth{\box\z@\hss}}}%
6064       \else
6065         \let\@eqnnum\bb1@eqnum
6066       \fi
6067     \fi}
6068 % Hack. YA luatex bug?:
6069 \expandafter\bb1@sreplace\csname] \endcsname{${$}\eqno\kern.001pt${$}%
6070 \else % amstex
6071   \ifx\bb1@noamsmath\@undefined
6072     \ifnum\bb1@eqnpos=\@ne
6073       \let\bb1@ams@lap\hbox
6074     \else
6075       \let\bb1@ams@lap\llap
6076     \fi
6077     \ExplSyntaxOn
6078     \bb1@sreplace\intertext@{\normalbaselines}%
6079     {\normalbaselines
6080       \ifx\bb1@eqnodir\relax\else\bb1@pardir\@ne\bb1@eqnodir\fi}%
6081     \ExplSyntaxOff
6082     \def\bb1@ams@tagbox#1#2{#1{\bb1@eqnodir#2}}% #1=hbox|@lap|flip
6083     \ifx\bb1@ams@lap\hbox % leqno
6084       \def\bb1@ams@flip#1{%
6085         \hbox to 0.01pt{\hss\hbox to\displaywidth{#{1}\hss}}}%
6086     \else % eqno
6087       \def\bb1@ams@flip#1{%
6088         \hbox to 0.01pt{\hbox to\displaywidth{\hss{#1}\hss}}}%
6089     \fi
6090     \def\bb1@ams@preset#1{%
6091       \ifnum\bb1@thetextdir>\z@
6092         \edef\bb1@eqnodir{\noexpand\bb1@textdir{\the\bb1@thetextdir}}%
6093         \bb1@sreplace\textdef@{\hbox}{\bb1@ams@tagbox\hbox}%
6094         \bb1@sreplace\maketag@@@{\hbox}{\bb1@ams@tagbox#1}%
6095       \fi}%
6096   \ifnum\bb1@eqnpos=\tw@%else
6097     \def\bb1@ams@equation{%
6098       \ifnum\bb1@thetextdir>\z@
6099         \edef\bb1@eqnodir{\noexpand\bb1@textdir{\the\bb1@thetextdir}}%
6100         \chardef\bb1@thetextdir\z@
6101         \bb1@add\normalfont{\bb1@eqnodir}%
6102         \ifcase\bb1@eqnpos

```

```

6103         \def\veqno##1##2{\bbl@eqno@flip{##1##2}}%
6104     \or
6105         \def\veqno##1##2{\bbl@leqno@flip{##1##2}}%
6106     \fi
6107 \fi}%
6108 \AddToHook{env/equation/begin}{\bbl@ams@equation}%
6109 \AddToHook{env/equation*/begin}{\bbl@ams@equation}%
6110 \fi
6111 \AddToHook{env/cases/begin}{\bbl@ams@preset\bbl@ams@lap}%
6112 \AddToHook{env/multline/begin}{\bbl@ams@preset\hbox}%
6113 \AddToHook{env/gather/begin}{\bbl@ams@preset\bbl@ams@lap}%
6114 \AddToHook{env/gather*/begin}{\bbl@ams@preset\bbl@ams@lap}%
6115 \AddToHook{env/align/begin}{\bbl@ams@preset\bbl@ams@lap}%
6116 \AddToHook{env/align*/begin}{\bbl@ams@preset\bbl@ams@lap}%
6117 \AddToHook{env/eqnalign/begin}{\bbl@ams@preset\hbox}%
6118 % Hackish, for proper alignment. Don't ask me why it works!:
6119 \bbl@exp{% Avoid a 'visible' conditional
6120     \\\AddToHook{env/align*/end}{\<iftag@>\<else>\\tag*{}<fi>}}%
6121 \AddToHook{env/flalign/begin}{\bbl@ams@preset\hbox}%
6122 \AddToHook{env/split/before}{%
6123     \ifnum\bbl@thetextdir>z@
6124         \bbl@ifsamestring\@currentenv{equation}%
6125         {\ifx\bbl@ams@lap\hbox % leqno
6126             \def\bbl@ams@flip#1{%
6127                 \hbox to 0.01pt{\hbox to\displaywidth{{#1}\hss}\hss}}%
6128             \else
6129                 \def\bbl@ams@flip#1{%
6130                     \hbox to 0.01pt{\hss\hbox to\displaywidth{\hss{#1}}}%
6131                 }%
6132             }%
6133         \fi}%
6134     \fi
6135 \fi}
6136 \fi
6137 \ifx\bbl@opt@layout\@nnil\endinput\fi % if no layout
6138 \ifnum\bbl@bidimode>z@
6139     \def\bbl@nextfake#1{% non-local changes, use always inside a group!
6140         \bbl@exp{%
6141             \def\\bbl@insidemath{0}%
6142             \mathdir\the\bodydir
6143             #1% Once entered in math, set boxes to restore values
6144             \<ifmmode>%
6145                 \everyvbox{%
6146                     \the\everyvbox
6147                     \bodydir\the\bodydir
6148                     \mathdir\the\mathdir
6149                     \everyhbox{\the\everyhbox}%
6150                     \everyvbox{\the\everyvbox}}%
6151                 \everyhbox{%
6152                     \the\everyhbox
6153                     \bodydir\the\bodydir
6154                     \mathdir\the\mathdir
6155                     \everyhbox{\the\everyhbox}%
6156                     \everyvbox{\the\everyvbox}}%
6157             \<fi>}}%
6158     \def\@hangfrom#1{%
6159         \setbox\@tempboxa\hbox{{#1}}%
6160         \hangindent\wd\@tempboxa
6161         \ifnum\bbl@getluadir{page}=\bbl@getluadir{par}\else
6162             \shapemode\@ne
6163         \fi
6164         \noindent\box\@tempboxa}
6165 \fi

```



```

6166 \IfBabelLayout{tabular}
6167   {\let\bbl@OL@@tabular\@tabular
6168     \bbl@replace\@tabular{$}\bbl@nextfake$}%
6169   \let\bbl@NL@@tabular\@tabular
6170   \AtBeginDocument{%
6171     \ifx\bbl@NL@@tabular\@tabular\else
6172       \bbl@replace\@tabular{$}\bbl@nextfake$}%
6173     \let\bbl@NL@@tabular\@tabular
6174   \fi}}
6175 {}
6176 \IfBabelLayout{lists}
6177   {\let\bbl@OL@list\list
6178     \bbl@sreplace\list{\parshape}\bbl@listparshape}%
6179   \let\bbl@NL@list\list
6180   \def\bbl@listparshape#1#2#3{%
6181     \parshape #1 #2 #3 %
6182     \ifnum\bbl@getluadir{page}=\bbl@getluadir{par}\else
6183       \shapemode\tw@
6184     \fi}}
6185 {}
6186 \IfBabelLayout{graphics}
6187   {\let\bbl@pictresetdir\relax
6188     \def\bbl@pictsetdir#1{%
6189       \ifcase\bbl@thetextdir
6190         \let\bbl@pictresetdir\relax
6191       \else
6192         \ifcase#1\bodydir TLT % Remember this sets the inner boxes
6193           \or\textdir TLT
6194           \else\bodydir TLT \textdir TLT
6195         \fi
6196         % \(\text|par)dir required in pgf:
6197         \def\bbl@pictresetdir{\bodydir TRT\pardir TRT\textdir TRT\relax}%
6198       \fi}%
6199   \AddToHook{env/picture/begin}{\bbl@pictsetdir\tw@}%
6200   \directlua{
6201     Babel.get_picture_dir = true
6202     Babel.picture_has_bidi = 0
6203     %
6204     function Babel.picture_dir (head)
6205       if not Babel.get_picture_dir then return head end
6206       if Babel.hlist_has_bidi(head) then
6207         Babel.picture_has_bidi = 1
6208       end
6209       return head
6210     end
6211     luatexbase.add_to_callback("hpack_filter", Babel.picture_dir,
6212       "Babel.picture_dir")
6213   }%
6214   \AtBeginDocument{%
6215     \long\def\put(#1,#2)#3{%
6216       \@killglue
6217       % Try:
6218       \ifx\bbl@pictresetdir\relax
6219         \def\bbl@tempc{0}%
6220       \else
6221         \directlua{
6222           Babel.get_picture_dir = true
6223           Babel.picture_has_bidi = 0
6224         }%
6225         \setbox\z@\hb@xt@\z@{%
6226           \@defaultunitsset\@tempdimc{#1}\unitlength
6227           \kern\@tempdimc
6228           #3\hss}% TODO: #3 executed twice (below). That's bad.

```

```

6229     \edef\bbl@tempc{\directlua{tex.print(Babel.picture_has_bidi)}}%
6230     \fi
6231     % Do:
6232     \@defaultunitsset\@tempdimc{#2}\unitlength
6233     \raise\@tempdimc\hb@xt@\z@{%
6234     \@defaultunitsset\@tempdimc{#1}\unitlength
6235     \kern\@tempdimc
6236     {\ifnum\bbl@tempc>\z@\bbl@pictresetdir\fi#3}\hss}%
6237     \ignorespaces}%
6238     \MakeRobust\put}%
6239     \AtBeginDocument
6240     {\AddToHook{cmd/diagbox@pict/before}{\let\bbl@pictsetdir\@gobble}%
6241     \ifx\pgfpicture\@undefined\else % TODO. Allow deactivate?
6242     \AddToHook{env/pgfpicture/begin}{\bbl@pictsetdir\@ne}%
6243     \bbl@add\pgfinterruptpicture{\bbl@pictresetdir}%
6244     \bbl@add\pgfsys@beginpicture{\bbl@pictsetdir\z@}%
6245     \fi
6246     \ifx\tikzpicture\@undefined\else
6247     \AddToHook{env/tikzpicture/begin}{\bbl@pictsetdir\z@}%
6248     \bbl@add\tikz@atbegin@node{\bbl@pictresetdir}%
6249     \bbl@sreplace\tikz{\begingroup}{\begingroup\bbl@pictsetdir\tw@}%
6250     \fi
6251     \ifx\tcolorbox\@undefined\else
6252     \AddToHook{env/tcolorbox/begin}{\bbl@pictsetdir\@ne}%
6253     \bbl@sreplace\tcb@savebox
6254     {\ignorespaces}{\ignorespaces\bbl@pictresetdir}%
6255     \ifx\tikzpicture\tcb@hooked\@undefined\else
6256     \bbl@sreplace\tikzpicture\tcb@hooked{\noexpand\tikzpicture}%
6257     {\textdir TLT\noexpand\tikzpicture}%
6258     \fi
6259     \fi
6260     }}
6261     {}

```

Implicitly reverses sectioning labels in `bidi=basic-r`, because the full stop is not in contact with L numbers any more. I think there must be a better way. Assumes `bidi=basic`, but there are some additional readjustments for `bidi=default`.

```

6262 \IfBabelLayout{counters}%
6263 {\let\bbl@OL@@textsuperscript\@textsuperscript
6264  \bbl@sreplace\@textsuperscript{\m@th}{\m@th\mathdir\pagedir}%
6265  \let\bbl@latinarabic=\@arabic
6266  \let\bbl@OL@@arabic\@arabic
6267  \def\@arabic#1{\babelsublr{\bbl@latinarabic#1}}%
6268  \@ifpackagewith{babel}{bidi=default}%
6269  {\let\bbl@asciroman=\@roman
6270   \let\bbl@OL@@roman\@roman
6271   \def\@roman#1{\babelsublr{\ensureascii{\bbl@asciroman#1}}}%
6272   \let\bbl@asciiRoman=\@Roman
6273   \let\bbl@OL@@roman\@Roman
6274   \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asciiRoman#1}}}%
6275   \let\bbl@OL@labelenumii\labelenumii
6276   \def\labelenumii{}\theenumii}%
6277   \let\bbl@OL@p@enumiii\p@enumiii
6278   \def\p@enumiii{\p@enumii}\theenumii{}\{}\{}\}
6279 }{<Footnote changes>}
6280 \IfBabelLayout{footnotes}%
6281 {\let\bbl@OL@footnote\footnote
6282  \BabelFootnote\footnote\languagename{}\{}\}%
6283  \BabelFootnote\localfootnote\languagename{}\{}\}%
6284  \BabelFootnote\mainfootnote{}\{}\{}\}
6285  {}

```

Some \TeX macros use internally the math mode for text formatting. They have very little in common and are grouped here, as a single option.

```

6286 \IfBabelLayout{extras}%
6287   {\let\bbl@OL@underline\underline
6288    \bbl@sreplace\underline{$\@@underline}{\bbl@nextfake$\@@underline}%
6289    \let\bbl@OL@LaTeX2e\LaTeX2e
6290    \DeclareRobustCommand{\LaTeXe}{\mbox{\m@th
6291     \if b\expandafter\@car\@series\@nil\boldmath\fi
6292     \babelsublr}%
6293     \LaTeX\kern.15em2\bbl@nextfake$_{\textstyle\varepsilon}}}}
6294   {}
6295 \end{luatex}

```

12.11 Lua: transforms

After declaring the table containing the patterns with their replacements, we define some auxiliary functions: `str_to_nodes` converts the string returned by a function to a node list, taking the node at base as a model (font, language, etc.); `fetch_word` fetches a series of glyphs and discretionaries, which pattern is matched against (if there is a match, it is called again before trying other patterns, and this is very likely the main bottleneck).

`post_hyphenate_replace` is the callback applied after `lang.hyphenate`. This means the automatic hyphenation points are known. As empty captures return a byte position (as explained in the `luatex` manual), we must convert it to a utf8 position. With `first`, the last byte can be the leading byte in a utf8 sequence, so we just remove it and add 1 to the resulting length. With `last` we must take into account the capture position points to the next character. Here `word_head` points to the starting node of the text to be matched.

```

6296 (*transforms)
6297 Babel.linebreaking.replacements = {}
6298 Babel.linebreaking.replacements[0] = {} -- pre
6299 Babel.linebreaking.replacements[1] = {} -- post
6300
6301 -- Discretionaries contain strings as nodes
6302 function Babel.str_to_nodes(fn, matches, base)
6303   local n, head, last
6304   if fn == nil then return nil end
6305   for s in string.utfvalues(fn(matches)) do
6306     if base.id == 7 then
6307       base = base.replace
6308     end
6309     n = node.copy(base)
6310     n.char = s
6311     if not head then
6312       head = n
6313     else
6314       last.next = n
6315     end
6316     last = n
6317   end
6318   return head
6319 end
6320
6321 Babel.fetch_subtext = {}
6322
6323 Babel.ignore_pre_char = function(node)
6324   return (node.lang == Babel.nohyphenation)
6325 end
6326
6327 -- Merging both functions doesn't seem feasible, because there are too
6328 -- many differences.
6329 Babel.fetch_subtext[0] = function(head)
6330   local word_string = ''
6331   local word_nodes = {}
6332   local lang
6333   local item = head
6334   local inmath = false

```

```

6335
6336 while item do
6337
6338     if item.id == 11 then
6339         inmath = (item.subtype == 0)
6340     end
6341
6342     if inmath then
6343         -- pass
6344
6345     elseif item.id == 29 then
6346         local locale = node.get_attribute(item, Babel.attr_locale)
6347
6348         if lang == locale or lang == nil then
6349             lang = lang or locale
6350             if Babel.ignore_pre_char(item) then
6351                 word_string = word_string .. Babel.us_char
6352             else
6353                 word_string = word_string .. unicode.utf8.char(item.char)
6354             end
6355             word_nodes[#word_nodes+1] = item
6356         else
6357             break
6358         end
6359
6360     elseif item.id == 12 and item.subtype == 13 then
6361         word_string = word_string .. ' '
6362         word_nodes[#word_nodes+1] = item
6363
6364         -- Ignore leading unrecognized nodes, too.
6365     elseif word_string ~= '' then
6366         word_string = word_string .. Babel.us_char
6367         word_nodes[#word_nodes+1] = item -- Will be ignored
6368     end
6369
6370     item = item.next
6371 end
6372
6373 -- Here and above we remove some trailing chars but not the
6374 -- corresponding nodes. But they aren't accessed.
6375 if word_string:sub(-1) == ' ' then
6376     word_string = word_string:sub(1,-2)
6377 end
6378 word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
6379 return word_string, word_nodes, item, lang
6380 end
6381
6382 Babel.fetch_subtext[1] = function(head)
6383     local word_string = ''
6384     local word_nodes = {}
6385     local lang
6386     local item = head
6387     local inmath = false
6388
6389     while item do
6390
6391         if item.id == 11 then
6392             inmath = (item.subtype == 0)
6393         end
6394
6395         if inmath then
6396             -- pass
6397

```

```

6398     elseif item.id == 29 then
6399         if item.lang == lang or lang == nil then
6400             if (item.char ~= 124) and (item.char ~= 61) then -- not =, not |
6401                 lang = lang or item.lang
6402                 word_string = word_string .. unicode.utf8.char(item.char)
6403                 word_nodes[#word_nodes+1] = item
6404             end
6405         else
6406             break
6407         end
6408
6409     elseif item.id == 7 and item.subtype == 2 then
6410         word_string = word_string .. '='
6411         word_nodes[#word_nodes+1] = item
6412
6413     elseif item.id == 7 and item.subtype == 3 then
6414         word_string = word_string .. '|'
6415         word_nodes[#word_nodes+1] = item
6416
6417     -- (1) Go to next word if nothing was found, and (2) implicitly
6418     -- remove leading USs.
6419     elseif word_string == '' then
6420         -- pass
6421
6422     -- This is the responsible for splitting by words.
6423     elseif (item.id == 12 and item.subtype == 13) then
6424         break
6425
6426     else
6427         word_string = word_string .. Babel.us_char
6428         word_nodes[#word_nodes+1] = item -- Will be ignored
6429     end
6430
6431     item = item.next
6432 end
6433
6434 word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
6435 return word_string, word_nodes, item, lang
6436 end
6437
6438 function Babel.pre_hyphenate_replace(head)
6439     Babel.hyphenate_replace(head, 0)
6440 end
6441
6442 function Babel.post_hyphenate_replace(head)
6443     Babel.hyphenate_replace(head, 1)
6444 end
6445
6446 Babel.us_char = string.char(31)
6447
6448 function Babel.hyphenate_replace(head, mode)
6449     local u = unicode.utf8
6450     local lbkr = Babel.linebreaking.replacements[mode]
6451
6452     local word_head = head
6453
6454     while true do -- for each subtext block
6455
6456         local w, w_nodes, nw, lang = Babel.fetch_subtext[mode](word_head)
6457
6458         if Babel.debug then
6459             print()
6460             print((mode == 0) and '@@@<' or '@@@>', w)

```

```

6461     end
6462
6463     if nw == nil and w == '' then break end
6464
6465     if not lang then goto next end
6466     if not lbkr[lang] then goto next end
6467
6468     -- For each saved (pre|post)hyphenation. TODO. Reconsider how
6469     -- loops are nested.
6470     for k=1, #lbkr[lang] do
6471         local p = lbkr[lang][k].pattern
6472         local r = lbkr[lang][k].replace
6473         local attr = lbkr[lang][k].attr or -1
6474
6475         if Babel.debug then
6476             print('*****', p, mode)
6477         end
6478
6479         -- This variable is set in some cases below to the first *byte*
6480         -- after the match, either as found by u.match (faster) or the
6481         -- computed position based on sc if w has changed.
6482         local last_match = 0
6483         local step = 0
6484
6485         -- For every match.
6486         while true do
6487             if Babel.debug then
6488                 print('====')
6489             end
6490             local new -- used when inserting and removing nodes
6491
6492             local matches = { u.match(w, p, last_match) }
6493
6494             if #matches < 2 then break end
6495
6496             -- Get and remove empty captures (with ()'s, which return a
6497             -- number with the position), and keep actual captures
6498             -- (from (...)), if any, in matches.
6499             local first = table.remove(matches, 1)
6500             local last = table.remove(matches, #matches)
6501             -- Non re-fetched substrings may contain \31, which separates
6502             -- subsubstrings.
6503             if string.find(w:sub(first, last-1), Babel.us_char) then break end
6504
6505             local save_last = last -- with A()BC()D, points to D
6506
6507             -- Fix offsets, from bytes to unicode. Explained above.
6508             first = u.len(w:sub(1, first-1)) + 1
6509             last = u.len(w:sub(1, last-1)) -- now last points to C
6510
6511             -- This loop stores in a small table the nodes
6512             -- corresponding to the pattern. Used by 'data' to provide a
6513             -- predictable behavior with 'insert' (w_nodes is modified on
6514             -- the fly), and also access to 'remove'd nodes.
6515             local sc = first-1 -- Used below, too
6516             local data_nodes = {}
6517
6518             local enabled = true
6519             for q = 1, last-first+1 do
6520                 data_nodes[q] = w_nodes[sc+q]
6521                 if enabled
6522                     and attr > -1
6523                     and not node.has_attribute(data_nodes[q], attr)

```

```

6524         then
6525             enabled = false
6526         end
6527     end
6528
6529     -- This loop traverses the matched substring and takes the
6530     -- corresponding action stored in the replacement list.
6531     -- sc = the position in substr nodes / string
6532     -- rc = the replacement table index
6533     local rc = 0
6534
6535     while rc < last-first+1 do -- for each replacement
6536         if Babel.debug then
6537             print('.....', rc + 1)
6538         end
6539         sc = sc + 1
6540         rc = rc + 1
6541
6542         if Babel.debug then
6543             Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
6544             local ss = ''
6545             for itt in node.traverse(head) do
6546                 if itt.id == 29 then
6547                     ss = ss .. unicode.utf8.char(itt.char)
6548                 else
6549                     ss = ss .. '{' .. itt.id .. '}'
6550                 end
6551             end
6552             print('*****', ss)
6553
6554         end
6555
6556         local crep = r[rc]
6557         local item = w_nodes[sc]
6558         local item_base = item
6559         local placeholder = Babel.us_char
6560         local d
6561
6562         if crep and crep.data then
6563             item_base = data_nodes[crep.data]
6564         end
6565
6566         if crep then
6567             step = crep.step or 0
6568         end
6569
6570         if (not enabled) or (crep and next(crep) == nil) then -- = {}
6571             last_match = save_last -- Optimization
6572             goto next
6573
6574         elseif crep == nil or crep.remove then
6575             node.remove(head, item)
6576             table.remove(w_nodes, sc)
6577             w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
6578             sc = sc - 1 -- Nothing has been inserted.
6579             last_match = utf8.offset(w, sc+1+step)
6580             goto next
6581
6582         elseif crep and crep.kashida then -- Experimental
6583             node.set_attribute(item,
6584                 Babel.attr_kashida,
6585                 crep.kashida)
6586             last_match = utf8.offset(w, sc+1+step)

```

```

6587         goto next
6588
6589     elseif crep and crep.string then
6590         local str = crep.string(matches)
6591         if str == '' then -- Gather with nil
6592             node.remove(head, item)
6593             table.remove(w_nodes, sc)
6594             w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
6595             sc = sc - 1 -- Nothing has been inserted.
6596         else
6597             local loop_first = true
6598             for s in string.utfvalues(str) do
6599                 d = node.copy(item_base)
6600                 d.char = s
6601                 if loop_first then
6602                     loop_first = false
6603                     head, new = node.insert_before(head, item, d)
6604                     if sc == 1 then
6605                         word_head = head
6606                     end
6607                     w_nodes[sc] = d
6608                     w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc+1)
6609                 else
6610                     sc = sc + 1
6611                     head, new = node.insert_before(head, item, d)
6612                     table.insert(w_nodes, sc, new)
6613                     w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc)
6614                 end
6615                 if Babel.debug then
6616                     print('.....', 'str')
6617                     Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
6618                 end
6619             end -- for
6620             node.remove(head, item)
6621         end -- if ''
6622         last_match = utf8.offset(w, sc+1+step)
6623         goto next
6624
6625     elseif mode == 1 and crep and (crep.pre or crep.no or crep.post) then
6626         d = node.new(7, 0) -- (disc, discretionary)
6627         d.pre = Babel.str_to_nodes(crep.pre, matches, item_base)
6628         d.post = Babel.str_to_nodes(crep.post, matches, item_base)
6629         d.replace = Babel.str_to_nodes(crep.no, matches, item_base)
6630         d.attr = item_base.attr
6631         if crep.pre == nil then -- TeXbook p96
6632             d.penalty = crep.penalty or tex.hyphenpenalty
6633         else
6634             d.penalty = crep.penalty or tex.exhyphenpenalty
6635         end
6636         placeholder = '|'
6637         head, new = node.insert_before(head, item, d)
6638
6639     elseif mode == 0 and crep and (crep.pre or crep.no or crep.post) then
6640         -- ERROR
6641
6642     elseif crep and crep.penalty then
6643         d = node.new(14, 0) -- (penalty, userpenalty)
6644         d.attr = item_base.attr
6645         d.penalty = crep.penalty
6646         head, new = node.insert_before(head, item, d)
6647
6648     elseif crep and crep.space then
6649         -- 655360 = 10 pt = 10 * 65536 sp

```



```

6650         d = node.new(12, 13)      -- (glue, spaceskip)
6651         local quad = font.getfont(item_base.font).size or 655360
6652         node.setglue(d, crep.space[1] * quad,
6653                     crep.space[2] * quad,
6654                     crep.space[3] * quad)
6655         if mode == 0 then
6656             placeholder = ' '
6657         end
6658         head, new = node.insert_before(head, item, d)
6659
6660     elseif crep and crep.spacefactor then
6661         d = node.new(12, 13)      -- (glue, spaceskip)
6662         local base_font = font.getfont(item_base.font)
6663         node.setglue(d,
6664                     crep.spacefactor[1] * base_font.parameters['space'],
6665                     crep.spacefactor[2] * base_font.parameters['space_stretch'],
6666                     crep.spacefactor[3] * base_font.parameters['space_shrink'])
6667         if mode == 0 then
6668             placeholder = ' '
6669         end
6670         head, new = node.insert_before(head, item, d)
6671
6672     elseif mode == 0 and crep and crep.space then
6673         -- ERROR
6674
6675     end -- ie replacement cases
6676
6677     -- Shared by disc, space and penalty.
6678     if sc == 1 then
6679         word_head = head
6680     end
6681     if crep.insert then
6682         w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc)
6683         table.insert(w_nodes, sc, new)
6684         last = last + 1
6685     else
6686         w_nodes[sc] = d
6687         node.remove(head, item)
6688         w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc+1)
6689     end
6690
6691     last_match = utf8.offset(w, sc+1+step)
6692
6693     ::next::
6694
6695     end -- for each replacement
6696
6697     if Babel.debug then
6698         print('.....', '/')
6699         Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
6700     end
6701
6702     end -- for match
6703
6704     end -- for patterns
6705
6706     ::next::
6707     word_head = nw
6708     end -- for substring
6709     return head
6710 end
6711
6712 -- This table stores capture maps, numbered consecutively

```

```

6713 Babel.capture_maps = {}
6714
6715 -- The following functions belong to the next macro
6716 function Babel.capture_func(key, cap)
6717   local ret = "[" .. cap:gsub('{{[0-9]}}', "]]..m[%1]..[" .. "]"
6718   local cnt
6719   local u = unicode.utf8
6720   ret, cnt = ret:gsub('{{[0-9]}|([^\]|+)|(.-)}', Babel.capture_func_map)
6721   if cnt == 0 then
6722     ret = u.gsub(ret, '{{(%x%x%x%x+)}',
6723       function (n)
6724         return u.char(tonumber(n, 16))
6725       end)
6726   end
6727   ret = ret:gsub("%[%[%]]%.", '')
6728   ret = ret:gsub("%.%.%.%[%[%]]%", '')
6729   return key .. "[[=function(m) return ]] .. ret .. [[ end]]
6730 end
6731
6732 function Babel.capt_map(from, mapno)
6733   return Babel.capture_maps[mapno][from] or from
6734 end
6735
6736 -- Handle the {n|abc|ABC} syntax in captures
6737 function Babel.capture_func_map(capno, from, to)
6738   local u = unicode.utf8
6739   from = u.gsub(from, '{{(%x%x%x%x+)}',
6740     function (n)
6741       return u.char(tonumber(n, 16))
6742     end)
6743   to = u.gsub(to, '{{(%x%x%x%x+)}',
6744     function (n)
6745       return u.char(tonumber(n, 16))
6746     end)
6747   local froms = {}
6748   for s in string.utfcharacters(from) do
6749     table.insert(froms, s)
6750   end
6751   local cnt = 1
6752   table.insert(Babel.capture_maps, {})
6753   local mlen = table.getn(Babel.capture_maps)
6754   for s in string.utfcharacters(to) do
6755     Babel.capture_maps[mlen][froms[cnt]] = s
6756     cnt = cnt + 1
6757   end
6758   return "]]..Babel.capt_map(m[" .. capno .. "], " ..
6759     (mlen) .. ").." .. "["
6760 end
6761
6762 -- Create/Extend reversed sorted list of kashida weights:
6763 function Babel.capture_kashida(key, wt)
6764   wt = tonumber(wt)
6765   if Babel.kashida_wts then
6766     for p, q in ipairs(Babel.kashida_wts) do
6767       if wt == q then
6768         break
6769       elseif wt > q then
6770         table.insert(Babel.kashida_wts, p, wt)
6771         break
6772       elseif table.getn(Babel.kashida_wts) == p then
6773         table.insert(Babel.kashida_wts, wt)
6774       end
6775     end

```

```

6776 else
6777     Babel.kashida_wts = { wt }
6778 end
6779 return 'kashida = ' .. wt
6780 end
6781 </transforms>

```

12.12 Lua: Auto bidi with basic and basic-r

The file `babel-data-bidi.lua` currently only contains data. It is a large and boring file and it is not shown here (see the generated file), but here is a sample:

```

[0x25]={d='et'},
[0x26]={d='on'},
[0x27]={d='on'},
[0x28]={d='on', m=0x29},
[0x29]={d='on', m=0x28},
[0x2A]={d='on'},
[0x2B]={d='es'},
[0x2C]={d='cs'},

```

For the meaning of these codes, see the Unicode standard.

Now the `basic-r` bidi mode. One of the aims is to implement a fast and simple bidi algorithm, with a single loop. I managed to do it for R texts, with a second smaller loop for a special case. The code is still somewhat chaotic, but its behavior is essentially correct. I cannot resist copying the following text from Emacs `bidi.c` (which also attempts to implement the bidi algorithm with a single loop):

Arrrrgh!! The UAX#9 algorithm is too deeply entrenched in the assumption of batch-style processing [...]. May the fleas of a thousand camels infest the armpits of those who design supposedly general-purpose algorithms by looking at their own implementations, and fail to consider other possible implementations!

Well, it took me some time to guess what the batch rules in UAX#9 actually mean (in other word, *what* they do and *why*, and not only *how*), but I think (or I hope) I've managed to understand them. In some sense, there are two bidi modes, one for numbers, and the other for text. Furthermore, setting just the direction in R text is not enough, because there are actually *two* R modes (set explicitly in Unicode with RLM and ALM). In `babel` the `dir` is set by a higher protocol based on the language/script, which in turn sets the correct `dir` (<l>, <r> or <al>).

From UAX#9: “Where available, markup should be used instead of the explicit formatting characters”. So, this simple version just ignores formatting characters. Actually, most of that annex is devoted to how to handle them.

BD14-BD16 are not implemented. Unicode (and the W3C) are making a great effort to deal with some special problematic cases in “streamed” plain text. I don’t think this is the way to go – particular issues should be fixed by a high level interface taking into account the needs of the document. And here is where `luatex` excels, because everything related to bidi writing is under our control.

```

6782 <*basic-r>
6783 Babel = Babel or {}
6784
6785 Babel.bidi_enabled = true
6786
6787 require('babel-data-bidi.lua')
6788
6789 local characters = Babel.characters
6790 local ranges = Babel.ranges
6791
6792 local DIR = node.id("dir")
6793
6794 local function dir_mark(head, from, to, outer)
6795     dir = (outer == 'r') and 'TLT' or 'TRT' -- ie, reverse
6796     local d = node.new(DIR)
6797     d.dir = '+' .. dir
6798     node.insert_before(head, from, d)
6799     d = node.new(DIR)

```

```

6800 d.dir = '-' .. dir
6801 node.insert_after(head, to, d)
6802 end
6803
6804 function Babel.bidi(head, ispar)
6805   local first_n, last_n          -- first and last char with nums
6806   local last_es                  -- an auxiliary 'last' used with nums
6807   local first_d, last_d          -- first and last char in L/R block
6808   local dir, dir_real

```

Next also depends on script/lang (<al>/<r>). To be set by babel. tex.pardir is dangerous, could be (re)set but it should be changed only in vmode. There are two strong's – strong = l/al/r and strong_lr = l/r (there must be a better way):

```

6809   local strong = ('TRT' == tex.pardir) and 'r' or 'l'
6810   local strong_lr = (strong == 'l') and 'l' or 'r'
6811   local outer = strong
6812
6813   local new_dir = false
6814   local first_dir = false
6815   local inmath = false
6816
6817   local last_lr
6818
6819   local type_n = ''
6820
6821   for item in node.traverse(head) do
6822
6823     -- three cases: glyph, dir, otherwise
6824     if item.id == node.id'glyph'
6825       or (item.id == 7 and item.subtype == 2) then
6826
6827       local itemchar
6828       if item.id == 7 and item.subtype == 2 then
6829         itemchar = item.replace.char
6830       else
6831         itemchar = item.char
6832       end
6833       local chardata = characters[itemchar]
6834       dir = chardata and chardata.d or nil
6835       if not dir then
6836         for nn, et in ipairs(ranges) do
6837           if itemchar < et[1] then
6838             break
6839           elseif itemchar <= et[2] then
6840             dir = et[3]
6841             break
6842           end
6843         end
6844       end
6845       dir = dir or 'l'
6846       if inmath then dir = ('TRT' == tex.mathdir) and 'r' or 'l' end

```

Next is based on the assumption babel sets the language AND switches the script with its dir. We treat a language block as a separate Unicode sequence. The following piece of code is executed at the first glyph after a 'dir' node. We don't know the current language until then. This is not exactly true, as the math mode may insert explicit dirs in the node list, so, for the moment there is a hack by brute force (just above).

```

6847   if new_dir then
6848     attr_dir = 0
6849     for at in node.traverse(item.attr) do
6850       if at.number == Babel.attr_dir then
6851         attr_dir = at.value % 3
6852       end
6853     end

```

```

6854     if attr_dir == 1 then
6855         strong = 'r'
6856     elseif attr_dir == 2 then
6857         strong = 'al'
6858     else
6859         strong = 'l'
6860     end
6861     strong_lr = (strong == 'l') and 'l' or 'r'
6862     outer = strong_lr
6863     new_dir = false
6864 end
6865
6866     if dir == 'nsm' then dir = strong end          -- W1

```

Numbers. The dual <al>/<r> system for R is somewhat cumbersome.

```

6867     dir_real = dir          -- We need dir_real to set strong below
6868     if dir == 'al' then dir = 'r' end -- W3

```

By W2, there are no <en> <et> <es> if strong == <al>, only <an>. Therefore, there are not <et en> nor <en et>, W5 can be ignored, and W6 applied:

```

6869     if strong == 'al' then
6870         if dir == 'en' then dir = 'an' end          -- W2
6871         if dir == 'et' or dir == 'es' then dir = 'on' end -- W6
6872         strong_lr = 'r'          -- W3
6873     end

```

Once finished the basic setup for glyphs, consider the two other cases: dir node and the rest.

```

6874     elseif item.id == node.id'dir' and not inmath then
6875         new_dir = true
6876         dir = nil
6877     elseif item.id == node.id'math' then
6878         inmath = (item.subtype == 0)
6879     else
6880         dir = nil          -- Not a char
6881     end

```

Numbers in R mode. A sequence of <en>, <et>, <an>, <es> and <cs> is typeset (with some rules) in L mode. We store the starting and ending points, and only when anything different is found (including nil, ie, a non-char), the textdir is set. This means you cannot insert, say, a whatsit, but this is what I would expect (with luacolor you may colorize some digits). Anyway, this behavior could be changed with a switch in the future. Note in the first branch only <an> is relevant if <al>.

```

6882     if dir == 'en' or dir == 'an' or dir == 'et' then
6883         if dir ~= 'et' then
6884             type_n = dir
6885         end
6886         first_n = first_n or item
6887         last_n = last_es or item
6888         last_es = nil
6889     elseif dir == 'es' and last_n then -- W3+W6
6890         last_es = item
6891     elseif dir == 'cs' then          -- it's right - do nothing
6892     elseif first_n then -- & if dir = any but en, et, an, es, cs, inc nil
6893         if strong_lr == 'r' and type_n ~= '' then
6894             dir_mark(head, first_n, last_n, 'r')
6895         elseif strong_lr == 'l' and first_d and type_n == 'an' then
6896             dir_mark(head, first_n, last_n, 'r')
6897             dir_mark(head, first_d, last_d, outer)
6898             first_d, last_d = nil, nil
6899         elseif strong_lr == 'l' and type_n ~= '' then
6900             last_d = last_n
6901         end
6902         type_n = ''
6903         first_n, last_n = nil, nil
6904     end

```

R text in L, or L text in R. Order of dir_ mark's are relevant: d goes outside n, and therefore it's emitted after. See dir_mark to understand why (but is the nesting actually necessary or is a flat dir structure enough?). Only L, R (and AL) chars are taken into account – everything else, including spaces, whatsits, etc., are ignored:

```

6905   if dir == 'l' or dir == 'r' then
6906       if dir ~= outer then
6907           first_d = first_d or item
6908           last_d = item
6909       elseif first_d and dir ~= strong_lr then
6910           dir_mark(head, first_d, last_d, outer)
6911           first_d, last_d = nil, nil
6912       end
6913   end

```

Mirroring. Each chunk of text in a certain language is considered a “closed” sequence. If <r on r> and <l on l>, it's clearly <r> and <l>, resp'tly, but with other combinations depends on outer. From all these, we select only those resolving <on> → <r>. At the beginning (when last_lr is nil) of an R text, they are mirrored directly.

TODO - numbers in R mode are processed. It doesn't hurt, but should not be done.

```

6914   if dir and not last_lr and dir ~= 'l' and outer == 'r' then
6915       item.char = characters[item.char] and
6916           characters[item.char].m or item.char
6917   elseif (dir or new_dir) and last_lr ~= item then
6918       local mir = outer .. strong_lr .. (dir or outer)
6919       if mir == 'rrr' or mir == 'lrr' or mir == 'rrl' or mir == 'rlr' then
6920           for ch in node.traverse(node.next(last_lr)) do
6921               if ch == item then break end
6922               if ch.id == node.id'glyph' and characters[ch.char] then
6923                   ch.char = characters[ch.char].m or ch.char
6924               end
6925           end
6926       end
6927   end

```

Save some values for the next iteration. If the current node is 'dir', open a new sequence. Since dir could be changed, strong is set with its real value (dir_real).

```

6928   if dir == 'l' or dir == 'r' then
6929       last_lr = item
6930       strong = dir_real           -- Don't search back - best save now
6931       strong_lr = (strong == 'l') and 'l' or 'r'
6932   elseif new_dir then
6933       last_lr = nil
6934   end
6935 end

```

Mirror the last chars if they are no directed. And make sure any open block is closed, too.

```

6936   if last_lr and outer == 'r' then
6937       for ch in node.traverse_id(node.id'glyph', node.next(last_lr)) do
6938           if characters[ch.char] then
6939               ch.char = characters[ch.char].m or ch.char
6940           end
6941       end
6942   end
6943   if first_n then
6944       dir_mark(head, first_n, last_n, outer)
6945   end
6946   if first_d then
6947       dir_mark(head, first_d, last_d, outer)
6948   end

```

In boxes, the dir node could be added before the original head, so the actual head is the previous node.

```

6949   return node.prev(head) or head

```

```

6950 end
6951 \</basic-r>

And here the Lua code for bidi=basic:

6952 \<*basic>
6953 Babel = Babel or {}
6954
6955 -- eg, Babel.fontmap[1][<prefontid>]=<dirfontid>
6956
6957 Babel.fontmap = Babel.fontmap or {}
6958 Babel.fontmap[0] = {} -- l
6959 Babel.fontmap[1] = {} -- r
6960 Babel.fontmap[2] = {} -- al/an
6961
6962 Babel.bidi_enabled = true
6963 Babel.mirroring_enabled = true
6964
6965 require('babel-data-bidi.lua')
6966
6967 local characters = Babel.characters
6968 local ranges = Babel.ranges
6969
6970 local DIR = node.id('dir')
6971 local GLYPH = node.id('glyph')
6972
6973 local function insert_implicit(head, state, outer)
6974   local new_state = state
6975   if state.sim and state.eim and state.sim ~= state.eim then
6976     dir = ((outer == 'r') and 'TLT' or 'TRT') -- ie, reverse
6977     local d = node.new(DIR)
6978     d.dir = '+' .. dir
6979     node.insert_before(head, state.sim, d)
6980     local d = node.new(DIR)
6981     d.dir = '-' .. dir
6982     node.insert_after(head, state.eim, d)
6983   end
6984   new_state.sim, new_state.eim = nil, nil
6985   return head, new_state
6986 end
6987
6988 local function insert_numeric(head, state)
6989   local new
6990   local new_state = state
6991   if state.san and state.ean and state.san ~= state.ean then
6992     local d = node.new(DIR)
6993     d.dir = '+TLT'
6994     _, new = node.insert_before(head, state.san, d)
6995     if state.san == state.sim then state.sim = new end
6996     local d = node.new(DIR)
6997     d.dir = '-TLT'
6998     _, new = node.insert_after(head, state.ean, d)
6999     if state.ean == state.eim then state.eim = new end
7000   end
7001   new_state.san, new_state.ean = nil, nil
7002   return head, new_state
7003 end
7004
7005 -- TODO - \hbox with an explicit dir can lead to wrong results
7006 -- <R \hbox dir TLT{<R>}> and <L \hbox dir TRT{<L>}>. A small attempt
7007 -- was s made to improve the situation, but the problem is the 3-dir
7008 -- model in babel/Unicode and the 2-dir model in LuaTeX don't fit
7009 -- well.
7010

```

```

7011 function Babel.bidi(head, ispar, hdir)
7012   local d -- d is used mainly for computations in a loop
7013   local prev_d = ''
7014   local new_d = false
7015
7016   local nodes = {}
7017   local outer_first = nil
7018   local inmath = false
7019
7020   local glue_d = nil
7021   local glue_i = nil
7022
7023   local has_en = false
7024   local first_et = nil
7025
7026   local ATDIR = Babel.attr_dir
7027
7028   local save_outer
7029   local temp = node.get_attribute(head, ATDIR)
7030   if temp then
7031     temp = temp % 3
7032     save_outer = (temp == 0 and 'l') or
7033                 (temp == 1 and 'r') or
7034                 (temp == 2 and 'al')
7035   elseif ispar then -- Or error? Shouldn't happen
7036     save_outer = ('TRT' == tex.pardir) and 'r' or 'l'
7037   else -- Or error? Shouldn't happen
7038     save_outer = ('TRT' == hdir) and 'r' or 'l'
7039   end
7040   -- when the callback is called, we are just _after_ the box,
7041   -- and the textdir is that of the surrounding text
7042   -- if not ispar and hdir ~= tex.textdir then
7043   --   save_outer = ('TRT' == hdir) and 'r' or 'l'
7044   -- end
7045   local outer = save_outer
7046   local last = outer
7047   -- 'al' is only taken into account in the first, current loop
7048   if save_outer == 'al' then save_outer = 'r' end
7049
7050   local fontmap = Babel.fontmap
7051
7052   for item in node.traverse(head) do
7053
7054     -- In what follows, #node is the last (previous) node, because the
7055     -- current one is not added until we start processing the neutrals.
7056
7057     -- three cases: glyph, dir, otherwise
7058     if item.id == GLYPH
7059       or (item.id == 7 and item.subtype == 2) then
7060
7061       local d_font = nil
7062       local item_r
7063       if item.id == 7 and item.subtype == 2 then
7064         item_r = item.replace -- automatic discs have just 1 glyph
7065       else
7066         item_r = item
7067       end
7068       local chardata = characters[item_r.char]
7069       d = chardata and chardata.d or nil
7070       if not d or d == 'nsm' then
7071         for nn, et in ipairs(ranges) do
7072           if item_r.char < et[1] then
7073             break

```



```

7074         elseif item_r.char <= et[2] then
7075             if not d then d = et[3]
7076             elseif d == 'nsm' then d_font = et[3]
7077             end
7078             break
7079         end
7080     end
7081 end
7082 d = d or 'l'
7083
7084 -- A short 'pause' in bidi for mapfont
7085 d_font = d_font or d
7086 d_font = (d_font == 'l' and 0) or
7087           (d_font == 'nsm' and 0) or
7088           (d_font == 'r' and 1) or
7089           (d_font == 'al' and 2) or
7090           (d_font == 'an' and 2) or nil
7091 if d_font and fontmap and fontmap[d_font][item_r.font] then
7092     item_r.font = fontmap[d_font][item_r.font]
7093 end
7094
7095 if new_d then
7096     table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})
7097     if inmath then
7098         attr_d = 0
7099     else
7100         attr_d = node.get_attribute(item, ATDIR)
7101         attr_d = attr_d % 3
7102     end
7103     if attr_d == 1 then
7104         outer_first = 'r'
7105         last = 'r'
7106     elseif attr_d == 2 then
7107         outer_first = 'r'
7108         last = 'al'
7109     else
7110         outer_first = 'l'
7111         last = 'l'
7112     end
7113     outer = last
7114     has_en = false
7115     first_et = nil
7116     new_d = false
7117 end
7118
7119 if glue_d then
7120     if (d == 'l' and 'l' or 'r') ~= glue_d then
7121         table.insert(nodes, {glue_i, 'on', nil})
7122     end
7123     glue_d = nil
7124     glue_i = nil
7125 end
7126
7127 elseif item.id == DIR then
7128     d = nil
7129     if head ~= item then new_d = true end
7130
7131 elseif item.id == node.id'glue' and item.subtype == 13 then
7132     glue_d = d
7133     glue_i = item
7134     d = nil
7135
7136 elseif item.id == node.id'math' then

```

```

7137     inmath = (item.subtype == 0)
7138
7139 else
7140     d = nil
7141 end
7142
7143 -- AL <= EN/ET/ES      -- W2 + W3 + W6
7144 if last == 'al' and d == 'en' then
7145     d = 'an'           -- W3
7146 elseif last == 'al' and (d == 'et' or d == 'es') then
7147     d = 'on'           -- W6
7148 end
7149
7150 -- EN + CS/ES + EN      -- W4
7151 if d == 'en' and #nodes >= 2 then
7152     if (nodes[#nodes][2] == 'es' or nodes[#nodes][2] == 'cs')
7153         and nodes[#nodes-1][2] == 'en' then
7154         nodes[#nodes][2] = 'en'
7155     end
7156 end
7157
7158 -- AN + CS + AN          -- W4 too, because uax9 mixes both cases
7159 if d == 'an' and #nodes >= 2 then
7160     if (nodes[#nodes][2] == 'cs')
7161         and nodes[#nodes-1][2] == 'an' then
7162         nodes[#nodes][2] = 'an'
7163     end
7164 end
7165
7166 -- ET/EN                  -- W5 + W7->l / W6->on
7167 if d == 'et' then
7168     first_et = first_et or (#nodes + 1)
7169 elseif d == 'en' then
7170     has_en = true
7171     first_et = first_et or (#nodes + 1)
7172 elseif first_et then      -- d may be nil here !
7173     if has_en then
7174         if last == 'l' then
7175             temp = 'l'    -- W7
7176         else
7177             temp = 'en'   -- W5
7178         end
7179     else
7180         temp = 'on'      -- W6
7181     end
7182     for e = first_et, #nodes do
7183         if nodes[e][1].id == GLYPH then nodes[e][2] = temp end
7184     end
7185     first_et = nil
7186     has_en = false
7187 end
7188
7189 -- Force mathdir in math if ON (currently works as expected only
7190 -- with 'l')
7191 if inmath and d == 'on' then
7192     d = ('TRT' == tex.mathdir) and 'r' or 'l'
7193 end
7194
7195 if d then
7196     if d == 'al' then
7197         d = 'r'
7198         last = 'al'
7199     elseif d == 'l' or d == 'r' then

```

```

7200         last = d
7201     end
7202     prev_d = d
7203     table.insert(nodes, {item, d, outer_first})
7204 end
7205
7206     outer_first = nil
7207
7208 end
7209
7210 -- TODO -- repeated here in case EN/ET is the last node. Find a
7211 -- better way of doing things:
7212 if first_et then      -- dir may be nil here !
7213     if has_en then
7214         if last == 'l' then
7215             temp = 'l'      -- W7
7216         else
7217             temp = 'en'     -- W5
7218         end
7219     else
7220         temp = 'on'        -- W6
7221     end
7222     for e = first_et, #nodes do
7223         if nodes[e][1].id == GLYPH then nodes[e][2] = temp end
7224     end
7225 end
7226
7227 -- dummy node, to close things
7228 table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})
7229
7230 ----- NEUTRAL -----
7231
7232 outer = save_outer
7233 last = outer
7234
7235 local first_on = nil
7236
7237 for q = 1, #nodes do
7238     local item
7239
7240     local outer_first = nodes[q][3]
7241     outer = outer_first or outer
7242     last = outer_first or last
7243
7244     local d = nodes[q][2]
7245     if d == 'an' or d == 'en' then d = 'r' end
7246     if d == 'cs' or d == 'et' or d == 'es' then d = 'on' end --- W6
7247
7248     if d == 'on' then
7249         first_on = first_on or q
7250     elseif first_on then
7251         if last == d then
7252             temp = d
7253         else
7254             temp = outer
7255         end
7256         for r = first_on, q - 1 do
7257             nodes[r][2] = temp
7258             item = nodes[r][1]      -- MIRRORING
7259             if Babel.mirroring_enabled and item.id == GLYPH
7260                 and temp == 'r' and characters[item.char] then
7261                 local font_mode = ''
7262                 if font.fonts[item.font].properties then

```

```

7263         font_mode = font.fonts[item.font].properties.mode
7264     end
7265     if font_mode ~= 'harf' and font_mode ~= 'plug' then
7266         item.char = characters[item.char].m or item.char
7267     end
7268     end
7269 end
7270 first_on = nil
7271 end
7272
7273 if d == 'r' or d == 'l' then last = d end
7274 end
7275
7276 ----- IMPLICIT, REORDER -----
7277
7278 outer = save_outer
7279 last = outer
7280
7281 local state = {}
7282 state.has_r = false
7283
7284 for q = 1, #nodes do
7285
7286     local item = nodes[q][1]
7287
7288     outer = nodes[q][3] or outer
7289
7290     local d = nodes[q][2]
7291
7292     if d == 'nsm' then d = last end          -- W1
7293     if d == 'en' then d = 'an' end
7294     local isdir = (d == 'r' or d == 'l')
7295
7296     if outer == 'l' and d == 'an' then
7297         state.san = state.san or item
7298         state.ean = item
7299     elseif state.san then
7300         head, state = insert_numeric(head, state)
7301     end
7302
7303     if outer == 'l' then
7304         if d == 'an' or d == 'r' then      -- im -> implicit
7305             if d == 'r' then state.has_r = true end
7306             state.sim = state.sim or item
7307             state.eim = item
7308         elseif d == 'l' and state.sim and state.has_r then
7309             head, state = insert_implicit(head, state, outer)
7310         elseif d == 'l' then
7311             state.sim, state.eim, state.has_r = nil, nil, false
7312         end
7313     else
7314         if d == 'an' or d == 'l' then
7315             if nodes[q][3] then -- nil except after an explicit dir
7316                 state.sim = item -- so we move sim 'inside' the group
7317             else
7318                 state.sim = state.sim or item
7319             end
7320             state.eim = item
7321         elseif d == 'r' and state.sim then
7322             head, state = insert_implicit(head, state, outer)
7323         elseif d == 'r' then
7324             state.sim, state.eim = nil, nil
7325         end
7326     end
7327 end

```

```

7326     end
7327
7328     if isdir then
7329         last = d          -- Don't search back - best save now
7330     elseif d == 'on' and state.san then
7331         state.san = state.san or item
7332         state.ean = item
7333     end
7334
7335 end
7336
7337 return node.prev(head) or head
7338 end
7339 </basic>

```

13 Data for CJK

It is a boring file and it is not shown here (see the generated file), but here is a sample:

```

[0x0021]={c='ex'},
[0x0024]={c='pr'},
[0x0025]={c='po'},
[0x0028]={c='op'},
[0x0029]={c='cp'},
[0x002B]={c='pr'},

```

For the meaning of these codes, see the Unicode standard.

14 The ‘nil’ language

This ‘language’ does nothing, except setting the hyphenation patterns to nohyphenation.

For this language currently no special definitions are needed or available.

The macro `\LdfInit` takes care of preventing that this file is loaded more than once, checking the category code of the `@` sign, etc.

```

7340 <*nil>
7341 \ProvidesLanguage{nil}[<<date>>] <<version>> Nil language]
7342 \LdfInit{nil}{datenil}

```

When this file is read as an option, i.e. by the `\usepackage` command, nil could be an ‘unknown’ language in which case we have to make it known.

```

7343 \ifx\l@nil\@undefined
7344   \newlanguage\l@nil
7345   \@namedef{bbl@hyphendata@the\l@nil}{\{}}% Remove warning
7346   \let\bbl@elt\relax
7347   \edef\bbl@languages{% Add it to the list of languages
7348     \bbl@languages\bbl@elt{nil}{the\l@nil}{\{}}
7349 \fi

```

This macro is used to store the values of the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`.

```

7350 \providehyphenmins{\CurrentOption}{\m@ne\m@ne}

```

The next step consists of defining commands to switch to (and from) the ‘nil’ language.

```

\captionnil
\datenil
7351 \let\captionnil\@empty
7352 \let\datenil\@empty

```

There is no locale file for this pseudo-language, so the corresponding fields are defined here.

```

7353 \def\bbl@inidata@nil{%
7354   \bbl@elt{identification}{tag.ini}{und}%

```

```

7355 \bbl@elt{identification}{load.level}{0}%
7356 \bbl@elt{identification}{charset}{utf8}%
7357 \bbl@elt{identification}{version}{1.0}%
7358 \bbl@elt{identification}{date}{2022-05-16}%
7359 \bbl@elt{identification}{name.local}{nil}%
7360 \bbl@elt{identification}{name.english}{nil}%
7361 \bbl@elt{identification}{name.babel}{nil}%
7362 \bbl@elt{identification}{tag.bcp47}{und}%
7363 \bbl@elt{identification}{language.tag.bcp47}{und}%
7364 \bbl@elt{identification}{tag.opentype}{dflt}%
7365 \bbl@elt{identification}{script.name}{Latin}%
7366 \bbl@elt{identification}{script.tag.bcp47}{Latn}%
7367 \bbl@elt{identification}{script.tag.opentype}{DFLT}%
7368 \bbl@elt{identification}{level}{1}%
7369 \bbl@elt{identification}{encodings}{}%
7370 \bbl@elt{identification}{derivate}{no}}
7371 \@namedef{bbl@tbcpl@nil}{und}
7372 \@namedef{bbl@lbcpl@nil}{und}
7373 \@namedef{bbl@lotf@nil}{dflt}
7374 \@namedef{bbl@elname@nil}{nil}
7375 \@namedef{bbl@lname@nil}{nil}
7376 \@namedef{bbl@esname@nil}{Latin}
7377 \@namedef{bbl@sname@nil}{Latin}
7378 \@namedef{bbl@sbcpl@nil}{Latn}
7379 \@namedef{bbl@sotf@nil}{Latn}

```

The macro `\ldf@finish` takes care of looking for a configuration file, setting the main language to be switched on at `\begin{document}` and resetting the category code of `@` to its original value.

```

7380 \ldf@finish{nil}
7381 /nil

```

15 Calendars

The code for specific calendars are placed in the specific files, loaded when requested by an ini file in the identification section with `require.calendars`.

Start with function to compute the Julian day. It's based on the little library `calendar.js`, by John Walker, in the public domain.

```

7382 <(*Compute Julian day)> ≡
7383 \def\bbl@fpmmod#1#2{(#1-#2*floor(#1/#2))}
7384 \def\bbl@cs@gregleap#1{%
7385   (\bbl@fpmmod{#1}{4} == 0) &&
7386   (!((\bbl@fpmmod{#1}{100} == 0) && (\bbl@fpmmod{#1}{400} != 0)))}
7387 \def\bbl@cs@jd#1#2#3{% year, month, day
7388   \fp_eval:n{ 1721424.5 + (365 * (#1 - 1)) +
7389     floor((#1 - 1) / 4) + (-floor((#1 - 1) / 100)) +
7390     floor((#1 - 1) / 400) + floor((((367 * #2) - 362) / 12) +
7391     ((#2 <= 2) ? 0 : (\bbl@cs@gregleap{#1} ? -1 : -2)) + #3) }
7392 </Compute Julian day>

```

15.1 Islamic

The code for the Civil calendar is based on it, too.

```

7393 <*ca-islamic>
7394 \ExplSyntaxOn
7395 <<Compute Julian day>>
7396 % == islamic (default)
7397 % Not yet implemented
7398 \def\bbl@ca@islamic#1-#2-#3\@@#4#5#6{

```

The Civil calendar

```

7399 \def\bbl@cs@isltojd#1#2#3{ % year, month, day
7400   ((#3 + ceil(29.5 * (#2 - 1)) +

```

```

7401  (#1 - 1) * 354 + floor((3 + (11 * #1)) / 30) +
7402  1948439.5) - 1) }
7403 \@namedef{bbl@ca@islamic-civil++}{\bbl@ca@islamicv1@x{+2}}
7404 \@namedef{bbl@ca@islamic-civil+}{\bbl@ca@islamicv1@x{+1}}
7405 \@namedef{bbl@ca@islamic-civil}{\bbl@ca@islamicv1@x{}}
7406 \@namedef{bbl@ca@islamic-civil-}{\bbl@ca@islamicv1@x{-1}}
7407 \@namedef{bbl@ca@islamic-civil--}{\bbl@ca@islamicv1@x{-2}}
7408 \def\bbl@ca@islamicv1@x#1#2-#3-#4\@#5#6#7{%
7409   \edef\bbl@tempa{%
7410     \fp_eval:n{ floor(\bbl@cs@jld{#2}{#3}{#4})+0.5 #1}}%
7411   \edef#5{%
7412     \fp_eval:n{ floor(((30*(\bbl@tempa-1948439.5)) + 10646)/10631) }}%
7413   \edef#6{\fp_eval:n{
7414     min(12,ceil((\bbl@tempa-(29+\bbl@cs@isltojd{#5}{1}{1}))/29.5)+1) }}%
7415   \edef#7{\fp_eval:n{ \bbl@tempa - \bbl@cs@isltojd{#5}{#6}{1} + 1} }}

```

The Umm al-Qura calendar, used mainly in Saudi Arabia, is based on moment-hijri, by Abdullah Alsigar (license MIT).

Since the main aim is to provide a suitable \today, and maybe some close dates, data just covers Hijri ~1435/~1460 (Gregorian ~2014/~2038).

```

7416 \def\bbl@cs@umalqura@data{56660, 56690,56719,56749,56778,56808,%
7417 56837,56867,56897,56926,56956,56985,57015,57044,57074,57103,%
7418 57133,57162,57192,57221,57251,57280,57310,57340,57369,57399,%
7419 57429,57458,57487,57517,57546,57576,57605,57634,57664,57694,%
7420 57723,57753,57783,57813,57842,57871,57901,57930,57959,57989,%
7421 58018,58048,58077,58107,58137,58167,58196,58226,58255,58285,%
7422 58314,58343,58373,58402,58432,58461,58491,58521,58551,58580,%
7423 58610,58639,58669,58698,58727,58757,58786,58816,58845,58875,%
7424 58905,58934,58964,58994,59023,59053,59082,59111,59141,59170,%
7425 59200,59229,59259,59288,59318,59348,59377,59407,59436,59466,%
7426 59495,59525,59554,59584,59613,59643,59672,59702,59731,59761,%
7427 59791,59820,59850,59879,59909,59939,59968,59997,60027,60056,%
7428 60086,60115,60145,60174,60204,60234,60264,60293,60323,60352,%
7429 60381,60411,60440,60469,60499,60528,60558,60588,60618,60648,%
7430 60677,60707,60736,60765,60795,60824,60853,60883,60912,60942,%
7431 60972,61002,61031,61061,61090,61120,61149,61179,61208,61237,%
7432 61267,61296,61326,61356,61385,61415,61445,61474,61504,61533,%
7433 61563,61592,61621,61651,61680,61710,61739,61769,61799,61828,%
7434 61858,61888,61917,61947,61976,62006,62035,62064,62094,62123,%
7435 62153,62182,62212,62242,62271,62301,62331,62360,62390,62419,%
7436 62448,62478,62507,62537,62566,62596,62625,62655,62685,62715,%
7437 62744,62774,62803,62832,62862,62891,62921,62950,62980,63009,%
7438 63039,63069,63099,63128,63157,63187,63216,63246,63275,63305,%
7439 63334,63363,63393,63423,63453,63482,63512,63541,63571,63600,%
7440 63630,63659,63689,63718,63747,63777,63807,63836,63866,63895,%
7441 63925,63955,63984,64014,64043,64073,64102,64131,64161,64190,%
7442 64220,64249,64279,64309,64339,64368,64398,64427,64457,64486,%
7443 64515,64545,64574,64603,64633,64663,64692,64722,64752,64782,%
7444 64811,64841,64870,64899,64929,64958,64987,65017,65047,65076,%
7445 65106,65136,65166,65195,65225,65254,65283,65313,65342,65371,%
7446 65401,65431,65460,65490,65520}
7447 \@namedef{bbl@ca@islamic-umalqura+}{\bbl@ca@islamcuqr@x{+1}}
7448 \@namedef{bbl@ca@islamic-umalqura}{\bbl@ca@islamcuqr@x{}}
7449 \@namedef{bbl@ca@islamic-umalqura-}{\bbl@ca@islamcuqr@x{-1}}
7450 \def\bbl@ca@islamcuqr@x#1#2-#3-#4\@#5#6#7{%
7451   \ifnum#2>2014 \ifnum#2<2038
7452     \bbl@afterfi\expandafter\@gobble
7453   \fi\fi
7454   {\bbl@error{Year-out-of-range}{The-allowed-range-is-2014-2038}}%
7455   \edef\bbl@tempd{\fp_eval:n{ % (Julian) day
7456     \bbl@cs@jld{#2}{#3}{#4} + 0.5 - 2400000 #1}}%
7457   \count@\@ne
7458   \bbl@foreach\bbl@cs@umalqura@data{%

```

```

7459 \advance\count@\@ne
7460 \ifnum##1>\bbl@tempd\else
7461 \edef\bbl@tempe{\the\count@}%
7462 \edef\bbl@tempb{##1}%
7463 \fi}%
7464 \edef\bbl@templ{\fp_eval:n{ \bbl@tempe + 16260 + 949 }}% month~lunar
7465 \edef\bbl@tempa{\fp_eval:n{ floor((\bbl@templ - 1 ) / 12) }}% annus
7466 \edef#5{\fp_eval:n{ \bbl@tempa + 1 }}%
7467 \edef#6{\fp_eval:n{ \bbl@templ - (12 * \bbl@tempa) }}%
7468 \edef#7{\fp_eval:n{ \bbl@tempd - \bbl@tempb + 1 }}%
7469 \ExplSyntaxOff
7470 \bbl@add\bbl@precalendar{%
7471 \bbl@replace\bbl@ld@calendar{-civil}{}}%
7472 \bbl@replace\bbl@ld@calendar{-umalqura}{}}%
7473 \bbl@replace\bbl@ld@calendar{+}{}}%
7474 \bbl@replace\bbl@ld@calendar{-}{}}%
7475 </ca-islamic>

```

16 Hebrew

This is basically the set of macros written by Michail Rozman in 1991, with corrections and adaptations by Rama Porrat, Misha, Dan Haran and Boris Lavva. This must be eventually replaced by computations with l3fp.

```

7476 <*ca-hebrew>
7477 \newcount\bbl@cntcommon
7478 \def\bbl@remainder#1#2#3{%
7479 #3 = #1 % c = a
7480 \divide #3 by #2 % c = a/b
7481 \multiply #3 by -#2 % c = -b(a/b)
7482 \advance #3 by #1 }% % c = a - b(a/b)
7483 \newif\ifbbl@divisible
7484 \def\bbl@checkifdivisible#1#2{%
7485 {\countdef\tmp = 0 % \tmp == \count0 - temporary variable
7486 \bbl@remainder{#1}{#2}{\tmp}%
7487 \ifnum \tmp = 0
7488 \global\bbl@divisibletrue
7489 \else
7490 \global\bbl@divisiblefalse
7491 \fi}}
7492 \newif\ifbbl@gregleap
7493 \def\bbl@ifgregleap#1{%
7494 \bbl@checkifdivisible{#1}{4}%
7495 \ifbbl@divisible
7496 \bbl@checkifdivisible{#1}{100}%
7497 \ifbbl@divisible
7498 \bbl@checkifdivisible{#1}{400}%
7499 \ifbbl@divisible
7500 \bbl@gregleaptrue
7501 \else
7502 \bbl@gregleapfalse
7503 \fi
7504 \else
7505 \bbl@gregleaptrue
7506 \fi
7507 \else
7508 \bbl@gregleapfalse
7509 \fi
7510 \ifbbl@gregleap}
7511 \def\bbl@gregdayspriormonths#1#2#3{% no month number 0
7512 {#3 = \ifcase #1 0 \or 0 \or 31 \or 59 \or 90 \or 120 \or 151 \or
7513 181 \or 212 \or 243 \or 273 \or 304 \or 334 \fi
7514 \bbl@ifgregleap#2}%

```



```

7515         \ifnum #1 > 2           % if month after February
7516         \advance #3 by 1 % add leap day
7517     \fi
7518 \fi
7519 \global\bbl@cntcommon = #3}%
7520 #3 = \bbl@cntcommon}
7521 \def\bbl@gregdaysprioryears#1#2{%
7522     {\countdef\tmpc = 4           % \tmpc==\count4
7523     \countdef\tmpb = 2           % \tmpb==\count2
7524     \tmpb = #1                   %
7525     \advance \tmpb by -1         %
7526     \tmpc = \tmpb               % \tmpc = \tmpb = year-1
7527     \multiply \tmpc by 365       % Days in prior years =
7528     #2 = \tmpc                  % = 365*(year-1) ...
7529     \tmpc = \tmpb               %
7530     \divide \tmpc by 4           % \tmpc = (year-1)/4
7531     \advance #2 by \tmpc         % ... plus Julian leap days ...
7532     \tmpc = \tmpb               %
7533     \divide \tmpc by 100         % \tmpc = (year-1)/100
7534     \advance #2 by -\tmpc        % ... minus century years ...
7535     \tmpc = \tmpb               %
7536     \divide \tmpc by 400         % \tmpc = (year-1)/400
7537     \advance #2 by \tmpc         % ... plus 4-century years.
7538     \global\bbl@cntcommon = #2}%
7539 #2 = \bbl@cntcommon}
7540 \def\bbl@absfromgreg#1#2#3#4{%
7541     {\countdef\tmpd = 0           % \tmpd==\count0
7542     #4 = #1                       % days so far this month
7543     \bbl@gregdayspriormonths{#2}{#3}{\tmpd}%
7544     \advance #4 by \tmpd         % add days in prior months
7545     \bbl@gregdaysprioryears{#3}{\tmpd}%
7546     \advance #4 by \tmpd         % add days in prior years
7547     \global\bbl@cntcommon = #4}%
7548 #4 = \bbl@cntcommon}
7549 \newif\ifbbl@hebrleap
7550 \def\bbl@checkleaphebryear#1{%
7551     {\countdef\tmpa = 0           % \tmpa==\count0
7552     \countdef\tmpb = 1           % \tmpb==\count1
7553     \tmpa = #1
7554     \multiply \tmpa by 7
7555     \advance \tmpa by 1
7556     \bbl@remainder{\tmpa}{19}{\tmpb}%
7557     \ifnum \tmpb < 7             % \tmpb = (7*year+1)%19
7558         \global\bbl@hebrleaptrue
7559     \else
7560         \global\bbl@hebrleapfalse
7561     \fi}}
7562 \def\bbl@hebrlapsedmonths#1#2{%
7563     {\countdef\tmpa = 0           % \tmpa==\count0
7564     \countdef\tmpb = 1           % \tmpb==\count1
7565     \countdef\tmpc = 2           % \tmpc==\count2
7566     \tmpa = #1                   %
7567     \advance \tmpa by -1         %
7568     #2 = \tmpa                  % #2 = \tmpa = year-1
7569     \divide #2 by 19             % Number of complete Meton cycles
7570     \multiply #2 by 235          % #2 = 235*((year-1)/19)
7571     \bbl@remainder{\tmpa}{19}{\tmpb}% \tmpa = years%19-years this cycle
7572     \tmpc = \tmpb               %
7573     \multiply \tmpb by 12        %
7574     \advance #2 by \tmpb         % add regular months this cycle
7575     \multiply \tmpc by 7         %
7576     \advance \tmpc by 1         %
7577     \divide \tmpc by 19          % \tmpc = (1+7*((year-1)%19))/19 -

```

```

7578 \advance #2 by \tmpc % add leap months
7579 \global\bbl@cntcommon = #2}%
7580 #2 = \bbl@cntcommon}
7581 \def\bbl@hebreleapseddays#1#2{%
7582 {\countdef\tmpa = 0 % \tmpa==\count0
7583 \countdef\tmpb = 1 % \tmpb==\count1
7584 \countdef\tmpc = 2 % \tmpc==\count2
7585 \bbl@hebreleapsedmonths{#1}{#2}%
7586 \tmpa = #2 %
7587 \multiply \tmpa by 13753 %
7588 \advance \tmpa by 5604 % \tmpa=MonthsElapsed*13753 + 5604
7589 \bbl@remainder{\tmpa}{25920}{\tmpc}% \tmpc == ConjunctionParts
7590 \divide \tmpa by 25920
7591 \multiply #2 by 29
7592 \advance #2 by 1
7593 \advance #2 by \tmpa % #2 = 1 + MonthsElapsed*29 +
7594 \bbl@remainder{#2}{7}{\tmpa}% % \tmpa == DayOfWeek
7595 \ifnum \tmpc < 19440
7596 \ifnum \tmpc < 9924
7597 \else % New moon at 9 h. 204 p. or later
7598 \ifnum \tmpa = 2 % on Tuesday ...
7599 \bbl@checkleaphebreyear{#1}% of a common year
7600 \ifbbl@hebrleap
7601 \else
7602 \advance #2 by 1
7603 \fi
7604 \fi
7605 \fi
7606 \ifnum \tmpc < 16789
7607 \else % New moon at 15 h. 589 p. or later
7608 \ifnum \tmpa = 1 % on Monday ...
7609 \advance #1 by -1
7610 \bbl@checkleaphebreyear{#1}% at the end of leap year
7611 \ifbbl@hebrleap
7612 \advance #2 by 1
7613 \fi
7614 \fi
7615 \fi
7616 \else
7617 \advance #2 by 1 % new moon at or after midday
7618 \fi
7619 \bbl@remainder{#2}{7}{\tmpa}% % \tmpa == DayOfWeek
7620 \ifnum \tmpa = 0 % if Sunday ...
7621 \advance #2 by 1
7622 \else %
7623 \ifnum \tmpa = 3 % Wednesday ...
7624 \advance #2 by 1
7625 \else
7626 \ifnum \tmpa = 5 % or Friday
7627 \advance #2 by 1
7628 \fi
7629 \fi
7630 \fi
7631 \global\bbl@cntcommon = #2}%
7632 #2 = \bbl@cntcommon}
7633 \def\bbl@daysinhebreyear#1#2{%
7634 {\countdef\tmpe = 12 % \tmpe==\count12
7635 \bbl@hebreleapseddays{#1}{\tmpe}%
7636 \advance #1 by 1
7637 \bbl@hebreleapseddays{#1}{#2}%
7638 \advance #2 by -\tmpe
7639 \global\bbl@cntcommon = #2}%
7640 #2 = \bbl@cntcommon}

```

```

7641 \def\bbl@hebrdayspriormonths#1#2#3{%
7642   {\countdef\tmpf= 14      % \tmpf==\count14
7643    #3 = \ifcase #1          % Days in prior month of regular year
7644      0 \or                  % no month number 0
7645      0 \or                  % Tishri
7646      30 \or                 % Heshvan
7647      59 \or                 % Kislev
7648      89 \or                 % Tebeth
7649      118 \or                % Shebat
7650      148 \or                % Adar I
7651      148 \or                % Adar II
7652      177 \or                % Nisan
7653      207 \or                % Iyar
7654      236 \or                % Sivan
7655      266 \or                % Tammuz
7656      295 \or                % Av
7657      325 \or                % Elul
7658      400                    % Dummy
7659   \fi
7660   \bbl@checkleaphebryear{#2}%
7661   \ifbbl@hebrleap          % in leap year
7662     \ifnum #1 > 6           % if month after Adar I
7663       \advance #3 by 30    % add 30 days
7664     \fi
7665   \fi
7666   \bbl@daysinhebryear{#2}{\tmpf}%
7667   \ifnum #1 > 3
7668     \ifnum \tmpf = 353      %
7669       \advance #3 by -1    %
7670     \fi                    % Short Kislev
7671     \ifnum \tmpf = 383      %
7672       \advance #3 by -1    %
7673     \fi                    %
7674   \fi
7675   \ifnum #1 > 2
7676     \ifnum \tmpf = 355      %
7677       \advance #3 by 1     %
7678     \fi                    % Long Heshvan
7679     \ifnum \tmpf = 385      %
7680       \advance #3 by 1     %
7681     \fi                    %
7682   \fi
7683   \global\bbl@cntcommon = #3}%
7684   #3 = \bbl@cntcommon}
7685 \def\bbl@absfromhebr#1#2#3#4{%
7686   {#4 = #1
7687   \bbl@hebrdayspriormonths{#2}{#3}{#1}%
7688   \advance #4 by #1         % Add days in prior months this year
7689   \bbl@hebreleaseddays{#3}{#1}%
7690   \advance #4 by #1         % Add days in prior years
7691   \advance #4 by -1373429    % Subtract days before Gregorian
7692   \global\bbl@cntcommon = #4}%    % 01.01.0001
7693   #4 = \bbl@cntcommon}
7694 \def\bbl@hebrfromgreg#1#2#3#4#5#6{%
7695   {\countdef\tmpx= 17      % \tmpx==\count17
7696   \countdef\tmpy= 18      % \tmpy==\count18
7697   \countdef\tmpz= 19      % \tmpz==\count19
7698   #6 = #3                  %
7699   \global\advance #6 by 3761 % approximation from above
7700   \bbl@absfromgreg{#1}{#2}{#3}{#4}%
7701   \tmpz = 1 \tmpy = 1
7702   \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
7703   \ifnum \tmpx > #4        %

```

```

7704      \global\advance #6 by -1 % Hyear = Gyear + 3760
7705      \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
7706      \fi %
7707      \advance #4 by -\tmpx % Days in this year
7708      \advance #4 by 1 %
7709      #5 = #4 %
7710      \divide #5 by 30 % Approximation for month from below
7711      \loop % Search for month
7712          \bbl@hebrdayspriormonths{#5}{#6}{\tmpx}%
7713          \ifnum \tmpx < #4
7714              \advance #5 by 1
7715              \tmpy = \tmpx
7716      \repeat
7717      \global\advance #5 by -1
7718      \global\advance #4 by -\tmpy}}
7719      \newcount\bbl@hebrday \newcount\bbl@hebrmonth \newcount\bbl@hebyear
7720      \newcount\bbl@gregday \newcount\bbl@gregmonth \newcount\bbl@gregyear
7721      %
7722      \def\bbl@ca@hebrew#1-#2-#3@@#4#5#6{%
7723          \bbl@gregday=#3 \bbl@gregmonth=#2 \bbl@gregyear=#1
7724          \bbl@hebrfromgreg
7725          {\bbl@gregday}{\bbl@gregmonth}{\bbl@gregyear}%
7726          {\bbl@hebrday}{\bbl@hebrmonth}{\bbl@hebyear}%
7727          \edef#4{\the\bbl@hebyear}%
7728          \edef#5{\the\bbl@hebrmonth}%
7729          \edef#6{\the\bbl@hebrday}%
7730      /ca-hebrew)

```

17 Persian

There is an algorithm written in TeX by Jabri, Abolhassani, Pournader and Esfahbod, created for the first versions of the FarsiTeX system (no longer available), but the original license is GPL, so its use with LPL is problematic. The code here follows loosely that by John Walker, which is free and accurate, but sadly very complex, so the relevant data for the years 2013-2050 have been pre-calculated and stored. Actually, all we need is the first day (either March 20 or March 21).

```

7731 < *ca-persian>
7732 \ExplSyntaxOn
7733 << Compute Julian day>>
7734 \def\bbl@cs@firstjal@xx{2012,2016,2020,2024,2028,2029,% March 20
7735     2032,2033,2036,2037,2040,2041,2044,2045,2048,2049}
7736 \def\bbl@ca@persian#1-#2-#3@@#4#5#6{%
7737     \edef\bbl@tempa{#1}% 20XX-03-\bbl@tempe = 1 farvardin:
7738     \ifnum\bbl@tempa>2012 \ifnum\bbl@tempa<2051
7739         \bbl@afterfi\expandafter\@gobble
7740     \fi\fi
7741     {\bbl@error{Year-out-of-range}{The-allowed-range-is-2013-2050}}%
7742     \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%
7743     \ifin@{\def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
7744     \edef\bbl@tempc{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{#2}{#3}+.5}}% current
7745     \edef\bbl@tempb{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{03}{\bbl@tempe}+.5}}% begin
7746     \ifnum\bbl@tempc<\bbl@tempb
7747         \edef\bbl@tempa{\fp_eval:n{\bbl@tempa-1}}% go back 1 year and redo
7748         \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%
7749         \ifin@{\def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
7750         \edef\bbl@tempb{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{03}{\bbl@tempe}+.5}}%
7751     \fi
7752     \edef#4{\fp_eval:n{\bbl@tempa-621}}% set Jalali year
7753     \edef#6{\fp_eval:n{\bbl@tempc-\bbl@tempb+1}}% days from 1 farvardin
7754     \edef#5{\fp_eval:n{% set Jalali month
7755         (#6 <= 186) ? ceil(#6 / 31) : ceil((#6 - 6) / 30)}}
7756     \edef#6{\fp_eval:n{% set Jalali day
7757         (#6 - ((#5 <= 7) ? ((#5 - 1) * 31) : (((#5 - 1) * 30) + 6))}}%

```

```
7758 \ExplSyntaxOff
7759 \ca-persian)
```

18 Coptic

Adapted from `jquery.calendars.package-1.1.4`, written by Keith Wood, 2010. Dual license: GPL and MIT.

```
7760 (*ca-coptic)
7761 \ExplSyntaxOn
7762 <<Compute Julian day>>
7763 \def\bbl@ca@coptic#1-#2-#3\@#4#5#6{%
7764   \edef\bbl@tempd{\fp_eval:n{floor(\bbl@cs@jd{#1}{#2}{#3}) + 0.5}}%
7765   \edef\bbl@tempc{\fp_eval:n{\bbl@tempd - 1825029.5}}%
7766   \edef#4{\fp_eval:n{%
7767     floor((\bbl@tempc - floor((\bbl@tempc+366) / 1461)) / 365) + 1}}%
7768   \edef\bbl@tempc{\fp_eval:n{%
7769     \bbl@tempd - (#4-1) * 365 - floor(#4/4) - 1825029.5}}%
7770   \edef#5{\fp_eval:n{floor(\bbl@tempc / 30) + 1}}%
7771   \edef#6{\fp_eval:n{\bbl@tempc - (#5 - 1) * 30 + 1}}%
7772 \ExplSyntaxOff
7773 \ca-coptic)
```

19 Buddhist

That's very simple.

```
7774 (*ca-buddhist)
7775 \def\bbl@ca@buddhist#1-#2-#3\@#4#5#6{%
7776   \edef#4{\number\numexpr#1+543\relax}%
7777   \edef#5{#2}%
7778   \edef#6{#3}}
7779 \ca-buddhist)
```

20 Support for Plain T_EX (plain.def)

20.1 Not renaming hyphen.tex

As Don Knuth has declared that the filename `hyphen.tex` may only be used to designate *his* version of the american English hyphenation patterns, a new solution has to be found in order to be able to load hyphenation patterns for other languages in a plain-based T_EX-format. When asked he responded:

That file name is “sacred”, and if anybody changes it they will cause severe upward/downward compatibility headaches.

People can have a file `locallyhyphen.tex` or whatever they like, but they mustn't diddle with `hyphen.tex` (or `plain.tex` except to preload additional fonts).

The files `bplain.tex` and `blplain.tex` can be used as replacement wrappers around `plain.tex` and `lplain.tex` to achieve the desired effect, based on the `babel` package. If you load each of them with `iniTEX`, you will get a file called either `bplain.fmt` or `blplain.fmt`, which you can use as replacements for `plain.fmt` and `lplain.fmt`.

As these files are going to be read as the first thing `iniTEX` sees, we need to set some category codes just to be able to change the definition of `\input`.

```
7780 (*bplain | blplain)
7781 \catcode`\{=1 % left brace is begin-group character
7782 \catcode`\}=2 % right brace is end-group character
7783 \catcode`\#=6 % hash mark is macro parameter character
```

If a file called `hyphen.cfg` can be found, we make sure that *it* will be read instead of the file `hyphen.tex`. We do this by first saving the original meaning of `\input` (and I use a one letter control sequence for that so as not to waste multi-letter control sequence on this in the format).

```
7784 \openin 0 hyphen.cfg
```

```

7785 \ifeof0
7786 \else
7787   \let\input

```

Then `\input` is defined to forget about its argument and load `hyphen.cfg` instead. Once that's done the original meaning of `\input` can be restored and the definition of `\a` can be forgotten.

```

7788   \def\input #1 {%
7789     \let\input\input
7790     \a hyphen.cfg
7791     \let\input\input
7792   }
7793 \fi
7794 </bplain>

```

Now that we have made sure that `hyphen.cfg` will be loaded at the right moment it is time to load `plain.tex`.

```

7795 <bplain>\a plain.tex
7796 <bplain>\a lplain.tex

```

Finally we change the contents of `\fmtname` to indicate that this is *not* the plain format, but a format based on plain with the `babel` package preloaded.

```

7797 <bplain>\def\fmtname{babel-plain}
7798 <bplain>\def\fmtname{babel-lplain}

```

When you are using a different format, based on `plain.tex` you can make a copy of `plain.tex`, rename it and replace `plain.tex` with the name of your format file.

20.2 Emulating some \LaTeX features

The file `babel.def` expects some definitions made in the $\text{\LaTeX} 2_{\epsilon}$ style file. So, in Plain we must provide at least some predefined values as well some tools to set them (even if not all options are available). There are no package options, and therefore an alternative mechanism is provided. For the moment, only `\babeloptionstrings` and `\babeloptionmath` are provided, which can be defined before loading `babel`. `\BabelModifiers` can be set too (but not sure it works).

```

7799 <{*Emulate LaTeX}> ≡
7800 \def\@empty{}
7801 \def\loadlocalcfg#1{%
7802   \openin0#1.cfg
7803   \ifeof0
7804     \closein0
7805   \else
7806     \closein0
7807     {\immediate\write16{*****}%
7808      \immediate\write16{* Local config file #1.cfg used}%
7809      \immediate\write16{*}%
7810     }
7811     \input #1.cfg\relax
7812   \fi
7813   \@endofldf}

```

20.3 General tools

A number of \LaTeX macro's that are needed later on.

```

7814 \long\def\@firstofone#1{#1}
7815 \long\def\@firstoftwo#1#2{#1}
7816 \long\def\@secondoftwo#1#2{#2}
7817 \def\@nnil{\nil}
7818 \def\@gobbletwo#1#2{}
7819 \def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}
7820 \def\@star@or@long#1{%
7821   \@ifstar
7822   {\let\l@ngrel@x\relax#1}%
7823   {\let\l@ngrel@x\long#1}}

```

```

7824 \let\l@ngrel@x\relax
7825 \def\@car#1#2\@nil{#1}
7826 \def\@cdr#1#2\@nil{#2}
7827 \let\@typeset@protect\relax
7828 \let\protected@edef\edef
7829 \long\def\@gobble#1{}
7830 \edef\@backslashchar{\expandafter\@gobble\string\}
7831 \def\strip@prefix#1>{}
7832 \def\g@addto@macro#1#2{{%
7833   \toks@\expandafter{#1#2}%
7834   \xdef#1{\the\toks@}}
7835 \def\@namedef#1{\expandafter\def\csname #1\endcsname}
7836 \def\@nameuse#1{\csname #1\endcsname}
7837 \def\@ifundefined#1{%
7838   \expandafter\ifx\csname#1\endcsname\relax
7839     \expandafter\@firstoftwo
7840   \else
7841     \expandafter\@secondoftwo
7842   \fi}
7843 \def\@expandtwoargs#1#2#3{%
7844   \edef\reserved@a{\noexpand#1{#2}{#3}}\reserved@a}
7845 \def\zap@space#1 #2{%
7846   #1%
7847   \ifx#2\@empty\else\expandafter\zap@space\fi
7848   #2}
7849 \let\bbl@trace\@gobble
7850 \def\bbl@error#1#2{%
7851   \begingroup
7852     \newlinechar=`^^J
7853     \def\{^^J(babel) }%
7854     \errhelp{#2}\errmessage{\{#1}%
7855   \endgroup}
7856 \def\bbl@warning#1{%
7857   \begingroup
7858     \newlinechar=`^^J
7859     \def\{^^J(babel) }%
7860     \message{\{#1}%
7861   \endgroup}
7862 \let\bbl@infowarn\bbl@warning
7863 \def\bbl@info#1{%
7864   \begingroup
7865     \newlinechar=`^^J
7866     \def\{^^J}%
7867     \wlog{#1}%
7868   \endgroup}

```

$\text{\LaTeX} 2_{\epsilon}$ has the command `\@onlypreamble` which adds commands to a list of commands that are no longer needed after `\begin{document}`.

```

7869 \ifx\@preamblecmds\@undefined
7870   \def\@preamblecmds{}
7871 \fi
7872 \def\@onlypreamble#1{%
7873   \expandafter\gdef\expandafter\@preamblecmds\expandafter{%
7874     \@preamblecmds\do#1}}
7875 \@onlypreamble\@onlypreamble

```

Mimick \LaTeX 's `\AtBeginDocument`; for this to work the user needs to add `\begin{document}` to his file.

```

7876 \def\begin{document}{%
7877   \@begin{document}hook
7878   \global\let\@begin{document}hook\@undefined
7879   \def\do##1{\global\let##1\@undefined}%
7880   \@preamblecmds
7881   \global\let\do\noexpand}

```

```

7882 \ifx\@begindocumenthook\@undefined
7883   \def\@begindocumenthook{}
7884 \fi
7885 \@onlypreamble\@begindocumenthook
7886 \def\AtBeginDocument{\g@addto@macro\@begindocumenthook}

```

We also have to mimic \LaTeX 's `\AtEndOfPackage`. Our replacement macro is much simpler; it stores its argument in `\@endoflfd`.

```

7887 \def\AtEndOfPackage#1{\g@addto@macro\@endoflfd{#1}}
7888 \@onlypreamble\AtEndOfPackage
7889 \def\@endoflfd{}
7890 \@onlypreamble\@endoflfd
7891 \let\bbl@afterlang\@empty
7892 \chardef\bbl@opt@hyphenmap\z@

```

\LaTeX needs to be able to switch off writing to its auxiliary files; plain doesn't have them by default. There is a trick to hide some conditional commands from the outer `\ifx`. The same trick is applied below.

```

7893 \catcode`\&=\z@
7894 \ifx&\if@files\@undefined
7895   \expandafter\let\csname if@files\expandafter\endcsname
7896     \csname iffalse\endcsname
7897 \fi
7898 \catcode`\&=4

```

Mimick \LaTeX 's commands to define control sequences.

```

7899 \def\newcommand{\@star@or@long\new@command}
7900 \def\new@command#1{%
7901   \@testopt{\@newcommand#1}0}
7902 \def\@newcommand#1[#2]{%
7903   \@ifnextchar [{\@xargdef#1[#2]}%
7904     {\@argdef#1[#2]}}
7905 \long\def\@argdef#1[#2]#3{%
7906   \@yargdef#1\@ne{#2}{#3}}
7907 \long\def\@xargdef#1[#2][#3]#4{%
7908   \expandafter\def\expandafter#1\expandafter{%
7909     \expandafter\@protected@testopt\expandafter #1%
7910     \csname\string#1\expandafter\endcsname{#3}}%
7911   \expandafter\@yargdef \csname\string#1\endcsname
7912     \tw@{#2}{#4}}
7913 \long\def\@yargdef#1#2#3{%
7914   \@tempcnta#3\relax
7915   \advance \@tempcnta \@ne
7916   \let\@hash@\relax
7917   \edef\reserved@a{\ifx#2\tw@ [\@hash@1]\fi}%
7918   \@tempcntb #2%
7919   \@whilenum\@tempcntb <\@tempcnta
7920   \do{%
7921     \edef\reserved@a{\reserved@a\@hash@\the\@tempcntb}%
7922     \advance\@tempcntb \@ne}%
7923   \let\@hash@##%
7924   \l@ngrelx\expandafter\def\expandafter#1\reserved@a}
7925 \def\providecommand{\@star@or@long\provide@command}
7926 \def\provide@command#1{%
7927   \begingroup
7928     \escapechar\m@ne\xdef\@gtempa{\string#1}%
7929   \endgroup
7930   \expandafter\@ifundefined\@gtempa
7931     {\def\reserved@a{\new@command#1}}%
7932     {\let\reserved@a\relax
7933       \def\reserved@a{\new@command\reserved@a}}%
7934   \reserved@a}%
7935 \def\DeclareRobustCommand{\@star@or@long\declare@robustcommand}

```



```

7936 \def\declare@robustcommand#1{%
7937   \edef\reserved@a{\string#1}%
7938   \def\reserved@b{#1}%
7939   \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
7940   \edef#1{%
7941     \ifx\reserved@a\reserved@b
7942       \noexpand\x@protect
7943       \noexpand#1%
7944     \fi
7945     \noexpand\protect
7946     \expandafter\noexpand\csname
7947       \expandafter\@gobble\string#1 \endcsname
7948   }%
7949   \expandafter\new@command\csname
7950     \expandafter\@gobble\string#1 \endcsname
7951 }
7952 \def\x@protect#1{%
7953   \ifx\protect\@typeset@protect\else
7954     \@x@protect#1%
7955   \fi
7956 }
7957 \catcode`\&=\z@ % Trick to hide conditionals
7958 \def\@x@protect#1&fi#2#3{&fi\protect#1}

```

The following little macro `\in@` is taken from `latex.ltx`; it checks whether its first argument is part of its second argument. It uses the boolean `\in@`; allocating a new boolean inside conditionally executed code is not possible, hence the construct with the temporary definition of `\bbl@tempa`.

```

7959 \def\bbl@tempa{\csname newif\endcsname&ifin@}
7960 \catcode`\&=4
7961 \ifx\in@\@undefined
7962   \def\in@#1#2{%
7963     \def\in@@##1#1##2##3\in@@{%
7964       \ifx\in@@#2\in@false\else\in@true\fi}%
7965     \in@@#2#1\in@\in@@}
7966 \else
7967   \let\bbl@tempa\@empty
7968 \fi
7969 \bbl@tempa

```

\LaTeX has a macro to check whether a certain package was loaded with specific options. The command has two extra arguments which are code to be executed in either the true or false case. This is used to detect whether the document needs one of the accents to be activated (activegrave and activeacute). For plain \TeX we assume that the user wants them to be active by default. Therefore the only thing we do is execute the third argument (the code for the true case).

```

7970 \def\@ifpackagewith#1#2#3#4{#3}

```

The \LaTeX macro `\@ifl@aded` checks whether a file was loaded. This functionality is not needed for plain \TeX but we need the macro to be defined as a no-op.

```

7971 \def\@ifl@aded#1#2#3#4{}

```

For the following code we need to make sure that the commands `\newcommand` and `\providecommand` exist with some sensible definition. They are not fully equivalent to their \LaTeX 2_ϵ versions; just enough to make things work in plain \TeX environments.

```

7972 \ifx\@tempcnta\@undefined
7973   \csname newcount\endcsname\@tempcnta\relax
7974 \fi
7975 \ifx\@tempcntb\@undefined
7976   \csname newcount\endcsname\@tempcntb\relax
7977 \fi

```

To prevent wasting two counters in \LaTeX (because counters with the same name are allocated later by it) we reset the counter that holds the next free counter (`\count10`).

```

7978 \ifx\bye\@undefined
7979   \advance\count10 by -2\relax

```

```

7980 \fi
7981 \ifx\@ifnextchar\@undefined
7982   \def\@ifnextchar#1#2#3{%
7983     \let\reserved@d=#1%
7984     \def\reserved@a{#2}\def\reserved@b{#3}%
7985     \futurelet\@let@token\@ifnch}
7986   \def\@ifnch{%
7987     \ifx\@let@token\@sptoken
7988       \let\reserved@c\@xifnch
7989     \else
7990       \ifx\@let@token\reserved@d
7991         \let\reserved@c\reserved@a
7992       \else
7993         \let\reserved@c\reserved@b
7994       \fi
7995     \fi
7996     \reserved@c}
7997   \def\:\let\@sptoken= } \: % this makes \@sptoken a space token
7998   \def\:\@xifnch} \expandafter\def\:\{\futurelet\@let@token\@ifnch}
7999 \fi
8000 \def\@testopt#1#2{%
8001   \@ifnextchar[{\#1}{\#1[#2]}}
8002 \def\@protected@testopt#1{%
8003   \ifx\protect\@typeset@protect
8004     \expandafter\@testopt
8005   \else
8006     \@x@protect#1%
8007   \fi}
8008 \long\def\@whilenum#1\do #2{\ifnum #1\relax #2\relax\@iwhilenum{#1\relax
8009   #2\relax}\fi}
8010 \long\def\@iwhilenum#1{\ifnum #1\expandafter\@iwhilenum
8011   \else\expandafter\@gobble\fi{#1}}

```

20.4 Encoding related macros

Code from `ltoutenc.dtx`, adapted for use in the plain \TeX environment.

```

8012 \def\DeclareTextCommand{%
8013   \@dec@text@cmd\providecommand
8014 }
8015 \def\ProvideTextCommand{%
8016   \@dec@text@cmd\providecommand
8017 }
8018 \def\DeclareTextSymbol#1#2#3{%
8019   \@dec@text@cmd\chardef#1{#2}#3\relax
8020 }
8021 \def\@dec@text@cmd#1#2#3{%
8022   \expandafter\def\expandafter#2%
8023     \expandafter{%
8024       \csname#3-cmd\expandafter\endcsname
8025       \expandafter#2%
8026       \csname#3\string#2\endcsname
8027     }%
8028   \let\@ifdefinable\@rc@ifdefinable
8029   \expandafter#1\csname#3\string#2\endcsname
8030 }
8031 \def\@current@cmd#1{%
8032   \ifx\protect\@typeset@protect\else
8033     \noexpand#1\expandafter\@gobble
8034   \fi
8035 }
8036 \def\@changed@cmd#1#2{%
8037   \ifx\protect\@typeset@protect
8038     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax

```

```

8039         \expandafter\ifx\csname ?\string#1\endcsname\relax
8040         \expandafter\def\csname ?\string#1\endcsname{%
8041             \@changed@x@err{#1}%
8042         }%
8043     \fi
8044     \global\expandafter\let
8045         \csname\cf@encoding\string#1\expandafter\endcsname
8046         \csname ?\string#1\endcsname
8047     \fi
8048     \csname\cf@encoding\string#1%
8049     \expandafter\endcsname
8050 \else
8051     \noexpand#1%
8052 \fi
8053 }
8054 \def\@changed@x@err#1{%
8055     \errhelp{Your command will be ignored, type <return> to proceed}%
8056     \errmessage{Command \protect#1 undefined in encoding \cf@encoding}}
8057 \def\DeclareTextCommandDefault#1{%
8058     \DeclareTextCommand#1?%
8059 }
8060 \def\ProvideTextCommandDefault#1{%
8061     \ProvideTextCommand#1?%
8062 }
8063 \expandafter\let\csname OT1-cmd\endcsname\@current@cmd
8064 \expandafter\let\csname?-cmd\endcsname\@changed@cmd
8065 \def\DeclareTextAccent#1#2#3{%
8066     \DeclareTextCommand#1#2#3[1]{\accent#3 ##1}
8067 }
8068 \def\DeclareTextCompositeCommand#1#2#3#4{%
8069     \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
8070     \edef\reserved@b{\string##1}%
8071     \edef\reserved@c{%
8072         \expandafter\@strip@args\meaning\reserved@a:-\@strip@args}%
8073     \ifx\reserved@b\reserved@c
8074         \expandafter\expandafter\expandafter\ifx
8075             \expandafter\@car\reserved@a\relax\relax\@nil
8076             \@text@composite
8077     \else
8078         \edef\reserved@b##1{%
8079             \def\expandafter\noexpand
8080                 \csname#2\string#1\endcsname####1{%
8081                 \noexpand\@text@composite
8082                 \expandafter\noexpand\csname#2\string#1\endcsname
8083                 ####1\noexpand\@empty\noexpand\@text@composite
8084                 {##1}%
8085             }%
8086         }%
8087         \expandafter\reserved@b\expandafter{\reserved@a{##1}}%
8088     \fi
8089     \expandafter\def\csname\expandafter\string\csname
8090         #2\endcsname\string#1-\string#3\endcsname{#4}
8091 \else
8092     \errhelp{Your command will be ignored, type <return> to proceed}%
8093     \errmessage{\string\DeclareTextCompositeCommand\space used on
8094         inappropriate command \protect#1}
8095 \fi
8096 }
8097 \def\@text@composite#1#2#3\@text@composite{%
8098     \expandafter\@text@composite@x
8099     \csname\string#1-\string#2\endcsname
8100 }
8101 \def\@text@composite@x#1#2{%

```

```

8102 \ifx#1\relax
8103     #2%
8104 \else
8105     #1%
8106 \fi
8107 }
8108 %
8109 \def\@strip@args#1:#2-#3\@strip@args{#2}
8110 \def\DeclareTextComposite#1#2#3#4{%
8111     \def\reserved@a{\DeclareTextCompositeCommand#1{#2}{#3}}%
8112     \bgroup
8113         \lccode`\@=#4%
8114         \lowercase{%
8115     \egroup
8116     \reserved@a @%
8117 }%
8118 }
8119 %
8120 \def\UseTextSymbol#1#2{#2}
8121 \def\UseTextAccent#1#2#3{
8122 \def\@use@text@encoding#1{
8123 \def\DeclareTextSymbolDefault#1#2{%
8124     \DeclareTextCommandDefault#1{\UseTextSymbol{#2}#1}%
8125 }
8126 \def\DeclareTextAccentDefault#1#2{%
8127     \DeclareTextCommandDefault#1{\UseTextAccent{#2}#1}%
8128 }
8129 \def\cf@encoding{OT1}

```

Currently we only use the \LaTeX 2_ϵ method for accents for those that are known to be made active in *some* language definition file.

```

8130 \DeclareTextAccent{"}{OT1}{127}
8131 \DeclareTextAccent{'}{OT1}{19}
8132 \DeclareTextAccent{^}{OT1}{94}
8133 \DeclareTextAccent`}{OT1}{18}
8134 \DeclareTextAccent{~}{OT1}{126}

```

The following control sequences are used in `babel.def` but are not defined for `PLAIN TEX`.

```

8135 \DeclareTextSymbol{\textquotedblleft}{OT1}{92}
8136 \DeclareTextSymbol{\textquotedblright}{OT1}{`\"}
8137 \DeclareTextSymbol{\textquoteleft}{OT1}{``}
8138 \DeclareTextSymbol{\textquoteright}{OT1}{``'}
8139 \DeclareTextSymbol{\i}{OT1}{16}
8140 \DeclareTextSymbol{\ss}{OT1}{25}

```

For a couple of languages we need the \LaTeX -control sequence `\scriptsize` to be available. Because plain $\text{T}_\text{E}\text{X}$ doesn't have such a sophisticated font mechanism as \LaTeX has, we just `\let` it to `\sevenrm`.

```

8141 \ifx\scriptsize\undefined
8142     \let\scriptsize\sevenrm
8143 \fi

```

And a few more “dummy” definitions.

```

8144 \def\language{english}%
8145 \let\bbl@opt@shorthands\@nnil
8146 \def\bbl@ifshorthand#1#2#3{#2}%
8147 \let\bbl@language@opts\@empty
8148 \ifx\babeloptionstrings\undefined
8149     \let\bbl@opt@strings\@nnil
8150 \else
8151     \let\bbl@opt@strings\babeloptionstrings
8152 \fi
8153 \def\BabelStringsDefault{generic}
8154 \def\bbl@tempa{normal}
8155 \ifx\babeloptionmath\bbl@tempa

```

```

8156 \def\bbl@mathnormal{\noexpand\textormath}
8157 \fi
8158 \def\AfterBabelLanguage#1#2{}
8159 \ifx\BabelModifiers\undefined\let\BabelModifiers\relax\fi
8160 \let\bbl@afterlang\relax
8161 \def\bbl@opt@safe{BR}
8162 \ifx\@uclclist\undefined\let\@uclclist\empty\fi
8163 \ifx\bbl@trace\undefined\def\bbl@trace#1{}\fi
8164 \expandafter\newif\csname ifbbl@single\endcsname
8165 \chardef\bbl@bidimode\z@
8166 <</Emulate LaTeX>>

A proxy file:
8167 <*plain>
8168 \input babel.def
8169 </plain>

```

21 Acknowledgements

I would like to thank all who volunteered as β -testers for their time. Michel Goossens supplied contributions for most of the other languages. Nico Poppelier helped polish the text of the documentation and supplied parts of the macros for the Dutch language. Paul Wackers and Werenfried Spit helped find and repair bugs. During the further development of the babel system I received much help from Bernd Raichle, for which I am grateful.

References

- [1] Huda Smitshuijzen Abifares, *Arabic Typography*, Saqi, 2001.
- [2] Johannes Braams, Victor Eijkhout and Nico Poppelier, *The development of national \TeX styles*, *TUGboat* 10 (1989) #3, p. 401–406.
- [3] Yannis Haralambous, *Fonts & Encodings*, O'Reilly, 2007.
- [4] Donald E. Knuth, *The \TeX book*, Addison-Wesley, 1986.
- [5] Jukka K. Korpela, *Unicode Explained*, O'Reilly, 2006.
- [6] Leslie Lamport, *\TeX , A document preparation System*, Addison-Wesley, 1986.
- [7] Leslie Lamport, in: \TeX hax Digest, Volume 89, #13, 17 February 1989.
- [8] Ken Lunde, *CJKV Information Processing*, O'Reilly, 2nd ed., 2009.
- [9] Hubert Partl, *German \TeX* , *TUGboat* 9 (1988) #1, p. 70–72.
- [10] Joachim Schrod, *International \TeX is ready to use*, *TUGboat* 11 (1990) #1, p. 87–90.
- [11] Apostolos Syropoulos, Antonis Tsolomitis and Nick Sofroniu, *Digital typography using \TeX* , Springer, 2002, p. 301–373.
- [12] K.F. Treebus. *Tekstwijzer; een gids voor het grafisch verwerken van tekst*, SDU Uitgeverij ('s-Gravenhage, 1988).