

Babel

Code

Version 24.5.50868
2024/05/22

Javier Bezos
Current maintainer

Johannes L. Braams
Original author

Localization and
internationalization

Unicode

TeX

pdfTeX

LuaTeX

XeTeX

Contents

1	Identification and loading of required files	3
2	locale directory	3
3	Tools	3
3.1	Multiple languages	7
3.2	The Package File (<code>\LaTeX</code> , <code>babel.sty</code>)	8
3.3	<code>base</code>	9
3.4	<code>key=value</code> options and other general option	10
3.5	Conditional loading of shorthands	11
3.6	Interlude for Plain	13
4	Multiple languages	13
4.1	Selecting the language	15
4.2	Errors	23
4.3	Hooks	25
4.4	Setting up language files	27
4.5	Shorthands	29
4.6	Language attributes	38
4.7	Support for saving macro definitions	39
4.8	Short tags	41
4.9	Hyphens	41
4.10	Multiencoding strings	43
4.11	Macros common to a number of languages	48
4.12	Making glyphs available	48
4.12.1	Quotation marks	48
4.12.2	Letters	50
4.12.3	Shorthands for quotation marks	50
4.12.4	Umlauts and tremas	51
4.13	Layout	52
4.14	Load engine specific macros	53
4.15	Creating and modifying languages	53
5	Adjusting the Babel bahavior	76
5.1	Cross referencing macros	79
5.2	Marks	81
5.3	Preventing clashes with other packages	82
5.3.1	<code>ifthen</code>	82
5.3.2	<code>varioref</code>	83
5.3.3	<code>hhline</code>	83
5.4	Encoding and fonts	84
5.5	Basic bidi support	85
5.6	Local Language Configuration	89
5.7	Language options	89
6	The kernel of Babel (<code>babel.def</code>, <code>common</code>)	92
7	Loading hyphenation patterns	96
8	Font handling with <code>fontspec</code>	100
9	Hooks for XeTeX and LuaTeX	103
9.1	XeTeX	103

10	Support for interchar	105
10.1	Layout	107
10.2	8-bit TeX	109
10.3	LuaTeX	110
10.4	Southeast Asian scripts	116
10.5	CJK line breaking	117
10.6	Arabic justification	119
10.7	Common stuff	124
10.8	Automatic fonts and ids switching	124
10.9	Bidi	130
10.10	Layout	132
10.11	Lua: transforms	139
10.12	Lua: Auto bidi with <code>basic</code> and <code>basic-r</code>	148
11	Data for CJK	159
12	The ‘nil’ language	159
13	Calendars	160
13.1	Islamic	161
13.2	Hebrew	162
13.3	Persian	166
13.4	Coptic and Ethiopic	167
13.5	Buddhist	167
14	Support for Plain TeX (<code>plain.def</code>)	169
14.1	Not renaming <code>hyphen.tex</code>	169
14.2	Emulating some L ^A T _E X features	169
14.3	General tools	170
14.4	Encoding related macros	174
15	Acknowledgements	176

The babel package is being developed incrementally, which means parts of the code are under development and therefore incomplete. Only documented features are considered complete. In other words, use babel in real documents only as documented (except, of course, if you want to explore and test them).

1 Identification and loading of required files

Code documentation is still under revision.

The babel package after unpacking consists of the following files:

babel.sty is the L^AT_EX package, which set options and load language styles.

babel.def is loaded by Plain.

switch.def defines macros to set and switch languages (it loads part babel.def).

plain.def is not used, and just loads babel.def, for compatibility.

hyphen.cfg is the file to be used when generating the formats to load hyphenation patterns.

There some additional tex, def and lua files

The babel installer extends docstrip with a few “pseudo-guards” to set “variables” used at installation time. They are used with <@name> at the appropriate places in the source code and defined with either <<name=value>>, or with a series of lines between <<*name>> and <</name>>. The latter is cumulative (eg, with *More package options*). That brings a little bit of literate programming. The guards <-name> and <+name> have been redefined, too. See babel.ins for further details.

2 locale directory

A required component of babel is a set of ini files with basic definitions for about 250 languages. They are distributed as a separate zip file, not packed as dtx. Most of them are essentially finished (except bugs and mistakes, of course). Some of them are still incomplete (but they will be usable), and there are some omissions (eg, there are no geographic areas in Spanish). Not all include LICR variants.

babel-*.ini files contain the actual data; babel-*.tex files are basically proxies to the corresponding ini files.

See [Keys in ini files](#) in the the babel site.

3 Tools

```
1 <<version=24.5.50868>>
2 <<date=2024/05/22>>
```

Do not use the following macros in ldf files. They may change in the future. This applies mainly to those recently added for replacing, trimming and looping. The older ones, like \bbl@afterfi, will not change.

We define some basic macros which just make the code cleaner. \bbl@add is now used internally instead of \addto because of the unpredictable behavior of the latter. Used in babel.def and in babel.sty, which means in L^AT_EX is executed twice, but we need them when defining options and babel.def cannot be load until options have been defined. This does not hurt, but should be fixed somehow.

```
3 <<*Basic macros>> ≡
4 \bbl@trace{Basic macros}
5 \def\bbl@stripslash{\expandafter\@gobble\string}
6 \def\bbl@add#1#2{%
7   \bbl@ifunset{\bbl@stripslash#1}%
8     {\def#1#2}%
9     {\expandafter\def\expandafter#1\expandafter{#1#2}}}
10 \def\bbl@xin@{\@expandtwoargs\in@}
11 \def\bbl@carg#1#2{\expandafter#1\csname#2\endcsname}%
12 \def\bbl@ncarg#1#2#3{\expandafter#1\expandafter#2\csname#3\endcsname}%
13 \def\bbl@ccarg#1#2#3{%
14   \expandafter#1\csname#2\expandafter\endcsname\csname#3\endcsname}%
15 \def\bbl@csarg#1#2{\expandafter#1\csname bbl@#2\endcsname}%
16 \def\bbl@cs#1{\csname bbl@#1\endcsname}
17 \def\bbl@c#1{\csname bbl@#1\language\endcsname}
```

```

18 \def\bbl@loop#1#2#3{\bbl@loop#1{#3}#2,\@nnil,}
19 \def\bbl@loopx#1#2{\expandafter\bbl@loop\expandafter#1\expandafter{#2}}
20 \def\bbl@loop#1#2#3,{%
21   \ifx\@nnil#3\relax\else
22     \def#1{#3}#2\bbl@afterfi\bbl@loop#1{#2}%
23   \fi}
24 \def\bbl@for#1#2#3{\bbl@loopx#1{#2}{\ifx#1\@empty\else#3\fi}}

```

`\bbl@add@list` This internal macro adds its second argument to a comma separated list in its first argument. When the list is not defined yet (or empty), it will be initiated. It presumes expandable character strings.

```

25 \def\bbl@add@list#1#2{%
26   \edef#1{%
27     \bbl@ifunset{\bbl@stripslash#1}%
28     {}%
29     {\ifx#1\@empty\else#1,\fi}%
30     #2}}

```

`\bbl@afterelse` Because the code that is used in the handling of active characters may need to look ahead, we take extra care to ‘throw’ it over the `\else` and `\fi` parts of an `\if`-statement¹. These macros will break if another `\if... \fi` statement appears in one of the arguments and it is not enclosed in braces.

```

31 \long\def\bbl@afterelse#1\else#2\fi{\fi#1}
32 \long\def\bbl@afterfi#1\fi{\fi#1}

```

`\bbl@exp` Now, just syntactical sugar, but it makes partial expansion of some code a lot more simple and readable. Here `\` stands for `\noexpand`, `\<.>` for `\noexpand` applied to a built macro name (which does not define the macro if undefined to `\relax`, because it is created locally), and `\[. .]` for one-level expansion (where `. .` is the macro name without the backslash). The result may be followed by extra arguments, if necessary.

```

33 \def\bbl@exp#1{%
34   \begingroup
35   \let\<\noexpand
36   \let\<\bbl@exp@en
37   \let\[\bbl@exp@ue
38   \edef\bbl@exp@aux{\endgroup#1}%
39   \bbl@exp@aux}
40 \def\bbl@exp@en#1>{\expandafter\noexpand\csname#1\endcsname}%
41 \def\bbl@exp@ue#1]{%
42   \unexpanded\expandafter\expandafter\expandafter{\csname#1\endcsname}}%

```

`\bbl@trim` The following piece of code is stolen (with some changes) from `keyval`, by David Carlisle. It defines two macros: `\bbl@trim` and `\bbl@trim@def`. The first one strips the leading and trailing spaces from the second argument and then applies the first argument (a macro, `\toks@` and the like). The second one, as its name suggests, defines the first argument as the stripped second argument.

```

43 \def\bbl@tempa#1{%
44   \long\def\bbl@trim##1##2{%
45     \futurelet\bbl@trim@a\bbl@trim@c##2\@nil\@nil#1\@nil\relax{##1}}%
46   \def\bbl@trim@c{%
47     \ifx\bbl@trim@a\@sptoken
48       \expandafter\bbl@trim@b
49     \else
50       \expandafter\bbl@trim@b\expandafter#1%
51     \fi}%
52   \long\def\bbl@trim@b#1##1 \@nil{\bbl@trim@i##1}}
53 \bbl@tempa{ }
54 \long\def\bbl@trim@i#1\@nil#2\relax#3{#3{#1}}
55 \long\def\bbl@trim@def#1{\bbl@trim{def#1}}

```

`\bbl@ifunset` To check if a macro is defined, we create a new macro, which does the same as `\@ifundefined`. However, in an ϵ -tex engine, it is based on `\ifcsname`, which is more efficient, and does not waste

¹This code is based on code presented in TUGboat vol. 12, no2, June 1991 in “An expansion Power Lemma” by Sonja Maus.

memory. Defined inside a group, to avoid `\ifcsname` being implicitly set to `\relax` by the `\csname` test.

```

56 \beginingroup
57   \gdef\bbl@ifunset#1{%
58     \expandafter\ifx\csname#1\endcsname\relax
59       \expandafter\@firstoftwo
60     \else
61       \expandafter\@secondoftwo
62     \fi}
63 \bbl@ifunset{ifcsname}%
64 {}%
65 {\gdef\bbl@ifunset#1{%
66   \ifcsname#1\endcsname
67     \expandafter\ifx\csname#1\endcsname\relax
68       \bbl@afterelse\expandafter\@firstoftwo
69     \else
70       \bbl@afterfi\expandafter\@secondoftwo
71     \fi
72   \else
73     \expandafter\@firstoftwo
74   \fi}}
75 \endgroup

```

`\bbl@ifblank` A tool from url, by Donald Arseneau, which tests if a string is empty or space. The companion macros tests if a macro is defined with some ‘real’ value, ie, not `\relax` and not empty,

```

76 \def\bbl@ifblank#1{%
77   \bbl@ifblank@i#1\@nil\@nil\@secondoftwo\@firstoftwo\@nil}
78 \long\def\bbl@ifblank@i#1#2\@nil#3#4#5\@nil#4}
79 \def\bbl@ifset#1#2#3{%
80   \bbl@ifunset{#1}{#3}{\bbl@exp{\bbl@ifblank{\@nameuse{#1}}}{#3}{#2}}}

```

For each element in the comma separated `<key>=<value>` list, execute `<code>` with #1 and #2 as the key and the value of current item (trimmed). In addition, the item is passed verbatim as #3. With the `<key>` alone, it passes `\@empty` (ie, the macro thus named, not an empty argument, which is what you get with `<key>=` and no value).

```

81 \def\bbl@forkv#1#2{%
82   \def\bbl@kvcmd##1##2##3{#2}%
83   \bbl@kvnext#1,\@nil,}
84 \def\bbl@kvnext#1,{%
85   \ifx\@nil#1\relax\else
86     \bbl@ifblank{#1}{\bbl@forkv@eq#1=\@empty=\@nil{#1}}%
87     \expandafter\bbl@kvnext
88   \fi}
89 \def\bbl@forkv@eq#1=#2=#3\@nil#4{%
90   \bbl@trim\def\bbl@forkv@a{#1}%
91   \bbl@trim{\expandafter\bbl@kvcmd\expandafter\bbl@forkv@a}{#2}{#4}}

```

A *for* loop. Each item (trimmed) is #1. It cannot be nested (it’s doable, but we don’t need it).

```

92 \def\bbl@vforeach#1#2{%
93   \def\bbl@forcmd##1{#2}%
94   \bbl@fornext#1,\@nil,}
95 \def\bbl@fornext#1,{%
96   \ifx\@nil#1\relax\else
97     \bbl@ifblank{#1}{\bbl@trim\bbl@forcmd{#1}}%
98     \expandafter\bbl@fornext
99   \fi}
100 \def\bbl@foreach#1{\expandafter\bbl@vforeach\expandafter{#1}}

```

`\bbl@replace` Returns implicitly `\toks@` with the modified string.

```

101 \def\bbl@replace#1#2#3{% in #1 -> repl #2 by #3
102   \toks@{}}
103 \def\bbl@replace@aux##1#2##2#2{%

```

```

104 \ifx\bbl@nil##2%
105 \toks@{\expandafter{\the\toks@##1}%
106 \else
107 \toks@{\expandafter{\the\toks@##1#3}%
108 \bbl@afterfi
109 \bbl@replace@aux##2#2%
110 \fi}%
111 \expandafter\bbl@replace@aux#1#2\bbl@nil#2%
112 \edef#1{\the\toks@}}

```

An extension to the previous macro. It takes into account the parameters, and it is string based (ie, if you replace elax by ho, then \relax becomes \rho). No checking is done at all, because it is not a general purpose macro, and it is used by babel only when it works (an example where it does *not* work is in \bbl@TG@@date, and also fails if there are macros with spaces, because they are retokenized). It may change! (or even merged with \bbl@replace; I'm not sure checking the replacement is really necessary or just paranoia).

```

113 \ifx\detokenize\undefined\else % Unused macros if old Plain TeX
114 \bbl@exp{\def\\bbl@parsedef##1\detokenize{macro:}}#2->#3\relax{%
115 \def\bbl@tempa{#1}%
116 \def\bbl@tempb{#2}%
117 \def\bbl@tempe{#3}}
118 \def\bbl@sreplace#1#2#3{%
119 \begingroup
120 \expandafter\bbl@parsedef\meaning#1\relax
121 \def\bbl@tempc{#2}%
122 \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
123 \def\bbl@tempd{#3}%
124 \edef\bbl@tempd{\expandafter\strip@prefix\meaning\bbl@tempd}%
125 \bbl@xin@{\bbl@tempc}{\bbl@tempe}% If not in macro, do nothing
126 \ifin@
127 \bbl@exp{\\bbl@replace\\bbl@tempe{\bbl@tempc}{\bbl@tempd}}%
128 \def\bbl@tempc{% Expanded an executed below as 'uplevel'
129 \\makeatletter % "internal" macros with @ are assumed
130 \\scantokens{%
131 \bbl@tempa\\@namedef{\bbl@stripslash#1}\bbl@tempb{\bbl@tempe}}%
132 \catcode64=\the\catcode64\relax}% Restore @
133 \else
134 \let\bbl@tempc\empty % Not \relax
135 \fi
136 \bbl@exp{% For the 'uplevel' assignments
137 \endgroup
138 \bbl@tempc}} % empty or expand to set #1 with changes
139 \fi

```

Two further tools. \bbl@ifsamestring first expand its arguments and then compare their expansion (sanitized, so that the catcodes do not matter). \bbl@engine takes the following values: 0 is pdfTeX, 1 is luatex, and 2 is xetex. You may use the latter it in your language style if you want.

```

140 \def\bbl@ifsamestring#1#2{%
141 \begingroup
142 \protected@edef\bbl@tempb{#1}%
143 \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
144 \protected@edef\bbl@tempc{#2}%
145 \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
146 \ifx\bbl@tempb\bbl@tempc
147 \aftergroup\@firstoftwo
148 \else
149 \aftergroup\@secondoftwo
150 \fi
151 \endgroup}
152 \chardef\bbl@engine=%
153 \ifx\directlua\undefined
154 \ifx\XeTeXinputencoding\undefined
155 \z@

```

```

156 \else
157 \tw@
158 \fi
159 \else
160 \@ne
161 \fi

```

A somewhat hackish tool (hence its name) to avoid spurious spaces in some contexts.

```

162 \def\bbl@bsphack{%
163 \ifhmode
164 \hskip\z@skip
165 \def\bbl@esphack{\loop\ifdim\lastskip>\z@\unskip\repeat\unskip}%
166 \else
167 \let\bbl@esphack\@empty
168 \fi}

```

Another hackish tool, to apply case changes inside a protected macros. It's based on the internal `\let's` made by `\MakeUppercase` and `\MakeLowercase` between things like `\oe` and `\OE`.

```

169 \def\bbl@cased{%
170 \ifx\oe\OE
171 \expandafter\in@\expandafter
172 {\expandafter\OE\expandafter}\expandafter{\oe}%
173 \ifin@
174 \bbl@afterelse\expandafter\MakeUppercase
175 \else
176 \bbl@afterfi\expandafter\MakeLowercase
177 \fi
178 \else
179 \expandafter\@firstofone
180 \fi}

```

The following adds some code to `\extras...` both before and after, while avoiding doing it twice. It's somewhat convoluted, to deal with `#s`. Used to deal with `alph`, `Alph` and `frenchspacing` when there are already changes (with `\babel@save`).

```

181 \def\bbl@extras@wrap#1#2#3{% 1:in-test, 2:before, 3:after
182 \toks@\expandafter\expandafter\expandafter{%
183 \csname extras\language\endcsname}%
184 \bbl@exp{\in@{#1}}{\the\toks@}}%
185 \ifin@\else
186 \@temptokena{#2}%
187 \edef\bbl@tempc{\the\@temptokena\the\toks@}%
188 \toks@\expandafter{\bbl@tempc#3}%
189 \expandafter\edef\csname extras\language\endcsname{\the\toks@}%
190 \fi}
191 <</Basic macros>>

```

Some files identify themselves with a \TeX macro. The following code is placed before them to define (and then undefine) if not in \TeX .

```

192 <<(*Make sure ProvidesFile is defined)>> \equiv
193 \ifx\ProvidesFile\@undefined
194 \def\ProvidesFile#1[#2 #3 #4]{%
195 \wlog{File: #1 #4 #3 <#2>}%
196 \let\ProvidesFile\@undefined}
197 \fi
198 <</Make sure ProvidesFile is defined>>

```

3.1 Multiple languages

`\language` Plain \TeX version 3.0 provides the primitive `\language` that is used to store the current language. When used with a pre-3.0 version this function has to be implemented by allocating a counter. The following block is used in `switch.def` and `hyphen.cfg`; the latter may seem redundant, but remember `babel` doesn't require loading `switch.def` in the format.

```

199 <<(*Define core switching macros)>> \equiv

```



```

200 \ifx\language\@undefined
201   \csname newcount\endcsname\language
202 \fi
203 <</Define core switching macros>>

```

`\last@language` Another counter is used to keep track of the allocated languages. \TeX and \LaTeX reserves for this purpose the count 19.

`\addlanguage` This macro was introduced for $\TeX < 2$. Preserved for compatibility.

```

204 <<*Define core switching macros>> ≡
205 \countdef\last@language=19
206 \def\addlanguage{\csname newlanguage\endcsname}
207 <</Define core switching macros>>

```

Now we make sure all required files are loaded. When the command `\AtBeginDocument` doesn't exist we assume that we are dealing with a plain-based format. In that case the file `plain.def` is needed (which also defines `\AtBeginDocument`, and therefore it is not loaded twice). We need the first part when the format is created, and `\orig@dump` is used as a flag. Otherwise, we need to use the second part, so `\orig@dump` is not defined (`plain.def` undefines it). Check if the current version of `switch.def` has been previously loaded (mainly, `hyphen.cfg`). If not, load it now. We cannot load `babel.def` here because we first need to declare and process the package options.

3.2 The Package File (\LaTeX , `babel.sty`)

```

208 (*package)
209 \NeedsTeXFormat{LaTeX2e}[2005/12/01]
210 \ProvidesPackage{babel}[\<<date>> v\<<version>> The Babel package]

```

Start with some “private” debugging tool, and then define macros for errors.

```

211 \@ifpackagewith{babel}{debug}
212   {\providecommand\bbbl@trace[1]{\message{^^J[ #1 ]}}%
213    \let\bbbl@debug\@firstofone
214    \ifx\directlua\@undefined\else
215      \directlua{ Babel = Babel or {}
216        Babel.debug = true }%
217      \input{babel-debug.tex}%
218    \fi}
219 {\providecommand\bbbl@trace[1]{}%
220  \let\bbbl@debug@gobble
221  \ifx\directlua\@undefined\else
222    \directlua{ Babel = Babel or {}
223      Babel.debug = false }%
224  \fi}
225 \def\bbbl@error#1{% Implicit #2#3#4
226   \begingroup
227     \catcode`\=0 \catcode`\==12 \catcode`\`=12
228     \input errbabel.def
229   \endgroup
230   \bbbl@error{#1}}
231 \def\bbbl@warning#1{%
232   \begingroup
233     \def\{\MessageBreak}%
234     \PackageWarning{babel}{#1}%
235   \endgroup}
236 \def\bbbl@infowarn#1{%
237   \begingroup
238     \def\{\MessageBreak}%
239     \PackageNote{babel}{#1}%
240   \endgroup}
241 \def\bbbl@info#1{%
242   \begingroup
243     \def\{\MessageBreak}%
244     \PackageInfo{babel}{#1}%

```

```
245 \endgroup}
```

This file also takes care of a number of compatibility issues with other packages and defines a few additional package options. Apart from all the language options below we also have a few options that influence the behavior of language definition files.

Many of the following options don't do anything themselves, they are just defined in order to make it possible for babel and language definition files to check if one of them was specified by the user.

But first, include here the *Basic macros* defined above.

```
246 <<Basic macros>>
247 \ifpackagewith{babel}{silent}
248 {\let\bbbl@info\@gobble
249 \let\bbbl@infowarn\@gobble
250 \let\bbbl@warning\@gobble}
251 {}
252 %
253 \def\AfterBabelLanguage#1{%
254 \global\expandafter\bbbl@add\csname#1.ldf-h@k\endcsname}%
```

If the format created a list of loaded languages (in \bbbl@languages), get the name of the 0-th to show the actual language used. Also available with base, because it just shows info.

```
255 \ifx\bbbl@languages\@undefined\else
256 \begingroup
257 \catcode\^^I=12
258 \ifpackagewith{babel}{showlanguages}{%
259 \begingroup
260 \def\bbbl@elt#1#2#3#4{\wlog{#2^^I#1^^I#3^^I#4}}%
261 \wlog{<*languages>}%
262 \bbbl@languages
263 \wlog{</languages>}%
264 \endgroup}{%
265 \endgroup
266 \def\bbbl@elt#1#2#3#4{%
267 \ifnum#2=\z@
268 \gdef\bbbl@nulllanguage{#1}%
269 \def\bbbl@elt##1##2##3##4{%
270 \fi}%
271 \bbbl@languages
272 \fi%
```

3.3 base

The first 'real' option to be processed is base, which set the hyphenation patterns then resets ver@babel.sty so that \LaTeX forgets about the first loading. After a subset of babel.def has been loaded (the old switch.def) and \AfterBabelLanguage defined, it exits.

Now the base option. With it we can define (and load, with luatex) hyphenation patterns, even if we are not interested in the rest of babel.

```
273 \bbbl@trace{Defining option 'base'}
274 \ifpackagewith{babel}{base}{%
275 \let\bbbl@onlyswitch\@empty
276 \let\bbbl@provide@locale\relax
277 \input babel.def
278 \let\bbbl@onlyswitch\@undefined
279 \ifx\directlua\@undefined
280 \DeclareOption*{\bbbl@patterns{\CurrentOption}}%
281 \else
282 \input luababel.def
283 \DeclareOption*{\bbbl@patterns@lua{\CurrentOption}}%
284 \fi
285 \DeclareOption{base}{}%
286 \DeclareOption{showlanguages}{}%
287 \ProcessOptions
288 \global\expandafter\let\csname opt@babel.sty\endcsname\relax
289 \global\expandafter\let\csname ver@babel.sty\endcsname\relax
290 \global\let\@ifl@ter@@\@ifl@ter
291 \def\@ifl@ter#1#2#3#4#5{\global\let\@ifl@ter\@ifl@ter@@}%
```

```
292 \endinput}{}%
```

3.4 key=value options and other general option

The following macros extract language modifiers, and only real package options are kept in the option list. Modifiers are saved and assigned to `\BabelModifiers` at `\bbl@load@language`; when no modifiers have been given, the former is `\relax`. How modifiers are handled are left to language styles; they can use `\in@`, loop them with `\@for` or load `keyval`, for example.

```
293 \bbl@trace{key=value and another general options}
294 \bbl@csarg\let{tempa\expandafter}\csname opt@babel.sty\endcsname
295 \def\bbl@tempb#1.#2{% Remove trailing dot
296   #1\ifx\@empty#2\else,\bbl@afterfi\bbl@tempb#2\fi}%
297 \def\bbl@tempe#1=#2\@{
298   \bbl@csarg\edef{mod@#1}{\bbl@tempb#2}}
299 \def\bbl@tempd#1.#2\@nnil{% TODO. Refactor lists?
300   \ifx\@empty#2%
301     \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
302   \else
303     \in@{,provide=}{, #1}%
304     \ifin@
305       \edef\bbl@tempc{%
306         \ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.\bbl@tempb#2}%
307     \else
308       \in@{ $modifiers$ }{ $#1$ }% TODO. Allow spaces.
309       \ifin@
310         \bbl@tempe#2\@
311       \else
312         \in@{=}{ #1}%
313         \ifin@
314           \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.#2}%
315         \else
316           \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
317           \bbl@csarg\edef{mod@#1}{\bbl@tempb#2}%
318         \fi
319       \fi
320     \fi
321   \fi}
322 \let\bbl@tempc\@empty
323 \bbl@foreach\bbl@tempa{\bbl@tempd#1.\@empty\@nnil}
324 \expandafter\let\csname opt@babel.sty\endcsname\bbl@tempc
```

The next option tells babel to leave shorthand characters active at the end of processing the package. This is *not* the default as it can cause problems with other packages, but for those who want to use the shorthand characters in the preamble of their documents this can help.

```
325 \DeclareOption{KeepShorthandsActive}{}
326 \DeclareOption{activeacute}{}
327 \DeclareOption{activegrave}{}
328 \DeclareOption{debug}{}
329 \DeclareOption{noconfigs}{}
330 \DeclareOption{showlanguages}{}
331 \DeclareOption{silent}{}
332 % \DeclareOption{mono}{}
333 \DeclareOption{shorthands=off}{\bbl@tempa shorthands=\bbl@tempa}
334 \chardef\bbl@iniflag\z@
335 \DeclareOption{provide=*}{\chardef\bbl@iniflag\@ne} % main -> +1
336 \DeclareOption{provide+=*}{\chardef\bbl@iniflag\tw@} % add = 2
337 \DeclareOption{provide*=*}{\chardef\bbl@iniflag\thr@@} % add + main
338 % A separate option
339 \let\bbl@autoload@options\@empty
340 \DeclareOption{provide=@*}{\def\bbl@autoload@options{import}}
341 % Don't use. Experimental. TODO.
342 \newif\ifbbl@single
343 \DeclareOption{selectors=off}{\bbl@singletrue}
```

```
344 <<More package options>>
```

Handling of package options is done in three passes. (I [JBL] am not very happy with the idea, anyway.) The first one processes options which has been declared above or follow the syntax `<key>=<value>`, the second one loads the requested languages, except the main one if set with the key `main`, and the third one loads the latter. First, we “flag” valid keys with a nil value.

```
345 \let\bbl@opt@shorthands\@nnil
346 \let\bbl@opt@config\@nnil
347 \let\bbl@opt@main\@nnil
348 \let\bbl@opt@headfoot\@nnil
349 \let\bbl@opt@layout\@nnil
350 \let\bbl@opt@provide\@nnil
```

The following tool is defined temporarily to store the values of options.

```
351 \def\bbl@tempa#1=#2\bbl@tempa{%
352   \bbl@csarg\ifx{opt#1}\@nnil
353     \bbl@csarg\edef{opt#1}{#2}%
354   \else
355     \bbl@error{bad-package-option}{#1}{#2}{}%
356   \fi}
```

Now the option list is processed, taking into account only currently declared options (including those declared with a =), and `<key>=<value>` options (the former take precedence). Unrecognized options are saved in `\bbl@language@opts`, because they are language options.

```
357 \let\bbl@language@opts\@empty
358 \DeclareOption*{%
359   \bbl@xin@{\string=}{\CurrentOption}%
360   \ifin@
361     \expandafter\bbl@tempa\CurrentOption\bbl@tempa
362   \else
363     \bbl@add@list\bbl@language@opts{\CurrentOption}%
364   \fi}
```

Now we finish the first pass (and start over).

```
365 \ProcessOptions*
366 \ifx\bbl@opt@provide\@nnil
367   \let\bbl@opt@provide\@empty % %%% MOVE above
368 \else
369   \chardef\bbl@iniflag\@ne
370   \bbl@exp{\bbl@forkv{\@nameuse{@raw@opt@babel.sty}}}{%
371     \in@{,provide,}{, #1,}%
372     \ifin@
373       \def\bbl@opt@provide{#2}%
374       \bbl@replace\bbl@opt@provide{;}{,}%
375     \fi}
376 \fi
377 %
```

3.5 Conditional loading of shorthands

If there is no `shorthands=<chars>`, the original babel macros are left untouched, but if there is, these macros are wrapped (in `babel.def`) to define only those given.

A bit of optimization: if there is no `shorthands=`, then `\bbl@ifshorthand` is always true, and it is always false if `shorthands` is empty. Also, some code makes sense only with `shorthands=...`

```
378 \bbl@trace{Conditional loading of shorthands}
379 \def\bbl@sh@string#1{%
380   \ifx#1\@empty\else
381     \ifx#1t\string~%
382     \else\ifx#1c\string,%
383     \else\string#1%
384   \fi\fi
385   \expandafter\bbl@sh@string
386 \fi}
```

```

387 \ifx\bbbl@opt@shorthands\@nnil
388   \def\bbbl@ifshorthand#1#2#3{#2}%
389 \else\ifx\bbbl@opt@shorthands\@empty
390   \def\bbbl@ifshorthand#1#2#3{#3}%
391 \else

```

The following macro tests if a shorthand is one of the allowed ones.

```

392   \def\bbbl@ifshorthand#1{%
393     \bbbl@xin@\string#1}{\bbbl@opt@shorthands}%
394     \ifin@
395     \expandafter\@firstoftwo
396   \else
397     \expandafter\@secondoftwo
398   \fi}

```

We make sure all chars in the string are ‘other’, with the help of an auxiliary macro defined above (which also zaps spaces).

```

399   \edef\bbbl@opt@shorthands{%
400     \expandafter\bbbl@sh@string\bbbl@opt@shorthands\@empty}%

```

The following is ignored with shorthands=off, since it is intended to take some additional actions for certain chars.

```

401   \bbbl@ifshorthand{'}%
402     {\PassOptionsToPackage{activeacute}{babel}}{}
403   \bbbl@ifshorthand{`}%
404     {\PassOptionsToPackage{activegrave}{babel}}{}
405 \fi\fi

```

With headfoot=lang we can set the language used in heads/foots. For example, in babel/3796 just add headfoot=english. It misuses \@resetactivechars, but seems to work.

```

406 \ifx\bbbl@opt@headfoot\@nnil\else
407   \g@addto@macro\@resetactivechars{%
408     \set@typeset@protect
409     \expandafter\select@language\x\expandafter{\bbbl@opt@headfoot}%
410     \let\protect\noexpand}
411 \fi

```

For the option safe we use a different approach – \bbbl@opt@safe says which macros are redefined (B for bibs and R for refs). By default, both are currently set, but in a future release it will be set to none.

```

412 \ifx\bbbl@opt@safe\@undefined
413   \def\bbbl@opt@safe{BR}
414   % \let\bbbl@opt@safe\@empty % Pending of \cite
415 \fi

```

For layout an auxiliary macro is provided, available for packages and language styles. Optimization: if there is no layout, just do nothing.

```

416 \bbbl@trace{Defining IfBabelLayout}
417 \ifx\bbbl@opt@layout\@nnil
418   \newcommand\IfBabelLayout[3]{#3}%
419 \else
420   \bbbl@exp{\bbbl@forkv{\@nameuse{@raw@opt@babel.sty}}}{%
421     \in{, layout, },{, #1, }%
422     \ifin@
423       \def\bbbl@opt@layout{#2}%
424       \bbbl@replace\bbbl@opt@layout{ }{.}%
425     \fi}
426   \newcommand\IfBabelLayout[1]{%
427     \@expandtwoargs\in{.#1.}{.\bbbl@opt@layout.}%
428     \ifin@
429       \expandafter\@firstoftwo
430     \else
431       \expandafter\@secondoftwo
432     \fi}
433 \fi
434 </package>
435 <*core>

```

3.6 Interlude for Plain

Because of the way docstrip works, we need to insert some code for Plain here. However, the tools provided by the babel installer for literate programming makes this section a short interlude, because the actual code is below, tagged as *Emulate LaTeX*.

```
436 \ifx\ldf@quit\undefined\else
437 \endinput\fi % Same line!
438 <<Make sure ProvidesFile is defined>>
439 \ProvidesFile{babel.def}[\<date>] v\<version> Babel common definitions]
440 \ifx\AtBeginDocument\undefined % TODO. change test.
441 <<Emulate LaTeX>>
442 \fi
443 <<Basic macros>>
```

That is all for the moment. Now follows some common stuff, for both Plain and \TeX . After it, we will resume the \TeX -only stuff.

```
444 </core>
445 <*package | core>
```

4 Multiple languages

This is not a separate file (switch.def) anymore.

Plain \TeX version 3.0 provides the primitive `\language` that is used to store the current language. When used with a pre-3.0 version this function has to be implemented by allocating a counter.

```
446 \def\bbbl@version{\<version>}
447 \def\bbbl@date{\<date>}
448 <<Define core switching macros>>
```

`\adddialect` The macro `\adddialect` can be used to add the name of a dialect or variant language, for which an already defined hyphenation table can be used.

```
449 \def\adddialect#1#2{%
450   \global\chardef#1#2\relax
451   \bbbl@usehooks{adddialect}{\#1}{\#2}}%
452   \begingroup
453     \count@#1\relax
454     \def\bbbl@elt##1##2###3###4{%
455       \ifnum\count@=##2\relax
456         \edef\bbbl@tempa{\expandafter\@gobbletwo\string#1}%
457         \bbbl@info{Hyphen rules for '\expandafter\@gobble\bbbl@tempa'
458                   set to \expandafter\string\csname l@##1\endcsname\\%
459                   (\string\language\the\count@). Reported}%
460         \def\bbbl@elt####1####2####3####4{%
461           \fi}%
462       \bbbl@cs{languages}%
463     \endgroup}
```

`\bbbl@iflanguage` executes code only if the language `l@` exists. Otherwise raises an error. The argument of `\bbbl@fixname` has to be a macro name, as it may get “fixed” if casing (lc/uc) is wrong. It’s an attempt to fix a long-standing bug when `\foreignlanguage` and the like appear in a `\MakeXXXcase`. However, a lowercase form is not imposed to improve backward compatibility (perhaps you defined a language named MYLANG, but unfortunately mixed case names cannot be trapped). Note `l@` is encapsulated, so that its case does not change.

```
464 \def\bbbl@fixname#1{%
465   \begingroup
466     \def\bbbl@tempe{l@}%
467     \edef\bbbl@tempd{\noexpand\@ifundefined{\noexpand\bbbl@tempe#1}}%
468     \bbbl@tempd
469     {\lowercase\expandafter{\bbbl@tempd}}%
470     {\uppercase\expandafter{\bbbl@tempd}}%
471     \@empty
472     {\edef\bbbl@tempd{\def\noexpand#1{\#1}}%
473       \uppercase\expandafter{\bbbl@tempd}}}%

```

```

474      {\edef\bbl@tempd{\def\noexpand#1{#1}}%
475       \lowercase\expandafter{\bbl@tempd}}}%
476      \@empty
477      \edef\bbl@tempd{\endgroup\def\noexpand#1{#1}}%
478      \bbl@tempd
479      \bbl@exp{\bbl@usehooks{language}{\language}{#1}}}%
480 \def\bbl@iflanguage#1{%
481   \ifundefined{l@#1}{\@nolannerr{#1}\@gobble}\@firstofone}

```

After a name has been ‘fixed’, the selectors will try to load the language. If even the fixed name is not defined, will load it on the fly, either based on its name, or if activated, its BCP47 code.

We first need a couple of macros for a simple BCP 47 look up. It also makes sure, with \bbl@bcpcase, casing is the correct one, so that sr-latn-ba becomes fr-Latn-BA. Note #4 may contain some \@empty’s, but they are eventually removed. \bbl@bcpllookup either returns the found ini or it is \relax.

```

482 \def\bbl@bcpcase#1#2#3#4\@@#5{%
483   \ifx\@empty#3%
484     \uppercase{\def#5{#1#2}}%
485   \else
486     \uppercase{\def#5{#1}}%
487     \lowercase{\edef#5{#5#2#3#4}}%
488   \fi}
489 \def\bbl@bcpllookup#1-#2-#3-#4\@@{%
490   \let\bbl@bcp\relax
491   \lowercase{\def\bbl@tempa{#1}}%
492   \ifx\@empty#2%
493     \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
494   \else\ifx\@empty#3%
495     \bbl@bcpcase#2\@empty\@empty\@@\bbl@tempb
496     \IfFileExists{babel-\bbl@tempa-\bbl@tempb.ini}%
497       {\edef\bbl@bcp{\bbl@tempa-\bbl@tempb}}%
498     {}%
499     \ifx\bbl@bcp\relax
500       \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
501     \fi
502   \else
503     \bbl@bcpcase#2\@empty\@empty\@@\bbl@tempb
504     \bbl@bcpcase#3\@empty\@empty\@@\bbl@tempc
505     \IfFileExists{babel-\bbl@tempa-\bbl@tempb-\bbl@tempc.ini}%
506       {\edef\bbl@bcp{\bbl@tempa-\bbl@tempb-\bbl@tempc}}%
507     {}%
508     \ifx\bbl@bcp\relax
509       \IfFileExists{babel-\bbl@tempa-\bbl@tempc.ini}%
510       {\edef\bbl@bcp{\bbl@tempa-\bbl@tempc}}%
511     {}%
512     \fi
513     \ifx\bbl@bcp\relax
514       \IfFileExists{babel-\bbl@tempa-\bbl@tempc.ini}%
515       {\edef\bbl@bcp{\bbl@tempa-\bbl@tempc}}%
516     {}%
517     \fi
518     \ifx\bbl@bcp\relax
519       \IfFileExists{babel-\bbl@tempa.ini}{\let\bbl@bcp\bbl@tempa}{}%
520     \fi
521   \fi\fi}
522 \let\bbl@initoload\relax
523 (-core)
524 \def\bbl@provide@locale{%
525   \ifx\babelprovide\@undefined
526     \bbl@error{base-on-the-fly}{}}}%
527   \fi
528   \let\bbl@auxname\language % Still necessary. TODO
529   \bbl@ifunset{\bbl@bcp@map@language}{}% Move uplevel??
530   {\edef\language{\@nameuse{\bbl@bcp@map@language}}}%

```

```

531 \ifbbl@bcpallowed
532   \expandafter\ifx\csname date\language\endcsname\relax
533     \expandafter
534     \bbl@bcplookup\language-\@empty-\@empty-\@empty\@
535     \ifx\bbl@bcp\relax\else % Returned by \bbl@bcplookup
536       \edef\language{\bbl@bcp@prefix\bbl@bcp}%
537       \edef\localename{\bbl@bcp@prefix\bbl@bcp}%
538       \expandafter\ifx\csname date\language\endcsname\relax
539         \let\bbl@initoload\bbl@bcp
540         \bbl@exp{\bbl@babelprovide[\bbl@autoload@bcptoptions]{\language}}%
541         \let\bbl@initoload\relax
542       \fi
543       \bbl@csarg\xdef{bcp@map@\bbl@bcp}{\localename}%
544     \fi
545   \fi
546 \fi
547 \expandafter\ifx\csname date\language\endcsname\relax
548   \IfFileExists{babel-\language.tex}%
549   {\bbl@exp{\bbl@babelprovide[\bbl@autoload@options]{\language}}}%
550   {}%
551 \fi}
552 (+core)

```

\iflanguage Users might want to test (in a private package for instance) which language is currently active. For this we provide a test macro, `\iflanguage`, that has three arguments. It checks whether the first argument is a known language. If so, it compares the first argument with the value of `\language`. Then, depending on the result of the comparison, it executes either the second or the third argument.

```

553 \def\iflanguage#1{%
554   \bbl@iflanguage{#1}%
555   \ifnum\csname l@#1\endcsname=\language
556     \expandafter\@firstoftwo
557   \else
558     \expandafter\@secondoftwo
559   \fi}}

```

4.1 Selecting the language

\selectlanguage The macro `\selectlanguage` checks whether the language is already defined before it performs its actual task, which is to update `\language` and activate language-specific definitions.

```

560 \let\bbl@select@type\z@
561 \edef\selectlanguage{%
562   \noexpand\protect
563   \expandafter\noexpand\csname selectlanguage \endcsname}

```

Because the command `\selectlanguage` could be used in a moving argument it expands to `\protect\selectlanguage`. Therefore, we have to make sure that a macro `\protect` exists. If it doesn't it is `\let` to `\relax`.

```

564 \ifx\@undefined\protect\let\protect\relax\fi

```

The following definition is preserved for backwards compatibility (eg, arabi, koma). It is related to a trick for 2.09, now discarded.

```

565 \let\xstring\string

```

Since version 3.5 babel writes entries to the auxiliary files in order to typeset table of contents etc. in the correct language environment.

\bbl@pop@language But when the language change happens *inside* a group the end of the group doesn't write anything to the auxiliary files. Therefore we need TeX's `aftergroup` mechanism to help us. The command `\aftergroup` stores the token immediately following it to be executed when the current group is closed. So we define a temporary control sequence `\bbl@pop@language` to be executed at the end of the group. It calls `\bbl@set@language` with the name of the current language as its argument.

`\bbl@language@stack` The previous solution works for one level of nesting groups, but as soon as more levels are used it is no longer adequate. For that case we need to keep track of the nested languages using a stack mechanism. This stack is called `\bbl@language@stack` and initially empty.

```
566 \def\bbl@language@stack{}
```

When using a stack we need a mechanism to push an element on the stack and to retrieve the information afterwards.

`\bbl@push@language` The stack is simply a list of languagenames, separated with a '+' sign; the push function can be simple:

```
\bbl@pop@language
567 \def\bbl@push@language{%
568   \ifx\language\@undefined\else
569     \ifx\currentgrouplevel\@undefined
570       \xdef\bbl@language@stack{\language+\bbl@language@stack}%
571     \else
572       \ifnum\currentgrouplevel=\z@
573         \xdef\bbl@language@stack{\language+}%
574       \else
575         \xdef\bbl@language@stack{\language+\bbl@language@stack}%
576       \fi
577     \fi
578   \fi}
```

Retrieving information from the stack is a little bit less simple, as we need to remove the element from the stack while storing it in the macro `\language`. For this we first define a helper function.

`\bbl@pop@lang` This macro stores its first element (which is delimited by the '+'-sign) in `\language` and stores the rest of the string in `\bbl@language@stack`.

```
579 \def\bbl@pop@lang#1+#2\@{%
580   \edef\language{#1}%
581   \xdef\bbl@language@stack{#2}}
```

The reason for the somewhat weird arrangement of arguments to the helper function is the fact it is called in the following way. This means that before `\bbl@pop@lang` is executed TeX first *expands* the stack, stored in `\bbl@language@stack`. The result of that is that the argument string of `\bbl@pop@lang` contains one or more language names, each followed by a '+'-sign (zero language names won't occur as this macro will only be called after something has been pushed on the stack).

```
582 \let\bbl@ifrestoring\@secondoftwo
583 \def\bbl@pop@language{%
584   \expandafter\bbl@pop@lang\bbl@language@stack\@
585   \let\bbl@ifrestoring\@firstoftwo
586   \expandafter\bbl@set@language\expandafter{\language}%
587   \let\bbl@ifrestoring\@secondoftwo}
```

Once the name of the previous language is retrieved from the stack, it is fed to `\bbl@set@language` to do the actual work of switching everything that needs switching.

An alternative way to identify languages (in the babel sense) with a numerical value is introduced in 3.30. This is one of the first steps for a new interface based on the concept of locale, which explains the name of `\localeid`. This means `\l@. . .` will be reserved for hyphenation patterns (so that two locales can share the same rules).

```
588 \chardef\localeid\z@
589 \def\bbl@id@last{0} % No real need for a new counter
590 \def\bbl@id@assign{%
591   \bbl@ifunset\bbl@id@\language}%
592   {\count@\bbl@id@last\relax
593     \advance\count@\@ne
594     \bbl@csarg\chardef{id@\language}\count@
595     \edef\bbl@id@last{\the\count@}%
596     \ifcase\bbl@engine\or
597       \directlua{
598         Babel = Babel or {}
599         Babel.locale_props = Babel.locale_props or {}
600         Babel.locale_props[\bbl@id@last] = {}
601         Babel.locale_props[\bbl@id@last].name = '\language'}
```

```

602     }%
603     \fi}%
604     }%
605     \chardef\localeid\bbl@cl{id@}}

```

The unprotected part of `\selectlanguage`. In case it is used as environment, declare `\endselectlanguage`, just for safety.

```

606 \expandafter\def\csname selectlanguage \endcsname#1{%
607   \ifnum\bbl@hymapsel=\@cclv\let\bbl@hymapsel\tw@\fi
608   \bbl@push@language
609   \aftergroup\bbl@pop@language
610   \bbl@set@language{#1}}
611 \let\endselectlanguage\relax

```

`\bbl@set@language` The macro `\bbl@set@language` takes care of switching the language environment *and* of writing entries on the auxiliary files. For historical reasons, language names can be either `language` or `\language`. To catch either form a trick is used, but unfortunately as a side effect the catcodes of letters in `\language` are messed up. This is a bug, but preserved for backwards compatibility. The list of auxiliary files can be extended by redefining `\BabelContentsFiles`, but make sure they are loaded inside a group (as `aux`, `toc`, `lof`, and `lot` do) or the last language of the document will remain active afterwards.

We also write a command to change the current language in the auxiliary files. `\bbl@savelastskip` is used to deal with skips before the write whatsit (as suggested by U Fischer). Adapted from `hyperref`, but it might fail, so I'll consider it a temporary hack, while I study other options (the ideal, but very likely unfeasible except perhaps in `luatex`, is to avoid the `\write` altogether when not needed).

```

612 \def\BabelContentsFiles{toc,lof,lot}
613 \def\bbl@set@language#1{% from selectlanguage, pop@
614   % The old buggy way. Preserved for compatibility.
615   \edef\language#1%
616   \ifnum\escapechar=\expandafter`\string#1\@empty
617     \else\string#1\@empty\fi}%
618   \ifcat\relax\noexpand#1%
619     \expandafter\ifx\csname date\language\endcsname\relax
620       \edef\language#1%
621       \let\localename\language
622     \else
623       \bbl@info{Using '\string\language' instead of 'language' is\\%
624         deprecated. If what you want is to use a\\%
625         macro containing the actual locale, make\\%
626         sure it does not not match any language.\\%
627         Reported}%
628       \ifx\scantokens\@undefined
629         \def\localename{??}%
630       \else
631         \scantokens\expandafter{\expandafter
632           \def\expandafter\localename\expandafter{\language}}%
633       \fi
634     \fi
635   \else
636     \def\localename#1% This one has the correct catcodes
637   \fi
638   \select@language{\language}%
639   % write to auxs
640   \expandafter\ifx\csname date\language\endcsname\relax\else
641     \if@files
642       \ifx\babel@aux\@gobbletwo\else % Set if single in the first, redundant
643         \bbl@savelastskip
644         \protected@write\@auxout{\string\babel@aux{\bbl@auxname}{}}%
645         \bbl@restorelastskip
646       \fi
647       \bbl@usehooks{write}{}%
648     \fi

```

```

649 \fi}
650 %
651 \let\bbl@restorelastskip\relax
652 \let\bbl@savelastskip\relax
653 %
654 \newif\ifbbl@bcpallowed
655 \bbl@bcpallowedfalse
656 \def\select@language#1{% from set@, babel@aux
657   \ifx\bbl@selectorname\@empty
658     \def\bbl@selectorname{select}%
659   % set hymap
660   \fi
661   \ifnum\bbl@hymapsel=\@cclv\chardef\bbl@hymapsel4\relax\fi
662   % set name
663   \edef\language#1}%
664   \bbl@fixname\language
665   % TODO. name@map must be here?
666   \bbl@provide@locale
667   \bbl@iflanguage\language{%
668     \let\bbl@select@type\z@
669     \expandafter\bbl@switch\expandafter{\language}}
670 \def\babel@aux#1#2{%
671   \select@language{#1}%
672   \bbl@foreach\BabelContentsFiles{% \relax -> don't assume vertical mode
673     \@writefile{##1}{\babel@toc{#1}{#2}\relax}}}% TODO - plain?
674 \def\babel@toc#1#2{%
675   \select@language{#1}}

```

First, check if the user asks for a known language. If so, update the value of `\language` and call `\originalTeX` to bring \TeX in a certain pre-defined state.

The name of the language is stored in the control sequence `\language`.

Then we have to *redefine* `\originalTeX` to compensate for the things that have been activated. To save memory space for the macro definition of `\originalTeX`, we construct the control sequence name for the `\noextras{lang}` command at definition time by expanding the `\csname` primitive.

Now activate the language-specific definitions. This is done by constructing the names of three macros by concatenating three words with the argument of `\selectlanguage`, and calling these macros.

The switching of the values of `\lefthyphenmin` and `\righthyphenmin` is somewhat different. First we save their current values, then we check if `\lang`hyphenmins is defined. If it is not, we set default values (2 and 3), otherwise the values in `\lang`hyphenmins will be used.

No text is supposed to be added with switching captions and date, so we remove any spurious spaces with `\bbl@bsphack` and `\bbl@esphack`.

```

676 \newif\ifbbl@usedategroup
677 \let\bbl@savextras\@empty
678 \def\bbl@switch#1{% from select@, foreign@
679   % make sure there is info for the language if so requested
680   \bbl@ensureinfo{#1}%
681   % restore
682   \originalTeX
683   \expandafter\def\expandafter\originalTeX\expandafter{%
684     \csname noextras#1\endcsname
685     \let\originalTeX\@empty
686     \babel@beginsave}%
687   \bbl@usehooks{afterreset}}}%
688   \languageshorthands{none}%
689   % set the locale id
690   \bbl@id@assign
691   % switch captions, date
692   \bbl@bsphack
693   \ifcase\bbl@select@type
694     \csname captions#1\endcsname\relax
695     \csname date#1\endcsname\relax
696   \else

```

```

697 \bbl@xin@{,captions,}{, \bbl@select@opts,}%
698 \ifin@
699 \csname captions#1\endcsname\relax
700 \fi
701 \bbl@xin@{,date,}{, \bbl@select@opts,}%
702 \ifin@ % if \foreign... within \<lang>date
703 \csname date#1\endcsname\relax
704 \fi
705 \fi
706 \bbl@esphack
707 % switch extras
708 \csname bbl@preextras@#1\endcsname
709 \bbl@usehooks{beforeextras}{}%
710 \csname extras#1\endcsname\relax
711 \bbl@usehooks{afterextras}{}%
712 % > babel-ensure
713 % > babel-sh-<short>
714 % > babel-bidi
715 % > babel-fontspec
716 \let\bbl@savextras\empty
717 % hyphenation - case mapping
718 \ifcase\bbl@opt@hyphenmap\or
719 \def\BabelLower##1##2{\lccode##1=##2\relax}%
720 \ifnum\bbl@hymapsel>4\else
721 \csname\language\name @bbl@hyphenmap\endcsname
722 \fi
723 \chardef\bbl@opt@hyphenmap\z@
724 \else
725 \ifnum\bbl@hymapsel>\bbl@opt@hyphenmap\else
726 \csname\language\name @bbl@hyphenmap\endcsname
727 \fi
728 \fi
729 \let\bbl@hymapsel@cclv
730 % hyphenation - select rules
731 \ifnum\csname l@ \language\endcsname=\l@unhyphenated
732 \edef\bbl@tempa{u}%
733 \else
734 \edef\bbl@tempa{\bbl@cclv\lnbrk}%
735 \fi
736 % linebreaking - handle u, e, k (v in the future)
737 \bbl@xin@{/u}{/\bbl@tempa}%
738 \ifin@\else\bbl@xin@{/e}{/\bbl@tempa}\fi % elongated forms
739 \ifin@\else\bbl@xin@{/k}{/\bbl@tempa}\fi % only kashida
740 \ifin@\else\bbl@xin@{/p}{/\bbl@tempa}\fi % padding (eg, Tibetan)
741 \ifin@\else\bbl@xin@{/v}{/\bbl@tempa}\fi % variable font
742 \ifin@
743 % unhyphenated/kashida/elongated/padding = allow stretching
744 \language\l@unhyphenated
745 \babel@savevariable\emergencystretch
746 \emergencystretch\maxdimen
747 \babel@savevariable\hbadness
748 \hbadness\@M
749 \else
750 % other = select patterns
751 \bbl@patterns{#1}%
752 \fi
753 % hyphenation - mins
754 \babel@savevariable\lefthyphenmin
755 \babel@savevariable\righthyphenmin
756 \expandafter\ifx\csname #1hyphenmins\endcsname\relax
757 \set@hyphenmins\tw@\thr@@\relax
758 \else
759 \expandafter\expandafter\expandafter\set@hyphenmins

```

```

760 \csname #1hyphenmins\endcsname\relax
761 \fi
762 % reset selector name
763 \let\bbl@selectorname\@empty}

```

`otherlanguage (env.)` The `otherlanguage` environment can be used as an alternative to using the `\selectlanguage` declarative command. The `\ignorespaces` command is necessary to hide the environment when it is entered in horizontal mode.

```

764 \long\def\otherlanguage#1{%
765 \def\bbl@selectorname{other}%
766 \ifnum\bbl@hymapsel=\@cclv\let\bbl@hymapsel\thr@@\fi
767 \csname selectlanguage \endcsname{#1}%
768 \ignorespaces}

```

The `\endotherlanguage` part of the environment tries to hide itself when it is called in horizontal mode.

```

769 \long\def\endotherlanguage{\@ignoretrue\ignorespaces}

```

`otherlanguage* (env.)` The `otherlanguage` environment is meant to be used when a large part of text from a different language needs to be typeset, but without changing the translation of words such as ‘figure’. This environment makes use of `\foreign@language`.

```

770 \expandafter\def\csname otherlanguage*\endcsname{%
771 \@ifnextchar[\bbl@otherlanguage@s{\bbl@otherlanguage@s[]}}
772 \def\bbl@otherlanguage@s[#1]#2{%
773 \def\bbl@selectorname{other*}%
774 \ifnum\bbl@hymapsel=\@cclv\chardef\bbl@hymapsel4\relax\fi
775 \def\bbl@select@opts{#1}%
776 \foreign@language{#2}}

```

At the end of the environment we need to switch off the extra definitions. The grouping mechanism of the environment will take care of resetting the correct hyphenation rules and “extras”.

```

777 \expandafter\let\csname endotherlanguage*\endcsname\relax

```

`\foreignlanguage` The `\foreignlanguage` command is another substitute for the `\selectlanguage` command. This command takes two arguments, the first argument is the name of the language to use for typesetting the text specified in the second argument.

Unlike `\selectlanguage` this command doesn’t switch *everything*, it only switches the hyphenation rules and the extra definitions for the language specified. It does this within a group and assumes the `\extras<lang>` command doesn’t make any `\global` changes. The coding is very similar to part of `\selectlanguage`.

`\bbl@beforeforeign` is a trick to fix a bug in bidi texts. `\foreignlanguage` is supposed to be a ‘text’ command, and therefore it must emit a `\leavevmode`, but it does not, and therefore the indent is placed on the opposite margin. For backward compatibility, however, it is done only if a right-to-left script is requested; otherwise, it is no-op.

(3.11) `\foreignlanguage*` is a temporary, experimental macro for a few lines with a different script direction, while preserving the paragraph format (thank the braces around `\par`, things like `\hangindent` are not reset). Do not use it in production, because its semantics and its syntax may change (and very likely will, or even it could be removed altogether). Currently it enters in `vmode` and then selects the language (which in turn sets the paragraph direction).

(3.11) Also experimental are the hook `foreign` and `foreign*`. With them you can redefine `\BabelText` which by default does nothing. Its behavior is not well defined yet. So, use it in horizontal mode only if you do not want surprises.

In other words, at the beginning of a paragraph `\foreignlanguage` enters into `hmode` with the surrounding `lang`, and with `\foreignlanguage*` with the new `lang`.

```

778 \providecommand\bbl@beforeforeign{}
779 \edef\foreignlanguage{%
780 \noexpand\protect
781 \expandafter\noexpand\csname foreignlanguage \endcsname}
782 \expandafter\def\csname foreignlanguage \endcsname{%
783 \ifstar\bbl@foreign@s\bbl@foreign@x}
784 \providecommand\bbl@foreign@x[3][]{%
785 \beginngroup
786 \def\bbl@selectorname{foreign}%

```

```

787 \def\bbl@select@opts{#1}%
788 \let\BabelText\@firstofone
789 \bbl@beforeforeign
790 \foreign@language{#2}%
791 \bbl@usehooks{foreign}{}%
792 \BabelText{#3}% Now in horizontal mode!
793 \endgroup}
794 \def\bbl@foreign@s#1#2{% TODO - \shapemode, \@setpar, ?\@@par
795 \begingroup
796 {\par}%
797 \def\bbl@selectorname{foreign*}%
798 \let\bbl@select@opts\@empty
799 \let\BabelText\@firstofone
800 \foreign@language{#1}%
801 \bbl@usehooks{foreign*}{}%
802 \bbl@dirparastext
803 \BabelText{#2}% Still in vertical mode!
804 {\par}%
805 \endgroup}

```

`\foreign@language` This macro does the work for `\foreignlanguage` and the `otherlanguage*` environment. First we need to store the name of the language and check that it is a known language. Then it just calls `bbl@switch`.

```

806 \def\foreign@language#1{%
807 % set name
808 \edef\language{#1}%
809 \ifbbl@usedategroup
810 \bbl@add\bbl@select@opts{,date,}%
811 \bbl@usedategroupfalse
812 \fi
813 \bbl@fixname\language
814 % TODO. name@map here?
815 \bbl@provide@locale
816 \bbl@iflanguage\language{%
817 \let\bbl@select@type\@ne
818 \expandafter\bbl@switch\expandafter{\language}}

```

The following macro executes conditionally some code based on the selector being used.

```

819 \def\IfBabelSelectorTF#1{%
820 \bbl@xin@{,\bbl@selectorname,}{,\zap@space#1 \@empty,}%
821 \ifin@
822 \expandafter\@firstoftwo
823 \else
824 \expandafter\@secondoftwo
825 \fi}

```

`\bbl@patterns` This macro selects the hyphenation patterns by changing the `\language` register. If special hyphenation patterns are available specifically for the current font encoding, use them instead of the default.

It also sets hyphenation exceptions, but only once, because they are global (here language `\lccode's` has been set, too). `\bbl@hyphenation@` is set to relax until the very first `\babelhyphenation`, so do nothing with this value. If the exceptions for a language (by its number, not its name, so that `:ENC` is taken into account) has been set, then use `\hyphenation` with both global and language exceptions and empty the latter to mark they must not be set again.

```

826 \let\bbl@hyphlist\@empty
827 \let\bbl@hyphenation@relax
828 \let\bbl@pttnlist\@empty
829 \let\bbl@patterns@relax
830 \let\bbl@hymapsel=\@cclv
831 \def\bbl@patterns#1{%
832 \language=\expandafter\ifx\csname l@#1:f@encoding\endcsname\relax
833 \csname l@#1\endcsname
834 \edef\bbl@tempa{#1}%

```

```

835 \else
836 \csname l@#1:f@encoding\endcsname
837 \edef\bbl@tempa{#1:f@encoding}%
838 \fi
839 \@expandtwoargs\bbl@usehooks{patterns}{{#1}{\bbl@tempa}}%
840 % > luatex
841 \@ifundefined{bbl@hyphenation@}{}{% Can be \relax!
842 \begingroup
843 \bbl@xin@{,\number\language,}{,\bbl@hyphlist}%
844 \ifin@else
845 \@expandtwoargs\bbl@usehooks{hyphenation}{{#1}{\bbl@tempa}}%
846 \hyphenation{%
847 \bbl@hyphenation@
848 \@ifundefined{bbl@hyphenation@#1}%
849 \empty
850 {\space\csname bbl@hyphenation@#1\endcsname}}%
851 \xdef\bbl@hyphlist{\bbl@hyphlist\number\language,}%
852 \fi
853 \endgroup}}

```

hyphenrules (*env.*) The environment `hyphenrules` can be used to select *just* the hyphenation rules. This environment does *not* change `\language` and when the hyphenation rules specified were not loaded it has no effect. Note however, `\lccode`'s and font encodings are not set at all, so in most cases you should use `otherlanguage*`.

```

854 \def\hyphenrules#1{%
855 \edef\bbl@tempf{#1}%
856 \bbl@fixname\bbl@tempf
857 \bbl@iflanguage\bbl@tempf{%
858 \expandafter\bbl@patterns\expandafter{\bbl@tempf}%
859 \ifx\languageshorthands@undefined\else
860 \languageshorthands{none}%
861 \fi
862 \expandafter\ifx\csname\bbl@tempf hyphenmins\endcsname\relax
863 \set@hyphenmins\tw@\thr@@\relax
864 \else
865 \expandafter\expandafter\expandafter\set@hyphenmins
866 \csname\bbl@tempf hyphenmins\endcsname\relax
867 \fi}}
868 \let\endhyphenrules\empty

```

`\providehyphenmins` The macro `\providehyphenmins` should be used in the language definition files to provide a *default* setting for the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`. If the macro `\<lang>hyphenmins` is already defined this command has no effect.

```

869 \def\providehyphenmins#1#2{%
870 \expandafter\ifx\csname #1hyphenmins\endcsname\relax
871 \namedef{#1hyphenmins}{#2}%
872 \fi}

```

`\set@hyphenmins` This macro sets the values of `\lefthyphenmin` and `\righthyphenmin`. It expects two values as its argument.

```

873 \def\set@hyphenmins#1#2{%
874 \lefthyphenmin#1\relax
875 \righthyphenmin#2\relax}

```

`\ProvidesLanguage` The identification code for each file is something that was introduced in \LaTeX 2_ϵ . When the command `\ProvidesFile` does not exist, a dummy definition is provided temporarily. For use in the language definition file the command `\ProvidesLanguage` is defined by `babel`. Depending on the format, ie, on if the former is defined, we use a similar definition or not.

```

876 \ifx\ProvidesFile@undefined
877 \def\ProvidesLanguage#1[#2 #3 #4]{%
878 \wlog{Language: #1 #4 #3 <#2>}%
879 }

```

```

880 \else
881   \def\ProvidesLanguage#1{%
882     \begingroup
883     \catcode\ 10 %
884     \@makeother\/%
885     \ifnextchar[%]
886       {\@provideslanguage{#1}}{\@provideslanguage{#1}[]}
887   \def\@provideslanguage#1[#2]{%
888     \wlog{Language: #1 #2}%
889     \expandafter\edef\csname ver@#1.ldf\endcsname{#2}%
890     \endgroup}
891 \fi

```

`\originalTeX` The macro `\originalTeX` should be known to \TeX at this moment. As it has to be expandable we `\let` it to `\@empty` instead of `\relax`.

```
892 \ifx\originalTeX\undefined\let\originalTeX\@empty\fi
```

Because this part of the code can be included in a format, we make sure that the macro which initializes the save mechanism, `\babel@beginsave`, is not considered to be undefined.

```
893 \ifx\babel@beginsave\undefined\let\babel@beginsave\relax\fi
```

A few macro names are reserved for future releases of babel, which will use the concept of ‘locale’:

```

894 \providecommand\setlocale{\bbl@error{not-yet-available}}{}{}
895 \let\uselocale\setlocale
896 \let\locale\setlocale
897 \let\selectlocale\setlocale
898 \let\textlocale\setlocale
899 \let\textlanguage\setlocale
900 \let\languagegetext\setlocale

```

4.2 Errors

`\@nolanerr` The babel package will signal an error when a documents tries to select a language that hasn’t been defined earlier. When a user selects a language for which no hyphenation patterns were loaded into the format he will be given a warning about that fact. We revert to the patterns for `\language=0` in that case. In most formats that will be (US)english, but it might also be empty.

`\@noopterr` When the package was loaded without options not everything will work as expected. An error message is issued in that case.
When the format knows about `\PackageError` it must be $\TeX 2\epsilon$, so we can safely use its error handling interface. Otherwise we’ll have to ‘keep it simple’.
Infos are not written to the console, but on the other hand many people think warnings are errors, so a further message type is defined: an important info which is sent to the console.

```

901 \edef\bbl@nulllanguage{\string\language=0}
902 \def\bbl@nocaption{\protect\bbl@nocaption@i}
903 \def\bbl@nocaption@i#1#2{% 1: text to be printed 2: caption macro \langXname
904   \global\@namedef{#2}{\textbf{?#1?}}%
905   \@nameuse{#2}%
906   \edef\bbl@tempa{#1}%
907   \bbl@sreplace\bbl@tempa{name}{}}%
908   \bbl@warning{%
909     \@backslashchar#1 not set for '\language'. Please,\\%
910     define it after the language has been loaded\\%
911     (typically in the preamble) with:\\%
912     \string\setlocalecaption{\language}{\bbl@tempa}{..}\\%
913     Feel free to contribute on github.com/latex3/babel.\\%
914     Reported}}
915 \def\bbl@tentative{\protect\bbl@tentative@i}
916 \def\bbl@tentative@i#1{%
917   \bbl@warning{%
918     Some functions for '#1' are tentative.\\%
919     They might not work as expected and their behavior\\%
920     could change in the future.\\%

```



```

921     Reported}}
922 \def\nolanerr#1{\bbl@error{undefined-language}{#1}{}}
923 \def\nopatterns#1{%
924   \bbl@warning
925     {No hyphenation patterns were preloaded for\%
926     the language '#1' into the format.\%
927     Please, configure your TeX system to add them and\%
928     rebuild the format. Now I will use the patterns\%
929     preloaded for \bbl@nulllanguage\space instead}}
930 \let\bbl@usehooks\@gobbletwo
931 \ifx\bbl@onlyswitch\@empty\endinput\fi
932 % Here ended switch.def

```

Here ended the now discarded switch.def. Here also (currently) ends the base option.

```

933 \ifx\directlua\@undefined\else
934   \ifx\bbl@luapatterns\@undefined
935     \input luababel.def
936   \fi
937 \fi
938 \bbl@trace{Compatibility with language.def}
939 \ifx\bbl@languages\@undefined
940   \ifx\directlua\@undefined
941     \openin1 = language.def % TODO. Remove hardcoded number
942     \ifeof1
943       \closein1
944       \message{I couldn't find the file language.def}
945     \else
946       \closein1
947       \begingroup
948         \def\addlanguage#1#2#3#4#5{%
949           \expandafter\ifx\csname lang@#1\endcsname\relax\else
950             \global\expandafter\let\csname l@#1\expandafter\endcsname
951             \csname lang@#1\endcsname
952           \fi}%
953         \def\uselanguage#1{%
954           \input language.def
955         \endgroup
956       \fi
957     \fi
958   \chardef\l@english\z@
959 \fi

```

`\addto` It takes two arguments, a *<control sequence>* and T_EX-code to be added to the *<control sequence>*. If the *<control sequence>* has not been defined before it is defined now. The control sequence could also expand to `\relax`, in which case a circular definition results. The net result is a stack overflow. Note there is an inconsistency, because the assignment in the last branch is global.

```

960 \def\addto#1#2{%
961   \ifx#1\@undefined
962     \def#1{#2}%
963   \else
964     \ifx#1\relax
965       \def#1{#2}%
966     \else
967       {\toks@\expandafter{#1#2}%
968       \xdef#1{the\toks@}}%
969     \fi
970   \fi}

```

The macro `\initiate@active@char` below takes all the necessary actions to make its argument a shorthand character. The real work is performed once for each character. But first we define a little tool.

```

971 \def\bbl@withactive#1#2{%
972   \begingroup

```

```

973 \lccode`~=#2\relax
974 \lowercase{\endgroup#1~}}

```

`\bbl@redefine` To redefine a command, we save the old meaning of the macro. Then we redefine it to call the original macro with the ‘sanitized’ argument. The reason why we do it this way is that we don’t want to redefine the \TeX macros completely in case their definitions change (they have changed in the past). A macro named `\macro` will be saved new control sequences named `\org@macro`.

```

975 \def\bbl@redefine#1{%
976 \edef\bbl@tempa{\bbl@stripslash#1}%
977 \expandafter\let\csname org@\bbl@tempa\endcsname#1%
978 \expandafter\def\csname\bbl@tempa\endcsname}
979 \@onlypreamble\bbl@redefine

```

`\bbl@redefine@long` This version of `\babel@redefine` can be used to redefine `\long` commands such as `\ifthenelse`.

```

980 \def\bbl@redefine@long#1{%
981 \edef\bbl@tempa{\bbl@stripslash#1}%
982 \expandafter\let\csname org@\bbl@tempa\endcsname#1%
983 \long\expandafter\def\csname\bbl@tempa\endcsname}
984 \@onlypreamble\bbl@redefine@long

```

`\bbl@redefineroobust` For commands that are redefined, but which *might* be robust we need a slightly more intelligent macro. A robust command `foo` is defined to expand to `\protect\foo_`. So it is necessary to check whether `\foo_` exists. The result is that the command that is being redefined is always robust afterwards. Therefore all we need to do now is define `\foo_`.

```

985 \def\bbl@redefineroobust#1{%
986 \edef\bbl@tempa{\bbl@stripslash#1}%
987 \bbl@ifunset{\bbl@tempa\space}%
988 {\expandafter\let\csname org@\bbl@tempa\endcsname#1%
989 \bbl@exp{\def\#1{\protect<\bbl@tempa\space>}}}%
990 {\bbl@exp{\let<org@\bbl@tempa><\bbl@tempa\space>}}}%
991 \namedef{\bbl@tempa\space}}
992 \@onlypreamble\bbl@redefineroobust

```

4.3 Hooks

Admittedly, the current implementation is a somewhat simplistic and does very little to catch errors, but it is meant for developers, after all. `\bbl@usehooks` is the commands used by `babel` to execute hooks defined for an event.

```

993 \bbl@trace{Hooks}
994 \newcommand\AddBabelHook[3][[]]{%
995 \bbl@ifunset{\bbl@hk@#2}{\EnableBabelHook{#2}}}%
996 \def\bbl@tempa##1,#3=##2,##3\empty{\def\bbl@tempb{##2}}%
997 \expandafter\bbl@tempa\bbl@evargs,#3=,\@empty
998 \bbl@ifunset{\bbl@ev@#2@#3@#1}%
999 {\bbl@csarg\bbl@add{ev@#3@#1}{\bbl@elth{#2}}}%
1000 {\bbl@csarg\let{ev@#2@#3@#1}\relax}%
1001 \bbl@csarg\newcommand{ev@#2@#3@#1}{\bbl@tempb}}
1002 \newcommand\EnableBabelHook[1]{\bbl@csarg\let{hk@#1}\@firstofone}
1003 \newcommand\DisableBabelHook[1]{\bbl@csarg\let{hk@#1}\@gobble}
1004 \def\bbl@usehooks{\bbl@usehooks@lang\language}
1005 \def\bbl@usehooks@lang#1#2#3{% Test for Plain
1006 \ifx\UseHook\undefined\else\UseHook{babel/*/#2}\fi
1007 \def\bbl@elth##1{%
1008 \bbl@cs{hk@##1}{\bbl@cs{ev@##1@#2@#3}}}%
1009 \bbl@cs{ev@#2@#3}%
1010 \ifx\language\undefined\else % Test required for Plain (?)
1011 \ifx\UseHook\undefined\else\UseHook{babel/#1/#2}\fi
1012 \def\bbl@elth##1{%
1013 \bbl@cs{hk@##1}{\bbl@cs{ev@##1@#2@#1@#3}}}%
1014 \bbl@cs{ev@#2@#1}%
1015 \fi}

```

To ensure forward compatibility, arguments in hooks are set implicitly. So, if a further argument is added in the future, there is no need to change the existing code. Note events intended for `hyphen.cfg` are also loaded (just in case you need them for some reason).

```

1016 \def\bbl@evargs{,% <- don't delete this comma
1017   everylanguage=1,loadkernel=1,loadpatterns=1,loadexceptions=1,%
1018   adddialect=2,patterns=2,defaultcommands=0,encodedcommands=2,write=0,%
1019   beforeextras=0,afterextras=0,stopcommands=0,stringprocess=0,%
1020   hyphenation=2,initiateactive=3,afterreset=0,foreign=0,foreign*=0,%
1021   beforestart=0,language=2,begindocument=1}
1022 \ifx\NewHook\undefined\else % Test for Plain (?)
1023   \def\bbl@tempa#1=#2\@{\NewHook{babel/#1}}
1024   \bbl@foreach\bbl@evargs{\bbl@tempa#1\@}
1025 \fi

```

`\babelensure` The user command just parses the optional argument and creates a new macro named `\bbl@e@{language}`. We register a hook at the `afterextras` event which just executes this macro in a “complete” selection (which, if undefined, is `\relax` and does nothing). This part is somewhat involved because we have to make sure things are expanded the correct number of times. The macro `\bbl@e@{language}` contains `\bbl@ensure{(include)}{(exclude)}{(fontenc)}`, which in turn loops over the macros names in `\bbl@captionslist`, excluding (with the help of `\in@`) those in the exclude list. If the fontenc is given (and not `\relax`), the `\fontencoding` is also added. Then we loop over the include list, but if the macro already contains `\foreignlanguage`, nothing is done. Note this macro (1) is not restricted to the preamble, and (2) changes are local.

```

1026 \bbl@trace{Defining babelensure}
1027 \newcommand\babelensure[2][{}]{%
1028   \AddBabelHook{babel-ensure}{afterextras}{%
1029     \ifcase\bbl@select@type
1030       \bbl@cl{e}%
1031     \fi}%
1032   \begingroup
1033     \let\bbl@ens@include\empty
1034     \let\bbl@ens@exclude\empty
1035     \def\bbl@ens@fontenc{\relax}%
1036     \def\bbl@tempb##1{%
1037       \ifx\@empty##1\else\noexpand##1\expandafter\bbl@tempb\fi}%
1038     \edef\bbl@tempa{\bbl@tempb#1\@empty}%
1039     \def\bbl@tempb##1=##2\@{\@namedef{\bbl@ens@##1}{##2}}%
1040     \bbl@foreach\bbl@tempa{\bbl@tempb##1\@}%
1041     \def\bbl@tempc{\bbl@ensure}%
1042     \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
1043       \expandafter{\bbl@ens@include}}%
1044     \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
1045       \expandafter{\bbl@ens@exclude}}%
1046     \toks@{\expandafter{\bbl@tempc}%
1047       \bbl@exp}%
1048   \endgroup
1049   \def\<bbl@e@#2>{\the\toks@{\bbl@ens@fontenc}}}%
1050 \def\bbl@ensure#1#2#3{% 1: include 2: exclude 3: fontenc
1051   \def\bbl@tempb##1{% elt for (excluding) \bbl@captionslist list
1052     \ifx##1\undefined % 3.32 - Don't assume the macro exists
1053       \edef##1{\noexpand\bbl@nocaption
1054         {\bbl@stripslash##1}{\language\bbl@stripslash##1}}%
1055     \fi
1056     \ifx##1\@empty\else
1057       \in@{##1}{#2}%
1058     \ifin@else
1059       \bbl@ifunset{\bbl@ensure@\language}%
1060       {\bbl@exp}%
1061       \\\DeclareRobustCommand\<bbl@ensure@\language>[1]{%
1062         \\\foreignlanguage{\language}%
1063         {\ifx\relax#3\else
1064           \\\fontencoding{#3}\selectfont
1065         \fi

```

```

1066         #####1}}}%
1067     {}%
1068     \toks@\expandafter{##1}%
1069     \edef##1{%
1070         \bbl@csarg\noexpand{ensure@\language}%
1071         {\the\toks@}}%
1072     \fi
1073     \expandafter\bbl@tempb
1074     \fi}%
1075     \expandafter\bbl@tempb\bbl@captionslist\today\@empty
1076     \def\bbl@tempa##1{% elt for include list
1077         \ifx##1\@empty\else
1078             \bbl@csarg\in@{ensure@\language\expandafter}\expandafter{##1}%
1079             \ifin@\else
1080                 \bbl@tempb##1\@empty
1081             \fi
1082             \expandafter\bbl@tempa
1083         \fi}%
1084     \bbl@tempa#1\@empty}
1085 \def\bbl@captionslist{%
1086     \prefacename\refname\abstractname\bibname\chaptername\appendixname
1087     \contentsname\listfigurename\listtablename\indexname\figurename
1088     \tablename\partname\enclname\ccname\headtoname\pagename\seename
1089     \alsoname\proofname\glossaryname}

```

4.4 Setting up language files

`\LdfInit` `\LdfInit` macro takes two arguments. The first argument is the name of the language that will be defined in the language definition file; the second argument is either a control sequence or a string from which a control sequence should be constructed. The existence of the control sequence indicates that the file has been processed before.

At the start of processing a language definition file we always check the category code of the `@`-sign. We make sure that it is a ‘letter’ during the processing of the file. We also save its name as the last called option, even if not loaded.

Another character that needs to have the correct category code during processing of language definition files is the equals sign, ‘=’, because it is sometimes used in constructions with the `\let` primitive. Therefore we store its current catcode and restore it later on.

Now we check whether we should perhaps stop the processing of this file. To do this we first need to check whether the second argument that is passed to `\LdfInit` is a control sequence. We do that by looking at the first token after passing #2 through `string`. When it is equal to `\@backslashchar` we are dealing with a control sequence which we can compare with `\@undefined`.

If so, we call `\ldf@quit` to set the main language, restore the category code of the `@`-sign and call `\endinput`

When #2 was *not* a control sequence we construct one and compare it with `\relax`.

Finally we check `\originalTeX`.

```

1090 \bbl@trace{Macros for setting language files up}
1091 \def\bbl@ldfinit{%
1092     \let\bbl@screset\@empty
1093     \let\BabelStrings\bbl@opt@string
1094     \let\BabelOptions\@empty
1095     \let\BabelLanguages\relax
1096     \ifx\originalTeX\@undefined
1097         \let\originalTeX\@empty
1098     \else
1099         \originalTeX
1100     \fi}
1101 \def\LdfInit#1#2{%
1102     \chardef\atcatcode=\catcode` \@
1103     \catcode` \@=11\relax
1104     \chardef\eqcatcode=\catcode` \=
1105     \catcode` \=12\relax
1106     \expandafter\if\expandafter\@backslashchar
1107         \expandafter\@car\string#2\@nil

```

```

1108 \ifx#2\undefined\else
1109 \ldf@quit{#1}%
1110 \fi
1111 \else
1112 \expandafter\ifx\csname#2\endcsname\relax\else
1113 \ldf@quit{#1}%
1114 \fi
1115 \fi
1116 \bbl@ldfinit}

```

`\ldf@quit` This macro interrupts the processing of a language definition file.

```

1117 \def\ldf@quit#1{%
1118 \expandafter\main@language\expandafter{#1}%
1119 \catcode\@=\atcatcode \let\atcatcode\relax
1120 \catcode\==\eqcatcode \let\eqcatcode\relax
1121 \endinput}

```

`\ldf@finish` This macro takes one argument. It is the name of the language that was defined in the language definition file.

We load the local configuration file if one is present, we set the main language (taking into account that the argument might be a control sequence that needs to be expanded) and reset the category code of the @-sign.

```

1122 \def\bbl@afterldf#1{% TODO. Merge into the next macro? Unused elsewhere
1123 \bbl@afterlang
1124 \let\bbl@afterlang\relax
1125 \let\BabelModifiers\relax
1126 \let\bbl@screset\relax}%
1127 \def\ldf@finish#1{%
1128 \loadlocalcfg{#1}%
1129 \bbl@afterldf{#1}%
1130 \expandafter\main@language\expandafter{#1}%
1131 \catcode\@=\atcatcode \let\atcatcode\relax
1132 \catcode\==\eqcatcode \let\eqcatcode\relax}

```

After the preamble of the document the commands `\LdfInit`, `\ldf@quit` and `\ldf@finish` are no longer needed. Therefore they are turned into warning messages in *LT_εX*.

```

1133 \@onlypreamble\LdfInit
1134 \@onlypreamble\ldf@quit
1135 \@onlypreamble\ldf@finish

```

`\main@language` This command should be used in the various language definition files. It stores its argument in `\bbl@main@language` to be used to switch to the correct language at the beginning of the document.

```

1136 \def\main@language#1{%
1137 \def\bbl@main@language{#1}%
1138 \let\language\name\bbl@main@language % TODO. Set localename
1139 \bbl@id@assign
1140 \bbl@patterns{\language\name}}

```

We also have to make sure that some code gets executed at the beginning of the document, either when the aux file is read or, if it does not exist, when the `\AtBeginDocument` is executed. Languages do not set `\pagedir`, so we set here for the whole document to the main `\bodydir`.

```

1141 \def\bbl@beforestart{%
1142 \def\@nolanerr##1{%
1143 \bbl@warning{Undefined language '##1' in aux.\\Reported}}%
1144 \bbl@usehooks{beforestart}}}%
1145 \global\let\bbl@beforestart\relax}
1146 \AtBeginDocument{%
1147 {\@nameuse{bbl@beforestart}}% Group!
1148 \if@filesw
1149 \providecommand\babel@aux[2]{}%
1150 \immediate\write\@mainaux{%
1151 \string\providecommand\string\babel@aux[2]{}%

```

```

1152 \immediate\write\@mainaux{\string\@nameuse{bbl@beforestart}}%
1153 \fi
1154 \expandafter\selectlanguage\expandafter{\bbl@main@language}%
1155 <-core>
1156 \ifx\bbl@normalsf\@empty
1157 \ifnum\sfcodes\@.=\@m
1158 \let\normalsfcodes\frenchspacing
1159 \else
1160 \let\normalsfcodes\nonfrenchspacing
1161 \fi
1162 \else
1163 \let\normalsfcodes\bbl@normalsf
1164 \fi
1165 <+core>
1166 \ifbbl@single % must go after the line above.
1167 \renewcommand\selectlanguage[1]{}%
1168 \renewcommand\foreignlanguage[2]{#2}%
1169 \global\let\babel@aux\@gobbletwo % Also as flag
1170 \fi}
1171 <-core>
1172 \AddToHook{begindocument/before}{%
1173 \let\bbl@normalsf\normalsfcodes
1174 \let\normalsfcodes\relax} % Hack, to delay the setting
1175 <+core>
1176 \ifcase\bbl@engine\or
1177 \AtBeginDocument{\pagedir\bodydir} % TODO - a better place
1178 \fi

```

A bit of optimization. Select in heads/foots the language only if necessary.

```

1179 \def\select@language@x#1{%
1180 \ifcase\bbl@select@type
1181 \bbl@ifsamestring\language@name{#1}{\select@language{#1}}%
1182 \else
1183 \select@language{#1}%
1184 \fi}

```

4.5 Shorthands

`\bbl@add@special` The macro `\bbl@add@special` is used to add a new character (or single character control sequence) to the macro `\dospecials` (and `\@sanitize` if \TeX is used). It is used only at one place, namely when `\initiate@active@char` is called (which is ignored if the char has been made active before). Because `\@sanitize` can be undefined, we put the definition inside a conditional. Items are added to the lists without checking its existence or the original catcode. It does not hurt, but should be fixed. It's already done with `\nfss@catcodes`, added in 3.10.

```

1185 \bbl@trace{Shorhands}
1186 \def\bbl@add@special#1{% 1:a macro like \, \?, etc.
1187 \bbl@add\dospecials{\do#1}% test @sanitize = \relax, for back. compat.
1188 \bbl@ifunset{@sanitize}{\bbl@add\@sanitize{\@makeother#1}}%
1189 \ifx\nfss@catcodes\undefined\else % TODO - same for above
1190 \begingroup
1191 \catcode`#1\active
1192 \nfss@catcodes
1193 \ifnum\catcode`#1=\active
1194 \endgroup
1195 \bbl@add\nfss@catcodes{\@makeother#1}%
1196 \else
1197 \endgroup
1198 \fi
1199 \fi}

```

`\bbl@remove@special` The companion of the former macro is `\bbl@remove@special`. It removes a character from the set macros `\dospecials` and `\@sanitize`, but it is not used at all in the babel core.

```

1200 \def\bbl@remove@special#1{%
1201   \begingroup
1202     \def\x##1##2{\ifnum`#1=`##2\noexpand\@empty
1203       \else\noexpand##1\noexpand##2\fi}%
1204     \def\do{\x\do}%
1205     \def\@makeother{\x\@makeother}%
1206   \edef\x{\endgroup
1207     \def\noexpand\dospecials{\dospecials}%
1208     \expandafter\ifx\csname @sanitize\endcsname\relax\else
1209       \def\noexpand\@sanitize{\@sanitize}%
1210     \fi}%
1211   \x}

```

`\initiate@active@char` A language definition file can call this macro to make a character active. This macro takes one argument, the character that is to be made active. When the character was already active this macro does nothing. Otherwise, this macro defines the control sequence `\normal@char<char>` to expand to the character in its ‘normal state’ and it defines the active character to expand to `\normal@char<char>` by default (`<char>` being the character to be made active). Later its definition can be changed to expand to `\active@char<char>` by calling `\bbl@activate{<char>}`. For example, to make the double quote character active one could have `\initiate@active@char{"}` in a language definition file. This defines " as `\active@prefix " \active@char` (where the first " is the character with its original catcode, when the shorthand is created, and `\active@char` is a single token). In protected contexts, it expands to `\protect "` or `\noexpand "` (ie, with the original "); otherwise `\active@char` is executed. This macro in turn expands to `\normal@char` in “safe” contexts (eg, `\label`), but `\user@active` in normal “unsafe” ones. The latter search a definition in the user, language and system levels, in this order, but if none is found, `\normal@char` is used. However, a deactivated shorthand (with `\bbl@deactivate` is defined as `\active@prefix "\normal@char`).

The following macro is used to define shorthands in the three levels. It takes 4 arguments: the (string’ed) character, `\<level>@group`, `<level>@active` and `<next-level>@active` (except in system).

```

1212 \def\bbl@active@def#1#2#3#4{%
1213   \@namedef{#3#1}{%
1214     \expandafter\ifx\csname#2@sh@#1\endcsname\relax
1215       \bbl@afterelse\bbl@sh@select#2#1{#3@arg#1}{#4#1}%
1216     \else
1217       \bbl@afterfi\csname#2@sh@#1\endcsname
1218     \fi}%

```

When there is also no current-level shorthand with an argument we will check whether there is a next-level defined shorthand for this active character.

```

1219   \long\@namedef{#3@arg#1}##1{%
1220     \expandafter\ifx\csname#2@sh@#1\string##1\endcsname\relax
1221       \bbl@afterelse\csname#4#1\endcsname##1%
1222     \else
1223       \bbl@afterfi\csname#2@sh@#1\string##1\endcsname
1224     \fi}}%

```

`\initiate@active@char` calls `\initiate@active@char` with 3 arguments. All of them are the same character with different catcodes: active, other (‘string’ed) and the original one. This trick simplifies the code a lot.

```

1225 \def\initiate@active@char#1{%
1226   \bbl@ifunset{active@char\string#1}%
1227   {\bbl@withactive
1228     {\expandafter\initiate@active@char\expandafter}#1\string#1#1}%
1229   {}}

```

The very first thing to do is saving the original catcode and the original definition, even if not active, which is possible (undefined characters require a special treatment to avoid making them `\relax` and preserving some degree of protection).

```

1230 \def\@initiate@active@char#1#2#3{%
1231   \bbl@csarg\edef{oricat@#2}{\catcode`#2=\the\catcode`#2\relax}%
1232   \ifx#1\@undefined

```

```

1233 \bbl@csarg\def{oridef@#2}{\def#1{\active@prefix#1\@undefined}}%
1234 \else
1235 \bbl@csarg\let{oridef@#2}#1%
1236 \bbl@csarg\edef{oridef@#2}{%
1237 \let\noexpand#1%
1238 \expandafter\noexpand\csname bbl@oridef@@#2\endcsname}%
1239 \fi

```

If the character is already active we provide the default expansion under this shorthand mechanism. Otherwise we write a message in the transcript file, and define `\normal@char⟨char⟩` to expand to the character in its default state. If the character is mathematically active when babel is loaded (for example ') the normal expansion is somewhat different to avoid an infinite loop (but it does not prevent the loop if the mathcode is set to "8000 *a posteriori*").

```

1240 \ifx#1#3\relax
1241 \expandafter\let\csname normal@char#2\endcsname#3%
1242 \else
1243 \bbl@info{Making #2 an active character}%
1244 \ifnum\mathcode`#2=\ifodd\bbl@engine"1000000 \else"8000 \fi
1245 \@namedef{normal@char#2}{%
1246 \textormath{#3}{\csname bbl@oridef@@#2\endcsname}}%
1247 \else
1248 \@namedef{normal@char#2}{#3}%
1249 \fi

```

To prevent problems with the loading of other packages after babel we reset the catcode of the character to the original one at the end of the package and of each language file (except with `KeepShorthandsActive`). It is re-activate again at `\begin{document}`. We also need to make sure that the shorthands are active during the processing of the .aux file. Otherwise some citations may give unexpected results in the printout when a shorthand was used in the optional argument of `\bibitem` for example. Then we make it active (not strictly necessary, but done for backward compatibility).

```

1250 \bbl@restoreactive{#2}%
1251 \AtBeginDocument{%
1252 \catcode`#2\active
1253 \if@filesw
1254 \immediate\write\@mainaux{\catcode`\string#2\active}%
1255 \fi}%
1256 \expandafter\bbl@add@special\csname#2\endcsname
1257 \catcode`#2\active
1258 \fi

```

Now we have set `\normal@char⟨char⟩`, we must define `\active@char⟨char⟩`, to be executed when the character is activated. We define the first level expansion of `\active@char⟨char⟩` to check the status of the `@safe@actives` flag. If it is set to true we expand to the 'normal' version of this character, otherwise we call `\user@active⟨char⟩` to start the search of a definition in the user, language and system levels (or eventually `normal@char⟨char⟩`).

```

1259 \let\bbl@tempa\@firstoftwo
1260 \if\string^#2%
1261 \def\bbl@tempa{\noexpand\textormath}%
1262 \else
1263 \ifx\bbl@mathnormal\@undefined\else
1264 \let\bbl@tempa\bbl@mathnormal
1265 \fi
1266 \fi
1267 \expandafter\edef\csname active@char#2\endcsname{%
1268 \bbl@tempa
1269 {\noexpand\if@safe@actives
1270 \noexpand\expandafter
1271 \expandafter\noexpand\csname normal@char#2\endcsname
1272 \noexpand\else
1273 \noexpand\expandafter
1274 \expandafter\noexpand\csname bbl@doactive#2\endcsname
1275 \noexpand\fi}%
1276 {\expandafter\noexpand\csname normal@char#2\endcsname}}%
1277 \bbl@csarg\edef{doactive#2}{%

```



```
1278 \expandafter\noexpand\csname user@active#2\endcsname}%
```

We now define the default values which the shorthand is set to when activated or deactivated. It is set to the deactivated form (globally), so that the character expands to

```
\active@prefix <char> \normal@char<char>
```

(where `\active@char<char>` is *one* control sequence!).

```
1279 \bbl@csarg\edef{active@#2}{%
1280 \noexpand\active@prefix\noexpand#1%
1281 \expandafter\noexpand\csname active@char#2\endcsname}%
1282 \bbl@csarg\edef{normal@#2}{%
1283 \noexpand\active@prefix\noexpand#1%
1284 \expandafter\noexpand\csname normal@char#2\endcsname}%
1285 \bbl@ncarg\let#1{\bbl@normal@#2}%
```

The next level of the code checks whether a user has defined a shorthand for himself with this character. First we check for a single character shorthand. If that doesn't exist we check for a shorthand with an argument.

```
1286 \bbl@active@def#2\user@group{user@active}{language@active}%
1287 \bbl@active@def#2\language@group{language@active}{system@active}%
1288 \bbl@active@def#2\system@group{system@active}{normal@char}%
```

In order to do the right thing when a shorthand with an argument is used by itself at the end of the line we provide a definition for the case of an empty argument. For that case we let the shorthand character expand to its non-active self. Also, When a shorthand combination such as `'` ends up in a heading \TeX would see `\protect'\protect'`. To prevent this from happening a couple of shorthand needs to be defined at user level.

```
1289 \expandafter\edef\csname\user@group @sh#2@\endcsname
1290 {\expandafter\noexpand\csname normal@char#2\endcsname}%
1291 \expandafter\edef\csname\user@group @sh#2@\string\protect@\endcsname
1292 {\expandafter\noexpand\csname user@active#2\endcsname}%
```

Finally, a couple of special cases are taken care of. (1) If we are making the right quote (`'`) active we need to change `\pr@ms` as well. Also, make sure that a single `'` in math mode 'does the right thing'. (2) If we are using the caret (`^`) as a shorthand character special care should be taken to make sure math still works. Therefore an extra level of expansion is introduced with a check for math mode on the upper level.

```
1293 \if\string'#2%
1294 \let\prim@s\bbl@prim@s
1295 \let\active@math@prime#1%
1296 \fi
1297 \bbl@usehooks{initiateactive}{{#1}{#2}{#3}}}
```

The following package options control the behavior of shorthands in math mode.

```
1298 <<More package options>> ≡
1299 \DeclareOption{math=active}{}
1300 \DeclareOption{math=normal}{\def\bbl@mathnormal{\noexpand\textormath}}
1301 <</More package options>>
```

Initiating a shorthand makes active the char. That is not strictly necessary but it is still done for backward compatibility. So we need to restore the original catcode at the end of package *and* the end of the *ldf*.

```
1302 \@ifpackagewith{babel}{KeepShorthandsActive}%
1303 {\let\bbl@restoreactive@gobble}%
1304 {\def\bbl@restoreactive#1{%
1305 \bbl@exp{%
1306 \\\AfterBabelLanguage\\\CurrentOption
1307 {\catcode`#1=\the\catcode`#1\relax}%
1308 \\\AtEndOfPackage
1309 {\catcode`#1=\the\catcode`#1\relax}}}%
1310 \AtEndOfPackage{\let\bbl@restoreactive@gobble}}
```

`\bbl@sh@select` This command helps the shorthand supporting macros to select how to proceed. Note that this macro needs to be expandable as do all the shorthand macros in order for them to work in expansion-only environments such as the argument of `\hyphenation`.

This macro expects the name of a group of shorthands in its first argument and a shorthand character in its second argument. It will expand to either `\bbl@firstcs` or `\bbl@scndcs`. Hence two more arguments need to follow it.

```
1311 \def\bbl@sh@select#1#2{%
1312   \expandafter\ifx\csname#1@sh@#2@sel\endcsname\relax
1313     \bbl@afterelse\bbl@scndcs
1314   \else
1315     \bbl@afterfi\csname#1@sh@#2@sel\endcsname
1316   \fi}
```

`\active@prefix` The command `\active@prefix` which is used in the expansion of active characters has a function similar to `\OT1-cmd` in that it `\protects` the active character whenever `\protect` is *not* `\@typeset@protect`. The `\@gobble` is needed to remove a token such as `\activechar`: (when the double colon was the active character to be dealt with). There are two definitions, depending of `\ifincsn` is available. If there is, the expansion will be more robust.

```
1317 \begingroup
1318 \bbl@ifunset{ifincsn}% TODO. Ugly. Correct? Only Plain?
1319 {\gdef\active@prefix#1{%
1320   \ifx\protect\@typeset@protect
1321   \else
1322     \ifx\protect\@unexpandable@protect
1323       \noexpand#1%
1324     \else
1325       \protect#1%
1326     \fi
1327     \expandafter\@gobble
1328   \fi}}
1329 {\gdef\active@prefix#1{%
1330   \ifincsn
1331     \string#1%
1332     \expandafter\@gobble
1333   \else
1334     \ifx\protect\@typeset@protect
1335     \else
1336       \ifx\protect\@unexpandable@protect
1337         \noexpand#1%
1338       \else
1339         \protect#1%
1340       \fi
1341       \expandafter\expandafter\expandafter\@gobble
1342     \fi
1343   \fi}}
1344 \endgroup
```

`\if@safe@actives` In some circumstances it is necessary to be able to reset the shorthand to its ‘normal’ value (usually the character with catcode ‘other’) on the fly. For this purpose the switch `@safe@actives` is available. The setting of this switch should be checked in the first level expansion of `\active@char⟨char⟩`. When this expansion mode is active (with `\@safe@activestrue`), something like `"13"13` becomes `"12"12` in an `\edef` (in other words, shorthands are `\string'ed`). This contrasts with `\protected@edef`, where catcodes are always left unchanged. Once converted, they can be used safely even after this expansion mode is deactivated (with `\@safe@activefalse`).

```
1345 \newif\if@safe@actives
1346 \@safe@activefalse
```

`\bbl@restore@actives` When the output routine kicks in while the active characters were made “safe” this must be undone in the headers to prevent unexpected typeset results. For this situation we define a command to make them “unsafe” again.

```
1347 \def\bbl@restore@actives{\if@safe@actives\@safe@activefalse\fi}
```

`\bbl@activate` Both macros take one argument, like `\initiate@active@char`. The macro is used to change the definition of an active character to expand to `\active@char<char>` in the case of `\bbl@activate`, or `\normal@char<char>` in the case of `\bbl@deactivate`.

```

1348 \chardef\bbl@activated\z@
1349 \def\bbl@activate#1{%
1350   \chardef\bbl@activated\@ne
1351   \bbl@withactive{\expandafter\let\expandafter}#1%
1352     \csname bbl@active@\string#1\endcsname}
1353 \def\bbl@deactivate#1{%
1354   \chardef\bbl@activated\tw@
1355   \bbl@withactive{\expandafter\let\expandafter}#1%
1356     \csname bbl@normal@\string#1\endcsname}

```

`\bbl@firstcs` These macros are used only as a trick when declaring shorthands.

```

\bbl@scndcs
1357 \def\bbl@firstcs#1#2{\csname#1\endcsname}
1358 \def\bbl@scndcs#1#2{\csname#2\endcsname}

```

`\declare@shorthand` The command `\declare@shorthand` is used to declare a shorthand on a certain level. It takes three arguments:

1. a name for the collection of shorthands, i.e. ‘system’, or ‘dutch’;
2. the character (sequence) that makes up the shorthand, i.e. `~` or `"a`;
3. the code to be executed when the shorthand is encountered.

The auxiliary macro `\babel@texpdf` improves the interoperativity with `hyperref` and takes 4 arguments: (1) The \TeX code in text mode, (2) the string for `hyperref`, (3) the \TeX code in math mode, and (4), which is currently ignored, but it’s meant for a string in math mode, like a minus sign instead of an hyphen (currently `hyperref` doesn’t discriminate the mode). This macro may be used in `ldf` files.

```

1359 \def\babel@texpdf#1#2#3#4{%
1360   \ifx\texorpdfstring\@undefined
1361     \textormath{#1}{#3}%
1362   \else
1363     \texorpdfstring{\textormath{#1}{#3}}{#2}%
1364     % \texorpdfstring{\textormath{#1}{#3}}{\textormath{#2}{#4}}%
1365   \fi}
1366 %
1367 \def\declare@shorthand#1#2{\@decl@short{#1}#2\@nil}
1368 \def\@decl@short#1#2#3\@nil#4{%
1369   \def\bbl@tempa{#3}%
1370   \ifx\bbl@tempa\@empty
1371     \expandafter\let\csname #1@sh@\string#2@sel\endcsname\bbl@scndcs
1372     \bbl@ifunset{#1@sh@\string#2@}{}%
1373     {\def\bbl@tempa{#4}%
1374       \expandafter\ifx\csname#1@sh@\string#2@\endcsname\bbl@tempa
1375       \else
1376         \bbl@info
1377           {Redefining #1 shorthand \string#2\\%
1378            in language \CurrentOption}%
1379       \fi}%
1380     \@namedef{#1@sh@\string#2@}{#4}%
1381   \else
1382     \expandafter\let\csname #1@sh@\string#2@sel\endcsname\bbl@firstcs
1383     \bbl@ifunset{#1@sh@\string#2@\string#3@}{}%
1384     {\def\bbl@tempa{#4}%
1385       \expandafter\ifx\csname#1@sh@\string#2@\string#3@\endcsname\bbl@tempa
1386       \else
1387         \bbl@info
1388           {Redefining #1 shorthand \string#2\string#3\\%
1389            in language \CurrentOption}%
1390       \fi}%
1391     \@namedef{#1@sh@\string#2@\string#3@}{#4}%
1392   \fi}

```

`\textormath` Some of the shorthands that will be declared by the language definition files have to be usable in both text and mathmode. To achieve this the helper macro `\textormath` is provided.

```
1393 \def\textormath{%
1394   \ifmmode
1395     \expandafter\@secondoftwo
1396   \else
1397     \expandafter\@firstoftwo
1398   \fi}
```

`\user@group` The current concept of ‘shorthands’ supports three levels or groups of shorthands. For each level the name of the level or group is stored in a macro. The default is to have a user group; use language `\language@group` group ‘english’ and have a system group called ‘system’.

```
1399 \def\user@group{user}
1400 \def\language@group{english} % TODO. I don't like defaults
1401 \def\system@group{system}
```

`\useshorthands` This is the user level macro. It initializes and activates the character for use as a shorthand character (ie, it’s active in the preamble). Languages can deactivate shorthands, so a starred version is also provided which activates them always after the language has been switched.

```
1402 \def\useshorthands{%
1403   \ifstar\bb@usesh@s{\bb@usesh@x{}}
1404 \def\bb@usesh@s#1{%
1405   \bb@usesh@x
1406     {\AddBabelHook{babel-sh-\string#1}{afterextras}{\bb@activate{#1}}}%
1407     {#1}}
1408 \def\bb@usesh@x#1#2{%
1409   \bb@ifshorthand{#2}%
1410   {\def\user@group{user}%
1411     \initiate@active@char{#2}%
1412     #1%
1413     \bb@activate{#2}}%
1414   {\bb@error{shorthand-is-off}{#2}{}}}
```

`\defineshorthand` Currently we only support two groups of user level shorthands, named internally `user` and `user@<lang>` (language-dependent user shorthands). By default, only the first one is taken into account, but if the former is also used (in the optional argument of `\defineshorthand`) a new level is inserted for it (`user@generic`, done by `\bb@set@user@generic`); we make also sure `{}` and `\protect` are taken into account in this new top level.

```
1415 \def\user@language@group{user@language@group}
1416 \def\bb@set@user@generic#1#2{%
1417   \bb@ifunset{user@generic@active#1}%
1418   {\bb@active@def#1\user@language@group{user@active}{user@generic@active}%
1419     \bb@active@def#1\user@group{user@generic@active}{language@active}%
1420     \expandafter\edef\csname#2@sh@#1@\endcsname{%
1421       \expandafter\noexpand\csname normal@char#1\endcsname}%
1422     \expandafter\edef\csname#2@sh@#1@\string\protect\endcsname{%
1423       \expandafter\noexpand\csname user@active#1\endcsname}}%
1424   \@empty}
1425 \newcommand\defineshorthand[3][user]{%
1426   \edef\bb@tempa{\zap@space#1 \@empty}%
1427   \bb@for\bb@tempb\bb@tempa{%
1428     \if*\expandafter\@car\bb@tempb\@nil
1429     \edef\bb@tempb{user@\expandafter\@gobble\bb@tempb}%
1430     \@expandtwoargs
1431     \bb@set@user@generic{\expandafter\string\@car#2\@nil}\bb@tempb
1432   \fi
1433   \declare@shorthand{\bb@tempb}{#2}{#3}}}
```

`\languageshorthands` A user level command to change the language from which shorthands are used. Unfortunately, `babel` currently does not keep track of defined groups, and therefore there is no way to catch a possible change in casing to fix it in the same way languages names are fixed. [TODO].

```
1434 \def\languageshorthands#1{\def\language@group{#1}}
```

`\aliasshorthand` *Deprecated*. First the new shorthand needs to be initialized. Then, we define the new shorthand in terms of the original one, but note with `\aliasshorthands{"}{/}` is `\active@prefix /\active@char/`, so we still need to let the latter to `\active@char`.

```

1435 \def\aliasshorthand#1#2{%
1436   \bbl@ifshorthand{#2}%
1437   {\expandafter\ifx\csname active@char\string#2\endcsname\relax
1438     \ifx\document\@notprerr
1439       \@notshorthand{#2}%
1440     \else
1441       \initiate@active@char{#2}%
1442       \bbl@ccarg\let{active@char\string#2}{active@char\string#1}%
1443       \bbl@ccarg\let{normal@char\string#2}{normal@char\string#1}%
1444       \bbl@activate{#2}%
1445     \fi
1446   \fi}%
1447   {\bbl@error{shorthand-is-off}{#2}{}}}
```

`\@notshorthand`

```

1448 \def\@notshorthand#1{\bbl@error{not-a-shorthand}{#1}{}}
```

`\shorthandon` The first level definition of these macros just passes the argument on to `\bbl@switch@sh`, adding `\shorthandoff` `\@nil` at the end to denote the end of the list of characters.

```

1449 \newcommand*\shorthandon[1]{\bbl@switch@sh\@ne#1\@nnil}
1450 \DeclareRobustCommand*\shorthandoff{%
1451   \@ifstar{\bbl@shorthandoff\tw@}{\bbl@shorthandoff\z@}}
1452 \def\bbl@shorthandoff#1#2{\bbl@switch@sh#1#2\@nnil}
```

`\bbl@switch@sh` The macro `\bbl@switch@sh` takes the list of characters apart one by one and subsequently switches the category code of the shorthand character according to the first argument of `\bbl@switch@sh`. But before any of this switching takes place we make sure that the character we are dealing with is known as a shorthand character. If it is, a macro such as `\active@char` should exist. Switching off and on is easy – we just set the category code to ‘other’ (12) and `\active`. With the starred version, the original catcode and the original definition, saved in `@initiate@active@char`, are restored.

```

1453 \def\bbl@switch@sh#1#2{%
1454   \ifx#2\@nnil\else
1455     \bbl@ifunset{\bbl@active@\string#2}%
1456     {\bbl@error{not-a-shorthand-b}{#2}{}}%
1457     {\ifcase#1%   off, on, off*
1458       \catcode`#2\relax
1459     \or
1460       \catcode`#2\active
1461       \bbl@ifunset{\bbl@shdef@\string#2}%
1462       {}%
1463       {\bbl@withactive{\expandafter\let\expandafter}#2%
1464         \csname bbl@shdef@\string#2\endcsname
1465         \bbl@csarg\let{shdef@\string#2}\relax}%
1466       \ifcase\bbl@activated\or
1467         \bbl@activate{#2}%
1468       \else
1469         \bbl@deactivate{#2}%
1470       \fi
1471     \or
1472       \bbl@ifunset{\bbl@shdef@\string#2}%
1473       {\bbl@withactive{\bbl@csarg\let{shdef@\string#2}}#2%
1474       {}%
1475       \csname bbl@oricat@\string#2\endcsname
1476       \csname bbl@oridef@\string#2\endcsname
1477       \fi}%
1478     \bbl@afterfi\bbl@switch@sh#1%
1479   \fi}
```

Note the value is that at the expansion time; eg. in the preamble shorthands are usually deactivated.

```

1480 \def\babelshorthand{\active@prefix\babelshorthand\bbl@putsh}
1481 \def\bbl@putsh#1{%
1482   \bbl@ifunset{\bbl@active@\string#1}%
1483   {\bbl@putsh@i#1@empty\@nnil}%
1484   {\csname bbl@active@\string#1\endcsname}}
1485 \def\bbl@putsh@i#1#2\@nnil{%
1486   \csname\language@group @sh@\string#1@%
1487   \ifx\@empty#2\else\string#2@\fi\endcsname}
1488 %
1489 \ifx\bbl@opt@shorthands\@nnil\else
1490   \let\bbl@s@initiate@active@char\initiate@active@char
1491   \def\initiate@active@char#1{%
1492     \bbl@ifshorthand{#1}{\bbl@s@initiate@active@char{#1}}{}}
1493   \let\bbl@s@switch@sh\bbl@switch@sh
1494   \def\bbl@switch@sh#1#2{%
1495     \ifx#2\@nnil\else
1496       \bbl@afterfi
1497       \bbl@ifshorthand{#2}{\bbl@s@switch@sh#1{#2}}{\bbl@switch@sh#1}%
1498       \fi}
1499   \let\bbl@s@activate\bbl@activate
1500   \def\bbl@activate#1{%
1501     \bbl@ifshorthand{#1}{\bbl@s@activate{#1}}{}}
1502   \let\bbl@s@deactivate\bbl@deactivate
1503   \def\bbl@deactivate#1{%
1504     \bbl@ifshorthand{#1}{\bbl@s@deactivate{#1}}{}}
1505   \fi

```

You may want to test if a character is a shorthand. Note it does not test whether the shorthand is on or off.

```

1506 \newcommand\ifbabelshorthand[3]{\bbl@ifunset{\bbl@active@\string#1}{#3}{#2}}

```

`\bbl@prim@s` One of the internal macros that are involved in substituting `\prime` for each right quote in
`\bbl@pr@m@s` mathmode is `\prim@s`. This checks if the next character is a right quote. When the right quote is active, the definition of this macro needs to be adapted to look also for an active right quote; the hat could be active, too.

```

1507 \def\bbl@prim@s{%
1508   \prime\futurelet\@let@token\bbl@pr@m@s}
1509 \def\bbl@if@primes#1#2{%
1510   \ifx#1\@let@token
1511     \expandafter\@firstoftwo
1512   \else\ifx#2\@let@token
1513     \bbl@afterelse\expandafter\@firstoftwo
1514   \else
1515     \bbl@afterfi\expandafter\@secondoftwo
1516   \fi\fi}
1517 \begingroup
1518 \catcode`\^=7 \catcode`\*=\active \lccode`\*=\^
1519 \catcode`\'=12 \catcode`\"=\active \lccode`\"=\^
1520 \lowercase{%
1521   \gdef\bbl@pr@m@s{%
1522     \bbl@if@primes" '%
1523     \pr@@s
1524     {\bbl@if@primes*\^ \pr@@t\egroup}}}
1525 \endgroup

```

Usually the `~` is active and expands to `\penalty\@M\.`. When it is written to the `.aux` file it is written expanded. To prevent that and to be able to use the character `~` as a start character for a shorthand, it is redefined here as a one character shorthand on system level. The system declaration is in most cases redundant (when `~` is still a non-break space), and in some cases is inconvenient (if `~` has been redefined); however, for backward compatibility it is maintained (some existing documents may rely on the babel value).

```

1526 \initiate@active@char{~}
1527 \declare@shorthand{system}{~}{\leavevmode\nobreak\ }
1528 \bbl@activate{~}

```

\OT1dqpos The position of the double quote character is different for the OT1 and T1 encodings. It will later be selected using the \f@encoding macro. Therefore we define two macros here to store the position of the character in these encodings.

```

1529 \expandafter\def\csname OT1dqpos\endcsname{127}
1530 \expandafter\def\csname T1dqpos\endcsname{4}

```

When the macro \f@encoding is undefined (as it is in plain \TeX) we define it here to expand to OT1

```

1531 \ifx\f@encoding\@undefined
1532   \def\f@encoding{OT1}
1533 \fi

```

4.6 Language attributes

Language attributes provide a means to give the user control over which features of the language definition files he wants to enable.

\languageattribute The macro \languageattribute checks whether its arguments are valid and then activates the selected language attribute. First check whether the language is known, and then process each attribute in the list.

```

1534 \bbl@trace{Language attributes}
1535 \newcommand\languageattribute[2]{%
1536   \def\bbl@tempc{#1}%
1537   \bbl@fixname\bbl@tempc
1538   \bbl@iflanguage\bbl@tempc{%
1539     \bbl@vforeach{#2}{%

```

To make sure each attribute is selected only once, we store the already selected attributes in \bbl@known@attrs. When that control sequence is not yet defined this attribute is certainly not selected before.

```

1540     \ifx\bbl@known@attrs\@undefined
1541       \in@false
1542     \else
1543       \bbl@xin@{,\bbl@tempc-##1,}{,\bbl@known@attrs,}%
1544     \fi
1545     \ifin@
1546       \bbl@warning{%
1547         You have more than once selected the attribute '##1'\%
1548         for language #1. Reported}%
1549     \else

```

When we end up here the attribute is not selected before. So, we add it to the list of selected attributes and execute the associated \TeX -code.

```

1550       \bbl@exp{%
1551         \\bbl@add@list\\bbl@known@attrs{\bbl@tempc-##1}}%
1552       \edef\bbl@tempa{\bbl@tempc-##1}%
1553       \expandafter\bbl@ifknown@trib\expandafter{\bbl@tempa}\bbl@attributes%
1554       {\csname\bbl@tempc @attr##1\endcsname}%
1555       {\@attrerr{\bbl@tempc}{##1}}%
1556     \fi}}%
1557 \@onlypreamble\languageattribute

```

The error text to be issued when an unknown attribute is selected.

```

1558 \newcommand*{\@attrerr}[2]{%
1559   \bbl@error{unknown-attribute}{#1}{#2}{}}

```

\bbl@declare@attribute This command adds the new language/attribute combination to the list of known attributes. Then it defines a control sequence to be executed when the attribute is used in a document. The result of this should be that the macro \extras... for the current language is extended, otherwise the attribute will not work as its code is removed from memory at \begin{document}.

```

1560 \def\bbl@declare@ttribute#1#2#3{%
1561   \bbl@xin@{,#2,}{,\BabelModifiers,}%
1562   \ifin@
1563     \AfterBabelLanguage{#1}{\languageattribute{#1}{#2}}%
1564   \fi
1565   \bbl@add@list\bbl@attributes{#1-#2}%
1566   \expandafter\def\csname#1@attr@#2\endcsname{#3}}

```

`\bbl@ifattributeset` This internal macro has 4 arguments. It can be used to interpret \TeX code based on whether a certain attribute was set. This command should appear inside the argument to `\AtBeginDocument` because the attributes are set in the document preamble, *after* babel is loaded. The first argument is the language, the second argument the attribute being checked, and the third and fourth arguments are the true and false clauses.

```

1567 \def\bbl@ifattributeset#1#2#3#4{%
1568   \ifx\bbl@known@attrs\@undefined
1569     \in@false
1570   \else
1571     \bbl@xin@{,#1-#2,}{,\bbl@known@attrs,}%
1572   \fi
1573   \ifin@
1574     \bbl@afterelse#3%
1575   \else
1576     \bbl@afterfi#4%
1577   \fi}

```

`\bbl@ifknown@ttrib` An internal macro to check whether a given language/attribute is known. The macro takes 4 arguments, the language/attribute, the attribute list, the \TeX -code to be executed when the attribute is known and the \TeX -code to be executed otherwise. We first assume the attribute is unknown. Then we loop over the list of known attributes, trying to find a match.

```

1578 \def\bbl@ifknown@ttrib#1#2{%
1579   \let\bbl@tempa\@secondoftwo
1580   \bbl@loopx\bbl@tempb{#2}{%
1581     \expandafter\in@\expandafter{\expandafter,\bbl@tempb,}{,#1,}%
1582     \ifin@
1583       \let\bbl@tempa\@firstoftwo
1584     \else
1585       \fi}%
1586   \bbl@tempa}

```

`\bbl@clear@ttribs` This macro removes all the attribute code from \LaTeX 's memory at `\begin{document}` time (if any is present).

```

1587 \def\bbl@clear@ttribs{%
1588   \ifx\bbl@attributes\@undefined\else
1589     \bbl@loopx\bbl@tempa{\bbl@attributes}{%
1590       \expandafter\bbl@clear@ttrib\bbl@tempa.}%
1591     \let\bbl@attributes\@undefined
1592   \fi}
1593 \def\bbl@clear@ttrib#1-#2.{%
1594   \expandafter\let\csname#1@attr@#2\endcsname\@undefined}
1595 \AtBeginDocument{\bbl@clear@ttribs}

```

4.7 Support for saving macro definitions

To save the meaning of control sequences using `\babel@save`, we use temporary control sequences. To save hash table entries for these control sequences, we don't use the name of the control sequence to be saved to construct the temporary name. Instead we simply use the value of a counter, which is reset to zero each time we begin to save new values. This works well because we release the saved meanings before we begin to save a new set of control sequence meanings (see `\selectlanguage` and `\originalTeX`). Note undefined macros are not undefined any more when saved – they are `\relax`'ed.

`\babel@savecnt` The initialization of a new save cycle: reset the counter to zero.

`\babel@beginsave` 1596 `\bbl@trace{Macros for saving definitions}`
1597 `\def\babel@beginsave{\babel@savecnt\z@}`

Before it's forgotten, allocate the counter and initialize all.

1598 `\newcount\babel@savecnt`

1599 `\babel@beginsave`

`\babel@save` The macro `\babel@save{csname}` saves the current meaning of the control sequence `<csname>` to `\originalTeX`². To do this, we let the current meaning to a temporary control sequence, the restore commands are appended to `\originalTeX` and the counter is incremented. The macro `\babel@savevariable{variable}` saves the value of the variable. `<variable>` can be anything allowed after the `\the` primitive. To avoid messing saved definitions up, they are saved only the very first time.

```
1600 \def\babel@save#1{%
1601   \def\bbl@tempa{,{#1,}}% Clumsy, for Plain
1602   \expandafter\bbl@add\expandafter\bbl@tempa\expandafter{%
1603     \expandafter{\expandafter,\bbl@savextras,}}%
1604   \expandafter\in@\bbl@tempa
1605   \ifin@ \else
1606     \bbl@add\bbl@savextras{,{#1,}}%
1607     \bbl@carg\let{babel@\number\babel@savecnt}#1\relax
1608     \toks@\expandafter{\originalTeX\let#1=}
1609     \bbl@exp{%
1610       \def\\originalTeX{\the\toks@<babel@\number\babel@savecnt>\relax}}%
1611     \advance\babel@savecnt@ne
1612   \fi}
1613 \def\babel@savevariable#1{%
1614   \toks@\expandafter{\originalTeX #1=}
1615   \bbl@exp{\def\\originalTeX{\the\toks@the#1\relax}}}
```

`\bbl@frenchspacing` Some languages need to have `\frenchspacing` in effect. Others don't want that. The command `\bbl@nonfrenchspacing` switches it off if necessary. A more refined way to switch the catcodes is done with ini files. Here an auxiliary macro is defined, but the main part is in `\babelprovide`. This new method should be ideally the default one.

```
1616 \def\bbl@frenchspacing{%
1617   \ifnum\the\sfcode`.=\@m
1618     \let\bbl@nonfrenchspacing\relax
1619   \else
1620     \frenchspacing
1621     \let\bbl@nonfrenchspacing\nonfrenchspacing
1622   \fi}
1623 \let\bbl@nonfrenchspacing\nonfrenchspacing
1624 \let\bbl@elt\relax
1625 \edef\bbl@fs@chars{%
1626   \bbl@elt{\string.}\@m{3000}\bbl@elt{\string?}\@m{3000}%
1627   \bbl@elt{\string!}\@m{3000}\bbl@elt{\string:}\@m{2000}%
1628   \bbl@elt{\string;}\@m{1500}\bbl@elt{\string,}\@m{1250}}
1629 \def\bbl@pre@fs{%
1630   \def\bbl@elt##1##2##3{\sfcode`##1=\the\sfcode`##2\relax}%
1631   \edef\bbl@save@sfcodes{\bbl@fs@chars}%
1632 \def\bbl@post@fs{%
1633   \bbl@save@sfcodes
1634   \edef\bbl@tempa{\bbl@cl{frspc}}%
1635   \edef\bbl@tempa{\expandafter\@car\bbl@tempa\@nil}%
1636   \if u\bbl@tempa % do nothing
1637   \else\if n\bbl@tempa % non french
1638     \def\bbl@elt##1##2##3{%
1639       \ifnum\sfcode`##1=##2\relax
1640       \babel@savevariable{\sfcode`##1}%

```

²`\originalTeX` has to be expandable, i. e. you shouldn't let it to `\relax`.

```

1641     \sfcode`##1=##3\relax
1642   \fi}%
1643   \bbl@fs@chars
1644 \else\if y\bbl@tempa    % french
1645   \def\bbl@elt##1##2##3{%
1646     \ifnum\sfcode`##1=##3\relax
1647       \babel@savevariable{\sfcode`##1}%
1648       \sfcode`##1=##2\relax
1649     \fi}%
1650   \bbl@fs@chars
1651   \fi\fi\fi}

```

4.8 Short tags

`\babeltags` This macro is straightforward. After zapping spaces, we loop over the list and define the macros `\text{<tag>}` and `\<tag>`. Definitions are first expanded so that they don't contain `\csname` but the actual macro.

```

1652 \bbl@trace{Short tags}
1653 \def\babeltags#1{%
1654   \edef\bbl@tempa{\zap@space#1 \@empty}%
1655   \def\bbl@tempb##1=##2\@{ }%
1656   \edef\bbl@tempc{%
1657     \noexpand\newcommand
1658     \expandafter\noexpand\csname ##1\endcsname{%
1659       \noexpand\protect
1660       \expandafter\noexpand\csname otherlanguage*\endcsname{##2}}
1661     \noexpand\newcommand
1662     \expandafter\noexpand\csname text##1\endcsname{%
1663       \noexpand\foreignlanguage{##2}}
1664   \bbl@tempc}%
1665   \bbl@for\bbl@tempa\bbl@tempa{%
1666     \expandafter\bbl@tempb\bbl@tempa\@{ }

```

4.9 Hyphens

`\babelhyphenation` This macro saves hyphenation exceptions. Two macros are used to store them: `\bbl@hyphenation@` for the global ones and `\bbl@hyphenation<lang>` for language ones. See `\bbl@patterns` above for further details. We make sure there is a space between words when multiple commands are used.

```

1667 \bbl@trace{Hyphens}
1668 \@onlypreamble\babelhyphenation
1669 \AtEndOfPackage{%
1670   \newcommand\babelhyphenation[2][\@empty]{%
1671     \ifx\bbl@hyphenation@\relax
1672       \let\bbl@hyphenation@\@empty
1673     \fi
1674     \ifx\bbl@hyphlist\@empty\else
1675       \bbl@warning{%
1676         You must not intermingle \string\selectlanguage\space and\\%
1677         \string\babelhyphenation\space or some exceptions will not\\%
1678         be taken into account. Reported}%
1679       \fi
1680     \ifx\@empty#1%
1681       \protected@edef\bbl@hyphenation@{\bbl@hyphenation@\space#2}%
1682     \else
1683       \bbl@vforeach{#1}{%
1684         \def\bbl@tempa{##1}%
1685         \bbl@fixname\bbl@tempa
1686         \bbl@iflanguage\bbl@tempa{%
1687           \bbl@csarg\protected@edef{hyphenation@\bbl@tempa}{%
1688             \bbl@ifunset{bbl@hyphenation@\bbl@tempa}%
1689             {}%
1690             {\csname bbl@hyphenation@\bbl@tempa\endcsname\space}%

```

```

1691          #2}}}%
1692      \fi}}

```

`\bbl@allowhyphens` This macro makes hyphenation possible. Basically its definition is nothing more than `\nobreak \hskip 0pt plus 0pt`³.

```

1693 \def\bbl@allowhyphens{\ifvmode\else\nobreak\hskip\z@skip\fi}
1694 \def\bbl@t@one{Tl}
1695 \def\allowhyphens{\ifx\cf@encoding\bbl@t@one\else\bbl@allowhyphens\fi}

```

`\babelhyphen` Macros to insert common hyphens. Note the space before `@` in `\babelhyphen`. Instead of protecting it with `\DeclareRobustCommand`, which could insert a `\relax`, we use the same procedure as shorthands, with `\active@prefix`.

```

1696 \newcommand\babelnullhyphen{\char\hyphenchar\font}
1697 \def\babelhyphen{\active@prefix\babelhyphen\bbl@hyphen}
1698 \def\bbl@hyphen{%
1699   \ifstar{\bbl@hyphen@i @}{\bbl@hyphen@i \@empty}}
1700 \def\bbl@hyphen@i#1#2{%
1701   \bbl@ifunset{\bbl@hy@#1#2\@empty}%
1702     {\csname bbl@#1usehyphen\endcsname\discretionary{#2}{#{#2}}}%
1703     {\csname bbl@hy@#1#2\@empty\endcsname}}

```

The following two commands are used to wrap the “hyphen” and set the behavior of the rest of the word – the version with a single `@` is used when further hyphenation is allowed, while that with `@@` if no more hyphens are allowed. In both cases, if the hyphen is preceded by a positive space, breaking after the hyphen is disallowed.

There should not be a discretionary after a hyphen at the beginning of a word, so it is prevented if preceded by a skip. Unfortunately, this does handle cases like “(-suffix)”. `\nobreak` is always preceded by `\leavevmode`, in case the shorthand starts a paragraph.

```

1704 \def\bbl@usehyphen#1{%
1705   \leavevmode
1706   \ifdim\lastskip>\z@\mbox{#1}\else\nobreak#1\fi
1707   \nobreak\hskip\z@skip}
1708 \def\bbl@usehyphen#1{%
1709   \leavevmode\ifdim\lastskip>\z@\mbox{#1}\else#1\fi}

```

The following macro inserts the hyphen char.

```

1710 \def\bbl@hyphenchar{%
1711   \ifnum\hyphenchar\font=\m@ne
1712     \babelnullhyphen
1713   \else
1714     \char\hyphenchar\font
1715   \fi}

```

Finally, we define the hyphen “types”. Their names will not change, so you may use them in `ldf`’s. After a space, the `\mbox` in `\bbl@hy@nobreak` is redundant.

```

1716 \def\bbl@hy@soft{\bbl@usehyphen{\discretionary{\bbl@hyphenchar}{}}{}}
1717 \def\bbl@hy@@soft{\bbl@usehyphen{\discretionary{\bbl@hyphenchar}{}}{}}
1718 \def\bbl@hy@hard{\bbl@usehyphen\bbl@hyphenchar}
1719 \def\bbl@hy@@hard{\bbl@usehyphen\bbl@hyphenchar}
1720 \def\bbl@hy@nobreak{\bbl@usehyphen{\mbox{\bbl@hyphenchar}}}
1721 \def\bbl@hy@@nobreak{\mbox{\bbl@hyphenchar}}
1722 \def\bbl@hy@repeat{%
1723   \bbl@usehyphen{%
1724     \discretionary{\bbl@hyphenchar}{\bbl@hyphenchar}{\bbl@hyphenchar}}}
1725 \def\bbl@hy@@repeat{%
1726   \bbl@usehyphen{%
1727     \discretionary{\bbl@hyphenchar}{\bbl@hyphenchar}{\bbl@hyphenchar}}}
1728 \def\bbl@hy@empty{\hskip\z@skip}
1729 \def\bbl@hy@@empty{\discretionary{}{}{}}

```

`\bbl@disc` For some languages the macro `\bbl@disc` is used to ease the insertion of discretionaries for letters that behave ‘abnormally’ at a breakpoint.

```

1730 \def\bbl@disc#1#2{\nobreak\discretionary{#2-}{#{#1}}\bbl@allowhyphens}

```

³TeX begins and ends a word for hyphenation at a glue node. The penalty prevents a linebreak at this glue node.

4.10 Multiencoding strings

The aim following commands is to provide a common interface for strings in several encodings. They also contains several hooks which can be used by luatex and xetex. The code is organized here with pseudo-guards, so we start with the basic commands.

Tools But first, a tool. It makes global a local variable. This is not the best solution, but it works.

```
1731 \bbl@trace{Multiencoding strings}
1732 \def\bbl@tglobal#1{\global\let#1#1}
```

The following option is currently no-op. It was meant for the deprecated \SetCase.

```
1733 <<*More package options>> ≡
1734 \DeclareOption{nocase}{}
1735 <</More package options>>
```

The following package options control the behavior of \SetString.

```
1736 <<*More package options>> ≡
1737 \let\bbl@opt@strings\@nnil % accept strings=value
1738 \DeclareOption{strings}{\def\bbl@opt@strings{\BabelStringsDefault}}
1739 \DeclareOption{strings=encoded}{\let\bbl@opt@strings\relax}
1740 \def\BabelStringsDefault{generic}
1741 <</More package options>>
```

Main command This is the main command. With the first use it is redefined to omit the basic setup in subsequent blocks. We make sure strings contain actual letters in the range 128-255, not active characters.

```
1742 \@onlypreamble\StartBabelCommands
1743 \def\StartBabelCommands{%
1744   \begingroup
1745   \@tempcnta="7F
1746   \def\bbl@tempa{%
1747     \ifnum\@tempcnta>"FF\else
1748       \catcode\@tempcnta=11
1749       \advance\@tempcnta\@ne
1750       \expandafter\bbl@tempa
1751     \fi}%
1752   \bbl@tempa
1753   <<Macros local to BabelCommands>>
1754   \def\bbl@provstring##1##2{%
1755     \providecommand##1{##2}%
1756     \bbl@tglobal##1}%
1757   \global\let\bbl@scafter\@empty
1758   \let\StartBabelCommands\bbl@startcmds
1759   \ifx\BabelLanguages\relax
1760     \let\BabelLanguages\CurrentOption
1761   \fi
1762   \begingroup
1763   \let\bbl@screset\@nnil % local flag - disable 1st stopcommands
1764   \StartBabelCommands}
1765 \def\bbl@startcmds{%
1766   \ifx\bbl@screset\@nnil\else
1767     \bbl@usehooks{stopcommands}{}%
1768   \fi
1769   \endgroup
1770   \begingroup
1771   \@ifstar
1772     {\ifx\bbl@opt@strings\@nnil
1773       \let\bbl@opt@strings\BabelStringsDefault
1774     \fi
1775     \bbl@startcmds@i}%
1776   \bbl@startcmds@i}
1777 \def\bbl@startcmds@i#1#2{%
1778   \edef\bbl@L{\zap@space#1 \@empty}}%
```

```

1779 \edef\bbbl@G{\zap@space#2 \@empty}%
1780 \bbbl@startcmds@ii}
1781 \let\bbbl@startcommands\StartBabelCommands

```

Parse the encoding info to get the label, input, and font parts.

Select the behavior of \SetString. There are two main cases, depending of if there is an optional argument: without it and strings=encoded, strings are defined always; otherwise, they are set only if they are still undefined (ie, fallback values). With labelled blocks and strings=encoded, define the strings, but with another value, define strings only if the current label or font encoding is the value of strings; otherwise (ie, no strings or a block whose label is not in strings=) do nothing. We presume the current block is not loaded, and therefore set (above) a couple of default values to gobble the arguments. Then, these macros are redefined if necessary according to several parameters.

```

1782 \newcommand\bbbl@startcmds@ii[1][\@empty]{%
1783 \let\SetString\@gobbletwo
1784 \let\bbbl@stringdef\@gobbletwo
1785 \let\AfterBabelCommands\@gobble
1786 \ifx\@empty#1%
1787 \def\bbbl@sc@label{generic}%
1788 \def\bbbl@encstring##1##2{%
1789 \ProvideTextCommandDefault##1{##2}%
1790 \bbbl@toglobal##1%
1791 \expandafter\bbbl@toglobal\csname\string? \string##1\endcsname}%
1792 \let\bbbl@sctest\in@true
1793 \else
1794 \let\bbbl@sc@charset\space % <- zapped below
1795 \let\bbbl@sc@fontenc\space % <- " "
1796 \def\bbbl@tempa##1=##2\@nil{%
1797 \bbbl@csarg\edef{sc@ \zap@space##1 \@empty}{##2 }}%
1798 \bbbl@foreach{label=#1}{\bbbl@tempa##1\@nil}%
1799 \def\bbbl@tempa##1 ##2{% space -> comma
1800 ##1%
1801 \ifx\@empty##2\else\ifx,##1,\else,\fi\bbbl@afterfi\bbbl@tempa##2\fi}%
1802 \edef\bbbl@sc@fontenc{\expandafter\bbbl@tempa\bbbl@sc@fontenc\@empty}%
1803 \edef\bbbl@sc@label{\expandafter\zap@space\bbbl@sc@label\@empty}%
1804 \edef\bbbl@sc@charset{\expandafter\zap@space\bbbl@sc@charset\@empty}%
1805 \def\bbbl@encstring##1##2{%
1806 \bbbl@foreach\bbbl@sc@fontenc{%
1807 \bbbl@ifunset{T@####1}%
1808 {}%
1809 {\ProvideTextCommand##1{####1}{##2}%
1810 \bbbl@toglobal##1%
1811 \expandafter
1812 \bbbl@toglobal\csname####1\string##1\endcsname}}}%
1813 \def\bbbl@sctest{%
1814 \bbbl@xin@{\bbbl@opt@strings,}{\bbbl@sc@label,\bbbl@sc@fontenc,}}%
1815 \fi
1816 \ifx\bbbl@opt@strings\@nnil % ie, no strings key -> defaults
1817 \else\ifx\bbbl@opt@strings\relax % ie, strings=encoded
1818 \let\AfterBabelCommands\bbbl@aftercmds
1819 \let\SetString\bbbl@setstring
1820 \let\bbbl@stringdef\bbbl@encstring
1821 \else % ie, strings=value
1822 \bbbl@sctest
1823 \ifin@
1824 \let\AfterBabelCommands\bbbl@aftercmds
1825 \let\SetString\bbbl@setstring
1826 \let\bbbl@stringdef\bbbl@provstring
1827 \fi\fi\fi
1828 \bbbl@scswitch
1829 \ifx\bbbl@G\@empty
1830 \def\SetString##1##2{%
1831 \bbbl@error{missing-group}{##1}{}}}%

```

```

1832 \fi
1833 \ifx\@empty#1%
1834 \bbl@usehooks{defaultcommands}{}%
1835 \else
1836 \@expandtwoargs
1837 \bbl@usehooks{encodedcommands}{\bbl@sc@charset}{\bbl@sc@fontenc}}%
1838 \fi}

```

There are two versions of `\bbl@scswitch`. The first version is used when `ldfs` are read, and it makes sure `\langle group \rangle \langle language \rangle` is reset, but only once (`\bbl@screset` is used to keep track of this). The second version is used in the preamble and packages loaded after `babel` and does nothing. The macro `\bbl@forlang` loops `\bbl@L` but its body is executed only if the value is in `\BabelLanguages` (inside `babel`) or `\date \langle language \rangle` is defined (after `babel` has been loaded). There are also two version of `\bbl@forlang`. The first one skips the current iteration if the language is not in `\BabelLanguages` (used in `ldfs`), and the second one skips undefined languages (after `babel` has been loaded).

```

1839 \def\bbl@forlang#1#2{%
1840 \bbl@for#1\bbl@L{%
1841 \bbl@xin@{,#1,}{,\BabelLanguages,}%
1842 \ifin@#2\relax\fi}}
1843 \def\bbl@scswitch{%
1844 \bbl@forlang\bbl@tempa{%
1845 \ifx\bbl@G\@empty\else
1846 \ifx\SetString\gobbletwo\else
1847 \edef\bbl@GL{\bbl@G\bbl@tempa}%
1848 \bbl@xin@{,\bbl@GL,}{,\bbl@screset,}%
1849 \ifin@\else
1850 \global\expandafter\let\csname\bbl@GL\endcsname\undefined
1851 \xdef\bbl@screset{\bbl@screset,\bbl@GL}%
1852 \fi
1853 \fi
1854 \fi}}
1855 \AtEndOfPackage{%
1856 \def\bbl@forlang#1#2{\bbl@for#1\bbl@L{\bbl@ifunset{date#1}{#2}}}%
1857 \let\bbl@scswitch\relax}
1858 \onlypreamble\EndBabelCommands
1859 \def\EndBabelCommands{%
1860 \bbl@usehooks{stopcommands}{}%
1861 \endgroup
1862 \endgroup
1863 \bbl@scafter}
1864 \let\bbl@endcommands\EndBabelCommands

```

Now we define commands to be used inside `\StartBabelCommands`.

Strings The following macro is the actual definition of `\SetString` when it is “active”. First save the “switcher”. Create it if undefined. Strings are defined only if undefined (ie, like `\providescommand`). With the event `stringprocess` you can preprocess the string by manipulating the value of `\BabelString`. If there are several hooks assigned to this event, preprocessing is done in the same order as defined. Finally, the string is set.

```

1865 \def\bbl@setstring#1#2{% eg, \prefacename{<string>}
1866 \bbl@forlang\bbl@tempa{%
1867 \edef\bbl@LC{\bbl@tempa\bbl@stripslash#1}%
1868 \bbl@ifunset{\bbl@LC}% eg, \germanchaptername
1869 {\bbl@exp{%
1870 \global\\bbl@add\<\bbl@G\bbl@tempa>{\bbl@scset\\#1\<\bbl@LC>}}}%
1871 }%
1872 \def\BabelString{#2}%
1873 \bbl@usehooks{stringprocess}{}%
1874 \expandafter\bbl@stringdef
1875 \csname\bbl@LC\expandafter\endcsname\expandafter{\BabelString}}

```

A little auxiliary command sets the string. TODO: Formerly used with casing. Very likely no longer necessary, although it's used in `\setlocalecaption`.

```
1876 \def\bbl@scset#1#2{\def#1{#2}}
```

Define `\SetStringLoop`, which is actually set inside `\StartBabelCommands`. The current definition is somewhat complicated because we need a count, but `\count@` is not under our control (remember `\SetString` may call hooks). Instead of defining a dedicated count, we just “pre-expand” its value.

```
1877 <<*Macros local to BabelCommands>> ≡
1878 \def\SetStringLoop##1##2{%
1879   \def\bbl@templ####1{\expandafter\noexpand\csname##1\endcsname}%
1880   \count@\z@
1881   \bbl@loop\bbl@tempa{##2}{% empty items and spaces are ok
1882     \advance\count@\@ne
1883     \toks@\expandafter{\bbl@tempa}%
1884     \bbl@exp{%
1885       \\SetString\bbl@templ{\romannumeral\count@}{\the\toks@}%
1886       \count@=\the\count@\relax}}}%
1887 <</Macros local to BabelCommands>>
```

Delaying code Now the definition of `\AfterBabelCommands` when it is activated.

```
1888 \def\bbl@aftercmds#1{%
1889   \toks@\expandafter{\bbl@scafter#1}%
1890   \xdef\bbl@scafter{\the\toks@}}
```

Case mapping The command `\SetCase` is deprecated. Currently it consists in a definition with a hack just for backward compatibility in the macro mapping.

```
1891 <<*Macros local to BabelCommands>> ≡
1892 \newcommand\SetCase[3][]{%
1893   \def\bbl@tempa####1####2{%
1894     \ifx####1\@empty\else
1895       \bbl@carg\bbl@add{extras\CurrentOption}{%
1896         \bbl@carg\babel@save{c__text_uppercase\_string####1_tl}%
1897         \bbl@carg\def{c__text_uppercase\_string####1_tl}{####2}%
1898         \bbl@carg\babel@save{c__text_lowercase\_string####2_tl}%
1899         \bbl@carg\def{c__text_lowercase\_string####2_tl}{####1}}%
1900       \expandafter\bbl@tempa
1901       \fi}%
1902   \bbl@tempa##1\@empty\@empty
1903   \bbl@carg\bbl@toglobal{extras\CurrentOption}}%
1904 <</Macros local to BabelCommands>>
```

Macros to deal with case mapping for hyphenation. To decide if the document is monolingual or multilingual, we make a rough guess – just see if there is a comma in the languages list, built in the first pass of the package options.

```
1905 <<*Macros local to BabelCommands>> ≡
1906 \newcommand\SetHyphenMap[1]{%
1907   \bbl@forlang\bbl@tempa{%
1908     \expandafter\bbl@stringdef
1909     \csname\bbl@tempa @bbl@hyphenmap\endcsname{##1}}}%
1910 <</Macros local to BabelCommands>>
```

There are 3 helper macros which do most of the work for you.

```
1911 \newcommand\BabelLower[2]{% one to one.
1912   \ifnum\lccode#1=#2\else
1913     \babel@savevariable{\lccode#1}%
1914     \lccode#1=#2\relax
1915   \fi}
1916 \newcommand\BabelLowerMM[4]{% many-to-many
1917   \@tempcnta=#1\relax
1918   \@tempcntb=#4\relax
1919   \def\bbl@tempa{%
1920     \ifnum\@tempcnta>#2\else
1921       \@expandtwoargs\BabelLower{\the\@tempcnta}{\the\@tempcntb}%
1922       \advance\@tempcnta#3\relax
```

```

1923 \advance\@tempcntb#3\relax
1924 \expandafter\bb\@tempa
1925 \fi}%
1926 \bb\@tempa}
1927 \newcommand\BabelLowerM0[4]{% many-to-one
1928 \@tempcnta=#1\relax
1929 \def\bb\@tempa{%
1930 \ifnum\@tempcnta>#2\else
1931 \@expandtwoargs\BabelLower{\the\@tempcnta}{#4}%
1932 \advance\@tempcnta#3
1933 \expandafter\bb\@tempa
1934 \fi}%
1935 \bb\@tempa}

```

The following package options control the behavior of hyphenation mapping.

```

1936 <<*More package options>> ≡
1937 \DeclareOption{hyphenmap=off}{\chardef\bb\@opt@hyphenmap\z@}
1938 \DeclareOption{hyphenmap=first}{\chardef\bb\@opt@hyphenmap\@ne}
1939 \DeclareOption{hyphenmap=select}{\chardef\bb\@opt@hyphenmap\tw@}
1940 \DeclareOption{hyphenmap=other}{\chardef\bb\@opt@hyphenmap\thr@@}
1941 \DeclareOption{hyphenmap=other*}{\chardef\bb\@opt@hyphenmap4\relax}
1942 <</More package options>>

```

Initial setup to provide a default behavior if hyphenmap is not set.

```

1943 \AtEndOfPackage{%
1944 \ifx\bb\@opt@hyphenmap\undefined
1945 \bb\@xin@{,}{\bb\@language@opts}%
1946 \chardef\bb\@opt@hyphenmap\ifin@4\else\@ne\fi
1947 \fi}

```

This sections ends with a general tool for resetting the caption names with a unique interface. With the old way, which mixes the switcher and the string, we convert it to the new one, which separates these two steps.

```

1948 \newcommand\setlocalecaption{% TODO. Catch typos.
1949 \@ifstar\bb\@setcaption@s\bb\@setcaption@x}
1950 \def\bb\@setcaption@x#1#2#3{% language caption-name string
1951 \bb\@trim@def\bb\@tempa{#2}%
1952 \bb\@xin@{.template}{\bb\@tempa}%
1953 \ifin@
1954 \bb\@ini@captions@template{#3}{#1}%
1955 \else
1956 \edef\bb\@tempd{%
1957 \expandafter\expandafter\expandafter
1958 \strip@prefix\expandafter\meaning\csname captions#1\endcsname}%
1959 \bb\@xin@
1960 {\expandafter\string\csname #2name\endcsname}%
1961 {\bb\@tempd}%
1962 \ifin@ % Renew caption
1963 \bb\@xin@{\string\bb\@scset}{\bb\@tempd}%
1964 \ifin@
1965 \bb\@exp{%
1966 \\bb\@ifsamestring{\bb\@tempa}{\language name}%
1967 {\bb\@scset\<#2name>\<#1#2name>}%
1968 {}}%
1969 \else % Old way converts to new way
1970 \bb\@ifunset{#1#2name}%
1971 {\bb\@exp{%
1972 \\bb\@add\<captions#1>{\def\<#2name>{\<#1#2name>}}}%
1973 \\bb\@ifsamestring{\bb\@tempa}{\language name}%
1974 {\def\<#2name>{\<#1#2name>}}}%
1975 {}}}%
1976 {}%
1977 \fi
1978 \else

```



```

1979 \bbl@xin@{\string\bbl@scset}{\bbl@tempd}% New
1980 \ifin@ % New way
1981 \bbl@exp{%
1982 \\\bbl@add\<captions#1>{\bbl@scset\<#2name>\<#1#2name>}%
1983 \\\bbl@ifsamestring{\bbl@tempa}{\language\name}%
1984 {\bbl@scset\<#2name>\<#1#2name>}%
1985 }%
1986 \else % Old way, but defined in the new way
1987 \bbl@exp{%
1988 \\\bbl@add\<captions#1>{\def\<#2name>\<#1#2name>}}%
1989 \\\bbl@ifsamestring{\bbl@tempa}{\language\name}%
1990 {\def\<#2name>\<#1#2name>}}%
1991 }%
1992 \fi%
1993 \fi
1994 \@namedef{#1#2name}{#3}%
1995 \toks@{\expandafter{\bbl@captionslist}}%
1996 \bbl@exp{\in@{\<#2name>}{\the\toks@}}%
1997 \ifin@ \else
1998 \bbl@exp{\bbl@add\<captionslist>\<#2name>}}%
1999 \bbl@toглобal\bbl@captionslist
2000 \fi
2001 \fi}
2002 % \def\bbl@setcaption@#1#2#3{ % TODO. Not yet implemented (w/o 'name')

```

4.11 Macros common to a number of languages

`\set@low@box` The following macro is used to lower quotes to the same level as the comma. It prepares its argument in box register 0.

```

2003 \bbl@trace{Macros related to glyphs}
2004 \def\set@low@box#1{\setbox\tw@ \hbox{,}\setbox\z@ \hbox{#1}%
2005 \dimen\z@ \ht\z@ \advance\dimen\z@ -\ht\tw@%
2006 \setbox\z@ \hbox{\lower\dimen\z@ \box\z@}\ht\z@ \ht\tw@ \dp\z@ \dp\tw@}

```

`\save@sf@q` The macro `\save@sf@q` is used to save and reset the current space factor.

```

2007 \def\save@sf@q#1{\leavevmode
2008 \begingroup
2009 \edef\@SF{\spacefactor\the\spacefactor}#1\@SF
2010 \endgroup}

```

4.12 Making glyphs available

This section makes a number of glyphs available that either do not exist in the OT1 encoding and have to be ‘faked’, or that are not accessible through `Tlenc.def`.

4.12.1 Quotation marks

`\quotedblbase` In the T1 encoding the opening double quote at the baseline is available as a separate character, accessible via `\quotedblbase`. In the OT1 encoding it is not available, therefore we make it available by lowering the normal open quote character to the baseline.

```

2011 \ProvideTextCommand{\quotedblbase}{OT1}{%
2012 \save@sf@q{\set@low@box{\textquotedblright\}}%
2013 \box\z@\kern-.04em\bbl@allowhyphens}}

```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```

2014 \ProvideTextCommandDefault{\quotedblbase}{%
2015 \UseTextSymbol{OT1}{\quotedblbase}}

```

`\quotesinglbase` We also need the single quote character at the baseline.

```

2016 \ProvideTextCommand{\quotesinglbase}{OT1}{%
2017 \save@sf@q{\set@low@box{\textquoteright\}}%
2018 \box\z@\kern-.04em\bbl@allowhyphens}}

```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```
2019 \ProvideTextCommandDefault{\quotesinglbase}{%
2020   \UseTextSymbol{OT1}{\quotesinglbase}}
```

`\guillemetleft` The guillemet characters are not available in OT1 encoding. They are faked. (Wrong names with o
`\guillemetright` preserved for compatibility.)

```
2021 \ProvideTextCommand{\guillemetleft}{OT1}{%
2022   \ifmmode
2023     \ll
2024   \else
2025     \save@sf@q{\nobreak
2026       \raise.2ex\hbox{$\scriptscriptstyle\ll$}\bbl@allowhyphens}%
2027   \fi}
2028 \ProvideTextCommand{\guillemetright}{OT1}{%
2029   \ifmmode
2030     \gg
2031   \else
2032     \save@sf@q{\nobreak
2033       \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
2034   \fi}
2035 \ProvideTextCommand{\guillemotleft}{OT1}{%
2036   \ifmmode
2037     \ll
2038   \else
2039     \save@sf@q{\nobreak
2040       \raise.2ex\hbox{$\scriptscriptstyle\ll$}\bbl@allowhyphens}%
2041   \fi}
2042 \ProvideTextCommand{\guillemotright}{OT1}{%
2043   \ifmmode
2044     \gg
2045   \else
2046     \save@sf@q{\nobreak
2047       \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
2048   \fi}
```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```
2049 \ProvideTextCommandDefault{\guillemetleft}{%
2050   \UseTextSymbol{OT1}{\guillemetleft}}
2051 \ProvideTextCommandDefault{\guillemetright}{%
2052   \UseTextSymbol{OT1}{\guillemetright}}
2053 \ProvideTextCommandDefault{\guillemotleft}{%
2054   \UseTextSymbol{OT1}{\guillemotleft}}
2055 \ProvideTextCommandDefault{\guillemotright}{%
2056   \UseTextSymbol{OT1}{\guillemotright}}
```

`\guilsinglleft` The single guillemets are not available in OT1 encoding. They are faked.

```
\guilsinglright 2057 \ProvideTextCommand{\guilsinglleft}{OT1}{%
2058   \ifmmode
2059     <%
2060   \else
2061     \save@sf@q{\nobreak
2062       \raise.2ex\hbox{$\scriptscriptstyle<$}\bbl@allowhyphens}%
2063   \fi}
2064 \ProvideTextCommand{\guilsinglright}{OT1}{%
2065   \ifmmode
2066     >%
2067   \else
2068     \save@sf@q{\nobreak
2069       \raise.2ex\hbox{$\scriptscriptstyle>$}\bbl@allowhyphens}%
2070   \fi}
```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```
2071 \ProvideTextCommandDefault{\guilsinglleft}{%
```

```

2072 \UseTextSymbol{OT1}{\guilsinglleft}}
2073 \ProvideTextCommandDefault{\guilsinglright}{%
2074 \UseTextSymbol{OT1}{\guilsinglright}}

```

4.12.2 Letters

\ij The dutch language uses the letter ‘ij’. It is available in T1 encoded fonts, but not in the OT1 encoded \IJ fonts. Therefore we fake it for the OT1 encoding.

```

2075 \DeclareTextCommand{\ij}{OT1}{%
2076 i\kern-0.02em\bb1@allowhyphens j}
2077 \DeclareTextCommand{\IJ}{OT1}{%
2078 I\kern-0.02em\bb1@allowhyphens J}
2079 \DeclareTextCommand{\ij}{T1}{\char188}
2080 \DeclareTextCommand{\IJ}{T1}{\char156}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2081 \ProvideTextCommandDefault{\ij}{%
2082 \UseTextSymbol{OT1}{\ij}}
2083 \ProvideTextCommandDefault{\IJ}{%
2084 \UseTextSymbol{OT1}{\IJ}}

```

\dj The croatian language needs the letters \dj and \DJ; they are available in the T1 encoding, but not in \DJ the OT1 encoding by default.

Some code to construct these glyphs for the OT1 encoding was made available to me by Stipčević Mario, (stipcevic@olimp.irb.hr).

```

2085 \def\crrtic@{\hrule height0.1ex width0.3em}
2086 \def\crttic@{\hrule height0.1ex width0.33em}
2087 \def\ddj@{%
2088 \setbox0\hbox{d}\dimen@=\ht0
2089 \advance\dimen@lex
2090 \dimen@.45\dimen@
2091 \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
2092 \advance\dimen@ii.5ex
2093 \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crrtic@}}}}
2094 \def\DDJ@{%
2095 \setbox0\hbox{D}\dimen@=.55\ht0
2096 \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
2097 \advance\dimen@ii.15ex % correction for the dash position
2098 \advance\dimen@ii-.15\fontdimen7\font % correction for cmtt font
2099 \dimen\thr@@\expandafter\rem@pt\the\fontdimen7\font\dimen@
2100 \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crttic@}}}}
2101 %
2102 \DeclareTextCommand{\dj}{OT1}{\ddj@ d}
2103 \DeclareTextCommand{\DJ}{OT1}{\DDJ@ D}

```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```

2104 \ProvideTextCommandDefault{\dj}{%
2105 \UseTextSymbol{OT1}{\dj}}
2106 \ProvideTextCommandDefault{\DJ}{%
2107 \UseTextSymbol{OT1}{\DJ}}

```

\SS For the T1 encoding \SS is defined and selects a specific glyph from the font, but for other encodings it is not available. Therefore we make it available here.

```

2108 \DeclareTextCommand{\SS}{OT1}{SS}
2109 \ProvideTextCommandDefault{\SS}{\UseTextSymbol{OT1}{\SS}}

```

4.12.3 Shorthands for quotation marks

Shorthands are provided for a number of different quotation marks, which make them usable both outside and inside mathmode. They are defined with \ProvideTextCommandDefault, but this is very likely not required because their definitions are based on encoding-dependent macros.

`\glq` The ‘german’ single quotes.

```
\grq 2110 \ProvideTextCommandDefault{\glq}{%
2111   \textormath{\quotesinglbase}{\mbox{\quotesinglbase}}}
```

The definition of `\grq` depends on the fontencoding. With T1 encoding no extra kerning is needed.

```
2112 \ProvideTextCommand{\grq}{T1}{%
2113   \textormath{\kern\z@\textquoteleft}{\mbox{\textquoteleft}}}%
2114 \ProvideTextCommand{\grq}{TU}{%
2115   \textormath{\textquoteleft}{\mbox{\textquoteleft}}}%
2116 \ProvideTextCommand{\grq}{OT1}{%
2117   \save@sf@q{\kern-.0125em
2118     \textormath{\textquoteleft}{\mbox{\textquoteleft}}}%
2119     \kern.07em\relax}}
2120 \ProvideTextCommandDefault{\grq}{\UseTextSymbol{OT1}\grq}
```

`\glqq` The ‘german’ double quotes.

```
\grqq 2121 \ProvideTextCommandDefault{\glqq}{%
2122   \textormath{\quotedblbase}{\mbox{\quotedblbase}}}
```

The definition of `\grqq` depends on the fontencoding. With T1 encoding no extra kerning is needed.

```
2123 \ProvideTextCommand{\grqq}{T1}{%
2124   \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}%
2125 \ProvideTextCommand{\grqq}{TU}{%
2126   \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}%
2127 \ProvideTextCommand{\grqq}{OT1}{%
2128   \save@sf@q{\kern-.07em
2129     \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}%
2130     \kern.07em\relax}}
2131 \ProvideTextCommandDefault{\grqq}{\UseTextSymbol{OT1}\grqq}
```

`\flq` The ‘french’ single guillemets.

```
\frq 2132 \ProvideTextCommandDefault{\flq}{%
2133   \textormath{\guilsinglleft}{\mbox{\guilsinglleft}}}%
2134 \ProvideTextCommandDefault{\frq}{%
2135   \textormath{\guilsinglright}{\mbox{\guilsinglright}}}
```

`\flqq` The ‘french’ double guillemets.

```
\frqq 2136 \ProvideTextCommandDefault{\flqq}{%
2137   \textormath{\guillemetleft}{\mbox{\guillemetleft}}}%
2138 \ProvideTextCommandDefault{\frqq}{%
2139   \textormath{\guillemetright}{\mbox{\guillemetright}}}
```

4.12.4 Umlauts and tremas

The command `\` needs to have a different effect for different languages. For German for instance, the ‘umlaut’ should be positioned lower than the default position for placing it over the letters a, o, u, A, O and U. When placed over an e, i, E or I it can retain its normal position. For Dutch the same glyph is always placed in the lower position.

`\umlauthigh` To be able to provide both positions of `\` we provide two commands to switch the positioning, the
`\umlautlow` default will be `\umlauthigh` (the normal positioning).

```
2140 \def\umlauthigh{%
2141   \def\bbl@umlauta##1{\leavevmode\bgroup%
2142     \accent\csname\fontencoding dqpos\endcsname
2143     ##1\bbl@allowhyphens\egroup}%
2144   \let\bbl@umlaute\bbl@umlauta}
2145 \def\umlautlow{%
2146   \def\bbl@umlauta{\protect\lower@umlaut}}
2147 \def\umlautelow{%
2148   \def\bbl@umlaute{\protect\lower@umlaut}}
2149 \umlauthigh
```

`\lower@umlaut` The command `\lower@umlaut` is used to position the `\` closer to the letter. We want the umlaut character lowered, nearer to the letter. To do this we need an extra *(dimen)* register.

```
2150 \expandafter\ifx\csname U@D\endcsname\relax
2151   \csname newdimen\endcsname\U@D
2152 \fi
```

The following code fools \TeX 's `make_accent` procedure about the current x-height of the font to force another placement of the umlaut character. First we have to save the current x-height of the font, because we'll change this font dimension and this is always done globally.

Then we compute the new x-height in such a way that the umlaut character is lowered to the base character. The value of `.45ex` depends on the METAFONT parameters with which the fonts were built. (Just try out, which value will look best.) If the new x-height is too low, it is not changed. Finally we call the `\accent` primitive, reset the old x-height and insert the base character in the argument.

```
2153 \def\lower@umlaut#1{%
2154   \leavevmode\bgroup
2155     \U@D 1ex%
2156     {\setbox\z@\hbox{%
2157       \char\csname\fontencoding dqpos\endcsname}%
2158       \dimen@ -.45ex\advance\dimen@\ht\z@
2159       \ifdim 1ex<\dimen@ \fontdimen5\font\dimen@ \fi}%
2160     \accent\csname\fontencoding dqpos\endcsname
2161     \fontdimen5\font\U@D #1%
2162   \egroup}
```

For all vowels we declare `\` to be a composite command which uses `\bbl@umlauta` or `\bbl@umlaute` to position the umlaut character. We need to be sure that these definitions override the ones that are provided when the package `fontenc` with option `OT1` is used. Therefore these declarations are postponed until the beginning of the document. Note these definitions only apply to some languages, but `babel` sets them for *all* languages – you may want to redefine `\bbl@umlauta` and/or `\bbl@umlaute` for a language in the corresponding `ldf` (using the `babel` switching mechanism, of course).

```
2163 \AtBeginDocument{%
2164   \DeclareTextCompositeCommand{\"}{OT1}{a}{\bbl@umlauta{a}}%
2165   \DeclareTextCompositeCommand{\"}{OT1}{e}{\bbl@umlaute{e}}%
2166   \DeclareTextCompositeCommand{\"}{OT1}{i}{\bbl@umlaute{i}}%
2167   \DeclareTextCompositeCommand{\"}{OT1}{\i}{\bbl@umlaute{i}}%
2168   \DeclareTextCompositeCommand{\"}{OT1}{o}{\bbl@umlauta{o}}%
2169   \DeclareTextCompositeCommand{\"}{OT1}{u}{\bbl@umlauta{u}}%
2170   \DeclareTextCompositeCommand{\"}{OT1}{A}{\bbl@umlauta{A}}%
2171   \DeclareTextCompositeCommand{\"}{OT1}{E}{\bbl@umlaute{E}}%
2172   \DeclareTextCompositeCommand{\"}{OT1}{I}{\bbl@umlaute{I}}%
2173   \DeclareTextCompositeCommand{\"}{OT1}{O}{\bbl@umlauta{O}}%
2174   \DeclareTextCompositeCommand{\"}{OT1}{U}{\bbl@umlauta{U}}}
```

Finally, make sure the default hyphenrules are defined (even if empty). For internal use, another empty `\language` is defined. Currently used in Amharic.

```
2175 \ifx\l@english\undefined
2176   \chardef\l@english\z@
2177 \fi
2178 % The following is used to cancel rules in ini files (see Amharic).
2179 \ifx\l@unhyphenated\undefined
2180   \newlanguage\l@unhyphenated
2181 \fi
```

4.13 Layout

`Layout` is mainly intended to set bidi documents, but there is at least a tool useful in general.

```
2182 \bbl@trace{Bidi layout}
2183 \providecommand\IfBabelLayout[3]{#3}%
2184 <-core>
2185 \newcommand\BabelPatchSection[1]{%
2186   \@ifundefined{#1}{}{%
```

```

2187 \bbl@exp{\let\<bbl@ss@#1>\<#1>}%
2188 \@namedef{#1}{%
2189 \ifstar{\bbl@presec@s{#1}}%
2190 {\@dblarg{\bbl@presec@x{#1}}}}}%
2191 \def\bbl@presec@x#1[#2]#3{%
2192 \bbl@exp{%
2193 \\\select@language@x{\bbl@main@language}%
2194 \\\bbl@cs{sspre@#1}%
2195 \\\bbl@cs{ss@#1}%
2196 [\\foreignlanguage{\language}{\unexpanded{#2}}}%
2197 {\foreignlanguage{\language}{\unexpanded{#3}}}%
2198 \\\select@language@x{\language}}}%
2199 \def\bbl@presec@s#1#2{%
2200 \bbl@exp{%
2201 \\\select@language@x{\bbl@main@language}%
2202 \\\bbl@cs{sspre@#1}%
2203 \\\bbl@cs{ss@#1}*%
2204 {\foreignlanguage{\language}{\unexpanded{#2}}}%
2205 \\\select@language@x{\language}}}%
2206 \IfBabelLayout{sectioning}%
2207 {\BabelPatchSection{part}%
2208 \BabelPatchSection{chapter}%
2209 \BabelPatchSection{section}%
2210 \BabelPatchSection{subsection}%
2211 \BabelPatchSection{subsubsection}%
2212 \BabelPatchSection{paragraph}%
2213 \BabelPatchSection{subparagraph}%
2214 \def\babel@toc#1{%
2215 \select@language@x{\bbl@main@language}}}%
2216 \IfBabelLayout{captions}%
2217 {\BabelPatchSection{caption}}}%
2218 \<+core>

```

4.14 Load engine specific macros

Some macros are not defined in all engines, so, after loading the files define them if necessary to raise an error.

```

2219 \bbl@trace{Input engine specific macros}
2220 \ifcase\bbl@engine
2221 \input txtbabel.def
2222 \or
2223 \input luababel.def
2224 \or
2225 \input xebabel.def
2226 \fi
2227 \providecommand\babelfont{\bbl@error{only-lua-xe}}{}{}{}
2228 \providecommand\babelprehyphenation{\bbl@error{only-lua}}{}{}{}
2229 \ifx\babelposthyphenation\undefined
2230 \let\babelposthyphenation\babelprehyphenation
2231 \let\babelpatterns\babelprehyphenation
2232 \let\babelcharproperty\babelprehyphenation
2233 \fi

```

4.15 Creating and modifying languages

Continue with \LaTeX only.

`\babelprovide` is a general purpose tool for creating and modifying languages. It creates the language infrastructure, and loads, if requested, an ini file. It may be used in conjunction to previously loaded ldf files.

```

2234 \</package | core>
2235 \<*package>
2236 \bbl@trace{Creating languages and reading ini files}

```

```

2237 \let\bbl@extend@ini@gobble
2238 \newcommand\babelprovide[2][]{%
2239   \let\bbl@savelangname\language
2240   \edef\bbl@savelocaleid{\the\localeid}%
2241   % Set name and locale id
2242   \edef\language{#2}%
2243   \bbl@id@assign
2244   % Initialize keys
2245   \bbl@vforeach{captions,date,import,main,script,language,%
2246     hyphenrules,linebreaking,justification,mapfont,maparabic,%
2247     mapdigits,intraspaces,intrapenalty,onchar,transforms,alpha,%
2248     Alph,labels,labels*,calendar,date,casing,interchar}%
2249     {\bbl@csarg\let{KVP@##1}\@nnil}%
2250   \global\let\bbl@release@transforms\@empty
2251   \global\let\bbl@release@casing\@empty
2252   \let\bbl@calendars\@empty
2253   \global\let\bbl@inidata\@empty
2254   \global\let\bbl@extend@ini@gobble
2255   \global\let\bbl@included@inis\@empty
2256   \gdef\bbl@key@list{;}%
2257   \bbl@forkv{#1}{%
2258     \in@{/}{##1}% With /, (re)sets a value in the ini
2259     \ifin@
2260       \global\let\bbl@extend@ini\bbl@extend@ini@aux
2261       \bbl@renewinikey##1\@{##2}%
2262     \else
2263       \bbl@csarg\ifx{KVP@##1}\@nnil\else
2264         \bbl@error{unknown-provide-key}{##1}{}%
2265       \fi
2266       \bbl@csarg\def{KVP@##1}{##2}%
2267     \fi}%
2268   \chardef\bbl@howloaded=0:none; 1:ldf without ini; 2:ini
2269   \bbl@ifunset{date#2}\z@{\bbl@ifunset{\bbl@llevel@#2}\@ne\tw@}%
2270   % == init ==
2271   \ifx\bbl@screset\@undefined
2272     \bbl@ldfinit
2273   \fi
2274   % == date (as option) ==
2275   % \ifx\bbl@KVP@date\@nnil\else
2276   % \fi
2277   % ==
2278   \let\bbl@lbkflag\relax % \@empty = do setup linebreak, only in 3 cases:
2279   \ifcase\bbl@howloaded
2280     \let\bbl@lbkflag\@empty % new
2281   \else
2282     \ifx\bbl@KVP@hyphenrules\@nnil\else
2283       \let\bbl@lbkflag\@empty
2284     \fi
2285     \ifx\bbl@KVP@import\@nnil\else
2286       \let\bbl@lbkflag\@empty
2287     \fi
2288   \fi
2289   % == import, captions ==
2290   \ifx\bbl@KVP@import\@nnil\else
2291     \bbl@exp{\bbl@ifblank{\bbl@KVP@import}}%
2292     {\ifx\bbl@initload\relax
2293       \begingroup
2294         \def\BabelBeforeIni##1##2{\gdef\bbl@KVP@import{##1}\endinput}%
2295         \bbl@input@texini{#2}%
2296       \endgroup
2297     \else
2298       \xdef\bbl@KVP@import{\bbl@initload}%
2299     \fi}%

```

```

2300     {}%
2301     \let\bbl@KVP@date\@empty
2302 \fi
2303 \let\bbl@KVP@captions@\bbl@KVP@captions % TODO. A dirty hack
2304 \ifx\bbl@KVP@captions\@nnil
2305     \let\bbl@KVP@captions\bbl@KVP@import
2306 \fi
2307 % ==
2308 \ifx\bbl@KVP@transforms\@nnil\else
2309     \bbl@replace\bbl@KVP@transforms{ }{,}%
2310 \fi
2311 % == Load ini ==
2312 \ifcase\bbl@howloaded
2313     \bbl@provide@new{#2}%
2314 \else
2315     \bbl@ifblank{#1}%
2316     {}% With \bbl@load@basic below
2317     {\bbl@provide@renew{#2}}%
2318 \fi
2319 % == include == TODO
2320 % \ifx\bbl@included@inis\@empty\else
2321 %     \bbl@replace\bbl@included@inis{ }{,}%
2322 %     \bbl@foreach\bbl@included@inis{%
2323 %         \openin\bbl@readstream=babel-##1.ini
2324 %         \bbl@extend@ini{#2}%
2325 %         \closein\bbl@readstream
2326 %     } \fi
2327 % Post tasks
2328 % -----
2329 % == subsequent calls after the first provide for a locale ==
2330 \ifx\bbl@inidata\@empty\else
2331     \bbl@extend@ini{#2}%
2332 \fi
2333 % == ensure captions ==
2334 \ifx\bbl@KVP@captions\@nnil\else
2335     \bbl@ifunset{\bbl@extracaps@#2}%
2336     {\bbl@exp{\bbl@babelensure[exclude=\\today]{#2}}}%
2337     {\bbl@exp{\bbl@babelensure[exclude=\\today,
2338         include=\bbl@extracaps@#2]{#2}}}%
2339     \bbl@ifunset{\bbl@ensure@language}%
2340     {\bbl@exp{%
2341         \\DeclareRobustCommand\<bbl@ensure@language>[1]{%
2342             \\foreignlanguage{language}%
2343             {###1}}}%
2344     }%
2345     \bbl@exp{%
2346         \\bbl@tglobal\<bbl@ensure@language>%
2347         \\bbl@tglobal\<bbl@ensure@language\space>}%
2348 \fi

```

At this point all parameters are defined if 'import'. Now we execute some code depending on them. But what about if nothing was imported? We just set the basic parameters, but still loading the whole ini file.

```

2349 \bbl@load@basic{#2}%
2350 % == script, language ==
2351 % Override the values from ini or defines them
2352 \ifx\bbl@KVP@script\@nnil\else
2353     \bbl@csarg\edef{sname@#2}{\bbl@KVP@script}%
2354 \fi
2355 \ifx\bbl@KVP@language\@nnil\else
2356     \bbl@csarg\edef{lname@#2}{\bbl@KVP@language}%
2357 \fi
2358 \ifcase\bbl@engine\or

```



```

2359 \bbl@ifunset{bbl@chrng@{language}}{%
2360   {\directlua{
2361     Babel.set_chranges_b('\bbl@cl{sbcpr}', '\bbl@cl{chrng}') }}%
2362 \fi
2363 % == onchar ==
2364 \ifx\bbl@KVP@onchar\@nnil\else
2365   \bbl@luahyphenate
2366   \bbl@exp{%
2367     \\\AddToHook{env/document/before}{\select@language{#2}}}%
2368   \directlua{
2369     if Babel.locale_mapped == nil then
2370       Babel.locale_mapped = true
2371       Babel.linebreaking.add_before(Babel.locale_map, 1)
2372       Babel.loc_to_scr = {}
2373       Babel.chr_to_loc = Babel.chr_to_loc or {}
2374     end
2375     Babel.locale_props[\the\localeid].letters = false
2376   }%
2377   \bbl@xin@{ letters }{ \bbl@KVP@onchar\space}%
2378   \ifin@
2379     \directlua{
2380       Babel.locale_props[\the\localeid].letters = true
2381     }%
2382   \fi
2383   \bbl@xin@{ ids }{ \bbl@KVP@onchar\space}%
2384   \ifin@
2385     \ifx\bbl@starthyphens\@undefined % Needed if no explicit selection
2386       \AddBabelHook{babel-onchar}{beforestart}{\bbl@starthyphens}%
2387     \fi
2388     \bbl@exp{\bbl@add\bbl@starthyphens
2389       {\bbl@patterns@lua{language}}}%
2390     % TODO - error/warning if no script
2391     \directlua{
2392       if Babel.script_blocks['\bbl@cl{sbcpr}'] then
2393         Babel.loc_to_scr[\the\localeid] = Babel.script_blocks['\bbl@cl{sbcpr}']
2394         Babel.locale_props[\the\localeid].lg = \the\@nameuse{l@language}\space
2395       end
2396     }%
2397   \fi
2398   \bbl@xin@{ fonts }{ \bbl@KVP@onchar\space}%
2399   \ifin@
2400     \bbl@ifunset{bbl@lsys@{language}}{\bbl@provide@lsys{language}}}%
2401     \bbl@ifunset{bbl@wdir@{language}}{\bbl@provide@dirs{language}}}%
2402     \directlua{
2403       if Babel.script_blocks['\bbl@cl{sbcpr}'] then
2404         Babel.loc_to_scr[\the\localeid] =
2405           Babel.script_blocks['\bbl@cl{sbcpr}']
2406       end}%
2407   \ifx\bbl@mapselect\@undefined % TODO. almost the same as mapfont
2408     \AtBeginDocument{%
2409       \bbl@patchfont{\bbl@mapselect}%
2410       {\selectfont}}%
2411     \def\bbl@mapselect{%
2412       \let\bbl@mapselect\relax
2413       \edef\bbl@prefontid{\fontid\font}}%
2414     \def\bbl@mapdir##1{%
2415       \begingroup
2416         \setbox\z@\hbox{% Force text mode
2417           \def\language{##1}%
2418           \let\bbl@ifrestoring\@firstoftwo % To avoid font warning
2419           \bbl@switchfont
2420           \ifnum\fontid\font>\z@ % A hack, for the pgf nullfont hack
2421             \directlua{

```

```

2422             Babel.locale_props[\the\csname bbl@id@##1\endcsname]%
2423             ['/\/bbl@prefontid'] = \fontid\font\space}%
2424         \fi}%
2425     \endgroup}%
2426 \fi
2427     \bbl@exp{\bbl@add\bbl@mapselect{\bbl@mapdir{\language}%}}%
2428 \fi
2429 % TODO - catch non-valid values
2430 \fi
2431 % == mapfont ==
2432 % For bidi texts, to switch the font based on direction
2433 \ifx\bbl@KVP@mapfont\@nnil\else
2434     \bbl@ifsamestring{\bbl@KVP@mapfont}{direction}{}%
2435     {\bbl@error{unknown-mapfont}{}}}%
2436     \bbl@ifunset{\bbl@sys@language}{\bbl@provide@sys{\language}}}%
2437     \bbl@ifunset{\bbl@wdir@language}{\bbl@provide@dirs{\language}}}%
2438     \ifx\bbl@mapselect\undefined % TODO. See onchar.
2439         \AtBeginDocument{%
2440             \bbl@patchfont{\bbl@mapselect}%
2441             {\selectfont}}%
2442         \def\bbl@mapselect{%
2443             \let\bbl@mapselect\relax
2444             \edef\bbl@prefontid{\fontid\font}}%
2445         \def\bbl@mapdir##1{%
2446             {\def\language{##1}%
2447             \let\bbl@ifrestoring\@firstoftwo % avoid font warning
2448             \bbl@switchfont
2449             \directlua{Babel.fontmap
2450             [\the\csname bbl@wdir@##1\endcsname]%
2451             [\bbl@prefontid]=\fontid\font}}}%
2452     \fi
2453     \bbl@exp{\bbl@add\bbl@mapselect{\bbl@mapdir{\language}%}}%
2454 \fi
2455 % == Line breaking: intraspace, intrapenalty ==
2456 % For CJK, East Asian, Southeast Asian, if interspace in ini
2457 \ifx\bbl@KVP@intraspace\@nnil\else % We can override the ini or set
2458     \bbl@csarg\edef{intsp@#2}{\bbl@KVP@intraspace}%
2459 \fi
2460 \bbl@provide@intraspace
2461 % == Line breaking: CJK quotes == TODO -> @extras
2462 \ifcase\bbl@engine\or
2463     \bbl@xin@{/c}{/\/bbl@cl{\lnbrk}}%
2464 \ifin@
2465     \bbl@ifunset{\bbl@quote@language}{%
2466         {\directlua{
2467             Babel.locale_props[\the\localeid].cjk_quotes = {}
2468             local cs = 'op'
2469             for c in string.utfvalues(
2470                 [[\csname bbl@quote@language\endcsname]]) do
2471                 if Babel.cjk_characters[c].c == 'qu' then
2472                     Babel.locale_props[\the\localeid].cjk_quotes[c] = cs
2473                 end
2474                 cs = (cs == 'op') and 'cl' or 'op'
2475             end
2476         }}%
2477     \fi
2478 \fi
2479 % == Line breaking: justification ==
2480 \ifx\bbl@KVP@justification\@nnil\else
2481     \let\bbl@KVP@linebreaking\bbl@KVP@justification
2482 \fi
2483 \ifx\bbl@KVP@linebreaking\@nnil\else
2484     \bbl@xin@{\bbl@KVP@linebreaking,%}

```

```

2485     {,elongated,kashida,cjk,padding,unhyphenated,}%
2486 \ifin@
2487 \bbl@csarg\xdef
2488     {lnbrk@\language\name}{\expandafter\@car\bbl@KVP@linebreaking\@nil}%
2489 \fi
2490 \fi
2491 \bbl@xin@{/e}{/\bbl@cl{lnbrk}}%
2492 \ifin@else\bbl@xin@{/k}{/\bbl@cl{lnbrk}}\fi
2493 \ifin@\bbl@arabicjust\fi
2494 \bbl@xin@{/p}{/\bbl@cl{lnbrk}}%
2495 \ifin@\AtBeginDocument{\@nameuse{\bbl@tibetanjust}}\fi
2496 % == Line breaking: hyphenate.other.(locale|script) ==
2497 \ifx\bbl@lbcflag\empty
2498     \bbl@ifunset{\bbl@hyotl@\language\name}{}%
2499     {\bbl@csarg\bbl@replace{\hyotl@\language\name}{ }{,}%
2500     \bbl@startcommands*{\language\name}{}%
2501     \bbl@csarg\bbl@foreach{\hyotl@\language\name}{%
2502     \ifcase\bbl@engine
2503     \ifnum##1<257
2504     \SetHyphenMap{\BabelLower{##1}{##1}}%
2505     \fi
2506     \else
2507     \SetHyphenMap{\BabelLower{##1}{##1}}%
2508     \fi}%
2509     \bbl@endcommands}%
2510 \bbl@ifunset{\bbl@hyots@\language\name}{}%
2511     {\bbl@csarg\bbl@replace{\hyots@\language\name}{ }{,}%
2512     \bbl@csarg\bbl@foreach{\hyots@\language\name}{%
2513     \ifcase\bbl@engine
2514     \ifnum##1<257
2515     \global\lccode##1=##1\relax
2516     \fi
2517     \else
2518     \global\lccode##1=##1\relax
2519     \fi}}%
2520 \fi
2521 % == Counters: maparabic ==
2522 % Native digits, if provided in ini (TeX level, xe and lua)
2523 \ifcase\bbl@engine\else
2524     \bbl@ifunset{\bbl@dgnat@\language\name}{}%
2525     {\expandafter\ifx\csname\bbl@dgnat@\language\name\endcsname\empty\else
2526     \expandafter\expandafter\expandafter
2527     \bbl@setdigits\csname\bbl@dgnat@\language\name\endcsname
2528     \ifx\bbl@KVP@maparabic\@nnil\else
2529     \ifx\bbl@latinarabic\undefined
2530     \expandafter\let\expandafter\@arabic
2531     \csname\bbl@counter@\language\name\endcsname
2532     \else % ie, if layout=counters, which redefines \@arabic
2533     \expandafter\let\expandafter\bbl@latinarabic
2534     \csname\bbl@counter@\language\name\endcsname
2535     \fi
2536     \fi
2537 \fi}%
2538 \fi
2539 % == Counters: mapdigits ==
2540 % > luababel.def
2541 % == Counters: alph, Alph ==
2542 \ifx\bbl@KVP@alph\@nnil\else
2543     \bbl@exp{%
2544     \\ \bbl@add\<\bbl@preextras@\language\name>{%
2545     \\ \babel@save\\ \@alph
2546     \let\\ \@alph\<\bbl@cntr@\bbl@KVP@alph @\language\name>}}%
2547 \fi

```

```

2548 \ifx\bbbl@KVP@Alph@\nnil\else
2549 \bbbl@exp{%
2550 \\\bbbl@add\<\bbbl@preextras@\language\>{%
2551 \\\babel@save\\\@Alph
2552 \let\\\@Alph\<\bbbl@cntr@\bbbl@KVP@Alph @\language\>}}%
2553 \fi
2554 % == Casing ==
2555 \bbbl@release@casing
2556 \ifx\bbbl@KVP@casing@\nnil\else
2557 \bbbl@csarg\xdef{casing@\language}%
2558 {\@nameuse{\bbbl@casing@\language}\bbbl@maybextx\bbbl@KVP@casing}%
2559 \fi
2560 % == Calendars ==
2561 \ifx\bbbl@KVP@calendar@\nnil
2562 \edef\bbbl@KVP@calendar{\bbbl@cl{calpr}}%
2563 \fi
2564 \def\bbbl@tempe##1##2\@{%% Get first calendar
2565 \def\bbbl@tempa{##1}}%
2566 \bbbl@exp{\\\bbbl@tempe\bbbl@KVP@calendar\space\\\@}%
2567 \def\bbbl@tempe##1.##2.##3\@{%%
2568 \def\bbbl@tempc{##1}%
2569 \def\bbbl@tempb{##2}}%
2570 \expandafter\bbbl@tempe\bbbl@tempa..\@
2571 \bbbl@csarg\edef{calpr@\language}%
2572 \ifx\bbbl@tempc@empty\else
2573 calendar=\bbbl@tempc
2574 \fi
2575 \ifx\bbbl@tempb@empty\else
2576 ,variant=\bbbl@tempb
2577 \fi}%
2578 % == engine specific extensions ==
2579 % Defined in XXXbabel.def
2580 \bbbl@provide@extra{#2}%
2581 % == require.babel in ini ==
2582 % To load or reload the babel-*.tex, if require.babel in ini
2583 \ifx\bbbl@beforestart\relax\else % But not in doc aux or body
2584 \bbbl@ifunset{\bbbl@rqtex@\language}%
2585 {\expandafter\ifx\csname \bbbl@rqtex@\language\endcsname\@empty\else
2586 \let\BabelBeforeIni\@gobbletwo
2587 \chardef\atcatcode=\catcode\@
2588 \catcode\@=11\relax
2589 \def\CurrentOption{#2}%
2590 \bbbl@input@texini{\bbbl@cs{rqtex@\language}}%
2591 \catcode\@=\atcatcode
2592 \let\atcatcode\relax
2593 \global\bbbl@csarg\let{rqtex@\language}\relax
2594 \fi}%
2595 \bbbl@foreach\bbbl@calendars{%
2596 \bbbl@ifunset{\bbbl@ca##1}{%
2597 \chardef\atcatcode=\catcode\@
2598 \catcode\@=11\relax
2599 \InputIfFileExists{babel-ca-##1.tex}{}}%
2600 \catcode\@=\atcatcode
2601 \let\atcatcode\relax}%
2602 {}}%
2603 \fi
2604 % == frenchspacing ==
2605 \ifcase\bbbl@howloaded\in@true\else\in@false\fi
2606 \ifin@else\bbbl@xin@{typography/frenchspacing}{\bbbl@key@list}\fi
2607 \ifin@
2608 \bbbl@extras@wrap{\\\bbbl@pre@fs}%
2609 {\bbbl@pre@fs}%
2610 {\bbbl@post@fs}%

```

```

2611 \fi
2612 % == transforms ==
2613 % > luababel.def
2614 \def\CurrentOption{#2}%
2615 \@nameuse{bbl@icsave@#2}%
2616 % == main ==
2617 \ifx\bbl@KVP@main\@nnil % Restore only if not 'main'
2618   \let\language\bbl@savelangname
2619   \chardef\localeid\bbl@savelocaleid\relax
2620 \fi
2621 % == hyphenrules (apply if current) ==
2622 \ifx\bbl@KVP@hyphenrules\@nnil\else
2623   \ifnum\bbl@savelocaleid=\localeid
2624     \language\@nameuse{l@\language}%
2625   \fi
2626 \fi}

```

Depending on whether or not the language exists (based on \date<language>), we define two macros. Remember \bbl@startcommands opens a group.

```

2627 \def\bbl@provide@new#1{%
2628   \@namedef{date#1}{}% marks lang exists - required by \StartBabelCommands
2629   \@namedef{extras#1}{}%
2630   \@namedef{noextras#1}{}%
2631   \bbl@startcommands*{#1}{captions}%
2632   \ifx\bbl@KVP@captions\@nnil % and also if import, implicit
2633     \def\bbl@tempb##1{% elt for \bbl@captionslist
2634       \ifx##1\@nnil\else
2635         \bbl@exp{%
2636           \\SetString\\##1{%
2637             \\bbl@nocaption{\bbl@stripslash##1}{#1\bbl@stripslash##1}}}%
2638           \expandafter\bbl@tempb
2639         \fi}%
2640     \expandafter\bbl@tempb\bbl@captionslist\@nnil
2641   \else
2642     \ifx\bbl@initoload\relax
2643       \bbl@read@ini{\bbl@KVP@captions}2% % Here letters cat = 11
2644     \else
2645       \bbl@read@ini{\bbl@initoload}2% % Same
2646     \fi
2647   \fi
2648   \StartBabelCommands*{#1}{date}%
2649   \ifx\bbl@KVP@date\@nnil
2650     \bbl@exp{%
2651       \\SetString\\today{\\bbl@nocaption{today}{#1today}}}%
2652   \else
2653     \bbl@savetoday
2654     \bbl@savedate
2655   \fi
2656   \bbl@endcommands
2657   \bbl@load@basic{#1}%
2658   % == hyphenmins == (only if new)
2659   \bbl@exp{%
2660     \gdef\<#1hyphenmins>{%
2661       {\bbl@ifunset{\bbl@lfthm@#1}{2}{\bbl@cs{lfthm@#1}}}%
2662       {\bbl@ifunset{\bbl@rgthm@#1}{3}{\bbl@cs{rgthm@#1}}}}}%
2663   % == hyphenrules (also in renew) ==
2664   \bbl@provide@hyphens{#1}%
2665   \ifx\bbl@KVP@main\@nnil\else
2666     \expandafter\main@language\expandafter{#1}%
2667   \fi}
2668 %
2669 \def\bbl@provide@renew#1{%
2670   \ifx\bbl@KVP@captions\@nnil\else

```

```

2671 \StartBabelCommands*{#1}{captions}%
2672 \bbl@read@ini{\bbl@KVP@captions}2% % Here all letters cat = 11
2673 \EndBabelCommands
2674 \fi
2675 \ifx\bbl@KVP@date\@nnil\else
2676 \StartBabelCommands*{#1}{date}%
2677 \bbl@savetoday
2678 \bbl@savedate
2679 \EndBabelCommands
2680 \fi
2681 % == hyphenrules (also in new) ==
2682 \ifx\bbl@lbfkflag\@empty
2683 \bbl@provide@hyphens{#1}%
2684 \fi}

```

Load the basic parameters (ids, typography, counters, and a few more), while captions and dates are left out. But it may happen some data has been loaded before automatically, so we first discard the saved values. (TODO. But preserving previous values would be useful.)

```

2685 \def\bbl@load@basic#1{%
2686 \ifcase\bbl@howloaded\or\or
2687 \ifcase\csname bbl@llevel@\language\endcsname
2688 \bbl@csarg\let\lname@\language\relax
2689 \fi
2690 \fi
2691 \bbl@ifunset{\bbl@lname@#1}%
2692 {\def\BabelBeforeIni##1##2{%
2693 \begingroup
2694 \let\bbl@ini@captions@aux\@gobbletwo
2695 \def\bbl@inidate ###1.###2.###3.###4\relax ###5###6}%
2696 \bbl@read@ini{##1}1%
2697 \ifx\bbl@initoload\relax\endinput\fi
2698 \endgroup}%
2699 \begingroup % boxed, to avoid extra spaces:
2700 \ifx\bbl@initoload\relax
2701 \bbl@input@texini{##1}%
2702 \else
2703 \setbox\z@\hbox{\BabelBeforeIni{\bbl@initoload}}}%
2704 \fi
2705 \endgroup}%
2706 {}%

```

The hyphenrules option is handled with an auxiliary macro. This macro is called in three cases: when a language is first declared with \babelprovide, with hyphenrules and with import.

```

2707 \def\bbl@provide@hyphens#1{%
2708 \@tempcnta\m@ne % a flag
2709 \ifx\bbl@KVP@hyphenrules\@nnil\else
2710 \bbl@replace\bbl@KVP@hyphenrules{ }{,}%
2711 \bbl@foreach\bbl@KVP@hyphenrules{%
2712 \ifnum\@tempcnta=\m@ne % if not yet found
2713 \bbl@ifsamestring{##1}{+}%
2714 {\bbl@carg\addlanguage{l@##1}}%
2715 }%
2716 \bbl@ifunset{l@##1}% After a possible +
2717 {}%
2718 {\@tempcnta\@nameuse{l@##1}}%
2719 \fi}%
2720 \ifnum\@tempcnta=\m@ne
2721 \bbl@warning{%
2722 Requested 'hyphenrules' for '\language' not found:\\%
2723 \bbl@KVP@hyphenrules.\\%
2724 Using the default value. Reported}%
2725 \fi
2726 \fi
2727 \ifnum\@tempcnta=\m@ne % if no opt or no language in opt found

```

```

2728 \ifx\bbbl@KVP@captions@@\@nnil % TODO. Hackish. See above.
2729 \bbbl@ifunset{\bbbl@hyphr@#1}{}% use value in ini, if exists
2730 {\bbbl@exp{\bbbl@ifblank{\bbbl@cs{hyphr@#1}}}%
2731 {}%
2732 {\bbbl@ifunset{\l@bbbl@c{hyphr}}}%
2733 {}% if hyphenrules found:
2734 {\@tempcnta\@nameuse{\l@bbbl@c{hyphr}}}%
2735 \fi
2736 \fi
2737 \bbbl@ifunset{\l@#1}%
2738 {\ifnum\@tempcnta=\m@ne
2739 \bbbl@carg\adddialect{\l@#1}\language
2740 \else
2741 \bbbl@carg\adddialect{\l@#1}\@tempcnta
2742 \fi}%
2743 {\ifnum\@tempcnta=\m@ne\else
2744 \global\bbbl@carg\chardef{\l@#1}\@tempcnta
2745 \fi}}

```

The reader of babel-...tex files. We reset temporarily some catcodes.

```

2746 \def\bbbl@input@texini#1{%
2747 \bbbl@bsphack
2748 \bbbl@exp{%
2749 \catcode`\%%=14 \catcode`\%%=0
2750 \catcode`\%{=1 \catcode`\%{=2
2751 \lowercase{\InputIfFileExists{babel-#1.tex}{}}}%
2752 \catcode`\%%=\the\catcode`\%\relax
2753 \catcode`\%{=\the\catcode`\%{relax
2754 \catcode`\%{=\the\catcode`\%\relax
2755 \catcode`\%{=\the\catcode`\%\relax}%
2756 \bbbl@esphack}

```

The following macros read and store ini files (but don't process them). For each line, there are 3 possible actions: ignore if starts with ;, switch section if starts with [, and store otherwise. There are used in the first step of \bbbl@read@ini.

```

2757 \def\bbbl@inline#1\bbbl@inline{%
2758 \ifnextchar[\bbbl@iniset{\ifnextchar\bbbl@iniskip\bbbl@inistore}#1\@@}% ]
2759 \def\bbbl@iniset[#1]#2\@@{\def\bbbl@section{#1}}
2760 \def\bbbl@iniskip#1\@@{% if starts with ;
2761 \def\bbbl@inistore#1=#2\@@{% full (default)
2762 \bbbl@trim@def\bbbl@tempa{#1}%
2763 \bbbl@trim\toks@{#2}%
2764 \bbbl@xin@{\bbbl@section/\bbbl@tempa;}{\bbbl@key@list}%
2765 \ifin@else
2766 \bbbl@xin@{,identification/include.}%
2767 {\bbbl@section/\bbbl@tempa}%
2768 \ifin@\xdef\bbbl@included@inis{\the\toks@}\fi
2769 \bbbl@exp{%
2770 \\\g@addto@macro\bbbl@inidata{%
2771 \\\bbbl@elt{\bbbl@section}{\bbbl@tempa}{\the\toks@}}}%
2772 \fi}
2773 \def\bbbl@inistore@min#1=#2\@@{% minimal (maybe set in \bbbl@read@ini)
2774 \bbbl@trim@def\bbbl@tempa{#1}%
2775 \bbbl@trim\toks@{#2}%
2776 \bbbl@xin@{.identification.}{\bbbl@section.}%
2777 \ifin@
2778 \bbbl@exp{\\\g@addto@macro\bbbl@inidata{%
2779 \\\bbbl@elt{identification}{\bbbl@tempa}{\the\toks@}}}%
2780 \fi}

```

Now, the 'main loop', which **must be executed inside a group**. At this point, \bbbl@inidata may contain data declared in \babelprovide, with 'slashed' keys. There are 3 steps: first read the ini file and store it; then traverse the stored values, and process some groups if required (date, captions, labels, counters); finally, 'export' some values by defining global macros (identification, typography,

characters, numbers). The second argument is 0 when called to read the minimal data for fonts; with \babelprovide it's either 1 or 2.

```

2781 \def\bbl@loop@ini{%
2782   \loop
2783     \if T\ifeof\bbl@readstream F\fi T\relax % Trick, because inside \loop
2784     \endlinechar\m@ne
2785     \read\bbl@readstream to \bbl@line
2786     \endlinechar\^^M
2787     \ifx\bbl@line\@empty\else
2788       \expandafter\bbl@iniline\bbl@line\bbl@iniline
2789     \fi
2790   \repeat}
2791 \ifx\bbl@readstream\@undefined
2792   \csname newread\endcsname\bbl@readstream
2793 \fi
2794 \def\bbl@read@ini#1#2{%
2795   \global\let\bbl@extend@ini\@gobble
2796   \openin\bbl@readstream=babel-#1.ini
2797   \ifeof\bbl@readstream
2798     \bbl@error{no-ini-file}{#1}{}{}%
2799   \else
2800     % == Store ini data in \bbl@inidata ==
2801     \catcode\ [=12 \catcode\ ]=12 \catcode\ ==12 \catcode\ &=12
2802     \catcode\ ;=12 \catcode\ |=12 \catcode\ %=14 \catcode\ -=12
2803     \bbl@info{Importing
2804               \ifcase#2font and identification \or basic \fi
2805               data for \language\name\%
2806               from babel-#1.ini. Reported}%
2807     \ifnum#2=\z@
2808       \global\let\bbl@inidata\@empty
2809       \let\bbl@inistore\bbl@inistore@min % Remember it's local
2810     \fi
2811     \def\bbl@section{identification}%
2812     \bbl@exp{\ \bbl@inistore tag.ini=#1\ \@}%
2813     \bbl@inistore load.level=#2\ @@
2814     \bbl@loop@ini
2815     % == Process stored data ==
2816     \bbl@csarg\xdef{lini@\language}{#1}%
2817     \bbl@read@ini@aux
2818     % == 'Export' data ==
2819     \bbl@ini@exports{#2}%
2820     \global\bbl@csarg\let{inidata@\language}\bbl@inidata
2821     \global\let\bbl@inidata\@empty
2822     \bbl@exp{\ \bbl@add@list\ \bbl@ini@loaded{\language}}%
2823     \bbl@tglobal\bbl@ini@loaded
2824   \fi
2825   \closein\bbl@readstream}
2826 \def\bbl@read@ini@aux{%
2827   \let\bbl@savestrings\@empty
2828   \let\bbl@savetoday\@empty
2829   \let\bbl@savestate\@empty
2830   \def\bbl@elt##1##2##3{%
2831     \def\bbl@section{##1}%
2832     \in@{=date.}{=##1}% Find a better place
2833     \ifin@
2834       \bbl@ifunset{bbl@inikv@##1}%
2835       {\bbl@ini@calendar{##1}}%
2836     }%
2837   \fi
2838   \bbl@ifunset{bbl@inikv@##1}{}%
2839   {\csname bbl@inikv@##1\endcsname{##2}{##3}}}%
2840   \bbl@inidata}

```


A variant to be used when the ini file has been already loaded, because it's not the first `\babelprovide` for this language.

```

2841 \def\bbl@extend@ini@aux#1{%
2842   \bbl@startcommands*{#1}{captions}%
2843   % Activate captions/... and modify exports
2844   \bbl@csarg\def\inikv@captions.licr}##1##2{%
2845     \setlocalecaption{#1}{##1}{##2}}%
2846   \def\bbl@inikv@captions##1##2{%
2847     \bbl@ini@captions@aux{##1}{##2}}%
2848   \def\bbl@stringdef##1##2{\gdef##1{##2}}%
2849   \def\bbl@exportkey##1##2##3{%
2850     \bbl@ifunset{bbl@kv@##2}{}%
2851     {\expandafter\ifx\csname bbl@kv@##2\endcsname\@empty\else
2852       \bbl@exp{\global\let<bbl@##1@\language\>\<bbl@kv@##2>}%
2853       \fi}}%
2854   % As with \bbl@read@ini, but with some changes
2855   \bbl@read@ini@aux
2856   \bbl@ini@exports\tw@
2857   % Update inidata@lang by pretending the ini is read.
2858   \def\bbl@elt##1##2##3{%
2859     \def\bbl@section{##1}%
2860     \bbl@iniline##2=##3\bbl@iniline}%
2861     \csname bbl@inidata@#1\endcsname
2862     \global\bbl@csarg\let{inidata@#1}\bbl@inidata
2863   \StartBabelCommands*{#1}{date}% And from the import stuff
2864   \def\bbl@stringdef##1##2{\gdef##1{##2}}%
2865   \bbl@savetoday
2866   \bbl@savestate
2867   \bbl@endcommands}

```

A somewhat hackish tool to handle calendar sections. TODO. To be improved.

```

2868 \def\bbl@ini@calendar#1{%
2869   \lowercase{\def\bbl@tempa{=1=}}%
2870   \bbl@replace\bbl@tempa{=date.gregorian}{}%
2871   \bbl@replace\bbl@tempa{=date.}{}%
2872   \in@{.licr}{#1=}%
2873   \ifin@
2874     \ifcase\bbl@engine
2875       \bbl@replace\bbl@tempa{.licr}{}%
2876     \else
2877       \let\bbl@tempa\relax
2878     \fi
2879   \fi
2880   \ifx\bbl@tempa\relax\else
2881     \bbl@replace\bbl@tempa{=}{}%
2882     \ifx\bbl@tempa\@empty\else
2883       \xdef\bbl@calendars{\bbl@calendars,\bbl@tempa}%
2884     \fi
2885     \bbl@exp{%
2886       \def<bbl@inikv@#1>####1####2{%
2887         \\bbl@inidate####1...\relax{####2}{\bbl@tempa}}}%
2888     \fi}

```

A key with a slash in `\babelprovide` replaces the value in the ini file (which is ignored altogether). The mechanism is simple (but suboptimal): add the data to the ini one (at this point the ini file has not yet been read), and define a dummy macro. When the ini file is read, just skip the corresponding key and reset the macro (in `\bbl@inistore` above).

```

2889 \def\bbl@renewinikey#1/#2\@#3{%
2890   \edef\bbl@tempa{\zap@space #1 \@empty}% section
2891   \edef\bbl@tempb{\zap@space #2 \@empty}% key
2892   \bbl@trim\toks@{#3}% value
2893   \bbl@exp{%
2894     \edef\\bbl@key@list{\bbl@key@list \bbl@tempa/\bbl@tempb;%}

```

```

2895    \\g@addto@macro\\bbl@inidata{%
2896    \\bbl@elt{\bbl@tempa}{\bbl@tempb}{\the\toks@}}}%

```

The previous assignments are local, so we need to export them. If the value is empty, we can provide a default value.

```

2897 \def\bbl@exportkey#1#2#3{%
2898   \bbl@ifunset{\bbl@kv@#2}%
2899   {\bbl@csarg\gdef{#1@{language}\language}{#3}}%
2900   {\expandafter\ifx\csname bbl@kv@#2\endcsname\@empty
2901     \bbl@csarg\gdef{#1@{language}\language}{#3}%
2902     \else
2903     \bbl@exp{\global\let<bbl@#1@{language}>\<bbl@kv@#2>}%
2904     \fi}}

```

Key-value pairs are treated differently depending on the section in the ini file. The following macros are the readers for identification and typography. Note `\bbl@ini@exports` is called always (via `\bbl@inisec`), while `\bbl@after@ini` must be called explicitly after `\bbl@read@ini` if necessary. Although BCP 47 doesn't treat 'x' as an extension, the CLDR and many other sources do (as a *private use extension*). For consistency with other single-letter subtags or 'singletons', here is considered an extension, too.

```

2905 \def\bbl@iniwarning#1{%
2906   \bbl@ifunset{\bbl@kv@identification.warning#1}}%
2907   {\bbl@warning{%
2908     From babel-\bbl@cs{lini@{language}\language}.ini:\\%
2909     \bbl@cs{@kv@identification.warning#1}\\%
2910     Reported }}%
2911 %
2912 \let\bbl@release@transforms\@empty
2913 \let\bbl@release@casing\@empty
2914 \def\bbl@ini@exports#1{%
2915   % Identification always exported
2916   \bbl@iniwarning}%
2917   \ifcase\bbl@engine
2918     \bbl@iniwarning{.pdflatex}%
2919   \or
2920     \bbl@iniwarning{.lualatex}%
2921   \or
2922     \bbl@iniwarning{.xelatex}%
2923   \fi%
2924   \bbl@exportkey{llevel}{identification.load.level}}%
2925   \bbl@exportkey{elname}{identification.name.english}}%
2926   \bbl@exp{\\bbl@exportkey{lname}{identification.name.opentype}%
2927     {\csname bbl@elname@{language}\endcsname}}%
2928   \bbl@exportkey{tbc}{identification.tag.bcp47}}%
2929   % Somewhat hackish. TODO:
2930   \bbl@exportkey{casing}{identification.tag.bcp47}}%
2931   \bbl@exportkey{lbc}{identification.language.tag.bcp47}}%
2932   \bbl@exportkey{lotf}{identification.tag.opentype}{dflt}%
2933   \bbl@exportkey{esname}{identification.script.name}}%
2934   \bbl@exp{\\bbl@exportkey{sname}{identification.script.name.opentype}%
2935     {\csname bbl@esname@{language}\endcsname}}%
2936   \bbl@exportkey{sbc}{identification.script.tag.bcp47}}%
2937   \bbl@exportkey{sotf}{identification.script.tag.opentype}{DFLT}%
2938   \bbl@exportkey{rbcp}{identification.region.tag.bcp47}}%
2939   \bbl@exportkey{vbcp}{identification.variant.tag.bcp47}}%
2940   \bbl@exportkey{extt}{identification.extension.t.tag.bcp47}}%
2941   \bbl@exportkey{extu}{identification.extension.u.tag.bcp47}}%
2942   \bbl@exportkey{extx}{identification.extension.x.tag.bcp47}}%
2943   % Also maps bcp47 -> language
2944   \ifbbl@bcptoname
2945     \bbl@csarg\xdef{bcp@map@{bbl@cl{tbc}}}{\language}%
2946   \fi
2947   \ifcase\bbl@engine\or
2948     \directlua{%

```

```

2949      Babel.locale_props[\the\bbl@cs{id@@\languagename}].script
2950      = '\bbl@cl{sbcpr}'%
2951 \fi
2952 % Conditional
2953 \ifnum#1>\z@          % 0 = only info, 1, 2 = basic, (re)new
2954   \bbl@exportkey{calpr}{date.calendar.preferred}{}%
2955   \bbl@exportkey{lnbrk}{typography.linebreaking}{h}%
2956   \bbl@exportkey{hyphr}{typography.hyphenrules}{}%
2957   \bbl@exportkey{lfthm}{typography.lefthyphenmin}{2}%
2958   \bbl@exportkey{rgthm}{typography.righthyphenmin}{3}%
2959   \bbl@exportkey{prehc}{typography.prehyphenchar}{}%
2960   \bbl@exportkey{hyotl}{typography.hyphenate.other.locale}{}%
2961   \bbl@exportkey{hyots}{typography.hyphenate.other.script}{}%
2962   \bbl@exportkey{intsp}{typography.intraspaces}{}%
2963   \bbl@exportkey{frspc}{typography.frenchspacing}{u}%
2964   \bbl@exportkey{chrng}{characters.ranges}{}%
2965   \bbl@exportkey{quote}{characters.delimiters.quotes}{}%
2966   \bbl@exportkey{dgnat}{numbers.digits.native}{}%
2967   \ifnum#1=\tw@          % only (re)new
2968     \bbl@exportkey{rqtex}{identification.require.babel}{}%
2969     \bbl@toglobal\bbl@savetoday
2970     \bbl@toglobal\bbl@savestate
2971     \bbl@savestrings
2972 \fi
2973 \fi}

```

A shared handler for key=val lines to be stored in \bbl@kv@<section>.<key>.

```

2974 \def\bbl@inikv#1#2{%      key=value
2975   \toks@{#2}%             This hides #'s from ini values
2976   \bbl@csarg\edef{@kv@\bbl@section.#1}{\the\toks@}}

```

By default, the following sections are just read. Actions are taken later.

```

2977 \let\bbl@inikv@identification\bbl@inikv
2978 \let\bbl@inikv@date\bbl@inikv
2979 \let\bbl@inikv@typography\bbl@inikv
2980 \let\bbl@inikv@numbers\bbl@inikv

```

The characters section also stores the values, but casing is treated in a different fashion. Much like transforms, a set of commands calling the parser are stored in \bbl@release@casing, which is executed in \babelprovide.

```

2981 \def\bbl@maybextx{-\bbl@csarg\ifx{extx@\languagename}\@empty x-\fi}
2982 \def\bbl@inikv@characters#1#2{%
2983   \bbl@ifsamestring{#1}{casing}% eg, casing = uV
2984   {\bbl@exp{%
2985     \\g@addto@macro\\bbl@release@casing{%
2986       \\bbl@casemapping}{\languagename}{\unexpanded{#2}}}%
2987     {\in@{casing.}{#1}% eg, casing.Uv = uV
2988       \ifin@
2989         \lowercase{\def\bbl@tempb{#1}}%
2990         \bbl@replace\bbl@tempb{casing.}{}%
2991         \bbl@exp{\\g@addto@macro\\bbl@release@casing{%
2992           \\bbl@casemapping
2993             {\bbl@maybextx\bbl@tempb}{\languagename}{\unexpanded{#2}}}%
2994         \else
2995           \bbl@inikv{#1}{#2}%
2996         \fi}}

```

Additive numerals require an additional definition. When .1 is found, two macros are defined – the basic one, without .1 called by \localenumerals, and another one preserving the trailing .1 for the ‘units’.

```

2997 \def\bbl@inikv@counters#1#2{%
2998   \bbl@ifsamestring{#1}{digits}%
2999   {\bbl@error{digits-is-reserved}{}}}%
3000   {}%

```

```

3001 \def\bbbl@tempc{#1}%
3002 \bbbl@trim@def{\bbbl@tempb*}{#2}%
3003 \in@{.1$}{#1$}%
3004 \ifin@
3005   \bbbl@replace\bbbl@tempc{.1}{}%
3006   \bbbl@csarg\protected@xdef{cntr@\bbbl@tempc @\languagename}{%
3007     \noexpand\bbbl@alphanumeric{\bbbl@tempc}}%
3008 \fi
3009 \in@{.F.}{#1}%
3010 \ifin@ \else \in@{.S.}{#1} \fi
3011 \ifin@
3012   \bbbl@csarg\protected@xdef{cntr@#1@\languagename}{\bbbl@tempb*}%
3013 \else
3014   \toks@{ }% Required by \bbbl@builddifcase, which returns \bbbl@tempa
3015   \expandafter\bbbl@builddifcase\bbbl@tempb* \ \ % Space after \
3016   \bbbl@csarg{\global\expandafter\let}{cntr@#1@\languagename}\bbbl@tempa
3017 \fi}

```

Now captions and captions.licr, depending on the engine. And below also for dates. They rely on a few auxiliary macros. It is expected the ini file provides the complete set in Unicode and LICR, in that order.

```

3018 \ifcase\bbbl@engine
3019   \bbbl@csarg\def{inikv@captions.licr}#1#2{%
3020     \bbbl@ini@captions@aux{#1}{#2}}
3021 \else
3022   \def\bbbl@inikv@captions#1#2{%
3023     \bbbl@ini@captions@aux{#1}{#2}}
3024 \fi

```

The auxiliary macro for captions define \<caption>name.

```

3025 \def\bbbl@ini@captions@template#1#2{% string language tempa=capt-name
3026   \bbbl@replace\bbbl@tempa{.template}{}%
3027   \def\bbbl@toreplace{#1}{}%
3028   \bbbl@replace\bbbl@toreplace{[ ]}{\nobreakspace{}}%
3029   \bbbl@replace\bbbl@toreplace{[ ]}{\csname}%
3030   \bbbl@replace\bbbl@toreplace{[ ]}{\csname the}%
3031   \bbbl@replace\bbbl@toreplace{[ ]}{name\endcsname{}}%
3032   \bbbl@replace\bbbl@toreplace{[ ]}{\endcsname{}}%
3033   \bbbl@xin@{,\bbbl@tempa,}{,chapter,appendix,part,}%
3034   \ifin@
3035     \@nameuse{\bbbl@patch\bbbl@tempa}%
3036     \global\bbbl@csarg\let{\bbbl@tempa fmt@#2}\bbbl@toreplace
3037   \fi
3038   \bbbl@xin@{,\bbbl@tempa,}{,figure,table,}%
3039   \ifin@
3040     \global\bbbl@csarg\let{\bbbl@tempa fmt@#2}\bbbl@toreplace
3041     \bbbl@exp{\gdef\<fnum@\bbbl@tempa>{%
3042       \\\bbbl@ifunset{\bbbl@bbbl@tempa fmt@\\\languagename}%
3043       {[fnum@\bbbl@tempa]}%
3044       {\\\@nameuse{\bbbl@bbbl@tempa fmt@\\\languagename}}}%
3045     \fi}
3046 \def\bbbl@ini@captions@aux#1#2{%
3047   \bbbl@trim@def\bbbl@tempa{#1}%
3048   \bbbl@xin@{.template}{\bbbl@tempa}%
3049   \ifin@
3050     \bbbl@ini@captions@template{#2}\languagename
3051   \else
3052     \bbbl@ifblank{#2}%
3053     {\bbbl@exp{%
3054       \toks@{\\bbbl@nocaption{\bbbl@tempa}{\languagename\bbbl@tempa name}}}%
3055     {\bbbl@trim\toks@{#2}}}%
3056     \bbbl@exp{%
3057       \\\bbbl@add\\bbbl@savestrings{%
3058         \\\SetString\<\bbbl@tempa name>{\the\toks@}}}%

```

```

3059 \toks@expandafter{\bbl@captionslist}%
3060 \bbl@exp{\in@{\<\bbl@tempa name>}{\the\toks@}}%
3061 \ifin@ \else
3062 \bbl@exp{%
3063 \\\bbl@add\<bbl@extracaps@language>{\<\bbl@tempa name>}%
3064 \\\bbl@tglobal\<bbl@extracaps@language>}%
3065 \fi
3066 \fi}

```

Labels. Captions must contain just strings, no format at all, so there is new group in ini files.

```

3067 \def\bbl@list@the{%
3068 part,chapter,section,subsection,subsubsection,paragraph,%
3069 subparagraph,enumi,enumii,enumiii,enumiv,equation,figure,%
3070 table,page,footnote,mpfootnote,mpfn}
3071 \def\bbl@map@cnt#1{% #1:roman,etc, // #2:enumi,etc
3072 \bbl@ifunset{\bbl@map@#1@language}%
3073 {\@nameuse{#1}}%
3074 {\@nameuse{\bbl@map@#1@language}}}%
3075 \def\bbl@inikv@labels#1#2{%
3076 \in@{.map}{#1}%
3077 \ifin@
3078 \ifx\bbl@KVP@labels\@nnil\else
3079 \bbl@xin@{ map }{ \bbl@KVP@labels\space}%
3080 \ifin@
3081 \def\bbl@tempc{#1}%
3082 \bbl@replace\bbl@tempc{.map}{}%
3083 \in@{,#2,},{arabic,roman,Roman,alph,Alph,fnsymbol,}%
3084 \bbl@exp{%
3085 \gdef\<bbl@map@\bbl@tempc @language>%
3086 {\ifin@<#2>\else\\localecounter{#2}\fi}}%
3087 \bbl@foreach\bbl@list@the{%
3088 \bbl@ifunset{the##1}{}%
3089 {\bbl@exp{\let\\bbl@tempd\<the##1>}%
3090 \bbl@exp{%
3091 \\\bbl@sreplace\<the##1>%
3092 {\<\bbl@tempc>{##1}}{\\\bbl@map@cnt{\bbl@tempc}{##1}}%
3093 \\\bbl@sreplace\<the##1>%
3094 {\<\@empty @\bbl@tempc>\<c@##1>}{\\bbl@map@cnt{\bbl@tempc}{##1}}}%
3095 \expandafter\ifx\csname the##1\endcsname\bbl@tempd\else
3096 \toks@expandafter\expandafter\expandafter{%
3097 \csname the##1\endcsname}%
3098 \expandafter\xdef\csname the##1\endcsname{\the\toks@}}%
3099 \fi}}%
3100 \fi
3101 \fi
3102 %
3103 \else
3104 %
3105 % The following code is still under study. You can test it and make
3106 % suggestions. Eg, enumerate.2 = ([enumi]).([enumii]). It's
3107 % language dependent.
3108 \in@{enumerate.}{#1}%
3109 \ifin@
3110 \def\bbl@tempa{#1}%
3111 \bbl@replace\bbl@tempa{enumerate.}{}%
3112 \def\bbl@toreplace{#2}%
3113 \bbl@replace\bbl@toreplace{[ ]}{\nobreakspace}%
3114 \bbl@replace\bbl@toreplace{[ ]}{\csname the}%
3115 \bbl@replace\bbl@toreplace{[ ]}{\endcsname}}%
3116 \toks@expandafter{\bbl@toreplace}%
3117 % TODO. Execute only once:
3118 \bbl@exp{%
3119 \\\bbl@add\<extras\language>%

```

```

3120      \\babel@save<labelenum\romannumeral\bbl@tempa>%
3121      \def<labelenum\romannumeral\bbl@tempa>{\the\toks@}%
3122      \\bbl@tglobal\<extras\language>%
3123      \fi
3124      \fi}

```

To show correctly some captions in a few languages, we need to patch some internal macros, because the order is hardcoded. For example, in Japanese the chapter number is surrounded by two string, while in Hungarian is placed after. These replacement works in many classes, but not all. Actually, the following lines are somewhat tentative.

```

3125 \def\bbl@chapttype{chapter}
3126 \ifx\@makechapterhead\@undefined
3127   \let\bbl@patchchapter\relax
3128 \else\ifx\thechapter\@undefined
3129   \let\bbl@patchchapter\relax
3130 \else\ifx\ps@headings\@undefined
3131   \let\bbl@patchchapter\relax
3132 \else
3133   \def\bbl@patchchapter{%
3134     \global\let\bbl@patchchapter\relax
3135     \gdef\bbl@chfmt{%
3136       \bbl@ifunset{bbl@\bbl@chapttype fmt@\language}%
3137       {\@chapapp\space\thechapter}
3138       {\@nameuse{bbl@\bbl@chapttype fmt@\language}}}
3139     \bbl@add\appendix{\def\bbl@chapttype{appendix}}% Not harmful, I hope
3140     \bbl@sreplace\ps@headings{\@chapapp\ \thechapter}{\bbl@chfmt}%
3141     \bbl@sreplace\chaptermark{\@chapapp\ \thechapter}{\bbl@chfmt}%
3142     \bbl@sreplace\@makechapterhead{\@chapapp\space\thechapter}{\bbl@chfmt}%
3143     \bbl@tglobal\appendix
3144     \bbl@tglobal\ps@headings
3145     \bbl@tglobal\chaptermark
3146     \bbl@tglobal\@makechapterhead}
3147     \let\bbl@patchappendix\bbl@patchchapter
3148   \fi\fi\fi
3149 \ifx\@part\@undefined
3150   \let\bbl@patchpart\relax
3151 \else
3152   \def\bbl@patchpart{%
3153     \global\let\bbl@patchpart\relax
3154     \gdef\bbl@partformat{%
3155       \bbl@ifunset{bbl@partfmt@\language}%
3156       {\partname\nobreakspace\thepart}
3157       {\@nameuse{bbl@partfmt@\language}}}
3158     \bbl@sreplace\@part{\partname\nobreakspace\thepart}{\bbl@partformat}%
3159     \bbl@tglobal\@part}
3160   \fi

```

Date. Arguments (year, month, day) are *not* protected, on purpose. In \today, arguments are always gregorian, and therefore always converted with other calendars. TODO. Document

```

3161 \let\bbl@calendar\@empty
3162 \DeclareRobustCommand\localedate[1][\bbl@localedate{#1}]
3163 \def\bbl@localedate#1#2#3#4{%
3164   \begingroup
3165     \edef\bbl@they{#2}%
3166     \edef\bbl@them{#3}%
3167     \edef\bbl@thed{#4}%
3168     \edef\bbl@tempe{%
3169       \bbl@ifunset{bbl@calpr@\language}{\bbl@cl{calpr}},%
3170       #1}%
3171     \bbl@replace\bbl@tempe{ }{}%
3172     \bbl@replace\bbl@tempe{CONVERT}{convert=}% Hackish
3173     \bbl@replace\bbl@tempe{convert}{convert=}%
3174     \let\bbl@ld@calendar\@empty
3175     \let\bbl@ld@variant\@empty

```

```

3176 \let\bbl@ld@convert\relax
3177 \def\bbl@tempb##1=##2\@{\@namedef\bbl@ld@##1}{##2}}%
3178 \bbl@foreach\bbl@tempe{\bbl@tempb##1\@}%
3179 \bbl@replace\bbl@ld@calendar{gregorian}{}%
3180 \ifx\bbl@ld@calendar\empty\else
3181 \ifx\bbl@ld@convert\relax\else
3182 \babelcalendar[\bbl@they-\bbl@them-\bbl@thed]%
3183 {\bbl@ld@calendar}\bbl@they\bbl@them\bbl@thed
3184 \fi
3185 \fi
3186 \@nameuse\bbl@precalendar}% Remove, eg, +, -civil (-ca-islamic)
3187 \edef\bbl@calendar{% Used in \month..., too
3188 \bbl@ld@calendar
3189 \ifx\bbl@ld@variant\empty\else
3190 .\bbl@ld@variant
3191 \fi}%
3192 \bbl@cased
3193 {\@nameuse\bbl@date@\language @\bbl@calendar}%
3194 \bbl@they\bbl@them\bbl@thed}%
3195 \endgroup}
3196 % eg: 1=months, 2=wide, 3=1, 4=dummy, 5=value, 6=calendar
3197 \def\bbl@inidate#1.#2.#3.#4\relax#5#6{% TODO - ignore with 'captions'
3198 \bbl@trim@def\bbl@tempa{#1.#2}%
3199 \bbl@ifsamestring{\bbl@tempa}{months.wide}% to savedate
3200 {\bbl@trim@def\bbl@tempa{#3}%
3201 \bbl@trim\toks@{#5}%
3202 \@temptokena\expandafter{\bbl@savestate}%
3203 \bbl@exp{% Reverse order - in ini last wins
3204 \def\\bbl@savestate{%
3205 \\SetString<month\romannumeral\bbl@tempa#6name>{\the\toks@}%
3206 \the\@temptokena}}}%
3207 {\bbl@ifsamestring{\bbl@tempa}{date.long}% defined now
3208 {\lowercase{\def\bbl@tempb{#6}}}%
3209 \bbl@trim@def\bbl@toreplace{#5}%
3210 \bbl@TG@@date
3211 \global\bbl@csarg\let{date@\language @\bbl@tempb}\bbl@toreplace
3212 \ifx\bbl@savetoday\empty
3213 \bbl@exp{% TODO. Move to a better place.
3214 \\AfterBabelCommands{%
3215 \def<\language date>{\\protect<\language date >}%
3216 \\newcommand<\language date >[4][]{%
3217 \\bbl@usedategroupttrue
3218 \<bbl@ensure@\language >{%
3219 \\localdate[####1]{####2}{####3}{####4}}}%
3220 \def\\bbl@savetoday{%
3221 \\SetString\\today{%
3222 \<\language date>[convert]%
3223 {\the\year}{\the\month}{\the\day}}}%
3224 \fi}%
3225 {}}}}

```

Dates will require some macros for the basic formatting. They may be redefined by language, so “semi-public” names (camel case) are used. Oddly enough, the CLDR places particles like “de” inconsistently in either in the date or in the month name. Note after `\bbl@replace\toks@` contains the resulting string, which is used by `\bbl@replace@finish@iii` (this implicit behavior doesn’t seem a good idea, but it’s efficient).

```

3226 \let\bbl@calendar\empty
3227 \newcommand\babelcalendar[2][\the\year-\the\month-\the\day]{%
3228 \@nameuse\bbl@ca@#2}#1\@%
3229 \newcommand\babelDateSpace{\nobreakspace}
3230 \newcommand\babelDateDot{\. \@ % TODO. \let instead of repeating
3231 \newcommand\babelDated[1]{\number#1}}
3232 \newcommand\babelDatedd[1]{\ifnum#1<10 0\fi\number#1}}

```

```

3233 \newcommand\BabelDateM[1]{\number#1}
3234 \newcommand\BabelDateMM[1]{\ifnum#1<10 0\fi\number#1}
3235 \newcommand\BabelDateMMM[1]{%
3236   \csname month\romannumeral#1\bbl@calendar name\endcsname}%
3237 \newcommand\BabelDateY[1]{\number#1}%
3238 \newcommand\BabelDateYY[1]{%
3239   \ifnum#1<10 0\number#1 %
3240   \else\ifnum#1<100 \number#1 %
3241   \else\ifnum#1<1000 \expandafter\@gobble\number#1 %
3242   \else\ifnum#1<10000 \expandafter\@gobbletwo\number#1 %
3243   \else
3244     \bbl@error{limit-two-digits}{\number#1}%
3245   \fi\fi\fi\fi}
3246 \newcommand\BabelDateYYYY[1]{\number#1} % TODO - add leading 0
3247 \newcommand\BabelDateU[1]{\number#1}%
3248 \def\bbl@replace@finish@iii#1{%
3249   \bbl@exp{\def\#1####1####2####3\the\toks@}}
3250 \def\bbl@TG@date{%
3251   \bbl@replace\bbl@toreplace{[ ]}{\BabelDateSpace{}}%
3252   \bbl@replace\bbl@toreplace{[.]}{\BabelDateDot{}}%
3253   \bbl@replace\bbl@toreplace{[d]}{\BabelDated{####3}}%
3254   \bbl@replace\bbl@toreplace{[dd]}{\BabelDatedd{####3}}%
3255   \bbl@replace\bbl@toreplace{[M]}{\BabelDateM{####2}}%
3256   \bbl@replace\bbl@toreplace{[MM]}{\BabelDateMM{####2}}%
3257   \bbl@replace\bbl@toreplace{[MMM]}{\BabelDateMMM{####2}}%
3258   \bbl@replace\bbl@toreplace{[y]}{\BabelDateY{####1}}%
3259   \bbl@replace\bbl@toreplace{[yy]}{\BabelDateYY{####1}}%
3260   \bbl@replace\bbl@toreplace{[yyy]}{\BabelDateYYY{####1}}%
3261   \bbl@replace\bbl@toreplace{[U]}{\BabelDateU{####1}}%
3262   \bbl@replace\bbl@toreplace{[y]}{\bbl@datecntr[####1]}%
3263   \bbl@replace\bbl@toreplace{[U]}{\bbl@datecntr[####1]}%
3264   \bbl@replace\bbl@toreplace{[m]}{\bbl@datecntr[####2]}%
3265   \bbl@replace\bbl@toreplace{[d]}{\bbl@datecntr[####3]}%
3266   \bbl@replace@finish@iii\bbl@toreplace}
3267 \def\bbl@datecntr{\expandafter\bbl@xdatecntr\expandafter}
3268 \def\bbl@xdatecntr[#1|#2]{\localenumeral{#2}{#1}}

```

Transforms.

```

3269 \bbl@csarg\let{inikv@transforms.prehyphenation}\bbl@inikv
3270 \bbl@csarg\let{inikv@transforms.posthyphenation}\bbl@inikv
3271 \def\bbl@transforms@aux#1#2#3#4,#5\relax{%
3272   #1[#2]{#3}{#4}{#5}}
3273 \begingroup % A hack. TODO. Don't require an specific order
3274   \catcode`\%=12
3275   \catcode`\&=14
3276   \gdef\bbl@transforms#1#2#3{%&
3277     \directlua{
3278       local str = [=[#2]=]
3279       str = str:gsub('%.%d+%.%d+$', '')
3280       token.set_macro('babeltempa', str)
3281     }&
3282     \def\babeltempc{}&
3283     \bbl@xin@{,\babeltempa,},{,\bbl@KVP@transforms,}&
3284     \ifin@ \else
3285       \bbl@xin@{:,\babeltempa,},{,\bbl@KVP@transforms,}&
3286     \fi
3287     \ifin@
3288       \bbl@foreach\bbl@KVP@transforms{%&
3289         \bbl@xin@{:,\babeltempa,},{,##1,}&
3290         \ifin@ & font:font:transform syntax
3291         \directlua{
3292           local t = {}
3293           for m in string.gmatch('##1'..'':', '(-.):') do

```



```

3294         table.insert(t, m)
3295     end
3296     table.remove(t)
3297     token.set_macro('babeltempc', ', fonts=' .. table.concat(t, ' '))
3298 }&%
3299 \fi}&%
3300 \in@{.0$}{#2$}&%
3301 \ifin@
3302     \directlua{&% (\attribute) syntax
3303         local str = string.match([[ \bbl@KVP@transforms]],
3304             '%([^(%-)]-)[^%)]-\babeltempa')
3305         if str == nil then
3306             token.set_macro('babeltempb', '')
3307         else
3308             token.set_macro('babeltempb', ', attribute=' .. str)
3309         end
3310     }&%
3311     \toks@{#3}&%
3312     \bbl@exp{&%
3313         \\g@addto@macro\\bbl@release@transforms{&%
3314             \relax &% Closes previous \bbl@transforms@aux
3315             \\bbl@transforms@aux
3316             \\\#1{label=\babeltempa\babeltempb\babeltempc}&%
3317             {\language\the\toks@}}&%
3318     \else
3319         \g@addto@macro\bbl@release@transforms{, {#3}}&%
3320     \fi
3321 \fi}
3322 \endgroup

```

Language and Script values to be used when defining a font or setting the direction are set with the following macros.

```

3323 \def\bbl@provide@lsys#1{%
3324     \bbl@ifunset{bbl@lname@#1}%
3325     {\bbl@load@info{#1}}%
3326     {%
3327         \bbl@csarg\let{lsys@#1}\@empty
3328         \bbl@ifunset{bbl@sname@#1}{\bbl@csarg\gdef{sname@#1}{Default}}{}%
3329         \bbl@ifunset{bbl@sotf@#1}{\bbl@csarg\gdef{sotf@#1}{DFLT}}{}%
3330         \bbl@csarg\bbl@add@list{lsys@#1}{Script=\bbl@cs{sname@#1}}%
3331         \bbl@ifunset{bbl@lname@#1}{%
3332             {\bbl@csarg\bbl@add@list{lsys@#1}{Language=\bbl@cs{lname@#1}}}%
3333         \ifcase\bbl@engine\or\or
3334             \bbl@ifunset{bbl@prehc@#1}{%
3335                 {\bbl@exp{\\bbl@ifblank{\bbl@cs{prehc@#1}}}%
3336                 {%
3337                     {\ifx\bbl@xenoxyph\undefined
3338                         \global\let\bbl@xenoxyph\bbl@xenoxyph@d
3339                     \ifx\AtBeginDocument\@notprerr
3340                         \expandafter\@secondoftwo % to execute right now
3341                     \fi
3342                     \AtBeginDocument{%
3343                         \bbl@patchfont{\bbl@xenoxyph}%
3344                         {\expandafter\select@language\expandafter{\language\the\toks@}}}%
3345                     \fi}}%
3346             \fi
3347             \bbl@csarg\bbl@to@global{lsys@#1}}
3348 \def\bbl@xenoxyph@d{%
3349     \bbl@ifset{bbl@prehc@\language\the\toks@}%
3350     {\ifnum\hyphenchar\font=\defaultshyphenchar
3351         \iffontchar\font\bbl@cl{prehc}\relax
3352         \hyphenchar\font\bbl@cl{prehc}\relax
3353     \else\iffontchar\font"200B

```

```

3354         \hyphenchar\font"200B
3355     \else
3356         \bbl@warning
3357             {Neither 0 nor ZERO WIDTH SPACE are available\\%
3358               in the current font, and therefore the hyphen\\%
3359               will be printed. Try changing the fontspec's\\%
3360               'HyphenChar' to another value, but be aware\\%
3361               this setting is not safe (see the manual).\\%
3362               Reported}%
3363         \hyphenchar\font\defaultshyphenchar
3364     \fi\fi
3365 \fi}%
3366 {\hyphenchar\font\defaultshyphenchar}}
3367 % \fi}

```

```

3368 \def\bbl@load@info#1{%
3369   \def\BabelBeforeIni##1##2{%
3370     \begingroup
3371       \bbl@read@ini{##1}0%
3372       \endinput           % babel- .tex may contain onlypreamble's
3373       \endgroup}%         boxed, to avoid extra spaces:
3374   {\bbl@input@texini{#1}}}
```

[illegible]

```
3406 \def\bbl@buildifcase#1 {% Returns \bbl@tempa, requires \toks@={}
```

```

3407 \ifx\#1% % \ before, in case #1 is multiletter
3408 \bbl@exp{%
3409 \def\#1\bbl@tempa###1{%
3410 \<ifcase>###1\space\the\toks@<else>\@ctrerr<fi>}%
3411 \else
3412 \toks@<expandafter{\the\toks@<or #1>%
3413 \expandafter\bbl@builddifcase
3414 \fi}

```

The code for additive counters is somewhat tricky and it's based on the fact the arguments just before @@ collects digits which have been left 'unused' in previous arguments, the first of them being the number of digits in the number to be converted. This explains the reverse set 76543210. Digits above 10000 are not handled yet. When the key contains the subkey .F., the number after is treated as an special case, for a fixed form (see babel-he.ini, for example).

```

3415 \newcommand\localecnum[2]{\bbl@cs{cnt#1@language}{#2}}
3416 \def\bbl@localecnum#1#2{\localecnum{#2}{#1}}
3417 \newcommand\localecnum[2]{%
3418 \expandafter\bbl@localecnum
3419 \expandafter{\number\csname c@#2\endcsname}{#1}}
3420 \def\bbl@alphnumeral#1#2{%
3421 \expandafter\bbl@alphnumeral@i\number#2 76543210@@{#1}}
3422 \def\bbl@alphnumeral@i#1#2#3#4#5#6#7#8\@#9{%
3423 \ifcase\car#8\@nil\or % Currently <10000, but prepared for bigger
3424 \bbl@alphnumeral@ii{#9}000000#1\or
3425 \bbl@alphnumeral@ii{#9}00000#1#2\or
3426 \bbl@alphnumeral@ii{#9}0000#1#2#3\or
3427 \bbl@alphnumeral@ii{#9}000#1#2#3#4\else
3428 \bbl@alphnum@invalid{>9999}%
3429 \fi}
3430 \def\bbl@alphnumeral@ii#1#2#3#4#5#6#7#8{%
3431 \bbl@ifunset{bbl@cnt#1.F.\number#5#6#7#8@language}%
3432 {\bbl@cs{cnt#1.4@language}{#5}
3433 \bbl@cs{cnt#1.3@language}{#6}
3434 \bbl@cs{cnt#1.2@language}{#7}
3435 \bbl@cs{cnt#1.1@language}{#8}
3436 \ifnum#6#7#8>\z@ % TODO. An ad hoc rule for Greek. Ugly.
3437 \bbl@ifunset{bbl@cnt#1.S.321@language}{}%
3438 {\bbl@cs{cnt#1.S.321@language}{}}%
3439 \fi}%
3440 {\bbl@cs{cnt#1.F.\number#5#6#7#8@language}{}}%
3441 \def\bbl@alphnum@invalid#1{%
3442 \bbl@error{alphabetic-too-large}{#1}{}}

```

The information in the identification section can be useful, so the following macro just exposes it with a user command.

```

3443 \def\bbl@localeinfo#1#2{%
3444 \bbl@ifunset{bbl@info@#2}{#1}%
3445 {\bbl@ifunset{bbl@csname bbl@info@#2\endcsname @language}{#1}%
3446 {\bbl@cs{csname bbl@info@#2\endcsname @language}{}}}
3447 \newcommand\localeinfo[1]{%
3448 \ifx*#1\empty % TODO. A bit hackish to make it expandable.
3449 \bbl@afterelse\bbl@localeinfo}%
3450 \else
3451 \bbl@localeinfo
3452 {\bbl@error{no-ini-info}{}}}%
3453 {#1}%
3454 \fi}
3455 % \namedef{bbl@info@name.locale}{lname}
3456 \namedef{bbl@info@tag.ini}{lini}
3457 \namedef{bbl@info@name.english}{elname}
3458 \namedef{bbl@info@name.opentype}{lname}
3459 \namedef{bbl@info@tag.bcp47}{tbcp}
3460 \namedef{bbl@info@language.tag.bcp47}{lbcp}
3461 \namedef{bbl@info@tag.opentype}{lotf}

```

```

3462 \@namedef{bbl@info@script.name}{esname}
3463 \@namedef{bbl@info@script.name.opentype}{sname}
3464 \@namedef{bbl@info@script.tag.bcp47}{sbcp}
3465 \@namedef{bbl@info@script.tag.opentype}{sotf}
3466 \@namedef{bbl@info@region.tag.bcp47}{rbcp}
3467 \@namedef{bbl@info@variant.tag.bcp47}{vbcp}
3468 \@namedef{bbl@info@extension.t.tag.bcp47}{extt}
3469 \@namedef{bbl@info@extension.u.tag.bcp47}{extu}
3470 \@namedef{bbl@info@extension.x.tag.bcp47}{extx}

```

\LaTeX needs to know the BCP 47 codes for some features. For that, it expects \BCPdata to be defined. While language, region, script, and variant are recognized, extension.(s) for singletons may change.

```

3471 \ifcase\bbl@engine % Converts utf8 to its code (expandable)
3472   \def\bbl@utftocode#1{\the\numexpr\decode@UTFviii#1\relax}
3473 \else
3474   \def\bbl@utftocode#1{\expandafter`\string#1}
3475 \fi
3476 % Still somewhat hackish. WIP. Note |\str_if_eq:nnTF| is fully
3477 % expandable (|\bbl@ifsamestring| isn't).
3478 \providecommand\BCPdata{}
3479 \ifx\renewcommand\undefined\else % For plain. TODO. It's a quick fix
3480   \renewcommand\BCPdata[1]{\bbl@bcpdata@i#1\@empty}
3481   \def\bbl@bcpdata@i#1#2#3#4#5#6\@empty{%
3482     \@nameuse{str_if_eq:nnTF}{#1#2#3#4#5}{main.}%
3483     {\bbl@bcpdata@ii#6}\bbl@main@language}%
3484     {\bbl@bcpdata@ii#1#2#3#4#5#6}\language}%
3485   \def\bbl@bcpdata@ii#1#2{%
3486     \bbl@ifunset{bbl@info@#1.tag.bcp47}%
3487     {\bbl@error{unknown-ini-field}{#1}{}}%
3488     {\bbl@ifunset{bbl@csname bbl@info@#1.tag.bcp47\endcsname @#2}{}%
3489     {\bbl@cs{csname bbl@info@#1.tag.bcp47\endcsname @#2}}}%
3490 \fi
3491 \@namedef{bbl@info@casing.tag.bcp47}{casing}
3492 \newcommand\BabelUppercaseMapping[3]{%
3493   \DeclareUppercaseMapping[\@nameuse{bbl@casing@#1}]{#2}{#3}}
3494 \newcommand\BabelTitlecaseMapping[3]{%
3495   \DeclareTitlecaseMapping[\@nameuse{bbl@casing@#1}]{#2}{#3}}
3496 \newcommand\BabelLowercaseMapping[3]{%
3497   \DeclareLowercaseMapping[\@nameuse{bbl@casing@#1}]{#2}{#3}}

```

The parser for casing and casing.(variant).

```

3498 \def\bbl@casemapping#1#2#3{% 1:variant
3499   \def\bbl@tempa##1 ##2{% Loop
3500     \bbl@casemapping@i{##1}%
3501     \ifx\@empty##2\else\bbl@afterfi\bbl@tempa##2\fi}%
3502   \edef\bbl@templ{\@nameuse{bbl@casing@#2}#1}% Language code
3503   \def\bbl@tempe{0}% Mode (upper/lower...)
3504   \def\bbl@tempc{#3}% Casing list
3505   \expandafter\bbl@tempa\bbl@tempc\@empty}
3506 \def\bbl@casemapping@i#1{%
3507   \def\bbl@tempb{#1}%
3508   \ifcase\bbl@engine % Handle utf8 in pdftex, by surrounding chars with {}
3509     \@nameuse{regex_replace_all:nnN}%
3510     {[{\x{c0}-\x{ff}}][{\x{80}-\x{bf}}]*}{\0}}\bbl@tempb
3511   \else
3512     \@nameuse{regex_replace_all:nnN}{.}{\0}}\bbl@tempb % TODO. needed?
3513   \fi
3514   \expandafter\bbl@casemapping@ii\bbl@tempb\@}
3515 \def\bbl@casemapping@ii#1#2#3\@{%
3516   \in@{#1#3}{<>}% ie, if <u>, <l>, <t>
3517   \ifin@
3518     \edef\bbl@tempe{%
3519       \if#2u1 \else\if#2l2 \else\if#2t3 \fi\fi\fi}%

```

```

3520 \else
3521   \ifcase\bb@tempe\relax
3522     \DeclareUppercaseMapping[\bb@templ]{\bb@uftocode{#1}}{#2}%
3523     \DeclareLowercaseMapping[\bb@templ]{\bb@uftocode{#2}}{#1}%
3524   \or
3525     \DeclareUppercaseMapping[\bb@templ]{\bb@uftocode{#1}}{#2}%
3526   \or
3527     \DeclareLowercaseMapping[\bb@templ]{\bb@uftocode{#1}}{#2}%
3528   \or
3529     \DeclareTitlecaseMapping[\bb@templ]{\bb@uftocode{#1}}{#2}%
3530   \fi
3531 \fi}

```

With version 3.75 \BabelEnsureInfo is executed always, but there is an option to disable it.

```

3532 <<(*More package options)>> ≡
3533 \DeclareOption{ensureinfo=off}{}
3534 <</More package options>>
3535 \let\bb@ensureinfo@gobble
3536 \newcommand\BabelEnsureInfo{%
3537   \ifx\InputIfFileExists\undefined\else
3538     \def\bb@ensureinfo##1{%
3539       \bb@ifunset{bb@lname@##1}{\bb@load@info{##1}}{}}%
3540   \fi
3541   \bb@foreach\bb@loaded{%
3542     \let\bb@ensuring\@empty % Flag used in a couple of babel-*.tex files
3543     \def\languagename{##1}%
3544     \bb@ensureinfo{##1}}}%
3545 \@ifpackagewith{babel}{ensureinfo=off}{}%
3546 {\AtEndOfPackage{% Test for plain.
3547   \ifx\undefined\bb@loaded\else\BabelEnsureInfo\fi}}

```

More general, but non-expandable, is \getlocaleproperty. To inspect every possible loaded ini, we define \LocaleForEach, where \bb@ini@loaded is a comma-separated list of locales, built by \bb@read@ini.

```

3548 \newcommand\getlocaleproperty{%
3549   \ifstar\bb@getproperty@s\bb@getproperty@x}
3550 \def\bb@getproperty@s#1#2#3{%
3551   \let#1\relax
3552   \def\bb@elt##1##2##3{%
3553     \bb@ifsamestring{##1/##2}{#3}%
3554     {\providecommand#1{##3}%
3555     \def\bb@elt####1####2####3{}}}%
3556   {}}%
3557   \bb@cs{inidata@#2}}%
3558 \def\bb@getproperty@x#1#2#3{%
3559   \bb@getproperty@s{#1}{#2}{#3}%
3560   \ifx#1\relax
3561     \bb@error{unknown-locale-key}{#1}{#2}{#3}%
3562   \fi}
3563 \let\bb@ini@loaded\@empty
3564 \newcommand\LocaleForEach{\bb@foreach\bb@ini@loaded}
3565 \def\ShowLocaleProperties#1{%
3566   \typeout{}%
3567   \typeout{*** Properties for language '#1' ***}
3568   \def\bb@elt##1##2##3{\typeout{##1/##2 = ##3}}%
3569   \@nameuse{bb@inidata@#1}%
3570   \typeout{*****}}

```

5 Adjusting the Babel bahavior

A generic high level interface is provided to adjust some global and general settings.

```

3571 \newcommand\babeladjust[1]{% TODO. Error handling.

```

```

3572 \bbl@forkv{#1}{%
3573   \bbl@ifunset{bbl@ADJ@##1@##2}%
3574   {\bbl@cs{ADJ@##1}{##2}}%
3575   {\bbl@cs{ADJ@##1@##2}}}%
3576 %
3577 \def\bbl@adjust@lua#1#2{%
3578   \ifvmode
3579     \ifnum\currentgrouplevel=\z@
3580       \directlua{ Babel.#2 }%
3581       \expandafter\expandafter\expandafter\@gobble
3582     \fi
3583   \fi
3584   {\bbl@error{adjust-only-vertical}{#1}{}}}% Gobbled if everything went ok.
3585 \@namedef{bbl@ADJ@bidi.mirroring@on}{%
3586   \bbl@adjust@lua{bidi}{mirroring_enabled=true}}
3587 \@namedef{bbl@ADJ@bidi.mirroring@off}{%
3588   \bbl@adjust@lua{bidi}{mirroring_enabled=false}}
3589 \@namedef{bbl@ADJ@bidi.text@on}{%
3590   \bbl@adjust@lua{bidi}{bidi_enabled=true}}
3591 \@namedef{bbl@ADJ@bidi.text@off}{%
3592   \bbl@adjust@lua{bidi}{bidi_enabled=false}}
3593 \@namedef{bbl@ADJ@bidi.math@on}{%
3594   \let\bbl@noamsmath\@empty}
3595 \@namedef{bbl@ADJ@bidi.math@off}{%
3596   \let\bbl@noamsmath\relax}
3597 \@namedef{bbl@ADJ@bidi.mapdigits@on}{%
3598   \bbl@adjust@lua{bidi}{digits_mapped=true}}
3599 \@namedef{bbl@ADJ@bidi.mapdigits@off}{%
3600   \bbl@adjust@lua{bidi}{digits_mapped=false}}
3601 %
3602 \@namedef{bbl@ADJ@linebreak.sea@on}{%
3603   \bbl@adjust@lua{linebreak}{sea_enabled=true}}
3604 \@namedef{bbl@ADJ@linebreak.sea@off}{%
3605   \bbl@adjust@lua{linebreak}{sea_enabled=false}}
3606 \@namedef{bbl@ADJ@linebreak.cjk@on}{%
3607   \bbl@adjust@lua{linebreak}{cjk_enabled=true}}
3608 \@namedef{bbl@ADJ@linebreak.cjk@off}{%
3609   \bbl@adjust@lua{linebreak}{cjk_enabled=false}}
3610 \@namedef{bbl@ADJ@justify.arabic@on}{%
3611   \bbl@adjust@lua{linebreak}{arabic.justify_enabled=true}}
3612 \@namedef{bbl@ADJ@justify.arabic@off}{%
3613   \bbl@adjust@lua{linebreak}{arabic.justify_enabled=false}}
3614 %
3615 \def\bbl@adjust@layout#1{%
3616   \ifvmode
3617     #1%
3618     \expandafter\@gobble
3619   \fi
3620   {\bbl@error{layout-only-vertical}{}}}% Gobbled if everything went ok.
3621 \@namedef{bbl@ADJ@layout.tabular@on}{%
3622   \ifnum\bbl@tabular@mode=\tw@
3623     \bbl@adjust@layout{\let\@tabular\bbl@NL@tabular}%
3624   \else
3625     \chardef\bbl@tabular@mode\@ne
3626   \fi}
3627 \@namedef{bbl@ADJ@layout.tabular@off}{%
3628   \ifnum\bbl@tabular@mode=\tw@
3629     \bbl@adjust@layout{\let\@tabular\bbl@OL@tabular}%
3630   \else
3631     \chardef\bbl@tabular@mode\z@
3632   \fi}
3633 \@namedef{bbl@ADJ@layout.lists@on}{%
3634   \bbl@adjust@layout{\let\list\bbl@NL@list}}

```

```

3635 \@namedef{bbl@ADJ@layout.lists@off}{%
3636   \bbl@adjust@layout{\let\list\bbl@OL@list}}
3637 %
3638 \@namedef{bbl@ADJ@autoload.bcp47@on}{%
3639   \bbl@bcpallowedtrue}
3640 \@namedef{bbl@ADJ@autoload.bcp47@off}{%
3641   \bbl@bcpallowedfalse}
3642 \@namedef{bbl@ADJ@autoload.bcp47.prefix}#1{%
3643   \def\bbl@bcp@prefix{#1}}
3644 \def\bbl@bcp@prefix{bcp47-}
3645 \@namedef{bbl@ADJ@autoload.options}#1{%
3646   \def\bbl@autoload@options{#1}}
3647 \let\bbl@autoload@bcptoptions\@empty
3648 \@namedef{bbl@ADJ@autoload.bcp47.options}#1{%
3649   \def\bbl@autoload@bcptoptions{#1}}
3650 \newif\ifbbl@bcptoname
3651 \@namedef{bbl@ADJ@bcp47.toname@on}{%
3652   \bbl@bcptonametrue}
3653 \BabelEnsureInfo{
3654 \@namedef{bbl@ADJ@bcp47.toname@off}{%
3655   \bbl@bcptonamefalse}
3656 \@namedef{bbl@ADJ@prehyphenation.disable@nohyphenation}{%
3657   \directlua{ Babel.ignore_pre_char = function(node)
3658     return (node.lang == \the\csname l@nohyphenation\endcsname)
3659   end }}
3660 \@namedef{bbl@ADJ@prehyphenation.disable@off}{%
3661   \directlua{ Babel.ignore_pre_char = function(node)
3662     return false
3663   end }}
3664 \@namedef{bbl@ADJ@interchar.disable@nohyphenation}{%
3665   \def\bbl@ignoreinterchar{%
3666     \ifnum\language=\l@nohyphenation
3667       \expandafter\@gobble
3668     \else
3669       \expandafter\@firstofone
3670     \fi}}
3671 \@namedef{bbl@ADJ@interchar.disable@off}{%
3672   \let\bbl@ignoreinterchar\@firstofone}
3673 \@namedef{bbl@ADJ@select.write@shift}{%
3674   \let\bbl@restorelastskip\relax
3675   \def\bbl@savelastskip{%
3676     \let\bbl@restorelastskip\relax
3677     \ifvmode
3678       \ifdim\lastskip=\z@
3679         \let\bbl@restorelastskip\nobreak
3680       \else
3681         \bbl@exp{%
3682           \def\\bbl@restorelastskip{%
3683             \skip@=\the\lastskip
3684             \\nobreak \vskip-\skip@ \vskip\skip@}}%
3685         \fi
3686       \fi}}
3687 \@namedef{bbl@ADJ@select.write@keep}{%
3688   \let\bbl@restorelastskip\relax
3689   \let\bbl@savelastskip\relax}
3690 \@namedef{bbl@ADJ@select.write@omit}{%
3691   \AddBabelHook{babel-select}{beforestart}{%
3692     \expandafter\babel@aux\expandafter{\bbl@main@language}}}%
3693 \let\bbl@restorelastskip\relax
3694 \def\bbl@savelastskip##1\bbl@restorelastskip{}}
3695 \@namedef{bbl@ADJ@select.encoding@off}{%
3696   \let\bbl@encoding@select@off\@empty}

```

5.1 Cross referencing macros

The \LaTeX book states:

The *key* argument is any sequence of letters, digits, and punctuation symbols; upper- and lowercase letters are regarded as different.

When the above quote should still be true when a document is typeset in a language that has active characters, special care has to be taken of the category codes of these characters when they appear in an argument of the cross referencing macros.

When a cross referencing command processes its argument, all tokens in this argument should be character tokens with category ‘letter’ or ‘other’.

The following package options control which macros are to be redefined.

```
3697 <<{*More package options}>> ≡
3698 \DeclareOption{safe=none}{\let\bbl@opt@safe\empty}
3699 \DeclareOption{safe=bib}{\def\bbl@opt@safe{B}}
3700 \DeclareOption{safe=ref}{\def\bbl@opt@safe{R}}
3701 \DeclareOption{safe=refbib}{\def\bbl@opt@safe{BR}}
3702 \DeclareOption{safe=bibref}{\def\bbl@opt@safe{BR}}
3703 <</More package options>>
```

`\@newl@bel` First we open a new group to keep the changed setting of `\protect` local and then we set the `@safe@actives` switch to true to make sure that any shorthand that appears in any of the arguments immediately expands to its non-active self.

```
3704 \bbl@trace{Cross referencing macros}
3705 \ifx\bbl@opt@safe\empty\else % ie, if 'ref' and/or 'bib'
3706   \def\@newl@bel#1#2#3{%
3707     \@safe@activestrue
3708     \bbl@ifunset{#1@#2}%
3709       \relax
3710     {\gdef\@multiplelabels{%
3711       \@latex@warning@no@line{There were multiply-defined labels}}%
3712       \@latex@warning@no@line{Label `#2' multiply defined}}%
3713     \global\@namedef{#1@#2}{#3}}}
```

`\@testdef` An internal \LaTeX macro used to test if the labels that have been written on the .aux file have changed. It is called by the `\enddocument` macro.

```
3714 \CheckCommand*\@testdef[3]{%
3715   \def\reserved@a{#3}%
3716   \expandafter\ifx\csname#1@#2\endcsname\reserved@a
3717   \else
3718     \@tempswatrue
3719   \fi}
```

Now that we made sure that `\@testdef` still has the same definition we can rewrite it. First we make the shorthands ‘safe’. Then we use `\bbl@tempa` as an ‘alias’ for the macro that contains the label which is being checked. Then we define `\bbl@tempb` just as `\@newl@bel` does it. When the label is defined we replace the definition of `\bbl@tempa` by its meaning. If the label didn’t change, `\bbl@tempa` and `\bbl@tempb` should be identical macros.

```
3720 \def\@testdef#1#2#3{% TODO. With @samestring?
3721   \@safe@activestrue
3722   \expandafter\let\expandafter\bbl@tempa\csname #1@#2\endcsname
3723   \def\bbl@tempb{#3}%
3724   \@safe@activesfalse
3725   \ifx\bbl@tempa\relax
3726   \else
3727     \edef\bbl@tempa{\expandafter\strip@prefix\meaning\bbl@tempa}%
3728   \fi
3729   \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
3730   \ifx\bbl@tempa\bbl@tempb
3731   \else
3732     \@tempswatrue
3733   \fi}
3734 \fi
```


`\ref` The same holds for the macro `\ref` that references a label and `\pageref` to reference a page. We make them robust as well (if they weren't already) to prevent problems if they should become expanded at the wrong moment.

```

3735 \bbl@xin@{R}\bbl@opt@safe
3736 \ifin@
3737 \edef\bbl@tempc{\expandafter\string\csname ref code\endcsname}%
3738 \bbl@xin@{\expandafter\strip@prefix\meaning\bbl@tempc}%
3739 {\expandafter\strip@prefix\meaning\ref}%
3740 \ifin@
3741 \bbl@redefine\@kernel@ref#1{%
3742   \@safe@activetrue\org@@kernel@ref{#1}\@safe@activfalse}
3743 \bbl@redefine\@kernel@pageref#1{%
3744   \@safe@activetrue\org@@kernel@pageref{#1}\@safe@activfalse}
3745 \bbl@redefine\@kernel@sref#1{%
3746   \@safe@activetrue\org@@kernel@sref{#1}\@safe@activfalse}
3747 \bbl@redefine\@kernel@spageref#1{%
3748   \@safe@activetrue\org@@kernel@spageref{#1}\@safe@activfalse}
3749 \else
3750 \bbl@redefineroquest\ref#1{%
3751   \@safe@activetrue\org@ref{#1}\@safe@activfalse}
3752 \bbl@redefineroquest\pageref#1{%
3753   \@safe@activetrue\org@pageref{#1}\@safe@activfalse}
3754 \fi
3755 \else
3756 \let\org@ref\ref
3757 \let\org@pageref\pageref
3758 \fi

```

`\@citex` The macro used to cite from a bibliography, `\cite`, uses an internal macro, `\@citex`. It is this internal macro that picks up the argument(s), so we redefine this internal macro and leave `\cite` alone. The first argument is used for typesetting, so the shorthands need only be deactivated in the second argument.

```

3759 \bbl@xin@{B}\bbl@opt@safe
3760 \ifin@
3761 \bbl@redefine\@citex[#1]#2{%
3762   \@safe@activetrue\edef\bbl@tempa{#2}\@safe@activfalse
3763   \org@@citex[#1]{\bbl@tempa}}

```

Unfortunately, the packages `natbib` and `cite` need a different definition of `\@citex`... To begin with, `natbib` has a definition for `\@citex` with *three* arguments... We only know that a package is loaded when `\begin{document}` is executed, so we need to postpone the different redefinition.

```

3764 \AtBeginDocument{%
3765   \@ifpackageloaded{natbib}{%

```

Notice that we use `\def` here instead of `\bbl@redefine` because `\org@@citex` is already defined and we don't want to overwrite that definition (it would result in parameter stack overflow because of a circular definition).

(Recent versions of `natbib` change dynamically `\@citex`, so PR4087 doesn't seem fixable in a simple way. Just load `natbib` before.)

```

3766   \def\@citex[#1][#2]#3{%
3767     \@safe@activetrue\edef\bbl@tempa{#3}\@safe@activfalse
3768     \org@@citex[#1][#2]{\bbl@tempa}}%
3769   }{}

```

The package `cite` has a definition of `\@citex` where the shorthands need to be turned off in both arguments.

```

3770 \AtBeginDocument{%
3771   \@ifpackageloaded{cite}{%
3772     \def\@citex[#1]#2{%
3773       \@safe@activetrue\org@@citex[#1][#2]\@safe@activfalse}%
3774     }{}

```

`\nocite` The macro `\nocite` which is used to instruct Bi_T_E_X to extract uncited references from the database.

```
3775 \bbl@redefine\nocite#1{%
3776   \@safe@activestruer\org@nocite{#1}\@safe@activesfalse}
```

`\bibcite` The macro that is used in the .aux file to define citation labels. When packages such as `natbib` or `cite` are not loaded its second argument is used to typeset the citation label. In that case, this second argument can contain active characters but is used in an environment where `\@safe@activestruer` is in effect. This switch needs to be reset inside the `\hbox` which contains the citation label. In order to determine during .aux file processing which definition of `\bibcite` is needed we define `\bibcite` in such a way that it redefines itself with the proper definition. We call `\bbl@cite@choice` to select the proper definition for `\bibcite`. This new definition is then activated.

```
3777 \bbl@redefine\bibcite{%
3778   \bbl@cite@choice
3779   \bibcite}
```

`\bbl@bibcite` The macro `\bbl@bibcite` holds the definition of `\bibcite` needed when neither `natbib` nor `cite` is loaded.

```
3780 \def\bbl@bibcite#1#2{%
3781   \org@bibcite{#1}\@safe@activesfalse#2}}
```

`\bbl@cite@choice` The macro `\bbl@cite@choice` determines which definition of `\bibcite` is needed. First we give `\bibcite` its default definition.

```
3782 \def\bbl@cite@choice{%
3783   \global\let\bibcite\bbl@bibcite
3784   \ifpackageloaded{natbib}\global\let\bibcite\org@bibcite}%
3785   \ifpackageloaded{cite}\global\let\bibcite\org@bibcite}%
3786   \global\let\bbl@cite@choice\relax}
```

When a document is run for the first time, no .aux file is available, and `\bibcite` will not yet be properly defined. In this case, this has to happen before the document starts.

```
3787 \AtBeginDocument{\bbl@cite@choice}
```

`\@bibitem` One of the two internal L^AT_EX macros called by `\bibitem` that write the citation label on the .aux file.

```
3788 \bbl@redefine\@bibitem#1{%
3789   \@safe@activestruer\org@bibitem{#1}\@safe@activesfalse}
3790 \else
3791   \let\org@nocite\nocite
3792   \let\org@citex\citex
3793   \let\org@bibcite\bibcite
3794   \let\org@bibitem\@bibitem
3795 \fi
```

5.2 Marks

`\markright` Because the output routine is asynchronous, we must pass the current language attribute to the head lines. To achieve this we need to adapt the definition of `\markright` and `\markboth` somewhat. However, headlines and footlines can contain text outside marks; for that we must take some actions in the output routine if the 'headfoot' options is used.

We need to make some redefinitions to the output routine to avoid an endless loop and to correctly handle the page number in bidi documents.

```
3796 \bbl@trace{Marks}
3797 \IfBabelLayout{sectioning}
3798   {\ifx\bbl@opt@headfoot\@nnil
3799     \g@addto@macro\@resetactivechars{%
3800       \set@typeset@protect
3801       \expandafter\select@language\x\expandafter{\bbl@main@language}%
3802       \let\protect\noexpand
3803       \ifcase\bbl@bidimode\else % Only with bidi. See also above
3804         \edef\thepage{%
3805           \noexpand\babelsublr{\unexpanded\expandafter{\thepage}}}%
3806       \fi}%
```

```

3807 \fi}
3808 {\ifbbl@single\else
3809 \bbl@ifunset{markright }\bbl@redefine\bbl@redefineroobust
3810 \markright#1{%
3811 \bbl@ifblank{#1}%
3812 {\org@markright{}}}%
3813 {\toks@{#1}%
3814 \bbl@exp{%
3815 \\\org@markright{\\protect\\foreignlanguage{\language}\language}%
3816 {\\\protect\\bbl@restore@actives\the\toks@}}}%

```

`\markboth` The definition of `\markboth` is equivalent to that of `\markright`, except that we need two token registers. The documentclasses report and book define and set the headings for the page. While doing so they also store a copy of `\markboth` in `\mkboth`. Therefore we need to check whether `\mkboth` has already been set. If so we need to do that again with the new definition of `\markboth`. (As of Oct 2019, \LaTeX stores the definition in an intermediate macro, so it's not necessary anymore, but it's preserved for older versions.)

```

3817 \ifx\mkboth\markboth
3818 \def\bbl@tempc{\let\mkboth\markboth}%
3819 \else
3820 \def\bbl@tempc{%
3821 \fi
3822 \bbl@ifunset{markboth }\bbl@redefine\bbl@redefineroobust
3823 \markboth#1#2{%
3824 \protected@edef\bbl@tempb##1{%
3825 \protect\foreignlanguage
3826 {\language}\protect\bbl@restore@actives##1}}%
3827 \bbl@ifblank{#1}%
3828 {\toks@{}}%
3829 {\toks@\expandafter{\bbl@tempb{#1}}}%
3830 \bbl@ifblank{#2}%
3831 {\@temptokena{}}%
3832 {\@temptokena\expandafter{\bbl@tempb{#2}}}%
3833 \bbl@exp{\\org@markboth{\the\toks@}{\the\@temptokena}}}%
3834 \bbl@tempc
3835 \fi} % end ifbbl@single, end \IfBabelLayout

```

5.3 Preventing clashes with other packages

5.3.1 `ifthen`

`\ifthenelse` Sometimes a document writer wants to create a special effect depending on the page a certain fragment of text appears on. This can be achieved by the following piece of code:

```

\ifthenelse{\isodd{\pageref{some:label}}}
{code for odd pages}
{code for even pages}

```

In order for this to work the argument of `\isodd` needs to be fully expandable. With the above redefinition of `\pageref` it is not in the case of this example. To overcome that, we add some code to the definition of `\ifthenelse` to make things work.

We want to revert the definition of `\pageref` and `\ref` to their original definition for the first argument of `\ifthenelse`, so we first need to store their current meanings.

Then we can set the `\@safe@actives` switch and call the original `\ifthenelse`. In order to be able to use shorthands in the second and third arguments of `\ifthenelse` the resetting of the switch *and* the definition of `\pageref` happens inside those arguments.

```

3836 \bbl@trace{Preventing clashes with other packages}
3837 \ifx\org@ref\undefined\else
3838 \bbl@xin@{R}\bbl@opt@safe
3839 \ifin@
3840 \AtBeginDocument{%
3841 \@ifpackageloaded{ifthen}{%

```

```

3842      \bbl@redefine@long\ifthenelse#1#2#3{%
3843      \let\bbl@temp@pref\pageref
3844      \let\pageref\org@pageref
3845      \let\bbl@temp@ref\ref
3846      \let\ref\org@ref
3847      \@safe@activetrue
3848      \org@ifthenelse{#1}%
3849      {\let\pageref\bbl@temp@pref
3850      \let\ref\bbl@temp@ref
3851      \@safe@activesfalse
3852      #2}%
3853      {\let\pageref\bbl@temp@pref
3854      \let\ref\bbl@temp@ref
3855      \@safe@activesfalse
3856      #3}%
3857      }%
3858      }{}%
3859      }
3860 \fi

```

5.3.2 varioref

`\@vppageref` When the package `varioref` is in use we need to modify its internal command `\@vppageref` in order to prevent problems when an active character ends up in the argument of `\vref`. The same needs to happen for `\vrefpagemum`.

```

3861 \AtBeginDocument{%
3862   \ifpackageloaded{varioref}{%
3863     \bbl@redefine\@vppageref#1[#2]#3{%
3864       \@safe@activetrue
3865       \org@@@vppageref{#1}[#2]#3}%
3866       \@safe@activesfalse}%
3867     \bbl@redefine\vrefpagemum#1#2{%
3868       \@safe@activetrue
3869       \org@vrefpagemum{#1}#2}%
3870       \@safe@activesfalse}%

```

The package `varioref` defines `\Ref` to be a robust command which uppercases the first character of the reference text. In order to be able to do that it needs to access the expandable form of `\ref`. So we employ a little trick here. We redefine the (internal) command `\Ref_` to call `\org@ref` instead of `\ref`. The disadvantage of this solution is that whenever the definition of `\Ref` changes, this definition needs to be updated as well.

```

3871   \expandafter\def\csname Ref \endcsname#1{%
3872     \protected@edef\@tempa{\org@ref{#1}}\expandafter\MakeUppercase\@tempa}
3873   }{}%
3874   }
3875 \fi

```

5.3.3 hhline

`\hhline` Delaying the activation of the shorthand characters has introduced a problem with the `hhline` package. The reason is that it uses the ‘:’ character which is made active by the french support in `babel`. Therefore we need to *reload* the package when the ‘:’ is an active character. Note that this happens *after* the category code of the @-sign has been changed to other, so we need to temporarily change it to letter again.

```

3876 \AtEndOfPackage{%
3877   \AtBeginDocument{%
3878     \ifpackageloaded{hhline}%
3879     {\expandafter\ifx\csname normal@char\string\endcsname\relax
3880       \else
3881         \makeatletter
3882         \def\@currname{hhline}\input{hhline.sty}\makeatother
3883       \fi}%
3884     {}}}}

```

`\substitutefontfamily` *Deprecated.* Use the tools provides by \TeX . The command `\substitutefontfamily` creates an `.fd` file on the fly. The first argument is an encoding mnemonic, the second and third arguments are font family names.

```

3885 \def\substitutefontfamily#1#2#3{%
3886   \lowercase{\immediate\openout15=#1#2.fd\relax}%
3887   \immediate\write15{%
3888     \string\ProvidesFile{#1#2.fd}%
3889     [\the\year/\two@digits{\the\month}/\two@digits{\the\day}
3890     \space generated font description file]^J
3891     \string\DeclareFontFamily{#1}{#2}{^^J
3892     \string\DeclareFontShape{#1}{#2}{m}{n}{<->ssub * #3/m/n}{^^J
3893     \string\DeclareFontShape{#1}{#2}{m}{it}{<->ssub * #3/m/it}{^^J
3894     \string\DeclareFontShape{#1}{#2}{m}{sl}{<->ssub * #3/m/sl}{^^J
3895     \string\DeclareFontShape{#1}{#2}{m}{sc}{<->ssub * #3/m/sc}{^^J
3896     \string\DeclareFontShape{#1}{#2}{b}{n}{<->ssub * #3/bx/n}{^^J
3897     \string\DeclareFontShape{#1}{#2}{b}{it}{<->ssub * #3/bx/it}{^^J
3898     \string\DeclareFontShape{#1}{#2}{b}{sl}{<->ssub * #3/bx/sl}{^^J
3899     \string\DeclareFontShape{#1}{#2}{b}{sc}{<->ssub * #3/bx/sc}{^^J
3900   }%
3901   \closeout15
3902 }
3903 \@onlypreamble\substitutefontfamily

```

5.4 Encoding and fonts

Because documents may use non-ASCII font encodings, we make sure that the logos of \TeX and \LaTeX always come out in the right encoding. There is a list of non-ASCII encodings. Requested encodings are currently stored in `\@fontenc@load@list`. If a non-ASCII has been loaded, we define versions of `\TeX` and `\LaTeX` for them using `\ensureascii`. The default ASCII encoding is set, too (in reverse order): the “main” encoding (when the document begins), the last loaded, or OT1.

```

\ensureascii
3904 \bbl@trace{Encoding and fonts}
3905 \newcommand\BabelNonASCII{LGR,LGI,X2,OT2,OT3,OT6,LHE,LWN,LMA,LMC,LMS,LMU}
3906 \newcommand\BabelNonText{TS1,T3,TS3}
3907 \let\org@TeX\TeX
3908 \let\org@LaTeX\LaTeX
3909 \let\ensureascii\@firstofone
3910 \let\asciientcoding\@empty
3911 \AtBeginDocument{%
3912   \def\@elt#1{,#1,}%
3913   \edef\bbl@tempa{\expandafter\@gobbletwo\@fontenc@load@list}%
3914   \let\@elt\relax
3915   \let\bbl@tempb\@empty
3916   \def\bbl@tempc{OT1}%
3917   \bbl@foreach\BabelNonASCII{% LGR loaded in a non-standard way
3918     \bbl@ifunset{T@#1}{\def\bbl@tempb{#1}}}%
3919   \bbl@foreach\bbl@tempa{%
3920     \bbl@xin@{,#1,}{,\BabelNonASCII,}%
3921     \ifin@
3922       \def\bbl@tempb{#1}% Store last non-ascii
3923     \else\bbl@xin@{,#1,}{,\BabelNonText,}% Pass
3924     \ifin@
3925       \def\bbl@tempc{#1}% Store last ascii
3926     \fi
3927   \fi}%
3928   \ifx\bbl@tempb\@empty\else
3929     \bbl@xin@{,\cf@encoding,}{,\BabelNonASCII,\BabelNonText,}%
3930     \ifin@
3931       \edef\bbl@tempc{\cf@encoding}% The default if ascii wins
3932     \fi
3933     \let\asciientcoding\bbl@tempc
3934     \renewcommand\ensureascii[1]{%

```

```

3935     {\fontencoding{\asciientencoding}\selectfont#1}}%
3936     \DeclareTextCommandDefault{\TeX}{\ensureascii{\org@TeX}}%
3937     \DeclareTextCommandDefault{\LaTeX}{\ensureascii{\org@LaTeX}}%
3938     \fi}

```

Now comes the old deprecated stuff (with a little change in 3.9l, for fontspec). The first thing we need to do is to determine, at `\begin{document}`, which latin fontencoding to use.

`\latinencoding` When text is being typeset in an encoding other than ‘latin’ (OT1 or T1), it would be nice to still have Roman numerals come out in the Latin encoding. So we first assume that the current encoding at the end of processing the package is the Latin encoding.

```

3939 \AtEndOfPackage{\edef\latinencoding{\cf@encoding}}

```

But this might be overruled with a later loading of the package `fontenc`. Therefore we check at the execution of `\begin{document}` whether it was loaded with the T1 option. The normal way to do this (using `\@ifpackageloaded`) is disabled for this package. Now we have to revert to parsing the internal macro `\@filelist` which contains all the filenames loaded.

```

3940 \AtBeginDocument{%
3941   \@ifpackageloaded{fontspec}%
3942   {\xdef\latinencoding{%
3943     \ifx\UTFencname\undefined
3944       EU\ifcase\bbl@engine\or2\or1\fi
3945     \else
3946       \UTFencname
3947     \fi}}%
3948   {\gdef\latinencoding{OT1}%
3949     \ifx\cf@encoding\bbl@t@one
3950       \xdef\latinencoding{\bbl@t@one}%
3951     \else
3952       \def\@elt#1{,#1,}%
3953       \edef\bbl@tempa{\expandafter\@gobbletwo\@fontencload@list}%
3954       \let\@elt\relax
3955       \bbl@xin@{,T1,}\bbl@tempa
3956       \ifin@
3957         \xdef\latinencoding{\bbl@t@one}%
3958       \fi
3959     \fi}}

```

`\latintext` Then we can define the command `\latintext` which is a declarative switch to a latin font-encoding. Usage of this macro is deprecated.

```

3960 \DeclareRobustCommand{\latintext}{%
3961   \fontencoding{\latinencoding}\selectfont
3962   \def\encodingdefault{\latinencoding}}

```

`\textlatin` This command takes an argument which is then typeset using the requested font encoding. In order to avoid many encoding switches it operates in a local scope.

```

3963 \ifx\@undefined\DeclareTextFontCommand
3964   \DeclareRobustCommand{\textlatin}[1]{\leavevmode\latintext #1}}
3965 \else
3966   \DeclareTextFontCommand{\textlatin}{\latintext}
3967 \fi

```

For several functions, we need to execute some code with `\selectfont`. With \TeX 2021-06-01, there is a hook for this purpose.

```

3968 \def\bbl@patchfont#1{\AddToHook{selectfont}{#1}}

```

5.5 Basic bidi support

Work in progress. This code is currently placed here for practical reasons. It will be moved to the correct place soon, I hope.

It is loosely based on `rlbabel.def`, but most of it has been developed from scratch. This `babel` module (by Johannes Braams and Boris Lavva) has served the purpose of typesetting R documents for two decades, and despite its flaws I think it is still a good starting point (some parts have been

copied here almost verbatim), partly thanks to its simplicity. I’ve also looked at ARABI (by Youssef Jabri), which is compatible with babel.

There are two ways of modifying macros to make them “bidi”, namely, by patching the internal low-level macros (which is what I have done with lists, columns, counters, tocs, much like `rlbabel` did), and by introducing a “middle layer” just below the user interface (sectioning, footnotes).

- `pdftex` provides a minimal support for bidi text, and it must be done by hand. Vertical typesetting is not possible.
- `xetex` is somewhat better, thanks to its font engine (even if not always reliable) and a few additional tools. However, very little is done at the paragraph level. Another challenging problem is text direction does not honour \TeX grouping.
- `luatex` can provide the most complete solution, as we can manipulate almost freely the node list, the generated lines, and so on, but bidi text does not work out of the box and some development is necessary. It also provides tools to properly set left-to-right and right-to-left page layouts. As `Lua \TeX -ja` shows, vertical typesetting is possible, too.

```

3969 \bbl@trace{Loading basic (internal) bidi support}
3970 \ifodd\bbl@engine
3971 \else % TODO. Move to txtbabel
3972   \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200 % Any xe+lua bidi=
3973     \bbl@error{bidi-only-lua}{\}\}\}%
3974     \let\bbl@beforeforeign\leavevmode
3975     \AtEndOfPackage{%
3976       \EnableBabelHook{babel-bidi}%
3977       \bbl@xebidipar}
3978   \fi\fi
3979   \def\bbl@loadxebidi#1{%
3980     \ifx\RTLfootnotetext\@undefined
3981       \AtEndOfPackage{%
3982         \EnableBabelHook{babel-bidi}%
3983         \bbl@loadfontspec % bidi needs fontspec
3984         \usepackage#1{bidi}%
3985         \let\bbl@digitsdotdash\DigitsDotDashInterCharToks
3986         \def\DigitsDotDashInterCharToks{% See the 'bidi' package
3987           \ifnum\@nameuse{bbl@wdir@}\languagename=\tw@ % 'AL' bidi
3988             \bbl@digitsdotdash % So ignore in 'R' bidi
3989           \fi}}%
3990     \fi}
3991   \ifnum\bbl@bidimode>200 % Any xe bidi=
3992     \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
3993       \bbl@tentative{bidi=bidi}
3994       \bbl@loadxebidi{}
3995     \or
3996       \bbl@loadxebidi{[rldocument]}
3997     \or
3998       \bbl@loadxebidi{}
3999     \fi
4000   \fi
4001 \fi
4002 % TODO? Separate:
4003 \ifnum\bbl@bidimode=\@ne % Any bidi= except default=1
4004   \let\bbl@beforeforeign\leavevmode
4005   \ifodd\bbl@engine
4006     \newattribute\bbl@attr@dir
4007     \directlua{ Babel.attr_dir = luatexbase.registernumber'bbl@attr@dir' }
4008     \bbl@exp{\output{\bodydir\pagedir\the\output}}
4009   \fi
4010   \AtEndOfPackage{%
4011     \EnableBabelHook{babel-bidi}%
4012     \ifodd\bbl@engine\else
4013       \bbl@xebidipar
4014     \fi}
4015 \fi

```

Now come the macros used to set the direction when a language is switched. First the (mostly) common macros.

```

4016 \bbl@trace{Macros to switch the text direction}
4017 \def\bbl@alscripts{,Arabic,Syriac,Thaana,}
4018 \def\bbl@rscripts{% TODO. Base on codes ??
4019   ,Imperial Aramaic,Avestan,Cypriot,Hatran,Hebrew,%
4020   Old Hungarian,Lydian,Mandaean,Manichaeen,%
4021   Meroitic Cursive,Meroitic,Old North Arabian,%
4022   Nabataean,N'Ko,Orkhon,Palmyrene,Inscriptional Pahlavi,%
4023   Psalter Pahlavi,Phoenician,Inscriptional Parthian,Samaritan,%
4024   Old South Arabian,}%
4025 \def\bbl@provide@dirs#1{%
4026   \bbl@xin@{\csname bbl@sname@#1\endcsname}{\bbl@alscripts\bbl@rscripts}%
4027   \ifin@
4028     \global\bbl@csarg\chardef{wdir@#1}\@ne
4029     \bbl@xin@{\csname bbl@sname@#1\endcsname}{\bbl@alscripts}%
4030     \ifin@
4031       \global\bbl@csarg\chardef{wdir@#1}\tw@
4032     \fi
4033   \else
4034     \global\bbl@csarg\chardef{wdir@#1}\z@
4035   \fi
4036   \ifodd\bbl@engine
4037     \bbl@csarg\ifcase{wdir@#1}%
4038       \directlua{ Babel.locale_props[\the\localeid].texdir = 'l' }%
4039     \or
4040       \directlua{ Babel.locale_props[\the\localeid].texdir = 'r' }%
4041     \or
4042       \directlua{ Babel.locale_props[\the\localeid].texdir = 'al' }%
4043     \fi
4044   \fi}
4045 \def\bbl@switchdir{%
4046   \bbl@ifunset{\bbl@lsys@\language name}{\bbl@provide@lsys{\language name}}{}%
4047   \bbl@ifunset{\bbl@wdir@\language name}{\bbl@provide@dirs{\language name}}{}%
4048   \bbl@exp{\bbl@setdirs\bbl@cl{wdir}}}%
4049 \def\bbl@setdirs#1{% TODO - math
4050   \ifcase\bbl@select@type % TODO - strictly, not the right test
4051     \bbl@bodydir{#1}%
4052     \bbl@paddir{#1}% <- Must precede \bbl@texdir
4053   \fi
4054   \bbl@texdir{#1}}
4055 % TODO. Only if \bbl@bidimode > 0?:
4056 \AddBabelHook{babel-bidi}{afterextras}{\bbl@switchdir}
4057 \DisableBabelHook{babel-bidi}

```

Now the engine-dependent macros. TODO. Must be moved to the engine files.

```

4058 \ifodd\bbl@engine % luatex=1
4059 \else % pdftex=0, xetex=2
4060   \newcount\bbl@dirlevel
4061   \chardef\bbl@thetexdir\z@
4062   \chardef\bbl@thepaddir\z@
4063   \def\bbl@texdir#1{%
4064     \ifcase#1\relax
4065       \chardef\bbl@thetexdir\z@
4066       \@nameuse{setlatin}%
4067       \bbl@texdir@i\beginL\endL
4068     \else
4069       \chardef\bbl@thetexdir\@ne
4070       \@nameuse{setnonlatin}%
4071       \bbl@texdir@i\beginR\endR
4072     \fi}
4073   \def\bbl@texdir@i#1#2{%
4074     \ifhmode

```



```

4075 \ifnum\currentgrouplevel>\z@
4076 \ifnum\currentgrouplevel=\bbl@dirlevel
4077 \bbl@error{multiple-bidi}{\}\}\}%
4078 \bgroup\aftergroup#2\aftergroup\egroup
4079 \else
4080 \ifcase\currentgrouptype\or % 0 bottom
4081 \aftergroup#2% 1 simple {}
4082 \or
4083 \bgroup\aftergroup#2\aftergroup\egroup % 2 hbox
4084 \or
4085 \bgroup\aftergroup#2\aftergroup\egroup % 3 adj hbox
4086 \or\or\or % vbox vtop align
4087 \or
4088 \bgroup\aftergroup#2\aftergroup\egroup % 7 noalign
4089 \or\or\or\or\or\or % output math disc insert vcent mathchoice
4090 \or
4091 \aftergroup#2% 14 \begingroup
4092 \else
4093 \bgroup\aftergroup#2\aftergroup\egroup % 15 adj
4094 \fi
4095 \fi
4096 \bbl@dirlevel\currentgrouplevel
4097 \fi
4098 #1%
4099 \fi}
4100 \def\bbl@pardir#1{\chardef\bbl@thepardir#1\relax}
4101 \let\bbl@bodydir\@gobble
4102 \let\bbl@pagedir\@gobble
4103 \def\bbl@dirparastext{\chardef\bbl@thepardir\bbl@thetextdir}

```

The following command is executed only if there is a right-to-left script (once). It activates the `\everypar` hack for xetex, to properly handle the par direction. Note text and par dirs are decoupled to some extent (although not completely).

```

4104 \def\bbl@xebidipar{%
4105 \let\bbl@xebidipar\relax
4106 \TeXeTstate\@ne
4107 \def\bbl@xeeverypar{%
4108 \ifcase\bbl@thepardir
4109 \ifcase\bbl@thetextdir\else\beginR\fi
4110 \else
4111 {\setbox\z@\lastbox\beginR\box\z@}%
4112 \fi}%
4113 \let\bbl@severypar\everypar
4114 \newtoks\everypar
4115 \everypar=\bbl@severypar
4116 \bbl@severypar{\bbl@xeeverypar\the\everypar}}
4117 \ifnum\bbl@bidimode>200 % Any xe bidi=
4118 \let\bbl@textdir\i\@gobbletwo
4119 \let\bbl@xebidipar\@empty
4120 \AddBabelHook{bidi}{foreign}{%
4121 \def\bbl@tempa{\def\BabelText###1}%
4122 \ifcase\bbl@thetextdir
4123 \expandafter\bbl@tempa\expandafter{\BabelText{\LR{##1}}}%
4124 \else
4125 \expandafter\bbl@tempa\expandafter{\BabelText{\RL{##1}}}%
4126 \fi}
4127 \def\bbl@pardir#1{\ifcase#1\relax\setLR\else\setRL\fi}
4128 \fi
4129 \fi

```

A tool for weak L (mainly digits). We also disable warnings with `hyperref`.

```

4130 \DeclareRobustCommand\babelsublr[1]{\leavevmode{\bbl@textdir\z@#1}}
4131 \AtBeginDocument{%
4132 \ifx\pdfstringdefDisableCommands\@undefined\else

```

```

4133 \ifx\pdfstringdefDisableCommands\relax\else
4134 \pdfstringdefDisableCommands{\let\babelsublr\@firstofone}%
4135 \fi
4136 \fi}

```

5.6 Local Language Configuration

`\loadlocalcfg` At some sites it may be necessary to add site-specific actions to a language definition file. This can be done by creating a file with the same name as the language definition file, but with the extension `.cfg`. For instance the file `norsk.cfg` will be loaded when the language definition file `norsk.ldf` is loaded.

For plain-based formats we don't want to override the definition of `\loadlocalcfg` from `plain.def`.

```

4137 \bbl@trace{Local Language Configuration}
4138 \ifx\loadlocalcfg\undefined
4139 \@ifpackagewith{babel}{noconfigs}%
4140 {\let\loadlocalcfg\@gobble}%
4141 {\def\loadlocalcfg#1{%
4142 \InputIfFileExists{#1.cfg}%
4143 {\typeout{*****^J%
4144 * Local config file #1.cfg used^^J%
4145 *}}}%
4146 \@empty}}
4147 \fi

```

5.7 Language options

Languages are loaded when processing the corresponding option *except* if a main language has been set. In such a case, it is not loaded until all options has been processed. The following macro inputs the `ldf` file and does some additional checks (`\input` works, too, but possible errors are not caught).

```

4148 \bbl@trace{Language options}
4149 \let\bbl@afterlang\relax
4150 \let\BabelModifiers\relax
4151 \let\bbl@loaded\@empty
4152 \def\bbl@load@language#1{%
4153 \InputIfFileExists{#1.ldf}%
4154 {\edef\bbl@loaded{\CurrentOption
4155 \ifx\bbl@loaded\@empty\else,\bbl@loaded\fi}%
4156 \expandafter\let\expandafter\bbl@afterlang
4157 \csname\CurrentOption.ldf-h@k\endcsname
4158 \expandafter\let\expandafter\BabelModifiers
4159 \csname bbl@mod@\CurrentOption\endcsname
4160 \bbl@exp{\AtBeginDocument{%
4161 \bbl@usehooks@lang{\CurrentOption}{begindocument}{\CurrentOption}}}%
4162 {\IfFileExists{babel-#1.tex}%
4163 {\def\bbl@tempa{%
4164 .\There is a locale ini file for this language.\%
4165 If it's the main language, try adding `provide=*'\%
4166 to the babel package options}}%
4167 {\let\bbl@tempa\empty}%
4168 \bbl@error{unknown-package-option}{\CurrentOption}}}

```

Now, we set a few language options whose names are different from `ldf` files. These declarations are preserved for backwards compatibility, but they must be eventually removed. Use proxy files instead.

```

4169 \def\bbl@try@load@lang#1#2#3{%
4170 \IfFileExists{\CurrentOption.ldf}%
4171 {\bbl@load@language{\CurrentOption}}%
4172 {\bbl@load@language{#2#3}}
4173 %
4174 \DeclareOption{hebrew}{%
4175 \ifcase\bbl@engine\or
4176 \bbl@error{only-pdftex-lang}{hebrew}{\LaTeX}}%

```

```

4177 \fi
4178 \input{rlbabel.def}%
4179 \bbl@load@language{hebrew}}
4180 \DeclareOption{hungarian}{\bbl@try@load@lang{}{magyar}{}}
4181 \DeclareOption{lowersorbian}{\bbl@try@load@lang{}{lsorbian}{}}
4182 \DeclareOption{polutonikogreek}{%
4183   \bbl@try@load@lang{}{greek}{\languageattribute{greek}{polutoniko}}}
4184 \DeclareOption{russian}{\bbl@try@load@lang{}{russianb}{}}
4185 \DeclareOption{ukrainian}{\bbl@try@load@lang{}{ukraineb}{}}
4186 \DeclareOption{uppersorbian}{\bbl@try@load@lang{}{usorbian}{}}

```

Another way to extend the list of ‘known’ options for babel was to create the file `bblopts.cfg` in which one can add option declarations. However, this mechanism is deprecated – if you want an alternative name for a language, just create a new `.ldf` file loading the actual one. You can also set the name of the file with the package option `config=<name>`, which will load `<name>.cfg` instead.

```

4187 \ifx\bbl@opt@config\@nnil
4188   \@ifpackagewith{babel}{noconfigs}}}%
4189   {\InputIfFileExists{bblopts.cfg}%
4190     {\typeout{*****^J%
4191               * Local config file bblopts.cfg used^^J%
4192               *}}}%
4193   {}}}%
4194 \else
4195   \InputIfFileExists{\bbl@opt@config.cfg}%
4196     {\typeout{*****^J%
4197               * Local config file \bbl@opt@config.cfg used^^J%
4198               *}}}%
4199     {\bbl@error{config-not-found}{}}}%
4200 \fi

```

Recognizing global options in packages not having a closed set of them is not trivial, as for them to be processed they must be defined explicitly. So, package options not yet taken into account and stored in `bbl@language@opts` are assumed to be languages. If not declared above, the names of the option and the file are the same. We first pre-process the class and package options to determine the main language, which is processed in the third ‘main’ pass, *except* if all files are `ldf` and there is no main key. In the latter case (`\bbl@opt@main` is still `\@nnil`), the traditional way to set the main language is kept — the last loaded is the main language.

```

4201 \ifx\bbl@opt@main\@nnil
4202   \ifnum\bbl@iniflag>\z@ % if all ldf's: set implicitly, no main pass
4203     \let\bbl@tempb\@empty
4204     \edef\bbl@tempa{\@classoptionslist,\bbl@language@opts}%
4205     \bbl@foreach\bbl@tempa{\edef\bbl@tempb{#1,\bbl@tempb}}}%
4206     \bbl@foreach\bbl@tempb{%   \bbl@tempb is a reversed list
4207       \ifx\bbl@opt@main\@nnil % ie, if not yet assigned
4208         \ifodd\bbl@iniflag % = *=
4209           \IfFileExists{babel-#1.tex}{\def\bbl@opt@main{#1}}}%
4210         \else % n +=
4211           \IfFileExists{#1.ldf}{\def\bbl@opt@main{#1}}}%
4212       \fi
4213     \fi}%
4214 \fi
4215 \else
4216   \bbl@info{Main language set with 'main='. Except if you have\\%
4217     problems, prefer the default mechanism for setting\\%
4218     the main language, ie, as the last declared.\\%
4219     Reported}%
4220 \fi

```

A few languages are still defined explicitly. They are stored in case they are needed in the ‘main’ pass (the value can be `\relax`).

```

4221 \ifx\bbl@opt@main\@nnil\else
4222   \bbl@ncarg\let\bbl@loadmain{ds@\bbl@opt@main}%
4223   \expandafter\let\csname ds@\bbl@opt@main\endcsname\relax
4224 \fi

```

Now define the corresponding loaders. With package options, assume the language exists. With class options, check if the option is a language by checking if the corresponding file exists.

```

4225 \bbl@foreach\bbl@language@opts{%
4226   \def\bbl@tempa{#1}%
4227   \ifx\bbl@tempa\bbl@opt@main\else
4228     \ifnum\bbl@iniflag<\tw@ % 0 0 (other = ldf)
4229       \bbl@ifunset{ds@#1}%
4230       {\DeclareOption{#1}{\bbl@load@language{#1}}}%
4231       {}%
4232     \else % + * (other = ini)
4233       \DeclareOption{#1}{%
4234         \bbl@ldfinit
4235         \babelprovide[import]{#1}%
4236         \bbl@afterldf{}}%
4237     \fi
4238   \fi}
4239 \bbl@foreach\@classoptionslist{%
4240   \def\bbl@tempa{#1}%
4241   \ifx\bbl@tempa\bbl@opt@main\else
4242     \ifnum\bbl@iniflag<\tw@ % 0 0 (other = ldf)
4243       \bbl@ifunset{ds@#1}%
4244       {\IfFileExists{#1.ldf}%
4245        {\DeclareOption{#1}{\bbl@load@language{#1}}}%
4246        {}}%
4247       {}%
4248     \else % + * (other = ini)
4249       \IfFileExists{babel-#1.tex}%
4250       {\DeclareOption{#1}{%
4251         \bbl@ldfinit
4252         \babelprovide[import]{#1}%
4253         \bbl@afterldf{}}}%
4254       {}%
4255     \fi
4256   \fi}

```

And we are done, because all options for this pass has been declared. Those already processed in the first pass are just ignored.

The options have to be processed in the order in which the user specified them (but remember class options are processed before):

```

4257 \def\AfterBabelLanguage#1{%
4258   \bbl@ifsamestring\CurrentOption{#1}{\global\bbl@add\bbl@afterlang{}}
4259   \DeclareOption*{}
4260   \ProcessOptions*

```

This finished the second pass. Now the third one begins, which loads the main language set with the key main. A warning is raised if the main language is not the same as the last named one, or if the value of the key main is not a language. With some options in provide, the package luatexbase is loaded (and immediately used), and therefore \babelprovide can't go inside a \DeclareOption; this explains why it's executed directly, with a dummy declaration. Then all languages have been loaded, so we deactivate \AfterBabelLanguage.

```

4261 \bbl@trace{Option 'main'}
4262 \ifx\bbl@opt@main\@nnil
4263   \edef\bbl@tempa{\@classoptionslist,\bbl@language@opts}
4264   \let\bbl@tempc\@empty
4265   \edef\bbl@templ{\bbl@loaded,}
4266   \edef\bbl@templ{\expandafter\strip@prefix\meaning\bbl@templ}
4267   \bbl@for\bbl@tempb\bbl@tempa{%
4268     \edef\bbl@tempd{\bbl@tempb,%
4269     \edef\bbl@tempd{\expandafter\strip@prefix\meaning\bbl@tempd}%
4270     \bbl@xin{\bbl@tempd}{\bbl@templ}%
4271     \ifin\edef\bbl@tempc{\bbl@tempb}\fi}
4272   \def\bbl@tempa#1,#2\@nnil{\def\bbl@tempb{#1}}
4273   \expandafter\bbl@tempa\bbl@loaded,\@nnil

```

```

4274 \ifx\bbl@tempb\bbl@tempc\else
4275   \bbl@warning{%
4276     Last declared language option is '\bbl@tempc',\%
4277     but the last processed one was '\bbl@tempb'.\%
4278     The main language can't be set as both a global\%
4279     and a package option. Use 'main=\bbl@tempc' as\%
4280     option. Reported}
4281 \fi
4282 \else
4283 \ifodd\bbl@iniflag % case 1,3 (main is ini)
4284   \bbl@ldfinit
4285   \let\CurrentOption\bbl@opt@main
4286   \bbl@exp{% \bbl@opt@provide = empty if *
4287     \\babelprovide[\bbl@opt@provide,import,main]{\bbl@opt@main}}%
4288   \bbl@afterldf{}
4289   \DeclareOption{\bbl@opt@main}{}
4290 \else % case 0,2 (main is ldf)
4291   \ifx\bbl@loadmain\relax
4292     \DeclareOption{\bbl@opt@main}{\bbl@load@language{\bbl@opt@main}}
4293   \else
4294     \DeclareOption{\bbl@opt@main}{\bbl@loadmain}
4295   \fi
4296   \ExecuteOptions{\bbl@opt@main}
4297   \@namedef{ds@\bbl@opt@main}{}%
4298 \fi
4299 \DeclareOption*{}
4300 \ProcessOptions*
4301 \fi
4302 \bbl@exp{%
4303   \\AtBeginDocument{\\bbl@usehooks@lang{/}{begindocument}{}}}%
4304 \def\AfterBabelLanguage{\bbl@error{late-after-babel}{}}{}

```

In order to catch the case where the user didn't specify a language we check whether `\bbl@main@language`, has become defined. If not, the nil language is loaded.

```

4305 \ifx\bbl@main@language\@undefined
4306   \bbl@info{%
4307     You haven't specified a language as a class or package\%
4308     option. I'll load 'nil'. Reported}
4309   \bbl@load@language{nil}
4310 \fi
4311 \</package>

```

6 The kernel of Babel (`babel.def`, common)

The kernel of the babel system is currently stored in `babel.def`. The file `babel.def` contains most of the code. The file `hyphen.cfg` is a file that can be loaded into the format, which is necessary when you want to be able to switch hyphenation patterns.

Because plain $\text{T}_{\text{E}}\text{X}$ users might want to use some of the features of the babel system too, care has to be taken that plain $\text{T}_{\text{E}}\text{X}$ can process the files. For this reason the current format will have to be checked in a number of places. Some of the code below is common to plain $\text{T}_{\text{E}}\text{X}$ and \LaTeX , some of it is for the \LaTeX case only.

Plain formats based on `etex` (`etex`, `xetex`, `luatex`) don't load `hyphen.cfg` but `etex.src`, which follows a different naming convention, so we need to define the babel names. It presumes `language.def` exists and it is the same file used when formats were created.

A proxy file for `switch.def`

```

4312 \<*kernel>
4313 \let\bbl@onlyswitch\@empty
4314 \input babel.def
4315 \let\bbl@onlyswitch\@undefined
4316 \</kernel>
4317 %
4318 % \section{Error messages}

```

```

4319%
4320% They are loaded when |\bbl@error| is first called. To save space, the
4321% main code just identifies them with a tag, and messages are stored in
4322% a separate file. Since it can be loaded anywhere, you make sure some
4323% catcodes have the right value, although those for |\|, |`|, |^M|,
4324% |%| and |=| are reset before loading the file.
4325%
4326 (*errors)
4327 \catcode`\{=1 \catcode`\}=2 \catcode`\#=6
4328 \catcode`\:=12 \catcode`\,=12 \catcode`\.=12 \catcode`\-=12
4329 \catcode`\'=12 \catcode`\(=12 \catcode`\)=12
4330 \catcode`\@=11 \catcode`\^=7
4331%
4332 \ifx\MessageBreak@undefined
4333   \gdef\bbl@error@i#1#2{%
4334     \begingroup
4335       \newlinechar=`^^J
4336       \def\{^^J(babel) }%
4337       \errhelp{#2}\errmessage{\{#1}%
4338     \endgroup}
4339 \else
4340   \gdef\bbl@error@i#1#2{%
4341     \begingroup
4342       \def\{\MessageBreak}%
4343       \PackageError{babel}{#1}{#2}%
4344     \endgroup}
4345 \fi
4346 \def\bbl@errmessage#1#2#3{%
4347   \expandafter\gdef\csname bbl@err@#1\endcsname##1##2##3{%
4348     \bbl@error@i{#2}{#3}}
4349 % Implicit #2#3#4:
4350 \gdef\bbl@error#1{\csname bbl@err@#1\endcsname}
4351%
4352 \bbl@errmessage{not-yet-available}
4353   {Not yet available}%
4354   {Find an armchair, sit down and wait}
4355 \bbl@errmessage{bad-package-option}%
4356   {Bad option '#1=#2'. Either you have misspelled the\\%
4357   key or there is a previous setting of '#1'. Valid\\%
4358   keys are, among others, 'shorthands', 'main', 'bidi',\\%
4359   'strings', 'config', 'headfoot', 'safe', 'math'.}%
4360   {See the manual for further details.}
4361 \bbl@errmessage{base-on-the-fly}
4362   {For a language to be defined on the fly 'base'\\%
4363   is not enough, and the whole package must be\\%
4364   loaded. Either delete the 'base' option or\\%
4365   request the languages explicitly}%
4366   {See the manual for further details.}
4367 \bbl@errmessage{undefined-language}
4368   {You haven't defined the language '#1' yet.\\%
4369   Perhaps you misspelled it or your installation\\%
4370   is not complete}%
4371   {Your command will be ignored, type <return> to proceed}
4372 \bbl@errmessage{shorthand-is-off}
4373   {I can't declare a shorthand turned off (\string#2)}
4374   {Sorry, but you can't use shorthands which have been\\%
4375   turned off in the package options}
4376 \bbl@errmessage{not-a-shorthand}
4377   {The character '\string #1' should be made a shorthand character;\\%
4378   add the command \string\usesshorthands\string{#1\string} to
4379   the preamble.\\%
4380   I will ignore your instruction}%
4381   {You may proceed, but expect unexpected results}

```

```

4382 \bbl@errmessage{not-a-shorthand-b}
4383   {I can't switch '\string#2' on or off--not a shorthand}%
4384   {This character is not a shorthand. Maybe you made\\%
4385     a typing mistake? I will ignore your instruction.}
4386 \bbl@errmessage{unknown-attribute}
4387   {The attribute #2 is unknown for language #1.}%
4388   {Your command will be ignored, type <return> to proceed}
4389 \bbl@errmessage{missing-group}
4390   {Missing group for string \string#1}%
4391   {You must assign strings to some category, typically\\%
4392     captions or extras, but you set none}
4393 \bbl@errmessage{only-lua-xe}
4394   {This macro is available only in LuaLaTeX and XeLaTeX.}%
4395   {Consider switching to these engines.}
4396 \bbl@errmessage{only-lua}
4397   {This macro is available only in LuaLaTeX.}%
4398   {Consider switching to that engine.}
4399 \bbl@errmessage{unknown-provide-key}
4400   {Unknown key '#1' in \string\babelprovide}%
4401   {See the manual for valid keys}%
4402 \bbl@errmessage{unknown-mapfont}
4403   {Option '\bbl@KVP@mapfont' unknown for\\%
4404     mapfont. Use 'direction'.}%
4405   {See the manual for details.}
4406 \bbl@errmessage{no-ini-file}
4407   {There is no ini file for the requested language\\%
4408     (#1: \languagename). Perhaps you misspelled it or your\\%
4409     installation is not complete.}%
4410   {Fix the name or reinstall babel.}
4411 \bbl@errmessage{digits-is-reserved}
4412   {The counter name 'digits' is reserved for mapping\\%
4413     decimal digits}%
4414   {Use another name.}
4415 \bbl@errmessage{limit-two-digits}
4416   {Currently two-digit years are restricted to the\\
4417     range 0-9999.}%
4418   {There is little you can do. Sorry.}
4419 \bbl@errmessage{alphabetic-too-large}
4420   {Alphabetic numeral too large (#1)}%
4421   {Currently this is the limit.}
4422 \bbl@errmessage{no-ini-info}
4423   {I've found no info for the current locale.\\%
4424     The corresponding ini file has not been loaded\\%
4425     Perhaps it doesn't exist}%
4426   {See the manual for details.}
4427 \bbl@errmessage{unknown-ini-field}
4428   {Unknown field '#1' in \string\BCPdata.\\%
4429     Perhaps you misspelled it.}%
4430   {See the manual for details.}
4431 \bbl@errmessage{unknown-locale-key}
4432   {Unknown key for locale '#2':\\%
4433     #3\\%
4434     \string#1 will be set to \relax}%
4435   {Perhaps you misspelled it.}%
4436 \bbl@errmessage{adjust-only-vertical}
4437   {Currently, #1 related features can be adjusted only\\%
4438     in the main vertical list.}%
4439   {Maybe things change in the future, but this is what it is.}
4440 \bbl@errmessage{layout-only-vertical}
4441   {Currently, layout related features can be adjusted only\\%
4442     in vertical mode.}%
4443   {Maybe things change in the future, but this is what it is.}
4444 \bbl@errmessage{bidi-only-lua}

```

```

4445 {The bidi method 'basic' is available only in\\%
4446 luatex. I'll continue with 'bidi=default', so\\%
4447 expect wrong results}%
4448 {See the manual for further details.}
4449 \bbl@errmessage{multiple-bidi}
4450 {Multiple bidi settings inside a group}%
4451 {I'll insert a new group, but expect wrong results.}
4452 \bbl@errmessage{unknown-package-option}
4453 {Unknown option '\CurrentOption'. Either you misspelled it\\%
4454 or the language definition file \CurrentOption.ldf\\%
4455 was not found%
4456 \bbl@tempa}
4457 {Valid options are, among others: shorthands=, KeepShorthandsActive,\\%
4458 activeacute, activegrave, noconfigs, safe=, main=, math=\\%
4459 headfoot=, strings=, config=, hyphenmap=, or a language name.}
4460 \bbl@errmessage{config-not-found}
4461 {Local config file '\bbl@opt@config.cfg' not found}%
4462 {Perhaps you misspelled it.}
4463 \bbl@errmessage{late-after-babel}
4464 {Too late for \string\AfterBabelLanguage}%
4465 {Languages have been loaded, so I can do nothing}
4466 \bbl@errmessage{double-hyphens-class}
4467 {Double hyphens aren't allowed in \string\babelcharclass\\%
4468 because it's potentially ambiguous}%
4469 {See the manual for further info}
4470 \bbl@errmessage{unknown-interchar}
4471 {'#1' for '\language' cannot be enabled.\\%
4472 Maybe there is a typo.}%
4473 {See the manual for further details.}
4474 \bbl@errmessage{unknown-interchar-b}
4475 {'#1' for '\language' cannot be disabled.\\%
4476 Maybe there is a typo.}%
4477 {See the manual for further details.}
4478 \bbl@errmessage{charproperty-only-vertical}
4479 {\string\babelcharproperty\space can be used only in\\%
4480 vertical mode (preamble or between paragraphs)}%
4481 {See the manual for further info}
4482 \bbl@errmessage{unknown-char-property}
4483 {No property named '#2'. Allowed values are\\%
4484 direction (bc), mirror (bmg), and linebreak (lb)}%
4485 {See the manual for further info}
4486 \bbl@errmessage{bad-transform-option}
4487 {Bad option '#1' in a transform.\\%
4488 I'll ignore it but expect more errors}%
4489 {See the manual for further info.}
4490 \bbl@errmessage{font-conflict-transforms}
4491 {Transforms cannot be re-assigned to different\\%
4492 fonts. The conflict is in '\bbl@kv@label'.\\%
4493 Apply the same fonts or use a different label}%
4494 {See the manual for further details.}
4495 \bbl@errmessage{transform-not-available}
4496 {'#1' for '\language' cannot be enabled.\\%
4497 Maybe there is a typo or it's a font-dependent transform}%
4498 {See the manual for further details.}
4499 \bbl@errmessage{transform-not-available-b}
4500 {'#1' for '\language' cannot be disabled.\\%
4501 Maybe there is a typo or it's a font-dependent transform}%
4502 {See the manual for further details.}
4503 \bbl@errmessage{year-out-range}
4504 {Year out of range.\\%
4505 The allowed range is #1}%
4506 {See the manual for further details.}
4507 \bbl@errmessage{only-pdfTeX-lang}

```



```

4508 {The '#1' ldf style doesn't work with #2,\\%
4509 but you can use the ini locale instead.\\%
4510 Try adding 'provide=*' to the option list. You may\\%
4511 also want to set 'bidi=' to some value.}%
4512 {See the manual for further details.}
4513 </errors>
4514 <*patterns>

```

7 Loading hyphenation patterns

The following code is meant to be read by $\text{\texttt{iniTeX}}$ because it should instruct $\text{\texttt{TeX}}$ to read hyphenation patterns. To this end the `docstrip` option `patterns` is used to include this code in the file `hyphen.cfg`. Code is written with lower level macros.

```

4515 <<Make sure ProvidesFile is defined>>
4516 \ProvidesFile{hyphen.cfg}[<<date>> v<<version>> Babel hyphens]
4517 \xdef\bbl@format{\jobname}
4518 \def\bbl@version{<<version>>}
4519 \def\bbl@date{<<date>>}
4520 \ifx\AtBeginDocument\undefined
4521 \def\empty{}
4522 \fi
4523 <<Define core switching macros>>

```

`\process@line` Each line in the file `language.dat` is processed by `\process@line` after it is read. The first thing this macro does is to check whether the line starts with `=`. When the first token of a line is an `=`, the macro `\process@synonym` is called; otherwise the macro `\process@language` will continue.

```

4524 \def\process@line#1#2 #3 #4 {%
4525 \ifx=#1%
4526 \process@synonym{#2}%
4527 \else
4528 \process@language{#1#2}{#3}{#4}%
4529 \fi
4530 \ignorespaces}

```

`\process@synonym` This macro takes care of the lines which start with an `=`. It needs an empty token register to begin with. `\bbl@languages` is also set to empty.

```

4531 \toks@{}
4532 \def\bbl@languages{}

```

When no languages have been loaded yet, the name following the `=` will be a synonym for hyphenation register 0. So, it is stored in a token register and executed when the first pattern file has been processed. (The `\relax` just helps to the `\if` below catching synonyms without a language.) Otherwise the name will be a synonym for the language loaded last.

We also need to copy the `hyphenmins` parameters for the synonym.

```

4533 \def\process@synonym#1{%
4534 \ifnum\last@language=\m@ne
4535 \toks@\expandafter{\the\toks@\relax\process@synonym{#1}}%
4536 \else
4537 \expandafter\chardef\csname l@#1\endcsname\last@language
4538 \wlog{\string\l@#1=\string\language\the\last@language}%
4539 \expandafter\let\csname #1hyphenmins\expandafter\endcsname
4540 \csname\language\hyphenmins\endcsname
4541 \let\bbl@elt\relax
4542 \edef\bbl@languages{\bbl@languages\bbl@elt{#1}{\the\last@language}{}}%
4543 \fi}

```

`\process@language` The macro `\process@language` is used to process a non-empty line from the ‘configuration file’. It has three arguments, each delimited by white space. The first argument is the ‘name’ of a language; the second is the name of the file that contains the patterns. The optional third argument is the name of a file containing hyphenation exceptions.

The first thing to do is call `\addlanguage` to allocate a pattern register and to make that register ‘active’. Then the pattern file is read.

For some hyphenation patterns it is needed to load them with a specific font encoding selected. This can be specified in the file `language.dat` by adding for instance ‘:T1’ to the name of the language. The macro `\bbl@get@enc` extracts the font encoding from the language name and stores it in `\bbl@hyph@enc`. The latter can be used in hyphenation files if you need to set a behavior depending on the given encoding (it is set to empty if no encoding is given).

Pattern files may contain assignments to `\lefthyphenmin` and `\righthyphenmin`. T_EX does not keep track of these assignments. Therefore we try to detect such assignments and store them in the

`\<lang>hyphenmins` macro. When no assignments were made we provide a default setting.

Some pattern files contain changes to the `\lccode` en `\uccode` arrays. Such changes should remain local to the language; therefore we process the pattern file in a group; the `\patterns` command acts globally so its effect will be remembered.

Then we globally store the settings of `\lefthyphenmin` and `\righthyphenmin` and close the group.

When the hyphenation patterns have been processed we need to see if a file with hyphenation exceptions needs to be read. This is the case when the third argument is not empty and when it does not contain a space token. (Note however there is no need to save hyphenation exceptions into the format.)

`\bbl@languages` saves a snapshot of the loaded languages in the form

`\bbl@elt{<language-name>}{<number>}{<patterns-file>}{<exceptions-file>}`. Note the last 2

arguments are empty in ‘dialects’ defined in `language.dat` with `=`. Note also the language name can have encoding info.

Finally, if the counter `\language` is equal to zero we execute the synonyms stored.

```

4544 \def\process@language#1#2#3{%
4545   \expandafter\addlanguage\csname l@#1\endcsname
4546   \expandafter\language\csname l@#1\endcsname
4547   \edef\language{#1}%
4548   \bbl@hook@everylanguage{#1}%
4549   % > luatex
4550   \bbl@get@enc#1:.\@@@
4551   \begingroup
4552     \lefthyphenmin\m@ne
4553     \bbl@hook@loadpatterns{#2}%
4554     % > luatex
4555     \ifnum\lefthyphenmin=\m@ne
4556       \else
4557         \expandafter\xdef\csname #1hyphenmins\endcsname{%
4558           \the\lefthyphenmin\the\righthyphenmin}%
4559       \fi
4560     \endgroup
4561     \def\bbl@tempa{#3}%
4562     \ifx\bbl@tempa\empty\else
4563       \bbl@hook@loadexceptions{#3}%
4564       % > luatex
4565     \fi
4566     \let\bbl@elt\relax
4567     \edef\bbl@languages{%
4568       \bbl@languages\bbl@elt{#1}{\the\language}{#2}{\bbl@tempa}}%
4569     \ifnum\the\language=\z@
4570       \expandafter\ifx\csname #1hyphenmins\endcsname\relax
4571         \set@hyphenmins\tw@\thr@@\relax
4572       \else
4573         \expandafter\expandafter\expandafter\set@hyphenmins
4574         \csname #1hyphenmins\endcsname
4575       \fi
4576       \the\toks@
4577       \toks@{}%
4578     \fi}

```

`\bbl@get@enc` The macro `\bbl@get@enc` extracts the font encoding from the language name and stores it in `\bbl@hyph@enc`. It uses delimited arguments to achieve this.

```

4579 \def\bbl@get@enc#1:#2:#3\@@@{\def\bbl@hyph@enc{#2}}

```

Now, hooks are defined. For efficiency reasons, they are dealt here in a special way. Besides `luatex`, format-specific configuration files are taken into account. `loadkernel` currently loads nothing, but

define some basic macros instead.

```
4580 \def\bbl@hook@everylanguage#1{}
4581 \def\bbl@hook@loadpatterns#1{\input #1\relax}
4582 \let\bbl@hook@loadexceptions\bbl@hook@loadpatterns
4583 \def\bbl@hook@loadkernel#1{%
4584   \def\addlanguage{\csname newlanguage\endcsname}%
4585   \def\adddialect##1##2{%
4586     \global\chardef##1##2\relax
4587     \wlog{\string##1 = a dialect from \string\language##2}}%
4588   \def\iflanguage##1{%
4589     \expandafter\ifx\csname l@##1\endcsname\relax
4590       \nolater{##1}%
4591     \else
4592       \ifnum\csname l@##1\endcsname=\language
4593         \expandafter\expandafter\expandafter\@firstoftwo
4594       \else
4595         \expandafter\expandafter\expandafter\@secondoftwo
4596       \fi
4597     \fi}%
4598   \def\providehyphenmins##1##2{%
4599     \expandafter\ifx\csname ##1hyphenmins\endcsname\relax
4600       \namedef{##1hyphenmins}{##2}%
4601     \fi}%
4602   \def\set@hyphenmins##1##2{%
4603     \lefthyphenmin##1\relax
4604     \righthyphenmin##2\relax}%
4605   \def\selectlanguage{%
4606     \errhelp{Selecting a language requires a package supporting it}%
4607     \errmessage{Not loaded}}%
4608   \let\foreignlanguage\selectlanguage
4609   \let\otherlanguage\selectlanguage
4610   \expandafter\let\csname otherlanguage*\endcsname\selectlanguage
4611   \def\bbl@usehooks##1##2{% TODO. Temporary!!
4612     \def\setlocale{%
4613       \errhelp{Find an armchair, sit down and wait}%
4614       \errmessage{(babel) Not yet available}}%
4615     \let\uselocale\setlocale
4616     \let\locale\setlocale
4617     \let\selectlocale\setlocale
4618     \let\localename\setlocale
4619     \let\textlocale\setlocale
4620     \let\textlanguage\setlocale
4621     \let\languagetext\setlocale}
4622   \begingroup
4623     \def\AddBabelHook#1#2{%
4624       \expandafter\ifx\csname bbl@hook@#2\endcsname\relax
4625         \def\next{\toks1}%
4626       \else
4627         \def\next{\expandafter\gdef\csname bbl@hook@#2\endcsname###1}%
4628       \fi
4629       \next}
4630   \ifx\directlua\@undefined
4631     \ifx\XeTeXinputencoding\@undefined\else
4632       \input xebabel.def
4633     \fi
4634   \else
4635     \input luababel.def
4636   \fi
4637   \openin1 = babel-\bbl@format.cfg
4638   \ifeof1
4639   \else
4640     \input babel-\bbl@format.cfg\relax
4641   \fi
```

```

4642 \closein1
4643 \endgroup
4644 \bbl@hook@loadkernel{switch.def}

```

\readconfigfile The configuration file can now be opened for reading.

```

4645 \openin1 = language.dat

```

See if the file exists, if not, use the default hyphenation file hyphen.tex. The user will be informed about this.

```

4646 \def\language{english}%
4647 \ifeof1
4648 \message{I couldn't find the file language.dat,\space
4649         I will try the file hyphen.tex}
4650 \input hyphen.tex\relax
4651 \chardef\l@english\z@
4652 \else

```

Pattern registers are allocated using count register \last@language. Its initial value is 0. The definition of the macro \newlanguage is such that it first increments the count register and then defines the language. In order to have the first patterns loaded in pattern register number 0 we initialize \last@language with the value -1.

```

4653 \last@language\m@ne

```

We now read lines from the file until the end is found. While reading from the input, it is useful to switch off recognition of the end-of-line character. This saves us stripping off spaces from the contents of the control sequence.

```

4654 \loop
4655   \endlinechar\m@ne
4656   \read1 to \bbl@line
4657   \endlinechar\^^M

```

If the file has reached its end, exit from the loop here. If not, empty lines are skipped. Add 3 space characters to the end of \bbl@line. This is needed to be able to recognize the arguments of \process@line later on. The default language should be the very first one.

```

4658   \if T\ifeof1F\fi T\relax
4659   \ifx\bbl@line\@empty\else
4660     \edef\bbl@line{\bbl@line\space\space\space}%
4661     \expandafter\process@line\bbl@line\relax
4662   \fi
4663 \repeat

```

Check for the end of the file. We must reverse the test for \ifeof without \else. Then reactivate the default patterns, and close the configuration file.

```

4664 \begingroup
4665   \def\bbl@elt#1#2#3#4{%
4666     \global\language=#2\relax
4667     \gdef\language{#1}%
4668     \def\bbl@elt##1##2##3##4{}}%
4669   \bbl@languages
4670 \endgroup
4671 \fi
4672 \closein1

```

We add a message about the fact that babel is loaded in the format and with which language patterns to the \everyjob register.

```

4673 \if/\the\toks@\else
4674   \errhelp{language.dat loads no language, only synonyms}
4675   \errmessage{Orphan language synonym}
4676 \fi

```

Also remove some macros from memory and raise an error if \toks@ is not empty. Finally load switch.def, but the latter is not required and the line inputting it may be commented out.

```

4677 \let\bbl@line\undefined
4678 \let\process@line\undefined

```

```

4679 \let\process@synonym\@undefined
4680 \let\process@language\@undefined
4681 \let\bbl@get@enc\@undefined
4682 \let\bbl@hyph@enc\@undefined
4683 \let\bbl@tempa\@undefined
4684 \let\bbl@hook@loadkernel\@undefined
4685 \let\bbl@hook@everylanguage\@undefined
4686 \let\bbl@hook@loadpatterns\@undefined
4687 \let\bbl@hook@loadexceptions\@undefined
4688 \</patterns>

```

Here the code for `iniTeX` ends.

8 Font handling with fontspec

Add the bidi handler just before `luaotfload`, which is loaded by default by `LaTeX`. Just in case, consider the possibility it has not been loaded. First, a couple of definitions related to bidi [misplaced].

```

4689 <<*More package options>> ≡
4690 \chardef\bbl@bidimode\z@
4691 \DeclareOption{bidi=default}{\chardef\bbl@bidimode=\@ne}
4692 \DeclareOption{bidi=basic}{\chardef\bbl@bidimode=101 }
4693 \DeclareOption{bidi=basic-r}{\chardef\bbl@bidimode=102 }
4694 \DeclareOption{bidi=bidi}{\chardef\bbl@bidimode=201 }
4695 \DeclareOption{bidi=bidi-r}{\chardef\bbl@bidimode=202 }
4696 \DeclareOption{bidi=bidi-l}{\chardef\bbl@bidimode=203 }
4697 <</More package options>>

```

With explicit languages, we could define the font at once, but we don't. Just wait and see if the language is actually activated. `bbl@font` replaces hardcoded font names inside `\.family` by the corresponding macro `\.default`.

At the time of this writing, `fontspec` shows a warning about there are languages not available, which some people think refers to `babel`, even if there is nothing wrong. Here is hack to patch `fontspec` to avoid the misleading (and mostly unuseful) message.

```

4698 <<*Font selection>> ≡
4699 \bbl@trace{Font handling with fontspec}
4700 \ifx\ExplSyntaxOn\@undefined\else
4701   \def\bbl@fs@warn@nx#1#2{% \bbl@tempfs is the original macro
4702     \in@{,#1,}{,no-script,language-not-exist,}%
4703     \ifin@else\bbl@tempfs@nx{#1}{#2}\fi}
4704   \def\bbl@fs@warn@nxx#1#2#3{%
4705     \in@{,#1,}{,no-script,language-not-exist,}%
4706     \ifin@else\bbl@tempfs@nxx{#1}{#2}{#3}\fi}
4707   \def\bbl@loadfontspec{%
4708     \let\bbl@loadfontspec\relax
4709     \ifx\fontspec\@undefined
4710       \usepackage{fontspec}%
4711     \fi}%
4712 \fi
4713 \@onlypreamble\babelfont
4714 \newcommand\babelfont[2][{}]{% 1=langs/scripts 2=fam
4715   \bbl@foreach{#1}{%
4716     \expandafter\ifx\csname date##1\endcsname\relax
4717       \IfFileExists{babel-##1.tex}%
4718       {\babelprovide{##1}}%
4719     }%
4720   \fi}%
4721 \edef\bbl@tempa{#1}%
4722 \def\bbl@tempb{#2}% Used by \bbl@bblfont
4723 \bbl@loadfontspec
4724 \EnableBabelHook{babel-fontspec}% Just calls \bbl@switchfont
4725 \bbl@bblfont}
4726 \newcommand\bbl@bblfont[2][{}]{% 1=features 2=fontname, @font=rm|sf|tt
4727   \bbl@ifunset{\bbl@tempb family}%

```

```

4728     {\bbl@providefam{\bbl@tempb}}}%
4729     {}%
4730 % For the default font, just in case:
4731 \bbl@ifunset{\bbl@lsys{\language}\bbl@provide@lsys{\language}}{}%
4732 \expandafter\bbl@ifblank\expandafter{\bbl@tempa}%
4733 {\bbl@csarg\edef{\bbl@tempb dflt@}{<{#1}{#2}}}% save bbl@rmdflt@
4734 \bbl@exp{%
4735     \let\bbl@tempb dflt@\language\bbl@tempb dflt@>%
4736     \bbl@font@set{\bbl@tempb dflt@\language}%
4737     \bbl@tempb default>\bbl@tempb family>}}%
4738 {\bbl@foreach\bbl@tempa{% ie bbl@rmdflt@lang / *scrt
4739     \bbl@csarg\def{\bbl@tempb dflt@##1}{<{#1}{#2}}}}}%

```

If the family in the previous command does not exist, it must be defined. Here is how:

```

4740 \def\bbl@providefam#1{%
4741     \bbl@exp{%
4742         \newcommand{<#1default>}{% Just define it
4743             \bbl@add@list{\bbl@font@fams{#1}}%
4744             \DeclareRobustCommand{<#1family>{%
4745                 \not@math@alphabet{<#1family>}\relax
4746                 % \prepare@family@series@update{#1}<#1default>% TODO. Fails
4747                 \fontfamily{<#1default>%
4748                 <ifx>\UseHooks\undefined<else>\UseHook{#1family}<fi>%
4749                 \selectfont}%
4750                 \DeclareTextFontCommand{<text#1>}{<#1family>}}}

```

The following macro is activated when the hook babel-fontspec is enabled. But before, we define a macro for a warning, which sets a flag to avoid duplicate them.

```

4751 \def\bbl@nostdfont#1{%
4752     \bbl@ifunset{\bbl@WFF@f@family}%
4753     {\bbl@csarg\gdef{WFF@f@family}}% Flag, to avoid dupl warns
4754     \bbl@infowarn{The current font is not a babel standard family:\%
4755         #1%
4756         \fontname\font}%
4757     There is nothing intrinsically wrong with this warning, and\%
4758     you can ignore it altogether if you do not need these\%
4759     families. But if they are used in the document, you should be\%
4760     aware 'babel' will not set Script and Language for them, so\%
4761     you may consider defining a new family with \string\babelfont.\%
4762     See the manual for further details about \string\babelfont.\%
4763     Reported}}
4764     {}%
4765 \gdef\bbl@switchfont{%
4766     \bbl@ifunset{\bbl@lsys{\language}\bbl@provide@lsys{\language}}{}%
4767     \bbl@exp{% eg Arabic -> arabic
4768         \lowercase{\edef{\bbl@tempa{\bbl@cl{sname}}}}%
4769         \bbl@foreach\bbl@font@fams{%
4770             \bbl@ifunset{\bbl@##1dflt@\language}% (1) language?
4771             {\bbl@ifunset{\bbl@##1dflt@*\bbl@tempa}% (2) from script?
4772                 {\bbl@ifunset{\bbl@##1dflt@}% 2=F - (3) from generic?
4773                     {}% 123=F - nothing!
4774                     {\bbl@exp{% 3=T - from generic
4775                         \global\let\bbl@##1dflt@\language>%
4776                         \bbl@##1dflt@>}}}%
4777                     {\bbl@exp{% 2=T - from script
4778                         \global\let\bbl@##1dflt@\language>%
4779                         \bbl@##1dflt@*\bbl@tempa>}}}%
4780                     {}% 1=T - language, already defined
4781             \def\bbl@tempa{\bbl@nostdfont}}% TODO. Don't use \bbl@tempa
4782             \bbl@foreach\bbl@font@fams{% don't gather with prev for
4783                 \bbl@ifunset{\bbl@##1dflt@\language}%
4784                 {\bbl@cs{famrst@##1}%
4785                 \global\bbl@csarg\let{famrst@##1}\relax}%
4786                 {\bbl@exp{% order is relevant. TODO: but sometimes wrong!

```

```

4787     \\bbl@add\\originalTeX{%
4788     \\bbl@font@rst{\\bbl@cl{##1dflt}}}%
4789     \\<##1default>\\<##1family>{##1}}%
4790     \\bbl@font@set\\<bbl@##1dflt@\\language\\>% the main part!
4791     \\<##1default>\\<##1family>}}}%
4792     \\bbl@ifrestoring{\\bbl@tempa}}}%

The following is executed at the beginning of the aux file or the document to warn about fonts not
defined with \\babelfont.

4793 \\ifx\\f@family\\undefined\\else    % if latex
4794     \\ifcase\\bbl@engine              % if pdftex
4795     \\let\\bbl@ckeckstdfonts\\relax
4796     \\else
4797     \\def\\bbl@ckeckstdfonts{%
4798     \\begingroup
4799     \\global\\let\\bbl@ckeckstdfonts\\relax
4800     \\let\\bbl@tempa\\empty
4801     \\bbl@foreach\\bbl@font@fams{%
4802     \\bbl@ifunset{\\bbl@##1dflt@}%
4803     {\\@nameuse{##1family}}%
4804     \\bbl@csarg\\gdef{WFF@\\f@family}}}% Flag
4805     \\bbl@exp{\\bbl@add\\bbl@tempa{* \\<##1family>= \\f@family\\}%
4806     \\space\\space\\fontname\\font\\}%
4807     \\bbl@csarg\\xdef{##1dflt@}{\\f@family}%
4808     \\expandafter\\xdef\\csname ##1default\\endcsname{\\f@family}}%
4809     }%
4810     \\ifx\\bbl@tempa\\empty\\else
4811     \\bbl@infowarn{The following font families will use the default\\%
4812     settings for all or some languages:\\%
4813     \\bbl@tempa
4814     There is nothing intrinsically wrong with it, but\\%
4815     'babel' will no set Script and Language, which could\\%
4816     be relevant in some languages. If your document uses\\%
4817     these families, consider redefining them with \\string\\babelfont.\\%
4818     Reported}%
4819     \\fi
4820     \\endgroup}
4821 \\fi
4822 \\fi

```

Now the macros defining the font with fontspec.

When there are repeated keys in fontspec, the last value wins. So, we just place the ini settings at the beginning, and user settings will take precedence. We must deactivate temporarily \\bbl@mapselect because \\selectfont is called internally when a font is defined.

For historical reasons, \TeX can select two different series (bx and b), for what is conceptually a single one. This can lead to problems when a single family requires several fonts, depending on the language, mainly because 'substitutions' with some combinations are not done consistently – sometimes bx/sc is the correct font, but sometimes points to b/n, even if b/sc exists. So, some substitutions are redefined (in a somewhat hackish way, by inspecting if the variant declaration contains >ssub*).

```

4823 \\def\\bbl@font@set#1#2#3{% eg \\bbl@rmdflt@lang \\rmdefault \\rmfamily
4824     \\bbl@xin@{<>}{#1}%
4825     \\ifin@
4826     \\bbl@exp{\\bbl@fontspec@set\\#1\\expandafter\\@gobbletwo#1\\#3}%
4827     \\fi
4828     \\bbl@exp{%
4829     \\def\\#2{#1}% eg, \\rmdefault{\\bbl@rmdflt@lang}
4830     \\bbl@ifsamestring{#2}{\\f@family}%
4831     {\\#3%
4832     \\bbl@ifsamestring{\\f@series}{\\bfdefault}{\\bfseries}}}%
4833     \\let\\bbl@tempa\\relax}%
4834     }%
4835 % TODO - next should be global?, but even local does its job. I'm
4836 % still not sure -- must investigate:

```

```

4837 \def\bbf@fontspec@set#1#2#3#4{% eg \bbf@rmdflt@lang fnt-opt fnt-nme \xxfamily
4838 \let\bbf@tempe\bbf@mapselect
4839 \edef\bbf@tempb{\bbf@stripslash#4/}% Catcodes hack (better pass it).
4840 \bbf@exp{\bbf@replace{\bbf@tempb{\bbf@stripslash\family/}}}%
4841 \let\bbf@mapselect\relax
4842 \let\bbf@temp@fam#4% eg, '\rmfamily', to be restored below
4843 \let#4\empty % Make sure \renewfontfamily is valid
4844 \bbf@exp{%
4845 \let\bbf@temp@pfam<\bbf@stripslash#4\space>% eg, '\rmfamily '
4846 \<keys_if_exist:nnF>{\fontspec-opentype}{Script/\bbf@cl{sname}}}%
4847 {\newfontscript{\bbf@cl{sname}}{\bbf@cl{sotf}}}%
4848 \<keys_if_exist:nnF>{\fontspec-opentype}{Language/\bbf@cl{lname}}}%
4849 {\newfontlanguage{\bbf@cl{lname}}{\bbf@cl{lotf}}}%
4850 \let\bbf@tempfs@nx<__fontspec_warning:nx>%
4851 \let<__fontspec_warning:nx>\bbf@fs@warn@nx
4852 \let\bbf@tempfs@nxx<__fontspec_warning:nxx>%
4853 \let<__fontspec_warning:nxx>\bbf@fs@warn@nxx
4854 \renewfontfamily\#4%
4855 [\bbf@cl{sys},% xetex removes unknown features :-(
4856 \ifcase\bbf@engine\or RawFeature={family=\bbf@tempb},\fi
4857 #2}{#3}% ie \bbf@exp{..}{#3}
4858 \bbf@exp{%
4859 \let<__fontspec_warning:nx>\bbf@tempfs@nx
4860 \let<__fontspec_warning:nxx>\bbf@tempfs@nxx}%
4861 \begingroup
4862 #4%
4863 \xdef#1{\f@family}% eg, \bbf@rmdflt@lang{FreeSerif(0)}
4864 \endgroup % TODO. Find better tests:
4865 \bbf@xin@{\string>\string s\string s\string u\string b\string*}%
4866 {\expandafter\meaning\csname TU/#1/bx/sc\endcsname}%
4867 \ifin@
4868 \global\bbf@ccarg\let{TU/#1/bx/sc}{TU/#1/b/sc}%
4869 \fi
4870 \bbf@xin@{\string>\string s\string s\string u\string b\string*}%
4871 {\expandafter\meaning\csname TU/#1/bx/scit\endcsname}%
4872 \ifin@
4873 \global\bbf@ccarg\let{TU/#1/bx/scit}{TU/#1/b/scit}%
4874 \fi
4875 \let#4\bbf@temp@fam
4876 \bbf@exp{\let<\bbf@stripslash#4\space>\bbf@temp@pfam
4877 \let\bbf@mapselect\bbf@tempe}%

```

font@rst and famrst are only used when there is no global settings, to save and restore de previous families. Not really necessary, but done for optimization.

```

4878 \def\bbf@font@rst#1#2#3#4{%
4879 \bbf@csarg\def{famrst@#4}{\bbf@font@set{#1}#2#3}}

```

The default font families. They are eurocentric, but the list can be expanded easily with \babel font.

```

4880 \def\bbf@font@fams{rm,sf,tt}
4881 <</Font selection>>

```

9 Hooks for XeTeX and LuaTeX

9.1 XeTeX

Unfortunately, the current encoding cannot be retrieved and therefore it is reset always to utf8, which seems a sensible default.

```

4882 <<(*Footnote changes)>> ≡
4883 \bbf@trace{Bidi footnotes}
4884 \ifnum\bbf@bidimode>\z@ % Any bidi=
4885 \def\bbf@footnote#1#2#3{%
4886 \ifnextchar%

```



```

4887     {\bbl@footnote@o{#1}{#2}{#3}}%
4888     {\bbl@footnote@x{#1}{#2}{#3}}}
4889 \long\def\bbl@footnote@x#1#2#3#4{%
4890     \bgroup
4891     \select@language@x{\bbl@main@language}%
4892     \bbl@fn@footnote{#2#1{\ignorespaces#4}#3}%
4893     \egroup}
4894 \long\def\bbl@footnote@o#1#2#3[#4]#5{%
4895     \bgroup
4896     \select@language@x{\bbl@main@language}%
4897     \bbl@fn@footnote[#4]{#2#1{\ignorespaces#5}#3}%
4898     \egroup}
4899 \def\bbl@footnotetext#1#2#3{%
4900     \@ifnextchar{%
4901         {\bbl@footnotetext@o{#1}{#2}{#3}}%
4902         {\bbl@footnotetext@x{#1}{#2}{#3}}}
4903 \long\def\bbl@footnotetext@x#1#2#3#4{%
4904     \bgroup
4905     \select@language@x{\bbl@main@language}%
4906     \bbl@fn@footnotetext{#2#1{\ignorespaces#4}#3}%
4907     \egroup}
4908 \long\def\bbl@footnotetext@o#1#2#3[#4]#5{%
4909     \bgroup
4910     \select@language@x{\bbl@main@language}%
4911     \bbl@fn@footnotetext[#4]{#2#1{\ignorespaces#5}#3}%
4912     \egroup}
4913 \def\BabelFootnote#1#2#3#4{%
4914     \ifx\bbl@fn@footnote\@undefined
4915         \let\bbl@fn@footnote\footnote
4916     \fi
4917     \ifx\bbl@fn@footnotetext\@undefined
4918         \let\bbl@fn@footnotetext\footnotetext
4919     \fi
4920     \bbl@ifblank{#2}%
4921     {\def#1{\bbl@footnote{\@firstofone}{#3}{#4}}
4922     \@namedef{\bbl@stripslash#1text}%
4923     {\bbl@footnotetext{\@firstofone}{#3}{#4}}}%
4924     {\def#1{\bbl@exp{\bbl@footnote{\foreignlanguage{#2}}}{#3}{#4}}%
4925     \@namedef{\bbl@stripslash#1text}%
4926     {\bbl@exp{\bbl@footnotetext{\foreignlanguage{#2}}}{#3}{#4}}}%
4927 \fi
4928 <</Footnote changes>>

```

Now, the code.

```

4929 (*xetex)
4930 \def\BabelStringsDefault{unicode}
4931 \let\xebbl@stop\relax
4932 \AddBabelHook{xetex}{encodedcommands}{%
4933     \def\bbl@tempa{#1}%
4934     \ifx\bbl@tempa\@empty
4935         \XeTeXinputencoding"bytes"%
4936     \else
4937         \XeTeXinputencoding"#1"%
4938     \fi
4939     \def\xebbl@stop{\XeTeXinputencoding"utf8"}}
4940 \AddBabelHook{xetex}{stopcommands}{%
4941     \xebbl@stop
4942     \let\xebbl@stop\relax}
4943 \def\bbl@input@classes{% Used in CJK intraspaces
4944     \input{load-unicode-xetex-classes.tex}%
4945     \let\bbl@input@classes\relax}
4946 \def\bbl@intraspace#1 #2 #3\@@{%
4947     \bbl@csarg\gdef{\xeisp@language}{#1}{#2}{#3}}

```

```

4948     {\XeTeXlinebreakskip #1em plus #2em minus #3em\relax}}
4949 \def\bbl@intrapenalty#1\@{
4950   \bbl@csarg\gdef{xeipn@\language\name}%
4951   {\XeTeXlinebreakpenalty #1\relax}}
4952 \def\bbl@provide@intraspace{%
4953   \bbl@xin@{/s}{/\bbl@ccl{lnbrk}}}%
4954   \ifin@ \else \bbl@xin@{/c}{/\bbl@ccl{lnbrk}} \fi
4955   \ifin@
4956     \bbl@ifunset{\bbl@intsp@\language\name}{}%
4957     {\expandafter\ifx\csname bbl@intsp@\language\name\endcsname\@empty\else
4958       \ifx\bbl@KVP@intraspace\@nnil
4959         \bbl@exp{%
4960           \\bbl@intraspace\bbl@ccl{intsp}\\\@}%
4961         \fi
4962         \ifx\bbl@KVP@intrapenalty\@nnil
4963           \bbl@intrapenalty0\@@
4964         \fi
4965       \fi
4966       \ifx\bbl@KVP@intraspace\@nnil\else % We may override the ini
4967         \expandafter\bbl@intraspace\bbl@KVP@intraspace\@@
4968       \fi
4969       \ifx\bbl@KVP@intrapenalty\@nnil\else
4970         \expandafter\bbl@intrapenalty\bbl@KVP@intrapenalty\@@
4971       \fi
4972       \bbl@exp{%
4973         % TODO. Execute only once (but redundant):
4974         \\bbl@add\<extras\language\name>%
4975         \XeTeXlinebreaklocale "\bbl@ccl{tbcpr}"%
4976         \<bbl@xeisp@\language\name>%
4977         \<bbl@xeipn@\language\name>}%
4978         \\bbl@tglobal\<extras\language\name>%
4979         \\bbl@add\<noextras\language\name>%
4980         \XeTeXlinebreaklocale ""}%
4981         \\bbl@tglobal\<noextras\language\name>}%
4982       \ifx\bbl@ispacesize\@undefined
4983         \gdef\bbl@ispacesize{\bbl@ccl{xeisp}}}%
4984       \ifx\AtBeginDocument\@notprerr
4985         \expandafter\@secondoftwo % to execute right now
4986       \fi
4987       \AtBeginDocument{\bbl@patchfont{\bbl@ispacesize}}%
4988     \fi}%
4989 \fi}
4990 \ifx\DisableBabelHook\@undefined\endinput\fi %%% TODO: why
4991 \AddBabelHook{babel-fontspec}{afterextras}{\bbl@switchfont}
4992 \AddBabelHook{babel-fontspec}{beforestart}{\bbl@ckeckstdfonts}
4993 \DisableBabelHook{babel-fontspec}
4994 <<Font selection>>
4995 \def\bbl@provide@extra#1{

```

10 Support for interchar

xetex reserves some values for CJK (although they are not set in XELATEX), so we make sure they are skipped. Define some user names for the global classes, too.

```

4996 \ifnum\Xe@alloc@intercharclass<\thr@@
4997   \Xe@alloc@intercharclass\thr@@
4998 \fi
4999 \chardef\bbl@xeiclass@default=\z@
5000 \chardef\bbl@xeiclass@cjkideogram=\@ne
5001 \chardef\bbl@xeiclass@cjkleftpunctuation=\tw@
5002 \chardef\bbl@xeiclass@cjkrightpunctuation=\thr@@
5003 \chardef\bbl@xeiclass@boundary=4095
5004 \chardef\bbl@xeiclass@ignore=4096

```

The machinery is activated with a hook (enabled only if actually used). Here `\bbl@tempc` is pre-set with `\bbl@usingxeclass`, defined below. The standard mechanism based on `\originalTeX` to save, set and restore values is used. `\count@` stores the previous char to be set, except at the beginning (0) and after `\bbl@upto`, which is the previous char negated, as a flag to mark a range.

```

5005 \AddBabelHook{babel-interchar}{beforeextras}{%
5006   \@nameuse{bbl@xechars@\language\language}}
5007 \DisableBabelHook{babel-interchar}
5008 \protected\def\bbl@charclass#1{%
5009   \ifnum\count@<\z@
5010     \count@-\count@
5011     \loop
5012       \bbl@exp{%
5013         \\babel@savevariable{\XeTeXcharclass`\Uchar\count@}}%
5014         \XeTeXcharclass\count@ \bbl@tempc
5015         \ifnum\count@<`#1\relax
5016         \advance\count@\@ne
5017       \repeat
5018   \else
5019     \babel@savevariable{\XeTeXcharclass`#1}%
5020     \XeTeXcharclass`#1 \bbl@tempc
5021   \fi
5022   \count@`#1\relax}

```

Now the two user macros. Char classes are declared implicitly, and then the macro to be executed at the `babel-interchar` hook is created. The list of chars to be handled by the hook defined above has internally the form `\bbl@usingxeclass\bbl@xeclass@punct@english\bbl@charclass{.}` `\bbl@charclass{,}` (etc.), where `\bbl@usingxeclass` stores the class to be applied to the subsequent characters. The `\ifcat` part deals with the alternative way to enter characters as macros (eg, `\j`). As a special case, hyphens are stored as `\bbl@upto`, to deal with ranges.

```

5023 \newcommand\bbl@ifinterchar[1]{%
5024   \let\bbl@tempa\@gobble           % Assume to ignore
5025   \edef\bbl@tempb{\zap@space#1 \@empty}%
5026   \ifx\bbl@KVP@interchar\@nnil\else
5027     \bbl@replace\bbl@KVP@interchar{ }{,}%
5028     \bbl@foreach\bbl@tempb{%
5029       \bbl@xin@{,##1,}{, \bbl@KVP@interchar,}%
5030       \ifin@
5031         \let\bbl@tempa\@firstofone
5032       \fi}%
5033   \fi
5034   \bbl@tempa}
5035 \newcommand\IfBabelIntercharT[2]{%
5036   \bbl@carg\bbl@add{\bbl@icsave@\CurrentOption}{\bbl@ifinterchar{#1}{#2}}}%
5037 \newcommand\babelcharclass[3]{%
5038   \EnableBabelHook{babel-interchar}%
5039   \bbl@csarg\newXeTeXintercharclass{xeclass@#2@#1}%
5040   \def\bbl@tempb##1{%
5041     \ifx##1\@empty\else
5042       \ifx##1-%
5043         \bbl@upto
5044       \else
5045         \bbl@charclass{%
5046           \ifcat\noexpand##1\relax\bbl@stripslash##1\else\string##1\fi}%
5047       \fi
5048       \expandafter\bbl@tempb
5049     \fi}%
5050   \bbl@ifunset{\bbl@xechars@#1}%
5051   {\toks@{%
5052     \babel@savevariable\XeTeXinterchartokenstate
5053     \XeTeXinterchartokenstate\@ne
5054   }}%
5055   {\toks@\expandafter\expandafter\expandafter{%
5056     \csname bbl@xechars@#1\endcsname}}}%

```

```

5057 \bbl@csarg\edef{xechars@#1}{%
5058   \the\toks@
5059   \bbl@usingxeclass\csname bbl@xeclass@#2@#1\endcsname
5060   \bbl@tempb#3\@empty}}
5061 \protected\def\bbl@usingxeclass#1{\count@ \z@ \let\bbl@tempc#1}
5062 \protected\def\bbl@upto{%
5063   \ifnum\count@>\z@
5064     \advance\count@\@ne
5065     \count@-\count@
5066   \else\ifnum\count@=\z@
5067     \bbl@charclass{-}%
5068   \else
5069     \bbl@error{double-hyphens-class}{}}{}{}%
5070 \fi\fi}

```

And finally, the command with the code to be inserted. If the language doesn't define a class, then use the global one, as defined above. For the definition there is a intermediate macro, which can be 'disabled' with `\bbl@ic@<label>@<lang>`.

```

5071 \def\bbl@ignoreinterchar{%
5072   \ifnum\language=\l@nohyphenation
5073     \expandafter\@gobble
5074   \else
5075     \expandafter\@firstofone
5076   \fi}
5077 \newcommand\babelinterchar[5][{}]{%
5078   \let\bbl@kv@label\@empty
5079   \bbl@forkv{#1}{\bbl@csarg\edef{kv@##1}{##2}}%
5080   \@namedef{\zap@space bbl@xeinter@\bbl@kv@label @#3@#4@#2 \@empty}%
5081   {\bbl@ignoreinterchar{#5}}%
5082   \bbl@csarg\let{ic@\bbl@kv@label @#2}\@firstofone
5083   \bbl@exp{\bbl@for\bbl@tempa{\zap@space#3 \@empty}}%
5084   \bbl@exp{\bbl@for\bbl@tempb{\zap@space#4 \@empty}}%
5085   \XeTeXinterchartoks
5086     \@nameuse{bbl@xeclass@\bbl@tempa @#2}%
5087     \bbl@ifunset{bbl@xeclass@\bbl@tempa @#2}{#2} %
5088     \@nameuse{bbl@xeclass@\bbl@tempb @#2}%
5089     \bbl@ifunset{bbl@xeclass@\bbl@tempb @#2}{#2} %
5090     = \expandafter{%
5091       \csname bbl@ic@\bbl@kv@label @#2\expandafter\endcsname
5092       \csname\zap@space bbl@xeinter@\bbl@kv@label
5093         @#3@#4@#2 \@empty\endcsname}}}}
5094 \DeclareRobustCommand\enablelocaleinterchar[1]{%
5095   \bbl@ifunset{bbl@ic@#1@\language}%
5096   {\bbl@error{unknown-interchar}{#1}{}}%
5097   {\bbl@csarg\let{ic@#1@\language}\@firstofone}}
5098 \DeclareRobustCommand\disablelocaleinterchar[1]{%
5099   \bbl@ifunset{bbl@ic@#1@\language}%
5100   {\bbl@error{unknown-interchar-b}{#1}{}}%
5101   {\bbl@csarg\let{ic@#1@\language}\@gobble}}
5102 </xetex>

```

10.1 Layout

Note elements like headlines and margins can be modified easily with packages like `fancyhdr`, `typearea` or `titlesp`, and `geometry`.

`\bbl@startskip` and `\bbl@endskip` are available to package authors. Thanks to the \TeX expansion mechanism the following constructs are valid: `\adim\bbl@startskip`, `\advance\bbl@startskip\adim`, `\bbl@startskip\adim`.

Consider `txtbabel` as a shorthand for *tex-xet babel*, which is the bidi model in both `pdftex` and `xetex`.

```

5103 <*xetex | texxet>
5104 \providecommand\bbl@provide@intraspace{}
5105 \bbl@trace{Redefinitions for bidi layout}
5106 \def\bbl@sspre@caption{%

```

```

5107 \bbl@exp{\everyhbox{\bbl@textdir\bbl@cs{wdir@\bbl@main@language}}}}
5108 \ifx\bbl@opt@layout@nnil\else % if layout=..
5109 \def\bbl@startskip{\ifcase\bbl@thepardir\leftskip\else\rightskip\fi}
5110 \def\bbl@endskip{\ifcase\bbl@thepardir\rightskip\else\leftskip\fi}
5111 \ifx\bbl@beforeforeign\leavevmode % A poor test for bidi=
5112 \def\hangfrom#1{%
5113   \setbox\@tempboxa\hbox{#{#1}}%
5114   \hangindent\ifcase\bbl@thepardir\wd\@tempboxa\else-\wd\@tempboxa\fi
5115   \noindent\box\@tempboxa}
5116 \def\raggedright{%
5117   \let\\\@centercr
5118   \bbl@startskip\z@skip
5119   \@rightskip\@flushglue
5120   \bbl@endskip\@rightskip
5121   \parindent\z@
5122   \parfillskip\bbl@startskip}
5123 \def\raggedleft{%
5124   \let\\\@centercr
5125   \bbl@startskip\@flushglue
5126   \bbl@endskip\z@skip
5127   \parindent\z@
5128   \parfillskip\bbl@endskip}
5129 \fi
5130 \IfBabelLayout{lists}
5131 {\bbl@sreplace\list
5132   {\@totalleftmargin\leftmargin}{\@totalleftmargin\bbl@listleftmargin}%
5133   \def\bbl@listleftmargin{%
5134     \ifcase\bbl@thepardir\leftmargin\else\rightmargin\fi}%
5135   \ifcase\bbl@engine
5136     \def\labelenumii{}\theenumii{}\pdfTeX doesn't reverse ()
5137     \def\p@enumiii{\p@enumii}\theenumii{}\fi
5138   \fi
5139   \bbl@sreplace\@verbatim
5140     {\leftskip\@totalleftmargin}%
5141     {\bbl@startskip\textwidth
5142       \advance\bbl@startskip-\linewidth}%
5143   \bbl@sreplace\@verbatim
5144     {\rightskip\z@skip}%
5145     {\bbl@endskip\z@skip}}%
5146 {}
5147 \IfBabelLayout{contents}
5148 {\bbl@sreplace\@dottedtocline{\leftskip}{\bbl@startskip}%
5149   \bbl@sreplace\@dottedtocline{\rightskip}{\bbl@endskip}}
5150 {}
5151 \IfBabelLayout{columns}
5152 {\bbl@sreplace\@outputdblcol{\hb@xt@\textwidth}{\bbl@outputbox}%
5153   \def\bbl@outputbox#1{%
5154     \hb@xt@\textwidth{%
5155       \hskip\columnwidth
5156       \hfil
5157       {\normalcolor\vrule \@width\columnseprule}%
5158       \hfil
5159       \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
5160       \hskip-\textwidth
5161       \hb@xt@\columnwidth{\box\@outputbox \hss}%
5162       \hskip\columnsep
5163       \hskip\columnwidth}}}%
5164 {}
5165 <<Footnote changes>>
5166 \IfBabelLayout{footnotes}%
5167 {\BabelFootnote\footnote\languagename{}\fi}%
5168 \BabelFootnote\localfootnote\languagename{}\fi}%
5169 \BabelFootnote\mainfootnote{}\fi}}

```

5170 {}

Implicitly reverses sectioning labels in bidi=basic, because the full stop is not in contact with L numbers any more. I think there must be a better way.

```
5171 \IfBabelLayout{counters*}%
5172 {\bbl@add\bbl@opt@layout{.counters.}%
5173 \AddToHook{shipout/before}{%
5174 \let\bbl@tempa\babelsublr
5175 \let\babelsublr\@firstofone
5176 \let\bbl@save@thepage\thepage
5177 \protected@edef\thepage{\thepage}%
5178 \let\babelsublr\bbl@tempa}%
5179 \AddToHook{shipout/after}{%
5180 \let\thepage\bbl@save@thepage}}{}
5181 \IfBabelLayout{counters}%
5182 {\let\bbl@latinarabic=@arabic
5183 \def\@arabic#1{\babelsublr{\bbl@latinarabic#1}}%
5184 \let\bbl@asciroman=@roman
5185 \def\@roman#1{\babelsublr{\ensureascii{\bbl@asciroman#1}}}%
5186 \let\bbl@asciiRoman=@Roman
5187 \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asciiRoman#1}}}}{}
5188 \fi % end if layout
5189 </xetex | texpet>
```

10.2 8-bit TeX

Which start just above, because some code is shared with xetex. Now, 8-bit specific stuff. If just one encoding has been declared, then assume no switching is necessary (1).

```
5190 <*texpet>
5191 \def\bbl@provide@extra#1{%
5192 % == auto-select encoding ==
5193 \ifx\bbl@encoding@select@off\empty\else
5194 \bbl@ifunset{\bbl@encoding@#1}%
5195 {\def\@elt#1{,##1,}%
5196 \edef\bbl@tempe{\expandafter\@gobbletwo\@fontenc@load@list}%
5197 \count@\z@
5198 \bbl@foreach\bbl@tempe{%
5199 \def\bbl@tempd{##1}% Save last declared
5200 \advance\count@\@ne}%
5201 \ifnum\count@>\@ne % (1)
5202 \getlocaleproperty*\bbl@tempa{#1}{identification/encodings}%
5203 \ifx\bbl@tempa\relax \let\bbl@tempa\empty \fi
5204 \bbl@replace\bbl@tempa{ },}%
5205 \global\bbl@csarg\let{encoding@#1}\empty
5206 \bbl@xin@{,\bbl@tempd,},{,\bbl@tempa,}%
5207 \ifin@else % if main encoding included in ini, do nothing
5208 \let\bbl@tempb\relax
5209 \bbl@foreach\bbl@tempa{%
5210 \ifx\bbl@tempb\relax
5211 \bbl@xin@{,##1,},{,\bbl@tempe,}%
5212 \ifin@\def\bbl@tempb{##1}\fi
5213 \fi}%
5214 \ifx\bbl@tempb\relax\else
5215 \bbl@exp{%
5216 \global\<\bbl@add>\<\bbl@preextras@#1>\<\bbl@encoding@#1>}%
5217 \gdef\<\bbl@encoding@#1>{%
5218 \\\babel@save\\\f@encoding
5219 \\\bbl@add\\\originalTeX\\\selectfont}%
5220 \\\fontencoding{\bbl@tempb}%
5221 \\\selectfont}}%
5222 \fi
5223 \fi
5224 \fi}%>
```

```

5225      {}%
5226    \fi}
5227 \</texxet>

```

10.3 LuaTeX

The loader for luatex is based solely on `language.dat`, which is read on the fly. The code shouldn't be executed when the format is build, so we check if `\AddBabelHook` is defined. Then comes a modified version of the loader in `hyphen.cfg` (without the `hyphenmins` stuff, which is under the direct control of `babel`).

The names `\l@<language>` are defined and take some value from the beginning because all `ldf` files assume this for the corresponding language to be considered valid, but patterns are not loaded (except the first one). This is done later, when the language is first selected (which usually means when the `ldf` finishes). If a language has been loaded, `\bbl@hyphendata@<num>` exists (with the names of the files read).

The default setup preloads the first language into the format. This is intended mainly for 'english', so that it's available without further intervention from the user. To avoid duplicating it, the following rule applies: if the "0th" language and the first language in `language.dat` have the same name then just ignore the latter. If there are new synonymous, they are added, but note if the language patterns have not been preloaded they won't at run time.

Other preloaded languages could be read twice, if they have been preloaded into the format. This is not optimal, but it shouldn't happen very often – with luatex patterns are best loaded when the document is typeset, and the "0th" language is preloaded just for backwards compatibility.

As of 1.1b, lua(e)tex is taken into account. Formerly, loading of patterns on the fly didn't work in this format, but with the new loader it does. Unfortunately, the format is not based on `babel`, and data could be duplicated, because languages are reassigned above those in the format (nothing serious, anyway). Note even with this format `language.dat` is used (under the principle of a single source), instead of `language.def`.

Of course, there is room for improvements, like tools to read and reassign languages, which would require modifying the language list, and better error handling.

We need catcode tables, but no format (targeted by `babel`) provide a command to allocate them (although there are packages like `ctablestack`). FIX - This isn't true anymore. For the moment, a dangerous approach is used - just allocate a high random number and cross the fingers. To complicate things, `etex.sty` changes the way languages are allocated.

This files is read at three places: (1) when `plain.def`, `babel.sty` starts, to read the list of available languages from `language.dat` (for the base option); (2) at `hyphen.cfg`, to modify some macros; (3) in the middle of `plain.def` and `babel.sty`, by `babel.def`, with the commands and other definitions for luatex (eg, `\babelpatterns`).

```

5228 \*luatex>
5229 \ifx\AddBabelHook\@undefined % When plain.def, babel.sty starts
5230 \bbl@trace{Read language.dat}
5231 \ifx\bbl@readstream\@undefined
5232   \csname newread\endcsname\bbl@readstream
5233 \fi
5234 \begingroup
5235   \toks@{}
5236   \count@ \z@ % 0=start, 1=0th, 2=normal
5237   \def\bbl@process@line#1#2 #3 #4 {%
5238     \ifx=#1%
5239       \bbl@process@synonym{#2}%
5240     \else
5241       \bbl@process@language{#1#2}{#3}{#4}%
5242     \fi
5243     \ignorespaces}
5244   \def\bbl@manylang{%
5245     \ifnum\bbl@last>\@ne
5246       \bbl@info{Non-standard hyphenation setup}%
5247     \fi
5248     \let\bbl@manylang\relax}
5249   \def\bbl@process@language#1#2#3{%
5250     \ifcase\count@
5251       \@ifundefined{zth#1}{\count@\tw@}{\count@\@ne}%
5252     \or

```

```

5253 \count@ \tw@
5254 \fi
5255 \ifnum \count@=\tw@
5256 \expandafter \addlanguage \csname l@#1\endcsname
5257 \language \allocationnumber
5258 \chardef \bbl@last \allocationnumber
5259 \bbl@many lang
5260 \let \bbl@elt \relax
5261 \xdef \bbl@languages {%
5262 \bbl@languages \bbl@elt{#1}{\the \language}{#2}{#3}}%
5263 \fi
5264 \the \toks@
5265 \toks@{}
5266 \def \bbl@process@synonym@aux#1#2{%
5267 \global \expandafter \chardef \csname l@#1\endcsname#2 \relax
5268 \let \bbl@elt \relax
5269 \xdef \bbl@languages {%
5270 \bbl@languages \bbl@elt{#1}{#2}{}}}%
5271 \def \bbl@process@synonym#1{%
5272 \ifcase \count@
5273 \toks@ \expandafter {\the \toks@ \relax \bbl@process@synonym{#1}}%
5274 \or
5275 \@ifundefined{zth@#1}{\bbl@process@synonym@aux{#1}{0}}}%
5276 \else
5277 \bbl@process@synonym@aux{#1}{\the \bbl@last}%
5278 \fi}
5279 \ifx \bbl@languages \@undefined % Just a (sensible?) guess
5280 \chardef \l@english \z@
5281 \chardef \l@USenglish \z@
5282 \chardef \bbl@last \z@
5283 \global \@namedef{\bbl@hyphendata@0}{\hyphen.tex}{}
5284 \gdef \bbl@languages {%
5285 \bbl@elt{english}{0}{\hyphen.tex}{}%
5286 \bbl@elt{USenglish}{0}{}}%
5287 \else
5288 \global \let \bbl@languages @format \bbl@languages
5289 \def \bbl@elt#1#2#3#4{% Remove all except language 0
5290 \ifnum #2>\z@ \else
5291 \noexpand \bbl@elt{#1}{#2}{#3}{#4}%
5292 \fi}%
5293 \xdef \bbl@languages {\bbl@languages}%
5294 \fi
5295 \def \bbl@elt#1#2#3#4{\@namedef{zth@#1}} % Define flags
5296 \bbl@languages
5297 \openin \bbl@readstream=language.dat
5298 \ifeof \bbl@readstream
5299 \bbl@warning{I couldn't find language.dat. No additional\\%
5300 patterns loaded. Reported}%
5301 \else
5302 \loop
5303 \endlinechar \m@ne
5304 \read \bbl@readstream to \bbl@line
5305 \endlinechar ``^M
5306 \if T\ifeof \bbl@readstream F\fi T\relax
5307 \ifx \bbl@line \empty \else
5308 \edef \bbl@line {\bbl@line \space \space \space}%
5309 \expandafter \bbl@process@line \bbl@line \relax
5310 \fi
5311 \repeat
5312 \fi
5313 \closein \bbl@readstream
5314 \endgroup
5315 \bbl@trace{Macros for reading patterns files}

```



```

5316 \def\bbl@get@enc#1:#2:#3\@@{\def\bbl@hyph@enc{#2}}
5317 \ifx\babelcatcodetablenum\undefined
5318   \ifx\newcatcodetable\undefined
5319     \def\babelcatcodetablenum{5211}
5320     \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
5321   \else
5322     \newcatcodetable\babelcatcodetablenum
5323     \newcatcodetable\bbl@pattcodes
5324   \fi
5325 \else
5326   \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
5327 \fi
5328 \def\bbl@luapatterns#1#2{%
5329   \bbl@get@enc#1::\@@
5330   \setbox\z@\hbox\bgroup
5331     \begingroup
5332       \savecatcodetable\babelcatcodetablenum\relax
5333       \initcatcodetable\bbl@pattcodes\relax
5334       \catcodetable\bbl@pattcodes\relax
5335       \catcode\#=6 \catcode\$_=3 \catcode\&=4 \catcode\^=7
5336       \catcode\_ =8 \catcode\{=1 \catcode\}=2 \catcode\~=13
5337       \catcode\@=11 \catcode\^^I=10 \catcode\^^J=12
5338       \catcode\<=12 \catcode\>=12 \catcode\*=12 \catcode\.=12
5339       \catcode\-=12 \catcode\/=12 \catcode\[=12 \catcode\]=12
5340       \catcode\`=12 \catcode\'=12 \catcode\"=12
5341       \input #1\relax
5342       \catcodetable\babelcatcodetablenum\relax
5343     \endgroup
5344     \def\bbl@tempa{#2}%
5345     \ifx\bbl@tempa\empty\else
5346       \input #2\relax
5347     \fi
5348   \egroup}%
5349 \def\bbl@patterns@lua#1{%
5350   \language=\expandafter\ifx\csname l@#1:f@encoding\endcsname\relax
5351     \csname l@#1\endcsname
5352     \edef\bbl@tempa{#1}%
5353   \else
5354     \csname l@#1:f@encoding\endcsname
5355     \edef\bbl@tempa{#1:f@encoding}%
5356   \fi\relax
5357   \@namedef{lu@texhyphen@loaded@the\language}{}% Temp
5358   \@ifundefined{bbl@hyphendata@the\language}%
5359     {\def\bbl@elt##1##2##3##4{%
5360       \ifnum##2=\csname l@bbl@tempa\endcsname % #2=spanish, dutch:OT1...
5361       \def\bbl@tempb{##3}%
5362       \ifx\bbl@tempb\empty\else % if not a synonymous
5363         \def\bbl@tempc{{##3}{##4}}%
5364       \fi
5365       \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
5366     \fi}%
5367   \bbl@languages
5368   \@ifundefined{bbl@hyphendata@the\language}%
5369     {\bbl@info{No hyphenation patterns were set for\\%
5370       language '\bbl@tempa'. Reported}}%
5371     {\expandafter\expandafter\expandafter\bbl@luapatterns
5372       \csname bbl@hyphendata@the\language\endcsname}}}%
5373 \endinput\fi
5374 % Here ends \ifx\AddBabelHook\undefined
5375 % A few lines are only read by hyphen.cfg
5376 \ifx\DisableBabelHook\undefined
5377   \AddBabelHook{luatex}{everylanguage}{%
5378     \def\process@language##1##2##3{%

```

```

5379     \def\process@line####1####2 ####3 ####4 {}}}
5380 \AddBabelHook{luatex}{loadpatterns}{%
5381     \input #1\relax
5382     \expandafter\gdef\csname bbl@hyphendata@the\language\endcsname
5383         {{#1}}}}
5384 \AddBabelHook{luatex}{loadexceptions}{%
5385     \input #1\relax
5386     \def\bbl@tempb##1##2{{##1}{#1}}%
5387     \expandafter\xdef\csname bbl@hyphendata@the\language\endcsname
5388         {\expandafter\expandafter\expandafter\bbl@tempb
5389         \csname bbl@hyphendata@the\language\endcsname}}
5390 \endinput\fi
5391 % Here stops reading code for hyphen.cfg
5392 % The following is read the 2nd time it's loaded
5393 % First, global declarations for lua
5394 \begingroup % TODO - to a lua file
5395 \catcode`\%=12
5396 \catcode`\'=12
5397 \catcode`\ "=12
5398 \catcode`\:=12
5399 \directlua{
5400     Babel = Babel or {}
5401     function Babel.lua_error(e, a)
5402         tex.print([[noexpand\csname bbl@error\endcsname{]] ..
5403             e .. '}' .. (a or '') .. '}]{}')
5404     end
5405     function Babel.bytes(line)
5406         return line:gsub(".",
5407             function (chr) return unicode.utf8.char(string.byte(chr)) end)
5408     end
5409     function Babel.begin_process_input()
5410         if luatexbase and luatexbase.add_to_callback then
5411             luatexbase.add_to_callback('process_input_buffer',
5412                 Babel.bytes, 'Babel.bytes')
5413         else
5414             Babel.callback = callback.find('process_input_buffer')
5415             callback.register('process_input_buffer', Babel.bytes)
5416         end
5417     end
5418     function Babel.end_process_input ()
5419         if luatexbase and luatexbase.remove_from_callback then
5420             luatexbase.remove_from_callback('process_input_buffer', 'Babel.bytes')
5421         else
5422             callback.register('process_input_buffer', Babel.callback)
5423         end
5424     end
5425     function Babel.addpatterns(pp, lg)
5426         local lg = lang.new(lg)
5427         local pats = lang.patterns(lg) or ''
5428         lang.clear_patterns(lg)
5429         for p in pp:gmatch('[^%s]+') do
5430             ss = ''
5431             for i in string.utfcharacters(p:gsub('%d', '')) do
5432                 ss = ss .. '%d?' .. i
5433             end
5434             ss = ss:gsub('^%d%?%', '%%.') .. '%d?'
5435             ss = ss:gsub('%.%d%?$', '%%.')
5436             pats, n = pats:gsub('%s' .. ss .. '%s', ' ' .. p .. ' ')
5437             if n == 0 then
5438                 tex.sprint(
5439                     [[\string\csname\space bbl@info\endcsname{New pattern: ]]
5440                     .. p .. [{}]])
5441                 pats = pats .. ' ' .. p

```

```

5442     else
5443         tex.sprint(
5444             [[\string\csname\space bbl@info\endcsname{Renew pattern: }]
5445             .. p .. [{}]])
5446     end
5447 end
5448 lang.patterns(lg, pats)
5449 end
5450 Babel.characters = Babel.characters or {}
5451 Babel.ranges = Babel.ranges or {}
5452 function Babel.hlist_has_bidi(head)
5453     local has_bidi = false
5454     local ranges = Babel.ranges
5455     for item in node.traverse(head) do
5456         if item.id == node.id'glyph' then
5457             local itemchar = item.char
5458             local chardata = Babel.characters[itemchar]
5459             local dir = chardata and chardata.d or nil
5460             if not dir then
5461                 for nn, et in ipairs(ranges) do
5462                     if itemchar < et[1] then
5463                         break
5464                     elseif itemchar <= et[2] then
5465                         dir = et[3]
5466                         break
5467                     end
5468                 end
5469             end
5470             if dir and (dir == 'al' or dir == 'r') then
5471                 has_bidi = true
5472             end
5473         end
5474     end
5475     return has_bidi
5476 end
5477 function Babel.set_chranges_b (script, chrng)
5478     if chrng == '' then return end
5479     texio.write('Replacing ' .. script .. ' script ranges')
5480     Babel.script_blocks[script] = {}
5481     for s, e in string.gmatch(chrng..' ', '(.)%.%.(.%)%s') do
5482         table.insert(
5483             Babel.script_blocks[script], {tonumber(s,16), tonumber(e,16)})
5484     end
5485 end
5486 function Babel.discard_sublr(str)
5487     if str:find( [[\string\indexentry]] ) and
5488        str:find( [[\string\babelsublr]] ) then
5489         str = str:gsub( [[\string\babelsublr%s*(%b{})]],
5490             function(m) return m:sub(2,-2) end )
5491     end
5492     return str
5493 end
5494 }
5495 \endgroup
5496 \ifx\newattribute\undefined\else % Test for plain
5497     \newattribute\bbl@attr@locale
5498     \directlua{ Babel.attr_locale = luatexbase.registernumber'bbl@attr@locale' }
5499     \AddBabelHook{luatex}{beforeextras}{%
5500         \setattribute\bbl@attr@locale\localeid}
5501 \fi
5502 \def\BabelStringsDefault{unicode}
5503 \let\luabbl@stop\relax
5504 \AddBabelHook{luatex}{encodedcommands}{%

```

```

5505 \def\bbl@tempa{utf8}\def\bbl@tempb{#1}%
5506 \ifx\bbl@tempa\bbl@tempb\else
5507   \directlua{Babel.begin_process_input()}%
5508   \def\luabbl@stop{%
5509     \directlua{Babel.end_process_input()}}%
5510 \fi}%
5511 \AddBabelHook{luatex}{stopcommands}{%
5512   \luabbl@stop
5513   \let\luabbl@stop\relax}
5514 \AddBabelHook{luatex}{patterns}{%
5515   \@ifundefined{bbl@hyphendata@the\language}%
5516     {\def\bbl@elt##1##2##3##4{%
5517       \ifnum##2=\csname l@##2\endcsname % #2=spanish, dutch:OT1...
5518       \def\bbl@tempb{##3}%
5519       \ifx\bbl@tempb@empty\else % if not a synonymous
5520         \def\bbl@tempc{{##3}{##4}}%
5521         \fi
5522         \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
5523       \fi}%
5524     \bbl@languages
5525     \@ifundefined{bbl@hyphendata@the\language}%
5526       {\bbl@info{No hyphenation patterns were set for\\
5527         language '#2'. Reported}}%
5528       {\expandafter\expandafter\expandafter\bbl@luapatterns
5529         \csname bbl@hyphendata@the\language\endcsname}}}%
5530   \@ifundefined{bbl@patterns@}{}%
5531   \begingroup
5532     \bbl@xin@{, \number\language, }{\bbl@pttnlist}%
5533     \ifin@else
5534       \ifx\bbl@patterns@empty\else
5535         \directlua{ Babel.addpatterns(
5536           [[\bbl@patterns@]], \number\language) }%
5537         \fi
5538         \@ifundefined{bbl@patterns@#1}%
5539           \@empty
5540           {\directlua{ Babel.addpatterns(
5541             [[\space\csname bbl@patterns@#1\endcsname]],
5542             \number\language) }}%
5543           \xdef\bbl@pttnlist{\bbl@pttnlist\number\language,}%
5544         \fi
5545     \endgroup}%
5546   \bbl@exp{%
5547     \bbl@ifunset{bbl@prehc@the\languagename}{}%
5548     {\bbl@ifblank{\bbl@cs{prehc@the\languagename}}{}}%
5549     {\prehyphenchar=\bbl@c{prehc}\relax}}}%

```

`\babelpatterns` This macro adds patterns. Two macros are used to store them: `\bbl@patterns@` for the global ones and `\bbl@patterns@<lang>` for language ones. We make sure there is a space between words when multiple commands are used.

```

5550 \@onlypreamble\babelpatterns
5551 \AtEndOfPackage{%
5552   \newcommand\babelpatterns[2][@empty]{%
5553     \ifx\bbl@patterns@relax
5554       \let\bbl@patterns@empty
5555     \fi
5556     \ifx\bbl@pttnlist@empty\else
5557       \bbl@warning{%
5558         You must not intermingle \string\selectlanguage\space and\\
5559         \string\babelpatterns\space or some patterns will not\\
5560         be taken into account. Reported}%
5561       \fi
5562       \ifx@empty#1%
5563         \protected@edef\bbl@patterns@{\bbl@patterns@space#2}%

```

```

5564 \else
5565 \edef\bbl@tempb{\zap@space#1 \@empty}%
5566 \bbl@for\bbl@tempa\bbl@tempb{%
5567 \bbl@fixname\bbl@tempa
5568 \bbl@iflanguage\bbl@tempa{%
5569 \bbl@csarg\protected@edef{patterns@\bbl@tempa}{%
5570 \ifundefined{bbl@patterns@\bbl@tempa}%
5571 \@empty
5572 {\csname bbl@patterns@\bbl@tempa\endcsname\space}%
5573 #2}}}%
5574 \fi}}

```

10.4 Southeast Asian scripts

First, some general code for line breaking, used by `\babelposthyphenation`. Replace regular (ie, implicit) discretionaries by spaceskips, based on the previous glyph (which I think makes sense, because the hyphen and the previous char go always together). Other discretionaries are not touched. See Unicode UAX 14.

```

5575 % TODO - to a lua file
5576 \directlua{
5577   Babel = Babel or {}
5578   Babel.linebreaking = Babel.linebreaking or {}
5579   Babel.linebreaking.before = {}
5580   Babel.linebreaking.after = {}
5581   Babel.locale = {} % Free to use, indexed by \localeid
5582   function Babel.linebreaking.add_before(func, pos)
5583     tex.print([[noexpand\csname bbl@luahyphenate\endcsname]])
5584     if pos == nil then
5585       table.insert(Babel.linebreaking.before, func)
5586     else
5587       table.insert(Babel.linebreaking.before, pos, func)
5588     end
5589   end
5590   function Babel.linebreaking.add_after(func)
5591     tex.print([[noexpand\csname bbl@luahyphenate\endcsname]])
5592     table.insert(Babel.linebreaking.after, func)
5593   end
5594 }
5595 \def\bbl@intraspace#1 #2 #3\@@{%
5596 \directlua{
5597   Babel = Babel or {}
5598   Babel.intraspaces = Babel.intraspaces or {}
5599   Babel.intraspaces['\csname bbl@sbc@p\language\endcsname'] = %
5600     {b = #1, p = #2, m = #3}
5601   Babel.locale_props[\the\localeid].intraspace = %
5602     {b = #1, p = #2, m = #3}
5603 }}
5604 \def\bbl@intrapenalty#1\@@{%
5605 \directlua{
5606   Babel = Babel or {}
5607   Babel.intrapenalties = Babel.intrapenalties or {}
5608   Babel.intrapenalties['\csname bbl@sbc@p\language\endcsname'] = #1
5609   Babel.locale_props[\the\localeid].intrapenalty = #1
5610 }}
5611 \begingroup
5612 \catcode`\%=12
5613 \catcode`\&=14
5614 \catcode`\'=12
5615 \catcode`\~=12
5616 \gdef\bbl@seaintraspace{&
5617 \let\bbl@seaintraspace\relax
5618 \directlua{
5619   Babel = Babel or {}

```

```

5620 Babel.sea_enabled = true
5621 Babel.sea_ranges = Babel.sea_ranges or {}
5622 function Babel.set_chranges (script, chrng)
5623     local c = 0
5624     for s, e in string.gmatch(chrng..' ', '(.-%.(-)%s') do
5625         Babel.sea_ranges[script..c]={tonumber(s,16), tonumber(e,16)}
5626         c = c + 1
5627     end
5628 end
5629 function Babel.sea_disc_to_space (head)
5630     local sea_ranges = Babel.sea_ranges
5631     local last_char = nil
5632     local quad = 655360      &% 10 pt = 655360 = 10 * 65536
5633     for item in node.traverse(head) do
5634         local i = item.id
5635         if i == node.id'glyph' then
5636             last_char = item
5637         elseif i == 7 and item.subtype == 3 and last_char
5638             and last_char.char > 0x0C99 then
5639             quad = font.getfont(last_char.font).size
5640             for lg, rg in pairs(sea_ranges) do
5641                 if last_char.char > rg[1] and last_char.char < rg[2] then
5642                     lg = lg:sub(1, 4) &% Remove trailing number of, eg, Cyril
5643                     local intraspace = Babel.intraspaces[lg]
5644                     local intrapenalty = Babel.intrapenalties[lg]
5645                     local n
5646                     if intrapenalty ~= 0 then
5647                         n = node.new(14, 0)      &% penalty
5648                         n.penalty = intrapenalty
5649                         node.insert_before(head, item, n)
5650                     end
5651                     n = node.new(12, 13)      &% (glue, spaceskip)
5652                     node.setglue(n, intraspace.b * quad,
5653                                 intraspace.p * quad,
5654                                 intraspace.m * quad)
5655                     node.insert_before(head, item, n)
5656                     node.remove(head, item)
5657                 end
5658             end
5659         end
5660     end
5661 end
5662 }&
5663 \bbl@luaohyphenate}

```

10.5 CJK line breaking

Minimal line breaking for CJK scripts, mainly intended for simple documents and short texts as a secondary language. Only line breaking, with a little stretching for justification, without any attempt to adjust the spacing. It is based on (but does not strictly follow) the Unicode algorithm.

We first need a little table with the corresponding line breaking properties. A few characters have an additional key for the width (fullwidth vs. halfwidth), not yet used. There is a separate file, defined below.

```

5664 \catcode`\%=14
5665 \gdef\bbl@cjkintraspaces{%
5666     \let\bbl@cjkintraspaces\relax
5667     \directlua{
5668         Babel = Babel or {}
5669         require('babel-data-cjk.lua')
5670         Babel.cjk_enabled = true
5671         function Babel.cjk_linebreak(head)
5672             local GLYPH = node.id'glyph'
5673             local last_char = nil

```

```

5674     local quad = 655360      % 10 pt = 655360 = 10 * 65536
5675     local last_class = nil
5676     local last_lang = nil
5677
5678     for item in node.traverse(head) do
5679         if item.id == GLYPH then
5680
5681             local lang = item.lang
5682
5683             local LOCALE = node.get_attribute(item,
5684                 Babel.attr_locale)
5685             local props = Babel.locale_props[LOCALE]
5686
5687             local class = Babel.cjk_class[item.char].c
5688
5689             if props.cjk_quotes and props.cjk_quotes[item.char] then
5690                 class = props.cjk_quotes[item.char]
5691             end
5692
5693             if class == 'cp' then class = 'cl' end % ]] as CL
5694             if class == 'id' then class = 'I' end
5695
5696             local br = 0
5697             if class and last_class and Babel.cjk_breaks[last_class][class] then
5698                 br = Babel.cjk_breaks[last_class][class]
5699             end
5700
5701             if br == 1 and props.linebreak == 'c' and
5702                 lang ~= \the\l@nohyphenation\space and
5703                 last_lang ~= \the\l@nohyphenation then
5704                 local intrapenalty = props.intrapenalty
5705                 if intrapenalty ~= 0 then
5706                     local n = node.new(14, 0)      % penalty
5707                     n.penalty = intrapenalty
5708                     node.insert_before(head, item, n)
5709                 end
5710                 local intraspace = props.intraspace
5711                 local n = node.new(12, 13)          % (glue, spaceskip)
5712                 node.setglue(n, intraspace.b * quad,
5713                     intraspace.p * quad,
5714                     intraspace.m * quad)
5715                 node.insert_before(head, item, n)
5716             end
5717
5718             if font.getfont(item.font) then
5719                 quad = font.getfont(item.font).size
5720             end
5721             last_class = class
5722             last_lang = lang
5723             else % if penalty, glue or anything else
5724                 last_class = nil
5725             end
5726         end
5727         lang.hyphenate(head)
5728     end
5729 }%
5730 \bbl@luahyphenate}
5731 \gdef\bbl@luahyphenate{%
5732 \let\bbl@luahyphenate\relax
5733 \directlua{
5734     luatexbase.add_to_callback('hyphenate',
5735     function (head, tail)
5736         if Babel.linebreaking.before then

```

```

5737     for k, func in ipairs(Babel.linebreaking.before) do
5738         func(head)
5739     end
5740 end
5741 if Babel.cjk_enabled then
5742     Babel.cjk_linebreak(head)
5743 end
5744 lang.hyphenate(head)
5745 if Babel.linebreaking.after then
5746     for k, func in ipairs(Babel.linebreaking.after) do
5747         func(head)
5748     end
5749 end
5750 if Babel.sea_enabled then
5751     Babel.sea_disc_to_space(head)
5752 end
5753 end,
5754 'Babel.hyphenate')
5755 }
5756 }
5757 \endgroup
5758 \def\bbl@provide@intraspace{%
5759     \bbl@ifunset{\bbl@intsp@{language}}{%
5760         {\expandafter\ifx\csname bbl@intsp@{language}\endcsname\@empty\else
5761             \bbl@xin@{/c}{\bbl@cl{lnbrk}}}%
5762         \ifin@             % cjk
5763             \bbl@cjk@intraspace
5764             \directlua{
5765                 Babel = Babel or {}
5766                 Babel.locale_props = Babel.locale_props or {}
5767                 Babel.locale_props[\the\localeid].linebreak = 'c'
5768             }%
5769             \bbl@exp{\bbl@intraspace\bbl@cl{intsp}}\@{}%
5770             \ifx\bbl@KVP@intrapenalty\@nnil
5771                 \bbl@intrapenalty0\@{}
5772             \fi
5773         \else             % sea
5774             \bbl@seaintraspace
5775             \bbl@exp{\bbl@intraspace\bbl@cl{intsp}}\@{}%
5776             \directlua{
5777                 Babel = Babel or {}
5778                 Babel.sea_ranges = Babel.sea_ranges or {}
5779                 Babel.set_chranges('\bbl@cl{sbcp}',
5780                                     '\bbl@cl{chrng}')
5781             }%
5782             \ifx\bbl@KVP@intrapenalty\@nnil
5783                 \bbl@intrapenalty0\@{}
5784             \fi
5785         \fi
5786     \fi
5787     \ifx\bbl@KVP@intrapenalty\@nnil\else
5788         \expandafter\bbl@intrapenalty\bbl@KVP@intrapenalty\@{}
5789     \fi}}

```

10.6 Arabic justification

WIP. \bbl@arabicjust is executed with both elongated an kashida. This must be fine tuned. The attribute kashida is set by transforms with kashida-

```

5790 \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200
5791 \def\bblar@chars{%
5792     0628,0629,062A,062B,062C,062D,062E,062F,0630,0631,0632,0633,%
5793     0634,0635,0636,0637,0638,0639,063A,063B,063C,063D,063E,063F,%
5794     0640,0641,0642,0643,0644,0645,0646,0647,0649}

```



```

5795 \def\bblar@elongated{%
5796   0626,0628,062A,062B,0633,0634,0635,0636,063B,%
5797   063C,063D,063E,063F,0641,0642,0643,0644,0646,%
5798   0649,064A}
5799 \begingroup
5800   \catcode\_ =11 \catcode\:=11
5801   \gdef\bblar@nofswarn{\gdef\msg_warning:nx##1##2##3{}}
5802 \endgroup
5803 \gdef\bblar@arabicjust{% TODO. Allow for several locales.
5804   \let\bblar@arabicjust\relax
5805   \newattribute\bblar@kashida
5806   \directlua{ Babel.attr_kashida = luatexbase.registernumber'bblar@kashida' }%
5807   \bblar@kashida=\z@
5808   \bbl@patchfont{\bbl@parsejalt}}%
5809   \directlua{
5810     Babel.arabic.elong_map = Babel.arabic.elong_map or {}
5811     Babel.arabic.elong_map[\the\localeid] = {}
5812     luatexbase.add_to_callback('post_linebreak_filter',
5813       Babel.arabic.justify, 'Babel.arabic.justify')
5814     luatexbase.add_to_callback('hpack_filter',
5815       Babel.arabic.justify_hbox, 'Babel.arabic.justify_hbox')
5816   }}%

```

Save both node lists to make replacement. TODO. Save also widths to make computations.

```

5817 \def\bblar@fetchjalt#1#2#3#4{%
5818   \bbl@exp{\bbl@foreach{#1}}{%
5819     \bbl@ifunset\bblar@JE@##1{%
5820       {\setbox\z@\hbox{\textdir TRT ^^^200d\char"##1#2}}%
5821       {\setbox\z@\hbox{\textdir TRT ^^^200d\char"\@nameuse\bblar@JE@##1#2}}%
5822     \directlua{%
5823       local last = nil
5824       for item in node.traverse(tex.box[0].head) do
5825         if item.id == node.id'glyph' and item.char > 0x600 and
5826           not (item.char == 0x200D) then
5827           last = item
5828         end
5829       end
5830       Babel.arabic.#3['##1#4'] = last.char
5831     }}

```

Elongated forms. Brute force. No rules at all, yet. The ideal: look at jalt table. And perhaps other tables (falt?, csw?). What about kaf? And diacritic positioning?

```

5832 \gdef\bblar@parsejalt{%
5833   \ifx\addfontfeature\@undefined\else
5834     \bbl@xin@{/e}{/\bbl@c{l}{lnbrk}}}%
5835   \ifin@
5836     \directlua{%
5837       if Babel.arabic.elong_map[\the\localeid][\fontid\font] == nil then
5838         Babel.arabic.elong_map[\the\localeid][\fontid\font] = {}
5839         tex.print([\string\csname\space bbl@parsejalti\endcsname])
5840       end
5841     }%
5842   \fi
5843 \fi}
5844 \gdef\bblar@parsejalti{%
5845   \begingroup
5846     \let\bblar@parsejalt\relax % To avoid infinite loop
5847     \edef\bblar@tempb{\fontid\font}%
5848     \bblar@nofswarn
5849     \bblar@fetchjalt\bblar@elongated{}{from}}%
5850     \bblar@fetchjalt\bblar@chars{^^^064a}{from}{a}% Alef maksura
5851     \bblar@fetchjalt\bblar@chars{^^^0649}{from}{y}% Yeh
5852     \addfontfeature{RawFeature+=jalt}%
5853     % \@namedef\bblar@JE@0643{06AA}% todo: catch medial kaf

```

```

5854 \bblar@fetchjalt\bblar@elongated{}{dest}{}%
5855 \bblar@fetchjalt\bblar@chars{^^^064a}{dest}{a}%
5856 \bblar@fetchjalt\bblar@chars{^^^0649}{dest}{y}%
5857 \directlua{%
5858     for k, v in pairs(Babel.arabic.from) do
5859         if Babel.arabic.dest[k] and
5860             not (Babel.arabic.from[k] == Babel.arabic.dest[k]) then
5861             Babel.arabic.elong_map[\the\localeid][\bbl@tempb]
5862                 [Babel.arabic.from[k]] = Babel.arabic.dest[k]
5863         end
5864     end
5865 }%
5866 \endgroup}

```

The actual justification (inspired by CHICKENIZE).

```

5867 \begingroup
5868 \catcode`#=11
5869 \catcode`~ =11
5870 \directlua{
5871
5872 Babel.arabic = Babel.arabic or {}
5873 Babel.arabic.from = {}
5874 Babel.arabic.dest = {}
5875 Babel.arabic.justify_factor = 0.95
5876 Babel.arabic.justify_enabled = true
5877 Babel.arabic.kashida_limit = -1
5878
5879 function Babel.arabic.justify(head)
5880     if not Babel.arabic.justify_enabled then return head end
5881     for line in node.traverse_id(node.id'hlist', head) do
5882         Babel.arabic.justify_hlist(head, line)
5883     end
5884     return head
5885 end
5886
5887 function Babel.arabic.justify_hbox(head, gc, size, pack)
5888     local has_inf = false
5889     if Babel.arabic.justify_enabled and pack == 'exactly' then
5890         for n in node.traverse_id(l2, head) do
5891             if n.stretch_order > 0 then has_inf = true end
5892         end
5893         if not has_inf then
5894             Babel.arabic.justify_hlist(head, nil, gc, size, pack)
5895         end
5896     end
5897     return head
5898 end
5899
5900 function Babel.arabic.justify_hlist(head, line, gc, size, pack)
5901     local d, new
5902     local k_list, k_item, pos_inline
5903     local width, width_new, full, k_curr, wt_pos, goal, shift
5904     local subst_done = false
5905     local elong_map = Babel.arabic.elong_map
5906     local cnt
5907     local last_line
5908     local GLYPH = node.id'glyph'
5909     local KASHIDA = Babel.attr_kashida
5910     local LOCALE = Babel.attr_locale
5911
5912     if line == nil then
5913         line = {}
5914         line.glue_sign = 1

```

```

5915     line.glue_order = 0
5916     line.head = head
5917     line.shift = 0
5918     line.width = size
5919 end
5920
5921 % Exclude last line. todo. But-- it discards one-word lines, too!
5922 % ? Look for glue = 12:15
5923 if (line.glue_sign == 1 and line.glue_order == 0) then
5924     elongs = {}      % Stores elongated candidates of each line
5925     k_list = {}      % And all letters with kashida
5926     pos_inline = 0  % Not yet used
5927
5928     for n in node.traverse_id(GLYPH, line.head) do
5929         pos_inline = pos_inline + 1 % To find where it is. Not used.
5930
5931         % Elongated glyphs
5932         if elong_map then
5933             local locale = node.get_attribute(n, LOCALE)
5934             if elong_map[locale] and elong_map[locale][n.font] and
5935                 elong_map[locale][n.font][n.char] then
5936                 table.insert(elongs, {node = n, locale = locale} )
5937                 node.set_attribute(n.prev, KASHIDA, 0)
5938             end
5939         end
5940
5941         % Tatwil
5942         if Babel.kashida_wts then
5943             local k_wt = node.get_attribute(n, KASHIDA)
5944             if k_wt > 0 then % todo. parameter for multi inserts
5945                 table.insert(k_list, {node = n, weight = k_wt, pos = pos_inline})
5946             end
5947         end
5948     end
5949 end % of node.traverse_id
5950
5951 if #elongs == 0 and #k_list == 0 then goto next_line end
5952 full = line.width
5953 shift = line.shift
5954 goal = full * Babel.arabic.justify_factor % A bit crude
5955 width = node.dimensions(line.head) % The 'natural' width
5956
5957 % == Elongated ==
5958 % Original idea taken from 'chickenize'
5959 while (#elongs > 0 and width < goal) do
5960     subst_done = true
5961     local x = #elongs
5962     local curr = elongs[x].node
5963     local oldchar = curr.char
5964     curr.char = elong_map[elongs[x].locale][curr.font][curr.char]
5965     width = node.dimensions(line.head) % Check if the line is too wide
5966     % Substitute back if the line would be too wide and break:
5967     if width > goal then
5968         curr.char = oldchar
5969         break
5970     end
5971     % If continue, pop the just substituted node from the list:
5972     table.remove(elongs, x)
5973 end
5974
5975 % == Tatwil ==
5976 if #k_list == 0 then goto next_line end
5977

```

```

5978 width = node.dimensions(line.head) % The 'natural' width
5979 k_curr = #k_list % Traverse backwards, from the end
5980 wt_pos = 1
5981
5982 while width < goal do
5983   subst_done = true
5984   k_item = k_list[k_curr].node
5985   if k_list[k_curr].weight == Babel.kashida_wts[wt_pos] then
5986     d = node.copy(k_item)
5987     d.char = 0x0640
5988     d.yoffset = 0 % TODO. From the prev char. But 0 seems safe.
5989     d.xoffset = 0
5990     line.head, new = node.insert_after(line.head, k_item, d)
5991     width_new = node.dimensions(line.head)
5992     if width > goal or width == width_new then
5993       node.remove(line.head, new) % Better compute before
5994       break
5995     end
5996     if Babel.fix_diacr then
5997       Babel.fix_diacr(k_item.next)
5998     end
5999     width = width_new
6000   end
6001   if k_curr == 1 then
6002     k_curr = #k_list
6003     wt_pos = (wt_pos >= table.getn(Babel.kashida_wts)) and 1 or wt_pos+1
6004   else
6005     k_curr = k_curr - 1
6006   end
6007 end
6008
6009 % Limit the number of tatweel by removing them. Not very efficient,
6010 % but it does the job in a quite predictable way.
6011 if Babel.arabic.kashida_limit > -1 then
6012   cnt = 0
6013   for n in node.traverse_id(GLYPH, line.head) do
6014     if n.char == 0x0640 then
6015       cnt = cnt + 1
6016       if cnt > Babel.arabic.kashida_limit then
6017         node.remove(line.head, n)
6018       end
6019     else
6020       cnt = 0
6021     end
6022   end
6023 end
6024
6025 ::next_line::
6026
6027 % Must take into account marks and ins, see luatex manual.
6028 % Have to be executed only if there are changes. Investigate
6029 % what's going on exactly.
6030 if subst_done and not gc then
6031   d = node.hpack(line.head, full, 'exactly')
6032   d.shift = shift
6033   node.insert_before(head, line, d)
6034   node.remove(head, line)
6035 end
6036 end % if process line
6037 end
6038 }
6039 \endgroup
6040 \fi\fi % ends Arabic just block: \ifnum\bbl@bidimode>100...

```

10.7 Common stuff

```
6041 \AddBabelHook{babel-fontspec}{afterextras}{\bbl@switchfont}
6042 \AddBabelHook{babel-fontspec}{beforestart}{\bbl@ckeckstdfonts}
6043 \DisableBabelHook{babel-fontspec}
6044 <<Font selection>>
```

10.8 Automatic fonts and ids switching

After defining the blocks for a number of scripts (must be extended and very likely fine tuned), we define a the function `Babel.locale_map`, which just traverse the node list to carry out the replacements. The table `loc_to_scr` stores the script range for each locale (whose id is the key), copied from this table (so that it can be modified on a locale basis); there is an intermediate table named `chr_to_loc` built on the fly for optimization, which maps a char to the locale. This locale is then used to get the `\language` as stored in `locale_props`, as well as the font (as requested). In the latter table a key starting with `/` maps the font from the global one (the key) to the local one (the value). Maths are skipped and discretionaries are handled in a special way.

```
6045 % TODO - to a lua file
6046 \directlua{
6047 Babel.script_blocks = {
6048   ['dflt'] = {},
6049   ['Arab'] = {{0x0600, 0x06FF}, {0x08A0, 0x08FF}, {0x0750, 0x077F},
6050               {0xFE70, 0xFEFF}, {0xFB50, 0xFDFF}, {0x1EE00, 0x1EEFF}},
6051   ['Armn'] = {{0x0530, 0x058F}},
6052   ['Beng'] = {{0x0980, 0x09FF}},
6053   ['Cher'] = {{0x13A0, 0x13FF}, {0xAB70, 0xABBF}},
6054   ['Copt'] = {{0x03E2, 0x03EF}, {0x2C80, 0x2CFF}, {0x102E0, 0x102FF}},
6055   ['Cyrl'] = {{0x0400, 0x04FF}, {0x0500, 0x052F}, {0x1C80, 0x1C8F},
6056               {0x2DE0, 0x2DFF}, {0xA640, 0xA69F}},
6057   ['Deva'] = {{0x0900, 0x097F}, {0xA8E0, 0xA8FF}},
6058   ['Ethi'] = {{0x1200, 0x137F}, {0x1380, 0x139F}, {0x2D80, 0x2DDF},
6059               {0xAB00, 0xAB2F}},
6060   ['Geor'] = {{0x10A0, 0x10FF}, {0x2D00, 0x2D2F}},
6061   % Don't follow strictly Unicode, which places some Coptic letters in
6062   % the 'Greek and Coptic' block
6063   ['Grek'] = {{0x0370, 0x03E1}, {0x03F0, 0x03FF}, {0x1F00, 0x1FFF}},
6064   ['Hans'] = {{0x2E80, 0x2EFF}, {0x3000, 0x303F}, {0x31C0, 0x31EF},
6065               {0x3300, 0x33FF}, {0x3400, 0x4DBF}, {0x4E00, 0x9FFF},
6066               {0xF900, 0xFAFF}, {0xFE30, 0xFE4F}, {0xFF00, 0xFFEF},
6067               {0x20000, 0x2A6DF}, {0x2A700, 0x2B73F},
6068               {0x2B740, 0x2B81F}, {0x2B820, 0x2CEAF},
6069               {0x2CEB0, 0x2EBEF}, {0x2F800, 0x2FA1F}},
6070   ['Hebr'] = {{0x0590, 0x05FF}},
6071   ['Jpan'] = {{0x3000, 0x303F}, {0x3040, 0x309F}, {0x30A0, 0x30FF},
6072               {0x4E00, 0x9FAF}, {0xFF00, 0xFFEF}},
6073   ['Khmr'] = {{0x1780, 0x17FF}, {0x19E0, 0x19FF}},
6074   ['Knda'] = {{0x0C80, 0x0CFF}},
6075   ['Kore'] = {{0x1100, 0x11FF}, {0x3000, 0x303F}, {0x3130, 0x318F},
6076               {0x4E00, 0x9FAF}, {0xA960, 0xA97F}, {0xAC00, 0xD7AF},
6077               {0xD7B0, 0xD7FF}, {0xFF00, 0xFFEF}},
6078   ['Lao'] = {{0x0E80, 0x0EFF}},
6079   ['Latn'] = {{0x0000, 0x007F}, {0x0080, 0x00FF}, {0x0100, 0x017F},
6080               {0x0180, 0x024F}, {0x1E00, 0x1EFF}, {0x2C60, 0x2C7F},
6081               {0xA720, 0xA7FF}, {0xAB30, 0xAB6F}},
6082   ['Mahj'] = {{0x11150, 0x1117F}},
6083   ['Mlym'] = {{0x0D00, 0x0D7F}},
6084   ['Mymr'] = {{0x1000, 0x109F}, {0xAA60, 0xAA7F}, {0xA9E0, 0xA9FF}},
6085   ['Orya'] = {{0x0B00, 0x0B7F}},
6086   ['Sinh'] = {{0x0D80, 0x0DFF}, {0x111E0, 0x111FF}},
6087   ['Syrc'] = {{0x0700, 0x074F}, {0x0860, 0x086F}},
6088   ['Taml'] = {{0x0B80, 0x0BFF}},
6089   ['Telu'] = {{0x0C00, 0x0C7F}},
6090   ['Tfng'] = {{0x2D30, 0x2D7F}},
6091   ['Thai'] = {{0x0E00, 0x0E7F}},
```

```

6092 ['Tibt'] = {{0x0F00, 0x0FFF}},
6093 ['Vaii'] = {{0xA500, 0xA63F}},
6094 ['Yiii'] = {{0xA000, 0xA48F}, {0xA490, 0xA4CF}}
6095 }
6096
6097 Babel.script_blocks.Cyrs = Babel.script_blocks.Cyrl
6098 Babel.script_blocks.Hant = Babel.script_blocks.Hans
6099 Babel.script_blocks.Kana = Babel.script_blocks.Jpan
6100
6101 function Babel.locale_map(head)
6102   if not Babel.locale_mapped then return head end
6103
6104   local LOCALE = Babel.attr_locale
6105   local GLYPH = node.id('glyph')
6106   local inmath = false
6107   local toloc_save
6108   for item in node.traverse(head) do
6109     local toloc
6110     if not inmath and item.id == GLYPH then
6111       % Optimization: build a table with the chars found
6112       if Babel.chr_to_loc[item.char] then
6113         toloc = Babel.chr_to_loc[item.char]
6114       else
6115         for lc, maps in pairs(Babel.loc_to_scr) do
6116           for _, rg in pairs(maps) do
6117             if item.char >= rg[1] and item.char <= rg[2] then
6118               Babel.chr_to_loc[item.char] = lc
6119               toloc = lc
6120               break
6121             end
6122           end
6123         end
6124         % Treat composite chars in a different fashion, because they
6125         % 'inherit' the previous locale.
6126         if (item.char >= 0x0300 and item.char <= 0x036F) or
6127            (item.char >= 0x1AB0 and item.char <= 0x1AFF) or
6128            (item.char >= 0x1DC0 and item.char <= 0x1DFF) then
6129           Babel.chr_to_loc[item.char] = -2000
6130           toloc = -2000
6131         end
6132         if not toloc then
6133           Babel.chr_to_loc[item.char] = -1000
6134         end
6135       end
6136       if toloc == -2000 then
6137         toloc = toloc_save
6138       elseif toloc == -1000 then
6139         toloc = nil
6140       end
6141       if toloc and Babel.locale_props[toloc] and
6142          Babel.locale_props[toloc].letters and
6143          tex.getcatcode(item.char) \string~= 11 then
6144         toloc = nil
6145       end
6146       if toloc and Babel.locale_props[toloc].script
6147          and Babel.locale_props[node.get_attribute(item, LOCALE)].script
6148          and Babel.locale_props[toloc].script ==
6149          Babel.locale_props[node.get_attribute(item, LOCALE)].script then
6150         toloc = nil
6151       end
6152       if toloc then
6153         if Babel.locale_props[toloc].lg then
6154           item.lang = Babel.locale_props[toloc].lg

```

```

6155         node.set_attribute(item, LOCALE, toloc)
6156     end
6157     if Babel.locale_props[toloc]['/'..item.font] then
6158         item.font = Babel.locale_props[toloc]['/'..item.font]
6159     end
6160 end
6161 toloc_save = toloc
6162 elseif not inmath and item.id == 7 then % Apply recursively
6163     item.replace = item.replace and Babel.locale_map(item.replace)
6164     item.pre      = item.pre and Babel.locale_map(item.pre)
6165     item.post     = item.post and Babel.locale_map(item.post)
6166 elseif item.id == node.id'math' then
6167     inmath = (item.subtype == 0)
6168 end
6169 end
6170 return head
6171 end
6172 }

```

The code for `\babelcharproperty` is straightforward. Just note the modified lua table can be different.

```

6173 \newcommand\babelcharproperty[1]{%
6174   \count@=#1\relax
6175   \ifvmode
6176     \expandafter\bbl@chprop
6177   \else
6178     \bbl@error{charproperty-only-vertical}{}{}{}%
6179   \fi}
6180 \newcommand\bbl@chprop[3][\the\count@]{%
6181   \@tempcnta=#1\relax
6182   \bbl@ifunset{bbl@chprop@#2}% {unknown-char-property}
6183   {\bbl@error{unknown-char-property}{}{#2}{}%
6184   }%
6185   \loop
6186     \bbl@cs{chprop@#2}{#3}%
6187     \ifnum\count@<\@tempcnta
6188       \advance\count@\@ne
6189     \repeat}
6190 \def\bbl@chprop@direction#1{%
6191   \directlua{
6192     Babel.characters[\the\count@] = Babel.characters[\the\count@] or {}
6193     Babel.characters[\the\count@]['d'] = '#1'
6194   }}
6195 \let\bbl@chprop@bc\bbl@chprop@direction
6196 \def\bbl@chprop@mirror#1{%
6197   \directlua{
6198     Babel.characters[\the\count@] = Babel.characters[\the\count@] or {}
6199     Babel.characters[\the\count@]['m'] = '\number#1'
6200   }}
6201 \let\bbl@chprop@bmg\bbl@chprop@mirror
6202 \def\bbl@chprop@linebreak#1{%
6203   \directlua{
6204     Babel.cjk_characters[\the\count@] = Babel.cjk_characters[\the\count@] or {}
6205     Babel.cjk_characters[\the\count@]['c'] = '#1'
6206   }}
6207 \let\bbl@chprop@lb\bbl@chprop@linebreak
6208 \def\bbl@chprop@locale#1{%
6209   \directlua{
6210     Babel.chr_to_loc = Babel.chr_to_loc or {}
6211     Babel.chr_to_loc[\the\count@] =
6212       \bbl@ifblank{#1}{-1000}{\the\bbl@cs{id@#1}}\space
6213   }}

```

Post-handling hyphenation patterns for non-standard rules, like `ff` to `ff-f`. There are still some

issues with speed (not very slow, but still slow). The Lua code is below.

```
6214 \directlua{
6215   Babel.nohyphenation = \the\l@nohyphenation
6216 }
```

Now the \TeX high level interface, which requires the function defined above for converting strings to functions returning a string. These functions handle the $\{n\}$ syntax. For example, $\text{pre}=\{1\}\{1\}$ becomes $\text{function}(m) \text{ return } m[1]..m[1]..'-' \text{ end}$, where m are the matches returned after applying the pattern. With a mapped capture the functions are similar to $\text{function}(m) \text{ return } \text{Babel.capt_map}(m[1],1) \text{ end}$, where the last argument identifies the mapping to be applied to $m[1]$. The way it is carried out is somewhat tricky, but the effect is not dissimilar to lua load – save the code as string in a TeX macro, and expand this macro at the appropriate place. As $\backslash\text{directlua}$ does not take into account the current catcode of $@$, we just avoid this character in macro names (which explains the internal group, too).

```
6217 \beginingroup
6218 \catcode`\~ = 12
6219 \catcode`\% = 12
6220 \catcode`\& = 14
6221 \catcode`\| = 12
6222 \gdef\babelprehyphenation{%&
6223   \@ifnextchar[{\bbl@settransform{0}}{\bbl@settransform{0}}{}]}
6224 \gdef\babelposthyphenation{%&
6225   \@ifnextchar[{\bbl@settransform{1}}{\bbl@settransform{1}}{}]}
6226 \gdef\bbl@settransform#1[#2]#3#4#5{%&
6227   \ifcase#1
6228     \bbl@activateprehyphen
6229   \or
6230     \bbl@activateposthyphen
6231   \fi
6232   \beginingroup
6233     \def\babeltempa{\bbl@add@list\babeltempb}%&
6234     \let\babeltempb@empty
6235     \def\bbl@tempa{#5}%&
6236     \bbl@replace\bbl@tempa{,}{ ,}%& TODO. Ugly trick to preserve {}
6237     \expandafter\bbl@foreach\expandafter{\bbl@tempa}{%&
6238       \bbl@ifsamestring{##1}{remove}%&
6239       {\bbl@add@list\babeltempb{nil}}}%&
6240     {\directlua{
6241       local rep = {[##1]=}
6242       rep = rep:gsub('^%s*(remove)%s*$', 'remove = true')
6243       rep = rep:gsub('^%s*(insert)%s*', ', 'insert = true, ')
6244       rep = rep:gsub('(string)%s*=%s*([^\s,]*)', Babel.capture_func)
6245       rep = rep:gsub('node%s*=%s*(%a)%s*(%a*)', Babel.capture_node)
6246       if #1 == 0 or #1 == 2 then
6247         rep = rep:gsub(&
6248           '(space)%s*=%s*([%-d%.]+)%s+([%-d%.]+)%s+([%-d%.]+)',
6249           'space = {' .. '%2, %3, %4' .. '}')
6250         rep = rep:gsub(&
6251           '(spacefactor)%s*=%s*([%-d%.]+)%s+([%-d%.]+)%s+([%-d%.]+)',
6252           'spacefactor = {' .. '%2, %3, %4' .. '}')
6253         rep = rep:gsub('(kashida)%s*=%s*([^\s,]*)', Babel.capture_kashida)
6254       else
6255         rep = rep:gsub(' (no)%s*=%s*([^\s,]*)', Babel.capture_func)
6256         rep = rep:gsub(' (pre)%s*=%s*([^\s,]*)', Babel.capture_func)
6257         rep = rep:gsub(' (post)%s*=%s*([^\s,]*)', Babel.capture_func)
6258       end
6259       tex.print([[ \string\babeltempa{[] .. rep .. []]])
6260     }]}%&
6261   \bbl@foreach\babeltempb{%&
6262     \bbl@forkv{##1}{%&
6263       \in@{,###1,}{,nil,step,data,remove,insert,string,no,pre,&
6264       no,post,penalty,kashida,space,spacefactor,kern,node}%&
6265     \ifin@else
```



```

6266         \bbl@error{bad-transform-option}{####1}{}}{}&%
6267     \fi}}&%
6268     \let\bbl@kv@attribute\relax
6269     \let\bbl@kv@label\relax
6270     \let\bbl@kv@fonts\@empty
6271     \bbl@forkv{#2}{\bbl@csarg\edef{kv@##1}{##2}}&%
6272     \ifx\bbl@kv@fonts\@empty\else\bbl@settransfont\fi
6273     \ifx\bbl@kv@attribute\relax
6274         \ifx\bbl@kv@label\relax\else
6275             \bbl@exp{\bbl@trim@def\bbl@kv@fonts{\bbl@kv@fonts}}&%
6276             \bbl@replace\bbl@kv@fonts{ }{,}&%
6277             \edef\bbl@kv@attribute{\bbl@ATR@\bbl@kv@label @#3@\bbl@kv@fonts}&%
6278             \count@\z@
6279             \def\bbl@elt##1##2##3{&%
6280                 \bbl@ifsamestring{#3,\bbl@kv@label}{##1,##2}&%
6281                 {\bbl@ifsamestring{\bbl@kv@fonts}{##3}&%
6282                     {\count@\@ne}&%
6283                     {\bbl@error{font-conflict-transforms}{}}{}}}&%
6284                 }}&%
6285             \bbl@transfont@list
6286             \ifnum\count@=\z@
6287                 \bbl@exp{\global\bbl@add\bbl@transfont@list
6288                     {\bbl@elt{#3}{\bbl@kv@label}{\bbl@kv@fonts}}}&%
6289             \fi
6290             \bbl@ifunset{\bbl@kv@attribute}&%
6291             {\global\bbl@carg\newattribute{\bbl@kv@attribute}}&%
6292             {}&%
6293             \global\bbl@carg\setattribute{\bbl@kv@attribute}\@ne
6294         \fi
6295     \else
6296         \edef\bbl@kv@attribute{\expandafter\bbl@stripslash\bbl@kv@attribute}&%
6297     \fi
6298     \directlua{
6299         local lbkr = Babel.linebreaking.replacements[#1]
6300         local u = unicode.utf8
6301         local id, attr, label
6302         if #1 == 0 then
6303             id = \the\csname bbl@id@#3\endcsname\space
6304         else
6305             id = \the\csname l@#3\endcsname\space
6306         end
6307         \ifx\bbl@kv@attribute\relax
6308             attr = -1
6309         \else
6310             attr = luatexbase.registernumber'\bbl@kv@attribute'
6311         \fi
6312         \ifx\bbl@kv@label\relax\else &% Same refs:
6313             label = [==[\bbl@kv@label]==]
6314         \fi
6315         &% Convert pattern:
6316         local patt = string.gsub([==[#4]==], '%s', '')
6317         if #1 == 0 then
6318             patt = string.gsub(patt, '|', ' ')
6319         end
6320         if not u.find(patt, '()', nil, true) then
6321             patt = '()' .. patt .. '()'
6322         end
6323         if #1 == 1 then
6324             patt = string.gsub(patt, '%(%)^', '^()')
6325             patt = string.gsub(patt, '%$(%)', '()$')
6326         end
6327         patt = u.gsub(patt, '{(.)}',
6328             function (n)

```

```

6329         return '%' .. (tonumber(n) and (tonumber(n)+1) or n)
6330     end)
6331     patt = u.gsub(patt, '{(%x%x%x%x+)}',
6332         function (n)
6333             return u.gsub(u.char(tonumber(n, 16)), '(%p)', '%%1')
6334         end)
6335     lbkr[id] = lbkr[id] or {}
6336     print('*****' .. patt)
6337     table.insert(lbkr[id],
6338         { label=label, attr=attr, pattern=patt, replace={\babeltempb} })
6339 }&%
6340 \endgroup}
6341 \endgroup
6342 \let\bbl@transfont@list@empty
6343 \def\bbl@settransfont{%
6344     \global\let\bbl@settransfont\relax % Execute only once
6345     \gdef\bbl@transfont{%
6346         \def\bbl@elt####1####2####3{%
6347             \bbl@ifblank{####3}%
6348             {\count@tw@}% Do nothing if no fonts
6349             {\count@z@
6350             \bbl@vforeach{####3}{%
6351                 \def\bbl@tempd{#####1}%
6352                 \edef\bbl@tempe{\bbl@transfam/\f@series/\f@shape}%
6353                 \ifx\bbl@tempd\bbl@tempe
6354                     \count@ne
6355                 \else\ifx\bbl@tempd\bbl@transfam
6356                     \count@ne
6357                 \fi\fi}%
6358             \ifcase\count@
6359                 \bbl@csarg\unsetattribute{ATR####2@####1@####3}%
6360             \or
6361                 \bbl@csarg\setattribute{ATR####2@####1@####3}\@ne
6362             \fi}}%
6363         \bbl@transfont@list}%
6364     \AddToHook{selectfont}{\bbl@transfont}% Hooks are global.
6365     \gdef\bbl@transfam{-unknown-}%
6366     \bbl@foreach\bbl@font@fams{%
6367         \AddToHook{##1family}{\def\bbl@transfam{##1}}%
6368         \bbl@ifsamestring{\@nameuse{##1default}}{\familydefault
6369             {\xdef\bbl@transfam{##1}}}%
6370         {}}}
6371 \DeclareRobustCommand\enablelocaletransform[1]{%
6372     \bbl@ifunset{\bbl@ATR@#1@languagename @}%
6373     {\bbl@error{transform-not-available}{#1}}}%
6374     {\bbl@csarg\setattribute{ATR@#1@languagename @}\@ne}}
6375 \DeclareRobustCommand\disablelocaletransform[1]{%
6376     \bbl@ifunset{\bbl@ATR@#1@languagename @}%
6377     {\bbl@error{transform-not-available-b}{#1}}}%
6378     {\bbl@csarg\unsetattribute{ATR@#1@languagename @}}}
6379 \def\bbl@activateposthyphen{%
6380     \let\bbl@activateposthyphen\relax
6381     \directlua{
6382         require('babel-transforms.lua')
6383         Babel.linebreaking.add_after(Babel.post_hyphenate_replace)
6384     }}
6385 \def\bbl@activateprehyphen{%
6386     \let\bbl@activateprehyphen\relax
6387     \directlua{
6388         require('babel-transforms.lua')
6389         Babel.linebreaking.add_before(Babel.pre_hyphenate_replace)
6390     }}

```

The following experimental (and unfinished) macro applies the prehyphenation transforms for the

current locale to a string (characters and spaces) and processes it in a fully expandable way (among other limitations, the string can't contain]=}). The way it operates is admittedly rather cumbersome: it converts the string to a node list, processes it, and converts it back to a string. The lua code is in the lua file below.

```
6391 \newcommand\localeprehyphenation[1]{%
6392   \directlua{ Babel.string_prehyphenation([=#1==], \the\localeid) }}
```

10.9 Bidi

As a first step, add a handler for bidi and digits (and potentially other processes) just before luaotfload is applied, which is loaded by default by \TeX . Just in case, consider the possibility it has not been loaded.

```
6393 \def\bbl@activate@preotf{%
6394   \let\bbl@activate@preotf\relax % only once
6395   \directlua{
6396     Babel = Babel or {}
6397     %
6398     function Babel.pre_otfload_v(head)
6399       if Babel.numbers and Babel.digits_mapped then
6400         head = Babel.numbers(head)
6401       end
6402       if Babel.bidi_enabled then
6403         head = Babel.bidi(head, false, dir)
6404       end
6405       return head
6406     end
6407     %
6408     function Babel.pre_otfload_h(head, gc, sz, pt, dir)
6409       if Babel.numbers and Babel.digits_mapped then
6410         head = Babel.numbers(head)
6411       end
6412       if Babel.bidi_enabled then
6413         head = Babel.bidi(head, false, dir)
6414       end
6415       return head
6416     end
6417     %
6418     luatexbase.add_to_callback('pre_linebreak_filter',
6419       Babel.pre_otfload_v,
6420       'Babel.pre_otfload_v',
6421     luatexbase.priority_in_callback('pre_linebreak_filter',
6422       'luaotfload.node_processor') or nil)
6423     %
6424     luatexbase.add_to_callback('hpack_filter',
6425       Babel.pre_otfload_h,
6426       'Babel.pre_otfload_h',
6427     luatexbase.priority_in_callback('hpack_filter',
6428       'luaotfload.node_processor') or nil)
6429   }}
```

The basic setup. The output is modified at a very low level to set the \bodydir to the \pagedir. Sadly, we have to deal with boxes in math with basic, so the \bbl@mathboxdir hack is activated every math with the package option bidi=.

```
6430 \breakafterdirmode=1
6431 \ifnum\bbl@bidimode>\@ne % Any bidi= except default=1
6432   \let\bbl@beforeforeign\leavevmode
6433   \AtEndOfPackage{\EnableBabelHook{babel-bidi}}
6434   \RequirePackage{luatexbase}
6435   \bbl@activate@preotf
6436   \directlua{
6437     require('babel-data-bidi.lua')
6438     \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
```

```

6439     require('babel-bidi-basic.lua')
6440   \or
6441     require('babel-bidi-basic-r.lua')
6442   \fi}
6443 \newattribute\bbbl@attr@dir
6444 \directlua{ Babel.attr_dir = luatexbase.registernumber'bbbl@attr@dir' }
6445 \bbbl@exp{\output{\bodydir\pagedir\the\output}}
6446 \fi
6447 \chardef\bbbl@thetextdir\z@
6448 \chardef\bbbl@thepardir\z@
6449 \def\bbbl@getluadir#1{%
6450   \directlua{
6451     if tex.#lmdir == 'TLT' then
6452       tex.sprint('0')
6453     elseif tex.#lmdir == 'TRT' then
6454       tex.sprint('1')
6455     end}}
6456 \def\bbbl@setluadir#1#2#3{% 1=text/par.. 2=\textdir.. 3=0 lr/1 rl
6457   \ifcase#3\relax
6458     \ifcase\bbbl@getluadir{#1}\relax\else
6459       #2 TLT\relax
6460     \fi
6461   \else
6462     \ifcase\bbbl@getluadir{#1}\relax
6463       #2 TRT\relax
6464     \fi
6465   \fi}
6466 % ..00PPTT, with masks 0xC (par dir) and 0x3 (text dir)
6467 \def\bbbl@thedir{0}
6468 \def\bbbl@textdir#1{%
6469   \bbbl@setluadir{text}\textdir{#1}%
6470   \chardef\bbbl@thetextdir#1\relax
6471   \edef\bbbl@thedir{\the\numexpr\bbbl@thepardir*4+#1}%
6472   \setattribute\bbbl@attr@dir{\numexpr\bbbl@thepardir*4+#1}}
6473 \def\bbbl@pardir#1{% Used twice
6474   \bbbl@setluadir{par}\pardir{#1}%
6475   \chardef\bbbl@thepardir#1\relax}
6476 \def\bbbl@bodydir{\bbbl@setluadir{body}\bodydir}% Used once
6477 \def\bbbl@pagedir{\bbbl@setluadir{page}\pagedir}% Unused
6478 \def\bbbl@dirparastext{\pardir\the\textdir\relax}% Used once

```

RTL text inside math needs special attention. It affects not only to actual math stuff, but also to ‘tabular’, which is based on a fake math.

```

6479 \ifnum\bbbl@bidimode>\z@ % Any bidi=
6480   \def\bbbl@insidemath{0}%
6481   \def\bbbl@everymath{\def\bbbl@insidemath{1}}
6482   \def\bbbl@everydisplay{\def\bbbl@insidemath{2}}
6483   \frozen@everymath\expandafter{%
6484     \expandafter\bbbl@everymath\the\frozen@everymath}
6485   \frozen@everydisplay\expandafter{%
6486     \expandafter\bbbl@everydisplay\the\frozen@everydisplay}
6487   \AtBeginDocument{
6488     \directlua{
6489       function Babel.math_box_dir(head)
6490         if not (token.get_macro('bbbl@insidemath') == '0') then
6491           if Babel.hlist_has_bidi(head) then
6492             local d = node.new(node.id'dir')
6493             d.dir = '+TRT'
6494             node.insert_before(head, node.has_glyph(head), d)
6495             local inmath = false
6496             for item in node.traverse(head) do
6497               if item.id == 11 then
6498                 inmath = (item.subtype == 0)

```

```

6499         elseif not inmath then
6500             node.set_attribute(item,
6501                 Babel.attr_dir, token.get_macro('bbl@thedir'))
6502         end
6503     end
6504 end
6505 end
6506 return head
6507 end
6508 luatexbase.add_to_callback("hpack_filter", Babel.math_box_dir,
6509     "Babel.math_box_dir", 0)
6510 }}%
6511 \fi

```

Experimental. Tentative name.

```

6512 \DeclareRobustCommand\localebox[1]{%
6513     {\def\bbl@insidemath{0}%
6514         \mbox{\foreignlanguage{\language}\{#1\}}}}

```

10.10 Layout

Unlike xetex, luatex requires only minimal changes for right-to-left layouts, particularly in monolingual documents (the engine itself reverses boxes – including column order or headings –, margins, etc.) with `bidibasic`, without having to patch almost any macro where text direction is relevant.

Still, there are three areas deserving special attention, namely, tabular, math, and graphics, text and intrinsically left-to-right elements are intermingled. I've made some progress in graphics, but they're essentially hacks; I've also made some progress in 'tabular', but when I decided to tackle math (both standard math and 'amsmath') the nightmare began. I'm still not sure how 'amsmath' should be modified, but the main problem is that, boxes are "generic" containers that can hold text, math, and graphics (even at the same time; remember that inline math is included in the list of text nodes marked with 'math' (11) nodes too).

`\@hangfrom` is useful in many contexts and it is redefined always with the layout option.

There are, however, a number of issues when the text direction is not the same as the box direction (as set by `\bodydir`), and when `\parbox` and `\hangindent` are involved. Fortunately, latest releases of luatex simplify a lot the solution with `\shapemode`.

With the issue #15 I realized commands are best patched, instead of redefined. With a few lines, a modification could be applied to several classes and packages. Now, `tabular` seems to work (at least in simple cases) with `array`, `tabularx`, `hhline`, `colortbl`, `longtable`, `booktabs`, etc. However, `dcolum` still fails.

```

6515 \bbl@trace{Redefinitions for bidi layout}
6516 %
6517 <<(*More package options)>> ≡
6518 \chardef\bbl@eqnpos\z@
6519 \DeclareOption{leqno}{\chardef\bbl@eqnpos\@ne}
6520 \DeclareOption{fleqn}{\chardef\bbl@eqnpos\tw@}
6521 <</More package options>>
6522 %
6523 \ifnum\bbl@bidimode>\z@ % Any bidi=
6524     \matheqdirmode\@ne % A luatex primitive
6525     \let\bbl@eqnodir\relax
6526     \def\bbl@eqdel{()}
6527     \def\bbl@eqnum{%
6528         {\normalfont\normalcolor
6529             \expandafter\@firstoftwo\bbl@eqdel
6530             \theequation
6531             \expandafter\@secondoftwo\bbl@eqdel}}
6532     \def\bbl@puteqno#1{\eqno\hbox{#1}}
6533     \def\bbl@putleqno#1{\leqno\hbox{#1}}
6534     \def\bbl@eqno@flip#1{%
6535         \ifdim\predisplaysize=-\maxdimen
6536             \eqno
6537             \hb@xt@.01pt{%

```

```

6538     \hb@xt@{\displaywidth{\hss{#1\glet\bb@upset\@currentlabel}}\hss}%
6539 \else
6540   \leqno\hbox{#1\glet\bb@upset\@currentlabel}%
6541 \fi
6542   \bb@exp{\def\\@currentlabel{[\bb@upset]}}
6543 \def\bb@leqno@flip#1{%
6544   \ifdim\predisplaysize=-\maxdimen
6545     \leqno
6546     \hb@xt@.01pt{%
6547       \hss\hb@xt@{\displaywidth{\#1\glet\bb@upset\@currentlabel}\hss}}%
6548 \else
6549   \eqno\hbox{#1\glet\bb@upset\@currentlabel}%
6550 \fi
6551   \bb@exp{\def\\@currentlabel{[\bb@upset]}}
6552 \AtBeginDocument{%
6553   \ifx\bb@noamsmath\relax\else
6554     \ifx\maketag@@@undefined % Normal equation, eqnarray
6555       \AddToHook{env/equation/begin}{%
6556         \ifnum\bb@thetextdir>\z@
6557           \def\bb@mathboxdir{\def\bb@insidemath{1}}%
6558           \let\@eqnnum\bb@eqnum
6559           \edef\bb@eqnodir{\noexpand\bb@textdir{\the\bb@thetextdir}}%
6560           \chardef\bb@thetextdir\z@
6561           \bb@add\normalfont{\bb@eqnodir}%
6562           \ifcase\bb@eqnpos
6563             \let\bb@puteqno\bb@eqno@flip
6564           \or
6565             \let\bb@puteqno\bb@leqno@flip
6566           \fi
6567         \fi}%
6568       \ifnum\bb@eqnpos=\tw@\else
6569         \def\endequation{\bb@puteqno{\@eqnnum}$$\@ignoretrue}%
6570       \fi
6571       \AddToHook{env/eqnarray/begin}{%
6572         \ifnum\bb@thetextdir>\z@
6573           \def\bb@mathboxdir{\def\bb@insidemath{1}}%
6574           \edef\bb@eqnodir{\noexpand\bb@textdir{\the\bb@thetextdir}}%
6575           \chardef\bb@thetextdir\z@
6576           \bb@add\normalfont{\bb@eqnodir}%
6577           \ifnum\bb@eqnpos=\@ne
6578             \def\@eqnnum{%
6579               \setbox\z@\hbox{\bb@eqnum}%
6580               \hbox to0.01pt{\hss\hbox to\displaywidth{\box\z@\hss}}}%
6581           \else
6582             \let\@eqnnum\bb@eqnum
6583           \fi
6584         \fi}
6585       % Hack. YA luatex bug?:
6586       \expandafter\bb@sreplace\csname] \endcsname{${$}\eqno\kern.001pt$}%
6587     \else % amstex
6588       \bb@exp{% Hack to hide maybe undefined conditionals:
6589         \chardef\bb@eqnpos=0%
6590         \<iftagsleft@>1\<else>\<if@fleqn>2\<fi>\<fi>\relax}%
6591       \ifnum\bb@eqnpos=\@ne
6592         \let\bb@ams@lap\hbox
6593       \else
6594         \let\bb@ams@lap\llap
6595       \fi
6596       \ExplSyntaxOn % Required by \bb@sreplace with \intertext@
6597       \bb@sreplace\intertext@{\normalbaselines}%
6598       {\normalbaselines
6599       \ifx\bb@eqnodir\relax\else\bb@pardir\@ne\bb@eqnodir\fi}%
6600       \ExplSyntaxOff

```

```

6601 \def\bb@ams@tagbox#1#2{#1{\bb@eqnudir#2}}% #1=hbox|@lap|flip
6602 \ifx\bb@ams@lap\hbox % leqno
6603 \def\bb@ams@flip#1{%
6604 \hbox to 0.01pt{\hss\hbox to\displaywidth{#1}\hss}}%
6605 \else % eqno
6606 \def\bb@ams@flip#1{%
6607 \hbox to 0.01pt{\hbox to\displaywidth{\hss{#1}\hss}}%
6608 \fi
6609 \def\bb@ams@preset#1{%
6610 \def\bb@mathboxdir{\def\bb@insidemath{1}}%
6611 \ifnum\bb@thetextdir>\z@
6612 \edef\bb@eqnudir{\noexpand\bb@textdir{\the\bb@thetextdir}}%
6613 \bb@replace\textdef@{\hbox}{\bb@ams@tagbox\hbox}%
6614 \bb@replace\maketag@@@{\hbox}{\bb@ams@tagbox#1}%
6615 \fi}%
6616 \ifnum\bb@eqnpos=\tw@ \else
6617 \def\bb@ams@equation{%
6618 \def\bb@mathboxdir{\def\bb@insidemath{1}}%
6619 \ifnum\bb@thetextdir>\z@
6620 \edef\bb@eqnudir{\noexpand\bb@textdir{\the\bb@thetextdir}}%
6621 \chardef\bb@thetextdir\z@
6622 \bb@add\normalfont{\bb@eqnudir}%
6623 \ifcase\bb@eqnpos
6624 \def\veqno##1##2{\bb@eqno@flip{##1##2}}%
6625 \or
6626 \def\veqno##1##2{\bb@leqno@flip{##1##2}}%
6627 \fi
6628 \fi}%
6629 \AddToHook{env/equation/begin}{\bb@ams@equation}%
6630 \AddToHook{env/equation*/begin}{\bb@ams@equation}%
6631 \fi
6632 \AddToHook{env/cases/begin}{\bb@ams@preset\bb@ams@lap}%
6633 \AddToHook{env/multline/begin}{\bb@ams@preset\hbox}%
6634 \AddToHook{env/gather/begin}{\bb@ams@preset\bb@ams@lap}%
6635 \AddToHook{env/gather*/begin}{\bb@ams@preset\bb@ams@lap}%
6636 \AddToHook{env/align/begin}{\bb@ams@preset\bb@ams@lap}%
6637 \AddToHook{env/align*/begin}{\bb@ams@preset\bb@ams@lap}%
6638 \AddToHook{env/alignat/begin}{\bb@ams@preset\bb@ams@lap}%
6639 \AddToHook{env/alignat*/begin}{\bb@ams@preset\bb@ams@lap}%
6640 \AddToHook{env/eqnalign/begin}{\bb@ams@preset\hbox}%
6641 % Hackish, for proper alignment. Don't ask me why it works!:
6642 \bb@exp{% Avoid a 'visible' conditional
6643 \\\AddToHook{env/align*/end}{\<iftag>\<else>\\tag*{\<fi>}}%
6644 \\\AddToHook{env/alignat*/end}{\<iftag>\<else>\\tag*{\<fi>}}%
6645 \AddToHook{env/flalign/begin}{\bb@ams@preset\hbox}%
6646 \AddToHook{env/split/before}{%
6647 \def\bb@mathboxdir{\def\bb@insidemath{1}}%
6648 \ifnum\bb@thetextdir>\z@
6649 \bb@ifsamestring@currentenv{equation}%
6650 {\ifx\bb@ams@lap\hbox % leqno
6651 \def\bb@ams@flip#1{%
6652 \hbox to 0.01pt{\hbox to\displaywidth{#1}\hss}\hss}%
6653 \else
6654 \def\bb@ams@flip#1{%
6655 \hbox to 0.01pt{\hss\hbox to\displaywidth{\hss{#1}}}%
6656 \fi}%
6657 }%
6658 \fi}%
6659 \fi\fi}
6660 \fi
6661 \def\bb@provide@extra#1{%
6662 % == Counters: mapdigits ==
6663 % Native digits

```

```

6664 \ifx\bbI@KVP@mapdigits\@nnil\else
6665   \bbI@ifunset{\bbI@dgnat@{language\name}}{%
6666     {\RequirePackage{luatexbase}}%
6667     \bbI@activate@preotf
6668     \directlua{
6669       Babel = Babel or {} %%% -> presets in luababel
6670       Babel.digits_mapped = true
6671       Babel.digits = Babel.digits or {}
6672       Babel.digits[\the\localeid] =
6673         table.pack(string.utfvalue('\bbI@cl{dgnat}'))
6674       if not Babel.numbers then
6675         function Babel.numbers(head)
6676           local LOCALE = Babel.attr_locale
6677           local GLYPH = node.id'glyph'
6678           local inmath = false
6679           for item in node.traverse(head) do
6680             if not inmath and item.id == GLYPH then
6681               local temp = node.get_attribute(item, LOCALE)
6682               if Babel.digits[temp] then
6683                 local chr = item.char
6684                 if chr > 47 and chr < 58 then
6685                   item.char = Babel.digits[temp][chr-47]
6686                 end
6687               end
6688             elseif item.id == node.id'math' then
6689               inmath = (item.subtype == 0)
6690             end
6691           end
6692           return head
6693         end
6694       end
6695     }%%
6696   \fi
6697   % == transforms ==
6698   \ifx\bbI@KVP@transforms\@nnil\else
6699     \def\bbI@elt##1##2##3{%
6700       \in@{${transforms.}}{##1}%
6701       \ifin@
6702         \def\bbI@tempa{##1}%
6703         \bbI@replace\bbI@tempa{transforms.}{}%
6704         \bbI@carg\bbI@transforms{babel\bbI@tempa}{##2}{##3}%
6705       \fi}%
6706     \csname bbl@inidata@{language\name}\endcsname
6707     \bbI@release@transforms\relax % \relax closes the last item.
6708   \fi}
6709 % Start tabular here:
6710 \def\localerestoredirs{%
6711   \ifcase\bbI@thetextdir
6712     \ifnum\textdirection=\z@ \else \textdir TLT \fi
6713   \else
6714     \ifnum\textdirection=\@ne \else \textdir TRT \fi
6715   \fi
6716   \ifcase\bbI@thepardir
6717     \ifnum\pardirection=\z@ \else \pardir TLT \bodydir TLT \fi
6718   \else
6719     \ifnum\pardirection=\@ne \else \pardir TRT \bodydir TRT \fi
6720   \fi}
6721 \IfBabelLayout{tabular}%
6722   {\chardef\bbI@tabular@mode\tw@}% All RTL
6723   {\IfBabelLayout{notabular}%
6724     {\chardef\bbI@tabular@mode\z@}%
6725     {\chardef\bbI@tabular@mode\@ne}}% Mixed, with LTR cols
6726 \ifnum\bbI@bidimode>\@ne % Any lua bidi= except default=1

```



```

6727 \ifcase\bb@tabular@mode\or % 1
6728   \let\bb@parabefore\relax
6729   \AddToHook{para/before}{\bb@parabefore}
6730   \AtBeginDocument{%
6731     \bb@replace\@tabular{$}{$%
6732       \def\bb@insidemath{0}%
6733       \def\bb@parabefore{\localerestoredirs}}%
6734     \ifnum\bb@tabular@mode=\@ne
6735       \bb@ifunset{\@tabclassz}{\{%
6736         \bb@exp{% Hide conditionals
6737           \\\bb@sreplace\\ \@tabclassz
6738             {\<ifcase>\\ \@chnum}%
6739             {\\\localerestoredirs\<ifcase>\\ \@chnum}}}%
6740         \@ifpackageloaded{colortbl}%
6741           {\bb@sreplace\@classz
6742             {\hbox\bgroup\bgroup}{\hbox\bgroup\bgroup\localerestoredirs}}%
6743           {\@ifpackageloaded{array}%
6744             {\bb@exp{% Hide conditionals
6745               \\\bb@sreplace\\ \@classz
6746                 {\<ifcase>\\ \@chnum}%
6747                 {\bgroup\\ \localerestoredirs\<ifcase>\\ \@chnum}%
6748                 \\\bb@sreplace\\ \@classz
6749                 {\do@row@strut\<fi>}{\do@row@strut\<fi>\egroup}}}%
6750             {}}%
6751     \fi}%
6752 \or % 2
6753   \let\bb@parabefore\relax
6754   \AddToHook{para/before}{\bb@parabefore}%
6755   \AtBeginDocument{%
6756     \@ifpackageloaded{colortbl}%
6757       {\bb@replace\@tabular{$}{$%
6758         \def\bb@insidemath{0}%
6759         \def\bb@parabefore{\localerestoredirs}}%
6760       \bb@sreplace\@classz
6761       {\hbox\bgroup\bgroup}{\hbox\bgroup\bgroup\localerestoredirs}}%
6762     {}}%
6763 \fi

```

Very likely the `\output` routine must be patched in a quite general way to make sure the `\bodydir` is set to `\pagedir`. Note outside `\output` they can be different (and often are). For the moment, two *ad hoc* changes.

```

6764 \AtBeginDocument{%
6765   \@ifpackageloaded{multicol}%
6766     {\toks@ \expandafter{\multi@column@out}%
6767     \edef\multi@column@out{\bodydir\pagedir\the\toks@}}%
6768   {%
6769   \@ifpackageloaded{paracol}%
6770     {\edef\pcol@output{%
6771       \bodydir\pagedir\unexpanded\expandafter{\pcol@output}}}%
6772     {}}%
6773 \fi
6774 \ifx\bb@opt@layout\@nnil\endinput\fi % if no layout

```

OMEGA provided a companion to `\mathdir` (`\nextfakemath`) for those cases where we did not want it to be applied, so that the writing direction of the main text was left unchanged. `\bb@nextfake` is an attempt to emulate it, because `luatex` has removed it without an alternative. Also, `\hangindent` does not honour direction changes by default, so we need to redefine `\@hangfrom`.

```

6775 \ifnum\bb@bidimode>\z@ % Any bidi=
6776 \def\bb@nextfake#1{% non-local changes, use always inside a group!
6777   \bb@exp{%
6778     \def\\bb@insidemath{0}%
6779     \mathdir\the\bodydir
6780     #1% Once entered in math, set boxes to restore values
6781     \<ifmmode>%

```

```

6782 \everyvbox{%
6783 \the\everyvbox
6784 \bodydir\the\bodydir
6785 \mathdir\the\mathdir
6786 \everyhbox{\the\everyhbox}%
6787 \everyvbox{\the\everyvbox}}%
6788 \everyhbox{%
6789 \the\everyhbox
6790 \bodydir\the\bodydir
6791 \mathdir\the\mathdir
6792 \everyhbox{\the\everyhbox}%
6793 \everyvbox{\the\everyvbox}}%
6794 \<fi>}}%
6795 \def\@hangfrom#1{%
6796 \setbox\@tempboxa\hbox{#{#1}}%
6797 \hangindent\wd\@tempboxa
6798 \ifnum\bb@getluadir{page}=\bb@getluadir{par}\else
6799 \shapemode\@ne
6800 \fi
6801 \noindent\box\@tempboxa}
6802 \fi
6803 \IfBabelLayout{tabular}
6804 {\let\bb@OL@tabular\@tabular
6805 \bb@replace\@tabular{$}{\bb@nextfake$}%
6806 \let\bb@NL@tabular\@tabular
6807 \AtBeginDocument{%
6808 \ifx\bb@NL@tabular\@tabular\else
6809 \bb@exp{\in{\bb@nextfake}{\@tabular}}}%
6810 \ifin\else
6811 \bb@replace\@tabular{$}{\bb@nextfake$}%
6812 \fi
6813 \let\bb@NL@tabular\@tabular
6814 \fi}}
6815 {}
6816 \IfBabelLayout{lists}
6817 {\let\bb@OL@list\list
6818 \bb@sreplace\list{\parshape}{\bb@listparshape}%
6819 \let\bb@NL@list\list
6820 \def\bb@listparshape#1#2#3{%
6821 \parshape #1 #2 #3 %
6822 \ifnum\bb@getluadir{page}=\bb@getluadir{par}\else
6823 \shapemode\tw@
6824 \fi}}
6825 {}
6826 \IfBabelLayout{graphics}
6827 {\let\bb@pictresetdir\relax
6828 \def\bb@pictsetdir#1{%
6829 \ifcase\bb@thetextdir
6830 \let\bb@pictresetdir\relax
6831 \else
6832 \ifcase#1\bodydir TLT % Remember this sets the inner boxes
6833 \or\textdir TLT
6834 \else\bodydir TLT \textdir TLT
6835 \fi
6836 % \text\par)dir required in pgf:
6837 \def\bb@pictresetdir{\bodydir TRT\pardir TRT\textdir TRT\relax}%
6838 \fi}%
6839 \AddToHook{env/picture/begin}{\bb@pictsetdir\tw@}%
6840 \directlua{
6841 Babel.get_picture_dir = true
6842 Babel.picture_has_bidi = 0
6843 %
6844 function Babel.picture_dir (head)

```

```

6845     if not Babel.get_picture_dir then return head end
6846     if Babel.hlist_has_bidi(head) then
6847         Babel.picture_has_bidi = 1
6848     end
6849     return head
6850 end
6851 luatexbase.add_to_callback("hpack_filter", Babel.picture_dir,
6852     "Babel.picture_dir")
6853 }%
6854 \AtBeginDocument{%
6855     \def\LS@rot{%
6856         \setbox\@outputbox\vbox{%
6857             \hbox dir TLT{\rotatebox{90}{\box\@outputbox}}}%
6858     \long\def\put(#1,#2)#3{%
6859         \@killglove
6860         % Try:
6861         \ifx\bbbl@pictresetdir\relax
6862             \def\bbbl@tempc{0}%
6863         \else
6864             \directlua{
6865                 Babel.get_picture_dir = true
6866                 Babel.picture_has_bidi = 0
6867             }%
6868             \setbox\z@\hb@xt@\z@{%
6869                 \@defaultunitsset\@tempdimc{#1}\unitlength
6870                 \kern\@tempdimc
6871                 #3\hss}% TODO: #3 executed twice (below). That's bad.
6872             \edef\bbbl@tempc{\directlua{tex.print(Babel.picture_has_bidi)}}%
6873         \fi
6874         % Do:
6875         \@defaultunitsset\@tempdimc{#2}\unitlength
6876         \raise\@tempdimc\hb@xt@\z@{%
6877             \@defaultunitsset\@tempdimc{#1}\unitlength
6878             \kern\@tempdimc
6879             {\ifnum\bbbl@tempc>\z@\bbbl@pictresetdir\fi#3}\hss}%
6880         \ignorespaces}%
6881     \MakeRobust\put}%
6882 \AtBeginDocument
6883 {\AddToHook{cmd/diagbox@pict/before}{\let\bbbl@pictsetdir\@gobble}%
6884 \ifx\pgfpicture\undefined\else % TODO. Allow deactivate?
6885     \AddToHook{env/pgfpicture/begin}{\bbbl@pictsetdir\@ne}%
6886     \bbbl@add\pgfinterruptpicture{\bbbl@pictresetdir}%
6887     \bbbl@add\pgfsys@beginpicture{\bbbl@pictsetdir\z@}%
6888 \fi
6889 \ifx\tikzpicture\undefined\else
6890     \AddToHook{env/tikzpicture/begin}{\bbbl@pictsetdir\tw}%
6891     \bbbl@add\tikz@atbegin@node{\bbbl@pictresetdir}%
6892     \bbbl@sreplace\tikz{\begingroup}{\begingroup\bbbl@pictsetdir\tw}%
6893 \fi
6894 \ifx\tcolorbox\undefined\else
6895     \def\tcb@drawing@env@begin{%
6896         \csname tcb@before\tcb@split@state\endcsname
6897         \bbbl@pictsetdir\tw@
6898         \begin{\kvtcb@graphenv}%
6899         \tcb@bbdraw
6900         \tcb@apply@graph@patches}%
6901     \def\tcb@drawing@env@end{%
6902         \end{\kvtcb@graphenv}%
6903         \bbbl@pictresetdir
6904         \csname tcb@after\tcb@split@state\endcsname}%
6905 \fi
6906 }}
6907 {}

```

Implicitly reverses sectioning labels in bidi=basic-r, because the full stop is not in contact with L numbers any more. I think there must be a better way. Assumes bidi=basic, but there are some additional readjustments for bidi=default.

```

6908 \IfBabelLayout{counters*}%
6909   {\bbl@add\bbl@opt@layout{.counters.}%
6910    \directlua{
6911      luatexbase.add_to_callback("process_output_buffer",
6912        Babel.discard_sublr , "Babel.discard_sublr") }%
6913   }}
6914 \IfBabelLayout{counters}%
6915   {\let\bbl@OL@@@textsuperscript\@textsuperscript
6916    \bbl@sreplace\@textsuperscript{\m@th}{\m@th\mathdir\pagedir}%
6917    \let\bbl@latin@arabic=\@arabic
6918    \let\bbl@OL@@@arabic\@arabic
6919    \def\@arabic#1{\babelsublr{\bbl@latin@arabic#1}}%
6920    \@ifpackagewith{babel}{bidi=default}%
6921    {\let\bbl@asci@roman=\@roman
6922     \let\bbl@OL@@@roman\@roman
6923     \def\@roman#1{\babelsublr{\ensureascii{\bbl@asci@roman#1}}}%
6924     \let\bbl@asci@Roman=\@Roman
6925     \let\bbl@OL@@@roman\@Roman
6926     \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asci@Roman#1}}}%
6927     \let\bbl@OL@labelenumii\labelenumii
6928     \def\labelenumii{}\theenumii}%
6929     \let\bbl@OL@p@enumiii\p@enumiii
6930     \def\p@enumiii{\p@enumii}\theenumii{}\}}{}
6931 <<Footnote changes>>
6932 \IfBabelLayout{footnotes}%
6933   {\let\bbl@OL@footnote\footnote
6934    \BabelFootnote\footnote\language\name{}}{}%
6935    \BabelFootnote\localfootnote\language\name{}}{}%
6936    \BabelFootnote\mainfootnote{}}{}{}
6937   {}

```

Some L^AT_EX macros use internally the math mode for text formatting. They have very little in common and are grouped here, as a single option.

```

6938 \IfBabelLayout{extras}%
6939   {\bbl@ncarg\let\bbl@OL@underline\underline }%
6940   \bbl@carg\bbl@sreplace{underline }%
6941   {\$@@underline}{\bgroup\bbl@nextfake$@@underline}%
6942   \bbl@carg\bbl@sreplace{underline }%
6943   {\m@th$}{\m@th$\egroup}%
6944   \let\bbl@OL@LaTeXe\LaTeXe
6945   \DeclareRobustCommand{\LaTeXe}{\mbox{\m@th
6946     \if b\expandafter\@car\@series\@nil\boldmath\fi
6947     \babelsublr{%
6948       \LaTeX\kern.15em2\bbl@nextfake$_{\textstyle\varepsilon}$}}}
6949   {}
6950 </luatex>

```

10.11 Lua: transforms

After declaring the table containing the patterns with their replacements, we define some auxiliary functions: `str_to_nodes` converts the string returned by a function to a node list, taking the node at base as a model (font, language, etc.); `fetch_word` fetches a series of glyphs and discretionary, which pattern is matched against (if there is a match, it is called again before trying other patterns, and this is very likely the main bottleneck).

`post_hyphenate_replace` is the callback applied after `lang.hyphenate`. This means the automatic hyphenation points are known. As empty captures return a byte position (as explained in the `luatex` manual), we must convert it to a utf8 position. With `first`, the last byte can be the leading byte in a utf8 sequence, so we just remove it and add 1 to the resulting length. With `last` we must take into account the capture position points to the next character. Here `word_head` points to the starting node of the text to be matched.

```

6951 (*transforms)
6952 Babel.linebreaking.replacements = {}
6953 Babel.linebreaking.replacements[0] = {} -- pre
6954 Babel.linebreaking.replacements[1] = {} -- post
6955
6956 -- Discretionaries contain strings as nodes
6957 function Babel.str_to_nodes(fn, matches, base)
6958   local n, head, last
6959   if fn == nil then return nil end
6960   for s in string.utfvalues(fn(matches)) do
6961     if base.id == 7 then
6962       base = base.replace
6963     end
6964     n = node.copy(base)
6965     n.char = s
6966     if not head then
6967       head = n
6968     else
6969       last.next = n
6970     end
6971     last = n
6972   end
6973   return head
6974 end
6975
6976 Babel.fetch_subtext = {}
6977
6978 Babel.ignore_pre_char = function(node)
6979   return (node.lang == Babel.nohyphenation)
6980 end
6981
6982 -- Merging both functions doesn't seem feasible, because there are too
6983 -- many differences.
6984 Babel.fetch_subtext[0] = function(head)
6985   local word_string = ''
6986   local word_nodes = {}
6987   local lang
6988   local item = head
6989   local inmath = false
6990
6991   while item do
6992
6993     if item.id == 11 then
6994       inmath = (item.subtype == 0)
6995     end
6996
6997     if inmath then
6998       -- pass
6999
7000     elseif item.id == 29 then
7001       local locale = node.get_attribute(item, Babel.attr_locale)
7002
7003       if lang == locale or lang == nil then
7004         lang = lang or locale
7005         if Babel.ignore_pre_char(item) then
7006           word_string = word_string .. Babel.us_char
7007         else
7008           word_string = word_string .. unicode.utf8.char(item.char)
7009         end
7010         word_nodes[#word_nodes+1] = item
7011       else
7012         break
7013       end

```

```

7014
7015     elseif item.id == 12 and item.subtype == 13 then
7016         word_string = word_string .. ' '
7017         word_nodes[#word_nodes+1] = item
7018
7019         -- Ignore leading unrecognized nodes, too.
7020     elseif word_string ~= '' then
7021         word_string = word_string .. Babel.us_char
7022         word_nodes[#word_nodes+1] = item -- Will be ignored
7023     end
7024
7025     item = item.next
7026 end
7027
7028 -- Here and above we remove some trailing chars but not the
7029 -- corresponding nodes. But they aren't accessed.
7030 if word_string:sub(-1) == ' ' then
7031     word_string = word_string:sub(1,-2)
7032 end
7033 word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
7034 return word_string, word_nodes, item, lang
7035 end
7036
7037 Babel.fetch_subtext[1] = function(head)
7038     local word_string = ''
7039     local word_nodes = {}
7040     local lang
7041     local item = head
7042     local inmath = false
7043
7044     while item do
7045
7046         if item.id == 11 then
7047             inmath = (item.subtype == 0)
7048         end
7049
7050         if inmath then
7051             -- pass
7052
7053         elseif item.id == 29 then
7054             if item.lang == lang or lang == nil then
7055                 if (item.char ~= 124) and (item.char ~= 61) then -- not =, not |
7056                     lang = lang or item.lang
7057                     word_string = word_string .. unicode.utf8.char(item.char)
7058                     word_nodes[#word_nodes+1] = item
7059                 end
7060             else
7061                 break
7062             end
7063
7064         elseif item.id == 7 and item.subtype == 2 then
7065             word_string = word_string .. '='
7066             word_nodes[#word_nodes+1] = item
7067
7068         elseif item.id == 7 and item.subtype == 3 then
7069             word_string = word_string .. '|'
7070             word_nodes[#word_nodes+1] = item
7071
7072         -- (1) Go to next word if nothing was found, and (2) implicitly
7073         -- remove leading USs.
7074         elseif word_string == '' then
7075             -- pass
7076

```

```

7077 -- This is the responsible for splitting by words.
7078 elseif (item.id == 12 and item.subtype == 13) then
7079     break
7080
7081 else
7082     word_string = word_string .. Babel.us_char
7083     word_nodes[#word_nodes+1] = item -- Will be ignored
7084 end
7085
7086 item = item.next
7087 end
7088
7089 word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
7090 return word_string, word_nodes, item, lang
7091 end
7092
7093 function Babel.pre_hyphenate_replace(head)
7094     Babel.hyphenate_replace(head, 0)
7095 end
7096
7097 function Babel.post_hyphenate_replace(head)
7098     Babel.hyphenate_replace(head, 1)
7099 end
7100
7101 Babel.us_char = string.char(31)
7102
7103 function Babel.hyphenate_replace(head, mode)
7104     local u = unicode.utf8
7105     local lbkr = Babel.linebreaking.replacements[mode]
7106
7107     local word_head = head
7108
7109     while true do -- for each subtext block
7110
7111         local w, w_nodes, nw, lang = Babel.fetch_subtext[mode](word_head)
7112
7113         if Babel.debug then
7114             print()
7115             print((mode == 0) and '@@@@<' or '@@@@>', w)
7116         end
7117
7118         if nw == nil and w == '' then break end
7119
7120         if not lang then goto next end
7121         if not lbkr[lang] then goto next end
7122
7123         -- For each saved (pre|post)hyphenation. TODO. Reconsider how
7124         -- loops are nested.
7125         for k=1, #lbkr[lang] do
7126             local p = lbkr[lang][k].pattern
7127             local r = lbkr[lang][k].replace
7128             local attr = lbkr[lang][k].attr or -1
7129
7130             if Babel.debug then
7131                 print('*****', p, mode)
7132             end
7133
7134             -- This variable is set in some cases below to the first *byte*
7135             -- after the match, either as found by u.match (faster) or the
7136             -- computed position based on sc if w has changed.
7137             local last_match = 0
7138             local step = 0
7139

```

```

7140 -- For every match.
7141 while true do
7142     if Babel.debug then
7143         print('====')
7144     end
7145     local new -- used when inserting and removing nodes
7146
7147     local matches = { u.match(w, p, last_match) }
7148
7149     if #matches < 2 then break end
7150
7151     -- Get and remove empty captures (with ())'s, which return a
7152     -- number with the position), and keep actual captures
7153     -- (from (...)), if any, in matches.
7154     local first = table.remove(matches, 1)
7155     local last = table.remove(matches, #matches)
7156     -- Non re-fetched substrings may contain \31, which separates
7157     -- subsubstrings.
7158     if string.find(w:sub(first, last-1), Babel.us_char) then break end
7159
7160     local save_last = last -- with A()BC()D, points to D
7161
7162     -- Fix offsets, from bytes to unicode. Explained above.
7163     first = u.len(w:sub(1, first-1)) + 1
7164     last = u.len(w:sub(1, last-1)) -- now last points to C
7165
7166     -- This loop stores in a small table the nodes
7167     -- corresponding to the pattern. Used by 'data' to provide a
7168     -- predictable behavior with 'insert' (w_nodes is modified on
7169     -- the fly), and also access to 'remove'd nodes.
7170     local sc = first-1 -- Used below, too
7171     local data_nodes = {}
7172
7173     local enabled = true
7174     for q = 1, last-first+1 do
7175         data_nodes[q] = w_nodes[sc+q]
7176         if enabled
7177             and attr > -1
7178             and not node.has_attribute(data_nodes[q], attr)
7179         then
7180             enabled = false
7181         end
7182     end
7183
7184     -- This loop traverses the matched substring and takes the
7185     -- corresponding action stored in the replacement list.
7186     -- sc = the position in substr nodes / string
7187     -- rc = the replacement table index
7188     local rc = 0
7189
7190     while rc < last-first+1 do -- for each replacement
7191         if Babel.debug then
7192             print('.....', rc + 1)
7193         end
7194         sc = sc + 1
7195         rc = rc + 1
7196
7197         if Babel.debug then
7198             Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
7199             local ss = ''
7200             for itt in node.traverse(head) do
7201                 if itt.id == 29 then
7202                     ss = ss .. unicode.utf8.char(itt.char)

```



```

7203         else
7204             ss = ss .. '{' .. itt.id .. '}'
7205         end
7206     end
7207     print('*****', ss)
7208
7209 end
7210
7211 local crep = r[rc]
7212 local item = w_nodes[sc]
7213 local item_base = item
7214 local placeholder = Babel.us_char
7215 local d
7216
7217 if crep and crep.data then
7218     item_base = data_nodes[crep.data]
7219 end
7220
7221 if crep then
7222     step = crep.step or 0
7223 end
7224
7225 if (not enabled) or (crep and next(crep) == nil) then -- = {}
7226     last_match = save_last    -- Optimization
7227     goto next
7228
7229 elseif crep == nil or crep.remove then
7230     node.remove(head, item)
7231     table.remove(w_nodes, sc)
7232     w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
7233     sc = sc - 1 -- Nothing has been inserted.
7234     last_match = utf8.offset(w, sc+1+step)
7235     goto next
7236
7237 elseif crep and crep.kashida then -- Experimental
7238     node.set_attribute(item,
7239         Babel.attr_kashida,
7240         crep.kashida)
7241     last_match = utf8.offset(w, sc+1+step)
7242     goto next
7243
7244 elseif crep and crep.string then
7245     local str = crep.string(matches)
7246     if str == '' then -- Gather with nil
7247         node.remove(head, item)
7248         table.remove(w_nodes, sc)
7249         w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
7250         sc = sc - 1 -- Nothing has been inserted.
7251     else
7252         local loop_first = true
7253         for s in string.utfvalues(str) do
7254             d = node.copy(item_base)
7255             d.char = s
7256             if loop_first then
7257                 loop_first = false
7258                 head, new = node.insert_before(head, item, d)
7259                 if sc == 1 then
7260                     word_head = head
7261                 end
7262                 w_nodes[sc] = d
7263                 w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc+1)
7264             else
7265                 sc = sc + 1

```

```

7266         head, new = node.insert_before(head, item, d)
7267         table.insert(w_nodes, sc, new)
7268         w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc)
7269     end
7270     if Babel.debug then
7271         print('.....', 'str')
7272         Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
7273     end
7274     end -- for
7275     node.remove(head, item)
7276 end -- if ''
7277 last_match = utf8.offset(w, sc+1+step)
7278 goto next
7279
7280 elseif mode == 1 and crep and (crep.pre or crep.no or crep.post) then
7281     d = node.new(7, 3) -- (disc, regular)
7282     d.pre = Babel.str_to_nodes(crep.pre, matches, item_base)
7283     d.post = Babel.str_to_nodes(crep.post, matches, item_base)
7284     d.replace = Babel.str_to_nodes(crep.no, matches, item_base)
7285     d.attr = item_base.attr
7286     if crep.pre == nil then -- TeXbook p96
7287         d.penalty = crep.penalty or tex.hyphenpenalty
7288     else
7289         d.penalty = crep.penalty or tex.exhyphenpenalty
7290     end
7291     placeholder = '|'
7292     head, new = node.insert_before(head, item, d)
7293
7294 elseif mode == 0 and crep and (crep.pre or crep.no or crep.post) then
7295     -- ERROR
7296
7297 elseif crep and crep.penalty then
7298     d = node.new(14, 0) -- (penalty, userpenalty)
7299     d.attr = item_base.attr
7300     d.penalty = crep.penalty
7301     head, new = node.insert_before(head, item, d)
7302
7303 elseif crep and crep.space then
7304     -- 655360 = 10 pt = 10 * 65536 sp
7305     d = node.new(12, 13) -- (glue, spaceskip)
7306     local quad = font.getfont(item_base.font).size or 655360
7307     node.setglue(d, crep.space[1] * quad,
7308                  crep.space[2] * quad,
7309                  crep.space[3] * quad)
7310     if mode == 0 then
7311         placeholder = ' '
7312     end
7313     head, new = node.insert_before(head, item, d)
7314
7315 elseif crep and crep.spacefactor then
7316     d = node.new(12, 13) -- (glue, spaceskip)
7317     local base_font = font.getfont(item_base.font)
7318     node.setglue(d,
7319                  crep.spacefactor[1] * base_font.parameters['space'],
7320                  crep.spacefactor[2] * base_font.parameters['space_stretch'],
7321                  crep.spacefactor[3] * base_font.parameters['space_shrink'])
7322     if mode == 0 then
7323         placeholder = ' '
7324     end
7325     head, new = node.insert_before(head, item, d)
7326
7327 elseif mode == 0 and crep and crep.space then
7328     -- ERROR

```

```

7329
7330     elseif crep and crep.kern then
7331         d = node.new(13, 1)      -- (kern, user)
7332         local quad = font.getfont(item_base.font).size or 655360
7333         d.attr = item_base.attr
7334         d.kern = crep.kern * quad
7335         head, new = node.insert_before(head, item, d)
7336
7337     elseif crep and crep.node then
7338         d = node.new(crep.node[1], crep.node[2])
7339         d.attr = item_base.attr
7340         head, new = node.insert_before(head, item, d)
7341
7342     end -- ie replacement cases
7343
7344     -- Shared by disc, space(factor), kern, node and penalty.
7345     if sc == 1 then
7346         word_head = head
7347     end
7348     if crep.insert then
7349         w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc)
7350         table.insert(w_nodes, sc, new)
7351         last = last + 1
7352     else
7353         w_nodes[sc] = d
7354         node.remove(head, item)
7355         w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc+1)
7356     end
7357
7358     last_match = utf8.offset(w, sc+1+step)
7359
7360     ::next::
7361
7362     end -- for each replacement
7363
7364     if Babel.debug then
7365         print('.....', '/')
7366         Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
7367     end
7368
7369     end -- for match
7370
7371     end -- for patterns
7372
7373     ::next::
7374     word_head = nw
7375     end -- for substring
7376     return head
7377 end
7378
7379 -- This table stores capture maps, numbered consecutively
7380 Babel.capture_maps = {}
7381
7382 -- The following functions belong to the next macro
7383 function Babel.capture_func(key, cap)
7384     local ret = "[" .. cap:gsub('{{([0-9])}}', "]]..m[%1]..[" .. "]"
7385     local cnt
7386     local u = unicode.utf8
7387     ret, cnt = ret:gsub('{{([0-9])|([^\]]+)|(.-)}}', Babel.capture_func_map)
7388     if cnt == 0 then
7389         ret = u.gsub(ret, '{(%%x%%x%%x+)}',
7390             function (n)
7391                 return u.char(tonumber(n, 16))
7392             end)
7393     end

```

```

7392         end)
7393     end
7394     ret = ret:gsub("%[%[%]%]%.%", '')
7395     ret = ret:gsub("%.%[%[%]%]", '')
7396     return key .. [[=function(m) return ]] .. ret .. [[ end]]
7397 end
7398
7399 function Babel.capt_map(from, mapno)
7400     return Babel.capture_maps[mapno][from] or from
7401 end
7402
7403 -- Handle the {n|abc|ABC} syntax in captures
7404 function Babel.capture_func_map(capno, from, to)
7405     local u = unicode.utf8
7406     from = u.gsub(from, '{(%x%x%x%x+)}',
7407         function (n)
7408             return u.char(tonumber(n, 16))
7409         end)
7410     to = u.gsub(to, '{(%x%x%x%x+)}',
7411         function (n)
7412             return u.char(tonumber(n, 16))
7413         end)
7414     local froms = {}
7415     for s in string.utfcharacters(from) do
7416         table.insert(froms, s)
7417     end
7418     local cnt = 1
7419     table.insert(Babel.capture_maps, {})
7420     local mlen = table.getn(Babel.capture_maps)
7421     for s in string.utfcharacters(to) do
7422         Babel.capture_maps[mlen][froms[cnt]] = s
7423         cnt = cnt + 1
7424     end
7425     return "]]..Babel.capt_map(m[" .. capno .. "], " ..
7426         (mlen) .. ").." .. "["
7427 end
7428
7429 -- Create/Extend reversed sorted list of kashida weights:
7430 function Babel.capture_kashida(key, wt)
7431     wt = tonumber(wt)
7432     if Babel.kashida_wts then
7433         for p, q in ipairs(Babel.kashida_wts) do
7434             if wt == q then
7435                 break
7436             elseif wt > q then
7437                 table.insert(Babel.kashida_wts, p, wt)
7438                 break
7439             elseif table.getn(Babel.kashida_wts) == p then
7440                 table.insert(Babel.kashida_wts, wt)
7441             end
7442         end
7443     else
7444         Babel.kashida_wts = { wt }
7445     end
7446     return 'kashida = ' .. wt
7447 end
7448
7449 function Babel.capture_node(id, subtype)
7450     local sbt = 0
7451     for k, v in pairs(node.subtypes(id)) do
7452         if v == subtype then sbt = k end
7453     end
7454     return 'node = {' .. node.id(id) .. ', ' .. sbt .. '}'

```

```

7455 end
7456
7457 -- Experimental: applies prehyphenation transforms to a string (letters
7458 -- and spaces).
7459 function Babel.string_prehyphenation(str, locale)
7460   local n, head, last, res
7461   head = node.new(8, 0) -- dummy (hack just to start)
7462   last = head
7463   for s in string.utfvalues(str) do
7464     if s == 20 then
7465       n = node.new(12, 0)
7466     else
7467       n = node.new(29, 0)
7468       n.char = s
7469     end
7470     node.set_attribute(n, Babel.attr_locale, locale)
7471     last.next = n
7472     last = n
7473   end
7474   head = Babel.hyphenate_replace(head, 0)
7475   res = ''
7476   for n in node.traverse(head) do
7477     if n.id == 12 then
7478       res = res .. ' '
7479     elseif n.id == 29 then
7480       res = res .. unicode.utf8.char(n.char)
7481     end
7482   end
7483   tex.print(res)
7484 end
7485 </transforms>

```

10.12 Lua: Auto bidi with basic and basic-r

The file `babel-data-bidi.lua` currently only contains data. It is a large and boring file and it is not shown here (see the generated file), but here is a sample:

```

[0x25]={d='et'},
[0x26]={d='on'},
[0x27]={d='on'},
[0x28]={d='on', m=0x29},
[0x29]={d='on', m=0x28},
[0x2A]={d='on'},
[0x2B]={d='es'},
[0x2C]={d='cs'},

```

For the meaning of these codes, see the Unicode standard.

Now the `basic-r` bidi mode. One of the aims is to implement a fast and simple bidi algorithm, with a single loop. I managed to do it for R texts, with a second smaller loop for a special case. The code is still somewhat chaotic, but its behavior is essentially correct. I cannot resist copying the following text from Emacs `bidi.c` (which also attempts to implement the bidi algorithm with a single loop):

Arrrgh!! The UAX#9 algorithm is too deeply entrenched in the assumption of batch-style processing [...]. May the fleas of a thousand camels infest the armpits of those who design supposedly general-purpose algorithms by looking at their own implementations, and fail to consider other possible implementations!

Well, it took me some time to guess what the batch rules in UAX#9 actually mean (in other word, *what* they do and *why*, and not only *how*), but I think (or I hope) I've managed to understand them. In some sense, there are two bidi modes, one for numbers, and the other for text. Furthermore, setting just the direction in R text is not enough, because there are actually *two* R modes (set explicitly in Unicode with RLM and ALM). In `babel` the `dir` is set by a higher protocol based on the `language/script`, which in turn sets the correct `dir` (`<l>`, `<r>` or `<al>`).

From UAX#9: “Where available, markup should be used instead of the explicit formatting characters”. So, this simple version just ignores formatting characters. Actually, most of that annex is devoted to how to handle them.

BD14-BD16 are not implemented. Unicode (and the W3C) are making a great effort to deal with some special problematic cases in “streamed” plain text. I don’t think this is the way to go – particular issues should be fixed by a high level interface taking into account the needs of the document. And here is where luatex excels, because everything related to bidi writing is under our control.

```

7486 (*basic-r)
7487 Babel = Babel or {}
7488
7489 Babel.bidi_enabled = true
7490
7491 require('babel-data-bidi.lua')
7492
7493 local characters = Babel.characters
7494 local ranges = Babel.ranges
7495
7496 local DIR = node.id("dir")
7497
7498 local function dir_mark(head, from, to, outer)
7499   dir = (outer == 'r') and 'TLT' or 'TRT' -- ie, reverse
7500   local d = node.new(DIR)
7501   d.dir = '+' .. dir
7502   node.insert_before(head, from, d)
7503   d = node.new(DIR)
7504   d.dir = '-' .. dir
7505   node.insert_after(head, to, d)
7506 end
7507
7508 function Babel.bidi(head, ispar)
7509   local first_n, last_n          -- first and last char with nums
7510   local last_es                  -- an auxiliary 'last' used with nums
7511   local first_d, last_d          -- first and last char in L/R block
7512   local dir, dir_real

```

Next also depends on script/lang (<al>/<r>). To be set by babel. tex.pardir is dangerous, could be (re)set but it should be changed only in vmode. There are two strong’s – strong = l/al/r and strong_lr = l/r (there must be a better way):

```

7513   local strong = ('TRT' == tex.pardir) and 'r' or 'l'
7514   local strong_lr = (strong == 'l') and 'l' or 'r'
7515   local outer = strong
7516
7517   local new_dir = false
7518   local first_dir = false
7519   local inmath = false
7520
7521   local last_lr
7522
7523   local type_n = ''
7524
7525   for item in node.traverse(head) do
7526
7527     -- three cases: glyph, dir, otherwise
7528     if item.id == node.id'glyph'
7529       or (item.id == 7 and item.subtype == 2) then
7530
7531       local itemchar
7532       if item.id == 7 and item.subtype == 2 then
7533         itemchar = item.replace.char
7534       else
7535         itemchar = item.char
7536       end
7537       local chardata = characters[itemchar]

```

```

7538     dir = chardata and chardata.d or nil
7539     if not dir then
7540         for nn, et in ipairs(ranges) do
7541             if itemchar < et[1] then
7542                 break
7543             elseif itemchar <= et[2] then
7544                 dir = et[3]
7545                 break
7546             end
7547         end
7548     end
7549     dir = dir or 'l'
7550     if inmath then dir = ('TRT' == tex.mathdir) and 'r' or 'l' end

```

Next is based on the assumption babel sets the language AND switches the script with its dir. We treat a language block as a separate Unicode sequence. The following piece of code is executed at the first glyph after a 'dir' node. We don't know the current language until then. This is not exactly true, as the math mode may insert explicit dirs in the node list, so, for the moment there is a hack by brute force (just above).

```

7551     if new_dir then
7552         attr_dir = 0
7553         for at in node.traverse(item.attr) do
7554             if at.number == Babel.attr_dir then
7555                 attr_dir = at.value & 0x3
7556             end
7557         end
7558         if attr_dir == 1 then
7559             strong = 'r'
7560         elseif attr_dir == 2 then
7561             strong = 'al'
7562         else
7563             strong = 'l'
7564         end
7565         strong_lr = (strong == 'l') and 'l' or 'r'
7566         outer = strong_lr
7567         new_dir = false
7568     end
7569
7570     if dir == 'nsm' then dir = strong end -- W1

```

Numbers. The dual <al>/<r> system for R is somewhat cumbersome.

```

7571     dir_real = dir -- We need dir_real to set strong below
7572     if dir == 'al' then dir = 'r' end -- W3

```

By W2, there are no <en> <et> <es> if strong == <al>, only <an>. Therefore, there are not <et en> nor <en et>, W5 can be ignored, and W6 applied:

```

7573     if strong == 'al' then
7574         if dir == 'en' then dir = 'an' end -- W2
7575         if dir == 'et' or dir == 'es' then dir = 'on' end -- W6
7576         strong_lr = 'r' -- W3
7577     end

```

Once finished the basic setup for glyphs, consider the two other cases: dir node and the rest.

```

7578     elseif item.id == node.id'dir' and not inmath then
7579         new_dir = true
7580         dir = nil
7581     elseif item.id == node.id'math' then
7582         inmath = (item.subtype == 0)
7583     else
7584         dir = nil -- Not a char
7585     end

```

Numbers in R mode. A sequence of <en>, <et>, <an>, <es> and <cs> is typeset (with some rules) in L mode. We store the starting and ending points, and only when anything different is found (including

nil, ie, a non-char), the textdir is set. This means you cannot insert, say, a whatsit, but this is what I would expect (with luacolor you may colorize some digits). Anyway, this behavior could be changed with a switch in the future. Note in the first branch only <an> is relevant if <al>.

```

7586     if dir == 'en' or dir == 'an' or dir == 'et' then
7587         if dir ~= 'et' then
7588             type_n = dir
7589         end
7590         first_n = first_n or item
7591         last_n = last_es or item
7592         last_es = nil
7593     elseif dir == 'es' and last_n then -- W3+W6
7594         last_es = item
7595     elseif dir == 'cs' then           -- it's right - do nothing
7596     elseif first_n then -- & if dir = any but en, et, an, es, cs, inc nil
7597         if strong_lr == 'r' and type_n ~= '' then
7598             dir_mark(head, first_n, last_n, 'r')
7599         elseif strong_lr == 'l' and first_d and type_n == 'an' then
7600             dir_mark(head, first_n, last_n, 'r')
7601             dir_mark(head, first_d, last_d, outer)
7602             first_d, last_d = nil, nil
7603         elseif strong_lr == 'l' and type_n ~= '' then
7604             last_d = last_n
7605         end
7606         type_n = ''
7607         first_n, last_n = nil, nil
7608     end

```

R text in L, or L text in R. Order of dir_ mark's are relevant: d goes outside n, and therefore it's emitted after. See dir_mark to understand why (but is the nesting actually necessary or is a flat dir structure enough?). Only L, R (and AL) chars are taken into account – everything else, including spaces, whatsits, etc., are ignored:

```

7609     if dir == 'l' or dir == 'r' then
7610         if dir ~= outer then
7611             first_d = first_d or item
7612             last_d = item
7613         elseif first_d and dir ~= strong_lr then
7614             dir_mark(head, first_d, last_d, outer)
7615             first_d, last_d = nil, nil
7616         end
7617     end

```

Mirroring. Each chunk of text in a certain language is considered a “closed” sequence. If <r on r> and <l on l>, it's clearly <r> and <l>, resptly, but with other combinations depends on outer. From all these, we select only those resolving <on> → <r>. At the beginning (when last_lr is nil) of an R text, they are mirrored directly.

TODO - numbers in R mode are processed. It doesn't hurt, but should not be done.

```

7618     if dir and not last_lr and dir ~= 'l' and outer == 'r' then
7619         item.char = characters[item.char] and
7620             characters[item.char].m or item.char
7621     elseif (dir or new_dir) and last_lr ~= item then
7622         local mir = outer .. strong_lr .. (dir or outer)
7623         if mir == 'rrr' or mir == 'lrr' or mir == 'rrl' or mir == 'rlr' then
7624             for ch in node.traverse(node.next(last_lr)) do
7625                 if ch == item then break end
7626                 if ch.id == node.id'glyph' and characters[ch.char] then
7627                     ch.char = characters[ch.char].m or ch.char
7628                 end
7629             end
7630         end
7631     end

```

Save some values for the next iteration. If the current node is 'dir', open a new sequence. Since dir could be changed, strong is set with its real value (dir_real).


```

7632     if dir == 'l' or dir == 'r' then
7633         last_lr = item
7634         strong = dir_real          -- Don't search back - best save now
7635         strong_lr = (strong == 'l') and 'l' or 'r'
7636     elseif new_dir then
7637         last_lr = nil
7638     end
7639 end

```

Mirror the last chars if they are no directed. And make sure any open block is closed, too.

```

7640 if last_lr and outer == 'r' then
7641     for ch in node.traverse_id(node.id('glyph', node.next(last_lr)) do
7642         if characters[ch.char] then
7643             ch.char = characters[ch.char].m or ch.char
7644         end
7645     end
7646 end
7647 if first_n then
7648     dir_mark(head, first_n, last_n, outer)
7649 end
7650 if first_d then
7651     dir_mark(head, first_d, last_d, outer)
7652 end

```

In boxes, the dir node could be added before the original head, so the actual head is the previous node.

```

7653 return node.prev(head) or head
7654 end
7655 </basic-r>

```

And here the Lua code for bidi=basic:

```

7656 (*basic)
7657 Babel = Babel or {}
7658
7659 -- eg, Babel.fontmap[1][<prefontid>]=<dirfontid>
7660
7661 Babel.fontmap = Babel.fontmap or {}
7662 Babel.fontmap[0] = {}          -- l
7663 Babel.fontmap[1] = {}          -- r
7664 Babel.fontmap[2] = {}          -- al/an
7665
7666 -- To cancel mirroring. Also OML, OMS, U?
7667 Babel.symbol_fonts = Babel.symbol_fonts or {}
7668 Babel.symbol_fonts[font.id('tenln')] = true
7669 Babel.symbol_fonts[font.id('tenlnw')] = true
7670 Babel.symbol_fonts[font.id('tencirc')] = true
7671 Babel.symbol_fonts[font.id('tencircw')] = true
7672
7673 Babel.bidi_enabled = true
7674 Babel.mirroring_enabled = true
7675
7676 require('babel-data-bidi.lua')
7677
7678 local characters = Babel.characters
7679 local ranges = Babel.ranges
7680
7681 local DIR = node.id('dir')
7682 local GLYPH = node.id('glyph')
7683
7684 local function insert_implicit(head, state, outer)
7685     local new_state = state
7686     if state.sim and state.eim and state.sim ~= state.eim then
7687         dir = ((outer == 'r') and 'TLT' or 'TRT') -- ie, reverse
7688         local d = node.new(DIR)

```

```

7689     d.dir = '+' .. dir
7690     node.insert_before(head, state.sim, d)
7691     local d = node.new(DIR)
7692     d.dir = '-' .. dir
7693     node.insert_after(head, state.eim, d)
7694 end
7695 new_state.sim, new_state.eim = nil, nil
7696 return head, new_state
7697 end
7698
7699 local function insert_numeric(head, state)
7700     local new
7701     local new_state = state
7702     if state.san and state.ean and state.san ~= state.ean then
7703         local d = node.new(DIR)
7704         d.dir = '+TLT'
7705         _, new = node.insert_before(head, state.san, d)
7706         if state.san == state.sim then state.sim = new end
7707         local d = node.new(DIR)
7708         d.dir = '-TLT'
7709         _, new = node.insert_after(head, state.ean, d)
7710         if state.ean == state.eim then state.eim = new end
7711     end
7712     new_state.san, new_state.ean = nil, nil
7713     return head, new_state
7714 end
7715
7716 local function glyph_not_symbol_font(node)
7717     if node.id == GLYPH then
7718         return not Babel.symbol_fonts[node.font]
7719     else
7720         return false
7721     end
7722 end
7723
7724 -- TODO - \hbox with an explicit dir can lead to wrong results
7725 -- <R \hbox dir TLT{<R>}> and <L \hbox dir TRT{<L>}>. A small attempt
7726 -- was s made to improve the situation, but the problem is the 3-dir
7727 -- model in babel/Unicode and the 2-dir model in LuaTeX don't fit
7728 -- well.
7729
7730 function Babel.bidi(head, ispar, hdir)
7731     local d -- d is used mainly for computations in a loop
7732     local prev_d = ''
7733     local new_d = false
7734
7735     local nodes = {}
7736     local outer_first = nil
7737     local inmath = false
7738
7739     local glue_d = nil
7740     local glue_i = nil
7741
7742     local has_en = false
7743     local first_et = nil
7744
7745     local has_hyperlink = false
7746
7747     local ATDIR = Babel.attr_dir
7748
7749     local save_outer
7750     local temp = node.get_attribute(head, ATDIR)
7751     if temp then

```

```

7752     temp = temp & 0x3
7753     save_outer = (temp == 0 and 'l') or
7754                 (temp == 1 and 'r') or
7755                 (temp == 2 and 'al')
7756 elseif ispar then      -- Or error? Shouldn't happen
7757     save_outer = ('TRT' == tex.pardir) and 'r' or 'l'
7758 else                  -- Or error? Shouldn't happen
7759     save_outer = ('TRT' == hdir) and 'r' or 'l'
7760 end
7761 -- when the callback is called, we are just _after_ the box,
7762 -- and the textdir is that of the surrounding text
7763 -- if not ispar and hdir ~= tex.textdir then
7764 --     save_outer = ('TRT' == hdir) and 'r' or 'l'
7765 -- end
7766 local outer = save_outer
7767 local last = outer
7768 -- 'al' is only taken into account in the first, current loop
7769 if save_outer == 'al' then save_outer = 'r' end
7770
7771 local fontmap = Babel.fontmap
7772
7773 for item in node.traverse(head) do
7774
7775     -- In what follows, #node is the last (previous) node, because the
7776     -- current one is not added until we start processing the neutrals.
7777
7778     -- three cases: glyph, dir, otherwise
7779     if glyph_not_symbol_font(item)
7780     or (item.id == 7 and item.subtype == 2) then
7781
7782         local d_font = nil
7783         local item_r
7784         if item.id == 7 and item.subtype == 2 then
7785             item_r = item.replace    -- automatic discs have just 1 glyph
7786         else
7787             item_r = item
7788         end
7789         local chardata = characters[item_r.char]
7790         d = chardata and chardata.d or nil
7791         if not d or d == 'nsm' then
7792             for nn, et in ipairs(ranges) do
7793                 if item_r.char < et[1] then
7794                     break
7795                 elseif item_r.char <= et[2] then
7796                     if not d then d = et[3]
7797                     elseif d == 'nsm' then d_font = et[3]
7798                     end
7799                     break
7800                 end
7801             end
7802         end
7803         d = d or 'l'
7804
7805         -- A short 'pause' in bidi for mapfont
7806         d_font = d_font or d
7807         d_font = (d_font == 'l' and 0) or
7808                 (d_font == 'nsm' and 0) or
7809                 (d_font == 'r' and 1) or
7810                 (d_font == 'al' and 2) or
7811                 (d_font == 'an' and 2) or nil
7812         if d_font and fontmap and fontmap[d_font][item_r.font] then
7813             item_r.font = fontmap[d_font][item_r.font]
7814         end

```

```

7815
7816     if new_d then
7817         table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})
7818     if inmath then
7819         attr_d = 0
7820     else
7821         attr_d = node.get_attribute(item, ATDIR)
7822         attr_d = attr_d & 0x3
7823     end
7824     if attr_d == 1 then
7825         outer_first = 'r'
7826         last = 'r'
7827     elseif attr_d == 2 then
7828         outer_first = 'r'
7829         last = 'al'
7830     else
7831         outer_first = 'l'
7832         last = 'l'
7833     end
7834     outer = last
7835     has_en = false
7836     first_et = nil
7837     new_d = false
7838 end
7839
7840 if glue_d then
7841     if (d == 'l' and 'l' or 'r') ~= glue_d then
7842         table.insert(nodes, {glue_i, 'on', nil})
7843     end
7844     glue_d = nil
7845     glue_i = nil
7846 end
7847
7848 elseif item.id == DIR then
7849     d = nil
7850
7851     if head ~= item then new_d = true end
7852
7853 elseif item.id == node.id'glue' and item.subtype == 13 then
7854     glue_d = d
7855     glue_i = item
7856     d = nil
7857
7858 elseif item.id == node.id'math' then
7859     inmath = (item.subtype == 0)
7860
7861 elseif item.id == 8 and item.subtype == 19 then
7862     has_hyperlink = true
7863
7864 else
7865     d = nil
7866 end
7867
7868 -- AL <= EN/ET/ES      -- W2 + W3 + W6
7869 if last == 'al' and d == 'en' then
7870     d = 'an'           -- W3
7871 elseif last == 'al' and (d == 'et' or d == 'es') then
7872     d = 'on'           -- W6
7873 end
7874
7875 -- EN + CS/ES + EN      -- W4
7876 if d == 'en' and #nodes >= 2 then
7877     if (nodes[#nodes][2] == 'es' or nodes[#nodes][2] == 'cs')

```

```

7878         and nodes[#nodes-1][2] == 'en' then
7879             nodes[#nodes][2] = 'en'
7880         end
7881     end
7882
7883     -- AN + CS + AN          -- W4 too, because uax9 mixes both cases
7884     if d == 'an' and #nodes >= 2 then
7885         if (nodes[#nodes][2] == 'cs')
7886             and nodes[#nodes-1][2] == 'an' then
7887             nodes[#nodes][2] = 'an'
7888         end
7889     end
7890
7891     -- ET/EN                  -- W5 + W7->l / W6->on
7892     if d == 'et' then
7893         first_et = first_et or (#nodes + 1)
7894     elseif d == 'en' then
7895         has_en = true
7896         first_et = first_et or (#nodes + 1)
7897     elseif first_et then      -- d may be nil here !
7898         if has_en then
7899             if last == 'l' then
7900                 temp = 'l'    -- W7
7901             else
7902                 temp = 'en'   -- W5
7903             end
7904         else
7905             temp = 'on'       -- W6
7906         end
7907         for e = first_et, #nodes do
7908             if glyph_not_symbol_font(nodes[e][1]) then nodes[e][2] = temp end
7909         end
7910         first_et = nil
7911         has_en = false
7912     end
7913
7914     -- Force mathdir in math if ON (currently works as expected only
7915     -- with 'l')
7916     if inmath and d == 'on' then
7917         d = ('TRT' == tex.mathdir) and 'r' or 'l'
7918     end
7919
7920     if d then
7921         if d == 'al' then
7922             d = 'r'
7923             last = 'al'
7924         elseif d == 'l' or d == 'r' then
7925             last = d
7926         end
7927         prev_d = d
7928         table.insert(nodes, {item, d, outer_first})
7929     end
7930
7931     outer_first = nil
7932
7933 end
7934
7935 -- TODO -- repeated here in case EN/ET is the last node. Find a
7936 -- better way of doing things:
7937 if first_et then      -- dir may be nil here !
7938     if has_en then
7939         if last == 'l' then
7940             temp = 'l'    -- W7

```

```

7941     else
7942         temp = 'en'    -- W5
7943     end
7944     else
7945         temp = 'on'    -- W6
7946     end
7947     for e = first_et, #nodes do
7948         if glyph_not_symbol_font(nodes[e][1]) then nodes[e][2] = temp end
7949     end
7950 end
7951
7952 -- dummy node, to close things
7953 table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})
7954
7955 ----- NEUTRAL -----
7956
7957 outer = save_outer
7958 last = outer
7959
7960 local first_on = nil
7961
7962 for q = 1, #nodes do
7963     local item
7964
7965     local outer_first = nodes[q][3]
7966     outer = outer_first or outer
7967     last = outer_first or last
7968
7969     local d = nodes[q][2]
7970     if d == 'an' or d == 'en' then d = 'r' end
7971     if d == 'cs' or d == 'et' or d == 'es' then d = 'on' end --- W6
7972
7973     if d == 'on' then
7974         first_on = first_on or q
7975     elseif first_on then
7976         if last == d then
7977             temp = d
7978         else
7979             temp = outer
7980         end
7981         for r = first_on, q - 1 do
7982             nodes[r][2] = temp
7983             item = nodes[r][1]    -- MIRRORING
7984             if Babel.mirroring_enabled and glyph_not_symbol_font(item)
7985                 and temp == 'r' and characters[item.char] then
7986                 local font_mode = ''
7987                 if item.font > 0 and font.fonts[item.font].properties then
7988                     font_mode = font.fonts[item.font].properties.mode
7989                 end
7990                 if font_mode ~= 'harf' and font_mode ~= 'plug' then
7991                     item.char = characters[item.char].m or item.char
7992                 end
7993             end
7994         end
7995         first_on = nil
7996     end
7997
7998     if d == 'r' or d == 'l' then last = d end
7999 end
8000
8001 ----- IMPLICIT, REORDER -----
8002
8003 outer = save_outer

```

```

8004 last = outer
8005
8006 local state = {}
8007 state.has_r = false
8008
8009 for q = 1, #nodes do
8010
8011     local item = nodes[q][1]
8012
8013     outer = nodes[q][3] or outer
8014
8015     local d = nodes[q][2]
8016
8017     if d == 'nsm' then d = last end          -- W1
8018     if d == 'en' then d = 'an' end
8019     local isdir = (d == 'r' or d == 'l')
8020
8021     if outer == 'l' and d == 'an' then
8022         state.san = state.san or item
8023         state.ean = item
8024     elseif state.san then
8025         head, state = insert_numeric(head, state)
8026     end
8027
8028     if outer == 'l' then
8029         if d == 'an' or d == 'r' then      -- im -> implicit
8030             if d == 'r' then state.has_r = true end
8031             state.sim = state.sim or item
8032             state.eim = item
8033         elseif d == 'l' and state.sim and state.has_r then
8034             head, state = insert_implicit(head, state, outer)
8035         elseif d == 'l' then
8036             state.sim, state.eim, state.has_r = nil, nil, false
8037         end
8038     else
8039         if d == 'an' or d == 'l' then
8040             if nodes[q][3] then -- nil except after an explicit dir
8041                 state.sim = item -- so we move sim 'inside' the group
8042             else
8043                 state.sim = state.sim or item
8044             end
8045             state.eim = item
8046         elseif d == 'r' and state.sim then
8047             head, state = insert_implicit(head, state, outer)
8048         elseif d == 'r' then
8049             state.sim, state.eim = nil, nil
8050         end
8051     end
8052
8053     if isdir then
8054         last = d          -- Don't search back - best save now
8055     elseif d == 'on' and state.san then
8056         state.san = state.san or item
8057         state.ean = item
8058     end
8059
8060 end
8061
8062 head = node.prev(head) or head
8063
8064 ----- FIX HYPERLINKS -----
8065
8066 if has_hyperlink then

```

```

8067     local flag, linking = 0, 0
8068     for item in node.traverse(head) do
8069         if item.id == DIR then
8070             if item.dir == '+TRT' or item.dir == '+TLT' then
8071                 flag = flag + 1
8072             elseif item.dir == '-TRT' or item.dir == '-TLT' then
8073                 flag = flag - 1
8074             end
8075         elseif item.id == 8 and item.subtype == 19 then
8076             linking = flag
8077         elseif item.id == 8 and item.subtype == 20 then
8078             if linking > 0 then
8079                 if item.prev.id == DIR and
8080                     (item.prev.dir == '-TRT' or item.prev.dir == '-TLT') then
8081                     d = node.new(DIR)
8082                     d.dir = item.prev.dir
8083                     node.remove(head, item.prev)
8084                     node.insert_after(head, item, d)
8085                 end
8086             end
8087             linking = 0
8088         end
8089     end
8090 end
8091
8092 return head
8093 end
8094 </basic>

```

11 Data for CJK

It is a boring file and it is not shown here (see the generated file), but here is a sample:

```

[0x0021]={c='ex'},
[0x0024]={c='pr'},
[0x0025]={c='po'},
[0x0028]={c='op'},
[0x0029]={c='cp'},
[0x002B]={c='pr'},

```

For the meaning of these codes, see the Unicode standard.

12 The ‘nil’ language

This ‘language’ does nothing, except setting the hyphenation patterns to nohyphenation.

For this language currently no special definitions are needed or available.

The macro \LdfInit takes care of preventing that this file is loaded more than once, checking the category code of the @ sign, etc.

```

8095 <nil>
8096 \ProvidesLanguage{nil}[\<date> v\<version>] Nil language]
8097 \LdfInit{nil}{datenil}

```

When this file is read as an option, i.e. by the \usepackage command, nil could be an ‘unknown’ language in which case we have to make it known.

```

8098 \ifx\l@nil\undefined
8099   \newlanguage\l@nil
8100   \@namedef{bbl@hyphendata@the\l@nil}{{}}% Remove warning
8101   \let\bbl@elt\relax
8102   \edef\bbl@languages{% Add it to the list of languages
8103     \bbl@languages\bbl@elt{nil}{the\l@nil}{{}}
8104 \fi

```


This macro is used to store the values of the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`.

```
8105 \providehyphenmins{\CurrentOption}{\m@ne\m@ne}
```

The next step consists of defining commands to switch to (and from) the ‘nil’ language.

```
\captionnil
```

```
\datenil 8106 \let\captionsnil\@empty
```

```
8107 \let\datenil\@empty
```

There is no locale file for this pseudo-language, so the corresponding fields are defined here.

```
8108 \def\bbl@inidata@nil{%
8109   \bbl@elt{identification}{tag.ini}{und}%
8110   \bbl@elt{identification}{load.level}{0}%
8111   \bbl@elt{identification}{charset}{utf8}%
8112   \bbl@elt{identification}{version}{1.0}%
8113   \bbl@elt{identification}{date}{2022-05-16}%
8114   \bbl@elt{identification}{name.local}{nil}%
8115   \bbl@elt{identification}{name.english}{nil}%
8116   \bbl@elt{identification}{name.babel}{nil}%
8117   \bbl@elt{identification}{tag.bcp47}{und}%
8118   \bbl@elt{identification}{language.tag.bcp47}{und}%
8119   \bbl@elt{identification}{tag.opentype}{dflt}%
8120   \bbl@elt{identification}{script.name}{Latin}%
8121   \bbl@elt{identification}{script.tag.bcp47}{Latn}%
8122   \bbl@elt{identification}{script.tag.opentype}{DFLT}%
8123   \bbl@elt{identification}{level}{1}%
8124   \bbl@elt{identification}{encodings}{}%
8125   \bbl@elt{identification}{derivate}{no}}
8126 \@namedef{bbl@tbc@nil}{und}
8127 \@namedef{bbl@lbc@nil}{und}
8128 \@namedef{bbl@casing@nil}{und} % TODO
8129 \@namedef{bbl@lotf@nil}{dflt}
8130 \@namedef{bbl@elname@nil}{nil}
8131 \@namedef{bbl@lname@nil}{nil}
8132 \@namedef{bbl@esname@nil}{Latin}
8133 \@namedef{bbl@sname@nil}{Latin}
8134 \@namedef{bbl@sbc@nil}{Latn}
8135 \@namedef{bbl@sotf@nil}{latn}
```

The macro `\ldf@finish` takes care of looking for a configuration file, setting the main language to be switched on at `\begin{document}` and resetting the category code of `@` to its original value.

```
8136 \ldf@finish{nil}
```

```
8137 \</nil>
```

13 Calendars

The code for specific calendars are placed in the specific files, loaded when requested by an ini file in the identification section with `require.calendars`.

Start with function to compute the Julian day. It's based on the little library `calendar.js`, by John Walker, in the public domain.

```
8138 <<*Compute Julian day>> ≡
8139 \def\bbl@fpmo#1#2{(#1-#2*floor(#1/#2))}
8140 \def\bbl@cs@gregleap#1{%
8141   (\bbl@fpmo{#1}{4} == 0) &&
8142   (!( \bbl@fpmo{#1}{100} == 0) && (\bbl@fpmo{#1}{400} != 0) )}
8143 \def\bbl@cs@jd#1#2#3{% year, month, day
8144   \fp_eval:n{ 1721424.5 + (365 * (#1 - 1)) +
8145     floor((#1 - 1) / 4) + (-floor((#1 - 1) / 100)) +
8146     floor((#1 - 1) / 400) + floor(((367 * #2) - 362) / 12) +
8147     ((#2 <= 2) ? 0 : (\bbl@cs@gregleap{#1} ? -1 : -2)) + #3 } }
8148 <</Compute Julian day>>
```

13.1 Islamic

The code for the Civil calendar is based on it, too.

```
8149 (*ca-islamic)
8150 \ExplSyntaxOn
8151 <<Compute Julian day>>
8152 % == islamic (default)
8153 % Not yet implemented
8154 \def\bbl@ca@islamic#1-#2-#3\@#4#5#6{}
```

The Civil calendar:

```
8155 \def\bbl@cs@isltojd#1#2#3{ % year, month, day
8156   ((#3 + ceil(29.5 * (#2 - 1)) +
8157    (#1 - 1) * 354 + floor((3 + (11 * #1)) / 30) +
8158    1948439.5) - 1) }
8159 \namedef\bbl@ca@islamic-civil+{\bbl@ca@islamicvl@x{+2}}
8160 \namedef\bbl@ca@islamic-civil+{\bbl@ca@islamicvl@x{+1}}
8161 \namedef\bbl@ca@islamic-civil{\bbl@ca@islamicvl@x{}}
8162 \namedef\bbl@ca@islamic-civil-{\bbl@ca@islamicvl@x{-1}}
8163 \namedef\bbl@ca@islamic-civil--{\bbl@ca@islamicvl@x{-2}}
8164 \def\bbl@ca@islamicvl@x#1#2-#3-#4\@#5#6#7{%
8165   \edef\bbl@tempa{%
8166     \fp_eval:n{ floor(\bbl@cs@jd{#2}{#3}{#4})+0.5 #1}}%
8167   \edef#5{%
8168     \fp_eval:n{ floor(((30*(\bbl@tempa-1948439.5)) + 10646)/10631) }}%
8169   \edef#6{\fp_eval:n{
8170     min(12,ceil((\bbl@tempa-(29+\bbl@cs@isltojd{#5}{1}{1}))/29.5)+1) }}%
8171   \edef#7{\fp_eval:n{ \bbl@tempa - \bbl@cs@isltojd{#5}{#6}{1} + 1} }}
```

The Umm al-Qura calendar, used mainly in Saudi Arabia, is based on moment-hijri, by Abdullah Alsigar (license MIT).

Since the main aim is to provide a suitable \today, and maybe some close dates, data just covers Hijri ~1435/~1460 (Gregorian ~2014/~2038).

```
8172 \def\bbl@cs@umalqura@data{56660, 56690,56719,56749,56778,56808,%
8173   56837,56867,56897,56926,56956,56985,57015,57044,57074,57103,%
8174   57133,57162,57192,57221,57251,57280,57310,57340,57369,57399,%
8175   57429,57458,57487,57517,57546,57576,57605,57634,57664,57694,%
8176   57723,57753,57783,57813,57842,57871,57901,57930,57959,57989,%
8177   58018,58048,58077,58107,58137,58167,58196,58226,58255,58285,%
8178   58314,58343,58373,58402,58432,58461,58491,58521,58551,58580,%
8179   58610,58639,58669,58698,58727,58757,58786,58816,58845,58875,%
8180   58905,58934,58964,58994,59023,59053,59082,59111,59141,59170,%
8181   59200,59229,59259,59288,59318,59348,59377,59407,59436,59466,%
8182   59495,59525,59554,59584,59613,59643,59672,59702,59731,59761,%
8183   59791,59820,59850,59879,59909,59939,59968,59997,60027,60056,%
8184   60086,60115,60145,60174,60204,60234,60264,60293,60323,60352,%
8185   60381,60411,60440,60469,60499,60528,60558,60588,60618,60648,%
8186   60677,60707,60736,60765,60795,60824,60853,60883,60912,60942,%
8187   60972,61002,61031,61061,61090,61120,61149,61179,61208,61237,%
8188   61267,61296,61326,61356,61385,61415,61445,61474,61504,61533,%
8189   61563,61592,61621,61651,61680,61710,61739,61769,61799,61828,%
8190   61858,61888,61917,61947,61976,62006,62035,62064,62094,62123,%
8191   62153,62182,62212,62242,62271,62301,62331,62360,62390,62419,%
8192   62448,62478,62507,62537,62566,62596,62625,62655,62685,62715,%
8193   62744,62774,62803,62832,62862,62891,62921,62950,62980,63009,%
8194   63039,63069,63099,63128,63157,63187,63216,63246,63275,63305,%
8195   63334,63363,63393,63423,63453,63482,63512,63541,63571,63600,%
8196   63630,63659,63689,63718,63747,63777,63807,63836,63866,63895,%
8197   63925,63955,63984,64014,64043,64073,64102,64131,64161,64190,%
8198   64220,64249,64279,64309,64339,64368,64398,64427,64457,64486,%
8199   64515,64545,64574,64603,64633,64663,64692,64722,64752,64782,%
8200   64811,64841,64870,64899,64929,64958,64987,65017,65047,65076,%
8201   65106,65136,65166,65195,65225,65254,65283,65313,65342,65371,%
8202   65401,65431,65460,65490,65520}
```

```

8203 \@namedef{bbl@ca@islamic-umalqura+}{\bbl@ca@islamcuqr@x{+1}}
8204 \@namedef{bbl@ca@islamic-umalqura}{\bbl@ca@islamcuqr@x{}}
8205 \@namedef{bbl@ca@islamic-umalqura-}{\bbl@ca@islamcuqr@x{-1}}
8206 \def\bbl@ca@islamcuqr@x#1#2-#3-#4\@@#5#6#7{%
8207   \ifnum#2>2014 \ifnum#2<2038
8208     \bbl@afterfi\expandafter\@gobble
8209   \fi\fi
8210   {\bbl@error{year-out-range}{2014-2038}{}}}%
8211 \edef\bbl@tempd{\fp_eval:n{ % (Julian) day
8212   \bbl@cs@jd{#2}{#3}{#4} + 0.5 - 2400000 #1}}%
8213 \count@\@ne
8214 \bbl@foreach\bbl@cs@umalqura@data{%
8215   \advance\count@\@ne
8216   \ifnum##1>\bbl@tempd\else
8217     \edef\bbl@tempe{\the\count@}%
8218     \edef\bbl@tempb{##1}%
8219     \fi}%
8220 \edef\bbl@templ{\fp_eval:n{ \bbl@tempe + 16260 + 949 }}% month~lunar
8221 \edef\bbl@tempa{\fp_eval:n{ floor((\bbl@templ - 1 ) / 12) }}% annus
8222 \edef#5{\fp_eval:n{ \bbl@tempa + 1 }}%
8223 \edef#6{\fp_eval:n{ \bbl@templ - (12 * \bbl@tempa) }}%
8224 \edef#7{\fp_eval:n{ \bbl@tempd - \bbl@tempb + 1 }}%
8225 \ExplSyntaxOff
8226 \bbl@add\bbl@precalendar{%
8227   \bbl@replace\bbl@ld@calendar{-civil}{}}%
8228   \bbl@replace\bbl@ld@calendar{-umalqura}{}}%
8229   \bbl@replace\bbl@ld@calendar{+}{}}%
8230   \bbl@replace\bbl@ld@calendar{-}{}}%
8231 \</ca-islamic>

```

13.2 Hebrew

This is basically the set of macros written by Michail Rozman in 1991, with corrections and adaptations by Rama Porrat, Misha, Dan Haran and Boris Lavva. This must be eventually replaced by computations with l3fp. An explanation of what's going on can be found in `hebcald.sty`

```

8232 (*ca-hebrew)
8233 \newcount\bbl@cntcommon
8234 \def\bbl@remainder#1#2#3{%
8235   #3=#1\relax
8236   \divide #3 by #2\relax
8237   \multiply #3 by -#2\relax
8238   \advance #3 by #1\relax}%
8239 \newif\ifbbl@divisible
8240 \def\bbl@checkifdivisible#1#2{%
8241   {\countdef\tmp=0
8242     \bbl@remainder{#1}{#2}{\tmp}%
8243     \ifnum \tmp=0
8244       \global\bbl@divisibletrue
8245     \else
8246       \global\bbl@divisiblefalse
8247     \fi}}
8248 \newif\ifbbl@gregleap
8249 \def\bbl@ifgregleap#1{%
8250   \bbl@checkifdivisible{#1}{4}%
8251   \ifbbl@divisible
8252     \bbl@checkifdivisible{#1}{100}%
8253     \ifbbl@divisible
8254       \bbl@checkifdivisible{#1}{400}%
8255       \ifbbl@divisible
8256         \bbl@gregleaptrue
8257       \else
8258         \bbl@gregleapfalse
8259     \fi

```

```

8260     \else
8261         \bbl@gregleaptrue
8262     \fi
8263 \else
8264     \bbl@gregleapfalse
8265 \fi
8266 \ifbbl@gregleap}
8267 \def\bbl@gregdayspriormonths#1#2#3{%
8268     {#3=\ifcase #1 0 \or 0 \or 31 \or 59 \or 90 \or 120 \or 151 \or
8269         181 \or 212 \or 243 \or 273 \or 304 \or 334 \fi
8270     \bbl@ifgregleap{#2}%
8271     \ifnum #1 > 2
8272         \advance #3 by 1
8273     \fi
8274     \fi
8275     \global\bbl@cntcommon=#3}%
8276     #3=\bbl@cntcommon}
8277 \def\bbl@gregdaysprioryears#1#2{%
8278     {\countdef\tmpc=4
8279     \countdef\tmpb=2
8280     \tmpb=#1\relax
8281     \advance \tmpb by -1
8282     \tmpc=\tmpb
8283     \multiply \tmpc by 365
8284     #2=\tmpc
8285     \tmpc=\tmpb
8286     \divide \tmpc by 4
8287     \advance #2 by \tmpc
8288     \tmpc=\tmpb
8289     \divide \tmpc by 100
8290     \advance #2 by -\tmpc
8291     \tmpc=\tmpb
8292     \divide \tmpc by 400
8293     \advance #2 by \tmpc
8294     \global\bbl@cntcommon=#2\relax}%
8295     #2=\bbl@cntcommon}
8296 \def\bbl@absfromgreg#1#2#3#4{%
8297     {\countdef\tmpd=0
8298     #4=#1\relax
8299     \bbl@gregdayspriormonths{#2}{#3}{\tmpd}%
8300     \advance #4 by \tmpd
8301     \bbl@gregdaysprioryears{#3}{\tmpd}%
8302     \advance #4 by \tmpd
8303     \global\bbl@cntcommon=#4\relax}%
8304     #4=\bbl@cntcommon}
8305 \newif\ifbbl@hebrleap
8306 \def\bbl@checkleaphebryear#1{%
8307     {\countdef\tmpa=0
8308     \countdef\tmpb=1
8309     \tmpa=#1\relax
8310     \multiply \tmpa by 7
8311     \advance \tmpa by 1
8312     \bbl@remainder{\tmpa}{19}{\tmpb}%
8313     \ifnum \tmpb < 7
8314         \global\bbl@hebrleaptrue
8315     \else
8316         \global\bbl@hebrleapfalse
8317     \fi}}
8318 \def\bbl@hebrlapsedmonths#1#2{%
8319     {\countdef\tmpa=0
8320     \countdef\tmpb=1
8321     \countdef\tmpc=2
8322     \tmpa=#1\relax

```

```

8323 \advance \tmpa by -1
8324 #2=\tmpa
8325 \divide #2 by 19
8326 \multiply #2 by 235
8327 \bbl@remainder{\tmpa}{19}{\tmpb}% \tmpa=years%19-years this cycle
8328 \tmpc=\tmpb
8329 \multiply \tmpb by 12
8330 \advance #2 by \tmpb
8331 \multiply \tmpc by 7
8332 \advance \tmpc by 1
8333 \divide \tmpc by 19
8334 \advance #2 by \tmpc
8335 \global\bbl@cntcommon=#2}%
8336 #2=\bbl@cntcommon}
8337 \def\bbl@hebreleapseddays#1#2{%
8338 {\countdef\tmpa=0
8339 \countdef\tmpb=1
8340 \countdef\tmpc=2
8341 \bbl@hebreleapsedmonths{#1}{#2}%
8342 \tmpa=#2\relax
8343 \multiply \tmpa by 13753
8344 \advance \tmpa by 5604
8345 \bbl@remainder{\tmpa}{25920}{\tmpc}% \tmpc == ConjunctionParts
8346 \divide \tmpa by 25920
8347 \multiply #2 by 29
8348 \advance #2 by 1
8349 \advance #2 by \tmpa
8350 \bbl@remainder{#2}{7}{\tmpa}%
8351 \ifnum \tmpc < 19440
8352 \ifnum \tmpc < 9924
8353 \else
8354 \ifnum \tmpa=2
8355 \bbl@checkleaphebyear{#1}% of a common year
8356 \ifbbl@hebrleap
8357 \else
8358 \advance #2 by 1
8359 \fi
8360 \fi
8361 \fi
8362 \ifnum \tmpc < 16789
8363 \else
8364 \ifnum \tmpa=1
8365 \advance #1 by -1
8366 \bbl@checkleaphebyear{#1}% at the end of leap year
8367 \ifbbl@hebrleap
8368 \advance #2 by 1
8369 \fi
8370 \fi
8371 \fi
8372 \else
8373 \advance #2 by 1
8374 \fi
8375 \bbl@remainder{#2}{7}{\tmpa}%
8376 \ifnum \tmpa=0
8377 \advance #2 by 1
8378 \else
8379 \ifnum \tmpa=3
8380 \advance #2 by 1
8381 \else
8382 \ifnum \tmpa=5
8383 \advance #2 by 1
8384 \fi
8385 \fi

```

```

8386 \fi
8387 \global\bbbl@cntcommon=#2\relax}%
8388 #2=\bbbl@cntcommon}
8389 \def\bbbl@daysinhebrewyear#1#2{%
8390 {\countdef\tmpe=12
8391 \bbbl@hebreleapseddays{#1}{\tmpe}%
8392 \advance #1 by 1
8393 \bbbl@hebreleapseddays{#1}{#2}%
8394 \advance #2 by -\tmpe
8395 \global\bbbl@cntcommon=#2}%
8396 #2=\bbbl@cntcommon}
8397 \def\bbbl@hebrdayspriormonths#1#2#3{%
8398 {\countdef\tmpf= 14
8399 #3=\ifcase #1\relax
8400 0 \or
8401 0 \or
8402 30 \or
8403 59 \or
8404 89 \or
8405 118 \or
8406 148 \or
8407 148 \or
8408 177 \or
8409 207 \or
8410 236 \or
8411 266 \or
8412 295 \or
8413 325 \or
8414 400
8415 \fi
8416 \bbbl@checkleaphebrewyear{#2}%
8417 \ifbbbl@hebrleap
8418 \ifnum #1 > 6
8419 \advance #3 by 30
8420 \fi
8421 \fi
8422 \bbbl@daysinhebrewyear{#2}{\tmpf}%
8423 \ifnum #1 > 3
8424 \ifnum \tmpf=353
8425 \advance #3 by -1
8426 \fi
8427 \ifnum \tmpf=383
8428 \advance #3 by -1
8429 \fi
8430 \fi
8431 \ifnum #1 > 2
8432 \ifnum \tmpf=355
8433 \advance #3 by 1
8434 \fi
8435 \ifnum \tmpf=385
8436 \advance #3 by 1
8437 \fi
8438 \fi
8439 \global\bbbl@cntcommon=#3\relax}%
8440 #3=\bbbl@cntcommon}
8441 \def\bbbl@absfromhebr#1#2#3#4{%
8442 {#4=#1\relax
8443 \bbbl@hebrdayspriormonths{#2}{#3}{#1}%
8444 \advance #4 by #1\relax
8445 \bbbl@hebreleapseddays{#3}{#1}%
8446 \advance #4 by #1\relax
8447 \advance #4 by -1373429
8448 \global\bbbl@cntcommon=#4\relax}%

```

```

8449 #4=\bbl@cntcommon}
8450 \def\bbl@hebrfromgreg#1#2#3#4#5#6{%
8451 {\countdef\tmpx= 17
8452 \countdef\tmpy= 18
8453 \countdef\tmpz= 19
8454 #6=#3\relax
8455 \global\advance #6 by 3761
8456 \bbl@absfromgreg{#1}{#2}{#3}{#4}%
8457 \tmpz=1 \tmpy=1
8458 \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
8459 \ifnum \tmpx > #4\relax
8460 \global\advance #6 by -1
8461 \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
8462 \fi
8463 \advance #4 by -\tmpx
8464 \advance #4 by 1
8465 #5=#4\relax
8466 \divide #5 by 30
8467 \loop
8468 \bbl@hebrdayspriormonths{#5}{#6}{\tmpx}%
8469 \ifnum \tmpx < #4\relax
8470 \advance #5 by 1
8471 \tmpy=\tmpx
8472 \repeat
8473 \global\advance #5 by -1
8474 \global\advance #4 by -\tmpy}}
8475 \newcount\bbl@hebrday \newcount\bbl@hebrmonth \newcount\bbl@hebryear
8476 \newcount\bbl@gregday \newcount\bbl@gregmonth \newcount\bbl@gregyear
8477 \def\bbl@ca@hebrew#1-#2-#3\@#4#5#6{%
8478 \bbl@gregday=#3\relax \bbl@gregmonth=#2\relax \bbl@gregyear=#1\relax
8479 \bbl@hebrfromgreg
8480 {\bbl@gregday}{\bbl@gregmonth}{\bbl@gregyear}%
8481 {\bbl@hebrday}{\bbl@hebrmonth}{\bbl@hebryear}%
8482 \edef#4{\the\bbl@hebryear}%
8483 \edef#5{\the\bbl@hebrmonth}%
8484 \edef#6{\the\bbl@hebrday}}
8485 \ca-hebrew)

```

13.3 Persian

There is an algorithm written in TeX by Jabri, Abolhassani, Pournader and Esfahbod, created for the first versions of the FarsiTeX system (no longer available), but the original license is GPL, so its use with LPL is problematic. The code here follows loosely that by John Walker, which is free and accurate, but sadly very complex, so the relevant data for the years 2013-2050 have been pre-calculated and stored. Actually, all we need is the first day (either March 20 or March 21).

```

8486 (*ca-persian)
8487 \ExplSyntaxOn
8488 <<Compute Julian day>>
8489 \def\bbl@cs@firstjal@xx{2012,2016,2020,2024,2028,2029,% March 20
8490 2032,2033,2036,2037,2040,2041,2044,2045,2048,2049}
8491 \def\bbl@ca@persian#1-#2-#3\@#4#5#6{%
8492 \edef\bbl@tempa{#1}% 20XX-03-\bbl@tempe = 1 farvardin:
8493 \ifnum\bbl@tempa>2012 \ifnum\bbl@tempa<2051
8494 \bbl@afterfi\expandafter@gobble
8495 \fi\fi
8496 {\bbl@error{year-out-range}{2013-2050}{}}}%
8497 \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%
8498 \ifin@{\def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
8499 \edef\bbl@tempc{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{#2}{#3}+.5}}% current
8500 \edef\bbl@tempb{\fp_eval:n{\bbl@cs@jd{\bbl@tempa}{03}{\bbl@tempe}+.5}}% begin
8501 \ifnum\bbl@tempc<\bbl@tempb
8502 \edef\bbl@tempa{\fp_eval:n{\bbl@tempa-1}}% go back 1 year and redo
8503 \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%

```

```

8504 \ifin@def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
8505 \edef\bbl@tempb{\fp_eval:n{\bbl@cs@jd{\bbl@tempe}{03}{\bbl@tempe}+.5}}%
8506 \fi
8507 \edef#4{\fp_eval:n{\bbl@tempe-621}}% set Jalali year
8508 \edef#6{\fp_eval:n{\bbl@tempc-\bbl@tempb+1}}% days from 1 farvardin
8509 \edef#5{\fp_eval:n{% set Jalali month
8510 (#6 <= 186) ? ceil(#6 / 31) : ceil((#6 - 6) / 30)}}
8511 \edef#6{\fp_eval:n{% set Jalali day
8512 (#6 - ((#5 <= 7) ? ((#5 - 1) * 31) : (((#5 - 1) * 30) + 6))}}}%
8513 \ExplSyntaxOff
8514 \ca-persian)

```

13.4 Coptic and Ethiopic

Adapted from `jquery.calendars.package-1.1.4`, written by Keith Wood, 2010. Dual license: GPL and MIT. The only difference is the epoch.

```

8515 (*ca-coptic)
8516 \ExplSyntaxOn
8517 <<Compute Julian day>>
8518 \def\bbl@ca@coptic#1-#2-#3\@#4#5#6{%
8519 \edef\bbl@tempd{\fp_eval:n{floor(\bbl@cs@jd{#1}{#2}{#3}) + 0.5}}%
8520 \edef\bbl@tempc{\fp_eval:n{\bbl@tempd - 1825029.5}}%
8521 \edef#4{\fp_eval:n{%
8522 floor((\bbl@tempc - floor((\bbl@tempc+366) / 1461)) / 365) + 1}}%
8523 \edef\bbl@tempc{\fp_eval:n{%
8524 \bbl@tempd - (#4-1) * 365 - floor(#4/4) - 1825029.5}}%
8525 \edef#5{\fp_eval:n{floor(\bbl@tempc / 30) + 1}}%
8526 \edef#6{\fp_eval:n{\bbl@tempc - (#5 - 1) * 30 + 1}}}%
8527 \ExplSyntaxOff
8528 \ca-coptic)
8529 (*ca-ethiopic)
8530 \ExplSyntaxOn
8531 <<Compute Julian day>>
8532 \def\bbl@ca@ethiopic#1-#2-#3\@#4#5#6{%
8533 \edef\bbl@tempd{\fp_eval:n{floor(\bbl@cs@jd{#1}{#2}{#3}) + 0.5}}%
8534 \edef\bbl@tempc{\fp_eval:n{\bbl@tempd - 1724220.5}}%
8535 \edef#4{\fp_eval:n{%
8536 floor((\bbl@tempc - floor((\bbl@tempc+366) / 1461)) / 365) + 1}}%
8537 \edef\bbl@tempc{\fp_eval:n{%
8538 \bbl@tempd - (#4-1) * 365 - floor(#4/4) - 1724220.5}}%
8539 \edef#5{\fp_eval:n{floor(\bbl@tempc / 30) + 1}}%
8540 \edef#6{\fp_eval:n{\bbl@tempc - (#5 - 1) * 30 + 1}}}%
8541 \ExplSyntaxOff
8542 \ca-ethiopic)

```

13.5 Buddhist

That's very simple.

```

8543 (*ca-buddhist)
8544 \def\bbl@ca@buddhist#1-#2-#3\@#4#5#6{%
8545 \edef#4{\number\numexpr#1+543\relax}%
8546 \edef#5{#2}%
8547 \edef#6{#3}}
8548 \ca-buddhist)
8549 %
8550 \subsection{Chinese}
8551 %
8552 % Brute force, with the Julian day of first day of each month. The
8553 % table has been computed with the help of \textsf{python-lunardate} by
8554 % Ricky Yeung, GPLv2 (but the code itself has not been used). The range
8555 % is 2015-2044.
8556 %

```



```

8557 % \begin{macrocode}
8558 (*ca-chinese)
8559 \ExplSyntaxOn
8560 <<Compute Julian day>>
8561 \def\bbl@ca@chinese#1-#2-#3\@@#4#5#6{%
8562 \edef\bbl@tempd{\fp_eval:n{%
8563 \bbl@cs@jd{#1}{#2}{#3} - 2457072.5 }}%
8564 \count@ \z@
8565 \@tempcnta=2015
8566 \bbl@foreach\bbl@cs@chinese@data{%
8567 \ifnum##1>\bbl@tempd\else
8568 \advance\count@\@ne
8569 \ifnum\count@>12
8570 \count@\@ne
8571 \advance\@tempcnta\@ne\fi
8572 \bbl@xin@{,##1,}{,\bbl@cs@chinese@leap,}%
8573 \ifin@
8574 \advance\count@\m@ne
8575 \edef\bbl@tempe{\the\numexpr\count@+12\relax}%
8576 \else
8577 \edef\bbl@tempe{\the\count@}%
8578 \fi
8579 \edef\bbl@tempb{##1}%
8580 \fi}%
8581 \edef#4{\the\@tempcnta}%
8582 \edef#5{\bbl@tempe}%
8583 \edef#6{\the\numexpr\bbl@tempd-\bbl@tempb+1\relax}}
8584 \def\bbl@cs@chinese@leap{%
8585 885,1920,2953,3809,4873,5906,6881,7825,8889,9893,10778}
8586 \def\bbl@cs@chinese@data{0,29,59,88,117,147,176,206,236,266,295,325,
8587 354,384,413,443,472,501,531,560,590,620,649,679,709,738,%
8588 768,797,827,856,885,915,944,974,1003,1033,1063,1093,1122,%
8589 1152,1181,1211,1240,1269,1299,1328,1358,1387,1417,1447,1477,%
8590 1506,1536,1565,1595,1624,1653,1683,1712,1741,1771,1801,1830,%
8591 1860,1890,1920,1949,1979,2008,2037,2067,2096,2126,2155,2185,%
8592 2214,2244,2274,2303,2333,2362,2392,2421,2451,2480,2510,2539,%
8593 2569,2598,2628,2657,2687,2717,2746,2776,2805,2835,2864,2894,%
8594 2923,2953,2982,3011,3041,3071,3100,3130,3160,3189,3219,3248,%
8595 3278,3307,3337,3366,3395,3425,3454,3484,3514,3543,3573,3603,%
8596 3632,3662,3691,3721,3750,3779,3809,3838,3868,3897,3927,3957,%
8597 3987,4016,4046,4075,4105,4134,4163,4193,4222,4251,4281,4311,%
8598 4341,4370,4400,4430,4459,4489,4518,4547,4577,4606,4635,4665,%
8599 4695,4724,4754,4784,4814,4843,4873,4902,4931,4961,4990,5019,%
8600 5049,5079,5108,5138,5168,5197,5227,5256,5286,5315,5345,5374,%
8601 5403,5433,5463,5492,5522,5551,5581,5611,5640,5670,5699,5729,%
8602 5758,5788,5817,5846,5876,5906,5935,5965,5994,6024,6054,6083,%
8603 6113,6142,6172,6201,6231,6260,6289,6319,6348,6378,6408,6437,%
8604 6467,6497,6526,6556,6585,6615,6644,6673,6703,6732,6762,6791,%
8605 6821,6851,6881,6910,6940,6969,6999,7028,7057,7087,7116,7146,%
8606 7175,7205,7235,7264,7294,7324,7353,7383,7412,7441,7471,7500,%
8607 7529,7559,7589,7618,7648,7678,7708,7737,7767,7796,7825,7855,%
8608 7884,7913,7943,7972,8002,8032,8062,8092,8121,8151,8180,8209,%
8609 8239,8268,8297,8327,8356,8386,8416,8446,8475,8505,8534,8564,%
8610 8593,8623,8652,8681,8711,8740,8770,8800,8829,8859,8889,8918,%
8611 8948,8977,9007,9036,9066,9095,9124,9154,9183,9213,9243,9272,%
8612 9302,9331,9361,9391,9420,9450,9479,9508,9538,9567,9597,9626,%
8613 9656,9686,9715,9745,9775,9804,9834,9863,9893,9922,9951,9981,%
8614 10010,10040,10069,10099,10129,10158,10188,10218,10247,10277,%
8615 10306,10335,10365,10394,10423,10453,10483,10512,10542,10572,%
8616 10602,10631,10661,10690,10719,10749,10778,10807,10837,10866,%
8617 10896,10926,10956,10986,11015,11045,11074,11103}
8618 \ExplSyntaxOff
8619 </ca-chinese>

```



```

8641 \def\loadlocalcfg#1{%
8642   \openin0#1.cfg
8643   \ifeof0
8644     \closein0
8645   \else
8646     \closein0
8647     {\immediate\writel6{*****}%
8648      \immediate\writel6{* Local config file #1.cfg used}%
8649      \immediate\writel6{*}%
8650     }
8651     \input #1.cfg\relax
8652   \fi
8653   \@endofldef}

```

14.3 General tools

A number of \TeX macro's that are needed later on.

```

8654 \long\def\@firstofone#1{#1}
8655 \long\def\@firstoftwo#1#2{#1}
8656 \long\def\@secondoftwo#1#2{#2}
8657 \def\@nnil{\@nil}
8658 \def\@gobbletwo#1#2{}
8659 \def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}
8660 \def\@star@or@long#1{%
8661   \@ifstar
8662   {\let\l@ngrel@x\relax#1}%
8663   {\let\l@ngrel@x\long#1}}
8664 \let\l@ngrel@x\relax
8665 \def\@car#1#2\@nil{#1}
8666 \def\@cdr#1#2\@nil{#2}
8667 \let\@typeset@protect\relax
8668 \let\protected@edef\edef
8669 \long\def\@gobble#1{}
8670 \edef\@backslashchar{\expandafter\@gobble\string\}
8671 \def\strip@prefix#1>{}
8672 \def\g@addto@macro#1#2{%
8673   \toks@\expandafter{#1#2}%
8674   \xdef#1{\the\toks@}}
8675 \def\@namedef#1{\expandafter\def\csname #1\endcsname}
8676 \def\@nameuse#1{\csname #1\endcsname}
8677 \def\@ifundefined#1{%
8678   \expandafter\ifx\csname#1\endcsname\relax
8679     \expandafter\@firstoftwo
8680   \else
8681     \expandafter\@secondoftwo
8682   \fi}
8683 \def\@expandtwoargs#1#2#3{%
8684   \edef\reserved@a{\noexpand#1{#2}{#3}}\reserved@a}
8685 \def\zap@space#1 #2{%
8686   #1%
8687   \ifx#2\@empty\else\expandafter\zap@space\fi
8688   #2}
8689 \let\bbl@trace\@gobble
8690 \def\bbl@error#1{% Implicit #2#3#4
8691   \begingroup
8692     \catcode`\:=0 \catcode`\==12 \catcode`\^=12
8693     \catcode`\^^M=5 \catcode`\%=14
8694     \input errbabel.def
8695   \endgroup
8696   \bbl@error{#1}}
8697 \def\bbl@warning#1{%
8698   \begingroup
8699     \newlinechar=`^^J

```

```

8700 \def\{^J(babel) }%
8701 \message{\#1}%
8702 \endgroup}
8703 \let\bbl@infowarn\bbl@warning
8704 \def\bbl@info#1{%
8705 \begingroup
8706 \newlinechar=`^J
8707 \def\{^J}%
8708 \wlog{#1}%
8709 \endgroup}

```

\LaTeX 2 ϵ has the command `\@onlypreamble` which adds commands to a list of commands that are no longer needed after `\begin{document}`.

```

8710 \ifx\@preamblecmds\undefined
8711 \def\@preamblecmds{}
8712 \fi
8713 \def\@onlypreamble#1{%
8714 \expandafter\gdef\expandafter\@preamblecmds\expandafter{%
8715 \@preamblecmds\do#1}}
8716 \@onlypreamble\@onlypreamble

```

Mimic \LaTeX 's `\AtBeginDocument`; for this to work the user needs to add `\begindocument` to his file.

```

8717 \def\begindocument{%
8718 \@begindocumenthook
8719 \global\let\@begindocumenthook\undefined
8720 \def\do##1{\global\let##1\@undefined}%
8721 \@preamblecmds
8722 \global\let\do\noexpand}

8723 \ifx\@begindocumenthook\undefined
8724 \def\@begindocumenthook{}
8725 \fi
8726 \@onlypreamble\@begindocumenthook
8727 \def\AtBeginDocument{\g@addto@macro\@begindocumenthook}

```

We also have to mimic \LaTeX 's `\AtEndOfPackage`. Our replacement macro is much simpler; it stores its argument in `\@endofldf`.

```

8728 \def\AtEndOfPackage#1{\g@addto@macro\@endofldf{#1}}
8729 \@onlypreamble\AtEndOfPackage
8730 \def\@endofldf{}
8731 \@onlypreamble\@endofldf
8732 \let\bbl@afterlang\@empty
8733 \chardef\bbl@opt@hyphenmap\z@

```

\LaTeX needs to be able to switch off writing to its auxiliary files; plain doesn't have them by default. There is a trick to hide some conditional commands from the outer `\ifx`. The same trick is applied below.

```

8734 \catcode`\&=\z@
8735 \ifx&if@filesw\undefined
8736 \expandafter\let\csname if@filesw\expandafter\endcsname
8737 \csname iffalse\endcsname
8738 \fi
8739 \catcode`\&=4

```

Mimic \LaTeX 's commands to define control sequences.

```

8740 \def\newcommand{\@star@or@long\new@command}
8741 \def\new@command#1{%
8742 \@testopt{\@newcommand#1}0}
8743 \def\@newcommand#1[#2]{%
8744 \@ifnextchar [{\@xargdef#1[#2]}%
8745 {\@argdef#1[#2]}}
8746 \long\def\@argdef#1[#2]#3{%
8747 \@yargdef#1\@ne{#2}{#3}}
8748 \long\def\@xargdef#1[#2]#3#4{%

```

```

8749 \expandafter\def\expandafter#1\expandafter{%
8750   \expandafter\@protected@testopt\expandafter #1%
8751   \csname\string#1\expandafter\endcsname{#3}}%
8752 \expandafter\@yargdef \csname\string#1\endcsname
8753 \tw@{#2}{#4}}
8754 \long\def\@yargdef#1#2#3{%
8755   \@tempcnta#3\relax
8756   \advance \@tempcnta \@ne
8757   \let\@hash@\relax
8758   \edef\reserved@a{\ifx#2\tw@ [\@hash@1]\fi}%
8759   \@tempcntb #2%
8760   \@whilenum \@tempcntb <\@tempcnta
8761   \do{%
8762     \edef\reserved@a{\reserved@a\@hash@the\@tempcntb}%
8763     \advance\@tempcntb \@ne}%
8764   \let\@hash@##%
8765   \l@ngrelx\expandafter\def\expandafter#1\reserved@a}
8766 \def\providecommand{\@star@or@long\providecommand}
8767 \def\providecommand#1{%
8768   \begingroup
8769     \escapechar\m@ne\xdef\@gtempa{\string#1}%
8770   \endgroup
8771   \expandafter\@ifundefined\@gtempa
8772     {\def\reserved@a{\newcommand#1}}%
8773     {\let\reserved@a\relax
8774     \def\reserved@a{\newcommand\reserved@a}}%
8775   \reserved@a}%
8776 \def\DeclareRobustCommand{\@star@or@long\declare@robustcommand}
8777 \def\declare@robustcommand#1{%
8778   \edef\reserved@a{\string#1}%
8779   \def\reserved@b{#1}%
8780   \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
8781   \edef#1{%
8782     \ifx\reserved@a\reserved@b
8783       \noexpand\x@protect
8784       \noexpand#1%
8785     \fi
8786     \noexpand\protect
8787     \expandafter\noexpand\csname
8788       \expandafter\@gobble\string#1 \endcsname
8789   }%
8790   \expandafter\newcommand\csname
8791     \expandafter\@gobble\string#1 \endcsname
8792 }
8793 \def\x@protect#1{%
8794   \ifx\protect\@typeset@protect\else
8795     \@x@protect#1%
8796   \fi
8797 }
8798 \catcode\&=\z@ % Trick to hide conditionals
8799 \def\@x@protect#1&fi#2#3{&fi\protect#1}

```

The following little macro `\in@` is taken from `latex.ltx`; it checks whether its first argument is part of its second argument. It uses the boolean `\in@`; allocating a new boolean inside conditionally executed code is not possible, hence the construct with the temporary definition of `\bbl@tempa`.

```

8800 \def\bbl@tempa{\csname newif\endcsname&fin@}
8801 \catcode\&=4
8802 \ifx\in@\@undefined
8803   \def\in@#1#2{%
8804     \def\in@@##1##2##3\in@{%
8805       \ifx\in@@##2\in@false\else\in@true\fi}%
8806     \in@@#2#1\in@\in@@}
8807 \else

```

```

8808 \let\bbl@tempa\@empty
8809 \fi
8810 \bbl@tempa

```

\LaTeX has a macro to check whether a certain package was loaded with specific options. The command has two extra arguments which are code to be executed in either the true or false case. This is used to detect whether the document needs one of the accents to be activated (activegrave and activeacute). For plain \TeX we assume that the user wants them to be active by default. Therefore the only thing we do is execute the third argument (the code for the true case).

```

8811 \def\@ifpackagewith#1#2#3#4{#3}

```

The \LaTeX macro `\@ifl@aded` checks whether a file was loaded. This functionality is not needed for plain \TeX but we need the macro to be defined as a no-op.

```

8812 \def\@ifl@aded#1#2#3#4{}

```

For the following code we need to make sure that the commands `\newcommand` and `\providecommand` exist with some sensible definition. They are not fully equivalent to their $\LaTeX 2_{\epsilon}$ versions; just enough to make things work in plain \TeX environments.

```

8813 \ifx\@tempcnta\undefined
8814 \csname newcount\endcsname\@tempcnta\relax
8815 \fi
8816 \ifx\@tempcntb\undefined
8817 \csname newcount\endcsname\@tempcntb\relax
8818 \fi

```

To prevent wasting two counters in \LaTeX (because counters with the same name are allocated later by it) we reset the counter that holds the next free counter (`\count10`).

```

8819 \ifx\bye\undefined
8820 \advance\count10 by -2\relax
8821 \fi
8822 \ifx\@ifnextchar\undefined
8823 \def\@ifnextchar#1#2#3{%
8824   \let\reserved@d=#1%
8825   \def\reserved@a{#2}\def\reserved@b{#3}%
8826   \futurelet\@let@token\@ifnch}
8827 \def\@ifnch{%
8828   \ifx\@let@token\@sptoken
8829     \let\reserved@c\@ifnch
8830   \else
8831     \ifx\@let@token\reserved@d
8832       \let\reserved@c\reserved@a
8833     \else
8834       \let\reserved@c\reserved@b
8835     \fi
8836   \fi
8837   \reserved@c}
8838 \def\:{\let\@sptoken= }\: % this makes \@sptoken a space token
8839 \def\:{\@xifnch} \expandafter\def\:{\futurelet\@let@token\@ifnch}
8840 \fi
8841 \def\@testopt#1#2{%
8842   \@ifnextchar[#{#1}{#1[#2]}}
8843 \def\@protected@testopt#1{%
8844   \ifx\protect\@typeset@protect
8845     \expandafter\@testopt
8846   \else
8847     \@xprotect#1%
8848   \fi}
8849 \long\def\@whilenum#1\do #2{\ifnum #1\relax #2\relax\@iwhilenum{#1\relax
8850   #2\relax}\fi}
8851 \long\def\@iwhilenum#1{\ifnum #1\expandafter\@iwhilenum
8852   \else\expandafter\@gobble\fi{#1}}

```

14.4 Encoding related macros

Code from `ltoutenc.dtx`, adapted for use in the plain $\text{T}_{\text{E}}\text{X}$ environment.

```
8853 \def\DeclareTextCommand{%
8854   \@dec@text@cmd\providecommand
8855 }
8856 \def\ProvideTextCommand{%
8857   \@dec@text@cmd\providecommand
8858 }
8859 \def\DeclareTextSymbol#1#2#3{%
8860   \@dec@text@cmd\chardef#1{#2}#3\relax
8861 }
8862 \def\@dec@text@cmd#1#2#3{%
8863   \expandafter\def\expandafter#2%
8864     \expandafter{%
8865       \csname#3-cmd\expandafter\endcsname
8866       \expandafter#2%
8867       \csname#3\string#2\endcsname
8868     }%
8869 %   \let\@ifdefinable\@rc@ifdefinable
8870   \expandafter#1\csname#3\string#2\endcsname
8871 }
8872 \def\@current@cmd#1{%
8873   \ifx\protect\@typeset@protect\else
8874     \noexpand#1\expandafter\@gobble
8875   \fi
8876 }
8877 \def\@changed@cmd#1#2{%
8878   \ifx\protect\@typeset@protect
8879     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
8880       \expandafter\ifx\csname ?\string#1\endcsname\relax
8881         \expandafter\def\csname ?\string#1\endcsname{%
8882           \@changed@x@err{#1}%
8883         }%
8884       \fi
8885       \global\expandafter\let
8886         \csname\cf@encoding\string#1\expandafter\endcsname
8887         \csname ?\string#1\endcsname
8888     \fi
8889     \csname\cf@encoding\string#1%
8890       \expandafter\endcsname
8891   \else
8892     \noexpand#1%
8893   \fi
8894 }
8895 \def\@changed@x@err#1{%
8896   \errhelp{Your command will be ignored, type <return> to proceed}%
8897   \errmessage{Command \protect#1 undefined in encoding \cf@encoding}}
8898 \def\DeclareTextCommandDefault#1{%
8899   \DeclareTextCommand#1?%
8900 }
8901 \def\ProvideTextCommandDefault#1{%
8902   \ProvideTextCommand#1?%
8903 }
8904 \expandafter\let\csname OT1-cmd\endcsname\@current@cmd
8905 \expandafter\let\csname?-cmd\endcsname\@changed@cmd
8906 \def\DeclareTextAccent#1#2#3{%
8907   \DeclareTextCommand#1{#2}[1]{\accent#3 ##1}
8908 }
8909 \def\DeclareTextCompositeCommand#1#2#3#4{%
8910   \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
8911   \edef\reserved@b{\string##1}%
8912   \edef\reserved@c{%
```

```

8913 \expandafter\@strip@args\meaning\reserved@a:-\@strip@args}%
8914 \ifx\reserved@b\reserved@c
8915 \expandafter\expandafter\expandafter\ifx
8916 \expandafter\@car\reserved@a\relax\relax\@nil
8917 \@text@composite
8918 \else
8919 \edef\reserved@b##1{%
8920 \def\expandafter\noexpand
8921 \csname#2\string#1\endcsname###1{%
8922 \noexpand\@text@composite
8923 \expandafter\noexpand\csname#2\string#1\endcsname
8924 ###1\noexpand\@empty\noexpand\@text@composite
8925 {##1}%
8926 }%
8927 }%
8928 \expandafter\reserved@b\expandafter{\reserved@a{##1}}%
8929 \fi
8930 \expandafter\def\csname\expandafter\string\csname
8931 #2\endcsname\string#1-\string#3\endcsname{#4}
8932 \else
8933 \errhelp{Your command will be ignored, type <return> to proceed}%
8934 \errmessage{\string\DeclareTextCompositeCommand\space used on
8935 inappropriate command \protect#1}
8936 \fi
8937 }
8938 \def\@text@composite#1#2#3\@text@composite{%
8939 \expandafter\@text@composite@x
8940 \csname\string#1-\string#2\endcsname
8941 }
8942 \def\@text@composite@x#1#2{%
8943 \ifx#1\relax
8944 #2%
8945 \else
8946 #1%
8947 \fi
8948 }
8949 %
8950 \def\@strip@args#1:#2-#3\@strip@args{#2}
8951 \def\DeclareTextComposite#1#2#3#4{%
8952 \def\reserved@a{\DeclareTextCompositeCommand#1{#2}{#3}}%
8953 \bgroup
8954 \lccode`\@=#4%
8955 \lowercase{%
8956 \egroup
8957 \reserved@a @%
8958 }%
8959 }
8960 %
8961 \def\UseTextSymbol#1#2{#2}
8962 \def\UseTextAccent#1#2#3{}
8963 \def\@use@text@encoding#1{}
8964 \def\DeclareTextSymbolDefault#1#2{%
8965 \DeclareTextCommandDefault#1{\UseTextSymbol{#2}#1}%
8966 }
8967 \def\DeclareTextAccentDefault#1#2{%
8968 \DeclareTextCommandDefault#1{\UseTextAccent{#2}#1}%
8969 }
8970 \def\cf@encoding{OT1}

```

Currently we only use the \TeX method for accents for those that are known to be made active in *some* language definition file.

```

8971 \DeclareTextAccent{"}{OT1}{127}
8972 \DeclareTextAccent{'}{OT1}{19}

```



```

8973 \DeclareTextAccent{\^}{OT1}{94}
8974 \DeclareTextAccent{\`}{OT1}{18}
8975 \DeclareTextAccent{\~}{OT1}{126}

```

The following control sequences are used in `babel.def` but are not defined for PLAIN \TeX .

```

8976 \DeclareTextSymbol{\textquotedblleft}{OT1}{92}
8977 \DeclareTextSymbol{\textquotedblright}{OT1}{`\"}
8978 \DeclareTextSymbol{\textquoteleft}{OT1}{`\'}
8979 \DeclareTextSymbol{\textquoteright}{OT1}{`\'}
8980 \DeclareTextSymbol{\i}{OT1}{16}
8981 \DeclareTextSymbol{\ss}{OT1}{25}

```

For a couple of languages we need the \TeX -control sequence `\scriptsize` to be available. Because plain \TeX doesn't have such a sophisticated font mechanism as \TeX has, we just `\let` it to `\sevenrm`.

```

8982 \ifx\scriptsize\@undefined
8983   \let\scriptsize\sevenrm
8984 \fi

```

And a few more “dummy” definitions.

```

8985 \def\language{english}%
8986 \let\bbl@opt@shorthands\@nnil
8987 \def\bbl@ifshorthand#1#2#3#2{%
8988   \let\bbl@language@opts\@empty
8989   \let\bbl@ensureinfo\@gobble
8990   \let\bbl@provide@locale\relax
8991   \ifx\babeloptionstrings\@undefined
8992     \let\bbl@opt@strings\@nnil
8993   \else
8994     \let\bbl@opt@strings\babeloptionstrings
8995   \fi
8996 \def\BabelStringsDefault{generic}
8997 \def\bbl@tempa{normal}
8998 \ifx\babeloptionmath\bbl@tempa
8999   \def\bbl@mathnormal{\noexpand\textormath}
9000 \fi
9001 \def\AfterBabelLanguage#1#2{}
9002 \ifx\BabelModifiers\@undefined\let\BabelModifiers\relax\fi
9003 \let\bbl@afterlang\relax
9004 \def\bbl@opt@safe{BR}
9005 \ifx\uclclist\@undefined\let\uclclist\@empty\fi
9006 \ifx\bbl@trace\@undefined\def\bbl@trace#1{}\fi
9007 \expandafter\newif\csname ifbbl@single\endcsname
9008 \chardef\bbl@bidimode\z@
9009 <</Emulate LaTeX>>

```

A proxy file:

```

9010 <*\plain>
9011 \input babel.def
9012 </\plain>

```

15 Acknowledgements

I would like to thank all who volunteered as β -testers for their time. Michel Goossens supplied contributions for most of the other languages. Nico Poppelier helped polish the text of the documentation and supplied parts of the macros for the Dutch language. Paul Wackers and Werenfried Spit helped find and repair bugs. During the further development of the babel system I received much help from Bernd Raichle, for which I am grateful. There are also many contributors for specific languages, which are mentioned in the respective files. Without them, babel just wouldn't exist.

References

- [1] Huda Smitshuijzen Abifares, *Arabic Typography*, Saqi, 2001.
- [2] Johannes Braams, Victor Eijkhout and Nico Poppelier, *The development of national \LaTeX styles*, *TUGboat* 10 (1989) #3, p. 401–406.
- [3] Yannis Haralambous, *Fonts & Encodings*, O'Reilly, 2007.
- [4] Donald E. Knuth, *The \TeX book*, Addison-Wesley, 1986.
- [5] Jukka K. Korpela, *Unicode Explained*, O'Reilly, 2006.
- [6] Leslie Lamport, *\LaTeX , A document preparation System*, Addison-Wesley, 1986.
- [7] Leslie Lamport, in: \TeX hax Digest, Volume 89, #13, 17 February 1989.
- [8] Ken Lunde, *CJKV Information Processing*, O'Reilly, 2nd ed., 2009.
- [9] Edward M. Reingold and Nachum Dershowitz, *Calendrical Calculations: The Ultimate Edition*, Cambridge University Press, 2018.
- [10] Hubert Partl, *German \TeX* , *TUGboat* 9 (1988) #1, p. 70–72.
- [11] Joachim Schrod, *International \LaTeX is ready to use*, *TUGboat* 11 (1990) #1, p. 87–90.
- [12] Apostolos Syropoulos, Antonis Tsolomitis and Nick Sofroniu, *Digital typography using \LaTeX* , Springer, 2002, p. 301–373.
- [13] K.F. Treebus. *Tekstwijzer, een gids voor het grafisch verwerken van tekst*, SDU Uitgeverij ('s-Gravenhage, 1988).