ChatGPT Documentation

Organisation of the repository: structure, naming and categories

Technical documentation · British English
November 2026

1. Introduction

ChatGPT is a conversational artificial intelligence assistant developed by OpenAI. In this repository it was given a specific role: the **organisation of the repository**, that is, defining the folder structure, the naming and the categorisation of the websites. This documentation describes the tool, that role and the resulting structure.

The text describes the function assigned to ChatGPT in the project. The tool's features, plans and interfaces change frequently; consult OpenAI's official material for current details.

Tools in the repository

Tool	Role in this repository
Mullvad VPN	Network layer: privacy and security of the connection when exploring the Surface Web and, as a complement, the dark web
ChatGPT	Organisation of the repository: folder structure, naming and categorisation
Gemini	Choice of the websites that make up the repository
Claude	Writing documentation and reports

2. What ChatGPT Is

Launched in November 2022, ChatGPT converses in natural language and is based on language models of the GPT family. Depending on the plan and configuration, it can:

- generate, summarise, proofread and translate text;
- help write and explain code, including automation scripts;
- analyse data, tables and files uploaded by the user;
- propose structures, taxonomies, lists and work plans;
- search for information on the web and work with images, where these features are available.

3. Role in the Repository: Organisation

The repository, called **WebAtlas**, is an atlas of websites. Its organisation is hierarchical, on four levels: the project root, the network branch (currently **Surface-Web**), the thematic categories and, within each category, one folder per site.

Level	Example content	Function
1. Root	WebAtlas	Starting point of the project
2. Network branch	Surface-Web	Separates the indexed web from other layers
3. Category	News, Sports, Government...	Groups sites by purpose
4. Site	WEB-NNN-Site-Name	One folder for each site

Categories and number of sites

Category folder	Content	Sites
Social-Networks	Social networks and messaging	11
News	Press and news agencies	11
Sports	Sports media, leagues and federations	8
Betting	Betting companies	3
Government	Government portals	6
Intelligence-Investigation	Intelligence, police and security	7
Operating-Systems	Operating systems	10
Communities	Forums and communities	2
Knowledge	Knowledge and science	3
Development-Technology	Development and infrastructure	5
Video-Platforms	Video platforms	1
Web-Portals	Web portals	1
Total		**68**

4. Naming Convention

- **Site folders** follow the pattern **WEB-NNN-Site-Name**: the WEB prefix, a three-digit number and the name with words separated by hyphens.
- **Single, global numbering**: the numbers run from 001 to 068 and do not restart in each category.
- **Numbering is not contiguous within categories**: the repository grew in stages, and the first sites received the lowest numbers across different categories. Later additions continued the sequence. The number therefore indicates the order of inclusion, not the position within the category.
- **Category names** are in English, hyphenated, with no accents or spaces, which avoids problems in systems and scripts.
- **In texts and reports**, each site is cited by name only, without the identifier. The identifier exists to organise the folders.

5. How ChatGPT Contributes to the Organisation

- **Taxonomy proposals**: suggesting clear, mutually exclusive categories and deciding where each site belongs (for example, separating portals, video platforms and communities).
- **Standardisation**: keeping a single naming pattern, avoiding variations in capitalisation, accents and spaces.
- **Automation**: generating shell or Python scripts that create the folder tree from a list.

- **Indexes and documentation**: producing a README file and up-to-date index tables.
- **Checking**: detecting duplicates, repeated or missing numbers and naming inconsistencies.
- **Evolving the structure**: proposing new branches as the project grows.

6. Possible Developments of the Structure

- Additional branches alongside Surface-Web, such as one dedicated to the dark web, supported by the Tor Browser documentation in this series.
- A profile file inside each site folder, with fields such as name, category, official address, country of origin, date of last check and notes.
- A global index table, allowing filtering by category, country and type of organisation.
- Version control with Git to record the history of changes to the structure.

7. Limitations and Precautions

- Language models can make mistakes or invent information; every proposal should be reviewed by a person.
- Structural changes need to be applied carefully so as not to break existing links, scripts or references.
- Avoid sending sensitive or confidential data; review the tool's privacy settings.
- Organisation is a project decision: the tool suggests and the team decides.

8. Good Practice

- Define the naming rules before creating many folders.
- Record the convention in a README file at the root.
- Ask ChatGPT to justify each category suggestion and check the justifications.
- Reserve numbering for new sites without reusing old numbers.

9. Conclusion

Organisation is what turns a list of websites into a navigable atlas. With the help of ChatGPT, WebAtlas gained a hierarchical structure, a consistent naming convention and a clear path for growth.