


Advanced Computer Vision



Supervised Learning (A Review)

Machine Learning Problems

Supervised Learning

Unsupervised Learning

Discrete

classification or
categorization

clustering

Continuous


regression

dimensionality
reduction



ImageNet

- Images for each category of WordNet
- 1000 classes
- 1.2mil images
- 100k test
- Top 5 error



Dataset split

Training Images



- Train classifier

Validation Images



- Measure error
- Tune model hyperparameters

Testing Images



- Secret labels
- Measure error

Random train/validate splits = cross validation

Training

Training Images



Image Features

Training Labels

Training

Learned classifier

Testing



Test Image

Image Features



Apply classifier

Prediction

Slide credit: D. Hoiem and L. Lazebnik

Features

- Raw pixels
- Histograms
- Templates
- SIFT descriptors
 - GIST
 - ORB
 - HOG
 - CNN....



Training

Training Images



Image Features



Training Labels



Training



Learned classifier

Testing



Test Image



Image Features



Apply classifier




Prediction

Recognition task and supervision

- Images in the training set must be annotated with the “correct answer” that the model is expected to produce

Contains a motorbike



Spectrum of supervision


Less

More



E.G., ImageNet

E.G., MS Coco



Unsupervised

“Weakly” supervised

Fully supervised

Fuzzy; definition depends on task

‘Semi-supervised’: small partial labeling

Training

Training Images



Image Features



Training Labels



Training



Learned classifier

Testing



Test Image



Image Features



Apply classifier



Prediction

Slide credit: D. Hoiem and L. Lazebnik

The machine learning framework


- Apply a prediction function to a feature representation of the image to get the desired output:

$$f(\text{apple image}) = \text{"apple"}$$

$$f(\text{tomato image}) = \text{"tomato"}$$

$$f(\text{cow image}) = \text{"cow"}$$

The machine learning framework



Training: Given a *training set* of labeled examples:

$$\{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_N, y_N)\}$$


Estimate the prediction function f by minimizing the prediction error on the training set.

Testing: Apply f to a unseen *test example* \mathbf{x}_u and output the predicted value $y_u = f(\mathbf{x}_u)$ to *classify* \mathbf{x}_u .


Classification

Assign \mathbf{x} to one of two (or more) classes.

A decision rule divides input space into *decision regions* separated by *decision boundaries*.



Classifiers: Nearest neighbor




$f(\mathbf{x}) = \text{label of the training example nearest to } \mathbf{x}$

- All we need is a distance function for our inputs
- No training required!
- What does the decision boundary look like?

Decision boundary for Nearest Neighbor Classifier





Divides input space into *decision regions* separated by *decision boundaries* – *Voronoi*.




from Duda *et al.*

Voronoi partitioning
of feature space
for two-category
2D and 3D data

k-nearest neighbor



Classifiers: Linear




Find a *linear function* to separate the classes

Classifiers: Linear SVM

Find a *linear function* to separate the classes:

$$f(\mathbf{x}) = \text{sgn}(\mathbf{w} \cdot \mathbf{x} + b)$$




Classifiers: Linear SVM

Find a *linear function* to separate the classes:

$$f(\mathbf{x}) = \text{sgn}(\mathbf{w} \cdot \mathbf{x} + b)$$

How?

\mathbf{X} = all data points




Define *hyperplane* $\mathbf{tX} - \mathbf{b} = 0$, where \mathbf{t} is tangent to hyperplane.

Minimize $\|\mathbf{t}\|$ s.t. $\mathbf{tX} - \mathbf{b}$ produces correct label for all \mathbf{X}

Classifiers: Linear SVM

Find a *linear function* to separate the classes:

$$f(\mathbf{x}) = \text{sgn}(\mathbf{w} \cdot \mathbf{x} + b)$$




What if my data are not linearly separable?


Introduce flexible 'hinge' loss (or 'soft-margin')

Nonlinear SVMs


- Datasets that are linearly separable work out great:



- But what if the dataset is just too hard?




- We can map it to a higher-dimensional space:



Nonlinear SVMs

Map the original input space to some higher-dimensional feature space where the training set is separable:



What about multi-class SVMs?

- Unfortunately, there is no “definitive” multi-class SVM.
- In practice, we combine multiple two-class SVMs
- One vs. others
 - Training: learn an SVM for each class vs. the others
 - Testing: apply each SVM to test example and assign to it the class of the SVM that returns the highest decision value
- One vs. one
 - Training: learn an SVM for each pair of classes
 - Testing: each learned SVM “votes” for a class to assign to the test example

SVMs: Pros and cons

- Pros
 - Many publicly available SVM packages:
<http://www.kernel-machines.org/software>
 - Kernel-based framework is very powerful, flexible
 - SVMs work very well in practice, even with very small training sample sizes
- Cons
 - No “direct” multi-class SVM, must combine two-class SVMs
 - Computation, memory
 - During training time, must compute matrix of kernel values for every pair of examples
 - Learning can take a very long time for large-scale problems

What to remember about classifiers

- No free lunch: machine learning algorithms are tools, not dogmas
- Try simple classifiers first
- Better to have smart features and simple classifiers than simple features and smart classifiers
- Use increasingly powerful classifiers with more training data (bias-variance tradeoff)

Training

Training Images



Image Features

Training Labels

Training

Learned classifier

Testing



Test Image

Image Features

Apply classifier

Prediction

Features and distance measures
define visual similarity.

Training labels
dictate that examples are the same or different.

Classifiers
learn weights (or parameters) of features and distance measures...
so that visual similarity predicts label similarity.

Generalization



Training set (labels known)



Test set (labels unknown)

How well does a learned model generalize from the data it was trained on to a new test set?

Generalization Error


Bias:

- Difference between the expected (or average) prediction of our model and the correct value.
- Error due to inaccurate assumptions/simplifications.

Variance:


- Amount that the estimate of the target function will change if different training data was used.

Bias/variance trade-off




Generalization Error Effects

- **Underfitting:** model is too “simple” to represent all the relevant class characteristics
 - High bias (few degrees of freedom) and low variance
 - High training error and high test error




Generalization Error Effects

- **Overfitting:** model is too “complex” and fits irrelevant characteristics (noise) in the data
 - Low bias (many degrees of freedom) and high variance
 - Low training error and high test error




Bias-Variance Trade-off



Models with too few parameters are inaccurate because of a large bias.


- Not enough flexibility!
- Too many assumptions




Models with too many parameters are inaccurate because of a large variance.

- Too much sensitivity to the sample.
- Slightly different data -> very different function.

Bias-variance tradeoff




Bias-variance tradeoff




Effect of Training Size

Fixed prediction model




Discriminative



“Learn the data boundary”

Generative



“Represent the data + boundary”

Bayesian methods:
Condition model on
data probabilistically

Many classifiers to choose from...

- K-nearest neighbor
- SVM
- Naïve Bayes
- Bayesian network
- Logistic regression
- Randomized Forests
- Boosted Decision Trees
- Restricted Boltzmann Machines
- Neural networks
- Deep Convolutional Network

Which is
the best?

Claim:

It is more important to have more or better labeled data than to use a different supervised learning technique.

*Again, deep learning may be an exception here for the same reason, but deep learning needs a lot of labeled data in the first place.

“The Unreasonable Effectiveness of Data” - Norvig