


# *Linux distribution*

A **Linux distribution** (often abbreviated as **distro**) is an operating system made from a software collection that is based upon the Linux kernel and, often, a package management system. Linux users usually obtain their operating system by downloading one of the Linux distributions, which are available for a wide variety of systems ranging from embedded devices (for example, OpenWrt)

and personal computers (for example, Linux Mint) to powerful supercomputers (for example, Rocks Cluster Distribution).



*Ubuntu, one of the most popular desktop Linux distributions*

A typical Linux distribution comprises a Linux kernel, GNU tools and libraries, additional software, documentation, a window system (the most common being

the X Window System), a window manager, and a desktop environment.

Most of the included software is free and open-source software made available both as compiled binaries and in source code form, allowing modifications to the original software. Usually, Linux distributions optionally include some proprietary software that may not be available in source code form, such as binary blobs required for some device drivers.<sup>[1]</sup>

A Linux distribution may also be described as a particular assortment of application and utility software (various GNU tools and


libraries, for example), packaged together with the Linux kernel in such a way that its capabilities meet the needs of many users.<sup>[2]</sup> The software is usually adapted to the distribution and then packaged into software packages by the distribution's maintainers. The software packages are available online in so-called repositories, which are storage locations usually distributed around the world.<sup>[3][4]</sup> Beside glue components, such as the distribution installers (for example, Debian-Installer and Anaconda) or the package management systems, there are only very few packages that are originally written

from the ground up by the maintainers of a Linux distribution.

Almost one thousand [Linux distributions](#) exist.<sup>[5][6]</sup> Because of the huge availability of software, distributions have taken a wide variety of forms, including those suitable for use on desktops, servers, laptops, netbooks, mobile phones and tablets,<sup>[7][8]</sup> as well as minimal environments typically for use in embedded systems.<sup>[9][10]</sup> There are commercially-backed distributions, such as [Fedora](#) ([Red Hat](#)), [openSUSE](#) ([SUSE](#)) and [Ubuntu](#) ([Canonical Ltd.](#)), and entirely community-driven distributions, such as

Debian, Slackware, Gentoo and Arch Linux. Most distributions come ready to use and pre-compiled for a specific instruction set, while some distributions (such as Gentoo) are distributed mostly in source code form and compiled locally during installation.<sup>[11]</sup>

## History



*GNUclad generated SVG of current Linux distributions*

*timeline as of December 2020<sup>[12]</sup>*

Linus Torvalds developed the Linux kernel and distributed its first version, 0.01, in 1991. Linux was initially distributed as source code only, and later as a pair of downloadable floppy disk images – one bootable and containing the Linux kernel itself, and the other with a set of GNU utilities and tools for setting up a file system. Since the installation procedure was complicated, especially in the face of growing amounts of available software, distributions sprang up to simplify this.<sup>[13]</sup>

Early distributions included the following:



- H. J. Lu's "Boot-root", the  
aforementioned disk image pair with the  
kernel and the absolute minimal tools to  
get started, in late 1991<sup>[14]</sup>
- MCC Interim Linux, which was made  
available to the public for download in  
February 1992
- Softlanding Linux System (SLS),  
released in 1992, was the most  
comprehensive distribution for a short  
time, including the X Window System
- Yggdrasil Linux/GNU/X, a commercial  
distribution first released in December  
1992


The two oldest and still active distribution projects started in 1993. The SLS distribution was not well maintained, so in July 1993 a new distribution, called Slackware and based on SLS, was released by Patrick Volkerding.<sup>[15]</sup> Also dissatisfied with SLS, Ian Murdock set to create a free distribution by founding Debian, which had its first release in December 1993.<sup>[16]</sup>

Users were attracted to Linux distributions as alternatives to the DOS and Microsoft Windows operating systems on IBM PC compatible computers, Mac OS on the Apple Macintosh, and proprietary versions

of Unix. Most early adopters were familiar with Unix from work or school. They embraced Linux distributions for their low (if any) cost, and availability of the source code for most or all of the software included.

As of 2017, Linux has become more popular in server and embedded devices markets than in the desktop market. For example, Linux is used on over 50% of web servers,<sup>[17]</sup> whereas its desktop market share is about 3.7%.<sup>[18]</sup>

## Components



*A Linux distribution is usually built around a package management system, which puts together the Linux kernel, free and open-source software, and occasionally some proprietary software.*

Many Linux distributions provide an installation system akin to that provided with other modern operating systems. On the other hand, some distributions, including Gentoo Linux, provide only the binaries of a basic kernel, compilation tools, and an installer; the installer compiles all the requested software for

the specific architecture of the user's computer, using these tools and the provided source code.

## Package management

...

Distributions are normally segmented into *packages*. Each package contains a specific application or service. Examples of packages are a library for handling the PNG image format, a collection of fonts or a web browser.

The package is typically provided as compiled code, with installation and removal of packages handled by a

package management system (PMS) rather than a simple file archiver. Each package intended for such a PMS contains meta-information such as a package description, version, and "dependencies". The package management system can evaluate this meta-information to allow package searches, to perform an automatic upgrade to a newer version, to check that all dependencies of a package are fulfilled, and/or to fulfill them automatically.

Although Linux distributions typically contain much more software than proprietary operating systems, it is normal

for local administrators to also install software not included in the distribution. An example would be a newer version of a software application than that supplied with a distribution, or an alternative to that chosen by the distribution (for example, KDE Plasma Workspaces rather than GNOME or vice versa for the user interface layer). If the additional software is distributed in source-only form, this approach requires local compilation. However, if additional software is locally added, the "state" of the local system may fall out of synchronization with the state of the package manager's database. If so, the local administrator will be required to take

additional measures to ensure the entire system is kept up to date. The package manager may no longer be able to do so automatically.

Most distributions install packages, including the kernel and other core operating system components, in a predetermined configuration. Few now require or even permit configuration adjustments at first install time. This makes installation less daunting, particularly for new users, but is not always acceptable. For specific requirements, much software must be carefully configured to be useful, to work



correctly with other software, or to be secure, and local administrators are often obliged to spend time reviewing and reconfiguring assorted software.

Some distributions go to considerable lengths to specifically adjust and customize most or all of the software included in the distribution. Not all do so. Some distributions provide configuration tools to assist in this process.

By replacing *everything* provided in a distribution, an administrator may reach a "distribution-less" state: everything was retrieved, compiled, configured, and

installed locally. It is possible to build such a system from scratch, avoiding a distribution altogether. One needs a way to generate the first binaries until the system is self-hosting. This can be done via compilation on another system capable of building binaries for the intended target (possibly by cross-compilation). For example, see Linux From Scratch.

## Types and trends

In broad terms, Linux distributions may be:

- Commercial or non-commercial

- Designed for enterprise users, power users, or for home users
- Supported on multiple types of hardware, or platform-specific, even to the extent of certification by the platform vendor
- Designed for servers, desktops, or embedded devices
- General purpose or highly specialized toward specific machine functionalities (e.g. firewalls, network routers, and computer clusters)
- Targeted at specific user groups, for example through language internationalization and localization, or

through inclusion of many music production or scientific computing packages

- Built primarily for security, usability, portability, or comprehensiveness
- Standard release or rolling release, see below.

The diversity of Linux distributions is due to technical, organizational, and philosophical variation among vendors and users. The permissive licensing of free software means that any user with sufficient knowledge and interest can customize an existing distribution or design one to suit his or her own needs.

# Rolling distributions

...

Rolling Linux distributions are kept updated using small and frequent updates. The terms *partially rolling* and *partly rolling* (along with synonyms *semi-rolling* and *half-rolling*), *fully rolling*, *truly rolling* and *optionally rolling* are sometimes used by software developers and users.<sup>[19][20][21][22][23][24]</sup>

Repositories of rolling distributions usually contains very recent software releases – often the latest stable software releases available. They have pseudo-releases and installation media that are simply a

snapshot of the software distribution at the time of the release of the installation image. Typically, a rolling release operating system installed from an older installation medium can be fully updated post-installation to a current state.

Depending on the use case, there can be pros and cons to both standard release and rolling release software development methodologies.<sup>[25]</sup>

In terms of the software development process, standard releases require significant development effort being spent on keeping old versions up to date due to

propagating bug fixes back to the newest branch, versus focusing more on the newest development branch. Also, unlike rolling releases, standard releases require more than one code branch to be developed and maintained, which increases the software development and software maintenance workload of the software developers and software maintainers.

On the other hand, software features and technology planning are easier in standard releases due to a better understanding of upcoming features in the next version(s). Software release cycles can also be

synchronized with those of major upstream software projects, such as desktop environments.

As far as the user experience, standard releases are often viewed as more stable and bug-free since software conflicts can be more easily addressed and the software stack more thoroughly tested and evaluated, during the software development cycle.<sup>[25][26]</sup> For this reason, they tend to be the preferred choice in enterprise environments and mission-critical tasks.<sup>[25]</sup>



However, rolling releases offer more current software which can also provide increased stability and fewer software bugs along with the additional benefits of new features, greater functionality, faster running speeds, and improved system and application security. Regarding software security, the rolling release model can have advantages in timely security updates, fixing system or application security bugs and vulnerabilities, that standard releases may have to wait till the next release for or patch in various versions. In a rolling release distribution, where the user has *chosen* to run it as a highly dynamic system, the constant flux

of software packages can introduce new unintended vulnerabilities.<sup>[25]</sup>

## Installation-free distributions (live CD/USB)

---

A "live" distribution is a Linux distribution that can be booted from removable storage media such as optical discs or USB flash drives, instead of being installed on and booted from a hard disk drive. The portability of installation-free distributions makes them advantageous for applications such as demonstrations, borrowing someone else's computer,

rescue operations, or as installation media for a standard distribution.

When the operating system is booted from a read-only medium such as a CD or DVD, any user data that needs to be retained between sessions cannot be stored on the boot device but must be written to another storage device, such as a USB flash drive or a hard disk drive.<sup>[27]</sup>

Many Linux distributions provide a "live" form in addition to their conventional form, which is a network-based or removable-media image intended to be used only for installation; such distributions include

SUSE, Ubuntu, Linux Mint, MEPIS and Fedora. Some distributions, including Knoppix, Puppy Linux, Devil-Linux, SuperGamer, SliTaz GNU/Linux and dyne:bolic, are designed primarily for live use. Additionally, some minimal distributions can be run directly from as little space as one floppy disk without the need to change the contents of the system's hard disk drive.<sup>[28]</sup>

## Examples

The website DistroWatch lists many Linux distributions, and displays some of the ones that have the most web traffic on the

site. The Wikimedia Foundation released an analysis of the browser User Agents of visitors to WMF websites until 2015, which includes details of the most popular Operating System identifiers, including some Linux distributions.<sup>[29]</sup> Many of the popular distributions are listed below.

## **Widely used GNU-based or GNU-compatible distributions**

...

- Debian, a non-commercial distribution and one of the earliest, maintained by a volunteer developer community with a strong commitment to free software

principles and democratic project management.

- Knoppix, the first Live CD distribution to run completely from removable media without installation to a hard disk, derived from Debian.
- Linux Mint Debian Edition (LMDE) uses Debian packages directly (rather than Ubuntu's)
- Ubuntu, a desktop and server distribution derived from Debian, maintained by British company Canonical Ltd.

- there are several distributions based on Ubuntu that mainly replace the GNOME stock desktop environment, like:  
Kubuntu based on KDE,  
Lubuntu based on LXQT,  
Xubuntu based on XFCE,  
Ubuntu MATE based on MATE,  
Ubuntu Budgie based on Budgie. Other official forks have specific uses like: Ubuntu Kylin for Chinese-speaking users, or Ubuntu Studio for media content creators.
- Linux Mint, a distribution based on and compatible with

Ubuntu. Supports multiple desktop environments, among others GNOME Shell fork Cinnamon and GNOME 2 fork MATE.

- Fedora, a community distribution sponsored by American company Red Hat and the successor to the company's previous offering, Red Hat Linux. It aims to be a technology testbed for Red Hat's commercial Linux offering, where new open source software is prototyped, developed, and tested in a communal setting before maturing into Red Hat Enterprise Linux.



- Red Hat Enterprise Linux (RHEL), a derivative of Fedora, maintained and commercially supported by Red Hat. It seeks to provide tested, secure, and stable Linux server and workstation support to businesses.
  - CentOS, a distribution derived from the same sources used by Red Hat, maintained by a dedicated volunteer community of developers with both 100% Red Hat-compatible versions and an upgraded version that is not always 100% upstream compatible.

- Oracle Linux, which is a derivative of Red Hat Enterprise Linux, maintained and commercially supported by Oracle
- Mandriva Linux was a Red Hat Linux derivative popular in several European countries and Brazil, backed by the French company of the same name. After the company went bankrupt, it was superseded by OpenMandriva Lx,<sup>[30][31]</sup> although a number of derivatives now have a larger user base.
  - Mageia, a community fork of Mandriva Linux created in 2010<sup>[31]</sup>

- PCLinuxOS, a derivative of Mandriva, which grew from a group of packages into a community-spawned desktop distribution
- openSUSE, a community distribution mainly sponsored by German company SUSE.
  - SUSE Linux Enterprise, derived from openSUSE, maintained and commercially supported by SUSE
- Arch Linux, a rolling release distribution targeted at experienced Linux users and maintained by a volunteer community, offers official binary packages and a wide range of unofficial user-submitted

source packages. Packages are usually defined by a single PKGBUILD text file.

- Manjaro Linux, a derivative of Arch Linux that includes a graphical installer and other ease-of-use features for less experienced Linux users. Rolling release packages from Arch repositories are held for further testing.<sup>[32]</sup>
- Gentoo, a distribution targeted at power users, known for its FreeBSD Ports-like automated system for compiling applications from source code
- Slackware, created in 1993, one of the first Linux distributions and among the

earliest still maintained, committed to remain highly Unix-like and easily modifiable by end users<sup>[33]</sup>

## Linux kernel based operating systems

...

- Android, Google's commercial operating system based on Android OSP that runs on many devices such as smart phones, smart TVs, set-top boxes.
- Chrome OS, Google's commercial operating system based on Chromium OS that only runs on Chromebooks, Chromeboxes and tablet computers. Like Android, it has the Google Play Store and other Google apps. Support

for applications that require GNU compatibility is available through a virtual machine called Crostini and referred to by Google as Linux support, see Chromebook#Integration with Linux.

Whether the above operating system count as a "Linux distribution" is a controversial topic. They use the Linux kernel, so the Linux Foundation<sup>[34]</sup> and Chris DiBona,<sup>[35]</sup> Google's open source chief, agree that Android is a Linux distribution; others, such as Google engineer Patrick Brady, disagree by noting the lack of support for many GNU tools in Android, including glibc.<sup>[36]</sup>

Other Linux kernel based operating systems include Cyanogenmod, its fork LineageOS, Android-x86 and recently Tizen and Mer/Sailfish OS.

## **Lightweight distributions**

...

Lightweight Linux distributions are those that have been designed with support for older hardware in mind, allowing older hardware to still be used productively, or, for maximum possible speed in newer hardware by leaving more resources available for use by applications.

Examples include Tiny Core Linux, Puppy Linux and Slitaz.

# Niche distributions

...

Other distributions target specific niches, such as:

- *Routers* – for example, targeted by the tiny embedded router distribution OpenWrt
- Internet of things – for example, targeted by Ubuntu Core<sup>[37]</sup>
- Home theater PCs – for example, targeted by KnoppMyth, Kodi (former XBMC) and Mythbuntu
- *Specific platforms* – for example, Raspberry Pi OS targets the Raspberry Pi platform



- *Education* – examples are Edubuntu and Karoshi, server systems based on PCLinuxOS
- *Scientific computer servers and workstations* – for example, targeted by Scientific Linux
- *Digital audio workstations for music production* – for example, targeted by Ubuntu Studio
- *Computer Security, digital forensics and penetration testing* – examples are Kali Linux and Parrot Security OS
- *Privacy and anonymity* – for example, targeted by Tails, Whonix, Qubes, or FreedomBox

- *Offline use* – for example, Endless OS
- Microsoft's Azure Sphere

## Interdistribution issues

The Free Standards Group is an organization formed by major software and hardware vendors that aims to improve interoperability between different distributions. Among their proposed standards are the Linux Standard Base, which defines a common ABI and packaging system for Linux, and the Filesystem Hierarchy Standard which recommends a standard filenames chart, notably the basic directory names found on the root of the tree of any Linux

filesystem. Those standards, however, see limited use, even among the distributions developed by members of the organization.

The diversity of Linux distributions means that not all software runs on all distributions, depending on what libraries and other system attributes are required.

Packaged software and software repositories are usually specific to a particular distribution, though cross-installation is sometimes possible on closely related distributions.

## Tools for choosing a

# distribution

---

The process of constantly switching between distributions is often referred to as "distro hopping".<sup>[38]</sup> Virtual machines such as VirtualBox and VMware Workstation virtualize hardware allowing users to test live media on a virtual machine. Some websites like DistroWatch offer lists of distributions, and link to screenshots of operating systems as a way to get a first impression of various distributions.

There are tools available to help people select an appropriate distribution, such as several versions of the Linux Distribution

Chooser,<sup>[39]</sup> and the universal package search tool *whohas*.<sup>[40]</sup> There are easy ways to try out several Linux distributions before deciding on one: Multi Distro is a Live CD that contains nine space-saving distributions.<sup>[41]</sup>

## Installation

There are several ways to install a Linux distribution. Nowadays, the most common method of installing Linux is by booting from a live USB memory stick, which can be created by using a USB image writer application and the ISO image, which can be downloaded from the various Linux

distribution websites. DVD disks, CD disks, network installations and even other hard drives can also be used as "installation media".<sup>[42]</sup>

Early Linux distributions were installed using sets of floppies but this has been abandoned by all major distributions.

Nowadays most distributions offer CD and DVD sets with the vital packages on the first disc and less important packages on later ones. They usually also allow installation over a network after booting from either a set of floppies or a CD with only a small amount of data on it.<sup>[43]</sup>

New users tend to begin by partitioning a hard drive in order to keep their previously installed operating system. The Linux distribution can then be installed on its own separate partition without affecting previously saved data.

In a Live CD setup, the computer boots the entire operating system from CD without first installing it on the computer's hard disk. Some distributions have a Live CD *installer*, where the computer boots the operating system from the disk, and then proceeds to install it onto the computer's hard disk, providing a seamless transition

from the OS running from the CD to the OS running from the hard disk.

Both servers and personal computers that come with Linux already installed are available from vendors including Hewlett-Packard, Dell and System76.

On embedded devices, Linux is typically held in the device's firmware and may or may not be consumer-accessible.

Anaconda, one of the more popular installers, is used by Red Hat Enterprise Linux, Fedora (which uses the Fedora Media Writer) and other distributions to simplify the installation process. Debian,



Ubuntu and many others use Debian-Installer.

## **Installation via an existing operating system** ...

Some distributions let the user install Linux on top of their current system, such as WinLinux or coLinux. Linux is installed to the Windows hard disk partition, and can be started from inside Windows itself.

Virtual machines (such as VirtualBox or VMware) also make it possible for Linux to be run inside another OS. The VM software simulates a separate computer onto which

the Linux system is installed. After installation, the virtual machine can be booted as if it were an independent computer.

Various tools are also available to perform full dual-boot installations from existing platforms without a CD, most notably:

- The (now deprecated) Wubi installer, which allows Windows users to download and install Ubuntu or its derivatives into a FAT32 or an NTFS partition without an installation CD, allowing users to easily dual boot between either operating system on the

same hard drive without losing data.

Replaced by Ubiquity.

- Win32-loader, which is in the process of being integrated in official Debian CDs/DVDs, and allows Windows users to install Debian without a CD, though it performs a network installation and thereby requires repartitioning<sup>[44]</sup>
- UNetbootin, which allows Windows and Linux users to perform similar no-CD network installations for a wide variety of Linux distributions and additionally provides live USB creation support

## Proprietary software

Some specific proprietary software products are not available in any form for Linux. As of September 2015, the Steam gaming service has 1,500 games available on Linux, compared to 2,323 games for Mac and 6,500 Windows games.<sup>[45][46][47]</sup> Emulation and API-translation projects like Wine and CrossOver make it possible to run non-Linux-based software on Linux systems, either by emulating a proprietary operating system or by translating proprietary API calls (e.g., calls to Microsoft's Win32 or DirectX APIs) into native Linux API calls. A virtual machine can also be used to run a proprietary OS (like Microsoft Windows) on top of Linux.

# OEM contracts

---

Computer hardware is usually sold with an operating system other than Linux already installed by the original equipment manufacturer (OEM). In the case of IBM PC compatibles the OS is usually Microsoft Windows; in the case of Apple Macintosh computers it has always been a version of Apple's OS, currently macOS; Sun Microsystems sold SPARC hardware with the Solaris installed; video game consoles such as the Xbox, PlayStation, and Wii each have their own proprietary OS. This limits Linux's market share: consumers are unaware that an alternative

exists, they must make a conscious effort to use a different operating system, and they must either perform the actual installation themselves, or depend on support from a friend, relative, or computer professional.

However, it is possible to buy hardware with Linux already installed. Lenovo, Hewlett-Packard, Dell, Affordy,<sup>[48]</sup> Purism, Pine64 and System76 all sell general-purpose Linux laptops.<sup>[49]</sup> Custom-order PC manufacturers will also build Linux systems, but possibly with the Windows key on the keyboard. Fixstars Solutions (formerly Terra Soft) sells Macintosh

computers and PlayStation 3 consoles with Yellow Dog Linux installed.

It is more common to find embedded devices sold with Linux as the default manufacturer-supported OS, including the Linksys NSLU2 NAS device, TiVo's line of personal video recorders, and Linux-based cellphones (including Android smartphones), PDAs, and portable music players.

The current Microsoft Windows license lets the manufacturer determine the refund policy.<sup>[50]</sup> With previous versions of Windows, it was possible to obtain a

refund if the manufacturer failed to provide the refund by litigation in the small claims courts.<sup>[51]</sup> On February 15, 1999, a group of Linux users in Orange County, California held a "Windows Refund Day" protest in an attempt to pressure Microsoft into issuing them refunds.<sup>[52]</sup> In France, the Linuxfrench and AFUL (French speaking Libre Software Users' Association) organizations along with free software activist Roberto Di Cosmo started a "Windows Detax" movement,<sup>[53]</sup> which led to a 2006 petition against "racketiciels" (translation: Racketware) with 39,415 signatories and the DGCCRF branch of the French government filing



several complaints against bundled software. On March 24, 2014, a new international petition was launched by AFUL on the Avaaz platform,<sup>[54]</sup> translated into several languages and supported by many organizations around the world.

## Statistics

There are no official figures on popularity, adoption, downloads or installed base of Linux distributions.

There are also no official figures for the total number of Linux systems,<sup>[55][56]</sup> partly due to the difficulty of quantifying the number of PCs running Linux (see Desktop

Linux adoption), since many users download Linux distributions. Hence, the sales figures for Linux systems and commercial Linux distributions indicate a much lower number of Linux systems and level of Linux adoption than is the case; this is mainly due to Linux being free and open source software that can be downloaded free of charge.<sup>[55][57]</sup> A Linux Counter Project had kept track of a running guesstimate of the number of Linux systems, but did not distinguish between rolling release and standard release distributions. It ceased operation in August 2018, though a few related blog

posts were created through October 2018.<sup>[58]</sup>

Desktop usage statistical reports for particular Linux distributions have been collected and published in January 2020<sup>[59]</sup> by the Linux Hardware Project.

## See also

- [Comparison of Linux distributions](#)
- [Lightweight Linux distribution](#)
- [List of Linux distributions](#)

## References

1. *"Explaining Why We Don't Endorse*

*Other Systems" . gnu.org. June 30, 2014. Retrieved January 5, 2015.*

2. *"Linux Operating Systems: Distributions" . swift.siphos.be. November 27, 2014. Retrieved January 8, 2015.*

3. *Chris Hoffman (June 27, 2012). "HTG Explains: How Software Installation & Package Managers Work On Linux" . howtogeek.com. Retrieved January 15, 2015.*

4. *"The status of CentOS mirrors" . centos.org. January 15, 2015. Retrieved January 15, 2015.*

5. *"The LWN.net Linux Distribution List" . LWN.net. Retrieved September 11, 2015.*
6. *"DistroWatch.com: Put the fun back into computing. Use Linux, BSD" . distrowatch.com.*
7. *Jim Martin. "How to install Ubuntu Touch on your Android phone or tablet" . PC Advisor.*
8. *David Hayward. "Install Linux on your x86 tablet: five distros to choose from" . TechRadar.*

9. *Brian Proffitt (February 3, 2010). "The Top 7 Best Linux Distributions for You" . linux.com. Archived from the original on January 5, 2015. Retrieved January 11, 2015.*
10. *Eric Brown (November 4, 2014). "Mobile Linux Distros Keep on Morphing" . linux.com. Retrieved January 11, 2015.*
11. *"Debian and Other Distros" . debian.org. December 7, 2013. Retrieved January 5, 2015.*
12. *"Linux Distributions Timeline" . FabioLolix. Retrieved December 23, 2020.*

13. *Berlich, Ruediger (April 2001). "ALL YOU NEED TO KNOW ABOUT... The early history of Linux, Part 2, Re: distribution" (PDF). LinuxUser. Retrieved May 4, 2013.*
14. *"A Short History of Linux Distributions [LWN.net]" . lwn.net. Retrieved September 30, 2018.*
15. *"The Slackware Linux Project: Slackware Release Announcement" . Slackware.com. July 16, 1993. Retrieved July 29, 2011.*
16. *"A Brief History of Debian - Debian Releases" . debian.org. May 4, 2013. Retrieved July 19, 2014.*

17. *"Usage statistics and market share of Unix for websites" . w3techs.org. November 5, 2016. Retrieved November 5, 2016.*
18. *"Browser & Platform Market Share January 2017" . w3counter.com. January 31, 2017. Retrieved February 21, 2017.*
19. *The Chakra Project. "half-rolling development model" . chakra-project-org.*
20. *The Chakra Project. "The Chakra Project Wiki: FAQs" . chakra-project-org. Archived from the original on August 27, 2011.*



21. *"Fedora Release Life-cycle Proposals" . fedoraproject.org.*
22. *"Fedora Development Mailing List" . fedoraproject.org.*
23. *Rev. "Linux Certification – Preparation" . walkingwithzen.com.*
24. *"Why openSUSE" . opensuse.org.*
25. *Chad Perrin (August 2, 2010), Point-release vs rolling-release: developer, user and security considerations , techrepublic.com, retrieved September 6, 2011*

26. *K.Mandla (March 9, 2007). "The pros and cons of a rolling release" . kmandla.wordpress.com. Retrieved January 26, 2012.*
27. *Jonathan Corbet (June 15, 2011). "Debating overlaysfs" . LWN.net. Retrieved January 5, 2015.*
28. *"PiTuX – a micro serial terminal distro" . asashi.net. Retrieved January 6, 2015.*
29. *"Wikimedia Traffic Analysis Report - Operating Systems" . stats.wikimedia.org. Retrieved July 23, 2018.*

30. *"Mandriva Linux will return to the community" . mandriva.com. Archived from the original on May 23, 2015. Retrieved January 14, 2015.*
31. *"The LWN.net Linux Distribution List" . LWN.net. Retrieved January 15, 2015.*
32. *"New Security Policy Report" . manjaro.github.io. Manjaro Linux. Archived from the original on December 3, 2017. Retrieved January 12, 2015.*
33. *"Slackware Linux Basics, Chapter 2" (PDF). rlworkman.net. Retrieved July 23, 2018.*

34. *Ask AC: Is Android Linux?. "Ask AC: Is Android Linux?" . Android Central. Retrieved March 14, 2013.*
35. *derStandard.at. "Google: "Android is the Linux desktop dream come true" - Suchmaschinen - derStandard.at "Web" . Derstandard.at. Retrieved March 14, 2013.*
36. *Paul, Ryan (February 24, 2009). "Dream(sheep++): A developer's introduction to Google Android" . Ars Technica. Retrieved April 22, 2013.*
37. *Dieguez Castro, Jose (2016). Introducing Linux Distros. Apress. pp. 49, 345. ISBN 978-1-4842-1393-3.*

38. *"How I stopped distro hopping" . Linux Today.*
39. *"Distro Selector" . Desktop Linux At Home. Archived from the original on July 22, 2011. Retrieved July 29, 2011.*
40. *"Philipp's Homepage: whohas" . Philippwesche.org. February 11, 2010. Retrieved July 29, 2011.*
41. *"Multi Distro is Linux times 9 on a single CD-R" . Linux.com. Retrieved July 29, 2011.*
42. *"2.4. Installation Media" . www.debian.org. Retrieved July 23, 2018.*

43. *"Network install from a minimal CD" .  
Debian. Retrieved July 29, 2011.*
44. *Debian Webmaster,  
webmaster@debian.org. "Debian -  
Details of package win32-loader in  
Lenny" . Packages.debian.org.  
Retrieved July 29, 2011.*
45. *Jared Newman (September 21, 2015).  
"Steam for Linux tops 1,500 games as  
launch of Valve's Steam Machines  
nears" . PCWorld.*
46. *"Steam's living room hardware blitz  
gets off to a muddy start" . Ars  
Technica.*

47. *"The state of Linux gaming in the SteamOS era" . Ars Technica.*
48. *"Affordy - TITAN Computers" . Shop.affordy.com. Archived from the original on May 29, 2009. Retrieved July 29, 2011.*
49. *"Laptops/Notebooks with Linux Preinstalled" . Mcelrath.org. June 10, 2010. Retrieved July 29, 2011.*
50. *"Microsoft Software License Terms: Windows 7 Professional" (PDF).*
51. *"Getting a Windows Refund in California Small Claims Court" . Linuxjournal.com. Retrieved July 29, 2011.*

52. *"Windows Refund Day" .  
Marc.merlins.org. February 15, 1999.  
Retrieved July 29, 2011.*
53. *Detaxe.org (in French) Say no to  
bundled software - Say yes to  
informed consumers*
54. *AM, Last modified: 04/29/2014 01:10.  
"International petition | AFUL" .  
no.more.racketware.info.*
55. *Prashanth Venkataram (September 10,  
2010). "Counter-Debunking the 1%  
myth" .  
dasublogbyprashanth.blogspot.com.  
Retrieved October 1, 2011.*



- 56. *Schestowitz, Roy (July 2007). "Can Linux Adoption Ever be Accurately Gauged?" . Retrieved May 23, 2008.*
- 57. *Caitlyn Martin (September 7, 2010). "Debunking the 1% myth" . oreilly.com. Retrieved October 1, 2011.*
- 58. *C. Lohner. "The Linuxcounter project is closed!" . Retrieved August 28, 2019.*
- 59. *A. Ponomarenko. "Linux Hardware Trends" . Retrieved March 11, 2020.*

## External links

---

**Linux distribution**  
at Wikipedia's sister projects

---

Media

from



Wikimedia

Commons

Textbooks



from

Wikibooks

Resources



from

Wikiversity

- The LWN.net Linux Distribution List – a categorized list with information about each entry

- List of GNU/Linux distributions considered free by the Free Software Foundation
- Google's approach to a large-scale live upgrading between two widely different Linux distributions: presentation and text version , LinuxCon 2013, by Marc Merlin
- Rolling release vs. fixed release Linux , ZDNet, February 3, 2015, by Steven J. Vaughan-Nichols

Retrieved from

"[https://en.wikipedia.org/w/index.php?title=Linux\\_distribution&oldid=998878283](https://en.wikipedia.org/w/index.php?title=Linux_distribution&oldid=998878283)"

---

Last edited 5 days ago by Dextor

Content is available under CC BY-SA 3.0 unless otherwise noted.