Sprache ändern in Deutsch

Welcome **U0UENDU** Logout

Mercedes-Benz

IAM Approval Tool

Request List | Download Area | Help

← Back to request (latest version)

Request No. 5289 - DHCCAAS

+ Create new OIDC Service Configuration version

OIDC Service Configuration details: kubernetes-oidc - Version 5 - Approved and Implemented

Authorization Management

Alice is the administration tool for the authorization data stored in the Runtime Directory (DRD). For Alice usage you will require the Authorization ID as Identifier.

Authorization management

☑ **Alice** Implemented

General Information

Service configuration name kubernetes-oidc

Service configuration description OIDC Kubernetes Auth for Alice Inte

IAM Service Environment Production

Comment

Location of your application Intranet

Authentication Services Implemented

OpenID Connect

Manage IAM Configuration

The settings are used to configure the authentication protocol used by the application. For more information, please check the Integration Guide.

Application Type

Application Type Native Desktop Application (Rich Client)

Authorization Code Flow

This option allows your applications, to use the Code Authorization flow, this flow is used for the user login to your application.

☑ **Allow / use Authorization Code Flow**

Client Type ○ Confidential Client (Default)

◉ Public Client

Client ID e80240d92-6a3d-4f01-8cc0-e24179f96a71

Token Type

You have the option to choose between Opaque Token and JWT. Please note that the choice of token type affects the configuration of your clients.

Token Type ○ Opaque Token (Default)

◉ JWT

Login Method

Select login method configurable for your application:
- Standard authentication (Corporate UserID + password)
- Multi Factor authentication (Corporate UserID + password and 2nd factor)
- Application controlled incl. MFA
If you select 'application controlled incl. MFA' you can configure which login method is used in your application. BE AWARE, your application is responsible to verify it ('acr' claim in the ID Token) for each login!

Login Method Multi Factor AuthN

OAuth 2.0 Refresh Token

Select this option if you want to receive refresh tokens for your public client. Public client MUST be capable of keeping refresh tokens confidential. By selecting this, you confirm that you are aware of this potential security issue and that your application is capable of keeping the refresh tokens confidential.

Refresh tokens needed and you can keep them confidentially? ○ No ◉ Yes

OpenID Connect Scopes

Below table shows all scopes, which are needed for the OIDC client application. The related claims can be seen in separate window while scope selection. These scopes are approved by HR.

To use the authorization scopes, the Authorization ID has to be set with the Alice Service. Additionally, rights in the DCIGAPAUTHGRPS attribute have to be set in the corresponding directory.

Scope	Approved by HR
OIDC Scopes	
openid	(default)
offline_access	(default)
Authorization scopes	
authorization_group	✓
entitlement_group	✓
scoped_entitlement	✓
Identity scopes	
group_type	(default)

+ (De) Select Scope

Custom URI Scheme(s)

Select this option if you need Custom URI Schemes in your native mobile application. Due to higher security we recommend the use of Claimed https URI Schemes (iOS Universal Links, Android App Links). By selecting you confirm that you are aware of the potential security risk.

Custom URI Schemes will be needed ◉ No ○ Yes

Redirect URI(s)

Please note that for the application type Native Desktop App wildcards are allowed, e.g. 127.0.0.1:*/*

FQDN URI	
https://127.0.0.1	
https://caas-staging.app.corpinfra.net/heartbeat/*	🗑
https://caas.app.corpinfra.net/heartbeat/*	🗑
http://127.0.0.1:*	🗑

+ Add URI

Logout URI

FQDN URI
https://127.0.0.1

OAuth 2.0

Client Credentials Grant

☑ **Allow/use Client Credentials Grant**

Client ID c20fb2b0-0bd-4920-8eb3-a3018aec8cd5

Client Secret ••

☑ **Allow/use Technical User for Client Credentials Grant**

Technical User, which was automatically created, it is connected to the Client ID of the Client Credential Grant. The technical user is assigned to the requester. The technical user will be deleted, if the feature is deselected and the configuration is sent.

UID of tech user TE9E450

Token Type

You have the option to choose between Opaque Token and JWT. Please note that the choice of token type affects the configuration of your clients.

Token Type ○ Opaque Token (Default)

◉ JWT

OAuth 2.0 Token Introspection

☐ **Allow/use OAuth 2.0 Token Introspection**

Authorization Service Implemented

To use this Authorization ID you need to add the OIDC-Service to your Service Configuration. The authorization scopes can be added.

Authorization ID DHCCAAS ⇄ Change Authorization ID

Stop & Deprovision Service Configuration

Workflow History >

Compare >

Back to request (latest version)

Cancel Save

© 2024 Mercedes-Benz Group AG. All rights reserved.

IAM Approval Tool 3.43.0