


NEPAL COLLEGE OF INFORMATION AND TECHNOLOGY

Balkumari, Lalitpur
Affiliated to Pokhara University



DATABASE MANAGEMENT SYSTEM

Laboratory Report

Lab Title	Lab 3: Familiarization with SQL Constraints & Wildcard Characters
Subject	Database Management System (DBMS)
Tool Used	XAMPP, phpMyAdmin, MySQL
Submitted By	Shahrish Mikrani
Roll No.	241540
Submitted To	Er. Manil Vaidhya
Date	9 rd Jun, 2026

Department of IT Engineering

Q1. Create table student with constraints

```
CREATE TABLE student(  
  id int primary KEY,  
  name varchar(30) NOT NULL,  
  age int NOT NULL check(age<20),  
  mobile bigint UNIQUE NOT NULL,  
  address varchar(30) DEFAULT 'KTM'  
)
```

✓ MySQL returned an empty result set (i.e. zero rows). (Que

```
SELECT * FROM `student`
```

☐ Profiling [[Edit inline](#)] [[Edit](#)] [[Explain SQL](#)] [[Create PHP](#)

id	name	age	mobile	address
----	------	-----	--------	---------

Q2. Create table stud with Foreign Key

```
CREATE TABLE stud(  
  sid int primary KEY,  
  id int,  
  fee_pay decimal,  
  fee_due decimal,  
  FOREIGN KEY (id) REFERENCES student(id)  
)
```

```
SELECT * FROM `stud`
```


☐ Profiling [[Edit inline](#)] [[Edit](#)] [[Explain SQL](#)] [[Cr](#)

sid	id	fee_pay	fee_due
-----	----	---------	---------

Query results operations

Q3. Add column gender with NOT NULL and DEFAULT

ALTER TABLE student ADD COLUMN gender varchar(30) NOT NULL DEFAULT 'Male';



Q4. Insert records (including invalid ones)

INSERT INTO student(id,name,age,mobile) VALUES
(123,ujjwal,21,9860599493);

Error

SQL query: [Copy](#)

```
INSERT INTO student(id,name,age,mobile) VALUES  
(123,ujjwal,21,9860599493);
```

MySQL said: 

#1054 – Unknown column 'ujjwal' in 'field list'

```
INSERT INTO student(id,name,age,mobile,address) VALUES
(123,'ujjwal',18,9860599493,'chitwan'),
(124,'Ram',13,9860599494,'gaur'),
(126,'ujjwal',19,9860599495,'bharatpur'),
(125,'shyam',15,9860599496,'Rautahat'),
(128,'ujjwal',12,9860599491,'pkr')
;
```

☐ Show all

Number of rows:

25

Filter rows:

Search this table

Sort by key:

No

Extra options

			id	name	age	mobile	address	gender	
☐	Edit	Copy	Delete	123	ujjwal	18	9860599493	chitwan	Male
☐	Edit	Copy	Delete	124	Ram	13	9860599494	gaur	Male
☐	Edit	Copy	Delete	125	shyam	15	9860599496	Rautahat	Male
☐	Edit	Copy	Delete	126	ujjwal	19	9860599495	bharatpur	Male
☐	Edit	Copy	Delete	128	ujjwal	12	9860599491	pkr	Male

☐ Check all

With selected:

Edit

Copy

Delete

Export

```
INSERT INTO stud(sid,id,fee_pay,fee_due) VALUES
(465,123,20000.674,10000.46),
(466,126,20000.674,10000.46),
(467,125,20000.674,10000.46);
```

☐ Show all

Number of rows: 25

Filter rows:

Extra options

				sid	id	fee_pay	fee_due
☐	Edit	Copy	Delete	465	123	20001	10000
☐	Edit	Copy	Delete	466	126	20001	10000
☐	Edit	Copy	Delete	467	125	20001	10000

☐ Check all

With selected:

Edit

Copy

Delete

Q5. Display all table info

```
SELECT * FROM student,stud;
```

Extra options									
id	name	age	mobile	address	gender	sid	id	fee_pay	fee_due
123	ujjwal	18	9860599493	chitwan	Male	465	123	20001	10000
123	ujjwal	18	9860599493	chitwan	Male	466	126	20001	10000
123	ujjwal	18	9860599493	chitwan	Male	467	125	20001	10000
124	Ram	13	9860599494	gaur	Male	465	123	20001	10000
124	Ram	13	9860599494	gaur	Male	466	126	20001	10000
124	Ram	13	9860599494	gaur	Male	467	125	20001	10000
125	shyam	15	9860599496	Rautahat	Male	465	123	20001	10000
125	shyam	15	9860599496	Rautahat	Male	466	126	20001	10000
125	shyam	15	9860599496	Rautahat	Male	467	125	20001	10000
126	ujjwal	19	9860599495	bharatpur	Male	465	123	20001	10000
126	ujjwal	19	9860599495	bharatpur	Male	466	126	20001	10000
126	ujjwal	19	9860599495	bharatpur	Male	467	125	20001	10000
128	ujjwal	12	9860599491	pkp	Male	465	123	20001	10000
128	ujjwal	12	9860599491	pkp	Male	466	126	20001	10000
128	ujjwal	12	9860599491	pkp	Male	467	125	20001	10000

Q6. Display distinct name

```
SELECT DISTINCT name FROM student,stud;
```

Extra options	
name	
ujjwal	
Ram	
shyam	
Show all	

Q7. Select name and id of 'Ram'

```
SELECT  
name ,id FROM  
student WHERE  
name='ram';
```

Extra options

		name	id
☐	 Edit	 Copy	 Delete
		Ram	124

Extra options

⌵	id	name	age	mobile	address	gender
	123	ujjwal	18	9860599493	chitwan	Male
	124	Ram	13	9860599494	gaur	Male
	125	shyam	15	9860599496	Rautahat	Male
	126	ujjwal	19	9860599495	bharatpur	Male
	128	ujjwal	12	9860599491	pkp	Male

Extra options

		id	name	age	mobile	address	gender		
☐	 Edit	 Copy	 Delete	5	ram	10	9800000000	KTM	Male
	☐ Check all	With selected:		 Edit	 Copy	 Delete	 Export		

Q8. Select info where id > 5

```
SELECT * FROM student WHERE id>5;
```

Q9. Select info where name is 'Ram' and address is 'Ktm'

```
SELECT * FROM `student` WHERE name='ram' AND address='ktm';
```

Extra options

↔T↔

☐

 Edit

 Copy

 Delete

☐

 Edit

 Copy

 Delete

name

ram

Ram

Q10. Display name starting with 'R' only

```
SELECT name
FROM student
WHERE name
LIKE 'r%';
```

☐ Profiling [[Edit inline](#)] [[Edit](#)] [[Explain SQL](#)] [[Create P](#)]

id	name	age	mobile	address	gender

Q12. Display info of Female

students

```
SELECT * FROM student WHERE gender='famaale';
```

☐ Profiling [[Edit inline](#)] [[Edit](#)] [[Explain SQL](#)] [[Create P](#)]

name

Q13. Display name which last letter is 'e'

```
SELECT name FROM `student` WHERE name LIKE '%e';
```


←T→						age	
☐		Edit		Copy		Delete	10
☐		Edit		Copy		Delete	18
☐		Edit		Copy		Delete	13
☐		Edit		Copy		Delete	15
☐		Edit		Copy		Delete	19
☐		Edit		Copy		Delete	12

Q15. Display info of student whose mobile has '0' at the end

```
SELECT * FROM
`student` WHERE
mobile%10=0;
```

age

```
SELECT DISTINCT age FROM `student`;
```

Q16. Display distinct

←T→				id	name	age	mobile	address	gender
☐		Edit	Copy Delete	123	ujjwal	18	9860599493	chitwan	Male
☐		Edit	Copy Delete	126	ujjwal	19	9860599495	bharatpur	Male

← T →							id	name	age	mobile	address	gender
Edit Copy Delete	125	shyam	15	9860599496	Rautahat	Male						

				id	name	age	mobile	address	gender
				123	ujjwal	18	9860599493	chitwan	Male

Q17. Display age between 15 and 20

SELECT * FROM `student` WHERE age>15 AND age<20;

				id	name	age	mobile	address	gender
				5	ram	10	9800000000	KTM	Male
				124	Ram	13	9860599494	gaur	Male
				125	shyam	15	9860599496	Rautahat	Male
				126	ujjwal	19	9860599495	bharatpur	Male
				128	ujjwal	12	9860599491	pkp	Male


Q18. Display student info where address starts with 'r' and ends with 't'

SELECT * FROM `student` WHERE address LIKE 'r%t';

				id	name	age	mobile	address	gender	marks
				5	ram	10	9800000000	KTM	Male	NULL
				123	ujjwal	18	9860599493	chitwan	Male	NULL
				124	Ram	13	9860599494	gaur	Male	NULL
				125	shyam	15	9860599496	Rautahat	Male	NULL
				126	ujjwal	19	9860599495	bharatpur	Male	NULL
				128	ujjwal	12	9860599491	pkp	Male	NULL

Q19. Display student info where address ends with 'u', 'n', or 'a'

```
SELECT *
FROM student
```



```
WHERE address REGEXP '[una]$';
```

Q20. Display student info where name is NOT starting with 'A', 'C', or 'D'

```
SELECT *
FROM student
WHERE address REGEXP '^[^acd]';
```

Q21. Add column marks with CHECK constraint marks > 50

```
ALTER TABLE student
ADD COLUMN marks INT CHECK (marks > 50);
```

Q22. Create table teacher

```
CREATE TABLE teacher(
    tid int,
```

```
tname varchar(30),
tgender varchar(30),
taddress varchar(30)
)
```

Table	Create Table
teacher	<pre>CREATE TABLE `teacher` (`tid` int(11) NOT NULL, `tname` varchar(30) DEFAULT NULL, `tgender` varchar(30) DEFAULT NULL, `taddress` varchar(30) DEFAULT 'ktm', PRIMARY KEY (`tid`), UNIQUE KEY `uq_tname` (`tname`), CONSTRAINT `chk_tgender` CHECK (`tgender` in ('male','female'))) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_general_ci</pre>

	#	Name	Type	Collation	Attributes	Null	Default	Comments	Extra	Action
☐	1	tid	int(11)			No	None			Change Drop More
☐	2	tname	varchar(30)	utf8mb4_general_ci		Yes	NULL			Change Drop More
☐	3	tgender	varchar(30)	utf8mb4_general_ci		Yes	NULL			Change Drop More
☐	4	taddress	varchar(30)	utf8mb4_general_ci		Yes	ktm			Change Drop More

Q23. Add constraints to teacher table using ALTER TABLE

```
ALTER TABLE teacher
```

```
ADD CONSTRAINT pk_tid PRIMARY KEY (tid);
```

```
ALTER TABLE teacher  
ADD CONSTRAINT uq_tname UNIQUE (tname);
```

Table	Create Table
stud	<pre>CREATE TABLE `stud` (`sid` int(11) NOT NULL, `id` int(11) DEFAULT NULL, `fee_pay` decimal(10,0) DEFAULT NULL, `fee_due` decimal(10,0) DEFAULT NULL, PRIMARY KEY (`sid`), KEY `id` (`id`)) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_general_ci</pre>

```
ALTER TABLE teacher  
ADD CONSTRAINT chk_tgender  
CHECK (tgender IN ('male', 'female'));
```

```
ALTER TABLE teacher  
ALTER taddress SET DEFAULT 'ktm';  
Q24. Drop PRIMARY KEY
```

```
ALTER TABLE teacher DROP PRIMARY KEY;
```

Q25. Drop FOREIGN KEY

```
ALTER TABLE stud DROP FOREIGN KEY stud_ibfk_1;
```