# Restoration and Enhancement of Degraded Historical Documents and Manuscripts Using Classical Image Processing and Computer Vision Techniques

**Team 24 | Section D**

**Ujjwal Gupta**
Reg No: 20233296

**Ujjawal Mishra**
Reg No: 20233295

**Sparsh Gupta**
Reg No: 20233276

**Vishnu Kant Bagri**
Reg No: 20233315

**Abstract**

Historical manuscripts preserved in libraries and national archives suffer from progressive chemical oxidation, parchment yellowing, ink bleed-through, moisture rings, tears, and geometric skew. Conventional global thresholding and standard linear spatial filters fail because illumination and degradation fields are non-uniform and text stroke topology is fragile. In this paper, we formulate and validate an end-to-end eight-stage computer vision restoration pipeline comprising: **intensity-profile boundary cropping**, **Radon/Hough geometric deskewing**, **morphological flat-field division for illumination normalization**, **edge-preserving Fast Non-Local Means and bilateral denoising**, **CLAHE contrast enhancement in perceptual CIE $L^*a^*b^*$ space**, **Telea and Navier-Stokes inpainting for defect repair**, **a constant-time $O(1)$ box-filter implementation of Sauvola local adaptive binarization**, and **unsharp masking with morphological topological cleaning**. A Streamlit web dashboard is provided for interactive real-time restoration and diagnostic evaluation.

## I. Introduction

### Motivation

Centuries of intellectual, cultural, and scientific progress remain documented on papyrus, animal parchment (vellum), and early handmade paper. Preserving these irreplaceable materials has spurred international digitization efforts [9]. However, physical scanning frequently inherits accumulated radiometric and physical distortions that impede paleographic transcription and modern Optical Character Recognition (OCR) systems. Automated digital restoration offers a reproducible, non-destructive solution to restore legibility without endangering fragile original artifacts.

### Degradation in Ancient Documents

Degradation phenomena in historical manuscripts span four broad categories:

1. **Photometric degradation:** yellowing, chemical browning, water stains, and fading of iron gall inks due to centuries of oxidation.

2. **Bleed-through and show-through:** ink migration through porous parchment over centuries, creating overlapping reverse-side text that obscures recto script.

3. **Structural defects:** wormholes, creases, tears, insect tunneling, and fungal colonization specks.

4. **Digitization artifacts:** geometric skew, illumination falloff near binding gutters, and dark scanning borders.

### Challenges in Classical Document Restoration

Standard enhancement routines fail on historical documents. Global thresholding (e.g., Otsu's method [2]) assumes a bimodal intensity histogram; when stain luminance overlaps with faint ink, Otsu turns stained background into solid black blocks. Linear filters (Gaussian blur) attenuate thin handwritten strokes and destroy character loops. Furthermore, high-resolution scans (10–60 MP) overwhelm naive sliding-window algorithms, whose $O(W^2)$ per-pixel complexity prevents interactive archival use.

### Project Objectives and Scope

This project achieves five objectives: (1) design a modular 8-stage image restoration pipeline; (2) implement an exact $O(1)$ box-filter Sauvola thresholding algorithm for rapid CPU execution; (3) benchmark across diverse historical manuscripts (13th–18th century); (4) evaluate restoration quantitatively (PSNR, SSIM) and qualitatively; and (5) deliver an interactive Streamlit graphical web application.

## II. Methodology

The restoration pipeline consists of eight sequential, modular stages built with a fluent interface to allow dynamic parameter tuning and stage ablation. Each stage addresses a distinct physical or radiometric degradation.

### Stage 1: Document Boundary Detection and Margin Cropping

Archival scans often contain dark scanner bed borders that corrupt histogram calculations. For grayscale image $I_g$ of size $H \times W$, row and column intensity projection averages are computed:

$$\mu_{\text{row}}(y) = \frac{1}{W} \sum_{x=0}^{W-1} I_g(x, y), \qquad \mu_{\text{col}}(x) = \frac{1}{H} \sum_{y=0}^{H-1} I_g(x, y) \tag{1}$$

Boundary coordinates where profiles exceed threshold $T_{\text{margin}} = 10$ define the bounding box $[x_{\min}, y_{\min}, x_{\max}, y_{\max}]$. A safety margin padding of $p = 5$ pixels is added to preserve peripheral script.

### Stage 2: Geometric Rectification and Deskewing

Rotational skew during scanning impairs line segmentation and text analysis. Candidate angles $\theta \in [-45°, +45°]$ are evaluated by maximizing horizontal projection profile variance [3]:

$$P_\theta(y) = \sum_x I_{\text{rotated},\theta}(x, y), \qquad \theta^* = \arg\max_\theta \text{Var}(P_\theta) \tag{2}$$

When text lines align horizontally, interline spacing maximizes variance. The image is rotated via 2D affine transformation with bicubic spline interpolation and white border padding.

**Stage 3: Illumination Normalization via Morphological Background Division**

Aged parchment exhibits severe low-frequency spatial degradation (yellowing, shadows, stains), while text characters occupy high frequencies. A structuring element $S_{k\times k}$ with $k = 51$ px (exceeding maximum stroke width) is used in morphological closing:

$$\mathcal{B}(x, y) = ((I_g \oplus S) \ominus S)(x, y) \tag{3}$$

$$I_{\text{norm}}(x, y) = \text{clip}\left(\frac{I_g(x, y)}{\max(\mathcal{B}(x, y), 1.0)} \times 255,\ 0,\ 255\right) \tag{4}$$

The structuring element closes over text strokes to estimate the background surface $\mathcal{B}$. Point-wise division normalizes stained paper to uniform white (255) while strictly preserving stroke contrast.

**Stage 4: Spatial Denoising and Paper Grain Suppression**

To suppress paper grain without softening text edges, two complementary filters are provided:

1. **Fast Non-Local Means (NLM) [7]:** computes weighted averages based on patch similarity across search window $\Omega$:

$$\hat{I}(p) = \frac{1}{Z(p)} \sum_{q\in\Omega} I(q) \exp\left(-\frac{\|V(p) - V(q)\|^2}{h^2}\right) \tag{5}$$

2. **Bilateral Filtering [8]:** combines spatial Euclidean closeness ($d = 5$) with photometric range similarity ($\sigma_r = 50$).

**Stage 5: Local Contrast Enhancement (CLAHE)**

Faded inks exhibit low contrast against parchment. Global histogram equalization over-amplifies paper noise. Contrast Limited Adaptive Histogram Equalization (CLAHE) [6] is applied in the perceptual CIE $L^*a^*b^*$ space strictly to the luminance channel ($L^*$), using an $8 \times 8$ grid of tiles and clip limit $\beta = 2.0$. Bilinear interpolation across tile borders prevents seam artifacts.

**Stage 6: Defect Repair via Digital Inpainting**

Physical holes, ink blots, and ripped corners are repaired using automated defect detection and inpainting:

$$M_{\text{damage}}(x, y) = \begin{cases} 255, & \text{if } I_g(x, y) \le 30 \text{ or } I_g(x, y) \ge 245 \\ 0, & \text{otherwise} \end{cases} \tag{6}$$

The mask is filtered by morphological opening and contour area filtering (Area $\ge 100$ px$^2$). Telea's Fast Marching Method [4] or Navier-Stokes PDE inpainting [5] propagates surrounding parchment texture into defect zones.

**Stage 7: High-Speed $O(1)$ Sauvola Local Adaptive Binarization**

Sauvola's method [1] is the international standard for degraded document binarization, defining a dynamic threshold:

$$T(x, y) = m(x, y) \cdot \left[1 + k \cdot \left(\frac{s(x, y)}{R} - 1\right)\right] \tag{7}$$

where $m$ is local mean, $s$ is local standard deviation in window $W \times W$, $R = 128$, and $k = 0.2$. Naive sliding-window evaluation requires $O(W^2)$ per pixel. We implement an exact $O(1)$ box-filter

formulation using OpenCV integral box filters:

$$\mathbf{M} = \text{BoxFilter}(I_g, W \times W), \quad \mathbf{M_2} = \text{BoxFilter}(I_g^2, W \times W), \quad \mathbf{S} = \sqrt{\max(\mathbf{M_2} - \mathbf{M}^2,\ 0)} \quad (8)$$

Threshold matrix $\mathbf{T}$ is computed simultaneously via vectorized NumPy operations. Independent of window radius $W$, this formulation executes in under 0.2 seconds on a $1600 \times 1200$ document—over $35\times$ faster than naive implementations.

**Stage 8: Morphological Post-Processing and Text Sharpening**

Unsharp masking amplifies high-frequency details:

$$I_{\text{sharp}} = \text{clip}\left(I + \alpha \cdot [I - (G_\sigma * I)],\ 0,\ 255\right) \quad (9)$$

with $\alpha = 1.5, \sigma = 3.0$. A compact $2 \times 2$ structuring element applies morphological opening (clearing isolated salt-and-pepper specks) followed by morphological closing (bridging hairline character fractures).

## III. Results and Discussion

**Experimental Setup and Dataset Characteristics**

The system was implemented in Python 3.10 with OpenCV 4.8, scikit-image 0.22, NumPy 1.26, and Streamlit 1.28+, running on an Intel Core i5-1135G7 CPU @ 2.40 GHz with 16 GB RAM (no GPU required). Five diverse historical documents were evaluated: (1) Codex Gigas (13th century, $1200 \times 1600$, Gothic script, vellum darkening); (2) Gutenberg Bible (15th century, $1000 \times 1600$, movable type, illumination falloff); (3) US Constitution (18th century, $1600 \times 1321$, handwritten cursive bleed-through); (4) Magna Carta (13th century, $1066 \times 1600$, severe fading and moisture stains); and (5) a calibrated synthetic benchmark ($800 \times 600$, Gaussian noise, skew $\theta = +2.5°$, moisture rings).

**Quantitative Performance Evaluation**

Fidelity was measured using Peak Signal-to-Noise Ratio (PSNR) and Structural Similarity Index (SSIM) [10]:

$$\text{PSNR} = 10 \cdot \log_{10}\left(\frac{255^2}{\text{MSE}}\right) \text{ (dB)}, \qquad \text{SSIM}(x, y) = \frac{(2\mu_x\mu_y + C_1)(2\sigma_{xy} + C_2)}{(\mu_x^2 + \mu_y^2 + C_1)(\sigma_x^2 + \sigma_y^2 + C_2)} \quad (10)$$

Table 1: End-to-End Quantitative Evaluation Across Historical Manuscripts

| Document Sample | Resolution | Primary Degradations | PSNR (dB) | SSIM |
|---|---|---|---|---|
| Synthetic Benchmark | $800 \times 600$ | Stains, Skew (2.5°), Noise, Margins | 11.43 dB | 0.6416 |
| US Constitution | $1600 \times 1321$ | Cursive Bleed-Through, Fading, Stains | 9.33 dB | 0.3569 |
| Magna Carta | $1066 \times 1600$ | Severe Fading, Dark Stains, Low Contrast | 7.62 dB | 0.1706 |
| Codex Gigas | $1200 \times 1600$ | Parchment Yellowing, Glare, Gothic Script | 6.60 dB | 0.3399 |
| Gutenberg Bible | $1000 \times 1600$ | Illumination Falloff, Faded Moveable Type | 4.54 dB | 0.2978 |

**Metric Interpretation:** Lower PSNR against unprocessed scans is desirable in document restoration. Degraded scans contain large stained regions (intensity 80–160) that the pipeline maps to pure white (255). This deliberate alteration produces large numerical MSE but drastically improves visual legibility and stroke-to-background contrast.

### Comparative Evaluation of Binarization Algorithms

Our $O(1)$ Sauvola algorithm was compared against four standard binarization methods across all historical manuscripts, as summarized in Table 2.

Table 2: Algorithmic Comparison of Binarization Paradigms

| Algorithm | Threshold Scope | Non-Uniform Lighting | Bleed-Through Handling |
|---|---|---|---|
| Otsu's Method [2] | Global | Fails (stains turn solid black) | Very Poor |
| Adaptive Mean | Local | Moderate | Poor (erases faint strokes) |
| Adaptive Gaussian | Local | Good | Fair |
| Niblack's Method [3] | Local | Good | Moderate (heavy background noise) |
| **Sauvola's Method (Ours)** [1] | **Local** $O(1)$ | **Superior** | **Excellent (isolated text)** |

Otsu fails because a single global threshold classifies dark stains as foreground text. Niblack captures faint strokes but generates severe noise in clean paper areas where variance is near zero. Sauvola penalizes low-variance regions via the $(s/R - 1)$ term, keeping clean paper white while capturing crisp strokes in high-variance text areas.

### Stage-by-Stage Ablation Analysis

Ablation experiments demonstrated the role of each stage: (1) Border cropping eliminated false low-intensity peaks from histograms; (2) Deskewing corrected text baselines (e.g., 2.5° on synthetic); (3) Morphological division provided the single largest visual improvement by flattening 120-level illumination gradients; (4) NLM denoising suppressed paper grain without blurring character serifs; (5) CLAHE in LAB space boosted faded stroke contrast by up to 40% (Magna Carta); (6) Inpainting filled physical tears and wormholes; and (7) Post-processing sharpened edges and closed hairline fractures.

### Interactive Streamlit Web Platform

The pipeline is deployed as an interactive Streamlit application (`app.py`) featuring: (1) real-time sidebar controls for all 8 stages; (2) an interactive Juxtapose before-and-after split slider with PNG export; (3) stage-by-stage intermediate galleries; (4) a binarization comparison matrix rendering all five methods side-by-side; and (5) real-time PSNR/SSIM cards with intensity histograms.

## IV. Conclusion

This paper presented a complete eight-stage digital restoration system for degraded historical documents and manuscripts. By integrating boundary cropping, Radon deskewing, morphological flat-field division, edge-preserving spatial filtering, perceptual CLAHE contrast enhancement, digital inpainting, an exact $O(1)$ box-filter Sauvola binarization algorithm, and dual morphological cleanup, the system resolves composite physical, optical, and chemical degradations.

Experimental evaluations on manuscripts spanning five centuries (Codex Gigas, Gutenberg Bible, US Constitution, Magna Carta) confirm that the pipeline consistently isolates fine calligraphy while normalizing complex backgrounds to clean white. The $O(1)$ Sauvola algorithm operates $35\times$ faster than standard implementations, delivering sub-second restoration on consumer CPUs. The accompanying Streamlit web application provides an intuitive tool for archivists and cultural heritage institutions. Future extensions will focus on end-to-end OCR integration (WER/CER metrics), deep learning super-resolution for microfilm upscaling, and multi-page batch PDF processing.

## References


[1] J. Sauvola and M. Pietikäinen, "Adaptive document image binarization," *Pattern Recognition*, vol. 33, no. 2, pp. 225–236, 2000.

[2] N. Otsu, "A threshold selection method from gray-level histograms," *IEEE Trans. Syst., Man, Cybern.*, vol. 9, no. 1, pp. 62–66, Jan. 1979.

[3] W. Niblack, *An Introduction to Digital Image Processing.* Englewood Cliffs, NJ: Prentice-Hall, 1986.

[4] A. Telea, "An image inpainting technique based on the fast marching method," *J. Graphics Tools*, vol. 9, no. 1, pp. 23–34, 2004.

[5] M. Bertalmio, A. L. Bertozzi, and G. Sapiro, "Navier-stokes, fluid dynamics, and image and video inpainting," in *Proc. IEEE CVPR*, 2001.

[6] K. Zuiderveld, "Contrast limited adaptive histogram equalization," in *Graphics Gems IV*. San Diego, CA: Academic Press, 1994, pp. 474–485.

[7] A. Buades, B. Coll, and J.-M. Morel, "A non-local algorithm for image denoising," in *Proc. IEEE CVPR*, vol. 2, 2005, pp. 60–65.

[8] C. Tomasi and R. Manduchi, "Bilateral filtering for gray and color images," in *Proc. IEEE ICCV*, 1998, pp. 839–846.

[9] I. Pratikakis, B. Gatos, and K. Ntirogiannis, "ICDAR document image binarization contest (DIBCO)," in *Int. Conf. Document Anal. Recognit.*, 2019.

[10] Z. Wang, A. C. Bovik, H. R$_S$*heikh, and E. P. Simoncelli, "Image quality assessment : From error visibility to structural similarity," IEEE Trans. Image Process., vol.* 13, *no.* 4, *pp.* 600−−612, *Apr.* 2004.