

API documentation



Get started here

This template contains a boilerplate for documentation that you can quickly customize and reuse.



How to use this template

- Replace the content given brackets (()) with your API's details.
- Tips are formatted in `codespan` - feel free to read and remove them.

Start with a brief overview of what your API offers.

The ((product name)) provides many API products, tools, and resources that enable you to ((add product value here)).

You can also list the APIs you offer, link to the relevant pages, or do both in this section.

Getting started guide

List the steps or points required to start using your APIs. Make sure to cover everything required to reach success with your API as quickly as possible.

To start using the ((add APIs here)), you need to -

The points given below are from The Postman API's documentation. You can reference it to write your own getting started guide.

- You must use a valid API Key to send requests to the API endpoints. You can get your API key from Postman's [integrations dashboard](#).
- The API has [rate and usage limits](#).
- The API only responds to HTTPS-secured communications. Any requests sent via HTTP return an HTTP 301 redirect to the corresponding HTTPS resources.
- The API returns request responses in JSON format. When an API request returns an error, it is sent in the JSON response as an error key.

Authentication

Add details on the authorization keys/tokens required, steps that cover how to get them, and the relevant error codes.

The ((product name)) API uses ((add your API's authorization type)) for authentication.

The details given below are from the Postman API's documentation. You can reference it to write your own authentication section.

Postman uses API keys for authentication. You can generate a Postman API key in the [API keys](#) section of your

Postman account settings.

You must include an API key in each request to the Postman API with the X-API-Key request header.

Authentication error response

If an API key is missing, malformed, or invalid, you will receive an HTTP 401 Unauthorized response code.

Rate and usage limits

Use this section to cover your APIs' terms of use. Include API limits, constraints, and relevant error codes, so consumers understand the permitted API usage and practices.

The example given below is from The Postman API's documentation. Use it as a reference to write your APIs' terms of use.

API access rate limits apply at a per-API key basis in unit time. The limit is 300 requests per minute. Also, depending on your plan, you may have usage limits. If you exceed either limit, your request will return an HTTP 429 Too Many Requests status code.

Each API response returns the following set of headers to help you identify your use status:

Header	Description
X-RateLimit-Limit	The maximum number of requests that the consumer is permitted to make per minute.
X-RateLimit-Remaining	The number of requests remaining in the current rate limit window.
X-RateLimit-Reset	The time at which the current rate limit window resets in UTC epoch seconds.

503 response

An HTTP 503 response from our servers indicates there is an unexpected spike in API access traffic. The server is usually operational within the next five minutes. If the outage persists or you receive any other form of an HTTP 5XX error, [contact support](#).

Need some help?

Add links that customers can refer to whenever they need help.

In case you have questions, go through our tutorials ((link to your video or help documentation here)). Or visit our FAQ page ((link to the relevant page)).

Or you can check out our community forum, there's a good chance our community has an answer for you. Visit our developer forum ((link to developer forum)) to review topics, ask questions, and learn from others.

You can also document or add links to libraries, code examples, and other resources needed to make a request.

AUTHORIZATION API Key

Key	X-API-Key
Value	{{token}}

User

The `/me` endpoints let you manage information about the authenticated user.

AUTHORIZATION API Key

This folder is using API Key from collection [API documentation](#)

GET New Request

AUTHORIZATION API Key

This request is using API Key from collection [API documentation](#)

IFMS

This Folder Contains the API Documentation of the all the APIs present in the Interview Feedback Managament System

AUTHORIZATION API Key

This folder is using API Key from collection [API documentation](#)

POST Login Request

`http://localhost:9090/auth/login`

Auth Login

This endpoint allows users to authenticate and obtain a token for accessing protected resources.

Request Body

- `email` (string): The email address of the user.
- `password` (string): The password for the user's account.

Response

The response is in JSON format with the following schema:

```
json
```

```
{
  "type": "object",
  "properties": {
    "token": {
      "type": "string"
    },
    "message": {
      "type": "string"
    }
  }
}
```

- `token` (string): The authentication token for accessing protected resources.
- `message` (string): A message related to the authentication status.

AUTHORIZATION API Key

This request is using API Key from collection [API documentation](#)

HEADERS

Authorization

Bearer

eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJhbGJjZS5ockBleGFtcGxILmNvbSIsImhhdCI6MTc0MzIxNzQ4NCwiZXhwIjoxNzQzMjlxMDg0fQ.Mh-QJoVge-_yd1dzOKxU1P37o7bJVBPGwcfKxVX3RYI

Body raw (json)

json

```
{
  "email": "alice.hr@example.com",
  "password": "securepassword"
}
```

POST Register Request



`http://localhost:9090/auth/login`

The `POST /auth/register` endpoint is used to register a new user with the provided details.

Request Body

- The request should include the following parameters in the raw request body:
 - `name` (string): The name of the user.
 - `email` (string): The email address of the user.
 - `password` (string): The password for the user account.
 - `role` (string): The role of the user.

Response

The response of this request is a JSON schema with the following properties:

- `status` (number): The status code of the response.
- `message` (string): A message indicating the result of the registration process.

Example:

```
json
{
  "status": 200,
  "message": "User registered successfully!"
}
```

AUTHORIZATION API Key

This request is using API Key from collection [API documentation](#)

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJhbGJjZS5ockBleGFtcGxILmNvbSIsImhdCI6MTc0MzIzODIxOSwiZXhwIjozNzQzMjQxODE5fQ.W0ggvAwmMrtIq1YICfdZ73CSG-ldAjq5Fig5B7g5k0
---------------	---

Body raw (json)

```
json
{
  "email": "alice.hr@example.com",
  "password": "securepassword"
}
```

POST Create Interview



http://localhost:9090/interviews

Create New Interview

This endpoint allows you to create a new interview by sending a POST request to the specified URL.

Request Body

- `candidateName` (string): The name of the candidate.
- `candidateEmail` (string): The email of the candidate.
- `scheduledAt` (array of integers): The timestamp for the scheduled interview.
- `status` (string): The status of the interview.
- `interviewerEmail` (string): The email of the interviewer.
- `interviewerName` (string): The name of the interviewer.

Response

Upon a successful request, the server will respond with a status code of 200 and a JSON object containing the following fields:

- `id` (integer): The ID of the newly created interview.
- `candidateName` (string): The name of the candidate.
- `candidateEmail` (string): The email of the candidate.
- `scheduledAt` (array of integers): The timestamp for the scheduled interview.
- `status` (string): The status of the interview.
- `interviewerEmail` (string): The email of the interviewer.
- `interviewerName` (string): The name of the interviewer.
- `hrManager` (null or string): The HR manager associated with the interview, or null if not assigned.

AUTHORIZATION API Key

This request is using API Key from collection [API documentation](#)

HEADERS

Authorization

Bearer

eyJhbGciOiJIUzI1NiJ9.eyJzdWUiOiJhbGJjZS5ockBleGFtcGxILmNvbSIsImhhdCI6MTc0MzIxNzQ5NCwiZXhwIjoxNzQzMjIxMDk0fQ.8M3z6fJdcRUZGNvoiJT_4jUwX3CFuA8PfLDAZ26fRKM

Body raw (json)

json

```
{
  "candidateName": "Uzair Hussain",
  "candidateEmail": "uzair@example.com",
  "scheduledAt": [
    2025,
    3,
    23,
    17,
    12
  ],
  "status": "SCHEDULED",
  "interviewerEmail": "utkarsh.interviewer@example.com",
  "interviewerName": "Utkarsh Jain"
```

```
}

```

GET HR_Dashboard



http://localhost:9090/interviews

Update Interview Details

This endpoint allows the user to update the details of a specific interview by sending an HTTP PUT request to the specified URL.

Request Body

- `candidateName` (string): The name of the candidate.
- `candidateEmail` (string): The email address of the candidate.
- `scheduledAt` (array of integers): The scheduled date and time of the interview.
- `status` (string): The status of the interview.
- `interviewerEmail` (string): The email address of the interviewer.
- `interviewerName` (string): The name of the interviewer.

Response

The response will have a status code of 200 and a content type of `application/json`. The response body will contain an array with an object having the following properties:

- `id` (number): The ID of the interview.
- `candidateName` (string): The name of the candidate.
- `candidateEmail` (string): The email address of the candidate.
- `scheduledAt` (array of integers): The scheduled date and time of the interview.
- `status` (string): The status of the interview.
- `interviewerEmail` (string): The email address of the interviewer.
- `interviewerName` (string): The name of the interviewer.
- `hrManager` (null): The HR manager associated with the interview.

AUTHORIZATION API Key

This request is using API Key from collection [API documentation](#)

HEADERS

Authorization

Bearer

eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJhbGJZS5ockBleGFtcGxlMnVbSislmhdCl6MTc0MzIxNzQ5NCwiZXhwIjoxNzQzMjIxMDk0fQ.8M3z6fJdcRUZGNvoiJT_4jUwX3CFuA8PfLDAZ26fRKM

Body raw (json)

json

```
{
  "candidateName": "Uzair Hussain",
  "candidateEmail": "uzair@example.com",
  "scheduledAt": [
    2025,
    3,
    23,
    17,
    12
  ],
  "status": "SCHEDULED",
  "interviewerEmail": "utkarsh.interviewer@example.com",
  "interviewerName": "Utkarsh Jain"
}
```

PUT Update Interview



<http://localhost:9090/interviews/9>

Update Interview Details

This endpoint allows the user to update the details of a specific interview.

Request Body

- `candidateName` (string): The name of the candidate.
- `candidateEmail` (string): The email address of the candidate.
- `scheduledAt` (array): An array containing the scheduled date and time of the interview.
- `status` (string): The status of the interview.
- `interviewerEmail` (string): The email address of the interviewer.
- `interviewerName` (string): The name of the interviewer.

Response

Upon a successful update, the server responds with a status code of 200 and a JSON object containing the updated details of the interview.

- `id` (number): The unique identifier of the interview.
- `candidateName` (string): The name of the candidate.
- `candidateEmail` (string): The email address of the candidate.
- `scheduledAt` (array): An array containing the scheduled date and time of the interview.
- `status` (string): The status of the interview.
- `interviewerEmail` (string): The email address of the interviewer.
- `interviewerName` (string): The name of the interviewer.
- `hrManager` (null): The HR manager associated with the interview.

AUTHORIZATION API Key

This request is using API Key from collection [API documentation](#)

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJhbGJjZS5ockBleGFtcGxlLmNvbSIsImhdCI6MTc0MzIxNzQ4NCwiZXhwIjoxNzQzMjIxMDg0fQ.Mh-QJoVge-_yd1dzOKxU1P37o7bJVBPgWcfKxVX3RYI
---------------	--

Body raw (json)

```
json

{
  "candidateName": "Uzair Hussain",
  "candidateEmail": "uzairhussain@example.com",
  "scheduledAt": [
    2025,
    4,
    23,
    17,
    12
  ],
  "status": "SCHEDULED",
  "interviewerEmail": "utkarsh.interviewer@example.com",
  "interviewerName": "Utkarsh Jain"
}
```

GET Delete Interview

Delete Interview

Deletes a specific interview based on the provided interview ID.

Request

- Method: DELETE
- Endpoint: `http://localhost:9090/interviews/9`

Response

- Status: 200
- Content-Type: text/plain
- Body: Interview Deleted Successfully

This request is using API Key from collection [API documentation](#)

GET Send Email



Send Email

This endpoint allows you to send an email for a scheduled interview.

Request Body

- `interviewId` (integer): The ID of the interview.
- `interviewerEmail` (string): The email address of the interviewer.
- `candidateName` (string): The name of the candidate.
- `scheduledAt` (string): The scheduled date and time of the interview in ISO 8601 format (e.g., "2025-03-28T10:00:00").

Response

Upon successful execution, the response will have a status code of 200 and a content type of text/plain, with the message "Email sent successfully."

This request is using API Key from collection [API documentation](#)

GET View Feedback



Get Interview Feedback

This endpoint retrieves the feedback for a specific interview.

Request

- Method: GET
- URL: `http://localhost:9090/feedback/interview/2`

Response

- Status: 200
- Content-Type: application/json
- ```
[{ "id": 0, "interview": { "id": 0, "candidateName": "", "candidateEmail": "", "scheduledAt": [0], "status": "", "interviewerEmail": "", "interviewerName": "", "hrManager": { "id": 0, "name": "", "email": "", "password": "", "role": "" } }, "interviewer": { "id": 0, "name": "", "email": "", "password": "", "role": "" }, "decision": "", "skillRatings": [{ "skillName": "", "rating": "", "topics": "", "comments": "", "id": 0 }], "comments": "" }]
```

## GET Submit feedback



### Feedback Submission

This endpoint allows you to submit feedback for an interview.

#### Request Body

- `interviewer_id` (Number) - The ID of the interviewer.
- `decision` (String) - The decision regarding the interview, e.g., "L1\_PASSED".
- `comments` (String) - Additional comments about the interview.
- `skill_ratings` (Object) - Ratings for different skills including "Basic Algorithm", "Code and Syntax", "Design Patterns", "SQL", "Git", "Overall Attitude", "Learning Ability", "Resume Explanation", and "Communication".

#### Response Body

The response is in JSON format and includes the following fields:

- `id` (Number) - The ID of the feedback.
- `interview` (Object) - Details of the interview including ID, candidate name, candidate email, scheduled time, status, interviewer email, interviewer name, and HR manager details.
- `interviewer` (Object) - Details of the interviewer including ID, name, email, password, and role.
- `decision` (String) - The decision made.
- `skillRatings` (Array) - Array of skill ratings including skill name, rating, topics, comments, and ID.
- `comments` (String) - Additional comments.

#### Response JSON Schema

json

```
{
 "type": "object",
 "properties": {
 "id": { "type": "number" },
 "interview": {
 "type": "object",
 "properties": {
 "id": { "type": "number" },
 "candidateName": { "type": "string" },
 "candidateEmail": { "type": "string" },
 "scheduledAt": { "type": "array" },
```

#### AUTHORIZATION API Key

This request is using API Key from collection [API documentation](#)