Chapter 9 - Emerging Trends in Distributed and Cloud Computing

Cloud Computing

Cloud computing refers to the on-demand delivery of IT services/resources over the internet. Cloud computing delivers on-demand IT resources over the internet. By using cloud computing users can access the services from anywhere whenever they need.

Nowadays, a massive amount of data is generated every second around the globe. Businesses collect and process that data from the people and get analytics to scale their business. When lots of organizations access their data simultaneously on the remote servers in data centers, data traffic might occur. Data traffic can cause some delay in accessing the data, lower bandwidth, etc. But **cloud computing** technology alone is not effective enough to store and process massive amounts of data and respond quickly.

For example, in the Tesla self-driving car, the sensors constantly monitor the area around the car. If it detects an obstacle or pedestrian on its way, then the car must be stopped or move around without hitting. When an obstacle is on its way, the data sent through the sensor must be processed quickly and help the car to detect before it hits. A little delay in detection could be a major issue. To overcome such challenges, **edge computing** and **fog computing** are introduced.

Edge and Fog Computing

Edge Computing and Fog Computing are distributed computing paradigms that move computation and data processing closer to the data sources (the "edge" of the network), rather than relying solely on distant, centralized cloud data centers. This approach is crucial for modern applications like the Internet of Things (IoT), autonomous vehicles, and industrial automation that require real-time processing and low latency.



Edge Computing

Edge computing is a distributed computing model that pushes the processing power and intelligence right to the network's edge, which is on or extremely close to the devices (sensors, cameras, machines) that generate the data.

- **Processing Location:** Computation occurs directly on the IoT device/sensor itself or a gateway device located in immediate proximity (at the device's "edge").
- **Goal:** To achieve the lowest possible latency and enable real-time decision-making without waiting for data to travel to a cloud server.
- **Data Handling:** Data is processed and analyzed locally; only filtered, summarized, or critical data (like alerts or final results) is typically sent to the cloud.
- **Scalability:** Scales by adding more independent edge devices, though the compute and storage resources of each node are often limited.



Figure：Edge computing architecture overview

Key Benefits:

- **Ultra-Low Latency:** Crucial for mission-critical applications (e.g., stopping a self-driving car).
- **Bandwidth Optimization:** Reduces the amount of data transferred over the network to the cloud.
- **High Security/Privacy:** Data can remain local on the device, minimizing the attack surface during transmission.
- **Local Operation:** Can operate even with intermittent or no cloud connectivity.
- **Examples:** Autonomous vehicle sensors processing data to make real-time driving decisions; smart manufacturing machines analyzing data on-site.

Fog Computing

Fog computing is a decentralized computing infrastructure that acts as an intermediate layer between the Edge layer and the Cloud layer. Coined by Cisco, the name "fog" is a metaphor for a "cloud" that is closer to the ground.

- **Processing Location:** Computation takes place on Fog Nodes (e.g., industrial controllers, routers, switches, or local servers) which are located geographically distributed within the local area network (LAN), between the edge devices and the central cloud.
- **Role:** It extends the cloud's capabilities closer to the edge, but it is further away from the devices than pure edge computing. It aggregates data from multiple edge devices.
- **Data Handling:** Fog nodes receive data from edge devices, perform initial processing, filtering, aggregation, and analysis, and then forward only the necessary subset of data to the cloud for long-term storage or deep analytics.
- **Architecture:** It often involves a three-layer architecture:
  - Edge Layer: Sensors and IoT devices (data generation).
  - Fog Layer: Fog Nodes (data aggregation, filtering, short-term storage, and analysis).
  - Cloud Layer: Central data centers (long-term storage, deep analysis, and heavy computation).



Fog Computing Architecture

Key Benefits:

- **Distributed Management:** Orchestrates and manages resources across many edge devices and the cloud.
- **Reduced Latency:** Better than the Cloud, but higher than pure Edge computing.
- **Scalability:** Highly scalable as an aggregation layer; can serve many edge devices and balance the load.
- **Examples:** A smart city network where traffic cameras (edge) send data to a local city-level fog node for immediate traffic light adjustment and only high-level summaries go to the central cloud.

Difference between Edge and Fog Computing

S.No.	Edge Computing (near/at device)	Fog Computing (between edge and cloud)
01	Scalability (layer): Scales by adding more edge devices, but each device is limited in compute/storage.	More scalable as an aggregation layer: add fog nodes to serve many edge devices and balance load.
02	Number of endpoints: Typically billions of edge devices (sensors, cameras, wearables).	Number of fog nodes: Fewer than edge devices, but can be many and geographically distributed.
03	Proximity to cloud: Farthest from cloud; runs on/near the device.	Closer to the cloud/data center than edge, often at gateways, PoPs, or MEC sites.
04	Relationship	Sometimes considered a peer/leaf layer.
05	Backhaul bandwidth need: Lowest—most data is processed locally; only summaries/alerts go upstream.	Medium—fog filters/aggregates, then forwards selected data to cloud. Lower than cloud-only, higher than pure edge.
06	Operational cost: Device-by-device management can be high (many distributed nodes).	Potentially lower per device due to centralized aggregation/management at fog nodes.
07	Privacy: Highest—data can remain local on device; smaller attack surface per node.	Medium—data is aggregated at fog nodes; still reduces exposure vs. sending everything to cloud.

08	Typical location: IoT device, gateway-on-device, on-prem controller.	Local gateway, ISP PoP, base station, micro-data center.
09	Power/compute: Lowest per node (constrained CPU/RAM); optimized for quick decisions.	Higher per node than edge (stronger CPUs/GPUs to process many devices).
10	Primary benefit: Ultra-low latency decisions right where data is created.	Filtering, aggregation, and regional analytics to cut latency and cloud load.

Serverless Architecture

Serverless architecture is a cloud computing execution model where the cloud provider (like AWS, Azure, or Google Cloud) **manages all the server-side infrastructure**. The term "serverless" is a misnomer; servers are still involved, but the developer is completely abstracted from the operational concerns of provisioning, scaling, and maintenance.

The developer only needs to write and deploy their code, often as small, independent functions, and the cloud provider dynamically manages the resources to run it in response to events.

How Serverless Architecture Works (FaaS)

The most common implementation of serverless is Function as a Service (FaaS), where developers deploy code in the form of discrete, event-driven functions.

- **Code Deployment:** A developer writes application logic as a set of stateless functions (e.g., in Node.js, Python, Java).
- **Event Trigger:** An external event or trigger occurs (e.g., an HTTP request from a user, a file upload to storage, a message in a queue, a database change).

- **Dynamic Execution:** The cloud provider's FaaS platform automatically allocates the necessary compute resources (often a container) to run the specific function.
  - If the function hasn't run recently, it experiences a "cold start" delay as the execution environment is initialized.
  - If it is already running (a "warm start"), it executes immediately.
- **Pay-per-Execution:** The function executes, performs its task, and immediately shuts down. The user is only billed for the exact duration the code was running (often measured in 100-millisecond increments) and the resources consumed.
- **Auto-Scaling:** If thousands of events occur simultaneously, the cloud provider instantly scales by executing the function in parallel instances without any manual configuration.

Key Benefits of Serverless Architecture

Benefit	Description
Reduced Operational Cost	You only pay for consumption (when the code is actually executing), not for idle server capacity or continuous uptime.
Automatic Scaling	The infrastructure scales instantly and automatically from zero to peak demand and back down, without developers needing to manage scaling policies or load balancers.
Reduced Operational Overhead	The cloud provider handles all server management, including provisioning, maintenance, patching, operating system updates, and capacity planning. This allows developers to focus purely on business logic.
Faster Time-to-Market	Simplified deployment models allow developers to deploy new features and updates quickly and independently, accelerating the development lifecycle.
Built-in High Availability	The cloud provider manages fault tolerance and redundancy across multiple availability zones automatically.

Serverless Architecture Drawbacks (Limitations)

Drawback	Description
Cold Starts	The first time an inactive function is invoked, there is a latency delay (the "cold start") as the execution environment spins up. This can impact performance for real-time, latency-sensitive applications.
Vendor Lock-in	Serverless functions are tightly integrated with the cloud provider's unique platform, services, and APIs, making it difficult to migrate the application to a different cloud vendor.
Limited Control	Developers lose control over the underlying operating system, runtime environment, and infrastructure configuration, which can be an issue for applications with highly specific, low-level requirements.
Execution Time Limits	Serverless platforms impose a maximum execution time (e.g., 15 minutes), making it unsuitable for long-running batch jobs or continuous processing tasks.
Debugging Complexity	Debugging and monitoring can be challenging since the application is fragmented into tiny, ephemeral functions with distributed logs and limited access to the runtime environment.

Common Serverless Use Cases

Serverless architecture is best suited for applications with variable or unpredictable traffic patterns and tasks that can be broken down into discrete, independent units.

- **Serverless APIs/Web Backends:** Using an API Gateway to trigger a function that processes an HTTP request for a web or mobile application.
- **Data Processing:** Processing files as soon as they are uploaded (e.g., generating image thumbnails, transcoding video, or running ETL jobs on data streams).
- **Event-Driven Workflows:** Automating tasks based on internal system events, such as sending a confirmation email after a new user signs up.
- **IoT Backends:** Handling and processing the massive, unpredictable streams of data arriving from thousands of Internet of Things (IoT) devices.

Docker and Kubernets

Docker is a platform for packaging and running applications in containers, while Kubernetes is the de facto platform for managing and orchestrating those containers at scale. They are complementary technologies, with Kubernetes often utilizing a Docker container runtime.



Docker: Containerization Platform

Docker is an open-source platform that enables developers to build, ship, and run applications quickly by packaging them and their dependencies into standardized units called containers.

- **Docker Image:** This is a read-only template or a blueprint that contains the application code, runtime, libraries, dependencies, and configuration files. It's the static definition of what a container will be.
- **Docker Container:** This is a runnable instance of a Docker image. It is a lightweight, isolated execution environment that shares the host machine's operating system (OS) kernel, making it much more efficient than a full Virtual Machine (VM).

In short, **Docker** is the tool that makes the container.

Kubernetes (K8s): Container Orchestration

Kubernetes (often abbreviated as K8s) is an open-source platform designed to automate deploying, scaling, and managing containerized applications, particularly in large-scale, distributed environments.

Once you have many containers running microservices, managing them manually across multiple servers becomes complex. Kubernetes solves this by providing an orchestration layer.

- **Cluster Management:** Kubernetes manages a cluster of physical or virtual machines (Nodes).

- **Pods:** The smallest deployable unit in Kubernetes, a Pod is a logical group of one or more containers that share network and storage resources. Kubernetes schedules and manages Pods, which in turn contain your Docker containers.
- **Service Discovery & Load Balancing:** Kubernetes provides ways for containers to find and communicate with each other and distributes traffic across multiple container replicas.
- **Self-Healing:** It monitors the health of containers and nodes, automatically restarting failed containers, replacing dead Pods, and re-scheduling containers on healthy nodes.
- **Scaling:** It can automatically scale the number of container replicas up or down based on traffic or other metrics.

In short, **Kubernetes** is the tool that manages and coordinates multiple containers across a cluster of machines.

Key Differences and Relationship

The relationship is not "versus" but "together." Docker packages the application; Kubernetes manages the package.

Feature	Docker (Containerization)	Kubernetes (Orchestration)
Primary Role	Packages an application and its environment.	Manages, scales, and automates containers at scale.
Unit of Work	Single Container (running instance of an image).	Pod (grouping of one or more containers).
Scope	Single host machine or local development.	Cluster of multiple machines (nodes).
Core Function	Building, shipping, and running containers.	Deployment, scaling, load balancing, and self-healing.
Comparable Tool	None (it's the standard container engine).	Docker Swarm, Mesos, Amazon ECS.

Cloud-native and Microservices

Cloud-native is a **broad approach and methodology** for building and running applications that take full advantage of the cloud computing model, while **microservices** is a **specific architectural style** that is the foundation for most modern cloud-native applications.
Microservices are a key component and enabler of a cloud-native strategy.

Cloud-Native Architecture

Cloud-native is less about **where** an application runs (though it is designed for the cloud) and more about **how** it is built, deployed, and managed. The goal is to maximize speed, agility, and resilience in a dynamic cloud environment.



Key Principles and Technologies

Cloud-native applications are designed to be highly scalable, fault-tolerant, and easily manageable through automation. This approach is underpinned by several core technologies and practices:

- **Microservices:** The application is broken down into small, independent, loosely coupled services.
- **Containers:** Microservices are packaged into containers (like Docker) with all their dependencies, ensuring they run consistently everywhere.
- **Orchestration:** Kubernetes (K8s) is used to automatically deploy, scale, and manage the containerized microservices across a cluster of servers.
- **DevOps and CI/CD:** Embracing a DevOps culture and using Continuous Integration/Continuous Delivery (CI/CD) pipelines to automate the build, test, and deployment process.
- **Immutable Infrastructure:** Components are never modified after deployment; instead, new versions are built and deployed to replace old ones.

Microservices

Microservices is an **architectural pattern** that structures an application as a collection of small, autonomous services modeled around a business domain.
Microservices are the core architectural pattern that drives the modern, agile development you see in cloud-native environments.
In the past, applications were often built as a single, indivisible unit called a Monolith.
In contrast, microservices break this structure apart.



Key Characteristics of Microservices

Characteristic	Description	Benefit in Cloud-Native
Independent Deployment	Each service can be developed, deployed, and updated without affecting others.	Enables faster release cycles and Continuous Delivery.
Decentralized Data	Each service manages its own database, making it fully independent.	Prevents a single database failure from taking down the entire system (Resilience).
Technology Diversity	Different services can be written in different programming languages and use different	Allows teams to use the best tool for each specific job.

	storage technologies.	
Independent Scaling	Only the services under heavy load need to be scaled (adding more instances).	Optimizes cloud resource usage and cost (Scalability).12

Core Principles of Microservices Architecture

Microservices architecture breaks a large application into small, independent services, each focused on a specific business capability. This design is built on the following principles:

- **Single Responsibility/Concern:** Each microservice should do one thing and one thing only (e.g., an "Order Service" handles orders, not user authentication or inventory). This makes services easier to understand, maintain, and scale.
- **Service Autonomy:** Services are loosely coupled and function independently. They should not rely heavily on the internal workings or deployment of other services.
- **Decentralized Data Management:** Crucially, each microservice owns its own database or data store. This prevents a single database from becoming a bottleneck and ensures the service can evolve its data structure independently.

- **Independent Deployment:** A change to one service should not require the redeployment of the entire application. Teams can deploy updates to their service at any time, which is essential for Continuous Delivery (CD).
- **Technology Diversity:** Teams are free to choose the best programming language, framework, or storage technology for their specific service, rather than being locked into a single technology stack (a common constraint in monolithic applications).

Example for **Microservice architecture**: