Deployment & Configuration Guide

For: AutoAlarm Services & CSV Report Cronjob

Purpose: This document outlines the deployment procedures for AutoAlarm Java services and the scheduling of CSV report generation via cronjob on the client server.

1. Auto_Alarm Services Deployment

1.1 Prerequisites

- Elasticsearch

- MongoDB

- Graylog Server

Before starting the deployment, import the extractors from any UDP input on the MQS server to the new Graylog server.

1.2 Deployment Directory

JAR File Location: /opt/AutoAlarmJarFiles1stApril/

Configuration Files: `/opt/AutoAlarmConfigFiles/

Gitlab_Url:-

https://gitlab.leotechnosoft.net/UjwalaB/ujwala_may2025/-/blob/Graylog6.1.10/AutoAlarmLabelRemoveAttach5thJun8084.jar

https://gitlab.leotechnosoft.net/UjwalaB/ujwala_may2025/-/blob/Graylog6.1.10/queue_config.properties8084?ref_type=heads

1.3 Configuration

Each service JAR file should have an associated configuration file named by port. For example, `8084.jar` should use `config.properties8084`.

Below are the essential keys to configure in the properties file:server_ip=<graylog_server_ip>
api_endpoint=<siem_ticket_api_endpoint>
api_endpoint_AlarmId=<siem_alarm_id_api_endpoint>

api_server_url=http://graylog-server:9000/api/search/universal/relative
siem_notification_endpoint=<siem_close_case_api>
input_id=<graylog_input_id>
apiserver_username=<graylog_username>
apiserver_password=<graylog_password>
risk_dashboard_siem_api=<siem_risk_update_api_endpoint>

1.4 Commands for Deployment

To run JAR in the background:

nohup java -jar filename.jar &

To check running services:

ps -ef | grep jar

2. CSV Report Generation via Cronjob

2.1 Deployment Paths

JAR File Path: /opt/Csv_JarFiles_Monthly_Weekly_Feb_06_025

Configuration Path: /opt/Csv_Weekly_Config_Feb_06_025

For example, configuration files should be set according to the port series. If the JAR file is named 8084.jar, then the corresponding configuration file should follow the naming pattern csv_config.properties1, and so on sequentially.

2.2 Configuration(Update the following properties in config.properties file)

Updatethe
graylog_url=<graylog_api_endpoint>
input_id=<graylog_input_id>
email_recipients=example@example.com

2.3 Cronjob Setup

To view current cronjobs:

crontab -l

To edit cronjobs:

crontab -e

Set the following entries to schedule the report generation:

Weekly Report (Every Monday at 12:00 AM):

0 0 * * 1 java -jar /opt/Csv_JarFiles_Monthly_Weekly_Feb_06_025/CsvWeekly8084.jar

Monthly Report (1st of each month at 12:00 AM):

0 0 1 * * java -jar /opt/Csv_JarFiles_Monthly_Weekly_Feb_06_025/CsvMonthly8084.jar

---