

OBJECTIVES:

- 1. Discuss the python dictionaries and arrays.
- 2. Demonstrate programs using python dictionaries and arrays.
- 3. Develop a python program using dictionaries and arrays.

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

*Python's standard library has array module. The array class in it allows you to construct an array of three basic types, integer, float and Unicode characters.

Syntax

The syntax of creating array is —
import array
obj = array.array(typecode[, initializer])

Parameters

- ❖typecode The typecode character used to create the array.
- ❖initializer array initialized from the optional value, which must be a list, a bytes-like object, or iterable over elements of the appropriate type.

Return type

The array() constructor returns an object of array.array class

```
import array as arr
# creating an array with integer type
a = arr.array('i', [1, 2, 3])
print (type(a), a)
# creating an array with char type
a = arr.array('u', 'BAT')
print (type(a), a)
# creating an array with float type
a = arr.array('d', [1.1, 2.2, 3.3])
print (type(a), a)
```

Arrays are sequence types and behave very much like lists, except that the type of objects stored in them is constrained.

```
<class 'array.array'> array('i', [1, 2, 3])
<class 'array.array'> array('u', 'BAT')
<class 'array.array'> array('d', [1.1, 2.2, 3.3])
```

Python array type is decided by a single character Typecode argument.

type code	Python data type	Byte size
'b'	signed integer	1
'B'	unsigned integer	1
'u'	Unicode character	2
'h'	signed integer	2
'H'	unsigned integer	2
'i'	signed integer	2
'I'	unsigned integer	2
T	signed integer	4
'L'	unsigned integer	4
'q'	signed integer	8
'Q'	unsigned integer	8
'f'	floating point	4
'd'	floating point	8

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

ACCESSING ARRAY ITEMS

Since the array object behaves very much like a sequence, you can perform indexing and slicing operation with it.

```
import array as arr
a = arr.array('i', [1, 2, 3])
#indexing
print (a[1])
#slicing
print (a[1:])
```

ACCESSING ARRAY ITEMS

Changing Array Items-You can assign value to an item in the array just as you assign a value to item in a list.

```
import array as arr
a = arr.array('i', [1, 2, 3])
a[1] = 20
print (a[1])
```

```
import array as arr
a = arr.array('i', [1, 2, 3])
# assignment
a[1] = 'A'
```

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

ADD ARRAY ITEMS

The append() Method

The append() method adds a new element at the end of given array.
import array as arr

a = arr.array('i', [1, 2, 3])

a.append(10)

print (a)

Syntax

array.append(v)

Parameters

❖v – new value is added at the end of the array. The new value must be of the same type as datatype argument used while declaring array object.

ADD ARRAY ITEMS

The insert() Method

The array class also defines insert() method. It is possible to insert a new element at the specified index.

Syntax

*array.insert(i, v)

Parameters

- ❖i The index at which new value is to be inserted.
- v The value to be inserted. Must be of the arraytype.

```
import array as arr
a = arr.array('i', [1, 2, 3])
a.insert(1,20)
print (a)
```

ADD ARRAY ITEMS

The extend() Method

The extend() method in array class appends all the elements from another array of same typecode.

Syntax

array.extend(x)

Parameters

x — Object of array.array class

```
import array as arr
a = arr.array('i', [1, 2, 3, 4, 5])
b = arr.array('i', [6,7,8,9,10])
a.extend(b)
print (a)
```

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

REMOVE ARRAY ITEMS

array.remove() Method

The remove() method removes the first occurrence of a given value from the array

import array as arr

a.remove(2)

print (a)

a = arr.array('i', [1, 2, 1, 4, 2])

Syntax

*array.remove(v)

Parameters

❖v — The value to be removed from the array

REMOVE ARRAY ITEMS

array.pop() Method

The pop() method removes an element at the specified index from the array, and returns the removed element.

Syntax

array.pop(i)

Parameters

import array as arr a = arr.array('i', [1, 2, 1, 4, 2]) a.pop(2) print (a)

❖i — The index for the eminent to be removed. The method returns element at ith position after removal.

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

LOOP ARRAYS

"for" Loop with Array

```
import array as arr
a = arr.array('d', [1, 2, 3])
for x in a:
    print (x)
```

```
import array as arr
a = arr.array('d', [1, 2, 3])
I = len(a)
for x in range(I):
    print (a[x])
```

"while" Loop with Array

```
import array as arr
a = arr.array('d', [1, 2, 3])
I = len(a)
idx = 0
while idx<I:
    print (a[idx])
    idx+=1</pre>
```

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

COPY ARRAYS

To create another physical copy of an array, we use another module in Python library, named copy and use deepcopy() function in the module. A deep copy constructs a new compound object and then, recursively inserts copies into it of the objects

found in the original.

```
import array, copy
a = arr.array('i', [1, 2, 3, 4, 5])
import copy
b = copy.deepcopy(a)
print (id(a), id(b))
a[2]=10
print (a,b)
```

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

REVERSE ARRAYS

```
import array as arr
a = arr.array('i', [10,5,15,4,6,20,9])
b = arr.array('i')
for i in range(len(a)-1, -1, -1):
    b.append(a[i])
print (a, b)
```

The array class doesn't have any built-in method to reverse array. Hence, we have to use another array. An empty array "b".

We traverse the numbers in array "a" in reverse order, and append each element to the "b" array. The array "b" now holds numbers from original array in reverse order.

REVERSE ARRAYS

```
from array import array as arr

a = arr.array('i', [10,5,15,4,6,20,9])

b = a.tolist()

b.reverse()

a = arr.array('i')

a.fromlist(b)

print (a)
```

Reverse the sequence of numbers in an array using the reverse() method in list class. List is a built-in type in Python. We have to first transfer the contents of an array to a list with tolist() method of array class. Call the reverse() method. If we now convert the list back to an array, we get the array with reversed order.

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

The array class doesn't have any function/method to give a sorted arrangement of its elements. However, we can achieve it with one of the following approaches —

- Using a sorting algorithm
- Using the sort() method from List
- Using the built-in sorted() function

Using a Sorting Algorithm

We shall implement the classical bubble sort algorithm to obtain the sorted array. To do it, we use two nested loops and swap the elements for rearranging in sorted order.

```
import array as arr
a = arr.array('i', [10,5,15,4,6,20,9])
for i in range(0, len(a)):
    for j in range(i+1, len(a)):
        if(a[i] > a[j]):
        temp = a[i];
        a[i] = a[j];
        a[j] = temp;
print (a)
```

Using the sort() Method from List

Even though array doesn't have a sort() method, Python's builtin List class does have a sort method.

```
from array import array as arr

a = arr.array('i', [10,5,15,4,6,20,9])

b=a.tolist()

b.sort()

a = arr.array('i')

a.fromlist(b)

print (a)
```

Using the Builtin sorted() Function

The third technique to sort an array is with the sorted() function, which is a built-in function.

The **syntax** of sorted() function is as follows –

sorted(iterable, reverse=False)

The function returns a new list containing all items from the iterable in ascending order. Set reverse parameter to True to get a descending order of items.

*The sorted() function can be used along with any iterable. Python array is an iterable as it is an indexed collection. Hence, an array can be used as a parameter to sorted() function.

Using the Builtin sorted() Function

```
from array import array as arr

a = arr.array('i', [4, 5, 6, 9, 10, 15, 20])

sorted(a)

print (a)
```

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

JOIN ARRAYS

First Method

To join two arrays, we can do it by **appending** each item from one array to other.

```
import array as arr
a = arr.array('i', [10,5,15,4,6,20,9])
b = arr.array('i', [2,7,8,11,3,10])
for i in range(len(b)):
    a.append(b[i])
print (a, b)
```

JOIN ARRAYS

Second Method

Using another method to join two arrays, first convert arrays to list objects. The list objects can be concatenated with the '+' operator. If "z" list is converted back to array, you get an array that represents the joined arrays

```
from array import array as arr
a = arr.array('i', [10,5,15,4,6,20,9])
b = arr.array('i', [2,7,8,11,3,10])
x=a.tolist()
y=b.tolist()
z = x + y
a=arr.array('i')
a.fromlist(z)
print (a)
```

JOIN ARRAYS

Third Method

We can also use the extend() method from the List class to append elements from one list to another. Convert the array to a list and then call the extend() method to merge the two lists.

```
from array import array as arr

a = arr.array('i', [10,5,15,4,6,20,9])

b = arr.array('i', [2,7,8,11,3,10])

a.extend(b)


print (a)
```

- Python Arrays
- Accessing Array Items
- Add Array Items
- Remove Array Items
- Loop Arrays

- Copy Arrays
- Reverse Arrays
- Sort Arrays
- Join Arrays
- Array Methods

ARRAY METHODS

Method	Description
append()	Adds an element at the end of the list
<u>clear()</u>	Removes all the elements from the list
copy()	Returns a copy of the list
<pre>count()</pre>	Returns the number of elements with the specified value
<pre>extend()</pre>	Add the elements of a list (or any iterable), to the end of the current list
<u>index()</u>	Returns the index of the first element with the specified value
insert()	Adds an element at the specified position
<u>pop()</u>	Removes the element at the specified position
remove()	Removes the first item with the specified value
reverse()	Reverses the order of the list
sort()	Sorts the list



learn python programming. (2023).
https://www.tutorialsteacher.com/python
python tutorial. (2022).
https://www.w3resource.com/python/python-tutorial.php

python tutorial. (n.d.). https://www.tutorialspoint.com/python/index.htm

python tutorial. (n.d.). https://www.w3schools.com/python/default.asp

References