

CSS Default Values

Element	Default CSS Value	Try it
a:link	color: (internal value); text-decoration: underline; cursor: auto;	Try it »
a:visited	color: (internal value); text-decoration: underline; cursor: auto;	Try it »
a:link:active	color: (internal value);	Try it »
a:visited:active	color: (internal value);	Try it »
abbr	None.	
address	display: block; font-style: italic;	Try it »
area	display: none;	
article	display: block;	
aside	display: block;	
audio	None.	
b	font-weight: bold;	Try it »
base	None.	
bdi	None.	
bdo	unicode-bidi: bidi-override;	
blockquote	display: block; margin-top: 1em; margin-bottom: 1em; margin-left: 40px; margin-right: 40px;	Try it »
body	display: block; margin: 8px;	Try it »
body:focus	outline: none;	Try it »
br	None.	
button	None	
canvas	None.	
caption	display: table-caption; text-align: center;	Try it »
cite	font-style: italic;	Try it »
code	font-family: monospace;	Try it »
col	display: table-column;	Try it »
colgroup	display: table-column-group	Try it »
datalist	display: none;	

CSS Default Values

dd	display: block; margin-left: 40px;	Try it »
del	text-decoration: line-through;	Try it »
details	display: block;	
dfn	font-style: italic;	Try it »
dialog	None.	
div	display: block;	Try it »
dl	display: block; margin-top: 1em; margin-bottom: 1em; margin-left: 0; margin-right: 0;	Try it »
dt	display: block;	Try it »
em	font-style: italic;	Try it »
embed:focus	outline: none;	
fieldset	display: block; margin-left: 2px; margin-right: 2px; padding-top: 0.35em; padding-bottom: 0.625em; padding-left: 0.75em; padding-right: 0.75em; border: 2px groove (internal value);	Try it »
figcaption	display: block;	
figure	display: block; margin-top: 1em; margin-bottom: 1em; margin-left: 40px; margin-right: 40px;	Try it »
footer	display: block;	
form	display: block; margin-top: 0em;	Try it »
h1	display: block; font-size: 2em; margin-top: 0.67em; margin-bottom: 0.67em; margin-left: 0; margin-right: 0; font-weight: bold;	Try it »

CSS Default Values

h2	display: block; font-size: 1.5em; margin-top: 0.83em; margin-bottom: 0.83em; margin-left: 0; margin-right: 0; font-weight: bold;	Try it »
h3	display: block; font-size: 1.17em; margin-top: 1em; margin-bottom: 1em; margin-left: 0; margin-right: 0; font-weight: bold;	Try it »
h4	display: block; margin-top: 1.33em; margin-bottom: 1.33em; margin-left: 0; margin-right: 0; font-weight: bold;	Try it »
h5	display: block; font-size: .83em; margin-top: 1.67em; margin-bottom: 1.67em; margin-left: 0; margin-right: 0; font-weight: bold;	Try it »
h6	display: block; font-size: .67em; margin-top: 2.33em; margin-bottom: 2.33em; margin-left: 0; margin-right: 0; font-weight: bold;	Try it »
head	display: none;	
header	display: block;	
hr	display: block; margin-top: 0.5em; margin-bottom: 0.5em;	Try it »

CSS Default Values

	margin-left: auto; margin-right: auto; border-style: inset; border-width: 1px;	
html	display: block;	
html:focus	outline: none;	
i	font-style: italic;	Try it »
iframe:focus	outline: none;	
iframe[seamless]	display: block;	
img	display: inline-block;	Try it »
input	None.	
ins	text-decoration: underline;	Try it »
kbd	font-family: monospace;	Try it »
label	cursor: default;	Try it »
legend	display: block; padding-left: 2px; padding-right: 2px; border: none;	Try it »
li	display: list-item;	
link	display: none;	
main	None.	
map	display: inline;	
mark	background-color: yellow; color: black;	Try it »
menu	display: block; list-style-type: disc; margin-top: 1em; margin-bottom: 1em; margin-left: 0; margin-right: 0; padding-left: 40px;	
menuitem	None.	
meta	None.	
meter	None.	
nav	display: block;	
noscript	None.	
object:focus	outline: none;	

CSS Default Values

ol	display: block; list-style-type: decimal; margin-top: 1em; margin-bottom: 1em; margin-left: 0; margin-right: 0; padding-left: 40px;	Try it »
optgroup	None.	
option	None.	
output	display: inline;	
p	display: block; margin-top: 1em; margin-bottom: 1em; margin-left: 0; margin-right: 0;	Try it »
param	display: none;	
picture	None.	
pre	display: block; font-family: monospace; white-space: pre; margin: 1em 0;	Try it »
progress	None.	
q	display: inline;	Try it »
q::before	content: open-quote;	Try it »
q::after	content: close-quote;	Try it »
rp	None.	
rt	line-height: normal;	
ruby	None.	
s	text-decoration: line-through;	Try it »
samp	font-family: monospace;	Try it »
script	display: none;	
section	display: block;	Try it »
select	None.	
small	font-size: smaller;	Try it »
source	None.	
span	None.	
strike	text-decoration: line-through;	Try it »
strong	font-weight: bold;	Try it »

CSS Default Values

style	display: none;	
sub	vertical-align: sub; font-size: smaller;	Try it »
summary	display: block;	
sup	vertical-align: super; font-size: smaller;	Try it »
table	display: table; border-collapse: separate; border-spacing: 2px; border-color: gray;	Try it »
tbody	display: table-row-group; vertical-align: middle; border-color: inherit;	
td	display: table-cell; vertical-align: inherit;	
template	None.	
textarea	None.	
tfoot	display: table-footer-group; vertical-align: middle; border-color: inherit;	
th	display: table-cell; vertical-align: inherit; font-weight: bold; text-align: center;	
thead	display: table-header-group; vertical-align: middle; border-color: inherit;	
time	None.	
title	display: none;	
tr	display: table-row; vertical-align: inherit; border-color: inherit;	
track	None.	
u	text-decoration: underline;	Try it »
ul	display: block; list-style-type: disc; margin-top: 1em; margin-bottom: 1em; margin-left: 0;	Try it »

CSS Default Values

	margin-right: 0; padding-left: 40px;	
var	font-style: italic;	Try it »
video	None.	
wbr	None.	