
Лабараторная работа 7 OSPF

Богдан Уладзіслаў ФПМІ, 3 курс, 3 група

Схема сеткі (такая ж, як і у лабараторнай 6):



Наладжваем OSPF.

process-id = area-id = 3

На прыкладзе роўтара М1:

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#router ospf 3
Router(config-router)#network 196.5.1.0 0.0.0.255 area 3
Router(config-router)#network 196.5.2.0 0.0.0.255 area 3
Router(config-router)#network 196.5.5.0 0.0.0.255 area 3
Router(config-router)#exit
Router(config)#exit
Router#
```

show ip route on M1:

```
Router#show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
        i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
        * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route
Gateway of last resort is not set
C
     196.5.1.0/24 is directly connected, Serial0/1
     196.5.2.0/24 is directly connected, Serial0/0
0
     196.5.3.0/24 [110/128] via 196.5.1.1, 00:00:50, Serial0/1
     [110/128] via 196.5.2.2, 00:00:50, Serial0/0 196.5.4.0/24 [110/65] via 196.5.1.1, 00:00:40, Serial0/1
0
     196.5.5.0/24 is directly connected, FastEthernet0/0
0
     196.5.6.0/24 [110/65] via 196.5.2.2, 00:02:00, Serial0/0
Router#
```

праз show ip ospf вызначаем ID роўтараў:

```
Router#show ip ospf
Routing Process "ospf 3" with ID 196.5.5.1
 Supports only single TOS(TOS0) routes
 Supports opaque LSA
 SPF schedule delay 5 secs, Hold time between two SPFs 10 secs
Minimum LSA interval 5 secs. Minimum LSA arrival 1 secs
Number of external LSA 0. Checksum Sum 0x000000
 Number of opaque AS LSA 0. Checksum Sum 0x000000
 Number of DCbitless external and opaque AS LSA 0
Number of DoNotAge external and opaque AS LSA 0
 Number of areas in this router is 1. 1 normal 0 stub 0 nssa
 External flood list length 0
     Area 3
          Number of interfaces in this area is 3
          Area has no authentication
          SPF algorithm executed 8 times
          Area ranges are
Number of LSA 3. Checksum Sum 0x024e28
          Number of opaque link LSA 0. Checksum Sum 0x000000
          Number of DCbitless LSA 0
Number of indication LSA 0
          Number of DoNotAge LSA 0
          Flood list length 0
  -More-- |
```

M1 : 196.5.5.1 M2 : 196.5.4.1 M3 : 196.5.6.1

Пераканаліся, што абіраецца максімальны з актыўных ІР-адрасоў.

Праз show ip ospf neighbor правяраем адносіны суседства:

Разбіраемся з коштамі на паслядоўных інтэрфейсах. На М1 зараз маем (каманда **show ip ospf interface**):

```
RUULEI #
Router#show ip ospf interface
Serial0/1 is up, line protocol is up
  Internet address is 196.5.1.2/24, Area 3
  Process ID 3, Router ID 196.5.5.1, Network Type POINT-TO-POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
  No designated router on this network
  No backup designated router on this network
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    Hello due in 00:00:07
  Index 1/1, flood queue length 0
  Next 0x0(0)/0x0(0)
 Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1, Adjacent neighbor count is 1
    Adjacent with neighbor 196.5.4.1
  Suppress hello for 0 neighbor(s)
Serial0/0 is up, line protocol is up
 Internet address is 196.5.2.1/24, Area 3
Process ID 3, Router ID 196.5.5.1, Network Type POINT-TO-POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
  No designated router on this network
  No backup designated router on this network
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    Hello due in 00:00:07
  Index 2/2, flood queue length 0
  Next 0x\theta(\theta)/0x\theta(\theta)
  Last flood scan length is 1, maximum is 1
  Last flood scan time is 0 msec, maximum is 0 msec
  Neighbor Count is 1 , Adjacent neighbor count is 1
    Adjacent with neighbor 196.5.6.1
  Suppress hello for 0 neighbor(s)
```

Пачаткова маем кошт праходу праз паслядоўныя парты 64.

На роўтары М1 на інтэрфейс S0/0 выстаўляем кошт **2000**:

```
Router(config)#
Router(config)#interface serial 0/0
Router(config-if)#ip ospf cost 2000
Router(config-if)#exit
```

Глядзім на абноўленую табліцу з дадзенымі інтэрфейсаў:

```
Router#
Router#show ip ospf interface
Serial0/1 is up, line protocol is up
  Internet address is 196.5.1.2/24, Area 3
  Process ID 3, Router ID 196.5.5.1, Network Type POINT-TO-POINT, Cost: 64
 Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0 No designated router on this network
 No backup designated router on this network
 Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    Hello due in 00:00:00
 Index 1/1, flood queue length \Theta Next \Theta \times \Theta(\Theta) / \Theta \times \Theta(\Theta)
 Last flood scan length is 1, maximum is 1
  Last flood scan time is 0 msec, maximum is 0 msec
 Neighbor Count is 1 , Adjacent neighbor count is 1
    Adjacent with neighbor 196.5.4.1
 Suppress hello for 0 neighbor(s)
Serial0/0 is up, line protocol is up
 Internet address is 196.5.2.1/24, Area 3
 Process ID 3, Router ID 196.5.5.1, Network Type POINT-TO-POINT, Cost: 2000
 Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
 No designated router on this network
  No backup designated router on this network
```

Усё класна, усё абнавілася! Цяпер і маршруты могуць памяняцца (праз падвышэнне кошту за праход).

Правяраем узаемадасягальнасць вузлоў у сетцы.

```
Packet Tracer PC Command Line 1.0
PC>ping 196.5.5.1
Pinging 196.5.5.1 with 32 bytes of data:
Reply from 196.5.5.1: bytes=32 time=3ms TTL=253
Reply from 196.5.5.1: bytes=32 time=1ms TTL=253
Reply from 196.5.5.1: bytes=32 time=1ms TTL=253
Reply from 196.5.5.1: bytes=32 time=1ms TTL=253
Ping statistics for 196.5.5.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 3ms, Average = 1ms
PC>tracert 196.5.5.1
Tracing route to 196.5.5.1 over a maximum of 30 hops:
                            0 ms
      0 ms
                 0 ms
                                      196.5.6.1
      1 ms
                 1 ms
                          3 ms
                                      196.5.5.1
Trace complete.
PC>
```

Адключым адзін з партоў на M3 так, каб пакеты пайшлі іншым шляхам.

```
PC>ping 196.5.5.1
Pinging 196.5.5.1 with 32 bytes of data:
Reply from 196.5.5.1: bytes=32 time=2ms TTL=253
Ping statistics for 196.5.5.1:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 2ms, Average = 2ms
PC>tracert 196.5.5.1
Tracing route to 196.5.5.1 over a maximum of 30 hops:
       0 ms
                  0 ms
                              0 ms
                                         196.5.6.1
                                         196.5.3.2
  2
       0 ms
                  2 ms
                              0 ms
       1 ms
                  1 ms
                              2 ms
                                         196.5.5.1
Trace complete.
PC>
```

Пакеты знайшлі альтэрнатыўны шлях! Выдатна!