


Лабараторная работа 2 частка 1

Богдан Уладзіслаў
ФПМІ, 3 курс, 3 група



Для кожнага маршрутызатара (на прыкладзе Router2) мяняем апісанне кожнага з інтэрфейсаў:

```
Router(config)#interface FastEthernet0/0
Router(config-if)#description Left Router to Top Switch
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#descr
Router(config-if)#description Left Router to Bottom Switch
Router(config-if)#exit
Router(config)#int
Router(config)#interface Ser
Router(config)#interface Serial
% Incomplete command.
Router(config)#interface Serial0/0/0
Router(config-if)#description Serial to Top
Router(config-if)#exit
Router(config)#interface Serial0/0/1
Router(config-if)#description Serial to Right
Router(config-if)#exit
```

Дадаем паролі на прывілегіяваны рэжым доступа:
Пароль без шыфравання:

```

Router>enable
Router#
Router#
Router#
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#
Router(config)#enable password nonsecret
Router(config)#
Router(config)#
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#
Router#
Router#desable
Translating "desable"...domain server (255.255.255.255)
% Unknown command or computer name, or unable to find computer address

Router#
Router#
Router#
Router#
Router#
Router#disable
Router>
Router>
Router>
Router>enable
Password:
Router#

```

```

Router>enable
Router#
Router#
Router#
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#
Router(config)#enable password nonsecret
Router(config)#
Router(config)#
Router(config)#exit

```

Цяпер пры ўваходзе ў прывілегіяваны рэжым мы павінныя ўводзіць пароль:

```

Router>enable
Password:
Router#

```

Тое самае з паролем з шыфраваннем:

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#enable secret secret
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#disable
Router>
Router>enable
Password:
Router#
```

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#enable secret secret
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#disable
Router>
Router>enable
Password:
Router#
```

Дадаем заголоўкі:

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#banner motd # That is a custom created banner! #
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#disable
Router>
```

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#banner motd # That is a custom created banner! #
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
```

```
Router#disable
Router>
```

Дадаем імёны світкам (камутатарам) на прыкладзе Switch0:

```
Switch>enable
Switch#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname TopSwitch
TopSwitch(config)#exit
TopSwitch#
%SYS-5-CONFIG_I: Configured from console by console

TopSwitch#disable
TopSwitch>
```

```
Switch>enable
Switch#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname TopSwitch
TopSwitch(config)#exit
TopSwitch#
%SYS-5-CONFIG_I: Configured from console by console

TopSwitch#disable
TopSwitch>
```