PMP100N08

100 V N-Channel Power MOSFET - SYNTHETIC TEST DATASHEET

1. Absolute Maximum Ratings

TA = 25 C unless otherwise noted. (Tj = 125 C maximum continuous)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	VDS	100	V
Continuous Drain Current	ID	25	A
Maximum Junction Temperature	TJ	175	C

2. Electrical Characteristics

TA = 25 C unless otherwise noted.

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Drain-Source On-Resistance	RDS(on)	-	5.5	7	mOhm	VGS = 10 V, ID = 10 A, TJ = 25 C
Gate-Source Threshold Voltage	VGS(th)	2	3.5	4.5	V	ID = 250 uA
Gate-Source Voltage	VGS	-	-	20	V	
Total Gate Charge	QG	-	62	-	nC	VGS = 10 V, ID = 10 A
Gate-Drain Charge	QGD	-	12	-	nC	VGS = 10 V, ID = 10 A
Input Capacitance	CISS	-	4900	-	pF	VDS = 50 V, VGS = 0 V, f = 1 MHz
Output Capacitance	COSS	-	900	-	pF	VDS = 50 V, VGS = 0 V, f = 1 MHz
Thermal Resistance, Junction-to-Case	RthJC	-	1.2	-	C/W	
Reverse Recovery Charge	Qrr	-	120	-	nC	ID = 10 A, di/dt = 100 A/us