

## REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

## NOTES1:

UL Standard

1.Rated voltage/current : 300V / 10A

2.Wire range : 22~16AWG

## IEC Standard

1.Rated voltage/current : 250V / 15A

2.Wire range : 0.2~1.5mm<sup>2</sup>

## NOTES2:

1.Dimension shall be interpreted per ASME Y14.5-2009

2.Pitch : 5.08mm, Poles : N=01~XXP

3.Stripping length : 11mm

2.Withstanding voltage : AC2000V/1Min.

3.Operating temperature: -40°C~+105°C




4.Undimensioned tolerances:

Pitch range in mm		Nominal dimension range in mm			
TO	Over	TO	Over	TO	Over
6	10	30	60	100	150
6	10	30	60	100	150
±0.15	±0.20	±0.30	±0.50	±0.70	±1.00
±0.30	±0.50	±0.70	±1.00	±1.30	±2*

5.RoHS Compliance

DG142R - 5.08 - XXP - 1Y - 00A (H)

(Series No.) (Pitch) (Poles) (Single Pitch) (Color):1.(Grey)  
2.(Blue)  
3.(Black)  
4.(Green)  
5.(Orange)  
6.(Red)  
7.(Transparent)  
8.(Yellow)  
9.(White)

DETACHED LISTS	PART NO.: /		<div> 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD</div>			
	APPD: /		NAME: DG142R-5.08-XXP-1Y-00A(H)			
	CHKD: /					
	DRFT: /		TITLE: CUSTOMER DRAWING		REV	DO
	<div> THIRD ANGLE PROJECTION</div>		DRAWING NO.: /		SHEET	1/1
			<div> MM (INCH)</div> DO NOT SCALE DRAWING		SCALE	1:1

