

Deep Learning-Driven RF Fingerprinting for Secure IoT Authentication: A Survey of Techniques and Challenges

Author Name

Department Name, Institution Name

email@example.com

Abstract—Radio frequency (RF) fingerprinting has emerged as a critical technique for secure authentication in IoT systems, leveraging hardware-induced signal distortions. This survey paper comprehensively reviews deep learning-based methods for RF fingerprinting, addressing challenges such as open-set recognition, data scarcity, and cross-device generalization. Traditional encryption-based approaches are computationally intensive for resource-constrained IoT nodes, while RF fingerprinting offers lightweight, hardware-centric authentication. Recent advances include contrastive learning, federated systems, and self-supervised frameworks to enhance robustness against dynamic environments and adversarial attacks. The paper evaluates CNN architectures, attention mechanisms, and prototype learning strategies, highlighting their effectiveness in improving identification accuracy across WiFi, LoRa, and ZigBee devices. Key challenges such as channel variability, signal imperfections, and scalability are discussed, alongside solutions like dual attention modules and adversarial disentanglement. This work synthesizes state-of-the-art methods, identifies research gaps, and provides guidelines for future developments in secure, scalable IoT authentication.

Index Terms—['Radio Frequency Fingerprinting', 'IoT Security', 'Deep Learning', 'Authentication', 'Contrastive Learning', 'Federated Learning']

I. INTRODUCTION

The rapid proliferation of Internet of Things (IoT) devices has fundamentally transformed modern connectivity, enabling seamless integration of physical and digital systems across industries. However, this growth has also introduced significant security challenges, particularly in ensuring robust authentication mechanisms to prevent unauthorized access and mitigate cyber threats. Traditional cryptographic methods, while widely used, are increasingly vulnerable to sophisticated attacks such as side-channel analysis, quantum computing threats, and resource-intensive brute-force techniques. These vulnerabilities necessitate the exploration of alternative authentication paradigms rooted in physical layer characteristics, which leverage the inherent uniqueness of hardware imperfections to enable secure device identification. Among these, RF fingerprinting has emerged as a promising solution, capitalizing on the distinct radio frequency (RF) signatures generated by devices due to manufacturing variations, component tolerances, and environmental interactions. This approach offers a hardware-centric authentication mechanism that is resilient to cryptographic attacks and can be implemented

with minimal computational overhead, making it particularly suitable for resource-constrained IoT environments.

The core principle of RF fingerprinting lies in the exploitation of physical layer features that are unique to individual devices, such as phase errors, amplitude distortions, and timing variations. These characteristics are inherently tied to the hardware architecture of transceivers and are difficult to replicate or spoof, thereby providing a strong foundation for secure authentication. However, the practical implementation of RF fingerprinting faces several challenges, including the variability of channel conditions, the impact of environmental factors on signal integrity, and the need for robust feature extraction techniques to ensure reliable identification across diverse operating scenarios. Additionally, the dynamic nature of IoT networks, characterized by mobility, heterogeneous device configurations, and fluctuating signal environments, further complicates the deployment of physical layer authentication methods. To address these challenges, recent research has focused on integrating advanced machine learning and signal processing techniques to enhance the accuracy, robustness, and scalability of RF fingerprinting systems.

A critical aspect of RF fingerprinting is the ability to extract and analyze features from raw RF signals, which requires sophisticated signal processing algorithms to isolate device-specific characteristics from noise and interference. Techniques such as adaptive filtering, channel correlation analysis, and signal space representation have been employed to improve the fidelity of feature extraction, enabling more accurate device identification. Moreover, the integration of deep learning models, particularly convolutional neural networks (CNNs), has demonstrated significant potential in processing complex RF fingerprints and achieving high classification accuracy. For instance, CNNs have been trained to recognize patterns in RF signals generated by devices with spatially variant phase errors, leveraging their ability to capture hierarchical features from raw data. This has led to the development of architectures such as ResNet-50, which has achieved over 99% accuracy in distinguishing between devices based on their RF fingerprints, outperforming traditional methods that rely on handcrafted features.

Despite these advancements, the deployment of RF fingerprinting in real-world IoT environments remains constrained by several technical and practical limitations. One major chal-

challenge is the variability of channel conditions, which can introduce distortions that degrade the reliability of RF fingerprints. To mitigate this, researchers have explored the use of simulated fading channels and adaptive training strategies to enhance the robustness of authentication systems. Additionally, the need for cross-receiver adaptation has emerged as a critical issue, as devices may exhibit different RF characteristics when operating in varying environments or with different transceivers. This has led to the development of domain adaptation techniques, such as adversarial training and feature disentanglement, which aim to improve the generalizability of RF fingerprinting models across diverse deployment scenarios. Furthermore, the integration of federated learning frameworks has been proposed to enable scalable and privacy-preserving authentication, allowing devices to collaboratively train models without sharing sensitive data.

The convergence of IoT with Industry 4.0 has further intensified the demand for secure authentication mechanisms, as the proliferation of interconnected devices in industrial settings introduces new vulnerabilities to cyber-physical systems. In this context, RF fingerprinting has been positioned as a critical enabler of physical layer security, offering a means to authenticate devices without relying on cryptographic protocols that may be compromised. However, the implementation of such systems requires addressing challenges related to computational complexity, energy efficiency, and the integration of hardware-specific features into existing security frameworks. For example, the use of software-defined radio (SDR) gateways and edge computing platforms has been proposed to facilitate adaptive and scalable authentication, enabling real-time processing of RF signals while minimizing latency. Additionally, the incorporation of lightweight CNN architectures has been explored to reduce computational overhead, making RF fingerprinting feasible for resource-constrained IoT devices such as ZigBee and LoRa nodes.

Another significant area of research has focused on the development of open-set recognition systems for RF fingerprinting, which address the limitations of closed-set assumptions by enabling the detection of unknown devices. This has led to the exploration of techniques such as prototype learning with consistency regularization and label smoothing, which enhance the ability of models to reject suspicious or unregistered devices. The effectiveness of these methods has been validated through benchmarking on datasets such as WIDEFT, where they demonstrated superior rejection rates and accuracy compared to traditional approaches. Furthermore, the integration of contrastive learning and data augmentation strategies has been shown to improve the generalization of RF fingerprinting models, particularly in scenarios with limited labeled data. These advancements underscore the importance of combining domain-specific knowledge with machine learning techniques to overcome the inherent limitations of RF fingerprinting in dynamic and adversarial environments.

The practical deployment of RF fingerprinting also necessitates the consideration of hardware imperfections and their impact on signal integrity. For instance, the presence of I/Q

imbalance in transceivers can introduce distortions that affect the accuracy of RF fingerprints, requiring specialized signal processing techniques to mitigate these effects. Techniques such as adaptive filtering and signal space representation have been employed to correct for I/Q imbalance, ensuring that the extracted features remain representative of the device's unique characteristics. Additionally, the use of statistical methods such as singular value decomposition (SVD) has been explored to enhance feature learning and improve the robustness of authentication systems against environmental noise. These approaches highlight the importance of tailoring signal processing strategies to the specific hardware configurations of IoT devices, ensuring that the extracted RF fingerprints are both unique and reliable.

In parallel, the integration of RF fingerprinting with other physical layer security mechanisms has been investigated to create multi-layered authentication frameworks. For example, the combination of RF fingerprints with channel state information (CSI) has been proposed to enhance the security of wireless communication systems, leveraging the unique characteristics of both signal and channel features. This hybrid approach has demonstrated improved resilience against spoofing attacks and has been validated through simulations and real-world experiments. Moreover, the use of attention mechanisms in deep learning models has been explored to improve the interpretability and efficiency of RF fingerprinting systems, enabling the identification of critical features that contribute to device authentication. These innovations reflect the growing emphasis on combining physical layer characteristics with advanced machine learning techniques to achieve robust and scalable authentication solutions.

The evolution of RF fingerprinting as a secure authentication mechanism for IoT devices is closely tied to the broader trends in wireless communication and cybersecurity. As the demand for secure and scalable authentication grows, the integration of RF fingerprinting with emerging technologies such as federated learning, edge computing, and AI-driven signal processing will play a pivotal role in addressing the challenges of real-world deployment. However, the successful implementation of these solutions requires overcoming technical barriers such as computational complexity, energy efficiency, and the need for standardized frameworks that support cross-platform compatibility. Future research directions include the development of self-adaptive techniques that can dynamically adjust to changing environmental conditions and the exploration of heterogeneous ecosystem management strategies to ensure seamless integration with existing security protocols. By addressing these challenges, the field of RF fingerprinting can continue to advance, providing a reliable and secure foundation for the next generation of IoT networks.

II. LITERATURE REVIEW

The rapid proliferation of Internet of Things (IoT) devices has intensified the demand for secure authentication mechanisms, particularly in environments where traditional cryptographic methods face vulnerabilities to advanced attacks.

This has spurred research into physical layer solutions, such as RF fingerprinting, which leverages hardware imperfections to create unique device identifiers. Early work focused on traditional encryption techniques, but their susceptibility to sophisticated attacks necessitated the exploration of alternative approaches rooted in signal processing and machine learning. RF fingerprinting emerged as a promising solution, capitalizing on the inherent variability in radio frequency (RF) signals generated by devices due to factors like antenna geometry, feed line configurations, and I/Q imbalance. These physical layer features, often imperceptible to conventional systems, offer a foundation for robust authentication frameworks. However, the effectiveness of RF fingerprinting has been constrained by challenges such as channel variations, environmental noise, and the need for adaptive models capable of operating in dynamic conditions. Recent advancements have integrated deep learning techniques to enhance the reliability and scalability of these methods, addressing limitations in traditional signal processing approaches while enabling real-time authentication in complex networks.

The evolution of RF fingerprinting has been marked by a shift from manual feature extraction to data-driven models that automate the identification of unique device signatures. Early studies emphasized the role of hardware imperfections, such as I/Q imbalance, in generating distinguishable fingerprints. Techniques like adaptive filtering and channel correlation were employed to analyze these imbalances, but their performance was often limited by the static nature of signal characteristics and the inability to adapt to changing environments. The introduction of deep learning, particularly convolutional neural networks (CNNs), has transformed this landscape by enabling the extraction of high-dimensional features from raw RF signals. For instance, CNNs have been trained to process simulated Rayleigh fading channels, demonstrating robustness to channel variations and achieving accuracy rates exceeding 99% in some cases. This shift underscores the growing reliance on machine learning to model the complex, non-linear relationships inherent in RF fingerprinting. However, the integration of deep learning has also introduced new challenges, such as the need for extensive labeled datasets and the computational demands of training large models. Researchers have addressed these issues through innovations like semi-supervised learning, contrastive learning, and data augmentation strategies, which reduce dependency on labeled data while improving generalization across diverse environments.

A critical aspect of RF fingerprinting is its ability to operate in real-world scenarios, where factors like multipath propagation, device aging, and temperature fluctuations can degrade signal quality. Studies have highlighted the importance of adaptive models that can mitigate these effects, ensuring consistent performance across varying conditions. For example, the use of SDR (Software-Defined Radio) gateways and Edge/Cloud integration has enabled scalable authentication frameworks capable of handling dynamic network topologies. These systems leverage AI-driven feature extraction to adapt to environmental changes, maintaining authentication accuracy

even in the presence of channel impairments. Additionally, the development of domain adaptation techniques has been pivotal in addressing the challenge of cross-receiver variability. Methods such as adversarial training and feature disentanglement have been employed to improve the invariance of fingerprints across different hardware platforms, reducing the need for extensive retraining. This is particularly relevant in scenarios like Industry 4.0, where the deployment of heterogeneous devices requires robust, self-adaptive authentication mechanisms. The integration of these techniques has not only enhanced the reliability of RF fingerprinting but also expanded its applicability to emerging domains such as cognitive radio networks and secure IoT ecosystems.

The application of RF fingerprinting extends beyond authentication to include anomaly detection and secure communication protocols. Recent work has explored the use of open-set recognition frameworks to address the limitations of closed-set assumptions, enabling systems to distinguish between known devices and unknown threats. Techniques like prototype learning with consistency regularization and label smoothing have been proposed to improve rejection rates and accuracy in detecting adversarial signals. These methods are particularly valuable in environments where the presence of unknown devices or malicious actors could compromise network security. Furthermore, the incorporation of attention mechanisms and specialized architectures like DAConv (Depthwise Adaptive Convolution) has enhanced the ability of models to focus on critical features while suppressing noise. This has led to significant improvements in performance metrics, such as the 99.53% accuracy achieved by DeepCRF in real-world scenarios, which outperforms traditional baselines. However, the effectiveness of these models is contingent on the quality of data and the ability to handle environmental variations, which remain persistent challenges in practical deployments.

Despite these advancements, the field continues to grapple with fundamental limitations, including the reliance on signal features that are sensitive to SNR (Signal-to-Noise Ratio) and the computational overhead of deep learning models. Studies have emphasized the need for lightweight architectures that balance performance with resource constraints, particularly for deployment on edge devices. For instance, the development of lightweight CNNs with separable convolutions and dropout mechanisms has enabled high accuracy while reducing parameter counts, making them suitable for low-cost Zigbee devices. Additionally, the exploration of self-supervised learning and federated learning frameworks has addressed the scarcity of labeled data and the need for privacy-preserving authentication mechanisms. These approaches not only improve scalability but also align with the growing demand for decentralized and secure IoT ecosystems. As the field progresses, the integration of RF fingerprinting with emerging technologies such as quantum-resistant cryptography and blockchain is being explored to further strengthen security against evolving threats.

The synthesis of these efforts highlights a paradigm shift in secure authentication, where physical layer features and

machine learning are synergistically combined to address the complexities of modern communication networks. While challenges such as channel robustness, environmental noise, and cross-device variability persist, the continuous refinement of deep learning techniques and domain adaptation strategies has significantly advanced the feasibility of RF fingerprinting. Future research is likely to focus on standardizing these methods, integrating them with existing security frameworks, and addressing the limitations of current models through hybrid approaches that combine the strengths of traditional signal processing and data-driven learning. The ultimate goal remains the development of secure, scalable, and adaptive authentication solutions that can meet the demands of next-generation wireless networks while mitigating the risks associated with traditional cryptographic methods.

III. METHODOLOGY ANALYSIS

The methodology analysis of secure IoT authentication through physical layer techniques, particularly RF fingerprinting, reveals a convergence of hardware imperfections, machine learning, and signal processing to address the vulnerabilities of traditional cryptographic methods. Central to this approach is the exploitation of unique hardware characteristics, such as I/Q imbalance, phase errors, and channel-specific features, which serve as fingerprints for device identification. These fingerprints are often enhanced through advanced signal processing techniques, including adaptive filtering, channel correlation, and signal space representation, to mitigate the effects of environmental noise and channel impairments. The integration of deep learning models, such as convolutional neural networks (CNNs), has further enabled the extraction and classification of these features with high accuracy, even under varying channel conditions. However, the methodologies employed across different studies highlight both the strengths and limitations of these approaches, particularly in terms of robustness, computational complexity, and scalability.

A recurring theme in the methodologies is the use of deep learning to process RF fingerprints, with CNNs being a dominant architecture. For instance, ResNet-50 and other CNN variants have demonstrated exceptional accuracy in classifying device fingerprints, achieving up to 99.2% accuracy in some cases. These models are often trained on simulated Rayleigh fading channels or real-world datasets, such as LTE/USRP and WIDEFT, to ensure robustness against channel variations. The incorporation of data augmentation techniques, such as contrastive learning and domain adaptation, further enhances the generalization capabilities of these models. For example, the DeepCRF framework leverages contrastive learning and data augmentation to extract micro-CSI features, achieving 99.53% accuracy in real-world scenarios. Similarly, the DAConv architecture integrates attention mechanisms with CNNs to improve feature learning and noise resilience, demonstrating significant performance improvements over traditional methods on USRP X310 datasets. These approaches underscore the importance of adapting deep learning techniques to the specific challenges of

RF fingerprinting, such as handling environmental noise and maintaining accuracy across diverse channel conditions.

The methodologies also emphasize the need for hardware-specific optimizations to enhance the reliability of RF fingerprints. For example, the use of SDR gateways and Edge/Cloud integration enables adaptive and scalable authentication mechanisms for IIoT environments, addressing the limitations of traditional PHY-layer techniques that rely on limited signal features and SNR dependency. Similarly, the CSCNet architecture introduces a three-pronged loss function and source-free adaptation framework to improve cross-receiver adaptation, demonstrating a 24% accuracy gain in short-term adaptation and 9% in long-term adaptation. These innovations highlight the role of AI-driven feature extraction and domain adaptation in overcoming the challenges of cross-device and cross-environment variability. However, the reliance on hardware-specific features also introduces complexities, such as the need for calibration to account for device aging, temperature effects, and other environmental factors. Techniques like SVD-based feature learning and the LjungBox test for feature selection are employed to address these challenges, ensuring that the extracted features remain statistically robust and invariant to external perturbations.

Another critical aspect of the methodologies is the integration of semi-supervised and self-supervised learning to reduce the dependency on labeled data. For instance, the DMEL framework combines CVCNN with metric losses and ensemble classifiers to enable few-shot learning for SEI, achieving 98% accuracy with minimal labeled samples. Similarly, the RF-SSL framework leverages contrastive pre-training and domain-informed augmentations to improve invariant feature extraction, demonstrating performance improvements in few-shot accuracy and anomaly detection. These approaches are particularly relevant in scenarios where labeled data is scarce or expensive to obtain, such as in real-world IoT deployments. However, the effectiveness of these methods is contingent on the quality of the unlabeled data and the design of the augmentation strategies, which must balance the need for diversity with the risk of introducing noise or bias.

The methodologies also address the limitations of traditional RF fingerprinting techniques, such as the reliance on steady-state signals and the challenges of transient analysis. For example, the FrFT-based approach for transient signal analysis, combined with RPCA for dimensionality reduction and KNN classification, achieves a 100% recognition rate at 20 dB SNR, showcasing the potential of time-frequency analysis in enhancing wireless network security. Similarly, the use of frequency domain analysis with k-NN classifiers for device identification highlights the trade-offs between spectral resolution, SNR, and classifier performance, emphasizing the need for adaptive algorithms that can dynamically adjust to varying environmental conditions. These techniques are particularly valuable in dynamic networks with high mobility and changing topologies, where traditional methods may struggle to maintain accuracy.

Despite the advancements in these methodologies, several

challenges remain. The computational demands of deep learning models, such as CNNs and contrastive learning frameworks, can be a barrier to real-time deployment in resource-constrained IoT devices. Techniques like lightweight CNN architectures with separable convolutions and dropout are proposed to address this, achieving high accuracy with significant parameter reduction. However, the trade-off between model complexity and identification performance must be carefully balanced, especially for low-cost devices like ZigBee modules. Additionally, the robustness of RF fingerprints to adversarial attacks and environmental noise remains a critical area for further research, as demonstrated by the need for adversarial disentanglement and domain adaptation techniques to ensure long-term reliability.

In summary, the methodologies presented in the reviewed studies collectively demonstrate the potential of physical layer techniques, particularly RF fingerprinting, to secure IoT networks. The integration of deep learning, signal processing, and domain adaptation has enabled the development of robust and scalable authentication mechanisms, capable of addressing the limitations of traditional cryptographic methods. However, the practical implementation of these approaches requires careful consideration of hardware constraints, computational efficiency, and environmental variability. Future research should focus on refining these methodologies to enhance their adaptability, reduce computational overhead, and ensure resilience against emerging threats, thereby advancing the deployment of secure, low-cost IoT authentication solutions.

IV. CHALLENGES AND FUTURE DIRECTIONS

The rapid proliferation of Internet of Things (IoT) devices has intensified the demand for secure authentication mechanisms, particularly in environments where traditional cryptographic methods face vulnerabilities to advanced attacks. Physical layer techniques, such as RF fingerprinting, have emerged as promising alternatives by leveraging hardware imperfections and signal characteristics inherent to wireless communication. However, the deployment of these methods in real-world scenarios is hindered by a range of challenges, including environmental variability, channel impairments, and the need for robustness against adversarial conditions. These challenges necessitate the integration of advanced machine learning (ML) and deep learning (DL) techniques to enhance the reliability and scalability of RF-based authentication systems. This section synthesizes the key challenges and future directions in the field, emphasizing the interplay between physical layer features, ML/DL innovations, and practical deployment constraints.

A central challenge in RF fingerprinting lies in the variability of signal characteristics across different operating conditions. Environmental factors such as temperature fluctuations, device aging, and multipath effects can introduce significant distortions in the captured signals, reducing the uniqueness and reliability of fingerprints. For instance, studies have highlighted the sensitivity of traditional methods to channel variations, where simulated Rayleigh fading channels can degrade

the performance of convolutional neural networks (CNNs) if not properly accounted for. Similarly, the reliance on steady-state signal analysis in frequency domain approaches often fails to capture transient behaviors, limiting their applicability in dynamic environments. Addressing these issues requires the development of adaptive signal processing techniques that can dynamically compensate for environmental changes while maintaining the integrity of the fingerprint features.

Another critical limitation is the scarcity of labeled data for training ML models, which hampers the scalability of RF fingerprinting systems. Many existing approaches depend on supervised learning frameworks that require extensive datasets for accurate classification, yet real-world deployment often involves limited or unlabelled data. This has led to the exploration of self-supervised and semi-supervised learning strategies, such as contrastive learning and domain-invariant augmentation, to mitigate the dependency on labeled samples. For example, recent work has demonstrated the effectiveness of contrastive learning in enhancing generalization across different channel conditions, while federated learning frameworks have been proposed to enable collaborative training without compromising data privacy. However, these methods face trade-offs between computational complexity and model performance, necessitating further optimization to balance efficiency with accuracy.

The integration of RF fingerprinting with existing security frameworks presents additional challenges, particularly in ensuring compatibility with cryptographic protocols and standardization efforts. While physical layer authentication offers inherent advantages in terms of low computational overhead and resistance to certain types of attacks, its adoption requires seamless integration with higher-layer security mechanisms. This includes addressing interoperability issues between different fingerprinting techniques and cryptographic algorithms, as well as ensuring compliance with industry standards for secure communication. For instance, the deployment of RF fingerprinting in Industrial Internet of Things (IIoT) environments demands robust solutions to handle the heterogeneity of devices and the dynamic nature of industrial networks. This has spurred research into hybrid architectures that combine physical layer features with traditional cryptographic methods, aiming to create a layered defense strategy against both physical and cyber threats.

The scalability of RF fingerprinting systems is further complicated by the need to handle large-scale IoT deployments, where the diversity of devices and operating conditions can introduce significant variability. Techniques such as domain adaptation and transfer learning have been proposed to address this challenge by enabling models trained on one dataset to generalize to new environments. For example, adversarial domain adaptation methods have shown promise in improving the robustness of fingerprinting systems across different hardware platforms and channel conditions. However, the effectiveness of these approaches depends on the quality of the source data and the ability to capture invariant features that remain consistent across domains. Future work must focus on

refining these techniques to ensure they can operate efficiently in resource-constrained environments while maintaining high accuracy.

Looking ahead, the future of RF fingerprinting in secure IoT and wireless networks hinges on the continued advancement of ML/DL methodologies tailored to the unique characteristics of physical layer signals. One promising direction is the development of attention-based architectures, such as the DA-Conv model, which enhances feature learning by dynamically weighting relevant signal components. These models can improve robustness against environmental noise and enable more accurate identification of devices under varying conditions. Additionally, the integration of edge computing and cloud-based analytics offers opportunities to optimize the trade-off between computational complexity and real-time performance, particularly in resource-limited IoT devices.

Another critical area for future research is the standardization of RF fingerprinting protocols and the establishment of benchmarking frameworks to evaluate the performance of different techniques. The lack of standardized datasets and evaluation metrics has hindered the comparison of methods across studies, making it difficult to identify the most effective approaches for specific applications. Efforts to create open-source datasets and standardized testing environments will be essential to accelerate the adoption of RF fingerprinting in both academic and industrial settings. Furthermore, the exploration of novel physical layer features, such as micro-CSI (channel state information) and hardware imperfections, could unlock new possibilities for secure authentication while reducing reliance on traditional cryptographic methods.

In conclusion, the challenges and future directions in RF fingerprinting for secure IoT and wireless networks underscore the need for a multidisciplinary approach that combines advances in signal processing, ML/DL, and system design. By addressing the limitations of existing methods through adaptive signal processing, scalable learning frameworks, and robust integration with security protocols, researchers can pave the way for more resilient and efficient authentication solutions. The continued evolution of these techniques will play a pivotal role in safeguarding the integrity of IoT ecosystems against emerging threats, ensuring their viability in the increasingly complex and interconnected digital landscape.

V. CONCLUSION

The rapid proliferation of Internet of Things (IoT) devices has intensified the demand for secure authentication mechanisms, particularly in environments where traditional cryptographic methods face vulnerabilities to advanced attacks. Physical layer solutions, such as RF fingerprinting, have emerged as promising alternatives by leveraging hardware imperfections inherent in wireless transceivers. These imperfections, including spatial phase errors, I/Q imbalance, and channel-specific characteristics, serve as unique identifiers for device authentication. Recent advancements in deep learning have further enhanced the feasibility of these approaches,

enabling robust authentication even in the presence of environmental noise, channel variations, and dynamic network conditions. However, the transition from theoretical models to real-world deployment remains a critical challenge, requiring careful consideration of scalability, computational efficiency, and integration with existing security frameworks. This synthesis of findings underscores the transformative potential of RF fingerprinting combined with machine learning techniques, while also highlighting the unresolved issues that necessitate further research.

The core of secure IoT authentication lies in the ability to distinguish legitimate devices from adversaries while maintaining resilience against evolving threats. RF fingerprinting, which exploits the unique physical layer characteristics of transmitters, has demonstrated significant promise in this regard. Studies have shown that spatially variant phase errors generated by antenna arrays and feed line configurations can be effectively captured and analyzed using deep convolutional neural networks (CNNs). For instance, ResNet-50 has achieved 99.2% accuracy in classifying devices based on RF fingerprints, outperforming traditional methods that rely on static features. Similarly, the integration of contrastive learning and data augmentation strategies has enabled models like DeepCRF to achieve 99.53% accuracy in real-world scenarios, even under varying signal-to-noise ratio (SNR) conditions. These results underscore the potential of deep learning to extract discriminative features from complex, high-dimensional data, thereby enhancing the reliability of physical layer authentication.

Despite these successes, the practical deployment of RF fingerprinting faces several challenges. One major limitation is the sensitivity of these methods to environmental factors such as channel impairments, device aging, and temperature fluctuations. For example, studies have shown that the performance of RF fingerprinting techniques can degrade significantly in the presence of multipath fading or when devices operate under different SNR conditions. To address this, researchers have proposed adaptive frameworks that combine AI-driven feature extraction with edge/cloud integration, enabling real-time adjustments to mitigate the impact of channel variations. Additionally, the reliance on limited signal features in traditional approaches has prompted the exploration of more comprehensive feature sets, such as those derived from micro-CSI (channel state information) or transient signal analysis. These innovations aim to improve the robustness of authentication systems while reducing the dependency on idealized assumptions about signal behavior.

The integration of machine learning with physical layer techniques also raises important questions about scalability and computational demands. While deep learning models like CNNs and contrastive representation learning have demonstrated high accuracy, their implementation on resource-constrained IoT devices remains a challenge. Lightweight architectures, such as separable convolutions and parameter-efficient designs, have been proposed to balance performance with computational efficiency. For instance, a lightweight

CNN achieved 100% accuracy for ZigBee devices with a significant reduction in model parameters, making it suitable for low-cost, energy-efficient applications. However, the trade-off between model complexity and identification accuracy remains a critical consideration, particularly in scenarios where real-time processing is required. Future work must focus on optimizing these models for edge devices while maintaining their ability to generalize across diverse operating conditions.

Another critical aspect of RF fingerprinting is its compatibility with existing security frameworks and the need for standardization. While individual studies have demonstrated the effectiveness of their proposed methods, the lack of standardized protocols for data collection, feature extraction, and authentication has hindered broader adoption. For example, the development of federated learning approaches for RFFI (Radio Frequency Fingerprinting for Identification) has shown promise in addressing data privacy concerns and enabling collaborative training across distributed networks. However, challenges such as trainability, scalability, and security in federated settings must be resolved to ensure seamless integration with existing systems. Additionally, the need for self-adaptive techniques that can dynamically adjust to changing network environments is becoming increasingly evident, particularly in the context of Industry 4.0 and cognitive radio networks. These systems require authentication mechanisms that can adapt to temporal shifts, hardware variations, and heterogeneous device ecosystems, which necessitates the development of more flexible and resilient algorithms.

The potential of RF fingerprinting extends beyond device authentication to broader applications in secure communication and network management. For instance, the use of frequency domain analysis combined with k-NN classifiers has enabled low-cost transmitter identification in cellular networks, while techniques like fractional Fourier transform (FrFT) and robust principal component analysis (RPCA) have enhanced the accuracy of transient signal analysis. These methods are particularly valuable in environments with high mobility and dynamic topologies, where traditional cryptographic methods may struggle to maintain security. However, the effectiveness of these techniques depends heavily on the quality of the underlying data and the ability to mitigate interference from external sources. Future research should focus on improving the robustness of these methods against adversarial attacks and ensuring their compatibility with emerging wireless standards.

The challenges and opportunities in RF fingerprinting research also highlight the importance of interdisciplinary collaboration. The integration of signal processing, machine learning, and network security requires a holistic approach that addresses both technical and practical constraints. For example, the development of domain adaptation techniques for RFFI has shown that adversarial training and feature disentanglement can significantly improve the generalization of models across different hardware platforms and environmental conditions. Similarly, the use of self-supervised learning frameworks has enabled the extraction of invariant features

from raw IQ data, reducing the reliance on labeled datasets and enhancing the scalability of authentication systems. These advancements underscore the potential of combining domain-specific knowledge with machine learning to create more adaptive and secure solutions.

In conclusion, the convergence of RF fingerprinting and deep learning represents a significant step forward in securing IoT and wireless networks. The ability to leverage hardware imperfections as unique identifiers, combined with the robustness of machine learning models, offers a viable alternative to traditional cryptographic methods. However, the path to widespread adoption requires overcoming several technical and operational challenges, including the need for real-world validation, standardization, and integration with existing security infrastructures. Future research should prioritize the development of self-adaptive techniques, federated learning frameworks, and lightweight models that can operate efficiently in resource-constrained environments. By addressing these challenges, the field can unlock the full potential of physical layer authentication, ensuring the security and reliability of next-generation wireless systems.

REFERENCES

- [1] Justin McMillen, Gokhan Mumcu, Yasin Yilmaz, "Deep Learning-based RF Fingerprint Authentication with Chaotic Antenna Arrays," 2023. doi: 10.48550/ARXIV.2303.07466.
- [2] Muhammad Aqib Khan, Muhammad Usman Siddiqui, "A Comprehensive Survey on Feature Extraction Techniques Using I/Q Imbalance in RFFI," arXiv, 2025. doi: arXiv:2502.02782v1.
- [3] Weidong Wang, Hongshu Liao, Lu Gan, "Open-Set RF Fingerprinting via Improved Prototype Learning," arXiv, 2023. doi: arXiv:2306.13895v1.
- [4] Qiao Tian, Yun Lin, Xinghao Guo, Jin Wang, Osama AlFarraj, Amr Tolba, "An Identity Authentication Method of a MIoT Device Based on Radio Frequency (RF) Fingerprint Technology," Sensors, 2020. doi: 10.3390/s20041213.
- [5] HANQING GU, LISHENG SU, WEIFENG ZHANG, CHUAN RAN, "Attention is Needed for RF Fingerprinting," 2023. doi: 10.1109/ACCESS.2023.3305533.
- [6] Emmanuel Lomba, Ricardo Severino, Ana Fernandez Vilas, "Work In Progress: Towards Adaptive RF Fingerprint-based Authentication of IIoT devices," 2023. doi: arXiv:2311.15888v1.
- [7] Ruiqi Kong, He (Henry) Chen, "DeepCRF: Deep Learning-Enhanced CSI-Based RF Fingerprinting for Channel-Resilient WiFi Device Identification," 2024 IEEE Conference on Computer Communications Workshops (INFOCOM WKSHPS), 2024. doi: arXiv:2411.06925v1.
- [8] Guanxiong Shen, Junqing Zhang, Xuyu Wang, Shiwen Mao, "Federated Radio Frequency Fingerprint Identification Powered by Unsupervised Contrastive Learning," null, 2024. doi: null.
- [9] Louis Morge-Rollet, Frdric Le Roy, Denis Le Jeune, Charles Canaff, Roland Gautier, "RF eigenfingerprints, an Efficient RF Fingerprinting Method in IoT Context," Sensors, 2022. doi: 10.3390/s22114291.
- [10] Zewei Guo, Zhen Jia, JinXiao Zhu, Wenhao Huang, Yin Chen, "SMoRFFI: A Large-Scale Same-Model 2.4 GHz Wi-Fi Dataset and Reproducible Framework for RF Fingerprinting," IEICE Tech. Rep., 2024.
- [11] Woongsup Lee, Seon Yeob Baek, Seong Hwan Kim, "Deep-Learning-Aided RF Fingerprinting for NFC Security," IEEE Communications Magazine, 2021. doi: 10.1109/MCOM.001.2000912.
- [12] Jian Yang, Shaoxian Zhu, Zhongyi Wen, Qiang Li, "Cross-Receiver Radio Frequency Fingerprint Identification: A Source-Free Adaptation Approach," Sensors, 2025. doi: 10.3390/s25144451.
- [13] Jiaqi Wang, Lishu Guo, Pengfei Liu, Peng Shang, Xiaochun Lu, Hang Zhao, "A Self-Supervised Contrastive Framework for Specific Emitter Identification with Limited Labeled Data," Remote Sens., 2025. doi: 10.3390/rs17152659.

- [14] Kevin Merchant, Shauna Revay, George Stantchev, Bryan Nousain, "Deep Learning for RF Device Fingerprinting in Cognitive Communication Networks," *IEEE Journal of Selected Topics in Signal Processing*, 2018. doi: 10.1109/JSTSP.2018.2796446.
- [15] Yurui Zhao, Xiang Wang, Liting Sun, Zhitao Huang, "A novel framework for extracting moment-based fingerprint features in specific emitter identification," *EURASIP Journal on Advances in Signal Processing*, 2023. doi: 10.1186/s13634-023-00978-4.
- [16] Abdurrahman Elmaghub, Bechir Hamdaoui, Weng-Keen Wong, "ADL-ID: Adversarial Disentanglement Learning for Wireless Device Fingerprinting Temporal Domain Adaptation," *arXiv*, 2023. doi: arXiv:2301.12360v1.
- [17] Irwin O. Kennedy, Patricia Scanlon, Francis J. Mullany, Milind M. Buddhikot, Keith E. Nolan, Thomas W. Rondeau, "Radio Transmitter Fingerprinting: A Steady State Frequency Domain Approach," *IEEE*, 2008.
- [18] Yun Lin, Jie Chang, "Improving Wireless Network Security Based On Radio Fingerprinting," 2019 IEEE 19th International Conference on Software Quality, Reliability and Security Companion (QRS-C), 2019. doi: 10.1109/QRS-C.2019.00076.
- [19] Jie Ma, Junqing Zhang, Guanxiong Shen, Linning Peng, Alan Marshall, "Towards Channel-Robust Radio Frequency Fingerprint Identification Using Contrastive Learning," 2025.
- [20] Kevin Merchant, Shauna Revay, George Stantchev, Bryan Nousain, "Deep Learning for RF Device Fingerprinting in Cognitive Communication Networks," *IEEE Journal of Selected Topics in Signal Processing*, 2018. doi: 10.1109/JSTSP.2018.2796446.
- [21] Jackson Wright, Abdurrahman Elmaghub, Bechir Hamdaoui, ",", 2023.
- [22] Linning Peng, Junqing Zhang, Ming Liu, Aiqun Hu, "Deep Learning Based RF Fingerprint Identification Using Differential Constellation Trace Figure," *IEEE Transactions on Vehicular Technology*, 2019. doi: 10.1109/TVT.2019.2950670.
- [23] Yu Wang, Guan Gui, Yun Lin, Hsiao-Chun Wu, Chau Yuen, Fumiyuki Adachi, "Few-Shot Specific Emitter Identification via Deep Metric Ensemble Learning," 2022.
- [24] Weidong Wang, Cheng Luo, Jiancheng An, Lu Gan, Hongshu Liao, Chau Yuen, "Semi-Supervised RF Fingerprinting with Consistency-Based Regularization," *IEEE Internet of Things Journal*, 2023. doi: arXiv:2304.14795v1.
- [25] Jason M. McGinthy, Lauren J. Wong, Alan J. Michaels, "Groundwork for Neural Network-Based Specific Emitter Identification Authentication for IoT," *IEEE Internet of Things Journal*, 2019. doi: 10.1109/IJOT.2019.2908759.
- [26] Melaku Msresha Woldeamueal, Belay Sitotaw Goshu, "A Self-supervised Framework for Generalized RF Fingerprinting and Zero-shot Anomaly Detection in Dynamic IoT Networks," *International Journal of Emerging IoT Technologies in Smart Electronics and Communication*, 2026.
- [27] Guangwei Qing, Huifang Wang, Tingping Zhang, "Radio frequency fingerprinting identification for Zigbee via lightweight CNN," *Physical Communication*, 2021. doi: 10.1016/j.phycom.2020.101250.
- [28] Irwin O. Kennedy, Patricia Scanlon, Francis J. Mullany, Milind M. Buddhikot, Keith E. Nolan, Thomas W. Rondeau, "Radio Transmitter Fingerprinting: A Steady State Frequency Domain Approach," *IEEE*, 2008.
- [29] Yun Lin, Jie Chang, "Improving Wireless Network Security Based On Radio Fingerprinting," 2019 IEEE 19th International Conference on Software Quality, Reliability and Security Companion (QRS-C), 2019. doi: 10.1109/QRS-C.2019.00076.