

Association Rule Mining

Dr Muhammad Atif Tahir

Professor

FAST, Karachi Campus

Association Rule Mining

- Given a set of transactions, find rules that will predict the occurrence of an item based on the occurrences of other items in the transaction

Market-Basket transactions

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Example of Association Rules

$\{\text{Diaper}\} \rightarrow \{\text{Beer}\},$
 $\{\text{Milk, Bread}\} \rightarrow \{\text{Eggs, Coke}\},$
 $\{\text{Beer, Bread}\} \rightarrow \{\text{Milk}\},$

Implication means co-occurrence,
not causality!

Definition: Association Rule

□ Association Rule

- An implication expression of the form $X \rightarrow Y$, where X and Y are itemsets
- Example:
 $\{\text{Milk, Diaper}\} \rightarrow \{\text{Beer}\}$

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

□ Rule Evaluation Metrics

- Support (s)
 - ◆ Fraction of transactions that contain both X and Y
- Confidence (c)
 - ◆ Measures how often items in Y appear in transactions that contain X

Example:

$\{\text{Milk, Diaper}\} \Rightarrow \text{Beer}$

$$s = \frac{\sigma(\text{Milk, Diaper, Beer})}{|T|} = \frac{2}{5} = 0.4$$

$$c = \frac{\sigma(\text{Milk, Diaper, Beer})}{\sigma(\text{Milk, Diaper})} = \frac{2}{3} = 0.67$$

Association Rule Mining Task

- Given a set of transactions T , the goal of association rule mining is to find all rules having
 - support $\geq \textit{minsup}$ threshold
 - confidence $\geq \textit{minconf}$ threshold
 - Brute-force approach:
 - List all possible association rules
 - Compute the support and confidence for each rule
 - Prune rules that fail the *minsup* and *minconf* thresholds
- ⇒ Computationally prohibitive!

Mining Association Rules

Example of Rules:

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

$\{\text{Milk, Diaper}\} \rightarrow \{\text{Beer}\}$ (s=0.4, c=0.67)
 $\{\text{Milk, Beer}\} \rightarrow \{\text{Diaper}\}$ (s=0.4, c=1.0)
 $\{\text{Diaper, Beer}\} \rightarrow \{\text{Milk}\}$ (s=0.4, c=0.67)
 $\{\text{Beer}\} \rightarrow \{\text{Milk, Diaper}\}$ (s=0.4, c=0.67)
 $\{\text{Diaper}\} \rightarrow \{\text{Milk, Beer}\}$ (s=0.4, c=0.5)
 $\{\text{Milk}\} \rightarrow \{\text{Diaper, Beer}\}$ (s=0.4, c=0.5)


Observations:

- All the above rules are binary partitions of the same itemset:
 $\{\text{Milk, Diaper, Beer}\}$
- Rules originating from the same itemset have identical support but can have different confidence
- Thus, we may decouple the support and confidence requirements

Mining Association Rules

- Two-step approach:
 1. Frequent Itemset Generation
 - Generate all itemsets whose support \geq minsup
 2. Rule Generation
 - Generate high confidence rules from each frequent itemset, where each rule is a binary partitioning of a frequent itemset
- Frequent itemset generation is still computationally expensive

Frequent Itemset Generation




Given d items, there are 2^d possible candidate itemsets

Frequent Itemset Generation

- Brute-force approach:


- Each itemset in the lattice is a **candidate** frequent itemset
- Count the support of each candidate by scanning the database



- Match each transaction against every candidate
- Complexity $\sim O(NMw) \Rightarrow$ **Expensive** since $M = 2^d$!!!

Computational Complexity

- Given d unique items:
 - Total number of itemsets = 2^d
 - Total number of possible association rules:



$$R = \sum_{k=1}^{d-1} \left[\binom{d}{k} \times \sum_{j=1}^{d-k} \binom{d-k}{j} \right]$$
$$= 3^d - 2^{d+1} + 1$$

If $d=6$, $R = 602$ rules

Frequent Itemset Generation Strategies

- Reduce the **number of candidates** (M)
 - Complete search: $M=2^d$
 - Use pruning techniques to reduce M
- Reduce the **number of transactions** (N)
 - Reduce size of N as the size of itemset increases
- Reduce the **number of comparisons** (NM)
 - Use efficient data structures to store the candidates or transactions
 - No need to match every candidate against every transaction

Frequent Itemset Generation Strategies

- Apriori principle
- FP Tree Generation

References

- Lecture Notes for Chapter 6, Introduction to Data Mining, by Tan, Steinbach, Kumar

Questions!