Real-Time Sign Language Recognition & Captioning

Milestone 3 Core Implementation & Comparative Evaluation Report

Authors: Prince Genel Umali, Kean Gabriel Salvahan, Justin Angelo Luzande | Course: CSST 106

1. Executive Overview & Problem Statement

This project develops an edge-capable computer vision system that translates 8 static sign language word gestures (Call, Dislike, Like, Mute, OK, Palm, Peace, Stop) in real time from live webcam video streams. While our Milestone 2 baseline relied on classical YCrCb skin masking and an SVM classifier, it proved highly fragile against background skin tones, faces, and room clutter. In Milestone 3 (cp3-core), we implemented an end-to-end deep learning architecture pairing the MediaPipe Tasks API (HandLandmarker) with a Multi-Layer Perceptron (MLP) classifier. This report delivers our comprehensive quantitative benchmark on 241 unseen test images, evaluates speed vs. accuracy trade-offs against the baseline, details an empirical error analysis, and defines our Phase 4 improvement plan.

2. Milestone 3 Local Benchmark Performance (Test Split: 241 Unseen Images)

OVERALL ACCURACY
73.86%
178 / 241 Unseen Test Images

MACRO-F1 SCORE
0.778
Weighted-F1: 0.781 across 8 classes

INFERENCE LATENCY
21.18 ms
Landmark extraction + MLP inference

SYSTEM THROUGHPUT
47.2 FPS
3.1x faster than 15 FPS real-time bar

Important Note on Local Benchmark Rigor ('Honest Accuracy Metric'):

Unlike isolated academic benchmarks that discard frames where the detector fails, our local evaluation script (src/evaluate.py) penalizes all 27 dropped detections (where MediaPipe returned 'no_hand') as misclassifications. On frames where a hand was successfully detected (214/241), recognition accuracy was 82.71% (177/214). Strictly accounting for detection dropouts produces our honest end-to-end system accuracy of 73.86%.

3. Baseline (MS2 SVM) vs. Main Method (MS3 MediaPipe + MLP) Comparison

Evaluation Metric / Dimension	MS2 Baseline (HOG + SVM)	MS3 Main Method (MediaPipe + MLP)
Architecture & Pipeline	YCrCb Skin Mask + Contours + HOG + SVM	MediaPipe Tasks API (HandLandmarker) + MLP
Feature Representation	7 Hu Moments + 3 Shape Ratios + HOG (3,790-D)	21 Normalized 3D Knuckle Landmarks (x,y,z: 63-D)
Input Framing	Requires tight Hand ROI bounding boxes	Full uncropped webcam frames (640x480 RGB)
Inference Latency	6.09 ms per image (Local CPU)	**21.18 ms per image (Local CPU)**
Throughput (Speed)	164.3 FPS (exceeds 15 FPS target)	**47.2 FPS (3.1x faster than 15 FPS target)**
Controlled Val Accuracy	96.25% (on JSON-cropped hand ROIs)	83.2% (on detected landmarks)
Unseen Full-Scene Test Acc	< 30.0% (fails on uncropped scenes)	**73.86% (Honest end-to-end on 241 images)**
Macro-F1 Score	0.9627 (cropped ROI validation only)	0.778 (full unseen test split, with dropouts)
Clutter & Lighting Invariance	Very Fragile: faces, wood, walls corrupt mask	High: deep skeletal landmarks ignore skin tone/background
Real-World Feasibility	Fails live webcam test without ROI constraint	Ready for live OpenCV HUD captioning deployment

Synthesis & Architectural Trade-offs:

While the MS2 classical baseline achieves remarkable inference latency (6.09 ms, 164.3 FPS), its 96.25% accuracy is an artifact of artificial cropping with ground-truth bounding boxes. In realistic uncropped webcam feeds, classical skin thresholding fatally segments faces, arms, and warm background surfaces. The MS3 MediaPipe+MLP main method introduces a slight latency overhead (21.18 ms vs 6.09 ms), yet achieves 47.2 FPS—more than triple the 15 FPS project target—while providing the landmark-level invariance essential for unconstrained live operation.

4. Error Analysis & Quantitative Confusion Matrix Diagnostic

To satisfy the grading rubric's strict Error Analysis and Testing mandates, we evaluated the entire 241-image unseen test set using src/evaluate.py. Below, Figure 1 displays the official Confusion Matrix generated directly from the local test run, complemented by per-class precision/recall metrics and mechanical root-cause diagnoses.




Figure 1: Milestone 3 Confusion Matrix (outputs/ms3_confusion_matrix.png)

Per-Class Evaluation Breakdown (digits=3):

Class	Precision	Recall	F1-Score	Support
CALL	1.000	0.577	0.732	26 (15 ok, 11 err)
DISLIKE	0.781	0.862	0.820	29 (25 ok, 4 err)
LIKE	0.656	0.875	0.750	24 (21 ok, 3 err)
MUTE	0.870	0.833	0.851	24 (20 ok, 4 err)
OK	1.000	0.857	0.923	28 (24 ok, 4 err)
PALM	0.826	0.679	0.745	28 (19 ok, 9 err)
PEACE	0.964	1.000	0.982	27 (27 ok, 0 err)
STOP	0.703	0.929	0.800	28 (26 ok, 2 err)
OVERALL	**0.850**	**0.827**	**0.778**	**241 (27 drop)**

Key Quantitative Takeaways:

* PEACE is nearly flawless (F1: 0.982, 100% recall).
* OK and DISLIKE demonstrate robust generalization (>0.82 F1).
* CALL (recall: 0.577) & PALM (recall: 0.679) represent our primary error centers, driven by specific mechanical flaws.

Detailed Mechanical Error Analysis (The 3 Primary Failure Modes):

Flaw A: Palm vs. Stop Geometry Confusion (Look-Alike Class Problem)

Confusion Matrix Evidence: 7 true 'Palm' signs misclassified as 'Stop'; 1 'Stop' misclassified as 'Palm'.

Both gestures present an open palm with 5 extended digits. MediaPipe normalizes 3D coordinates relative to the hand bounding box, which standardizes joint positions but strips away absolute wrist pitch and forearm angle. Consequently, an open palm facing forward (Palm) and an elevated open hand (Stop) yield nearly identical 63-dimensional coordinate arrays, leading the MLP to assign borderline probabilities without directional wrist inclination.

Flaw B: Call vs. Like / Dislike Confusion (Perspective & Rotation Vulnerability)

Confusion Matrix Evidence: 5 true 'Call' signs misclassified as 'Like', 2 as 'Dislike' (11 total errors).

In natural signing, the 'Call' gesture (thumb and pinky extended, intermediate fingers curled) is performed with the wrist tilted toward the ear. When captured at oblique angles, the extended pinky is foreshortened or self-occluded behind the fist. MediaPipe's single-camera 3D projection perceives curled digits with only the thumb protruding, projecting a feature vector indistinguishable from a 'Like' or 'Dislike' fist.

Flaw C: Two-Hand Interference & Resting Hand Distraction (The 'num_hands=1' Flaw)

Confusion Matrix Evidence: Highly prevalent in uncropped full-body test frames (see fail_1, fail_7, fail_8, fail_10).

MediaPipe HandLandmarker was instantiated with num_hands=1. In natural seated postures, subjects frequently hold an idle hand on their lap or thigh while gesturing with the other. Because the resting hand is closer, static, and devoid of motion blur, the detection anchor frequently locks onto the inactive hand. The MLP correctly classifies this resting hand as a relaxed fist ('Like' or 'Mute'), discarding the active gesture.

5. The 10-Image Annotated Failure Gallery (src/evaluate.py MISMATCH Cases)

Generated via src/generate_failures.py, these 10 visual artifacts capture exact [MISMATCH] frames. Each thumbnail depicts the detected MediaPipe skeleton (red joints), ground truth label, and incorrect prediction.




#1: CALL -> MUTE
Locked to resting hand



#2: CALL -> DISLIKE
Downward thumb angle



#3: CALL -> LIKE
Pinky self-occlusion



#4: CALL -> LIKE
Oblique wrist rotation



#5: CALL -> DISLIKE
Tilt inverted thumb axis



#6: CALL -> STOP
Spread finger transition



#7: CALL -> LIKE
Lap hand distraction



#8: CALL -> LIKE
Resting hand preferred



#9: CALL -> PEACE
Pinky/thumb spread false V



#10: CALL -> MUTE
Waist fist tracked

6. Phase 4 Improvement Plan: Mechanical Causes to Concrete Solutions

Identified Failure Cause	Algorithmic & Pipeline Enhancement	Expected Impact & Verification Metric
Palm vs. Stop Confusion (Open hand geometry similarity; lack of wrist pitch angle)	1. Merge 'Palm' & 'Stop' into unified 'Open Hand' gesture in vocabulary, OR 2. Augment feature vector with wrist-to-elbow directional vector to supply absolute elevation angle to the MLP classifier.	Eliminates largest off-diagonal error cell (7 samples); Projected to increase Macro-F1 from 0.778 to > 0.815.
Call vs. Like / Dislike (Wrist tilt occludes pinky; perceived as fist)	1. Apply synthetic 3D rotation augmentation (random pitch/yaw/roll jitter up to +/-25 deg) on 3D landmarks during MLP training. 2. Retrain MLP with higher regularization (dropout / weight decay).	Makes MLP invariant to oblique viewing angles; Restores Call recall from 0.577 to > 0.800.
Resting Hand Interference (The 'num_hands=1' flaw; locks onto lap/waist hand)	1. Reconfigure MediaPipe HandLandmarker to num_hands=2. 2. Implement postprocess() heuristic selecting hand with highest vertical coordinate (closest to face/chest: min y-landmark).	Completely eliminates idle lap-hand false detections (fail_1, 7, 8, 10); Recovers 8-10 test frames; boosts full-scene accuracy to > 82%.
Single-Frame Dropouts & Temporal Prediction Flicker	1. Implement a 5-frame rolling majority voting temporal buffer. 2. Enforce confidence threshold tau = 0.75, suppressing flickering sub-threshold predictions in the live OpenCV HUD.	Smooths live captioning; stabilizes HUD display; Prevents single dropped frames from glitching subtitles.

7. Milestone 4 Roadmap & Execution Timeline (Git Tag: cp4-80)

- Deliverable 1: Live Webcam OpenCV Application (src/run.py) featuring high-contrast HUD captioning banner.
- Deliverable 2: Deployment of 5-frame temporal smoothing filter & confidence gating (tau = 0.75).
- Deliverable 3: Integration of num_hands=2 active hand heuristic, resolving lap-hand interference.
- Target Delivery: Milestone 4 80% Progress Check (Thu Nov 12, 11:30 PM). Codebase verified and frozen.