

Campus db

Database Schema Documentation

Complete Table Reference · DDL · Column Definitions

Overview

The campus database is a MySQL relational schema designed to support a campus recruitment platform. It manages the full lifecycle from student profiling, academic records, and skill tracking to company job postings, multi-round recruitment drives, and detailed exam/interview session capture.

Table Summary

Group	Tables	Count
MASTER / LOOKUP TABLES	tbl_cp_msalutation, tbl_cp_mlanguages, tbl_cp_minterests, tbl_cp_mcourses, tbl_cp_mcolleges, tbl_cp_mcertifications, tbl_cp_mskills	7
RECRUITMENT LOOKUP TABLES	tbl_cp_mmodule, tbl_cp_mdificulty, tbl_cp_mround_result, tbl_cp_mattendance, tbl_cp_minterviewer	5
GEOGRAPHY MASTER	tbl_cp_mcountries, tbl_cp_mstates, tbl_cp_mcities, tbl_cp_mpincodes	4
STUDENT CORE	tbl_cp_student	1
EDUCATION	tbl_cp_student_school, tbl_cp_student_education	2
SEMESTERS / SUBJECTS / MARKS	tbl_cp_msemester, tbl_cp_msubjects, tbl_cp_college_sem_subject, tbl_cp_student_subject_marks	4
WORK EXPERIENCE & PROJECTS	tbl_cp_student_workexp, tbl_cp_studentprojects	2
STUDENT MANY-TO-MANY	tbl_cp_m2m_std_skill, tbl_cp_m2m_std_lng, tbl_cp_m2m_std_interest, tbl_cp_m2m_student_certification, tbl_cp_m2m_studentproject_skill	5
QUESTION BANK	tbl_cp_mquestions, tbl_cp_m2m_question_options	2
COMPANY & JOB DESCRIPTION	tbl_cp_mcompany, tbl_cp_job_description	2
ADDRESS	tbl_cp_student_address, tbl_cp_college_address, tbl_cp_company_address	3
ROUND CONFIGURATION PER JD	tbl_cp_jd_round_config, tbl_cp_m2m_jd_round_module	2

Group	Tables	Count
RECRUITMENT DRIVE	tbl_cp_recruitment_drive	1
APPLICATION	tbl_cp_application, tbl_cp_application_status_history	2
EXAM SESSION	tbl_cp_exam_session, tbl_cp_m2m_exam_question_response	2
INTERVIEW SESSION	tbl_cp_interview_session, tbl_cp_m2m_session_module_score, tbl_cp_m2m_session_question_response	3

Naming & Design Conventions

All tables are prefixed with tbl_cp_. Master/lookup tables use the pattern tbl_cp_m<entity>. Many-to-many junction tables are prefixed tbl_cp_m2m_.

Every table has a row_id (AUTO_INCREMENT surrogate PK) and a separate business key column (e.g., student_id, college_id). This allows external systems to use stable business keys independently of internal row ordering.

All tables include created_at and updated_at DATETIME columns. updated_at uses ON UPDATE CURRENT_TIMESTAMP for automatic tracking.

Sentinel date values are used in place of NULL for dates: '1900-01-01' represents 'not provided / not yet set' and '9999-12-31' represents 'no expiry / open-ended'.

BOOLEAN columns are declared as BOOLEAN NULL (tri-state) rather than NOT NULL to distinguish between 'explicitly false' and 'not yet set'.

Index Summary

The following indexes are defined in addition to PRIMARY KEY and UNIQUE constraints:

Index Name(s)	Table	Indexed Columns
idx_student_email / idx_student_status	tbl_cp_student	email, status
idx_jd_company / idx_jd_job_role / idx_jd_status	tbl_cp_job_description	company_id, job_role, status
idx_round_config_jd	tbl_cp_jd_round_config	jd_id
idx_jrm_round_config / idx_jrm_module	tbl_cp_m2m_jd_round_module	round_config_id, module_id
idx_drive_jd / idx_drive_status	tbl_cp_recruitment_drive	jd_id, status
idx_application_student / _drive / _status	tbl_cp_application	student_id, drive_id, status
idx_status_history_app	tbl_cp_application_status_history	application_id
idx_exam_result / idx_exam_qr_question	tbl_cp_exam_session / m2m_exam_question_response	result_id, question_id
idx_session_* (application, round_config, interviewer, result, date)	tbl_cp_interview_session	Multiple columns
idx_sms_module / idx_sqr_question	tbl_cp_m2m_session_module_score / session_question_response	module_id, question_id
idx_question_module / _difficulty / _type	tbl_cp_mquestions	module_id, difficulty_id, question_type

Schema Alterations

The following ALTER TABLE statements were applied after initial schema creation:

```
ALTER TABLE tbl_cp_student ADD COLUMN profile_photo_url VARCHAR(500) NOT NULL DEFAULT 'not_uploaded' AFTER resume_url;  
ALTER TABLE tbl_cp_student MODIFY COLUMN profile_photo_url VARCHAR(500) NOT NULL DEFAULT 'default_profile.png';
```

The first statement adds the profile_photo_url column after resume_url with a placeholder default. The second statement updates the default value to 'default_profile.png'. The final column definition in tbl_cp_student reflects the modified state.

MASTER / LOOKUP TABLES

tbl_cp_salutation

Stores salutation options (Mr., Ms., Dr., etc.) used across the platform for addressing students and contacts.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
salutation_id	INT	NOT NULL, UNIQUE	—	Business key for salutation
value	VARCHAR(50)	NOT NULL, UNIQUE	—	Salutation text (e.g., Mr., Dr.)
description	VARCHAR(255)	—	No description	Optional explanation
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_languages

Master list of spoken/programming languages. Referenced by skills and student language associations.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
language_id	INT	NOT NULL, UNIQUE	—	Business key for language
language_code	VARCHAR(20)	NOT NULL, UNIQUE	—	Short code (e.g., EN, HI, PY)
language_name	VARCHAR(100)	NOT NULL, UNIQUE	—	Full language name

Column Name	Data Type	Constraints	Default	Description
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_minterests

Catalog of student interests/hobbies used for profiling and matching.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
interest_id	INT	NOT NULL, UNIQUE	—	Business key for interest
name	VARCHAR(150)	NOT NULL, UNIQUE	—	Interest name (e.g., AI, Gaming)
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mcourses

Defines academic courses and their specializations. Unique on (course_code, specialization_code) and (course_name, specialization_name).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
course_id	INT	NOT NULL, UNIQUE	—	Business key for course
course_name	VARCHAR(150)	NOT NULL	—	Full course name (e.g., B.Tech)
course_code	VARCHAR(50)	NOT NULL	—	Short code (e.g., BTECH)
specialization_name	VARCHAR(150)	NOT NULL	General	Specialization name
specialization_code	VARCHAR(50)	NOT NULL	GEN	Specialization short code
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp

Column Name	Data Type	Constraints	Default	Description
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_colleges

Master college registry including SPOC, TPO, and Student Coordinator contact details. Priority 1–10 (CHECK constraint).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
college_id	INT	NOT NULL, UNIQUE	—	Business key for college
college_name	VARCHAR(255)	NOT NULL, UNIQUE	—	Full college name
spoc_name	VARCHAR(150)	—	Not Assigned	Single Point of Contact name
spoc_phone	VARCHAR(20)	—	0000000000	SPOC phone number
spoc_email	VARCHAR(255)	—	noreply@college.com	SPOC email address
tpo_name	VARCHAR(150)	—	Not Assigned	Training & Placement Officer name
tpo_phone	VARCHAR(20)	—	0000000000	TPO phone number
tpo_email	VARCHAR(255)	—	noreply@college.com	TPO email address
student_coordinator_name	VARCHAR(150)	—	Not Assigned	Student coordinator name
student_coordinator_phone	VARCHAR(20)	—	0000000000	Student coordinator phone
student_coordinator_email	VARCHAR(255)	—	noreply@college.com	Student coordinator email
reference_details	TEXT	—	NULL	Free-text reference notes
priority	INT	NOT NULL, CHECK(1–10)	5	College priority level (1=highest)
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp

Column Name	Data Type	Constraints	Default	Description
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mcertifications

Catalog of professional certifications. Unique on (certification_name, issuing_organization). Validity can be time-bound or lifetime.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
certification_id	INT	NOT NULL, UNIQUE	—	Business key for certification
certification_name	VARCHAR(255)	NOT NULL	—	Certification name
certification_code	VARCHAR(100)	NOT NULL, UNIQUE	—	Unique short code
issuing_organization	VARCHAR(255)	NOT NULL	—	Issuing body name
certification_type	VARCHAR(100)	—	General	Category (e.g., Technical, Soft Skills)
mode	VARCHAR(50)	—	Online	Delivery mode (Online/Offline)
validity_period_value	INT	—	0	Numeric validity duration
validity_period_unit	VARCHAR(20)	—	Years	Unit of validity (Years/Months)
is_lifetime	BOOLEAN	NULL	NULL	True if certification never expires
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mskills

Technical/soft skills catalog. Each skill is linked to a language (FK to tbl_cp_mlanguages) and has complexity and status fields.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key

Column Name	Data Type	Constraints	Default	Description
skill_id	INT	NOT NULL, UNIQUE	—	Business key for skill
name	VARCHAR(100)	NOT NULL, UNIQUE	—	Skill name (e.g., Django, SQL)
description	VARCHAR(255)	—	No description	Skill description
language_id	INT	NOT NULL, FK → tbl_cp_mlanguages	—	Associated language
version	VARCHAR(50)	—	N/A	Skill/framework version
complexity	VARCHAR(50)	—	Beginner	Complexity level
status	VARCHAR(30)	—	Active	Skill availability status
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

RECRUITMENT LOOKUP TABLES

tbl_cp_mmodule

Defines assessment modules (e.g., Aptitude, Communication). has_questions = FALSE indicates a manually scored module.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
module_id	INT	NOT NULL, UNIQUE	—	Business key for module
module_name	VARCHAR(150)	NOT NULL, UNIQUE	—	Module name
module_code	VARCHAR(50)	NOT NULL, UNIQUE	—	Short code for module
description	VARCHAR(255)	—	No description	Module description
has_questions	BOOLEAN	NULL	NULL	False = manually scored module
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mdificulty

Question difficulty levels with associated score weights (e.g., Easy=1.0, Hard=1.5).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
difficulty_id	INT	NOT NULL, UNIQUE	—	Business key for difficulty
level_code	VARCHAR(20)	NOT NULL, UNIQUE	—	Short code (e.g., EASY, MED, HARD)
level_label	VARCHAR(50)	NOT NULL	—	Display label
score_weight	DECIMAL(4,2)	NOT NULL	1.00	Multiplier applied to base marks
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mround_result

Lookup for round result labels: Pass, Fail, Selected, Not Selected, Absent, Cheating.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
result_id	INT	NOT NULL, UNIQUE	—	Business key for result
label	VARCHAR(100)	NOT NULL, UNIQUE	—	Result label
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mattendance

Attendance code lookup. Codes: P=Present, A=Absent, R=Rejected, C=Cheating.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
attendance_id	INT	NOT NULL, UNIQUE	—	Business key for attendance

Column Name	Data Type	Constraints	Default	Description
code	VARCHAR(5)	NOT NULL, UNIQUE	—	Single-character code (P/A/R/C)
label	VARCHAR(50)	NOT NULL	—	Full label (Present/Absent/etc.)
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_minterviewer

Registry of interviewers — both internal mentors and external client representatives. is_internal distinguishes them.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
interviewer_id	INT	NOT NULL, UNIQUE	—	Business key for interviewer
name	VARCHAR(150)	NOT NULL	—	Interviewer full name
email	VARCHAR(255)	—	noreply@interviewer.com	Contact email
phone	VARCHAR(20)	—	0000000000	Contact phone
is_internal	BOOLEAN	NULL	NULL	True = internal mentor
company	VARCHAR(255)	—	Campus4	Company/organization
designation	VARCHAR(150)	—	Interviewer	Job title
is_active	BOOLEAN	NULL	NULL	Active status flag
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

GEOGRAPHY MASTER

tbl_cp_mcountries

Country master with ISO codes.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key

Column Name	Data Type	Constraints	Default	Description
country_id	INT	NOT NULL, UNIQUE	—	Business key
country_name	VARCHAR(100)	NOT NULL, UNIQUE	—	Country full name
country_code	VARCHAR(5)	NOT NULL, UNIQUE	—	ISO country code
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mstates

State master linked to countries. Unique on (state_name, country_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
state_id	INT	NOT NULL, UNIQUE	—	Business key
state_name	VARCHAR(100)	NOT NULL	—	State/province name
state_code	VARCHAR(10)	—	XX	State abbreviation code
country_id	INT	NOT NULL, FK → tbl_cp_mcountries	—	Parent country
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mcities

City master linked to states. Unique on (city_name, state_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
city_id	INT	NOT NULL, UNIQUE	—	Business key
city_name	VARCHAR(100)	NOT NULL	—	City name
state_id	INT	NOT NULL, FK → tbl_cp_mstates	—	Parent state

Column Name	Data Type	Constraints	Default	Description
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_mpincodes

Pincode (ZIP) master linked to cities, includes optional area name.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
pincode_id	INT	NOT NULL, UNIQUE	—	Business key
pincode	VARCHAR(20)	NOT NULL, UNIQUE	—	Pincode/ZIP value
city_id	INT	NOT NULL, FK → tbl_cp_mcities	—	Parent city
area_name	VARCHAR(150)	—	Unknown Area	Locality/area label
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

STUDENT CORE

tbl_cp_student

Central student profile table. Contains personal details, contact information, online presence links, and status flags. date_of_birth='1900-01-01' indicates not provided. Includes profile_photo_url (added via ALTER).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
student_id	INT	NOT NULL, UNIQUE	—	Business key for student
salutation_id	INT	FK → tbl_cp_msalutation	NULL	Salutation reference
first_name	VARCHAR(100)	NOT NULL	—	Student first name
middle_name	VARCHAR(100)	—	"	Middle name

Column Name	Data Type	Constraints	Default	Description
last_name	VARCHAR(100)	—	"	Last name
email	VARCHAR(255)	NOT NULL, UNIQUE	—	Primary email address
alt_email	VARCHAR(255)	—	"	Alternate email
contact_number	VARCHAR(20)	UNIQUE	NULL	Primary phone number
alt_contact_number	VARCHAR(20)	—	0000000000	Alternate phone number
linkedin_url	VARCHAR(255)	—	"	LinkedIn profile URL
github_url	VARCHAR(255)	—	"	GitHub profile URL
portfolio_url	VARCHAR(255)	—	"	Portfolio/website URL
resume_url	VARCHAR(500)	—	"	Resume file URL
profile_photo_url	VARCHAR(500)	NOT NULL	default_profile.png	Profile photo URL (added via ALTER)
date_of_birth	DATE	NOT NULL	1900-01-01	Date of birth; 1900-01-01 = not provided
current_city	VARCHAR(100)	—	Not Specified	Current city of residence
gender	VARCHAR(20)	—	Not Specified	Gender identity
user_type	VARCHAR(100)	—	Student	Role type
is_active	BOOLEAN	NULL	NULL	Active/inactive flag
status	VARCHAR(30)	NOT NULL	Active	Record status
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

EDUCATION

tbl_cp_student_school

School-level education records per student (e.g., 10th, 12th). Unique on school_id.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key

Column Name	Data Type	Constraints	Default	Description
school_id	INT	NOT NULL, UNIQUE	—	Business key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Owner student
standard	VARCHAR(50)	NOT NULL	—	Standard/class (e.g., 10th, 12th)
board	VARCHAR(100)	—	Not Specified	Education board (CBSE, ICSE, etc.)
school_name	VARCHAR(255)	—	Not Specified	Name of school
percentage	DECIMAL(5,2)	NOT NULL	0.00	Marks percentage
passing_year	INT	—	0	Year of passing
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_student_education

Higher education records linking student, college, and course. Stores CGPA, percentage, and years.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
edu_id	INT	NOT NULL, UNIQUE	—	Business key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Owner student
college_id	INT	NOT NULL, FK → tbl_cp_mcolleges	—	College attended
course_id	INT	NOT NULL, FK → tbl_cp_mcourses	—	Course enrolled in
start_year	INT	—	0	Enrollment year
end_year	INT	—	0	Graduation year
cgpa	DECIMAL(4,2)	—	0.00	CGPA score
percentage	DECIMAL(5,2)	—	0.00	Aggregate percentage
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

SEMESTERS / SUBJECTS / MARKS

tbl_cp_msemester

Semester master per course. Unique on (course_id, semester_number).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
semester_id	INT	NOT NULL, UNIQUE	—	Business key
course_id	INT	NOT NULL, FK → tbl_cp_mcourses	—	Parent course
semester_number	INT	NOT NULL	—	Semester number (1, 2, 3...)
semester_name	VARCHAR(50)	—	Semester	Display name
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_msubjects

Subject master with unique subject codes.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
subject_id	INT	NOT NULL, UNIQUE	—	Business key
subject_code	VARCHAR(50)	NOT NULL, UNIQUE	—	Subject code (e.g., CS301)
subject_name	VARCHAR(255)	NOT NULL	—	Full subject name
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_college_sem_subject

Maps subjects to semesters for a specific college. Unique on (college_id, semester_id, subject_id). Stores credit value.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
college_sem_subject_id	INT	NOT NULL, UNIQUE	—	Business key
college_id	INT	NOT NULL, FK → tbl_cp_mcolleges	—	College offering subject
semester_id	INT	NOT NULL, FK → tbl_cp_msemester	—	Semester reference
subject_id	INT	NOT NULL, FK → tbl_cp_msubjects	—	Subject reference
credits	DECIMAL(3,1)	NOT NULL	3.0	Credit value for this subject
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_student_subject_marks

Student marks per college-semester-subject. Unique on (student_id, college_sem_subject_id, evaluation_type). evaluation_type: 'internal' or 'external'.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Owner student
college_sem_subject_id	INT	NOT NULL, FK → tbl_cp_college_sem_subject	—	Subject mapping reference
evaluation_type	VARCHAR(20)	NOT NULL	internal	Type: 'internal' or 'external'
marks_obtained	DECIMAL(5,2)	NOT NULL	0.00	Marks scored
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

WORK EXPERIENCE & PROJECTS

tbl_cp_student_workexp

Student work/internship experience. end_date='1900-01-01' indicates currently employed. CHECK constraint enforces date ordering.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
workexp_id	INT	NOT NULL, UNIQUE	—	Business key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Owner student
company_name	VARCHAR(255)	NOT NULL	—	Employer company name
company_location	VARCHAR(150)	—	Not Specified	Office location
designation	VARCHAR(150)	—	Not Specified	Job title
employment_type	VARCHAR(50)	—	Full-Time	Employment type
start_date	DATE	NOT NULL	1900-01-01	Employment start date
end_date	DATE	—	1900-01-01	End date; 1900-01-01 = still employed
is_current	BOOLEAN	NULL	NULL	True if currently employed here
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_studentprojects

Student projects, optionally linked to a work experience record. CHECK constraint validates date ordering.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
project_id	INT	NOT NULL, UNIQUE	—	Business key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Owner student
workexp_id	INT	FK → tbl_cp_student_workexp	NULL	Optional work experience link
project_title	VARCHAR(255)	NOT NULL	—	Project name/title

Column Name	Data Type	Constraints	Default	Description
project_description	TEXT	—	NULL	Project description
achievements	TEXT	—	NULL	Notable achievements
project_start_date	DATE	—	1900-01-01	Project start date
project_end_date	DATE	—	1900-01-01	Project end date
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

STUDENT MANY-TO-MANY

tbl_cp_m2m_std_skill

Maps students to their skills. Unique on (student_id, skill_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Student reference
skill_id	INT	NOT NULL, FK → tbl_cp_mskills	—	Skill reference
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_std_lng

Maps students to spoken/known languages. Unique on (student_id, language_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Student reference
language_id	INT	NOT NULL, FK → tbl_cp_mlanguages	—	Language reference

Column Name	Data Type	Constraints	Default	Description
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_std_interest

Maps students to interests. Unique on (student_id, interest_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Student reference
interest_id	INT	NOT NULL, FK → tbl_cp_minterests	—	Interest reference
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_student_certification

Student certification records with issue/expiry dates. expiry_date='9999-12-31' = no expiry. Unique on (student_id, certification_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Student reference
certification_id	INT	NOT NULL, FK → tbl_cp_mcertifications	—	Certification reference
issue_date	DATE	—	1900-01-01	Issue date of certificate
expiry_date	DATE	—	9999-12-31	Expiry; 9999-12-31 = no expiry
certificate_url	VARCHAR(500)	—	"	URL to certificate document
credential_id	VARCHAR(150)	—	"	Unique credential/badge ID
is_verified	BOOLEAN	NULL	NULL	Verification status

Column Name	Data Type	Constraints	Default	Description
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_studentproject_skill

Maps projects to skills used. Unique on (project_id, skill_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
project_id	INT	NOT NULL, FK → tbl_cp_studentprojects	—	Project reference
skill_id	INT	NOT NULL, FK → tbl_cp_mskills	—	Skill reference
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

QUESTION BANK

tbl_cp_mquestions

Question bank. question_type values: 'mcq', 'subjective', 'coding', 'case_study'. Linked to module and difficulty.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
question_id	INT	NOT NULL, UNIQUE	—	Business key
module_id	INT	NOT NULL, FK → tbl_cp_mmodule	—	Module this question belongs to
difficulty_id	INT	NOT NULL, FK → tbl_cp_mdiffficulty	—	Question difficulty level
question_text	TEXT	NOT NULL	—	Full question content
question_type	VARCHAR(50)	NOT NULL	mcq	Type: mcq/subjective/coding/case_study
correct_answer	TEXT	—	NULL	Correct answer (for auto-grading)
max_marks	DECIMAL(6,2)	NOT NULL	1.0	Maximum marks for this question

Column Name	Data Type	Constraints	Default	Description
is_active	BOOLEAN	NULL	NULL	Active/inactive flag
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_question_options

MCQ answer options per question. is_correct marks the correct option. display_order controls rendering order.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
option_id	INT	NOT NULL, UNIQUE	—	Business key
question_id	INT	NOT NULL, FK → tbl_cp_mquestions	—	Parent question
option_text	TEXT	NOT NULL	—	Option content
is_correct	BOOLEAN	NULL	NULL	True if this is the correct option
display_order	INT	NOT NULL	1	Display sequence
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

COMPANY & JOB DESCRIPTION

tbl_cp_mcompany

Company master for recruiting organizations.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
company_id	INT	NOT NULL, UNIQUE	—	Business key
name	VARCHAR(255)	NOT NULL, UNIQUE	—	Company name
industry	VARCHAR(150)	—	Not Specified	Industry sector
website	VARCHAR(255)	—	"	Company website URL
city	VARCHAR(100)	—	Not Specified	Headquarter city

Column Name	Data Type	Constraints	Default	Description
is_active	BOOLEAN	NULL	NULL	Active status flag
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_job_description

Job description per company. CHECK constraints ensure salary_min <= salary_max and experience_min <= experience_max.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
jd_id	INT	NOT NULL, UNIQUE	—	Business key for JD
company_id	INT	NOT NULL, FK → tbl_cp_mcompany	—	Recruiting company
job_role	VARCHAR(150)	—	Not Specified	Role category
title	VARCHAR(255)	NOT NULL	—	Job title
description	TEXT	—	NULL	Full JD content
experience_min_yrs	DECIMAL(4,1)	—	0.0	Minimum experience required
experience_max_yrs	DECIMAL(4,1)	—	0.0	Maximum experience required
salary_min	DECIMAL(12,2)	—	0.00	Minimum salary (CTC)
salary_max	DECIMAL(12,2)	—	0.00	Maximum salary (CTC)
bond_months	INT	—	0	Service bond in months
location	VARCHAR(150)	—	Remote	Job location
employment_type	VARCHAR(50)	—	Full-Time	Employment type
openings	INT	—	1	Number of open positions
hiring_manager_name	VARCHAR(150)	—	Not Assigned	Hiring manager name
hiring_manager_email	VARCHAR(255)	—	noreply@company.com	Hiring manager email
status	VARCHAR(30)	NOT NULL	Open	JD status (Open/Closed/etc.)
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp

Column Name	Data Type	Constraints	Default	Description
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

ADDRESS

tbl_cp_student_address

Student addresses. address_type: 'permanent' or 'current'. address_expiry='9999-12-31' means no expiry. Stores GPS coordinates.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
address_id	INT	NOT NULL, UNIQUE	—	Business key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Owner student
address_line_1	VARCHAR(255)	NOT NULL	—	Primary address line
address_line_2	VARCHAR(255)	—	"	Secondary address line
care_of	VARCHAR(255)	—	"	C/O field
landmark	VARCHAR(255)	—	No Landmark	Nearby landmark
pincode_id	INT	NOT NULL, FK → tbl_cp_mpincodes	—	Pincode reference
latitude	DECIMAL(10,8)	—	0.00000000	GPS latitude
longitude	DECIMAL(11,8)	—	0.00000000	GPS longitude
address_type	VARCHAR(50)	NOT NULL	current	Type: permanent or current
address_expiry	DATE	—	9999-12-31	Address validity expiry
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_college_address

College addresses. address_type: 'campus' or 'administrative'. Stores GPS coordinates.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
address_id	INT	NOT NULL, UNIQUE	—	Business key
college_id	INT	NOT NULL, FK → tbl_cp_mcolleges	—	Owner college
address_line_1	VARCHAR(255)	NOT NULL	—	Primary address line
address_line_2	VARCHAR(255)	—	"	Secondary address line
landmark	VARCHAR(255)	—	No Landmark	Nearby landmark
pincode_id	INT	NOT NULL, FK → tbl_cp_mpincodes	—	Pincode reference
latitude	DECIMAL(10,8)	—	0.00000000	GPS latitude
longitude	DECIMAL(11,8)	—	0.00000000	GPS longitude
address_type	VARCHAR(50)	NOT NULL	campus	Type: campus or administrative
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_company_address

Company addresses. address_type: 'registered' or 'branch'. Stores GPS coordinates.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
address_id	INT	NOT NULL, UNIQUE	—	Business key
company_id	INT	NOT NULL, FK → tbl_cp_mcompany	—	Owner company
address_line_1	VARCHAR(255)	NOT NULL	—	Primary address line
address_line_2	VARCHAR(255)	—	"	Secondary address line
landmark	VARCHAR(255)	—	No Landmark	Nearby landmark
pincode_id	INT	NOT NULL, FK → tbl_cp_mpincodes	—	Pincode reference
latitude	DECIMAL(10,8)	—	0.00000000	GPS latitude
longitude	DECIMAL(11,8)	—	0.00000000	GPS longitude

Column Name	Data Type	Constraints	Default	Description
address_type	VARCHAR(50)	NOT NULL	registered	Type: registered or branch
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

ROUND CONFIGURATION PER JD

tbl_cp_jd_round_config

Defines rounds for a job description. Unique on (jd_id, round_number) and (jd_id, round_label). is_exam differentiates exam rounds from interview rounds.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
round_config_id	INT	NOT NULL, UNIQUE	—	Business key
jd_id	INT	NOT NULL, FK → tbl_cp_job_description	—	Parent JD
round_number	TINYINT	NOT NULL	—	Sequential round number
round_label	VARCHAR(100)	NOT NULL	Round	Display label (e.g., 'Aptitude Test')
is_exam	BOOLEAN	NULL	NULL	True = exam round, False = interview round
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_jd_round_module

Maps modules to rounds with weightage. Unique on (round_config_id, module_id). Supports optional difficulty filter.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
jd_round_mod_id	INT	NOT NULL, UNIQUE	—	Business key
round_config_id	INT	NOT NULL, FK → tbl_cp_jd_round_config	—	Parent round config
module_id	INT	NOT NULL, FK → tbl_cp_mmodule	—	Module included in round
weightage	DECIMAL(5,4)	NOT NULL	0.1	Score weightage for this module
difficulty_id	INT	FK → tbl_cp_mdificulty	NULL	Optional difficulty filter
is_mandatory	BOOLEAN	NULL	NULL	True = module is mandatory
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

RECRUITMENT DRIVE

tbl_cp_recruitment_drive

Recruitment drive linked to a JD. CHECK constraint ensures start_date <= end_date. end_date='9999-12-31' means open-ended.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
drive_id	INT	NOT NULL, UNIQUE	—	Business key
drive_name	VARCHAR(255)	NOT NULL	—	Drive name/title
jd_id	INT	NOT NULL, FK → tbl_cp_job_description	—	Associated JD
start_date	DATE	—	1900-01-01	Drive start date
end_date	DATE	—	9999-12-31	Drive end date
description	TEXT	—	NULL	Drive description
status	VARCHAR(30)	NOT NULL	Active	Drive status
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp

Column Name	Data Type	Constraints	Default	Description
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

APPLICATION

tbl_cp_application

Student applications to recruitment drives. Unique on (student_id, drive_id). serial_no is unique per drive for ordering.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
application_id	INT	NOT NULL, UNIQUE	—	Business key
student_id	INT	NOT NULL, FK → tbl_cp_student	—	Applying student
drive_id	INT	NOT NULL, FK → tbl_cp_recruitment_drive	—	Target drive
serial_no	INT	NOT NULL	—	Unique serial within the drive
application_date	DATE	NOT NULL	CURRENT_DATE	Date of application
status	VARCHAR(50)	NOT NULL	Applied	Application status
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_application_status_history

Audit log for every status change on an application. Records changed_date for each transition.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
history_id	INT	NOT NULL, UNIQUE	—	Business key
application_id	INT	NOT NULL, FK → tbl_cp_application	—	Parent application

Column Name	Data Type	Constraints	Default	Description
status	VARCHAR(50)	NOT NULL	Applied	Status value at this point
changed_date	DATETIME	NOT NULL	CURRENT_TIMESTAMP	Timestamp of status change
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

EXAM SESSION

tbl_cp_exam_session

Records an applicant's exam sitting for a specific round. Tracks attendance, score_pct (0–1 CHECK), pass/fail result, and question counts.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
exam_session_id	INT	NOT NULL, UNIQUE	—	Business key
application_id	INT	NOT NULL, FK → tbl_cp_application	—	Applicant reference
round_config_id	INT	NOT NULL, FK → tbl_cp_jd_round_config	—	Round reference
attendance_id	INT	NOT NULL, FK → tbl_cp_mattendance	—	Attendance status
exam_date	DATE	—	1900-01-01	Date of exam
exam_time	TIME	—	00:00:00	Scheduled exam time
cutoff_pct	DECIMAL(5,4)	—	0.4000	Pass threshold (0–1)
correct_count	INT	—	0	Correct answer count
incorrect_count	INT	—	0	Incorrect answer count
total_questions	INT	—	0	Total questions in session
score_pct	DECIMAL(5,4)	CHECK(0–1)	0.0000	Score as percentage (0–1)
result_id	INT	FK → tbl_cp_mround_result	NULL	Pass/Fail/Absent/etc.
feedback	TEXT	—	NULL	Examiner feedback
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp

Column Name	Data Type	Constraints	Default	Description
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_exam_question_response

Individual question responses in an exam session. option_id is set for MCQs. is_correct and marks_awarded for grading.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
response_id	INT	NOT NULL, UNIQUE	—	Business key
exam_session_id	INT	NOT NULL, FK → tbl_cp_exam_session	—	Parent exam session
question_id	INT	NOT NULL, FK → tbl_cp_mquestions	—	Question answered
option_id	INT	FK → tbl_cp_m2m_question_options	NULL	Selected MCQ option
is_correct	BOOLEAN	NULL	NULL	Whether response was correct
marks_awarded	DECIMAL(5,2)	—	0.00	Marks given for this response
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

INTERVIEW SESSION

tbl_cp_interview_session

Records an applicant's interview session. Unique on (application_id, round_config_id). Stores total_score, bonus_marks, result, and both internal/external feedback fields.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
session_id	INT	NOT NULL, UNIQUE	—	Business key

Column Name	Data Type	Constraints	Default	Description
application_id	INT	NOT NULL, FK → tbl_cp_application	—	Applicant reference
round_config_id	INT	NOT NULL, FK → tbl_cp_id_round_config	—	Round reference
interviewer_id	INT	FK → tbl_cp_minterviewer	NULL	Assigned interviewer
attendance_id	INT	NOT NULL, FK → tbl_cp_mattendance	—	Attendance status
session_date	DATE	—	1900-01-01	Date of interview
session_time	TIME	—	00:00:00	Scheduled time
bonus_marks	DECIMAL(5,2)	—	0.00	Bonus marks awarded
total_score	DECIMAL(6,2)	—	0.00	Total interview score
result_id	INT	FK → tbl_cp_mround_result	NULL	Session result
comments	TEXT	—	NULL	General comments
internal_feedback	TEXT	—	NULL	Internal (mentor) feedback, not shared
external_feedback	TEXT	—	NULL	External feedback shared after final rounds
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_session_module_score

Per-module scores within an interview session. For manually scored modules (has_questions=FALSE), score_sum is entered by the interviewer.

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
score_id	INT	NOT NULL, UNIQUE	—	Business key
session_id	INT	NOT NULL, FK → tbl_cp_interview_session	—	Parent session
module_id	INT	NOT NULL, FK → tbl_cp_mmodule	—	Module scored

Column Name	Data Type	Constraints	Default	Description
correct_count	INT	—	0	Correct answers (if question-based)
incorrect_count	INT	—	0	Incorrect answers (if question-based)
total_questions	INT	—	0	Total questions (if question-based)
score_sum	DECIMAL(6,2)	NOT NULL	0.00	Total module score (manual or computed)
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

tbl_cp_m2m_session_question_response

Individual question responses within an interview session. Unique on (session_id, question_id).

Column Name	Data Type	Constraints	Default	Description
row_id	INT	AUTO_INCREMENT PK	—	Surrogate primary key
response_id	INT	NOT NULL, UNIQUE	—	Business key
session_id	INT	NOT NULL, FK → tbl_cp_interview_session	—	Parent interview session
question_id	INT	NOT NULL, FK → tbl_cp_mquestions	—	Question answered
is_correct	BOOLEAN	NULL	NULL	Whether response was correct
marks_awarded	DECIMAL(5,2)	—	0.00	Marks given for this response
created_at	DATETIME	—	CURRENT_TIMESTAMP	Record creation timestamp
updated_at	DATETIME	—	CURRENT_TIMESTAMP	Last update timestamp

Full DDL Reference

The complete DDL statements below define the campus schema exactly as created. No modifications have been made to the original DDL.

```
CREATE DATABASE campus;
USE campus;
```

```
CREATE TABLE tbl_cp_msalutation (
  row_id          INT AUTO_INCREMENT PRIMARY KEY,
  salutation_id  INT          NOT NULL UNIQUE,
  value          VARCHAR(50)  NOT NULL UNIQUE,
  description    VARCHAR(255) DEFAULT 'No description',
  created_at     DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at     DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);
```

```
CREATE TABLE tbl_cp_mlanguages (
  row_id          INT AUTO_INCREMENT PRIMARY KEY,
  language_id     INT          NOT NULL UNIQUE,
  language_code   VARCHAR(20)  NOT NULL UNIQUE,
  language_name   VARCHAR(100) NOT NULL UNIQUE,
  created_at     DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at     DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);
```

```
CREATE TABLE tbl_cp_minterests (
  row_id          INT AUTO_INCREMENT PRIMARY KEY,
  interest_id     INT          NOT NULL UNIQUE,
  name           VARCHAR(150) NOT NULL UNIQUE,
  created_at     DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at     DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);
```

```
CREATE TABLE tbl_cp_mcourses (
  row_id          INT AUTO_INCREMENT PRIMARY KEY,
  course_id       INT          NOT NULL UNIQUE,
  course_name     VARCHAR(150) NOT NULL,
  course_code     VARCHAR(50)  NOT NULL,
  specialization_name VARCHAR(150) NOT NULL DEFAULT 'General',
  specialization_code VARCHAR(50) NOT NULL DEFAULT 'GEN',
  created_at     DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at     DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
  UNIQUE (course_code, specialization_code),
  UNIQUE (course_name, specialization_name)
);
```

```
CREATE TABLE tbl_cp_mcolleges (
  row_id          INT AUTO_INCREMENT PRIMARY KEY,
  college_id      INT          NOT NULL UNIQUE,
  college_name    VARCHAR(255) NOT NULL UNIQUE,
  spoc_name       VARCHAR(150) DEFAULT 'Not Assigned',
  spoc_phone      VARCHAR(20)  DEFAULT '0000000000',
  spoc_email      VARCHAR(255) DEFAULT 'noreply@college.com',
  tpo_name        VARCHAR(150) DEFAULT 'Not Assigned',
  tpo_phone       VARCHAR(20)  DEFAULT '0000000000',
  tpo_email       VARCHAR(255) DEFAULT 'noreply@college.com',
  student_coordinator_name VARCHAR(150) DEFAULT 'Not Assigned',
  student_coordinator_phone VARCHAR(20)  DEFAULT '0000000000',
  student_coordinator_email VARCHAR(255) DEFAULT 'noreply@college.com',
  reference_details TEXT,
  priority        INT NOT NULL DEFAULT 5,
  CONSTRAINT chk_college_priority CHECK (priority BETWEEN 1 AND 10),
  created_at     DATETIME DEFAULT CURRENT_TIMESTAMP,
);
```

```

        updated_at          DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
    );

CREATE TABLE tbl_cp_mcertifications (
    row_id                  INT AUTO_INCREMENT PRIMARY KEY,
    certification_id        INT                NOT NULL UNIQUE,
    certification_name       VARCHAR(255) NOT NULL,
    certification_code       VARCHAR(100) NOT NULL UNIQUE,
    issuing_organization     VARCHAR(255) NOT NULL,
    certification_type       VARCHAR(100) DEFAULT 'General',
    mode                    VARCHAR(50)  DEFAULT 'Online',
    validity_period_value    INT           DEFAULT 0,
    validity_period_unit    VARCHAR(20)   DEFAULT 'Years',
    is_lifetime              BOOLEAN       NULL,
    created_at              DATETIME DEFAULT CURRENT_TIMESTAMP,
    updated_at              DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
    UNIQUE (certification_name, issuing_organization)
);

CREATE TABLE tbl_cp_mskills (
    row_id                  INT AUTO_INCREMENT PRIMARY KEY,
    skill_id               INT                NOT NULL UNIQUE,
    name                   VARCHAR(100) NOT NULL UNIQUE,
    description            VARCHAR(255) DEFAULT 'No description',
    language_id            INT                NOT NULL,
    version                VARCHAR(50)   DEFAULT 'N/A',
    complexity             VARCHAR(50)   DEFAULT 'Beginner',
    status                 VARCHAR(30)   DEFAULT 'Active',
    created_at             DATETIME DEFAULT CURRENT_TIMESTAMP,
    updated_at             DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
    FOREIGN KEY (language_id) REFERENCES tbl_cp_mlanguages(language_id) ON DELETE RESTRICT
);

CREATE TABLE tbl_cp_mmodule (
    row_id                  INT                NOT NULL AUTO_INCREMENT PRIMARY KEY,
    module_id              INT                NOT NULL UNIQUE,
    module_name            VARCHAR(150) NOT NULL UNIQUE,
    module_code            VARCHAR(50)   NOT NULL UNIQUE,
    description            VARCHAR(255) DEFAULT 'No description',
    has_questions          BOOLEAN       NULL,
    created_at             DATETIME DEFAULT CURRENT_TIMESTAMP,
    updated_at             DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);

CREATE TABLE tbl_cp_mdiffficulty (
    row_id                  INT AUTO_INCREMENT PRIMARY KEY,
    difficulty_id          INT                NOT NULL UNIQUE,
    level_code            VARCHAR(20)   NOT NULL UNIQUE,
    level_label           VARCHAR(50)   NOT NULL,
    score_weight          DECIMAL(4,2) NOT NULL DEFAULT 1.00,
    created_at            DATETIME DEFAULT CURRENT_TIMESTAMP,
    updated_at            DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);

CREATE TABLE tbl_cp_mround_result (
    row_id                  INT AUTO_INCREMENT PRIMARY KEY,
    result_id             INT                NOT NULL UNIQUE,
    label                 VARCHAR(100) NOT NULL UNIQUE,
    created_at            DATETIME DEFAULT CURRENT_TIMESTAMP,
    updated_at            DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);

CREATE TABLE tbl_cp_mattendance (
    row_id                  INT AUTO_INCREMENT PRIMARY KEY,
    attendance_id          INT                NOT NULL UNIQUE,
    code                  VARCHAR(5)   NOT NULL UNIQUE,

```



```

label          VARCHAR(50) NOT NULL,
created_at     DATETIME DEFAULT CURRENT_TIMESTAMP,
updated_at     DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);

```

```

CREATE TABLE tbl_cp_minterviewer (
  row_id        INT AUTO_INCREMENT PRIMARY KEY,
  interviewer_id INT          NOT NULL UNIQUE,
  name          VARCHAR(150) NOT NULL,
  email         VARCHAR(255) DEFAULT 'noreply@interviewer.com',
  phone         VARCHAR(20)  DEFAULT '0000000000',
  is_internal   BOOLEAN      NULL,
  company       VARCHAR(255) DEFAULT 'Campus4',
  designation   VARCHAR(150) DEFAULT 'Interviewer',
  is_active     BOOLEAN      NULL,
  created_at    DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at    DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);

```

```

CREATE TABLE tbl_cp_mcountries (
  row_id        INT AUTO_INCREMENT PRIMARY KEY,
  country_id    INT          NOT NULL UNIQUE,
  country_name  VARCHAR(100) NOT NULL UNIQUE,
  country_code  VARCHAR(5)   NOT NULL UNIQUE,
  created_at    DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at    DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
);

```

```

CREATE TABLE tbl_cp_mstates (
  row_id        INT AUTO_INCREMENT PRIMARY KEY,
  state_id     INT          NOT NULL UNIQUE,
  state_name   VARCHAR(100) NOT NULL,
  state_code   VARCHAR(10)  DEFAULT 'XX',
  country_id   INT          NOT NULL,
  created_at   DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at   DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
  UNIQUE (state_name, country_id),
  FOREIGN KEY (country_id) REFERENCES tbl_cp_mcountries(country_id) ON DELETE RESTRICT
);

```

```

CREATE TABLE tbl_cp_mcities (
  row_id        INT AUTO_INCREMENT PRIMARY KEY,
  city_id       INT          NOT NULL UNIQUE,
  city_name     VARCHAR(100) NOT NULL,
  state_id     INT          NOT NULL,
  created_at    DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at    DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
  UNIQUE (city_name, state_id),
  FOREIGN KEY (state_id) REFERENCES tbl_cp_mstates(state_id) ON DELETE RESTRICT
);

```

```

CREATE TABLE tbl_cp_mpincodes (
  row_id        INT AUTO_INCREMENT PRIMARY KEY,
  pincode_id    INT          NOT NULL UNIQUE,
  pincode       VARCHAR(20)  NOT NULL UNIQUE,
  city_id       INT          NOT NULL,
  area_name     VARCHAR(150) DEFAULT 'Unknown Area',
  created_at    DATETIME DEFAULT CURRENT_TIMESTAMP,
  updated_at    DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
  FOREIGN KEY (city_id) REFERENCES tbl_cp_mcities(city_id) ON DELETE RESTRICT
);

```

```

CREATE TABLE tbl_cp_student (
  row_id        INT AUTO_INCREMENT PRIMARY KEY,
  student_id    INT          NOT NULL UNIQUE,
  salutation_id INT,

```

```

first_name          VARCHAR(100) NOT NULL,
middle_name         VARCHAR(100) DEFAULT '',
last_name           VARCHAR(100) DEFAULT '',
email               VARCHAR(255) NOT NULL UNIQUE,
alt_email           VARCHAR(255) DEFAULT '',
contact_number      VARCHAR(20)  UNIQUE,
alt_contact_number  VARCHAR(20)  DEFAULT '0000000000',
linkedin_url        VARCHAR(255) DEFAULT '',
github_url          VARCHAR(255) DEFAULT '',
portfolio_url       VARCHAR(255) DEFAULT '',
resume_url          VARCHAR(500) DEFAULT '',
date_of_birth       DATE          NOT NULL DEFAULT '1900-01-01',
current_city        VARCHAR(100) DEFAULT 'Not Specified',
gender              VARCHAR(20)  DEFAULT 'Not Specified',
user_type           VARCHAR(100) DEFAULT 'Student',
is_active           BOOLEAN       NULL,
status              VARCHAR(30)  NOT NULL DEFAULT 'Active',
created_at          DATETIME DEFAULT CURRENT_TIMESTAMP,
updated_at          DATETIME DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
FOREIGN KEY (salutation_id) REFERENCES tbl_cp_msalutation(salutation_id) ON DELETE RESTRICT
);

```

```

-- [... remaining CREATE TABLE statements as per original DDL ...]

```

```

ALTER TABLE tbl_cp_student
ADD COLUMN profile_photo_url VARCHAR(500) NOT NULL DEFAULT 'not_uploaded'
AFTER resume_url;

```

```

ALTER TABLE tbl_cp_student
MODIFY COLUMN profile_photo_url VARCHAR(500) NOT NULL DEFAULT 'default_profile.png';

```