

```
fs@DESKTOP-P44M87A MINGW64 /c/5V
$ pwd
/c/5V

fs@DESKTOP-P44M87A MINGW64 /c/5V
$ git --version
git version 2.52.0.windows.1

fs@DESKTOP-P44M87A MINGW64 /c/5V
$ git init
Initialized empty Git repository in C:/5V/.git/

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ nano file1.txt

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ ls
file1.txt

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ cat fill.txt
cat: fill.txt: No such file or directory

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ cat file1.txt
hello from SE lab

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        file1.txt

nothing added to commit but untracked files present (use "git add" to track)

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ git add file1.txt
warning: in the working copy of 'file1.txt', LF will be replaced by CRLF the next time Git touches it

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ git status
On branch master

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
        new file:   file1.txt

fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ git global --config --list
git: 'global' is not a git command. See 'git --help'.
```

```

fs@DESKTOP-P44M87A MINGW64 /c/SV (master)
$ git global --config --list
git: 'global' is not a git command. See 'git --help'.

fs@DESKTOP-P44M87A MINGW64 /c/SV (master)
$ git config --global --list
fatal: unable to read config file 'C:/Users/fs/.gitconfig': No such file or directory

fs@DESKTOP-P44M87A MINGW64 /c/SV (master)
$ git config --global --user.name=Umgang
error: unknown option `user.name=Umgang'
usage: git config list [<file-option>] [<display-option>] [--includes]
      or: git config get [<file-option>] [<display-option>] [--includes] [--all] [--regexp] [--value=<pattern>] [--fixed-value] [--default-
1] <name>
      or: git config set [<file-option>] [--type=<type>] [--all] [--value=<pattern>] [--fixed-value] <name> <value>
      or: git config unset [<file-option>] [--all] [--value=<pattern>] [--fixed-value] <name>
      or: git config rename-section [<file-option>] <old-name> <new-name>
      or: git config remove-section [<file-option>] <name>
      or: git config edit [<file-option>]
      or: git config [<file-option>] --get-colorbool <name> [<stdout-is-tty>]

Config file location
--[no-]global      use global config file
--[no-]system      use system config file
--[no-]local       use repository config file
--[no-]worktree    use per-worktree config file
-f, --[no-]file <file>
                  use given config file
--[no-]blob <blob-id> read config from given blob object

Action
--get              get value: name [<value-pattern>]
--get-all         get all values: key [<value-pattern>]
--get-regexp       get values for regexp: name-regex [<value-pattern>]
--get-urlmatch     get value specific for the URL: section[.var] URL
--replace-all     replace all matching variables: name value [<value-pattern>]
--add             add a new variable: name value
--unset           remove a variable: name [<value-pattern>]
--unset-all       remove all matches: name [<value-pattern>]
--rename-section   rename section: old-name new-name
--remove-section   remove a section: name
-l, --list         list all
-e, --edit         open an editor
--get-color        find the color configured: slot [<default>]
--get-colorbool    find the color setting: slot [<stdout-is-tty>]

Display options
-z, --[no-]null    terminate values with NUL byte
--[no-]name-only    show variable names only
--[no-]show-origin  show origin of config (file, standard input, blob, command line)
--[no-]show-scope   show scope of config (worktree, local, global, system, command)
--[no-]show-names   show config keys in addition to their values

Type
-t, --[no-]type <type>
                  value is given this type
--bool            value is "true" or "false"
--int             value is decimal number

```

Type

-t, --[no-]type <type>	value is given this type
--bool	value is "true" or "false"
--int	value is decimal number
--bool-or-int	value is --bool or --int
--bool-or-str	value is --bool or string
--path	value is a path (file or directory name)
--expiry-date	value is an expiry date

Other

--[no-]default <value>	with --get, use default value when missing entry
--[no-]comment <value>	human-readable comment string (# will be prepended as needed)
--[no-]fixed-value	use string equality when comparing values to value pattern
--[no-]includes	respect include directives on lookup

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git config --global user.name "Umang"
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git config --global user.email "umangumang708@gmail.com"
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git config --global --list
```

```
user.name=Umang
```

```
user.email=umangumang708@gmail.com
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git lock
```

```
git: 'lock' is not a git command. See 'git --help'.
```

The most similar commands are

```
fsck
hook
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git commit
```

```
Aborting commit due to empty commit message.
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git commit -m "Hello"
```

```
[master (root-commit) 7320e7c] Hello
```

```
1 file changed, 2 insertions(+)
```

```
create mode 100644 file1.txt
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git remote add origin https://github.com/DiamondDevil-dotcom/SE-Lab-.git
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
```

```
$ git branch -M main
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
```

```
$ git push -u origin main
```

```
info: please complete authentication in your browser...
```

```
Enumerating objects: 3, done.
```

```
Counting objects: 100% (3/3), done.
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (master)
$ git branch -M main

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ git push -u origin main
info: please complete authentication in your browser...
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 228 bytes | 76.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/DiamondDevil-dotcom/SE-Lab-.git
 * [new branch]      main -> main
branch 'main' set up to track 'origin/main'.

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ cat file1.txt
hello from SE lab

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ touch file2.txt

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ git add file2.txt

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   file2.txt

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ git commit -m "Hello world"
[main af18843] Hello world
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 file2.txt

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ git push file2.txt
fatal: invalid gitfile format: file2.txt
fatal: Could not read from remote repository.

Please make sure you have the correct access rights
and the repository exists.

fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
$ git pull
remote: Enumerating objects: 5, done.
remote: Counting objects: 100% (5/5), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (3/3), 910 bytes | 37.00 KiB/s, done.
From https://github.com/DiamondDevil-dotcom/SE-Lab-
 7320e7c..ed48b04  main      -> origin/main
Merge made by the 'ort' strategy.
 file1.txt | 1 +
```

```
fatal: Could not read from remote repository.
```

```
Please make sure you have the correct access rights  
and the repository exists.
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
```

```
$ git pull
```

```
remote: Enumerating objects: 5, done.
```

```
remote: Counting objects: 100% (5/5), done.
```

```
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
```

```
Unpacking objects: 100% (3/3), 910 bytes | 37.00 KiB/s, done.
```

```
From https://github.com/DiamondDevil-dotcom/SE-Lab-
```

```
7320e7c..ed48b04 main -> origin/main
```

```
Merge made by the 'ort' strategy.
```

```
file1.txt | 1 +
```

```
1 file changed, 1 insertion(+)
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
```

```
$ cat file1.txt
```

```
hello from SE lab
```

```
niiiiiiiiiiiiiiiiiii
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
```

```
$ git push
```

```
Enumerating objects: 7, done.
```

```
Counting objects: 100% (7/7), done.
```

```
Delta compression using up to 4 threads
```

```
Compressing objects: 100% (4/4), done.
```

```
Writing objects: 100% (5/5), 571 bytes | 285.00 KiB/s, done.
```

```
Total 5 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
```

```
To https://github.com/DiamondDevil-dotcom/SE-Lab-.git
```

```
ed48b04..9183e7f main -> main
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
```

```
$ git pull
```

```
remote: Enumerating objects: 5, done.
```

```
remote: Counting objects: 100% (5/5), done.
```

```
remote: Compressing objects: 100% (2/2), done.
```

```
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
```

```
Unpacking objects: 100% (3/3), 933 bytes | 44.00 KiB/s, done.
```

```
From https://github.com/DiamondDevil-dotcom/SE-Lab-
```

```
9183e7f..edcd612 main -> origin/main
```

```
Updating 9183e7f..edcd612
```

```
Fast-forward
```

```
file2.txt | 1 +
```

```
1 file changed, 1 insertion(+)
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
```

```
$ cat file2.txt
```

```
Hello from file 2
```

```
fs@DESKTOP-P44M87A MINGW64 /c/5V (main)
```

```
$ ~
```