

# The Bias-Variance Tradeoff: A Deep Dive

---

Nipun Batra and teaching staff

IIT Gandhinagar

August 15, 2025

# Table of Contents

1. Understanding the Problem Setup
2. Source 1: Noise - The Irreducible Error
3. Source 2: Bias - Systematic Model Limitations
4. Source 3: Variance - Dataset Sensitivity
5. Mathematical Derivation: The Bias-Variance Decomposition

# Understanding the Problem Setup

# The Learning Problem: A Real-World Example


## Definition: Our Scenario

**Goal:** Predict housing prices based on house area

## Example: The True Relationship

**Unknown to us:** There exists a true function  $f_{\theta_{\text{true}}}$  that perfectly relates area to price:

$$y_t = f_{\theta_{\text{true}}}(x_t)$$



# The Three Sources of Prediction Error

## Important: Fundamental Question

**Why do our predictions fail?** What causes the difference between our predictions and reality?

## Definition: Three Universal Sources of Error

**Every machine learning prediction suffers from:**

1. **Noise** - Irreducible randomness in the data
2. **Bias** - Systematic errors from model assumptions
3. **Variance** - Sensitivity to particular training sets

## Key Points

**The Tradeoff:** We can often reduce bias OR variance, but not both simultaneously!

# Source 1: Noise - The Irreducible Error

# Understanding Noise: The Fundamental Limitation

## Definition: What is Noise?

**Noise** represents factors affecting the target that we cannot observe or control

## Example: Real-World Noise Sources

### In housing prices:

- House condition (hard to measure precisely)
- Neighborhood market dynamics
- Buyer's personal preferences
- Economic conditions on sale day
- Unmeasurable aesthetic factors

## Important: Key Insight


# Noise: Mathematical Formulation

## Key Points

The Noisy Relationship **True relationship becomes:**


$$y_t = f_{\theta_{\text{true}}}(x_t) + \epsilon_t$$

where  $\epsilon_t \sim \mathcal{N}(0, \sigma^2)$  is the noise term





# Visualizing Noise: Data Distribution



## Key Points

### Key Observation:

- Data points scatter around the true function

The spread (variance) is constant:  $\sigma^2$

## **Source 2: Bias - Systematic Model Limitations**

# Understanding Bias: Model Flexibility


## Definition: What is Bias?

**Bias** measures how well our model class can represent the true function


## Example: Extreme Example: Constant Function

**Model choice:**  $\hat{f}(x) = c$  (constant, regardless of house size)

**Question:** Can this model capture the true price-size relationship?



# Bias: Fitting a Constant Model




## Key Points

### Best Constant Fit:

- The optimal constant is the average of all prices
- But this completely ignores the size information!

# Bias: Visualizing the Systematic Error



## Definition: Bias Definition



$$\text{Bias}(x) = f_{\theta_{\text{true}}}(x) - E[\hat{f}(x)]$$

**The systematic difference between truth and average prediction**

# Multiple Datasets: Understanding Variability

## Key Points

**Crucial Insight:** Many different datasets are possible from the same true relationship!




## Example:

Same underlying relationship, different data points due to:

- Random sampling of houses


# Fitting Models to Different Datasets



## Key Points

**Question:** If we fit the same model type (constant) to different datasets, what happens?

# Different Predictions from Different Datasets



## Important:

Key Observation: Even with the same model type, we get different predictions!


## Definition:

This variability leads us to two concepts:

- **Average prediction:** What happens "on average" across all



# Many Datasets: The Full Picture




## Key Points

**Multiple Datasets:** Each gives a slightly different constant fit

## Example:

The Big Question: What is the "typical" or "expected" prediction

# The Average Model: Expected Prediction



## Definition: Expected Prediction

$E[\hat{f}(x)] = \text{Average prediction across all possible training sets}$


## Key Points

# Bias: The Final Definition

## Definition: Bias Formula

$$\text{Bias}(x) = f_{\theta_{\text{true}}}(x) - E[\hat{f}(x)]$$

**Difference between truth and expected prediction**




# Model Complexity vs Bias: The Relationship

## Key Points

### Universal Pattern:

- **Increase complexity** → Model becomes more flexible
- **More flexible** → Can better approximate true function
- **Better approximation** → Bias decreases



# High-Complexity Models: Near-Zero Bias



## Important:

High-Degree Polynomials: Can approximate almost any smooth function!

## Definition:

## **Source 3: Variance - Dataset Sensitivity**

# From Bias to Variance: The Other Side

## Important:

We've seen: High-complexity models have low bias

**Question:** If low bias is good, why not always use high-complexity models?

## Definition: Enter Variance

**Variance** measures how much predictions change when we train on different datasets

## Key Points

### Intuition:


- Simple models: Stable, consistent predictions
- Complex models: Highly sensitive to specific training data

# Understanding Variance: Prediction Consistency

## Definition: Variance Definition

**Variance** = How much do predictions vary across different training sets?

$$\text{Var}(\hat{f}(x)) = E[(\hat{f}(x) - E[\hat{f}(x)])^2]$$






# Low Complexity: Low Variance


## Key Points

### Simple Models (e.g., linear):

- Few parameters to estimate
- Robust to data variations
- Consistent predictions



# High Complexity: The Variance Problem Emerges



## Important:

### Warning Signs:


- Models look very different across datasets

# High Complexity: Extreme Variance


## Key Points

### Complex Models (e.g., high-degree polynomials):

- Many parameters to estimate
- Overfit to specific training data
- Dramatically different predictions



# The Bias-Variance Tradeoff: The Central Tension



## Important: The Fundamental Tradeoff

- **Simple models:** High bias, low variance
- **Complex models:** Low bias, high variance
- **Optimal complexity:** Balance between the two

# Mathematical Derivation: The Bias-Variance Decomposition

# Why Mathematical Analysis Matters

## Definition: The Goal

**Question:** Can we mathematically prove that  $\text{error} = \text{bias}^2 + \text{variance} + \text{noise}$ ?

## Key Points

### Why This Matters

- **Theoretical foundation:** Understand the fundamental nature of learning
- **Model selection:** Know exactly what we're trading off
- **Algorithm design:** Create methods that explicitly balance bias and variance

## Example: Expected Error Across All Possible Datasets

# Setting Up the Mathematical Framework

## Definition: What We Want to Prove

$$E[\text{Error}] = \text{Noise} + \text{Bias}^2 + \text{Variance}$$

## Key Points

### Our Approach

1. Start with prediction error at a single point
2. Use squared loss:  $(y - \hat{f}(x))^2$
3. Take expectation over all sources of randomness
4. Apply algebraic manipulation to separate terms

## Example: Sources of Randomness

- **Training set:** Which data points we observe

# Mathematical Setup: Defining the Components

## Definition: True Relationship with Noise

$$y = f_{\text{true}}(x) + \epsilon \quad \text{where } \epsilon \sim \mathcal{N}(0, \sigma^2)$$

## Key Points

### Key Definitions

- $f_{\text{true}}(x)$ : The unknown true function
- $\hat{f}(x)$ : Our model's prediction (depends on training data)
- $E[\hat{f}(x)]$ : Expected prediction over all possible training sets
- $\epsilon$ : Irreducible noise with variance  $\sigma^2$





# Formal Definitions: Bias and Variance

## Definition: Bias


$$\text{Bias}(x) = f_{\text{true}}(x) - E[\hat{f}(x)]$$

**Systematic error:** Difference between truth and expected prediction

## Definition: Variance

$$\text{Variance}(x) = E[(\hat{f}(x) - E[\hat{f}(x)])^2]$$

**Prediction instability:** Expected squared deviation from mean prediction



# The Main Theorem: Bias-Variance Decomposition

## Important: The Fundamental Result

For any point  $x$  and any learning algorithm:

$$E[(y - \hat{f}(x))^2] = \sigma^2 + [\text{Bias}(x)]^2 + \text{Variance}(x)$$

## Definition: Component Interpretation

- $\sigma^2$ : **Irreducible error** (noise)
- $[\text{Bias}(x)]^2$ : **Systematic error** (underfitting)
- $\text{Variance}(x)$ : **Random error** (overfitting)

## Key Points

**Coming Up:** We'll prove this step-by-step using careful algebraic manipulation

# Starting the Proof: Expected Squared Error

## Definition: What We're Proving

$$E[(y - \hat{f}(x))^2] = \sigma^2 + [\text{Bias}(x)]^2 + \text{Variance}(x)$$

## Key Points

### Our Strategy

1. Start with squared error:  $(y - \hat{f}(x))^2$
2. Add and subtract strategic terms
3. Expand and use linearity of expectation
4. Show cross-terms cancel out
5. Identify the three components

## Example: Key Insight

## Step 1: Setting Up the Expectation

### Definition: Squared Loss at Point $x$

**Individual prediction error:**  $(y - \hat{f}(x))^2$

### Key Points

Taking Expectations **Expected error over all randomness:**

$$E_{\mathcal{D}, y}[(y - \hat{f}(x))^2]$$

where:

- $\mathcal{D}$ : Random training set
- $y$ : Random target (includes noise)

### Example: Why Two Sources of Randomness?

## Step 2: The Add-and-Subtract Trick

### Key Points

Starting Point

$$E[(y - \hat{f}(x))^2]$$

### Example: Strategic Addition and Subtraction

**Add and subtract**  $f_{\text{true}}(x)$ :

$$E[(y - f_{\text{true}}(x) + f_{\text{true}}(x) - \hat{f}(x))^2]$$

### Definition: Grouping Terms

$$E[\underbrace{(y - f_{\text{true}}(x))}_{\text{noise: } \epsilon} + \underbrace{(f_{\text{true}}(x) - \hat{f}(x))}_{\text{prediction error}}]^2$$

**Important:**

## Step 3: Expanding the Square

### Key Points

Using  $(a + b)^2 = a^2 + 2ab + b^2$

$$E[\epsilon^2 + 2\epsilon(f_{\text{true}}(x) - \hat{f}(x)) + (f_{\text{true}}(x) - \hat{f}(x))^2]$$

### Example: Applying Linearity of Expectation

$$E[\epsilon^2] + 2E[\epsilon(f_{\text{true}}(x) - \hat{f}(x))] + E[(f_{\text{true}}(x) - \hat{f}(x))^2]$$

### Definition: Let's Call These

- **Term 1:**  $E[\epsilon^2]$  (the noise term)
- **Term 2:**  $2E[\epsilon(f_{\text{true}}(x) - \hat{f}(x))]$  (cross-term)
- **Term 3:**  $E[(f_{\text{true}}(x) - \hat{f}(x))^2]$  (prediction error)

# Analyzing Term 1: The Noise Component

## Definition: Term 1 Analysis

$$E[\epsilon^2] = E[(y - f_{\text{true}}(x))^2]$$

## Key Points

Key Insight **Independence:** The noise  $\epsilon$  doesn't depend on our training set!

- Noise is a property of the data generation process
- Training set selection doesn't affect noise level

## Example: Simplification

$$E[\epsilon^2] = E[(y - f_{\text{true}}(x))^2] = \text{Var}(\epsilon) = \sigma^2$$

# Analyzing Term 2: The Cross-Term

## Definition: Term 2 Analysis

$$2E[\epsilon(f_{\text{true}}(x) - \hat{f}(x))]$$

## Key Points

Key Independence Property **Crucial insight:**  $\epsilon$  (noise) is independent of  $\hat{f}(x)$  (our prediction)

- Noise occurs in nature, regardless of our model
- Our model  $\hat{f}$  depends only on training data
- Training data and future noise are independent

## Example: Using Independence

$$E[\epsilon(f_{\text{true}}(x) - \hat{f}(x))] = E[\epsilon] \cdot E[f_{\text{true}}(x) - \hat{f}(x)]$$



# Analyzing Term 3: The Prediction Error

## Definition: Term 3 Analysis

$$E[(f_{\text{true}}(x) - \hat{f}(x))^2]$$

## Key Points

Another Independence **Key insight:**  $(f_{\text{true}}(x) - \hat{f}(x))$  doesn't depend on the noise  $\epsilon$

- $f_{\text{true}}(x)$  is deterministic
- $\hat{f}(x)$  depends only on training inputs/outputs (not future noise)

## Example: Simplification

$$E[(f_{\text{true}}(x) - \hat{f}(x))^2] = \text{MSE of prediction}$$

# Interim Summary: Progress So Far

## Definition: What We Have

$$\begin{aligned} E[(y - \hat{f}(x))^2] &= \sigma^2 + 0 + E[(f_{\text{true}}(x) - \hat{f}(x))^2] \\ &= \sigma^2 + E[(f_{\text{true}}(x) - \hat{f}(x))^2] \end{aligned}$$

## Key Points

Next Challenge **Goal:** Decompose  $E[(f_{\text{true}}(x) - \hat{f}(x))^2]$  into bias<sup>2</sup> + variance

## Example: Strategy for Next Step

**Another add-and-subtract trick:** We'll add and subtract  $E[\hat{f}(x)]$  inside the MSE term

## Step 4: Decomposing the MSE Term

### Key Points

Current Status

$$E[(y - \hat{f}(x))^2] = \sigma^2 + E[(f_{\text{true}}(x) - \hat{f}(x))^2]$$

### Definition: The Second Add-and-Subtract Trick

**Add and subtract**  $E[\hat{f}(x)]$  in the MSE term:

$$E[(f_{\text{true}}(x) - E[\hat{f}(x)] + E[\hat{f}(x)] - \hat{f}(x))^2]$$

### Example: Grouping Strategically

$$E[\underbrace{(f_{\text{true}}(x) - E[\hat{f}(x)])}_{\text{bias}} + \underbrace{(E[\hat{f}(x)] - \hat{f}(x))}_{\text{variance}}]^2$$

## Step 5: Expanding the Bias-Variance Square

### Key Points

Our Expression

$$E[(\text{bias} + \text{variance deviation})^2]$$

### Definition: Let's Define

- $\alpha = f_{\text{true}}(x) - E[\hat{f}(x)]$  (bias)
- $\beta = E[\hat{f}(x)] - \hat{f}(x)$  (variance deviation)

### Example: Expanding $(\alpha + \beta)^2$

$$E[(\alpha + \beta)^2] = E[\alpha^2] + 2E[\alpha\beta] + E[\beta^2]$$

# Analyzing the Bias Term: $E[\alpha^2]$

## Definition: The $\alpha^2$ Term

$$E[\alpha^2] = E[(f_{\text{true}}(x) - E[\hat{f}(x)])^2]$$

## Key Points

Key Insight  $(f_{\text{true}}(x) - E[\hat{f}(x)])$  is **deterministic!**

- $f_{\text{true}}(x)$  is a fixed function value
- $E[\hat{f}(x)]$  is the expected prediction (a constant)
- No randomness left to average over!

## Example: Simplification

$$E[\alpha^2] = (f_{\text{true}}(x) - E[\hat{f}(x)])^2 = [\text{Bias}(x)]^2$$

# Analyzing the Cross-Term: $E[\alpha\beta]$

## Definition: The Cross-Term

$$E[\alpha\beta] = E[(f_{\text{true}}(x) - E[\hat{f}(x)])(E[\hat{f}(x)] - \hat{f}(x))]$$

## Key Points

Another Independence Argument **Key insight:**  $(f_{\text{true}}(x) - E[\hat{f}(x)])$  is deterministic (constant)

- Can factor it out of the expectation
- Remaining term has expectation zero

## Example: Factoring Out the Constant

$$\begin{aligned} E[\alpha\beta] &= (f_{\text{true}}(x) - E[\hat{f}(x)]) \cdot E[E[\hat{f}(x)] - \hat{f}(x)] \\ &= \text{bias} \cdot (E[\hat{f}(x)] - E[\hat{f}(x)]) = \text{bias} \cdot 0 = 0 \end{aligned}$$

## Analyzing the Variance Term: $E[\beta^2]$

### Definition: The $\beta^2$ Term

$$E[\beta^2] = E[(E[\hat{f}(x)] - \hat{f}(x))^2]$$

### Key Points

Recognizing the Pattern **This is exactly the definition of variance!**

$$\text{Variance}(\hat{f}(x)) = E[(\hat{f}(x) - E[\hat{f}(x)])^2]$$

### Example: Rewriting for Clarity

$$\begin{aligned} E[\beta^2] &= E[(E[\hat{f}(x)] - \hat{f}(x))^2] = E[(\hat{f}(x) - E[\hat{f}(x)])^2] \\ &= \text{Variance}(\hat{f}(x)) \end{aligned}$$

### Important: Result

# The Complete Bias-Variance Decomposition

## Important: Putting It All Together

$$E[(y - \hat{f}(x))^2] = \sigma^2 + [\text{Bias}(x)]^2 + \text{Variance}(x)$$

## Definition: Component Summary

- $\sigma^2 = \text{Irreducible error}$  (noise in data)
- $[\text{Bias}(x)]^2 = \text{Systematic error}$  (model assumptions)
- $\text{Variance}(x) = \text{Random error}$  (training set sensitivity)

## Key Points

### The Fundamental Tradeoff

- **Reduce bias:** Use more complex models  $\rightarrow$  Increase variance
- **Reduce variance:** Use simpler models  $\rightarrow$  Increase bias



# Summary: The Bias-Variance Tradeoff

## Definition: What We've Proven

**Every prediction error can be decomposed as:**

$$\text{Total Error} = \text{Noise} + \text{Bias}^2 + \text{Variance}$$

## Key Points

### Key Takeaways

- **Noise:** Cannot be reduced (irreducible)
- **Bias:** Reduced by increasing model complexity
- **Variance:** Reduced by decreasing model complexity
- **Optimal model:** Balances bias and variance

## Important: Practical Applications