

# Conventions, Accuracy Metrics, Classification, Regression

---

Nipun Batra

IIT Gandhinagar

August 1, 2025


# Outline

1. Introduction to Machine Learning
2. Machine Learning Fundamentals
3. Classification vs Regression
4. Evaluation Metrics
5. Advanced Topics

# Digit Recognition Problem

Let us work on the digit recognition problem.

**Notebook:** [rule-based-vs-ml.html](#)



# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

- The heights of each of the | need to be similar within tolerance

# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

- The heights of each of the | need to be similar within tolerance

# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

- The heights of each of the | need to be similar within tolerance
- Each of the | can be slightly slanted. Similarly the horizontal line can be slanted.



# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

- The heights of each of the | need to be similar within tolerance
- Each of the | can be slightly slanted. Similarly the horizontal line can be slanted.

# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

- The heights of each of the | need to be similar within tolerance
- Each of the | can be slightly slanted. Similarly the horizontal line can be slanted.
- There can be some cases of 4 where the first | is at 45 degrees

# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

- The heights of each of the | need to be similar within tolerance
- Each of the | can be slightly slanted. Similarly the horizontal line can be slanted.
- There can be some cases of 4 where the first | is at 45 degrees

# Rule-based Approach for Digit Recognition

Maybe 4 can be thought of as: | + — + | + another vertical |

- The heights of each of the | need to be similar within tolerance
- Each of the | can be slightly slanted. Similarly the horizontal line can be slanted.
- There can be some cases of 4 where the first | is at 45 degrees
- There can be some cases of 4 where the width of each stroke is different

# Pop Quiz: Rule-Based vs ML

## Quick Quiz 1

Why is it difficult to write rules for digit recognition?

a) Digits are always the same

**Answer:** b) Handwriting variations make rule-based approaches extremely complex!

# Pop Quiz: Rule-Based vs ML

## Quick Quiz 1

Why is it difficult to write rules for digit recognition?

- a) Digits are always the same
- b) Variations in handwriting, rotation, thickness make rules complex

**Answer:** b) Handwriting variations make rule-based approaches extremely complex!

# Pop Quiz: Rule-Based vs ML

## Quick Quiz 1

Why is it difficult to write rules for digit recognition?

- a) Digits are always the same
- b) Variations in handwriting, rotation, thickness make rules complex
- c) Rules are faster than ML

**Answer:** b) Handwriting variations make rule-based approaches extremely complex!

# Apple Quality Features

- Size



# Apple Quality Features

- Size

# Apple Quality Features

- Size

# Apple Quality Features

- Size
- Colour

# Apple Quality Features

- Size
- Colour

# Apple Quality Features

- Size
- Colour
- Texture

## Should We Include Sample Numbers?

Answer: Usually no! Sample numbers are typically arbitrary identifiers and not meaningful features. Let us remove it.

## Should We Include Sample Numbers?

Answer: Usually no! Sample numbers are typically arbitrary identifiers and not meaningful features. Let us remove it. Let us modify our data table for now.

<b>Colour</b>	<b>Size</b>	<b>Texture</b>	<b>Condition</b>
Orange	Small	Smooth	Good
Red	Small	Rough	Good
Orange	Medium	Smooth	Bad
Yellow	Large	Smooth	Bad

# Training Set Components

The training set consists of two parts:



# Training Set Components

The training set consists of two parts:

# Training Set Components

The training set consists of two parts:

1. Features (Input Variables)

# Training Set Components

The training set consists of two parts:

1. Features (Input Variables)

# Training Set Components

The training set consists of two parts:

1. Features (Input Variables)
2. Output or Response Variable

# Dataset Notation

We call this matrix as  $\mathcal{D}$ , containing:

1. Feature matrix ( $\mathbf{X} \in \mathbb{R}^{n \times d}$ ) containing data of  $n$  samples each of which is  $d$  dimensional.

# Dataset Notation

We call this matrix as  $\mathcal{D}$ , containing:

1. Feature matrix ( $\mathbf{X} \in \mathbb{R}^{n \times d}$ ) containing data of  $n$  samples each of which is  $d$  dimensional.
2. Output vector ( $\mathbf{y} \in \mathbb{R}^n$ ) containing output variable for  $n$  samples.

## Dataset Example

Example (after encoding):  $\mathbf{x}_1 = \begin{bmatrix} 1 \\ 0 \\ 1 \end{bmatrix}$  (Orange=1, Small=0, Smooth=1)

## Dataset Example

Example (after encoding):  $\mathbf{x}_1 = \begin{bmatrix} 1 \\ 0 \\ 1 \end{bmatrix}$  (Orange=1, Small=0, Smooth=1)



## Dataset Example

Example (after encoding):  $\mathbf{x}_1 = \begin{bmatrix} 1 \\ 0 \\ 1 \end{bmatrix}$  (Orange=1, Small=0, Smooth=1)

- Complete dataset:  $\mathcal{D} = \{(\mathbf{x}_i^\top, y_i)\}_{i=1}^n$

# Machine Learning Goal

Learn  $f$ : Condition =  $f(\text{colour, size, texture})$

# Machine Learning Goal

Learn  $f$ : Condition =  $f(\text{colour, size, texture})$

# Machine Learning Goal

Learn  $f$ : Condition =  $f(\text{colour, size, texture})$

1. From Training Dataset

# Machine Learning Goal

Learn  $f$ : Condition =  $f(\text{colour, size, texture})$

1. From Training Dataset

# Machine Learning Goal

Learn  $f$ : Condition =  $f(\text{colour, size, texture})$

1. From Training Dataset
2. To Predict the condition for the Testing set

Colour	Size	Texture	Condition
Orange	Small	Smooth	Good
Red	Small	Rough	Good
Orange	Medium	Smooth	Bad
Yellow	Large	Smooth	Bad
Red	Large	Rough	?
Orange	Large	Rough	?

# Can We Judge Performance Only on Test Set?

A: Ideally, no!

# Can We Judge Performance Only on Test Set?

A: Ideally, no!



# Can We Judge Performance Only on Test Set?

A: Ideally, no!

- Ideally - we want to predict “well” on all possible inputs. But, can we test that?

# Can We Judge Performance Only on Test Set?

A: Ideally, no!

- Ideally - we want to predict “well” on all possible inputs. But, can we test that?

# Can We Judge Performance Only on Test Set?

A: Ideally, no!

- Ideally - we want to predict “well” on all possible inputs. But, can we test that?
- No! Since, the test set is only a sample from all possible inputs.

# Training vs Test Sets

Both the training set and the test set are samples drawn from the hidden true distribution (also sometimes called population)

# Training vs Test Sets

Both the training set and the test set are samples drawn from the hidden true distribution (also sometimes called population)  
More discussion later once we study bias and variance

# Energy Consumption Example

- # People (More people  $\implies$  More Energy)

# Energy Consumption Example

- # People (More people  $\implies$  More Energy)

# Energy Consumption Example

- # People (More people  $\implies$  More Energy)



# Energy Consumption Example

- # People (More people  $\implies$  More Energy)
- Temperature (Higher Temp.  $\implies$  Higher Energy)

# Energy Consumption Example

- # People (More people  $\implies$  More Energy)
- Temperature (Higher Temp.  $\implies$  Higher Energy)

# People	Temp (C)	Energy (kWh)
4000	30	30
4200	30	32
4200	35	40
3000	20	?
1000	45	?

# Pop Quiz: Training Data

## Quick Quiz 2

What makes a good feature for machine learning?

a) Sample ID numbers

**Answer:** b) Features should be meaningful and related to what you're predicting!

# Pop Quiz: Training Data

## Quick Quiz 2

What makes a good feature for machine learning?

- a) Sample ID numbers
- b) Meaningful characteristics that relate to the output

**Answer:** b) Features should be meaningful and related to what you're predicting!

# Pop Quiz: Training Data

## Quick Quiz 2

What makes a good feature for machine learning?

- a) Sample ID numbers
- b) Meaningful characteristics that relate to the output
- c) Random numbers

**Answer:** b) Features should be meaningful and related to what you're predicting!

# Classification vs Regression

- Classification

# Classification vs Regression

- Classification

# Classification vs Regression

- Classification



# Classification vs Regression

- Classification
  - Output variable is discrete

# Classification vs Regression

- Classification
  - Output variable is discrete

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)



# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous
  - i.e.  $y_i \in \mathbb{R}$

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous
  - i.e.  $y_i \in \mathbb{R}$



# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous
  - i.e.  $y_i \in \mathbb{R}$
  - Examples - Predicting:

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous
  - i.e.  $y_i \in \mathbb{R}$
  - Examples - Predicting:

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous
  - i.e.  $y_i \in \mathbb{R}$
  - Examples - Predicting:
    - How much energy will campus consume?

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous
  - i.e.  $y_i \in \mathbb{R}$
  - Examples - Predicting:
    - How much energy will campus consume?

# Classification vs Regression

- Classification
  - Output variable is discrete
  - i.e.  $y_i \in \{1, 2, \dots, k\}$  where  $k$  is number of classes
  - Examples - Predicting:
    - Will I get a loan? (Yes, No)
    - What is the quality of fruit? (Good, Bad)
- Regression
  - Output variable is continuous
  - i.e.  $y_i \in \mathbb{R}$
  - Examples - Predicting:
    - How much energy will campus consume?
    - How much rainfall will fall?

# Pop Quiz: Problem Types

## Quick Quiz 3

Predicting house prices is an example of:

a) Classification (discrete output)

**Answer:** b) Regression - house prices are continuous values!

# Pop Quiz: Problem Types

## Quick Quiz 3

Predicting house prices is an example of:

- a) Classification (discrete output)
- b) Regression (continuous output)

**Answer:** b) Regression - house prices are continuous values!

# Pop Quiz: Problem Types

## Quick Quiz 3

Predicting house prices is an example of:

- a) Classification (discrete output)
- b) Regression (continuous output)
- c) Neither

**Answer:** b) Regression - house prices are continuous values!



## Accuracy Calculation

$$\text{Accuracy} = \frac{|\{i : y_i = \hat{y}_i\}|}{n} = \frac{3}{5} = 0.6$$

# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$

# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$ 
  - Reads as: “Number of indices  $i$  such that  $y_i = \hat{y}_i$ ”

# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$ 
  - Reads as: “Number of indices  $i$  such that  $y_i = \hat{y}_i$ ”
  - Counts how many samples satisfy the condition

# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$ 
  - Reads as: “Number of indices  $i$  such that  $y_i = \hat{y}_i$ ”
  - Counts how many samples satisfy the condition

# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$ 
  - Reads as: “Number of indices  $i$  such that  $y_i = \hat{y}_i$ ”
  - Counts how many samples satisfy the condition

# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$ 
  - Reads as: “Number of indices  $i$  such that  $y_i = \hat{y}_i$ ”
  - Counts how many samples satisfy the condition
- **Alternative: Indicator function notation**

$$\text{Accuracy} = \frac{\sum_{i=1}^n \mathbf{1}[y_i = \hat{y}_i]}{n}$$

$$\text{where } \mathbf{1}[\text{condition}] = \begin{cases} 1 & \text{if condition is true} \\ 0 & \text{if condition is false} \end{cases}$$

# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$ 
  - Reads as: “Number of indices  $i$  such that  $y_i = \hat{y}_i$ ”
  - Counts how many samples satisfy the condition
- **Alternative: Indicator function notation**

$$\text{Accuracy} = \frac{\sum_{i=1}^n \mathbf{1}[y_i = \hat{y}_i]}{n}$$

$$\text{where } \mathbf{1}[\text{condition}] = \begin{cases} 1 & \text{if condition is true} \\ 0 & \text{if condition is false} \end{cases}$$



# Accuracy Notation

- **Set cardinality notation:**  $|\{i : y_i = \hat{y}_i\}|$ 
  - Reads as: “Number of indices  $i$  such that  $y_i = \hat{y}_i$ ”
  - Counts how many samples satisfy the condition
- **Alternative: Indicator function notation**

$$\text{Accuracy} = \frac{\sum_{i=1}^n \mathbf{1}[y_i = \hat{y}_i]}{n}$$

where  $\mathbf{1}[\text{condition}] = \begin{cases} 1 & \text{if condition is true} \\ 0 & \text{if condition is false} \end{cases}$

- Both notations are mathematically equivalent and commonly used in ML literature

# When Precision/Recall Matter

Cases for this:

- Cancer Screening

# When Precision/Recall Matter

Cases for this:

- Cancer Screening
- Planet Detection

## Precision Metric

$$\text{Precision} = \frac{|\{i : y_i = \hat{y}_i = \text{Good}\}|}{|\{i : \hat{y}_i = \text{Good}\}|} = \frac{2}{4} = 0.5$$

**Definition:** “The fraction of relevant instances among the retrieved instances”

**In simple terms:** Out of all times we predict “Good”, how many times is it actually “Good”?

## Accuracy vs Precision/Recall

$$\text{Accuracy} = \frac{98}{100} = 0.98$$

$$\text{Recall} = \frac{0}{1} = 0$$

$$\text{Precision} = \frac{0}{1} = 0$$

# Confusion Matrix

		Ground Truth	
		Positive	Negative
Predicted	Positive	<b>True Positive (TP)</b>	<b>False Positive (FP)</b>
	Negative	<b>False Negative (FN)</b>	<b>True Negative (TN)</b>

# Confusion Matrix

		Ground Truth	
		Positive	Negative
Predicted	Positive	<b>True Positive (TP)</b>	<b>False Positive (FP)</b>
	Negative	<b>False Negative (FN)</b>	<b>True Negative (TN)</b>

## Key Insight

Each cell represents a different type of prediction outcome:

# Confusion Matrix

		Ground Truth	
		Positive	Negative
Predicted	Positive	<b>True Positive (TP)</b>	<b>False Positive (FP)</b>
	Negative	<b>False Negative (FN)</b>	<b>True Negative (TN)</b>

## Key Insight

Each cell represents a different type of prediction outcome:

- **TP**: Correctly predicted positive



# Confusion Matrix

		Ground Truth	
		Positive	Negative
Predicted	Positive	<b>True Positive (TP)</b>	<b>False Positive (FP)</b>
	Negative	<b>False Negative (FN)</b>	<b>True Negative (TN)</b>

## Key Insight

Each cell represents a different type of prediction outcome:

- **TP**: Correctly predicted positive
- **FP**: Incorrectly predicted positive

# Confusion Matrix

		Ground Truth	
		Positive	Negative
Predicted	Positive	<b>True Positive (TP)</b>	<b>False Positive (FP)</b>
	Negative	<b>False Negative (FN)</b>	<b>True Negative (TN)</b>

## Key Insight

Each cell represents a different type of prediction outcome:

- **TP**: Correctly predicted positive
- **FP**: Incorrectly predicted positive
- **FN**: Missed a positive (dangerous!)

# Confusion Matrix

		Ground Truth	
		Positive	Negative
Predicted	Positive	<b>True Positive (TP)</b>	<b>False Positive (FP)</b>
	Negative	<b>False Negative (FN)</b>	<b>True Negative (TN)</b>

## Key Insight

Each cell represents a different type of prediction outcome:

- **TP**: Correctly predicted positive
- **FP**: Incorrectly predicted positive
- **FN**: Missed a positive (dangerous!)
- **TN**: Correctly predicted negative

Precision: "How accurate are my positive predictions?"

		Ground Truth	
		Positive	Negative
Predicted	Positive	TP	FP
	Negative	FN	TN

  
$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}} = \frac{\text{Correct Positives}}{\text{All Predicted Positives}}$$

Precision: "How accurate are my positive predictions?"

		Ground Truth	
		Positive	Negative
Predicted	Positive	TP	FP
	Negative	FN	TN

  
$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}} = \frac{\text{Correct Positives}}{\text{All Predicted Positives}}$$

**Focus:** Look at the PREDICTED POSITIVE ROW

**Question:** When I predict "positive", how often am I right?

**Answer:** Out of all my positive predictions (TP + FP), TP are correct.

Recall: "How many actual positives did I find?"

		Ground Truth	
		Positive	Negative
Predicted	Positive	TP	FP
	Negative	FN	TN

Recall =  $\frac{\text{TP}}{\text{TP} + \text{FN}} = \frac{\text{Correct Positives}}{\text{All Actual Positives}}$

Recall: "How many actual positives did I find?"

		Ground Truth	
		Positive	Negative
Predicted	Positive	TP	FP
	Negative	FN	TN

  
$$\text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}} = \frac{\text{Correct Positives}}{\text{All Actual Positives}}$$

**Focus:** Look at the ACTUAL POSITIVE COLUMN

**Question:** Of all things that ARE positive, how many did I catch?

**Answer:** Out of all actual positives (TP + FN), I found TP of them.

## Example: Medical Diagnosis

Let's say we're testing for a disease:

		Actually Has Disease	
		Yes	No
Test Says	Positive	90	10
	Negative	5	895



## Example: Medical Diagnosis

Let's say we're testing for a disease:

		Actually Has Disease	
		Yes	No
Test Says	Positive	90	10
	Negative	5	895

$$\text{Precision} = \frac{90}{90 + 10} = \frac{90}{100} = 0.90 \text{ (90\%)}$$

$$\text{Recall} = \frac{90}{90 + 5} = \frac{90}{95} = 0.95 \text{ (95\%)}$$

$$\text{Accuracy} = \frac{90 + 895}{1000} = 0.985 \text{ (98.5\%)}$$

## Example: Medical Diagnosis

Let's say we're testing for a disease:

		Actually Has Disease	
		Yes	No
Test Says	Positive	90	10
	Negative	5	895

$$\text{Precision} = \frac{90}{90 + 10} = \frac{90}{100} = 0.90 \text{ (90\%)}$$

$$\text{Accuracy} = \frac{90 + 895}{1000} = 0.985 \text{ (98.5\%)}$$

## Example: Medical Diagnosis

Let's say we're testing for a disease:

		Actually Has Disease	
		Yes	No
Test Says	Positive	90	10
	Negative	5	895

$$\text{Precision} = \frac{90}{90 + 10} = \frac{90}{100} = 0.90 \text{ (90\%)}$$

$$\text{Recall} = \frac{90}{90 + 5} = \frac{90}{95} = 0.95 \text{ (95\%)}$$

$$\text{Accuracy} = \frac{90 + 895}{1000} = 0.985 \text{ (98.5\%)}$$

# Mean Error Issues

Is there any downside with using mean error?

# Mean Error Issues

Is there any downside with using mean error? Errors can get cancelled out

# Pop Quiz: Metrics Choice

## Quick Quiz 4

For cancer detection (1 positive case in 1000), which metric is most important?

a) Accuracy only

**Answer:** b) Recall - we cannot afford to miss cancer cases!

# Pop Quiz: Metrics Choice

## Quick Quiz 4

For cancer detection (1 positive case in 1000), which metric is most important?

- a) Accuracy only
- b) Recall (finding all cancer cases)

**Answer:** b) Recall - we cannot afford to miss cancer cases!

# Pop Quiz: Metrics Choice

## Quick Quiz 4

For cancer detection (1 positive case in 1000), which metric is most important?

- a) Accuracy only
- b) Recall (finding all cancer cases)
- c) Speed of prediction

**Answer:** b) Recall - we cannot afford to miss cancer cases!



# Pop Quiz

## Quick Quiz 1

Which metrics should you use for imbalanced datasets?

1. Accuracy only

**Answer:** c) Precision, recall, and F1-score give a more complete picture!

# Pop Quiz

## Quick Quiz 1

Which metrics should you use for imbalanced datasets?

1. Accuracy only
2. Mean squared error

**Answer:** c) Precision, recall, and F1-score give a more complete picture!

# Pop Quiz

## Quick Quiz 1

Which metrics should you use for imbalanced datasets?

1. Accuracy only
2. Mean squared error
3. Precision, recall, and F1-score

**Answer:** c) Precision, recall, and F1-score give a more complete picture!

# Key Takeaways

- **ML vs Traditional Programming:**

ML learns rules from data, traditional programming uses predefined rules

# Key Takeaways

- **ML vs Traditional Programming:**

ML learns rules from data, traditional programming uses predefined rules

# Key Takeaways

- **ML vs Traditional Programming:**

ML learns rules from data, traditional programming uses predefined rules

- **Features matter:**

Choose meaningful features, avoid arbitrary identifiers

# Key Takeaways

- **ML vs Traditional Programming:**

ML learns rules from data, traditional programming uses predefined rules

- **Features matter:**

Choose meaningful features, avoid arbitrary identifiers

# Key Takeaways

- **ML vs Traditional Programming:**

ML learns rules from data, traditional programming uses predefined rules

- **Features matter:**

Choose meaningful features, avoid arbitrary identifiers

- **Classification vs Regression:**

Discrete outputs vs continuous outputs



# Key Takeaways

- **ML vs Traditional Programming:**  
ML learns rules from data, traditional programming uses predefined rules
- **Features matter:**  
Choose meaningful features, avoid arbitrary identifiers
- **Classification vs Regression:**  
Discrete outputs vs continuous outputs

# Key Takeaways

- **ML vs Traditional Programming:**

ML learns rules from data, traditional programming uses predefined rules

- **Features matter:**

Choose meaningful features, avoid arbitrary identifiers

- **Classification vs Regression:**

Discrete outputs vs continuous outputs

- **Accuracy isn't everything:**

For imbalanced data, use precision, recall, F1-score

# Key Takeaways

- **ML vs Traditional Programming:**

ML learns rules from data, traditional programming uses predefined rules

- **Features matter:**

Choose meaningful features, avoid arbitrary identifiers

- **Classification vs Regression:**

Discrete outputs vs continuous outputs

- **Accuracy isn't everything:**

For imbalanced data, use precision, recall, F1-score

# Key Takeaways

- **ML vs Traditional Programming:**  
ML learns rules from data, traditional programming uses predefined rules
- **Features matter:**  
Choose meaningful features, avoid arbitrary identifiers
- **Classification vs Regression:**  
Discrete outputs vs continuous outputs
- **Accuracy isn't everything:**  
For imbalanced data, use precision, recall, F1-score
- **Visualization is crucial:**  
Always plot your data first

# Key Takeaways

- **ML vs Traditional Programming:**  
ML learns rules from data, traditional programming uses predefined rules
- **Features matter:**  
Choose meaningful features, avoid arbitrary identifiers
- **Classification vs Regression:**  
Discrete outputs vs continuous outputs
- **Accuracy isn't everything:**  
For imbalanced data, use precision, recall, F1-score
- **Visualization is crucial:**  
Always plot your data first

# Key Takeaways

- **ML vs Traditional Programming:**  
ML learns rules from data, traditional programming uses predefined rules
- **Features matter:**  
Choose meaningful features, avoid arbitrary identifiers
- **Classification vs Regression:**  
Discrete outputs vs continuous outputs
- **Accuracy isn't everything:**  
For imbalanced data, use precision, recall, F1-score
- **Visualization is crucial:**  
Always plot your data first
- **Use baselines:**  
Simple baseline models help validate your approach

# Summary: Evaluation Metrics

Task	Common Metrics	When to Use
<b>Classification</b>	Accuracy, Precision, Recall, F1 Confusion Matrix	Balanced/Imbalanced data Multi-class problems
<b>Regression</b>	MSE, RMSE, MAE Mean Error	Continuous predictions Check for bias

## Remember

Choose metrics based on your problem's characteristics and business requirements!