

# Cross-Validation

---

Nipun Batra and teaching staff

IIT Gandhinagar

July 30, 2025

Does not use the full dataset for training and does not test on the full dataset

Does not use the full dataset for training and does not test on the full dataset

Does not use the full dataset for training and does not test on the full dataset

No way to optimize hyperparameters

Does not use the full dataset for training and does not test on the full dataset

No way to optimize hyperparameters

Does not use the full dataset for training and does not test on the full dataset

No way to optimize hyperparameters

This simple train/test split has limitations we need to address

Answer

## Answer

- Does not utilize the full dataset for training



## Answer

- Does not utilize the full dataset for training
- Cannot optimize hyperparameters systematically

## Answer

- Does not utilize the full dataset for training
- Cannot optimize hyperparameters systematically

## Answer

- Does not utilize the full dataset for training
- Cannot optimize hyperparameters systematically
- Results depend on the particular split chosen

## Answer

- Does not utilize the full dataset for training
- Cannot optimize hyperparameters systematically
- Results depend on the particular split chosen
- May not get reliable performance estimates

Over multiple iterations, use different parts of the dataset for training and testing

Over multiple iterations, use different parts of the dataset for training and testing

Over multiple iterations, use different parts of the dataset for training and testing

Typically done via different random splits of the dataset

Over multiple iterations, use different parts of the dataset for training and testing

Typically done via different random splits of the dataset



Over multiple iterations, use different parts of the dataset for training and testing

Typically done via different random splits of the dataset

**Challenge:** How to ensure systematic evaluation?

Over multiple iterations, use different parts of the dataset for training and testing

Typically done via different random splits of the dataset

**Challenge:** How to ensure systematic evaluation?

Over multiple iterations, use different parts of the dataset for training and testing

Typically done via different random splits of the dataset

**Challenge:** How to ensure systematic evaluation?

May not use every data point for training or testing with random splits

Over multiple iterations, use different parts of the dataset for training and testing

Typically done via different random splits of the dataset

**Challenge:** How to ensure systematic evaluation?

May not use every data point for training or testing with random splits

Over multiple iterations, use different parts of the dataset for training and testing

Typically done via different random splits of the dataset

**Challenge:** How to ensure systematic evaluation?

May not use every data point for training or testing with random splits

May be computationally expensive

- Each data point is used for testing exactly once

- Each data point is used for testing exactly once
- Each data point is used for training  $(k - 1)/k$  of the time

- Each data point is used for testing exactly once
- Each data point is used for training  $(k - 1)/k$  of the time



- Each data point is used for testing exactly once
- Each data point is used for training  $(k - 1)/k$  of the time
- Provides more robust performance estimates

## Answer

80 data points (4 out of 5 folds =  $4/5 \times 100 = 80$ )

Validation set helps select the best hyperparameters

Validation set helps select the best hyperparameters

Validation set helps select the best hyperparameters

Test set remains untouched until final evaluation

Validation set helps select the best hyperparameters

Test set remains untouched until final evaluation

Validation set helps select the best hyperparameters

Test set remains untouched until final evaluation

This prevents overfitting to the test set

Each fold provides one validation score



Each fold provides one validation score

Each fold provides one validation score

Process is systematic and exhaustive

Answer

## Answer

- Simple CV: Used for model evaluation only

## Answer

- Simple CV: Used for model evaluation only
- Nested CV: Outer loop for model evaluation, inner loop for hyperparameter tuning

## Answer

- Simple CV: Used for model evaluation only
- Nested CV: Outer loop for model evaluation, inner loop for hyperparameter tuning

## Answer

- Simple CV: Used for model evaluation only
- Nested CV: Outer loop for model evaluation, inner loop for hyperparameter tuning
- Nested CV provides unbiased estimates when doing hyperparameter search

Final model is trained on entire training set



Final model is trained on entire training set

Final model is trained on entire training set  
Standard deviation gives confidence in results

Answer

## Answer

- Single fold results can be misleading due to data variance

## Answer

- Single fold results can be misleading due to data variance
- Averaging provides more robust performance estimates

## Answer

- Single fold results can be misleading due to data variance
- Averaging provides more robust performance estimates

## Answer

- Single fold results can be misleading due to data variance
- Averaging provides more robust performance estimates
- Reduces impact of lucky/unlucky splits

## Answer

- Single fold results can be misleading due to data variance
- Averaging provides more robust performance estimates
- Reduces impact of lucky/unlucky splits
- Standard deviation indicates reliability of the estimate



Special case where  $k = n$  (number of data points)

Special case where  $k = n$  (number of data points)

Special case where  $k = n$  (number of data points)  
Each fold uses exactly one data point for testing

Special case where  $k = n$  (number of data points)  
Each fold uses exactly one data point for testing

Special case where  $k = n$  (number of data points)

Each fold uses exactly one data point for testing

**Advantages:**

- Maximum use of data for training

Special case where  $k = n$  (number of data points)

Each fold uses exactly one data point for testing

**Advantages:**

- Maximum use of data for training
- Deterministic (no randomness)

Special case where  $k = n$  (number of data points)

Each fold uses exactly one data point for testing

**Advantages:**

- Maximum use of data for training
- Deterministic (no randomness)

Special case where  $k = n$  (number of data points)

Each fold uses exactly one data point for testing

**Advantages:**

- Maximum use of data for training
- Deterministic (no randomness)



Special case where  $k = n$  (number of data points)

Each fold uses exactly one data point for testing

**Advantages:**

- Maximum use of data for training
- Deterministic (no randomness)

**Disadvantages:**

- Computationally expensive

Special case where  $k = n$  (number of data points)

Each fold uses exactly one data point for testing

**Advantages:**

- Maximum use of data for training
- Deterministic (no randomness)

**Disadvantages:**

- Computationally expensive
- High variance in estimates

Maintains class distribution in each fold

Maintains class distribution in each fold

Maintains class distribution in each fold  
Important for imbalanced datasets

Maintains class distribution in each fold  
Important for imbalanced datasets

Maintains class distribution in each fold

Important for imbalanced datasets

Each fold has approximately same proportion of classes

Maintains class distribution in each fold

Important for imbalanced datasets

Each fold has approximately same proportion of classes



Maintains class distribution in each fold

Important for imbalanced datasets

Each fold has approximately same proportion of classes

**Example:** If dataset is 70% class A, 30% class B, each fold maintains this ratio

Maintains class distribution in each fold

Important for imbalanced datasets

Each fold has approximately same proportion of classes

**Example:** If dataset is 70% class A, 30% class B, each fold maintains this ratio

Maintains class distribution in each fold

Important for imbalanced datasets

Each fold has approximately same proportion of classes

**Example:** If dataset is 70% class A, 30% class B, each fold maintains this ratio

Reduces variance in performance estimates

Answer

## Answer

- Regular CV might create folds with very few (or zero) positive examples

## Answer

- Regular CV might create folds with very few (or zero) positive examples
- This would give misleading performance estimates

## Answer

- Regular CV might create folds with very few (or zero) positive examples
- This would give misleading performance estimates

## Answer

- Regular CV might create folds with very few (or zero) positive examples
- This would give misleading performance estimates
- Stratified CV ensures each fold has  $\sim 10\%$  positive examples



## Answer

- Regular CV might create folds with very few (or zero) positive examples
- This would give misleading performance estimates
- Stratified CV ensures each fold has  $\sim 10\%$  positive examples
- Results in more reliable and consistent evaluation

Regular CV assumes data points are independent

Regular CV assumes data points are independent

Regular CV assumes data points are independent

Time series data has temporal dependencies

Regular CV assumes data points are independent

Time series data has temporal dependencies

Regular CV assumes data points are independent

Time series data has temporal dependencies

**Forward Chaining:** Train on past, test on future

Regular CV assumes data points are independent

Time series data has temporal dependencies

**Forward Chaining:** Train on past, test on future

Regular CV assumes data points are independent

Time series data has temporal dependencies

**Forward Chaining:** Train on past, test on future

**Rolling Window:** Fixed-size training window



Regular CV assumes data points are independent

Time series data has temporal dependencies

**Forward Chaining:** Train on past, test on future

**Rolling Window:** Fixed-size training window

Regular CV assumes data points are independent

Time series data has temporal dependencies

**Forward Chaining:** Train on past, test on future

**Rolling Window:** Fixed-size training window

**Expanding Window:** Growing training set over time

Regular CV assumes data points are independent

Time series data has temporal dependencies

**Forward Chaining:** Train on past, test on future

**Rolling Window:** Fixed-size training window

**Expanding Window:** Growing training set over time

Regular CV assumes data points are independent

Time series data has temporal dependencies

**Forward Chaining:** Train on past, test on future

**Rolling Window:** Fixed-size training window

**Expanding Window:** Growing training set over time

Never use future data to predict past!

**Data Leakage:** Information from test set influences training

**Data Leakage:** Information from test set influences training

**Data Leakage:** Information from test set influences training

**Incorrect Splitting:** Not accounting for grouped data

**Data Leakage:** Information from test set influences training

**Incorrect Splitting:** Not accounting for grouped data



**Data Leakage:** Information from test set influences training

**Incorrect Splitting:** Not accounting for grouped data

**Overfitting to CV:** Too much hyperparameter tuning

**Data Leakage:** Information from test set influences training

**Incorrect Splitting:** Not accounting for grouped data

**Overfitting to CV:** Too much hyperparameter tuning

**Data Leakage:** Information from test set influences training

**Incorrect Splitting:** Not accounting for grouped data

**Overfitting to CV:** Too much hyperparameter tuning

**Wrong Preprocessing:** Scaling on entire dataset before splitting

**Data Leakage:** Information from test set influences training

**Incorrect Splitting:** Not accounting for grouped data

**Overfitting to CV:** Too much hyperparameter tuning

**Wrong Preprocessing:** Scaling on entire dataset before splitting

**Data Leakage:** Information from test set influences training

**Incorrect Splitting:** Not accounting for grouped data

**Overfitting to CV:** Too much hyperparameter tuning

**Wrong Preprocessing:** Scaling on entire dataset before splitting

**Ignoring Class Imbalance:** Not using stratified CV when needed

Answer

## Answer

- This causes data leakage!

## Answer

- This causes data leakage!
- Test fold statistics influence the training preprocessing



## Answer

- This causes data leakage!
- Test fold statistics influence the training preprocessing

## Answer

- This causes data leakage!
- Test fold statistics influence the training preprocessing
- Should compute statistics only on training folds

## Answer

- This causes data leakage!
- Test fold statistics influence the training preprocessing
- Should compute statistics only on training folds
- Apply same transformation to corresponding test fold

## Answer

- This causes data leakage!
- Test fold statistics influence the training preprocessing
- Should compute statistics only on training folds
- Apply same transformation to corresponding test fold
- This gives more realistic performance estimates

**Better Data Utilization:** Every point used for both training and testing

**Better Data Utilization:** Every point used for both training and testing

**Better Data Utilization:** Every point used for both training and testing

**Robust Evaluation:** Multiple train/test splits reduce variance

**Better Data Utilization:** Every point used for both training and testing

**Robust Evaluation:** Multiple train/test splits reduce variance



**Better Data Utilization:** Every point used for both training and testing

**Robust Evaluation:** Multiple train/test splits reduce variance

**Hyperparameter Tuning:** Systematic way to select best parameters

**Better Data Utilization:** Every point used for both training and testing

**Robust Evaluation:** Multiple train/test splits reduce variance

**Hyperparameter Tuning:** Systematic way to select best parameters

**Better Data Utilization:** Every point used for both training and testing

**Robust Evaluation:** Multiple train/test splits reduce variance

**Hyperparameter Tuning:** Systematic way to select best parameters

**Model Comparison:** Fair comparison between different algorithms

**Better Data Utilization:** Every point used for both training and testing

**Robust Evaluation:** Multiple train/test splits reduce variance

**Hyperparameter Tuning:** Systematic way to select best parameters

**Model Comparison:** Fair comparison between different algorithms

**Better Data Utilization:** Every point used for both training and testing

**Robust Evaluation:** Multiple train/test splits reduce variance

**Hyperparameter Tuning:** Systematic way to select best parameters

**Model Comparison:** Fair comparison between different algorithms

**Confidence Estimates:** Standard deviation indicates reliability

**K-Fold (k=5,10):** General purpose, most common

**K-Fold (k=5,10):** General purpose, most common

**K-Fold (k=5,10):** General purpose, most common

**Stratified:** Imbalanced classification problems



**K-Fold (k=5,10):** General purpose, most common

**Stratified:** Imbalanced classification problems

**K-Fold (k=5,10):** General purpose, most common

**Stratified:** Imbalanced classification problems

**LOOCV:** Small datasets, when computational cost is acceptable

**K-Fold (k=5,10):** General purpose, most common

**Stratified:** Imbalanced classification problems

**LOOCV:** Small datasets, when computational cost is acceptable

**K-Fold (k=5,10):** General purpose, most common

**Stratified:** Imbalanced classification problems

**LOOCV:** Small datasets, when computational cost is acceptable

**Time Series CV:** Temporal data with dependencies

**K-Fold (k=5,10):** General purpose, most common

**Stratified:** Imbalanced classification problems

**LOOCV:** Small datasets, when computational cost is acceptable

**Time Series CV:** Temporal data with dependencies

**K-Fold (k=5,10):** General purpose, most common

**Stratified:** Imbalanced classification problems

**LOOCV:** Small datasets, when computational cost is acceptable

**Time Series CV:** Temporal data with dependencies

**Nested CV:** When doing extensive hyperparameter search

Always preprocess within each fold separately

Always preprocess within each fold separately



Always preprocess within each fold separately

Use stratification for classification problems

Always preprocess within each fold separately

Use stratification for classification problems

Always preprocess within each fold separately

Use stratification for classification problems

Report mean  $\pm$  standard deviation

Always preprocess within each fold separately

Use stratification for classification problems

Report mean  $\pm$  standard deviation

Always preprocess within each fold separately

Use stratification for classification problems

Report mean  $\pm$  standard deviation

Don't overfit to cross-validation results

Always preprocess within each fold separately

Use stratification for classification problems

Report mean  $\pm$  standard deviation

Don't overfit to cross-validation results

Always preprocess within each fold separately

Use stratification for classification problems

Report mean  $\pm$  standard deviation

Don't overfit to cross-validation results

Consider computational cost vs. benefit trade-off

Always preprocess within each fold separately

Use stratification for classification problems

Report mean  $\pm$  standard deviation

Don't overfit to cross-validation results

Consider computational cost vs. benefit trade-off



Always preprocess within each fold separately

Use stratification for classification problems

Report mean  $\pm$  standard deviation

Don't overfit to cross-validation results

Consider computational cost vs. benefit trade-off

Use nested CV for unbiased hyperparameter search

# Next time: Ensemble Learning

- How to combine various models?

# Next time: Ensemble Learning

- How to combine various models?
- Why combine multiple models?

# Next time: Ensemble Learning

- How to combine various models?
- Why combine multiple models?

# Next time: Ensemble Learning

- How to combine various models?
- Why combine multiple models?
- How can we reduce bias?

# Next time: Ensemble Learning

- How to combine various models?
- Why combine multiple models?
- How can we reduce bias?
- How can we reduce variance?

# Next time: Ensemble Learning

- How to combine various models?
- Why combine multiple models?
- How can we reduce bias?
- How can we reduce variance?
- Bootstrap aggregating (Bagging)

# Next time: Ensemble Learning

- How to combine various models?
- Why combine multiple models?
- How can we reduce bias?
- How can we reduce variance?
- Bootstrap aggregating (Bagging)



# Next time: Ensemble Learning

- How to combine various models?
- Why combine multiple models?
- How can we reduce bias?
- How can we reduce variance?
- Bootstrap aggregating (Bagging)
- Boosting methods