

#### **Cross-Validation**


Nipun Batra and teaching staff

July 20, 2025


IIT Gandhinagar








 Does not use the full dataset for training and does not test on the full dataset



 Does not use the full dataset for training and does not test on the full dataset



- Does not use the full dataset for training and does not test on the full dataset
- No way to optimize hyperparameters

 Over multiple iterations, use different parts of the dataset for training and testing.

 Over multiple iterations, use different parts of the dataset for training and testing.

- Over multiple iterations, use different parts of the dataset for training and testing.
- Typically done via different random splits of the dataset.

- Over multiple iterations, use different parts of the dataset for training and testing.
- Typically done via different random splits of the dataset.

- Over multiple iterations, use different parts of the dataset for training and testing.
- Typically done via different random splits of the dataset.
- Challenge?


- Over multiple iterations, use different parts of the dataset for training and testing.
- Typically done via different random splits of the dataset.
- Challenge?

- Over multiple iterations, use different parts of the dataset for training and testing.
- Typically done via different random splits of the dataset.
- Challenge?
- May not use every data point for training or testing


- Over multiple iterations, use different parts of the dataset for training and testing.
- Typically done via different random splits of the dataset.
- Challenge?
- May not use every data point for training or testing

- Over multiple iterations, use different parts of the dataset for training and testing.
- Typically done via different random splits of the dataset.
- Challenge?
- May not use every data point for training or testing
- May be computationally expensive

### K-Fold cross-validation: Utilize full dataset for testing




# K-Fold cross-validation: Utilize full dataset for testing




Each data point is used for testing exactly once.

### Optimizing Hyperparameters via the Validation Set




#### **Nested Cross Validation**

Divide your training set into k equal parts. Cyclically use 1 part as "validation set" and the rest for training. Here k=4



#### **Nested Cross Validation**

Average out the validation accuracy across all the folds Use the model with highest validation accuracy



• How to combine various models?

- How to combine various models?
- Why to combine multiple models?

- How to combine various models?
- Why to combine multiple models?
- How can we reduce bias?

- How to combine various models?
- Why to combine multiple models?
- How can we reduce bias?
- How can we reduce variance?