

First understand how files link together

JavaScript uses `import` and `export`.

For example, imagine `readingsService.mjs` contains:

```
1 export async function createReading(  
2   branchId,  
3   body  
4 ) {  
5   // code  
6 }
```

The word:

```
1 export
```

means:

Allow another JavaScript file to use this function.

Then your controller can do:

```
1 import {  
2   createReading  
3 } from "../services/readingsService.mjs";
```

That means:

Go to `readingsService.mjs` and bring its exported `createReading` function into this file.

So these two pieces are connected:

```
1 readingsService.mjs  
2  
3 export createReading()  
4  
5   | imported by  
6   ▼  
7 readingsController.mjs  
8  
9 import { createReading }
```

This is how your files communicate.

Understanding `../` and `./`

You'll see things like:

```
1 import {
```

```
2   createReading
3 } from "../services/readingsService.mjs";
```

The:

```
1 | ../
```

means:

Go up one folder.

For example, the controller is here:

```
1 | link-dynamodb/
2 |   └─ controller/
3 |       └─ readingsController.mjs
```

From `controller`, doing:

```
1 | ../
```

takes us back to:

```
1 | link-dynamodb/
```

Then:

```
1 | services/readingsService.mjs
```

takes us into:

```
1 | link-dynamodb/
2 |   └─ services/
3 |       └─ readingsService.mjs
```

So:

```
1 | "../services/readingsService.mjs"
```

literally means:

```
1 | Go up one folder
2 |   ↓
3 | go into services
4 |   ↓
5 | open readingsService.mjs
```

Whereas:

```
1 | "../controller/readingsController.mjs"
```

uses:

```
1 | ./
```

which means:

Start from the folder I am already in. First understand how files link together