HCIA-AI V4.0 Certification — Complete Instructor Lecture Notes

Comprehensive Summary of Official Training Meetings • Core Technical Explanations • Key Formulas & Exam Traps

Curated by: Umed Jamal Nouri • v1.1 (Nov 2026) • github.com/UmedJaMala

Executive Curriculum & Training Overview

This document synthesizes the complete live meeting recordings and closed-caption transcripts from the official Huawei HCIA-AI V4.0 certification training. The course covers the full spectrum of artificial intelligence, spanning mathematical fundamentals, classical machine learning, deep neural architectures, Huawei Ascend & CANN hardware acceleration, MindSpore / PyTorch frameworks, large foundation models, prompt engineering, and cutting-edge industrial applications. Special attention is devoted to specific exam warnings, common student misconceptions, and formulas emphasized directly by the instructor during class.

LECTURE 1: AI OVERVIEW: DEFINITIONS, TECHNOLOGIES & ECOSYSTEM

Date: **July 21, 2026** • Official Module: **Chapter 1: AI Overview**

1. Course Introduction & AI Evolutionary Stages

• **Historical Milestones:** The birth of AI at the Dartmouth Workshop in 1956 (John McCarthy, Marvin Minsky, Claude Shannon). The historical boom and bust cycles (the two AI winters caused by compute/data bottlenecks).

• **Hierarchy of Intelligence:** Deep Learning is a subset of Machine Learning, which in turn is a subset of Artificial Intelligence: *Deep Learning (subset of) Machine Learning (subset of) AI*.

• **Weak AI vs Strong AI (AGI):** Weak AI focuses on narrow, dedicated tasks (e.g., face recognition, speech-to-text, game playing). Strong AI / AGI aims for general autonomous cognitive and cross-domain reasoning abilities matching or exceeding human intellect.

• **The Three Cognitive Schools:** *Symbolism* (rule-based, logical deduction), *Connectionism* (bionic neural networks, learning from data), and *Behaviorism* (cybernetics, perception-action feedback).

2. Huawei's Full-Stack All-Scenario AI Solution

The instructor emphasized Huawei's strategic architecture consisting of four integrated layers:

• **Ascend AI Chips:** Ascend 310 (low-power edge inference, 8W/16 TOPS) and Ascend 910 (cloud-scale high-throughput training, 310W / 256 TFLOPS FP16, 512 TOPS INT8).

• **CANN (Compute Architecture for Neural Networks):** Chip enabling layer bridging hardware and software frameworks via AscendCL and TBE (Tensor Boost Engine).

• **MindSpore:** Unified all-scenario AI development framework spanning device, edge, and cloud.

• **Application Enablement (ModelArts):** Full-lifecycle cloud AI development platform providing ExeML, smart annotation, and MoXing.

EXAM WARNING — INSTRUCTOR EMPHASIS

"Huawei loves to test the distinction between Ascend 310 (Edge Inference) and Ascend 910 (Cloud Training). Also memorize the hierarchy of AI schools: Connectionism is the theoretical foundation of modern Deep Learning!"

LECTURE 2: MACHINE LEARNING ENGINEERING WORKFLOW & CORE ALGORITHMS

Date: **July 26, 2026** • Official Module: **Chapter 2: Machine Learning**

1. The Machine Learning Engineering Lifecycle

The instructor broke down the standard ML pipeline: Problem Formulation → Data Collection & Cleaning → Feature Engineering (Extraction, Selection, Scaling) → Model Training → Validation & Evaluation → Model Deployment.

• **Feature Exploration:** Dealing with the 'curse of dimensionality' where data points become sparse in high-dimensional spaces.

• **Gradient Descent Method:** Iterative optimization algorithm navigating the loss curvature to find the local/global minimum: $w = w - alpha * grad(L)$.

2. Supervised, Unsupervised & Ensemble Algorithms

• **Supervised Classifiers:** Decision Trees (Information Gain / Gini index), Support Vector Machines (SVM finds the maximum-margin hyperplane; uses kernel trick for non-linear mappings), and K-Nearest Neighbors (KNN is an instance-based lazy

learner sensitive to feature scaling).

• **Unsupervised Clustering:** K-Means partitions data into *k* clusters by iteratively updating centroids to minimize within-cluster distance (sensitive to initial seed selection and outliers).

• **Ensemble Learning:** *Bagging (Bootstrap Aggregating)* trains parallel models on bootstrap samples to reduce variance (e.g., Random Forest). *Boosting* trains models sequentially where subsequent learners correct prior errors to reduce bias (e.g., AdaBoost, GBDT, XGBoost).

3. Model Evaluation, Metrics & Overfitting

• **Confusion Matrix:** Precision = TP / (TP + FP); Recall = TP / (TP + FN); F1-Score = 2 * (P * R) / (P + R). ROC curve plots True Positive Rate vs False Positive Rate (AUC measures ranking quality).

• **Bias-Variance Trade-off:** High variance (Overfitting) = memorizing training noise; solved by L1/L2 regularization, dropout, pruning, or bagging. High bias (Underfitting) = model too simple; solved by increasing model capacity or feature engineering.

KEY TAKEAWAY FOR EXAM

"Remember: Bagging (Random Forest) reduces variance by training parallel models on bootstrap samples; Boosting (AdaBoost/GBDT) reduces bias by training models sequentially!"

LECTURE 3: DEEP LEARNING: PERCEPTRONS, ACTIVATIONS & BACKPROPAGATION

Date: **July 28, 2026** • Official Module: **Chapter 3: Deep Learning**

1. Frank Rosenblatt's Perceptron (1957) & The XOR Dilemma

A perceptron computes a weighted sum of inputs and fires (+1) if the sum exceeds a threshold Theta, otherwise remaining off (-1 or 0):

Output = 1 if (W1*X1 + W2*X2 >= Theta) else 0

• **AND Gate Implementation:** Requires both inputs to be 1. The instructor demonstrated setting weights *W1 = 0.5, W2 = 0.5* and threshold *Theta = 0.7*. (0+0=0 < 0.7; 0.5+0=0.5 < 0.7; 0.5+0.5=1.0 >= 0.7 -> ON).

• **OR Gate Implementation:** Fires if either input is 1. Weights *W1 = 0.5, W2 = 0.5* with threshold *Theta = 0.3*. (0.5 >= 0.3 -> ON).

• **NAND Gate Implementation:** Inverted AND gate. Uses negative weights *W1 = -0.5, W2 = -0.5* and threshold *Theta = -0.7*.

• **The Historical XOR Dilemma:** Single-layer perceptrons can ONLY create a linear decision boundary (a straight line or hyperplane). Because XOR (0,0->0; 0,1->1; 1,0->1; 1,1->0) is **linearly non-separable**, a single-layer perceptron strictly fails! Solving XOR requires a **Multi-Layer Perceptron (MLP)** with hidden layers and non-linear activations.

2. Activation Functions & Their Trade-offs

Without non-linear activation functions, stacking 1,000 dense layers simply collapses mathematically into a single linear matrix multiplication. Activations introduce non-linearity:

• **Sigmoid:** *sigma(x) = 1 / (1 + e^(-x))*. Maps inputs to (0, 1). Maximum derivative is exactly **0.25** at x = 0. In deep networks (>5 layers), multiplying numbers <= 0.25 across layers causes the gradient to vanish to near zero.

• **Tanh (Hyperbolic Tangent):** Maps inputs to (-1, 1). Zero-centered, which aids gradient descent convergence, but still suffers from gradient saturation at extreme values.

• **ReLU (Rectified Linear Unit):** *f(x) = max(0, x)*. Constant gradient of 1 for x > 0 (completely avoids vanishing gradient). Drawback: 'Dying ReLU' phenomenon when weights become negative and neurons permanently output zero.

3. Backpropagation & The Chain Rule

The instructor detailed the two-phase training process:
1. **Forward Propagation:** Input signals pass through weighted layers, activations fire, and output predictions are compared against ground-truth labels using a Loss Function (MSE for regression, Cross-Entropy for classification).
2. **Backward Propagation (BPTT / Backprop):** The error gradient flows backwards from output to input using the calculus **Chain Rule**: *dL/dw = (dL/dy) * (dy/dz) * (dz/dw)*.
• **FNN Structure (TM pp. 210–213):** Transmits signals unidirectionally with **no feedback**; represented as a **Directed Acyclic Graph (DAG)**; *b* is the activation **threshold** (adding hidden layers builds hierarchical capability vs only adding nodes to one layer).
• **Gradient Stability (TM p. 235):** Vanishing gradients (Sigmoid max derivative = **0.25**) are mitigated via **ReLU** (derivative 1 for x>0) & **LSTM**. Exploding gradients are mitigated via **Gradient Clipping** AND **L1/L2 Weight Regularization**.

EXAM FORMULA & TRAP
"Single-layer perceptrons CANNOT solve XOR (requires MLP)! The maximum derivative of Sigmoid is 0.25 (not 1.0!). Batch Normalization standardizes intermediate activations across mini-batches to mitigate internal covariate shift!"

LECTURE 4: COMPUTER VISION, CNNS & RECURRENT NEURAL NETWORKS

Date: **July 30, 2026** • Official Module: **Chapter 3: Deep Learning**

1. Why Fully Connected Networks Fail on Images

Passing a 1000x1000 RGB image directly into a dense layer requires 3 million input nodes, resulting in billions of weights in a single layer (computational explosion and catastrophic overfitting). Dense layers also destroy 2D spatial pixel relationships.

2. Convolutional Neural Network (CNN) Trio

A standard CNN architecture alternates three core layer types:

- **Convolutional Layer:** Applies small filter kernels (e.g., 3x3, 5x5) across the image. Core properties: *Local Receptive Fields* and *Weight / Parameter Sharing* (the same filter weights scan the entire image, drastically reducing parameter count).
- **Pooling Layer:** Downsamples spatial dimensions (height and width). Max Pooling extracts sharp textures/edges; Average Pooling smooths background. **Crucial: Pooling layers contain ZERO learnable parameters!**
- **Fully Connected Layer:** Flattens high-level 2D feature maps into a 1D vector for final class score generation.

3. Sequential Data & Recurrent Neural Networks (RNN)

For temporal or sequential data (speech, text, time series), the network must maintain memory of past context. Standard RNNs pass a hidden state *h_t* through time. However, unfolding RNNs over hundreds of time steps causes exponential gradient decay (vanishing gradients), making vanilla RNNs incapable of capturing long-range dependencies.

INSTRUCTOR WARNING
"Be careful in the exam: Pooling layers do NOT have learnable weights! They perform fixed mathematical operations (max or average). Output size formula: Output = (Input - Kernel + 2*Padding) / Stride + 1."

LECTURE 5: SEQ2SEQ, LSTM, ATTENTION & TRANSFORMERS

Date: **August 2, 2026** • Official Module: **Chapter 3: Deep Learning & Foundation Models**

1. Gated Sequential Architectures: LSTM vs GRU

To solve the RNN vanishing gradient dilemma, specialized gating mechanisms regulate information flow:

- **LSTM (Long Short-Term Memory):** Utilizes a separate Cell State *C_t* and **Three Gates**: *Forget Gate* (discards irrelevant history), *Input Gate* (writes new information), and *Output Gate* (decides output hidden state).
- **GRU (Gated Recurrent Unit):** Simplifies LSTM by merging cell and hidden states. Utilizes only **Two Gates**: *Reset Gate* and *Update Gate* (faster computation, fewer parameters).

2. The Attention Mechanism & Transformer Revolution

In traditional Seq2Seq Encoder-Decoder networks, encoding an entire sentence into a single fixed-length context vector creates an information bottleneck. **Attention** allows the decoder to dynamically attend to relevant input tokens at every generation step.
• **Query, Key, Value (Q, K, V):** The query vector matches against key vectors to compute compatibility weights, which scale the value vectors.
• **Scaled Dot-Product Formula:** *Attention(Q, K, V) = Softmax((Q * K^T) / sqrt(d_k)) * V*.
• **Transformer Architecture:** Discards recurrence entirely! Enables massive parallel training on GPUs/NPUs. Relies on Multi-Head Attention, Positional Encodings (injecting word order), and Layer Normalization.

CORE EXAM FACT
"LSTM has 3 gates; GRU has 2 gates. Transformers do not use recurrent loops, which allows full parallelization during training!"

LECTURE 6: AI FRAMEWORKS: MINDSPORE, PYTORCH & COMPUTATIONAL GRAPHS

Date: **August 4, 2026** • Official Module: **Chapter 4: AI Development Framework**

1. The Role of Deep Learning Frameworks

AI frameworks liberate developers from writing low-level CUDA/CANN GPU/NPU kernels from scratch. They provide automatic differentiation, operator libraries, and memory management.

- **Static Graphs (Define-and-Run):** Used in TensorFlow 1.x and MindSpore Graph Mode. The computation graph is compiled and optimized before execution. Highly efficient for deployment, but rigid and difficult to debug.
- **Dynamic Graphs (Define-by-Run):** Used in PyTorch and MindSpore PyNative Mode. Computations execute eagerly line-by-line as Python code runs. Superior developer experience and effortless debugging.

2. PyTorch Mechanics & ONNX Interoperability

- **PyTorch Workflow:** Neural networks inherit from *torch.nn.Module*. Layers initialized in *__init__()*, forward flow defined in *forward()*. Must call *optimizer.zero_grad()* before *loss.backward()* to clear accumulated gradients.
- **ONNX (Open Neural Network Exchange):** Universal open format allowing models trained in PyTorch or TensorFlow to be exported and executed on Ascend, mobile, or cloud runtimes.
- **Operator Fusion:** Combines consecutive operations (e.g., Conv + ReLU + Add) into one kernel to reduce memory overhead.
- **Official Model File Formats (TM p. 329): .ckpt** (Protocol Buffers; saves parameters by default for resuming interrupted training/fine-tuning), **.pt / .pth** (PyTorch default format for complete models/weights), **.onnx** (cross-framework migration & TensorRT inference), and **.bin** (common binary requiring conversion from PyTorch).
- **Official PyTorch LeNet Workflow & llama.cpp (TM pp. 355–359, 374):** LeNet flattens conv outputs via *x.view(-1, 16*5*5)* into *nn.Linear(16*5*5, 120)* and trains via *zero_grad()* → *loss.backward()* → *step()*; **llama.cpp** executes C/C++ LLM inference locally or on cloud **without requiring an AI framework**.

EXAM CODE TRAP

"In PyTorch, why do we call zero_grad()? Because PyTorch accumulates gradients by default! Also, nn.CrossEntropyLoss expects raw unnormalized logits (do NOT apply Softmax beforehand!)."

LECTURE 7: HUAWEI CANN, ATLAS PRODUCT LINE & PRODUCTION TOOLS

Date: **August 7, 2026** • Official Module: **Chapter 4: AI Frameworks & Platforms**

1. Production Frameworks & Ecosystem Tools

The instructor urged students to memorize the specialized TensorFlow and Huawei deployment variants:

- **TensorFlow.js:** Client-side inference and training in web browsers via JavaScript.
- **TensorFlow Lite (TFLite):** Lightweight runtime optimized for mobile, Android, and IoT edge devices.
- **TFX (TensorFlow Extended):** End-to-end industrial platform for pipeline management from data ingestion to model serving.
- **TFRecord:** Google's binary protocol-buffer storage format for high-throughput I/O pipelines on massive datasets.

2. Huawei CANN & Atlas Hardware Family

- **CANN Layers:** AscendCL (programming API for C++/Python), Graph Engine (GE - graph compilation and scheduling), and TBE (Tensor Boost Engine - custom operator development).
- **ATC (Ascend Tensor Compiler):** Converts third-party models (ONNX, Caffe, MindSpore) into offline **.om** format for Ascend execution.
- **Atlas Portfolio:** Atlas 200 (accelerator module), Atlas 300 (PCIe acceleration card), Atlas 500 (intelligent edge station), Atlas 800 (training/inference server), Atlas 900 (AI supercomputing cluster).

DIRECT INSTRUCTOR QUOTE FOR THE EXAM

"What's the difference between platform and frameworks? What are the production tools? Try to memorize as much as you can from those things! Also remember matrix transpose: (A * B)^T = B^T * A^T, not A^T * B^T!"

LECTURE 8: LARGE MODEL DISTRIBUTED TRAINING & 3D PARALLELISM

Date: **August 13, 2026** • Official Module: **Chapter 5: Business Process & Foundation Models**

1. Distributed Parallelism Strategies for Massive Models

Modern LLMs (billions of parameters) cannot fit into the VRAM of a single GPU or Ascend chip. Distributed training partitions the workload:

- **Data Parallelism:** Model weights are replicated on every device. The training mini-batch is partitioned. Each device computes gradients independently, followed by an *AllReduce* operation to average gradients across all devices.

• **Tensor Parallelism (Model Parallelism):** Large weight matrices (e.g., attention projection matrices) are split across multiple NPUs along row-wise or column-wise dimensions.

• **Pipeline Parallelism:** Deep network layers are partitioned sequentially across devices (Device 1 has layers 1-8, Device 2 has 9-16). Execution is pipelined with micro-batches.

• **3D Parallelism:** The ultimate combination of Data + Tensor + Pipeline parallelism, utilized in Huawei's Atlas 900 cluster for massive foundation models.

2. Parameter-Efficient Fine-Tuning (PEFT)

Instead of full fine-tuning (modifying all 100B weights), PEFT freezes base weights to preserve general pre-trained knowledge:
• **LoRA (Low-Rank Adaptation):** Decomposes weight update matrices into low-rank matrices: $W = W_0 + B * A$.
• **Adapter Tuning:** Injects small trainable adapter layers inside Transformer feed-forward and attention blocks.
• **Prefix Tuning / Prompt Tuning:** Prepends learnable virtual continuous token vectors to key/value matrices.

EXAM ESSENTIALS
"Know the difference between Data Parallelism (batch split, model replicated) and Tensor Parallelism (weight matrices split across chips). PEFT freezes the base model to prevent catastrophic forgetting!"

LECTURE 9: MODEL ALIGNMENT (RLHF), PROMPTING & SAFETY

Date: **August 16, 2026** • Official Module: **Chapter 5: AI Business Process & Prompt Engineering**

1. Model Alignment & The 3H Principle

Raw pre-trained foundation models are simple text predictors that often output toxic, biased, or hallucinated responses. Alignment aligns model outputs with human social values following the **3H Principle: Helpful, Honest, Harmless**.

2. The RLHF Pipeline (Reinforcement Learning from Human Feedback)

• **Step 1 - Pre-training:** Self-supervised learning on web-scale text corpora to acquire general language and world knowledge.

• **Step 2 - Supervised Fine-Tuning (SFT):** Training on high-quality demonstration question-answer pairs curated by human experts.

• **Step 3 - Reward Model (RM) Training:** Humans rank multiple candidate responses to a prompt from best to worst. The Reward Model is trained to score answers mirroring human preferences.

• **Step 4 - Reinforcement Learning (PPO):** The language model's generation policy is fine-tuned using PPO to maximize rewards from the Reward Model.

3. Prompt Engineering Techniques & Vulnerabilities

• **Chain-of-Thought (CoT):** Asking models to 'think step by step' or providing demonstration exemplars with intermediate reasoning paths to solve multi-step math and logic problems.

• **ReAct Framework:** Combines Reasoning traces and Action execution with external tools (calculators, web search, APIs).

• **Security Threats:** *Prompt Injection* (tricking the model to ignore safety rules via malicious user input), *Jailbreaking*, and *Data Contamination* (test benchmark questions accidentally leaked into pre-training data).

EXAM TAKEAWAY
"In RLHF, what is the Reward Model trained on? Pairwise human preference rankings! What does CoT prompting do? Decomposes complex reasoning into explicit intermediate steps."

LECTURE 10: INDUSTRY APPLICATIONS, AI ETHICS & FINAL EXAM STRATEGY

Date: **August 18, 2026** • Official Module: **Chapter 6: Cutting-Edge AI Applications**

1. Huawei Smart Ecosystem: Celia & Smart Cockpit

• **Huawei Celia (Xiaoyi):** Personal AI assistant integrating Automatic Speech Recognition (ASR), Natural Language Understanding (NLU), Dialogue State Tracking (DST), and Text-to-Speech (TTS).

• **Smart Vehicles & Smart Home:** HarmonyOS Intelligent Cockpit, acoustic detection cameras, and Driver Monitoring Systems (DMS) detecting driver drowsiness via computer vision.

• **Autonomous Driving Solutions:** Huawei Qiankun full-stack intelligent driving solution, multi-sensor fusion (LiDAR, millimeter-wave radar, HD cameras), and SLAM (Simultaneous Localization and Mapping).

• **AI for Science (Pangu-Weather):** Huawei's 3D neural network for global meteorological forecasting, completing 24-hour global weather predictions in seconds with accuracy rivaling supercomputers.

2. AI Ethics & Governance Principles

Key ethical pillars emphasized in the Huawei syllabus: Fairness and non-discrimination (mitigating dataset bias), Privacy and data security, Transparency and explainability (XAI), and Human oversight/accountability.

3. Official Huawei Exam Strategy & Passing Guide

• **Exam Format:** 60 questions total (True/False, Single-Answer, Multiple-Answer).
• **Duration & Score:** 90 minutes. Total score: 1000 points. **Passing score: 600 points (60%)**.
• **Time Management:** Spend ~1 minute per question, leaving 30 minutes to review flagged questions.
• **Multiple-Choice Warning:** Huawei multiple-choice questions have NO partial credit! You must select all correct options.

FINAL INSTRUCTOR ADVICE

"Focus on understanding the concepts rather than blind memorization. Review the Master Question Bank thoroughly, pay close attention to Ascend chip specs, MindSpore methods, and parallelism types, and you will comfortably pass with 800+ points!"

Master Quick-Review Cheat Sheet & Exam Reference Guide

High-yield formulas, hardware specifications, and trap avoidance rules emphasized across all 10 lectures:

Concept / Term	Core Role & Characteristics	Exam Key / Trap to Avoid
Ascend 310	Ultra-low power AI SoC (8W / 16 TOPS)	For **Edge Inference** (not cloud training)
Ascend 910	High throughput cloud AI processor (310W / 256 TFLOPS FP16, 512 TOPS INT8)	For **Cloud Training** (not edge IoT)
Atlas 500	Intelligent Edge Station with wide temperature range (-40°C to 70°C)	Edge computing appliance (not supercomputer)
Atlas 900	Massive AI training cluster combining thousands of Ascend 910s	World's fastest AI training cluster for large foundation models
CANN / TBE	Tensor Boost Engine inside CANN software stack	For **Custom Operator development** on DaVinci cores
MindSpore Cell	Base class for building neural network models	Override **construct()** for forward computation
Sigmoid Derivative	sigma'(x) = sigma(x) * (1 - sigma(x))	Maximum derivative is **0.25** at x = 0 (causes vanishing grad)
CNN Pooling	Max / Average Pooling downsampling	Contains **ZERO learnable parameters**
Matrix Transpose	Transpose of matrix product	**(A * B)^T = B^T * A^T** (reverses order)
Data Parallelism	Splits batch across NPUs; replicates model	Requires gradient synchronization via **AllReduce**
Tensor Parallelism	Splits individual weight matrices row/col-wise	Used when a single layer cannot fit in GPU/NPU memory
RLHF 3H Criteria	Helpful, Honest, Harmless alignment	Reward Model is trained on **human pairwise rankings**
Pangu-Weather	Huawei 3D deep neural network weather model	Outperforms traditional numerical PDEs in speed by 10,000x
FNN & DAG	Unidirectional multi-layer network; zero feedback	Represented as **DAG**; bias *b* = activation **threshold**
Exploding Grad	Exponential gradient growth during backprop	Solved by **Gradient Clipping** and **L1/L2 Regularization**
Model Files	.ckpt (ProtoBuf) | .pt/.pth (PyTorch) | .onnx | .bin	**.ckpt** resumes training; **.onnx** migrates frameworks/TensorRT
llama.cpp	Standalone C/C++ LLM runtime engine	Runs LLM inference **without needing an AI framework**

Essential Mathematical Formulas & Operating Rules

• **Perceptron Activation:** y = 1 if (sum(w_i * x_i) >= Theta) else 0 | **AND:** W1=0.5, W2=0.5, Theta=0.7 | **OR:** W1=0.5, W2=0.5, Theta=0.3
• **CNN Output Dimension:** Output_Size = floor((Input_Size - Kernel_Size + 2 * Padding) / Stride) + 1
• **Scaled Dot-Product Attention:** Attention(Q, K, V) = Softmax((Q * K^T) / sqrt(d_k)) * V
• **Classification Metrics:** Precision = TP / (TP + FP) | Recall = TP / (TP + FN) | F1 = 2 * (Precision * Recall) / (Precision + Recall)
• **Gradient Descent Update:** w_(t+1) = w_t - alpha * grad(L(w_t)) | Momentum incorporates velocity: v_(t+1) = beta * v_t + (1 - beta) * grad(L)

FINAL EXAM STRATEGY — 1000 POINTS ROADMAP

1. **Passing Mark:** 600 / 1000 (60%). 60 total questions in 90 minutes (~1.5 min/question).
2. **Multiple-Choice Discipline:** No partial credit is awarded. Do not guess blindly on multi-choice.
3. **Review Strategy:** Flag unsure questions and finish the first pass in 55 minutes, then spend 30 minutes verifying flagged items.
4. **Huawei Core Syllabus:** Review the 900-question Master Bank, verify Ascend/CANN terminology, and trust your preparation!