Akoizo Original Practice - Form 5

Division B | Boomilever | 50-minute written practice

Original Akoizo curriculum practice. This is not a historical tournament paper. Written build, CAD, lab and communication exercises supplement real practical preparation.

Name: _____ Date: _____

1. (2 points) Which joint is usually strongest for the same glue?

Unit: Joints, adhesives, and the bolt hook.
Worked-case data: A chord joint must carry 300 N. Your glue holds about 2 N per mm^2 of long-grain overlap. How much bonded area do you need, with a safety factor of 1.5?
Separate investigation observations:
Failure 1: Hook crushed into an oval around the bolt at 10 kg.
Failure 2: Strut-to-chord butt joint split at 13 kg.
Fix trial: Basswood bearing pad (+0.15 g) and two gussets (+0.10 g): held 15 kg.

A. A long-grain overlap with gussets

B. An end-grain butt joint

C. A joint wrapped in tape

D. A joint where glue coats the whole member

Answer: _____

2. (2 points) In the triangle model, which change lowers the strut compression the most?

A. Moving the wall contact deeper (within the allowed line)

B. Making the chord thicker

C. Adding glue to the bolt hook

D. Moving the chain from 41 to 44 cm

Answer: _____

3. (4 points) Why does strength beyond 15 kg add nothing to the score?

Answer: _____
_____
_____

4. (2 points) When may a team adjust its structure?

Unit: The test apparatus, setup, and loading procedure.
Worked-case data: Plan the six-minute window for a team that has practiced setup.
Separate investigation observations:
Run 1: Setup took 5 min; fast pour; failed at 9 kg with violent swing.
Run 2: Setup took 2 min; slow pour with stick tips; held 15 kg.
Inspection: Both structures were identical builds from the same wood batch.

A. Only after the first kilogram

B. After check-in, before the six minutes

C. Before sand loading begins, within the six minutes

D. At any time

Answer: _____

5. (4 points) Why sort balsa by density before building?

Unit: Wood selection, density, and buckling.
Worked-case data: A strut buckles at 120 N with an unbraced length of 30 cm. A brace is added at its midpoint. Estimate the new buckling load.
Separate investigation observations:
Stick A: 0.11 g/cm^3 - failed as a strut at 6 kg.
Stick B: 0.18 g/cm^3, same size - held 11 kg as a strut.
Stick C: 0.11 g/cm^3 with a midpoint brace - held 15 kg.

Answer: _____
_____
_____

6. (4 points) What two horizontal forces form the couple that balances the load moment?

Unit: Statics of a cantilever: moments, tension, and compression.
Worked-case data: A 15 kg load hangs 42 cm from the wall. The strut meets the wall 20 cm below the bolt. Estimate the horizontal chord force.
Separate investigation observations:
Test A: Strut 15 cm deep, 3 mm square: bowed sideways at 9 kg.
Test B: Same strut with one mid-length brace: held 15 kg.
Test C: Chord 1.5 x 3 mm: never failed in any test.
Test D: Chord-to-bolt joint glued with a single drop: pulled off at 12 kg.

Answer: _____
_____
_____

7. (4 points) Name two items every build-log entry should record and say why.

Unit: Testing, failure analysis, and iteration.
Worked-case data: Your log shows: 9.2 g held 15 kg; 8.4 g held 15 kg; 7.9 g failed at 13.1 kg (strut buckled). What should the competition build be?
Separate investigation observations:
Builds 1-3: 8.1 g, 8.3 g, 8.2 g: all held 15 kg.
Builds 4-5: 7.4 g, 7.5 g: failed at 12 kg and 14 kg, strut buckled.
Build 6: 7.6 g with a stiffer, denser strut: held 15 kg.

Answer: _____
_____
_____

8. (4 points) How could you find out how much of your structure's mass is glue?

Answer: _____
_____
_____

9. (2 points) What explains the change in bracing between the designs?

Supplied synthetic observations:
Design X: Reach 45 cm, contact 19 cm: strut needed 2 braces.
Design Y: Reach 41 cm, contact 19 cm: strut needed 1 brace.
Design Z: Reach 41 cm, contact 14 cm: strut needed 3 braces.

A. Longer reach and shallower contact both raise strut force

B. Bracing depends only on wood type

C. Shallower contact always lowers force

Answer: _____

10. (2 points) Define "Tier 1" in the context of Boomilever.

Answer: _____
_____
_____

11. (6 points) Solve this case and explain your reasoning: Plan the six-minute window for a team that has practiced setup.

Answer: _____
_____
_____

12. (2 points) What is the best conclusion from these strut tests?

Supplied synthetic observations:
Stick A: 0.11 g/cm^3 - failed as a strut at 6 kg.
Stick B: 0.18 g/cm^3, same size - held 11 kg as a strut.
Stick C: 0.11 g/cm^3 with a midpoint brace - held 15 kg.

A. Both density and unbraced length control buckling; bracing helped most

B. Only density matters

C. Light wood can never be a strut

Answer: _____

13. (2 points) Define “Tension member” in the context of Boomilever.

Answer: _____
_____
_____

14. (2 points) Define “Failure mode” in the context of Boomilever.

Answer: _____
_____
_____

15. (2 points) Define “Gusset” in the context of Boomilever.

Answer: _____
_____
_____

16. (2 points) Define “Second moment of area (I)” in the context of Boomilever.

Answer: _____
_____
_____

17. (2 points) Define “Margin” in the context of Boomilever.

Answer: _____
_____
_____

18. (2 points) Define “Euler load” in the context of Boomilever.

Answer: _____
_____
_____