```html
<!DOCTYPE html>
<html>
<body>
<form method="post" action="process.jsp">
First name:<br>
<input type="text" name="first_name">
<br>
Last name:<br>
<input type="text" name="last_name">
<br>
City name:<br>
<input type="text" name="city_name">
<br>
Email Id:<br>
<input type="email" name="email">
<br><br>
<input type="submit" value="submit">
</form>
</body>
</html>
```

process.jsp

```jsp
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<%@page import="java.sql.*,java.util.*"%>

<%
String first_name=request.getParameter("first_name");
String last_name=request.getParameter("last_name");
String city_name=request.getParameter("city_name");
String email=request.getParameter("email");

try
{
Class.forName("com.mysql.jdbc.Driver");
Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/test", "root", "");
Statement st=conn.createStatement();

int i=st.executeUpdate("insert into
users(first_name,last_name,city_name,email)values('"+first_name+"','"+last_name+"','"+city_name+"','"+email+"')");
out.println("Data is successfully inserted!");
}
catch(Exception e)
{
System.out.print(e);
```

```
      e.printStackTrace();
   }
%>
```

Here is the code for newuser.jsp

```html
<html>
<head>
<title>new user</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
</head>

<body bgcolor="#FFFFFF" text="#000000">



<h1>Please enter your details</h1>


<form action="validate_new_user.jsp" method="post">
   <table cellspacing="5" cellpadding="5" border="1">
     <tr>
        <td align="right">Name:</td>
        <td><input type="text" name="NewName"></td>
     </tr>
     <tr>
        <td align="right">Email Address:</td>
        <td><input type="text" name="EmailAddress"></td>
     </tr>
     <tr>
        <td align="right">Nationality:</td>
        <td><input type="text" name="Nationality"></td>
     </tr>
     <tr>
        <td align="right">User Name:</td>
```

```html
      <td><input type="text" name="UserName"></td>
    </tr>
    <tr>
      <td align="right">Password:</td>
      <td><input type="password" name="Password"></td>
    </tr>

  </table>
  <input type="submit" value="Submit">
</form>


</body>
</html>
```

Here is the code for validate_new_user.jsp

```html
<html>
<head>
<title>Validate New User</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
</head>

<body bgcolor="#FFFFFF" text="#000000">
<%@ page import="javax.servlet.*" %>
<%@ page import="javax.servlet.http.*" %>
<%@ page import="java.sql.*" %>

<%
    Connection con = null;
```

```
        String names = request.getParameter("NewName");
        String eaddress = request.getParameter("EmailAddress");
        String nation = request.getParameter("Nationality");
        String userid = request.getParameter("UserName");
        String pw = request.getParameter("Password");


        String queryText = "insert into user_details (\"fullName\",
\"emailAddress\",

\"nationality\", \"username\", \"password\")

values('"+names+"','"+eaddress+"','"+nation+"','"+
userid+"','"+pw+"')";

        try {
            Class.forName("com.mysql.jdbc.Driver").newInstance
();
            con =

DriverManager.getConnection("jdbc:mysql://localhost:3306/proj
ect","root","password");

            Statement stat = con.createStatement();

            ResultSet rst = stat.executeQuery(queryText);

            rst.close();
            stat.close();
            con.close();
        } catch (Exception e) { }

        response.sendRedirect("success.htm");
%>
```

```
</body>
</html>
```