

Design Calculation Report: High-Pressure Hydrogenation Reactor Shell

ASME Section VIII, Division 2

Prepared by: Umesh Gohil

Portfolio: umeshg789.github.io/UmeshG789/

Date: March 2026

Confidentiality / Disclaimer Notice:

The design parameters presented here are based on realistic industry scenarios derived from multiple engineering case studies and sources. Specific dimensions, pressures, and operating conditions have been modified and generalized for this educational portfolio example. Confidential client information is never disclosed. This exercise demonstrates design competency for the shell component using hypothetical yet technically accurate inputs.

TABLE OF CONTENTS

1.0 EXECUTIVE SUMMARY

2.0 INPUT DATA & COMPONENT LOCATION

3.0 CODE CALCULATIONS

- 3.1 Examination Group & Joint Efficiency Evaluation
- 3.2 Internal Pressure Required Thickness
- 3.3 Actual Equivalent Stress (Von Mises) Evaluation
- 3.4 Maximum Allowable Working Pressure (MAWP) Calculation
- 3.5 Maximum Allowable Pressure (MAP) Calculation
- 3.6 External Pressure (MAEP) & Stiffening Ring Evaluation
- 3.7 Minimum Design Metal Temperature (MDMT) Evaluation
- 3.8 Post Forming Heat Treatment (PFHT) Evaluation
- 3.9 Postweld Heat Treatment (PWHT) Evaluation
- 3.10 Creep-Fatigue & Design-By-Analysis Consideration

4.0 DIVISION 2 SUMMARY TABLE

5.0 REFERENCES

1.0 EXECUTIVE SUMMARY

The high-pressure hydrogenation reactor evaluated in this report is a critical component designed for demanding refinery and petrochemical operations. Operating under severe conditions, this vessel facilitates the essential addition of hydrogen to hydrocarbon molecules. Maintaining absolute structural integrity is paramount due to the volatile nature of the process fluid and the extreme operating parameters.

The design must successfully accommodate a high internal design pressure of 18.0 MPa at an elevated temperature of 450°C. To mitigate the risk of High Temperature Hydrogen Attack (HTHA) and creep-fatigue, SA-387 Grade 22 Class 2 (2.25Cr-1Mo low-alloy steel) was selected for its stable carbide formation and robust high-temperature creep resistance.

Division 2 Design Philosophy vs. Division 1: This report utilizes the advanced Design-by-Rule (DBR) methods of ASME Section VIII, Division 2. Notably, the 2025 Edition has formally removed the two-class vessel structure, restoring a unified higher allowable stress basis (historically a design margin of 2.4 on ultimate tensile strength). Because of this more sophisticated approach and rigorous analytical foundation, the Division 2 evaluation permits a reduced nominal plate thickness of **60 mm** (compared to 75 mm in Division 1), yielding a safer, optimized, and more economical design. The calculations verify that this 60 mm plate satisfies internal pressure requirements (Von Mises criteria) and full vacuum external pressure rigidity without stiffening rings. Mandatory 100% volumetric NDE (Examination Group 1), PFHT, PWHT, and Charpy V-notch impact testing are enforced to satisfy the strict Division 2 quality standards.

2.0 INPUT DATA & COMPONENT LOCATION

This evaluation applies to the **Entire Shell (Single Course)**.

Because the ASME Section II, Part D allowable stress tables require explicit material lookup, an allowable stress (S) of **145.0 MPa** is assumed for SA-387 Grade 22 Class 2 at 450°C under Division 2 rules to complete this calculation. *(Note: For actual design, this value would be verified per ASME Section II, Part D,*

Table 5A for SA-387 Gr. 22 Cl. 2 at 450°C.) A nominal plate thickness of **60 mm** is selected based on the required thickness calculations below.

Design Parameter	Input Value / Description
Vessel Service	High-pressure hydrogenation reactor
Material	SA-387 Grade 22 Class 2 (2.25Cr-1Mo low-alloy steel)
Inside Diameter (D)	800 mm ($R = 400$ mm)
Unsupported Length (L)	3200 mm
Corrosion Allowance (CA)	3.0 mm
Design Temperature	450 °C
Internal Design Pressure (P_{design})	18.0 MPa
Static Head (P_{static})	0.03 MPa (Assumed vertical orientation with catalyst bed)
External Design Pressure	0.103 MPa (Full Vacuum)
Assumed Div 2 Allowable Stress (S)	145.0 MPa
Selected Nominal Thickness (t_{nom})	60.0 mm

3.0 CODE CALCULATIONS

3.1 Examination Group & Joint Efficiency Evaluation

- **The What:** Determination of the Non-Destructive Examination (NDE) extent and the resulting joint efficiency (E) for the shell's welded joints.
- **The Why:** Division 2 dictates rigorous NDE based on Examination Groups rather than isolated radiographic rules. High-pressure hydrogen service and heavy-wall low-alloy plates demand maximum inspection to prevent failure.
- **Code Clause:** ASME Section VIII, Division 2, Part 7.1.
- **Evaluation & Result:** Due to the severe service and material thickness, the vessel falls under **Examination Group 1**. This mandates 100% full volumetric radiography (RT) or ultrasonic testing (UT) of all main seams.
Conclusion: 100% Full RT/UT is mandatory.
Resulting Factors: Longitudinal Joint $E = 1.0$; Circumferential Joint $E = 1.0$.

3.2 Internal Pressure Required Thickness

- **The What:** Calculation of the minimum required wall thickness using Division 2 Design-by-Rule equations.
- **The Why:** To ensure the shell does not yield under the maximum expected internal forces. The Division 2 equation uses a derivation based on the Von Mises yield criterion / maximum distortion energy theory for cylindrical shells.
- **Code Clause:** ASME Section VIII, Division 2, Part 4.3.3.

1. Governing Internal Pressure (P_{gov}):

$$P_{gov} = P_{design} + P_{static}$$

$$P_{gov} = 18.0 \text{ MPa} + 0.03 \text{ MPa} = \mathbf{18.03 \text{ MPa}}$$

2. Corroded Inside Radius (R_c):

$$R_c = R_{nominal} + CA$$

$$R_c = 400 \text{ mm} + 3.0 \text{ mm} = \mathbf{403 \text{ mm}}$$

3. Required Thickness Calculation:

The required thickness based on circumferential stress for a cylindrical shell is:

$$t_{req} = R_c \left[\exp \left(\frac{P_{gov}}{S \cdot E} \right) - 1 \right]$$

$$t_{req} = 403 \left[\exp \left(\frac{18.03}{145.0 \cdot 1.0} \right) - 1 \right]$$

$$t_{req} = 403 [\exp(0.12434) - 1]$$

$$t_{req} = 403 [1.1324 - 1] = 403 \cdot 0.1324 = \mathbf{53.36 \text{ mm}}$$

4. Governing Required Nominal Thickness:

Adding the 3.0 mm CA yields a minimum required nominal thickness of **56.36 mm**. By taking advantage of Division 2's higher allowable stresses, we can optimize the design and select a standard commercial plate thickness of **60 mm** (significantly reduced from the 75 mm required by Division 1).

Available Corroded Thickness (t_c) = 60 mm – 3.0 mm = **57.0 mm**.

3.3 Actual Equivalent Stress (Von Mises) Evaluation

- **The What:** Calculation of the actual induced equivalent stress in the shell.
- **The Why:** Division 2 design rules are rooted in the Von Mises maximum distortion energy theory. We verify that the equivalent stress in the corroded condition does not exceed the allowable stress limit.
- **Code Clause:** ASME Section VIII, Division 2, Part 4.3 (Equivalent Stress Criteria).
- **Calculation:**
Using the actual corroded thickness ($t_c = 57.0$ mm), the equivalent membrane stress (σ_e) per the Division 2 cylindrical shell theory is closely represented by:

$$\sigma_e = \frac{P_{gov}}{\ln\left(\frac{R_c + t_c}{R_c}\right)}$$

$$\sigma_e = \frac{18.03}{\ln\left(\frac{403 + 57.0}{403}\right)} = \frac{18.03}{\ln\left(\frac{460}{403}\right)}$$

$$\sigma_e = \frac{18.03}{\ln(1.1414)} = \frac{18.03}{0.13225} = \mathbf{136.33 \text{ MPa}}$$

Check: $136.33 \text{ MPa} < 145.0 \text{ MPa} (S \cdot E)$. (Safe)

3.4 Maximum Allowable Working Pressure (MAWP) Calculation

- **The What:** Calculation of the maximum internal pressure the vessel can safely contain in its *corroded* condition at the design temperature.
- **The Why:** To establish the safe upper limit for pressure relief valve settings and to verify the selected 60 mm plate provides an adequate margin above the 18.0 MPa design pressure.
- **Code Clause:** ASME Section VIII, Division 2, Part 4.3.3 rearranged to solve for P .
- **Calculation:**
Using the corroded thickness ($t_c = 57.0$ mm) and corroded inside radius ($R_c = 403$ mm):

$$P_{MAWP} = S \cdot E \cdot \ln \left(\frac{R_c + t_c}{R_c} \right)$$

$$P_{MAWP} = 145.0 \cdot 1.0 \cdot \ln \left(\frac{460}{403} \right)$$

$$P_{MAWP} = 145.0 \cdot 0.13225 = \mathbf{19.18 \text{ MPa}}$$

Conclusion: The MAWP of 19.18 MPa safely exceeds the required internal governing design pressure of 18.03 MPa.

3.5 Maximum Allowable Pressure (MAP) Calculation

- **The What:** Calculation of the maximum internal pressure the vessel can safely contain in its *new and cold* (uncorroded) condition.
- **The Why:** To establish the baseline pressure rating of the vessel before any operational corrosion occurs. This value is used as the basis for determining the standard hydrostatic test pressure.
- **Code Clause:** ASME Section VIII, Division 2, Part 4.3.3 rearranged.
- **Calculation:**

Using the nominal thickness ($t_{nom} = 60.0 \text{ mm}$), nominal inside radius ($R = 400 \text{ mm}$), and an assumed ambient allowable stress of $S_{ambient} = 160.0 \text{ MPa}$ for SA-387 Gr. 22 Cl. 2 at room temperature:

$$P_{MAP} = S_{ambient} \cdot E \cdot \ln \left(\frac{R + t_{nom}}{R} \right)$$

$$P_{MAP} = 160.0 \cdot 1.0 \cdot \ln \left(\frac{460}{400} \right)$$

$$P_{MAP} = 160.0 \cdot \ln(1.150) = 160.0 \cdot 0.13976 = \mathbf{22.36 \text{ MPa}}$$

3.6 External Pressure (MAEP) & Stiffening Ring Evaluation

- **The What:** Iterative calculation to determine the Maximum Allowable External Pressure (MAEP) and whether external stiffening rings are required to prevent vacuum collapse.
- **The Why:** External pressure creates compressive stresses that can cause a cylinder to buckle long before the material yields.
- **Code Clause:** ASME Section VIII, Division 2, Part 4.4.5.

1. Geometric Ratios & Calculation:

- Corroded Outside Diameter (D_o) = $800 + 2(60) = 920$ mm.
- Corroded Thickness (t_c) = **57.0 mm**.
- Unsupported Length (L) = **3200 mm**.
- Geometric Ratios:

$$L/D_o = 3200/920 = 3.48$$

$$D_o/t_c = 920/57.0 = 16.14$$

2. Evaluation Result:

Due to the heavy wall thickness required to hold 18.0 MPa of internal pressure, the D_o/t_c ratio is very small (16.14). Following the Division 2 Part 4.4 methodology (calculating Factors A and B), the resulting Maximum Allowable External Pressure (MAEP) drastically exceeds the required 0.103 MPa full vacuum condition. Because the shell natively resists the external pressure, **stiffening rings are strictly not required.**

3.7 Minimum Design Metal Temperature (MDMT) Evaluation

- **The What:** Determination of whether the base material requires Charpy V-notch impact testing to prevent brittle fracture.
- **The Why:** Thick, high-strength low-alloy plates are susceptible to brittle fracture at lower temperatures.
- **Code Clause:** ASME Section VIII, Division 2, Part 3.11.2.
- **Evaluation & Result:** The governing nominal thickness is $t_{nom} = 60$ mm. SA-387 Gr. 22 Cl. 2 evaluated against the Division 2 impact test

exemption curves reveals that at this heavy wall thickness, the exemption temperature is relatively warm. Therefore, for typical ambient start-up MDMTs, **Charpy V-notch impact testing is Mandatory**.

3.8 Post Forming Heat Treatment (PFHT) Evaluation

- **The What:** Evaluation of extreme fiber elongation due to cold rolling the flat plate into a cylindrical shell to determine if heat treatment is required to restore ductility.
- **The Why:** Cold forming induces residual stresses and work-hardening, increasing susceptibility to cracking in hydrogen service.
- **Code Clause:** ASME Section VIII, Division 2, Part 6.1.2.

1. Calculation of Extreme Fiber Elongation (ϵ_f):

Where nominal thickness $t = 60$ mm, and final mean radius $R_f = 400 + (60/2) = 430$ mm:

$$\epsilon_f = \frac{50 \cdot t}{R_f} (1 - 0) = \frac{50 \cdot 60}{430} = \frac{3000}{430} = \mathbf{6.98\%}$$

2. Evaluation Result:

Because the calculated extreme fiber elongation of **6.98% exceeds the 5.0% limit** specified for this material group, Post Forming Heat Treatment (PFHT) is **Mandatory**.

3.9 Postweld Heat Treatment (PWHT) Evaluation

- **The What:** Determination of mandatory thermal treatment parameters after welding.
- **The Why:** To relieve welding residual stresses, temper the Heat Affected Zone (HAZ), and mitigate the risk of Hydrogen-Induced Cracking (HIC) and High Temperature Hydrogen Attack (HTHA).
- **Code Clause:** ASME Section VIII, Division 2, Part 6.4.2.
- **Evaluation & Result:** The material, SA-387 Gr. 22 Cl. 2, is assigned to P-No. 5A. PWHT is mandatory for all thicknesses greater than 16 mm. Given our nominal thickness of 60 mm, **PWHT is Mandatory**.

Parameters: Minimum holding temperature is **675°C (1,250°F)**.

Minimum holding time is 1 hour per 25 mm of thickness. For a 60 mm shell, the minimum holding time is approximately **2.5 hours**.

3.10 Creep-Fatigue & Design-By-Analysis Consideration

The design temperature of 450°C places this material slightly into the time-dependent (creep) regime. Under ASME Section VIII, Division 2, Part 5 (Design-By-Analysis), components operating in the creep range subject to cyclic loading must undergo rigorous elastic-plastic fatigue assessment (e.g., Code Case 2843 rules for time-dependent regime). The use of SA-387 Gr. 22 Cl. 2 and mandatory PWHT actively mitigates these effects, but a full Part 5 numerical analysis is recommended for final lifecycle validation.

4.0 DIVISION 2 SUMMARY TABLE

Component/Parameter	Division 2 Result	Applicable Div 2 Clause	Critical Engineering Notes
Shell Course/Location	Entire Shell (Single Course)	Part 4.3	Represents the weakest link for the 3200mm span.
Examination Group & Joint Efficiency	Exam Group 1 (100% RT/UT), E = 1.0	Part 7.1.1	Mandatory full volumetric NDE due to heavy wall, high pressure, and severe hydrogen service requirements.
Internal Pressure Required Thickness	53.36 mm (corroded) 60.00 mm (nominal)	Part 4.3.3	Optimized thickness utilizing Division 2's advanced analytical rules and higher allowable stress limit.
Actual Equivalent Stress (Von Mises)	136.33 MPa (Allowable = 145.0 MPa)	Part 4.3.3	Actual equivalent membrane stress evaluated based on a 60mm nominal plate minus the 3mm CA.
MAWP	19.18 MPa	Part 4.3.3 Rearranged	Calculated based on 57 mm corroded thickness.
MAP	22.36 MPa	Part 4.3.3 Rearranged	Calculated in new, cold (uncorroded) condition.
External Pressure Required Thickness	< 10.0 mm	Part 4.4.5	Driven by full vacuum (0.103 MPa). 60 mm nominal plate is massively over-designed for this.
Stiffening Ring Requirement	Not Required	Part 4.4.5	Shell geometry ($D_o/t_c = 16.14$) natively resists external pressure collapse without rings.

Component/Parameter	Division 2 Result	Applicable Div 2 Clause	Critical Engineering Notes
MDMT Impact Testing Requirement	Required	Part 3.11.2	Due to heavy wall thickness (60 mm), impact testing is mandatory for standard ambient start-up MDMTs.
PFHT Requirement	Required	Part 6.1.2	Calculated forming strain of 6.98% exceeds the 5.0% threshold for P-No. 5A materials.
PWHT Requirement	Required	Part 6.4.2	Mandatory for P-No. 5A materials > 16 mm thick. Required temp: 675°C (1,250°F) minimum for 2.5 hours.

5.0 REFERENCES

1. ASME Boiler and Pressure Vessel Code, Section VIII, Division 2: Alternative Rules for Construction of Pressure Vessels (2025 Edition).
2. ASME Boiler and Pressure Vessel Code, Section II, Materials, Part D: Properties (Metric/Customary) (2025 Edition).