



## Docker Compose: Replicas

I create a project folder named 'replica' and a docker compose file named 'docker-compose.yaml'.




I edit the docker-compose.yaml file. I paste the given code.




This compose file will use Nginx:alpine image, it will broadcast in the port range of 8000-8001 and it will create 2 containers by using deploy and replicas command.

I use 'docker compose up' command in order to run the yaml file.



I check the running service on the browser.



I check the running containers by using 'docker ps' command.

```
muhammedumit@Umits-MacBook replica % docker ps
```

CONTAINER ID	IMAGE	COMMAND	NAMES	CREATED
506d83f5a83c	nginx:alpine	"/docker-entrypoint..."	replica-web-1	4 minutes ago
Up 37 seconds	0.0.0.0:8000->80/tcp			
37e09f7662fd	nginx:alpine	"/docker-entrypoint..."	replica-web-2	4 minutes ago
Up 37 seconds	0.0.0.0:8001->80/tcp			

I tear down the service by using 'docker compose down'.

```
● muhammedumit@Umits-MacBook replica % docker compose down
```

[+] Running	3/0	
✓ Container	replica-web-2	Removed 0.0s
✓ Container	replica-web-1	Removed 0.0s
✓ Network	replica_default	Removed 0.1s