

Name of the Student: _____

5 questions in 120 minutes

Question 1 (10%)

Give the C..R expression, or the open form as sequences of car's and cdr's, needed to get x in the following:

- (a) (a b x d)
- (b) (a (b (x d)))
- (c) (a (b (d) x))
- (d) (((a (b (x) d))))

Question 2 (20%)

Evaluate the following:

- (a) (cons NIL NIL)
- (b) (cons (1 2) NIL)
- (c) (cons ('A 'B) NIL)
- (d) (cons '(A B) '(C D))
- (e) (cons (list 'A 'B) (append '(C D) NIL))
- (f) (list (append (list nil) nil))
- (g) (append (list 'A 4) 'B)
- (h) (and (defun x (x) x) (x 1))
- (i) (* (or 2 4) (and (defvar k) (setf k 3)))
- (j) (if (if '(nil) nil 'knew) nil 'a)

Name of the Student: _____

Question 3 (20%)

Assume you have entered the following expressions one by one at the top-level.

```
(defvar k)
(defvar j)
(defvar i)
(setf k '(a b))
(setf j '(c))
(setf i (append k j))
```

Draw the resulting situation in terms of cons cell diagrams, indicating where i, j and k are pointing to.

Name of the Student: _____

Question 4 (30%)

Write recursive functions for the tasks below. Do not use built-in list functions like LAST and MEMBER. For the third task, you may use LENGTH, if you like.

- (a) FIRSTN: takes an integer n and a list, and returns the list of first n elements; it returns NIL if N is out of the range of the list.

- (b) NTHCDR: takes an integer n and a list, returns the nth cdr of the list.

- (c) TRIM-LAST: takes an integer n and a list, removes the last n elements.

Name of the Student: _____

Question 5 (20%)

Write a recursive function COUNT taking an object and a list and returns the number of times the object occurs in the second. You need to count embedded occurrences as well, no matter how deep it is. For instance (count 'x '(a (b (x)) c x) should return 2.

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.