PAKISTAN HAVY SPECIFICATION

FOR

WEBBING BLACK - PN PERSONNEL

FOREWORD

Development Directorate, Naval Headquarters, Karachi, to provide necessary guidance to the potential manufacturers/suppliers of the items mentioned herein. This specification is to be used for testing and deciding upon acceptance, or otherwise, of the items mentioned. Any alteration or addition in this specification can be suggested to ITD Directorate, however, it can not be implemented without approval of DITD. This specification supersedes all other specifications promulgated earlier in relation to the items mentioned herein.

SCOPE

2. This specification covers manufacturing/inspection requirements of Webbing black to be used by PN Personnel.

MATERIAL SPECIFICATIONS

3. BA	SE MATERIAL	
a.	Material	100% Cotton
b.	Coloui	Black Pantone Shade 19-4005/6/7 TCX
ţĊ.	Width	1.25' (32 mm + 1 mm)
d.	Thickness	0.1181" (3 mm)
e.	No of Thread per CM Warp	45/47 (5-Folds) (2 Folds)*
1.	No of Thread per CM Well	16/17 (5 Folds) (3 Folds) * PD 2400/10
g.	Count of Yarn	5% 10s (NAVAL HEADQUARTERS) NAVAL HEADQUARTERS)
h.	Breaking Strength (Grip) full width x 7" to 8"	365 + 20 KO TECHATCAL DEVELOPATION
i.	Weight per Meter	79 4 6 Grms

^{*}Amended vide GMPD letter PD/2400/10/GEN/9/960 dated 16 April 2010.

^{**}Amended vide CINS letter INS/C/5014/05/5230 dated 27 November 2012.

^{***} Amended vide letter TD/2400/GEN/12/\$5604 dated 14 December 2012.

j.	Weave	Plain
k.	Nature of Dye	Vat dye
1.	Washing test No.2(PS-1337/C-86)	GS 4/5
m.	Material and guage of tip at one end.	Brass 22 SWG
n.	Width of Brass tip	1.25" 32 mm + 1mm as fitted.
0.	Length of brass tip	(0.625°) 16mm as fitted
ρ.	Thickness of the brass tip	(0.1181") 3mm as fitled.
q.	Make shape, feel/ finish and shape	As per stock stample held by CINS.

INSPECTION DETAILS

- 4. While inspecting bulk supply 20% of total supply may be inspected for finishing and 1% of total supply may be tested for material quality.
- 5. A failure of 20% out of the total quantity inspected will be considered as recommended for rejection of complete supply.

FACKING INSTRUCTIONS

6. The webbing shall be packed in double walled corrugated cartons, (3 dozen in each carton). Complete sealing of box shall be ensured through masking tape or similar material.

KHALID WASIM COMMODORE DIRECTOR GENERAL

P-2 of 2

