

PAKISTAN NAVY SPECIFICATION 02/2018

PROMULGATION DATE: 26 Mar 2018

GENERAL SERVICE DIGITAL CAMOUFLAGE DRESS NO 4B (ASHORE) 60% COTTON - 40% POLYESTER

Prepared by:

Directorate of Indigenous Technical Development at NSSD, West Wharf Road KARACHI

Tel: 021 48508410 Fax: 021 99214765

AMENDMENT RECORD

Amd No	Date	Text Effected	Signature and Date

REVISION NOTE

The specification has been prepared to bring the test methods and procedures into line with up-to-date PN requirements and facilities held in Pakistan. CINS may request to amend any test requirement/ test procedure in light of the experience emanating from its inspection history, through the feedback form placed at Annex J. However, such an alternation will be effective when the amendment is promulgated by this Directorate, and will be effective on the contracts which materialize after the promulgation date of respective amendment.

CONTENTS

Descr	<u>ription</u>	<u>Page</u>
Conte	ents	03
<u>Detail</u>	<u>ls</u>	
Usage Introd Scope Relate Terms Techn Manuf Qualit Testin Tende Advar Inspector Stamp Special Packir Identif Packir	uction eled Documents s & Definitions nical Details of GSDC Dress No. 4B (Ashore) 60% Cotton- 40% Polyester facturing Details of GSDC Dress No. 4B (Ashore) 60% Cotton-40% Polyester by of Workmanship and finishing fing er Sample fines Sample force Sample forcion for Accepted/Rejected Stores by Inspector finistructions fi	04 04 04 04 05 05 05 05 05 06 06 07 07 07 08 08 08
A. B. C. D. E. F. G. H.	Technical Details of GSDC Dress No. 4B (Ashore) 60% Cotton - 40% Polyester Manufacturing Details of GSDC Dress No 4B (Ashore) 60% Cotton - 40% Polyester Technical details of PAK Navy Soft Tally Manufacturing details of Pak Navy Soft Tally Technical details of Camouflage Jockey Cap / Sea Cap Manufacturing details of Camouflage Jockey Cap / Sea Cap Terms & Definitions Guidelines for Inspection – Specific Parts Defects Feedback Form	10 14 23 24 26 28 32 33 35

1. **DESIGNATION**

1.1 General Service Digital Camouflage (GSDC) Dress No. 4B (Ashore) 60% Cotton - 40% Polyester (Bush Jacket, Trouser, PAK NAVY Soft Tally and Camouflage Jockey Cap).

2. USAGE

2.1 This dress will be used by Officers, CPOs and Sailors of Pakistan Navy on Ashore vide NHQ letter PN/NS Dte/03/878204 dated 30 Nov 17.

3. **INTRODUCTION**

- 3.1 This specification is prepared by Directorate of Indigenous Technical Development, Karachi, to provide necessary guidance to the potential manufacturers/ suppliers of the items mentioned herein. This specification is to be used for testing and deciding upon acceptance, or otherwise, of the items mentioned. Any alteration or addition in this specification can be suggested to ITD Directorate. However, it cannot be implemented without prior approval of DITD. This specification supersedes and replaces PN Specifications No. 02/2017 and PN Specification 04/2017 promulgated earlier in relation to the items mentioned herein.
- 3.2 This specification booklet includes 09 Annexes, and consists 35 pages, including the cover.

4. SCOPE

- 4.1 This specification covers the manufacturing / inspection requirements of cloth made from Poly cotton blend to be used in the manufacturing of uniform, namely General Service Digital Camouflage (GSDC) Dress No. 4B (Ashore) 60% Cotton-40% Polyester (Bush Jacket & Trouser) to be used by personnel of Pakistan Navy. This specification lays down the standard to which the stores shown under designation above should conform. It defines and lays down the quality, standard and details of materials, workmanship and finish. It also lays down the details of sampling, testing, inspection rejection, marking, preservation, packing and delivery etc.
- 4.2 The supplier/ manufacturer shall comply in every respect with the terms of this specification and ensure that the stores conform to it, in all respects.

5. **RELATED DOCUMENTS**

5.1 The standards and documents that have been referred to in this specification are:

a.	ISO 1833	Textile – Quantitative chemical analysis.
b.	ISO-3801	Determination of mass per unit length and area.
C.	ISO-7211/2	Determination of number of threads per unit length.
d.	ISO-7211/5	Determination of linear density of yarn removed from fabric.
e.	ISO-105-C03	Colour fastness to Washing test No. 3.
f.	ISO-105-E02	Colour fastness to Seawater test.
g.	ISO-105-X12	Colour fastness to Rubbing test.
h.	ISO-105-E04	Colour fastness to Perspiration.
j.	ISO 13934-01 1999	Textile- Tensile properties of fabrics (strip method)
k.	ISO 13937-01 1999	Textile- Tear properties of fabric (Elmendorf)
m	AATCC 128-2009	Wrinkle Recovery of fabric
n.	AATCC 79-2010	Absorbency of Textiles
Ο.	ISO 9237:1995	Determination of permeability of fabric to air

p. AATCC 195:2010 Test for evaluation of Moisture Management

q. ASTM D 1230 Flammability of Apparels

r. ISO 6330 (3A) Domestic washing and drying procedures for textile testing

s. BS EN ISO 12945-2 Determination of fabric propensity to surface fuzzing and to pilling t. BS EN ISO 12947-4 Determination of the abrasion resistance of fabrics by the Martindale

method

u. BS EN 25077 Determination of Dimensional Change in washing and drying.

v. ISO 3071 Determination of pH of aqueous extract

w. AATCC 16 option 3 Colorfastness to light
 x. BS 4162 Methods of test for buttons
 y. AATCC 133 Colorfastness to hot press

z. ASTM D 5171 Standard test method for impact resistance of plastic sew through

buttons

a1. ASTM D5169 Dynamic shear strength of hook and loops touch fastener (Velcro)

a2. ASTM D 5170 T Peel Strength of hook and loop touch fastener (Velcro)

6. **TERMS & DEFINITIONS**

6.1 Definitions for the terms used in this standard are given at Annex G.

7. <u>TECHNICAL DETAILS FOR GENERAL SERVICE DIGITAL CAMOUFLAGE (GSDC) DRESS NO. 4B (ASHORE) 60% COTTON- 40% POLYESTER</u>

7.1 The technical details of General Service Digital Camouflage (GSDC) Dress No. 4B (Ashore) 60% Cotton- 40% Polyester is given at Annex A of this specification.

8. <u>MANUFACTURING DETAILS FOR GENERAL SERVICE DIGITAL CAMOUFLAGE</u> (GSDC) DRESS NO. 4B (ASHORE) 60% COTTON- 40% POLYESTER

8.1 Manufacturing details of General Service Digital Camouflage (GSDC) Dress No. 4B (Ashore) 60% Cotton- 40% Polyester will be as per Annex B of this specification.

9. QUALITY OF WORKMANSHIP AND FINISHING

9.1 Workmanship and finish of the General Service Digital Camouflage (GSDC) Dress No. 4B shall be equal to the sealed sample. It shall be best of its class and to the entire satisfaction of the inspector.

10. **TESTING**

10.1 The material shall be subjected to tests laid down in this specification at Annex A of this specification and related documents. At least one complete dress and 03 meter fabric will be required to complete all the tests mentioned at Annex A of this specification. The material may also be subjected to such tests which are deemed necessary by the inspection authority in order to determine their suitability. Inspecting Authority reserves the right to get any B/R samples tested from any reputable laboratory other than PN. However, any test considered important by Inspecting Authority other than Annex A may also be conducted in order to check its suitability.

11. **TENDER SAMPLE**

- 11.1 Tender sample to be approved by INS
- 11.2 For each contract following material shall be supplied by the manufacturer at the time of tendering.

Finished Garment 03 Nos. a. b. Fabric 05 Meter Fused Buckram 01 Meter C. 05 Nos. d. Buttons Stitching Thread 50 Grams e. Velcro 0.5 meter f. Waist adjustment Tape 02 No.s g.

12. **ADVANCE SAMPLE**

- 12.1 Advance sample or pre-production sample, when required, shall be submitted in accordance with terms of the contract for inspection, testing and approval by CINS. The minimum quantities required are 05 dresses along with samples of materials used in manufacturing of garments for inspection.
- 12.2 Whenever Tender, Advance or pre-production sample is not required, the suppliers / manufacturer are advised in their own interest to submit to the Inspecting Officer or his representative an initial delivery of One % of the contract or ten dresses, whichever are more along with samples of materials for inspection.
- 12.3 The approval of the sample mentioned in Para 11 & 12 authorizes the commencement of bulk production but does not relieve the suppliers/ manufactures from compliance with all the provisions of this specification. One approved sample shall be properly sealed by INS and returned to the firm for guidance; rest of the approved sample shall be retained by INS for future use in bulk Inspection.
- 12.4 The Pre-production sample shall be manufactured by the manufacturer with the same facilities which will be used for manufacturing of the bulk items.
- 12.5 Firm shall provide advance sample along with quality verification reports of fabric from an accredited laboratory to ensure in process inspection/ quality procedure of the firm.

13 **INSPECTION**

- 13.1 <u>Bulk representative sample</u> B/R random sampling will be carried out as per rules in vogue.
- 13.2 <u>Bulk Inspection</u> Bulk inspection will be carried out after satisfactory completion of Visual Examination and Testing of B/R Sample.
- 13.3 <u>Inspection of Store</u> 100% of the offered store shall be inspected. The guide lines for such examination/inspection are listed at Annex H. Stage inspection of Dresses be carried out as deemed appropriate.
- 13.4 <u>Inspection/ Acceptance and Rejection of Stores</u> Inspection/ acceptance is to be carried out to the satisfaction of Chief Inspector Naval Stores.
- 13.5. The dresses shall be examined for the correctness of material, shape, design, dimension, size, workmanship and finish.
- 13.6. All dresses shall be inspected w.r.t defective shape, discoloration/ fading, pinholes, closing of dresses are to be especially checked.
- 13.7. CINS reserves the right to reject the whole supply in case, upon examination, material or packing of any sample or portion of the consignment is found NOT CONFORMING to this specification.

- 13.8. If on examination of 5% of any delivery, 20% of those examined from bulk supply are found NOT CONFORMING to this specification in respect of the pattern, dimensions, workmanship and finish, the whole consignment may be rejected without any compromise.
- 13.9. All stores and packing NOT fully in accordance with this specification shall be rejected.
- 13.10. Dresses with major defects as described in Annex H of this specification will be rejected.
- 13.11. <u>Responsibility for Inspection</u> The supplier is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. PN reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.
- 13.12 <u>Responsibility for Compliance</u> The inspection set forth in this specification shall become a part of the supplier's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to PN for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit PN to acceptance of defective stores (material).
- 13.13 **Replacement by the Contractor** The supplier/ manufacturer is responsible for replacement of the consignment or any part thereof whenever it is found to be not conforming to this specification. The supplies so tendered in replacement, shall be subjected to testing/Inspection and acceptance by the Inspecting Officer.
- 13.14 **Responsibility for Safety** The supplier/manufacturer is wholly responsible for the safety of supplies during inspection, storage at firm's premises, proper packing, dispatch and delivery up to consignee.
- 14. **STAMPING OF ACCEPTED/ REJECTED STORES BY THE INSPECTOR** Following instructions are to be followed:
- 14.1 <u>Stamping of Accepted Stores</u> Each acceptable Dress shall be stamped with Inspector's Individual Acceptance Mark. The stamping shall be legible.
- 14.2 <u>Stamping of Rejected Stores</u> The rejected Dress shall be marked with Inspector's Rejection Mark to avoid re-submission by the supplier.
- 14.3 The Inspector is the authority in all matters pertaining to inspection.
- 15. **SPECIAL INSTRUCTIONS**
- 15.1 **CARE INSTRUCTIONS** Care instructions in English and Urdu shall be attached with each Dress as indicated in the drawing and have minimum requirement as follows:
 - Washing procedure.
 - Drying procedure.
 - Any Prohibition.
- 16. **PACKING DETAILS** The store when ordered to be delivered 'PACKED' shall be packed as per following instructions:

- The Dresses shall be packed in a neat, dry and clean condition in standard polyethylene.
- 10 Dresses shall be further packed in a thick Boxboard.
- Each Box Board packing shall be securely and properly packed.
- Each box board shall consist of same size.
- 17. <u>IDENTIFICATION LABEL</u> Each Dress shall bear following minimum information mentioned on identification label, attached as indicated in the drawing:
 - a. Item name/ item description with NSN/Pattern No.
 - b. Material Composition and size
 - c. Contract number and Date
 - d. Year of manufacture
 - e. Contractor's name, initials, or trade mark
 - f. Batch no.
- PACKING LIST Firm is bound to provide a packing list of store offered for inspection alongwith the challan, which include complete details about the store i.e Pattern No., Designation, quality packed, size, quantity, contract No, and Date, Challan No. and Date. A packing list shall be enclosed after completion of inspection with each packed box giving full details about the stores packed i.e. Pattern No., Designation, quality packed, size, quantity, contract No, and Date, I/Note No. or voucher No. and date, consignee, Consignor, Date of packing and packer's signature.
- 19. MARKING OF STORES In addition to any special marking required by contract or order, the marking of packages shall be stenciled with quick drying Black ink/ Paint in accordance with Specification No. NS/MISC/002/80 with clearly defined characters as described below:
 - a. On Front and Top
 - (1) Catalogue No and Designation of the store packed.
 - (2) Contract No and date.
 - (3) Quantity of the Items packed.
 - b. On Back
 - (1) Consignee address.
 - (2) Designation i.e Railway Station.
 - (3) Weight of the Package.
 - (4) The No. of individual Package and the total No of Packages in the consignment joined by the Word 'of 'e.g. 2 of 300.
 - c. On Bottom
 - (1) Consignor's Name.
 - (2) Voucher No. or inspection note no. and date.
 - (3) Month and year of packing.

20. **DELIVERY**

- 20.1 The consignment of store will be delivered in accordance with the terms of contract.
- 20.2 The store shall be delivered in Brand new, clean and dry condition.
- 20.3 The contractor / manufacturer is fully responsible for the safety of the supplies during inspection, storage at firms premises proper packing, dispatch and delivery up to consignee.

XXXXSDXXX AZHAR MIR

Commander Pakistan Navy Director

Annexes:

- A. Technical details for General Service Digital Camouflage (GSDC) Dress No. 4B (Ashore) 60% Cotton- 40% Polyester
- B. Manufacturing details for General Service Digital Camouflage (GSDC) Dress No. 4B (Ashore) 60% Cotton- 40% Polyester
- C. Technical details of PAK Navy Soft Tally
- D. Manufacturing details of Pak Navy Soft Tally
- E. Technical details of Camouflage Jockey Cap / Sea Cap
- F. Manufacturing details of Camouflage Jockey Cap / Sea Cap
- G. Terms & Definitions
- H. Guidelines for Inspection Specific Parts Defects
- J. Feedback Form

Distribution:			
DP (N)			
CINS			
DNS			
CO PNCSD			

ANNEX A TO PN SPECIFICATION NO 02/2018 PROMULGATION DATE 26 Mar 2018

TECHNICAL DETAILS FOR GENERAL SERVICE DIGITAL CAMOUFLAGE (GSDC) DRESS NO. 4B (ASHORE) 60% COTTON - 40% POLYESTER

S NO	ITEM		REQUIREMENT
BASE	FABRIC MATERIAL SPECIFIC	CATION (RI	BBED CAMOUFLAGE CLOTH)
1.	Material		60% Cotton – 40 % Polyester
2.	Count of Yarn	Warp Weft	20 ^s ± 2 (29.5 ± 2 Tex) 16 ^s ± 2 (37 ± 2 Tex) Ring spun Combed yarn shall be used
3.	Threads per Inch	Warp Weft	123 <u>+</u> 5 (Ends) 63 +5 (Picks)
 4. 5. 	Colors Scheme Black Dark G Mediun Light gr Grey Pastel G Weave Pattern	n grey ey	19-1101 TCX 18-5203 TCX 17-4405 TCX 15-4003 TCX 16-4702 TCX 13-4303 TCX Or As per approved sample held with CINS Twill weave 2/1 + Rip Stop
6.	Threads /Rip	Warp Weft	2 each single 2 each single
7.	Size of Rip	Warp	6mm+1mm
8. 9. 10.	Weight (gm/sq.mtr) Finish Finish width	,	245 gm ± 2% Mercerize, pre- shrink by sanforize and hydrophilic softener (nano finish) 59"
11.	Nature of Dye	Ground Print	Vat disperse dye Vat disperse print
12.	Digital Camouflage Design P	attern	As per Appendix I and approved sample held with CINS
BASE	FABRIC PERFORMANCE TE	STING	
1.	Color fastness to washing a. Change in Shade b. Staining		GS: 4 or better GS: 4 or better
2.	Color Fastness to Rubbing (I Staining	Ory)	GS: 4 or better
3.	Color Fastness to Rubbing (\ Staining	Vet)	GS: 3 or better
4.	Color Fastness to light Change in Shade		GS: 4 or better

5.	Color Fastness to perspiration	
	a. Change in Shade	GS: 4 or better
	b. Staining	GS: 4 or better
6.	Color Fastness to Sea Water	00 4 - 1 - 1 - 1
	a. Change in Shade	GS: 4 or better
7	b. Staining	GS: 4 or better
7.	Tensile strength (N) Warp Weft	1000 <u>+</u> 5% 800 + 5%
8.	Tear Strength(N) Warp	44 ± 5%
0.	Weft	44 ± 5% 48 ± 5%
9.	Flammability	Class1
3.	1 lammability	Flame spread time ≥ 3.5 sec
10.	Dimensional Stability test after 3 HL	Tiame spread time = 0.0 300
10.	40°C	
	Warp	+2%
	Weft	+2%
11.	Wrinkle recovery	Minimum 2
12.	Crease recovery	150° ± 3%
13.	Appearance after 5-10 washes (3A)	Satisfactory
	with tumble dry	
14.	Pilling resistance after 5,000 cycles	Grade 4
15.	Abrasion resistance after 6,000 cycles	No thread break
16	Air permeability(mm/sec at 100 Pa)	Minimum 45
17.	Moisture Management	0.60 Min
18.	Water absorbency (drop test)	Front side 7 sec(max)
		Back side 6 sec (max)
19	pH level	6-8
	HING THREAD SPECIFICATION	
1.	Material	Polyester
2.	Construction	2 cord each single
3.	Count of yarn	2/31.5 Tex <u>+</u> 3%
4.	Breaking Strength (24")	2.23 Kg ± 250 gms
5.	Shade	Light grey or Pantone 15-4003 TCX
6.	Color fastness to washing (Test No. 3)	CC: 4
	a. Change in Shade	GS: 4 GS: 4
	b. Staining	33. 4
VELCE	RO TAPE MATERIAL SPECIFICATION	
1	Material	
1.	Material Male	Nylon
	Female	Nylon
2.	Colour	Light grey or Pantone 15-4003 TCX
۷.	Colodi	Light grey of Fantone 13-4003 TCA
VELCF	O TAPE PERFORMANCE TESTING	
1.	1. Before sticking / unsticking 300	Satisfactory
	times at 300 g.	
	2. After sticking / unsticking 300	Satisfactory
	times at 300g.	
2.	Peel Strength (lbs per in width)	1.5
3.	Shear strength(PSI)	10
0.	Choan onongan(i Oi)	
	•	·


WAIST	ADJUSTMENT TAPE	
1.	Material	100% Cotton
2.	Color	Light grey or Pantone 15-4003 TCX
BUTTO	NS MATERIAL SPECIFICATION	
1	Material	Plastic
2.	Color	Black Pantone # 19-4006 TCX
BUTTO	N PREFORMANCE TESTING	1
1.	Color fastness to water	GS 4 or better
2.	Pull test at 90 N Impact resistance	No crack, chips or breakage No structural failure No center break out No crack, chips or breakage
4.	Color fastness to heat (hot pressing)	GS 4
5.	Appearance after washing	No color transfer on fabric

Appendix:

I. DIGITAL CAMOUFLAGE DESIGN/ PATTERN OF DRESS NO. 4B

DIGITAL CAMOUFLAGE DESIGN/ PATTERN OF DRESS NO. 4B

4B Pixilated Camo



ANNEX B TO PN SPECIFICATION NO 02 2018 PROMULGATION DATE 26 Mar 2018

MANUFACTURING DETAILS OF GENERAL SERVICE DIGITAL CAMOUFLAGE (GSDC) DRESS NO. 4B (ASHORE) 60% Cotton-40% POLYESTER

- 1 GSDC Dress No. 4B (Ashore) 60% Cotton-40% Polyester is to be manufactured as per measurement schedule and drawing at Appendix I and Appendix II respectively.
- 2 'PAK NAVY' soft tally as per Annex C and D of this specification shall be attached above left chest pocket of Dress No. 4B. Jockey /Sea Cap shall be supplied as per Annex E and F.
- 3. The sewing/stitching thread should match with the base fabric colour i.e light grey Pantone 15-4003 TCX and spun polyester.
- 4. In Bush jacket metallic air vents are placed at arm pits both side front and back and two in upper and lower side of each back pleat. Outer dia is 11mm and inner dia is 4.5 mm. Shade of metallic brass air vents should match with the base fabric color i.e. light grey Pantone 15-4003 TCX.
- 5. Polyester Buttons used should be Mat finished, 4 holes with 19 mm dia (30) ligne with 4 mm thickness and black in colour. Buttons of 16 mm dia with 4 mm thickness shall be used on shoulders only. The button is to be fastened with same matching black colour thread with cross sewing neatly.
- 6. On bush jacket collar ends, pockets and flaps, front placket, sleeves loops and back pleats are to be reinforced with bartack.
- 7. In Bush jacket on back pleats, joint of front and back panels, sleeves, arm joint, shoulder, cuffs and elbow patch double needle stitching is required.
- 8. Bush jacket shall be 1" bottom hemmed.
- 9. Soft paper fusing shall be used in collar, front pocket flaps and shoulder flaps.
- 10. Buttonholes are to have at least 22 stitches per 2 cm and to be bar-tacked or taper barred.
- 11. In trouser fly, cross pockets, knee and seat patches, thigh pockets, and side and seat seam are to be double needle stitched.
- 12. On trouser on front cross pockets end, thigh pockets, pockets bag and its flaps and back pockets and its flap, waist loops inner side bartack shall be done.
- 13. Two spare buttons each for bush jacket and trouser be provided/ stitched on the garment.
- 14. Pocket lining of same camouflage fabric shall be used.
- 15. Bottom adjustment dori/ rope of same fabric shall be attached at bottom of trouser. One end of the dori/ rope shall be stitched with the trouser to avoid slippage of rope during washing.

Appendices:

- I. MEASUREMENT SCHEDULE OF DRESS NO. 4B BUSH JACKET AND TROUSER
- II DRAWING OF DRESS NO. 4B BUSH JACKET AND TROUSER

APPENDIX I TO ANNEX B TO
PN SPECIFICATION NO 02/2018
PROMULGATION DATE 26 Mar 2018

i	MEASUREMENT SCHEDULE OF DRESS NO. 4B CAMOUFLAGE BUSHJACKET (INCHES)																	
		XXS	XSF	XSL	SF	SL	MF	ML	LF	LL	XLF	XLL	XXL	XXL1	XXL2	XXL3	XXL4	
SR	Description	34	36	36	38	38	40	40	42	42	44	46	48	48	50	52	54	TOL
	I comble from a contant band.	20.5	20.5	04	20.5	24	20.5	04	20.5	24	04	24	04	24	24	20	20	0.75
1	Length from center back.	29.5	29.5	31	29.5	31	29.5	31	29.5	31	31	31	31	31	31	32	32	0.75
2	Chest.	20	21	21	22	22	23	23	24	24	25	26	27	27	28	29	30	0.5
3	Waist.	19	20	20	21	21	22	22	23	23	24	25	26 27	26	27	28	29	0.5
4	Bottom.	20	21	21	22	22	23	23	24	24	25	26		27	28	29	30	0.5
5	Shoulder.	16.75	17.25	17.25	18	18	18.75	18.75	19.5	19.5	20.25	20.25	21	21	21	21	21.5	0.25
6	Sleeve Length.	23.5	24	24.75	24	24.75	24.5	25.25	24.5	25.25	25	25.5	25.5	25.5	26	27	27	0.5
7	Sleeve opening.	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	0.375
8	Arm hole.	10	10.5	10.5	10.5	10.5	11	11	11	11	11.5	11.5	11.5	11.5	11.5	12	12	0.5
9	Sleeves patch length.	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	0.25
10	Sleeves patch width top.	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	0.25
11	Sleeve patch width bottom.	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	0.25
12	Flag Velcro size.	4/6CM	4/6CM	4/6CM	4/6CM	4/6CM												
13	Flag Velcro placement from	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
	shoulder seam.																	
14	Cuff height.	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	0.125
15	Sleeve loop height.	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	0.25
16	Sleeve loop Width.	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	0.125
17	Front flap width.	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	0.25
18	Front flap height.	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	0.125
19	Front pocket length including flap.	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	0.25
20	Front pocket width	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	
21	Front pocket side box.	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0.125
22	Front pocket placement.	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	0.25
23	Front placket width right side.	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	0.125
24	Front placket width left side.	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.125
25	Front pocket hem.	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0.125
26	Front pocket Velcro height.	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	
27	Front pocket Velcro width.	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	
28	Front pocket tally Velcro (width & Length).	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	
29	Collar.	15	15.5	15.5	16	16.5	16.5	16.5	17	17	17.5	18	18	18	18.5	19	19	0.375
20	Collar height from center back.	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	0.125
31	Collar corner.	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	0.125
32	Side loop width	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	0.125
' j																		


	MEASUREMENT SCHEDULE OF DRESS NO. 4 B CAMOUFLAGE TROUSER (INCHES)																	
		XXS	XSF	XSL	SF	SL	MF	ML	LF	LL	XLF	XĹL	XXL	XXL1	XXL2	XXL3	XXL4	
SR	DESCRIPTION	28	30	30	32	32	34	34	36	36	38	40	42	44	46	48	50	TOL
1	Waist.	28	30	30	32	32	34	34	36	36	38	40	42	44	46	48	50	0.5
2	Hip (8in from belt)	37	39	39	41	41	43	43	45	45	47	49	51	54	56	58	60	0.5
3	Thigh	25	26	26	27	27	28	28	29	29	30	31	32	34	35	36	37	0.5
4	Bottom Knee on 13" from crouch.	21	21.5	21.5	22	22	22.5	22.5	23	23	23.5	24	24	24	25	25	26	0.25
5	Bottom	17.75	17.75	17.75	18	18	18.25	18.25	18.5	18.5	18.75	19	19	19	19	19	19	0.25
6	Inseam	33	31	33	31	33	31	33	31	33	33	33	33	33	33	33	33	1
7	Front rise include	11.25	11.5	11.75	11.75	12	12	12.25	12.25	12.5	12.75	13	13.25	13.25	13.5	13.75	14	0.25
8	Back rise	16.25	16.5	16.75	16.75	17	17	17.25	17.25	17.5	17.75	18	18.25	18.25	18.5	18.75	19	0.25
9	Front patch length	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	0.25
10	Front pocket opening waist	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	0.25
11	Front pocket side seam	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	0.25
12	Thigh pocket length	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	9	9	9	9	9	9	9	0.25
13	Thigh pocket width	8	8	8	8	8	8	8	8	8	8.5	8.5	8.5	8.5	8.5	8.5	8.5	0.25
14	Thigh pocket flap height	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	0.125
15	Back pocket flap width	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	0.25
16	Back pocket flap height	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	0.125
17	Back patch inside length	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	0.25
18	Waist belt	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.125
19	Thigh pocket placement	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	0.25
20	Belt loop length	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	0.25
21	Belt loop width bottom	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	0.125
22	Belt loop width top	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.125
23	Fly width	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.125
24	Fly length full	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.75	7.75	7.75	7.75	7.75	7.75	7.75	0.25


MEASUREMENT SCHEDULE OF FMTs DRESS 4B


	MEASUREMENT SCHE	DULE OF	DRESS N	IO. 4B C	MOUFLA	GE BUSH	JACKET	(INCHES)		
		XXS 1	XXS 2	XXS 3	XXS 4	XXS 5	XXS 6	XXS 7	XXS 8	
SR	Description									TOL
1	Length from center back.	30	30	30	30	30	30	30	30	0.75
2	Chest.	38	38	40	42	44	46	48	50	0.5
3	Waist.	34	36	38	40	42	44	46	48	0.5
4	Bottom.	38	40	42	44	46	48	50	52	0.5
5	Shoulder.	15	15	15	15.5	15.5	16	16	16.5	0.25
6	Sleeve Length.	22	22	22.5	22.5	23	23	23.5	23.5	0.5
7	Sleeve opening.	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	0.375
8	Arm hole.	8	8	8	9	9	9	9.5	9.5	0.5
9	Sleeves patch length.	7.75	7.75	7.75	7.75	7.75	7.75	7.75	7.75	0.25
10	Sleeves patch width top.	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	0.25
11	Sleeve patch width bottom.	7.25	7.25	7.25	7.25	7.25	7.25	7.25	7.25	0.25
12	Flag Velcro size.	4/6CM	4/6CM	4/6CM	4/6CM	4/6CM	4/6CM	4/6CM	4/6CM	
13	Flag Velcro placement from shoulder seam.	1	1	1	1	1	1	1	1	
14	Cuff height.	2	2	2	2	2	2	2	2	0.125
15	Sleeve loop height.	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	0.25
16	Sleeve loop Width.	2	2	2	2	2	2	2	2	0.125
17	Front flap width.	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	0.25
18	Front flap height.	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	0.125
19	Front pocket length including flap.	7	7	7	7	7	7	7	7	0.25
20	Front pocket width	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	
21	Front pocket side box.	1	1	1	1	1	1	1	1	0.125
22	Front pocket placement.	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	0.25
23	Front placket width right side.	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	0.125
24	Front placket width left side.	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.125
25	Front pocket hem.	1	1	1	1	1	1	1	1	0.125
26	Front pocket Velcro height.	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	
27	Front pocket Velcro width.	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	
28	Front pocket tally Velcro (width & Length).	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	
29	Collar.	13	13	13.5	13.5	14	14	15	15	0.375
20	Collar height from center back.	3.125	3.125	3.125	3.125	3.125	3.125	3.125	3.125	0.125
31	Collar corner.	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	0.125
32	Side loop width	2	2	2	2	2	2	2	2	0.125
33	Side loop length	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	0.125


	MEASUREMENT SC	HEDULE OF D	RESS NO.	4 B CAM	OUFLAGE	TROUSE	R (INCHE	S)		
		XXS 1	XXS 2	XXS 3	XXS 4	XXS 5	XXS 6	XXS 7	XXS 8	
SR	DESCRIPTION	26	28	30	32	34	36	38	40	TOL
1	Waist.	26	28	30	32	34	36	38	40	0.5
2	Hip (8in from belt)	35	37	39	41	43	45	47	49	0.5
3	Thigh	24	25	26	27	28	29	30	31	0.5
4	Bottom Knee on 13" from crouch.	20.5	21	21.5	22	22.5	23	23.5	24	0.25
5	Bottom	17.25	17.75	17.75	18	18.25	18.5	18.75	19	0.25
6	Inseam	33	33	33	33	33	33	33	33	1
7	Front rise include	11	11.25	11.75	12	12.25	12.5	12.75	13	0.25
8	Back rise	16	16.25	16.75	17	17.25	17.5	17.75	18	0.25
9	Front patch length	11	11	11	11	11	11	11	11	0.25
10	Front pocket opening waist	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	0.25
11	Front pocket side seam	7	7	7	7	7	7	7	7	0.25
12	Thigh pocket length	8.5	8.5	8.5	8.5	8.5	8.5	9	9	0.25
13	Thigh pocket width	8	8	8	8	8	8	8.5	8.5	0.25
14	Thigh pocket flap height	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75	0.125
15	Back pocket flap width	6	6	6	6	6	6	6	6	0.25
16	Back pocket flap height	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	0.125
17	Back patch inside length	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	0.25
18	Waist belt	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.125
19	Thigh pocket placement	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	0.25
20	Belt loop length	4.75	4.75	4.75	4.75	4.75	4.75	4.75	4.75	0.25
21	Belt loop width bottom	2	2	2	2	2	2	2	2	0.125
22	Belt loop width top	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.875	0.125
23	Fly width	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.125
24	Fly length full	7.25	7.25	7.25	7.25	7.25	7.25	7.75	7.75	0.25

APPENDIX II TO ANNEX B TO PN SPECIFICATION NO 02/2018 PROMULGATION DATE 26 Mar 2018










SIDE VIEW

1222

NOTE	:			
	FOR FURTHER D	ETAILS SEE	SEALED	SAMPLE.

						D. T. T.	T 77		
			14	THIGH POCKET FLAP HEIGHT	2.75	DIT	D K	AR	АСНІ
			13	THIGH POCKET WIDTH	8				
			12	THIGH POCKET LENGTH	8.5	TITLE:			
25	BOTTOM ADJUSTMENT ROPE	2/8	11	FRONT POCKET SIDE SEAM	7	i irou	JSER C	AMOU	IFLAGE
24	FLY LENGTH FULL	7.25	10	FRONT POCKET OPENING WAIST	2.25	1	SI7F:	MF-34	
23	FLY WIDTH	1.75	9	FRONT PATCH LENGTH	11		51ZL.	1111 34	
22	BELT LOOP WIDTH TOP	2	8	BACK RISE	17	DWG.NO. TD-2	2414/2017	DIMENS	IONS: INCHES
21	BELT LOOP WIDTH BOTTOM	2	7	FRONT RISE INCLUDE	12	DATE: 1	9-12-2017	SCALE:	N.T.S
20	BEIT LOOP LENGTH	4.75	6	INSEAM	31		T		
19	THIGH POCKET PLACEMENT	10.5	5	воттом	18.25	DRAWN BY	CHECK	ED BY	APPROVED B
18	WAIST BELT	1.75	4	KNEE ON 13 FROM CROUCH	22.5				
17	BACK PATCH INSIDE LENGTH	6.25	3	THIGH	28	SD	SD		SD
16	BACK POCKET FLAP HEIGHT	2.5	2	HIP(8 FROM BELT)	43	50	50		50
15	BACK POCKET FLAP WIDTH	6	1	WAIST	34	1			
S.NO	ITEM	INC	S.NO	ITEM	INC	H.D/M	LT.CDR		CDR
	DESCRIPTION				M.ASGHAR I/c DWG	ASMA SO	HAIL O.R&D	AZHAR MIR DI	

	TROUSER CAMOUFLAGE SIZE:MF-34						
	DWG.NO. TD-2	2414/2017	DIMENS	IONS: INCHES			
4	DATE: 19-12-2017		SCALE:	N.T.S			
;	DRAWN BY CHECK		ED BY	APPROVED BY			
,	SDSI			SD			
	H.D/M LT.CDR M.ASGHAR ASMA SO		HAIL	CDR AZHAR MIR			
	I/c DWG.	S	O.R&D	DITD			



ANNEX C TO
PN SPECIFICATION NO 02/2018
PROMULGATION DATE 26 Mar 2018

TECH. DETAILS OF 'PAK NAVY' SOFT TALLY FOR CAMOUFLAGE DRESS NO 4B

S NO	MAIN FABRIC	REQUIREMENT					
BASE FABRIC MATERIAL SPECIFICATION							
1.	Material	As per Annex A of this specification					
2.	Colour	Light grey or Pantone 15-4003TCX					
EMBRO	EMBROIDERY THREAD MATERIAL SPECIFICATION						
1. 2. 3.	Material Color Count of yarn	100% Viscose Black Pantone # 19-4006 TCX 2/36					
EMBRO	DIDERY THREAD PERFORMANCE TEST	ING					
1.	Color fastness to washing (Test No. 3) a. Change in Shade b. Staining	GS: 4 GS: 4					
VELCR	VELCRO TAPE MATERIAL SPECIFICATION						
1.	Material Male Female Colour	Nylon Nylon Light grey or Pantone 15-4003 TCX					
VELCE	O TARE REPEORMANCE TESTING						
VELCR	O TAPE PERFORMANCE TESTING						
1.	Manual Sticking/ Unsticking	a. Satisfactory after sticking and unsticking 300 times.					
		b. Satisfactory after sticking ad unsticking 300 times on applying weight of 300g.					
2.	Peel Strength (lbs per in width)	1.5					
3.	Shear strength(PSI)	10					

ANNEX D TO
PN SPECIFICATION NO 02/2018
PROMULGATION DATE 26 Mar 2018


MANUFACTURING DETAILS OF 'PAK NAVY' SOFT TALLY

- 1 PAK NAVY Soft Tally shall be fabricated in accordance with the shape and design as illustrated in the drawing at Appendix I of this Annex.
- 2 The thickness of embroidery shall be 3mm.
- The embroidery shall be neat and clean and all loose ends shall be trimmed off. The embroidery shall be parallel to the centre line of the tally.

Appendix:

I DRAWING OF 'PAK NAVY' SOFT TALLY.

APPENDIX I TO ANNEX D TO PN SPECIFICATION NO 02/2018 PROMULGATION DATE 26 Mar 2018



ANNEX E TO PN SPECIFICATION NO 02/2018 PROMULGATION DATE 26 Mar 2018

TECHNICAL DETAILS FOR CAMOUFLAGE JOCKEY / SEA CAP

S NO	ITEM	REQUIREMENT			
BASE	FABRIC MATERIAL SPECIFICATION				
1.	Material specification	As per Annex A of this specification			
STITC	HING THREAD MATERIAL SPECIFICATION	DN			
1.	Material	Polyester			
2.	Color	Light grey or Pantone # 15-4003 TCX			
3.	Count of yarn	26/3 3/22.7 Tex <u>+</u> 3%			
4.	Construction	3 cord each single			
STITC	HINGTHREAD PERFORMANCE TESTING				
1.	Color fastness to washing (Test No. 3)				
	a. Change in Shade	GS: 4			
	b. Staining	GS: 4			
2.	Strength, cN	2680			
3.	Tenacity, cN/Tex	39.24			
4.	Elongation %	18.53			
PLAS	TIC PEAKMATERIAL SPECIFICATION				
1.	Material	Plastic (virgin)			
2.	Thickness	1.5 -1.7 mm			
3.	Hardness	97 <u>+</u> 1 IRHD			
4.	Density	0.92 g/cc <u>+</u> 0.01			
CARE	LABEL MATERIAL SPECIFICATION				
1.	Material	Polyester with visible printing which remain satisfactory after washing test.			
2.	Shade	Nearest to ground fabric color i.e. light grey			
FMRR	OIDERY THREAD MATERIAL SPECIFICA	TION			
1.	Colour	Black Pantone# 19-4006 TCX			
2.	Material	Viscose			
3.	Count of yarn	2/44 <u>+</u> 2			
<u>EMBR</u>	OIDERY THREAD PERFORMANCE TEST	<u>ING</u>			
1	Colour factness to washing Test No. 2	I			
1.	Colour fastness to washing Test No. 3 1. Change in Shade 2. Staining	GS: 4			
	Cotton	GS: 4			

	Wool	GS: 4					
VELC	VELCRO TAPE MATERIAL SPECIFICATION						
1.	Material Male Female	Nylon Nylon					
2.	Colour	Light Grey or Pantone # 15-4003 TCX					
VELC	VELCRO TAPE PERFORMANCE TESTING						
1.	Performance Test 1. Before sticking / unsticking 300 times at 300 g.	Satisfactory					
	2. After sticking / unsticking 300 times at 300g.	Satisfactory					
2.	Peel Strength (lbs per in width)	1.5					
3.	Shear strength(PSI)	10					

ANNEX F TO PN SPECIFICATION NO 02/2018 PROMULGATION DATE 26 Mar 2018

MANUFACTURING DETAILS OF CAMOUFLAGE JOCKEY / SEA CAP

- 1 Camouflage Jockey / Sea Cap shall be fabricated in accordance with the shape and design as illustrated in the drawing at Annex C.
- 2 It is a 6 panel style Jockey Cap. The panels are stitched with each other using double needle stitch neatly using 10-12 SPI.
- 3 Pipen used on inner side of Cap is 10mm wide of same fabric used in upper of cap.
- Velcro tape used for adjustment of cap shall be 2.5 cm of best trade quality. The color of Velcro and embroidery on eyelets shall be light grey and matches with the base color of fabric.
- 5 The dia of top Button is 16mm and it is covered with same fabric used in upper of cap.
- 6 Sweat absorbing band and inner side of peak shall be of same upper fabric.
- 7 Care label and identification label may be attached with the sweat absorbing band.

Appendices:


- I MEASUREMENT SCHEDULE OF CAMOUFLAGE JOCKEY / SEA CAP.
- II DRAWING OF CAMOUFLAGE JOCKEY / SEA CAP.


MEASUREMENTS AND DIMENSIONS

S.No.	DESCRIPTIONS	SIZE	CM	TOLERANCE		
	Internal circumference	55	57	59	61	<u>+</u> 0.5
a.	Peak width from center	7.5	7.5	7.5	7.5	<u>+</u> 0.2
b.	Peak width from edges	13	13	13	13	<u>+</u> 0.2
C.	Peak Length from bottom edges	16	16	16	16	<u>+</u> 0.2
d.	Peak Length from top edges	18	18	18	18	<u>+</u> 0.2
e.	Height of Cap	12	12	12	12	<u>+</u> 0.5

<u>Note:</u>
The tolerances are given only for made up caps to cover the stitching allowance. Manufacturer will ensure exact size.

APPENDIX I TO ANNEX F TO PN SPECIFICATION NO 02 2018 PROMULGATION DATE 26 Mar 2018





ANNEX G TO PN SPECIFICATION NO 02 2018 PROMULGATION DATE 26 Mar 2018

TERMS & DEFINITIONS

- 1. <u>Inspection Authority</u>. Chief Inspector of Naval Stores (CINS). His verdict in respect of inspection matters is to be taken as final.
- 2. <u>Inspecting Officer</u>. An officer nominated by the Chief Inspector of Naval Stores (CINS) for carrying out inspection of stores supplied by the supplier, against a specified contract or order, in accordance with the particulates stipulated therein.
- 3. <u>Inspector</u>. The term inspector shall include the "Inspection Authority", inspecting officer and their representatives, duly authorized for the purpose of discharging inspection duties involved.
- 4. <u>Sealed Pattern</u>. It denotes a pattern, sealed and signed by the Inspection Authority & held in his custody, and represents the standard of store in respect of materials, dimensions, design, workmanship and finish, etc. There is only one sealed pattern for each store, which cannot be removed from custody of the inspection authority.

GUDELINES FOR INSPECTION – GENERAL DEFECTS

Defect

1. Material Defect and Workmanship Damages

- a. Any hole, scissor or knife tear, mend, burn or weakening defect, such as smash, multiple float, loose slub, or needle chews, that might develop in to hole.
- b. Cloth stiffened, hardened, or seared by heat, where thermo activated shade.
- c. Any garment portion puckered, twisted, or pleated at joining seam.

2. **Shaded Parts**

a. Any part shaded or any shade bar.

Colour

a. Any component of not specified color.

4. <u>Cleanliness</u>

- a. Any slub, spot, or stain on outer side.
- b. Threads ends not trimmed or loose threads ends not removed (to be scored only when condition exists on major portion of garment).
- c. Any shade identification stamping visible on outer side.

5. Component and Assembly

- a. Any component not as specified or any defect of component or defect of assembly not herein classified.
- b. Any component, component part, or required operation omitted or any other operation improperly performed not herein specified/ classified.

6. Seams and Stitching

- a. Any seam twisted, puckered, or pleated (unless otherwise classified herein).
- b. Any part of Jacket and Trouser caught in unrelated operation or stitching.
- c. Any edge not properly forced out, i.e, having fold more than specified.

- d. Ends of stitching that are not caught in other seam or stitching not securely tacked.
- e. Ends of seams or stitches that are not caught in other seams or stitching secured but backstitched for distance less than specified.
- f. Thread breaks not securely overstitched.
- g. Stitching tension tight resulting in breakage of stitches when normal pull is applied.
- h. Stitching per 20 mm on major portion of seam one or two stitches more or less than specified, except on labels.
- j. Stitches per 20 mm on major portion of seam more than three stitches more or less than specified, except on labels.
- k. Any bar tacks omitted, loose, misplaced or not serving intended purpose.
- I. Three or more bar tacks missing, loose, misplaced, or not serving intended purpose on multiple pencil compartment pocket.
- m. Skipped or broken stitches in two or more sewn eyelets.
- n. Stitch tension loose resulting in loose seam.
- p. Stitches in sewn eyelet one or two stitches less than specified.

ANNEX J TO PN SPECIFICATION NO 02 2018 PROMULGATION DATE 26 Mar 2018

FEED BACK FORM

m Designation:	
ttern #:	
rent Equipment:	
I SPEC #:	
oblem Faced:	
chnical Solution:	
ancial Effect (if any):	

Name Stamp

COUNTERSIGNED

Name Stamp

AMENDMENTS IN PN SPECIFICATION 02/2018

S. No	PN Specification 02/2018. along	Description
	with page. No./clause	A: 3
1.	Page 1	General Service Digital Camouflage Dress No. 4B (Ashore) 60% Cotton - 40% Polyester
2.	Page 3	Technical Details of GSDC Dress No 4B (Ashore)
	_	60% Cotton- 40% Polyester
	Details & Annexes	Manufacturing Details of GSDC Dress No. 4B (Ashore) 60% Cotton-40% Polyester
3.	Page 4	General Service Digital Camouflage (GSDC) Dress
	clause1.1	No.4B (Ashore) 60% Cotton - 40% Polyester (Bush
		Jacket, Trouser, PAK NAVY Soft Tally and
		Camouflage Jockey Cap
4.	Page 4	This specification covers the manufacturing /
	Clause 4.1	inspection requirements of cloth made from Poly
		cotton blend to be used in the manufacturing of
		uniform, namely General Service Digital Camouflage
		(GSDC) Dress No.4B (Ashore) 60% Cotton-40%
		Polyester (Bush Jacket & Trouser) to be used by personnel of Pakistan Navy. This specification lays
		down the standard to which the stores shown under
		designation above should conform. It defines and lays
		down the quality, standard and details of materials,
	2	workmanship and finish. It also lays down the details
	in Ki	of sampling, testing, inspection rejection, marking,
	ego Ar	preservation, packing and delivery etc.
5.	Page 5 Clause 7	Technical details For General Service Digital
	Clause 7	Camouflage (GSDC) Dress No 4b (Ashore) 60%
		Cotton- 40% Polyester
6.	raye J	The technical details of General Service Digital
	Clause 7.1	Camouflage (GSDC) Dress No 4B (Ashore) 60%
	N. C.	Cotton- 40% Polyester is given at Annex A of this
	- ~	specification.
7.	Page 5	Manufacturing details for General Service Digital
	Clause 8.	Camouflage (GSDC) Dress No. 4B (Ashore) 60%
	40	Cotton- 40% Polyester
8.	Page 5	Manufacturing details of General Service Digital
	Clause 8.1	Camouflage (GSDC) Dress No. 4B (Ashore) 60%
		Cotton- 40% Polyester will be as per Annex B of this specification
9.	Page 5	Workmanship and finish of the General Service Digital
J.	Clause 9.1	Camouflage (GSDC) Dress No 4B shall be equal to
	Oldado J. I	Carricanage (CODO) DIC33 110 TD Shall be equal to

		the sealed sample. It shall be best of its class and to
10.	Page 9 and 10 (Annex A)	the entire satisfaction of the inspector. Technical details for General Service Digital Camouflage (GSDC) Dress No 4B (Ashore) 60% Cotton- 40% Polyester
11.	Annex B	Manufacturing details for General Service Digital Camouflage (GSDC) Dress No 4B (Ashore) 60% Cotton- 40% Polyester
12.	Page 12 and 13 Appendix:	Digital Camouflage design/ pattern of Dress No. 4B
13.	Page 14 Annex B	Manufacturing details of General Service Digital Camouflage (GSDC) Dress No 4B (Ashore) 60% Cotton-40% Polyester
14.	Clause 1	GSDC Dress No 4B (Ashore) 60% Cotton-40% Polyester is to be manufactured as per measurement schedule and drawing at Appendix I and Appendix II respectively.
15.	Clause 2	PAK NAVY' soft tally as per Annex C and D of this specification shall be attached above left chest pocket of Dress No. 4B. Jockey /Sea Cap shall be supplied as per Annex E and F.
16.	Page 14, 15 ,16 ,17 and 18 Appendices I	Measurement schedule of Dress No.4B Bush Jacket and Trouser
17.	Appendices II	Drawing of Dress No. 4B Bush Jacket And Trouser
18.	Page 23	Pech. Details of 'PAK NAVY' soft tally for camouflage DRESS NO 4B
19.	Page 25	Pak Navy soft tally for Camouflage DRESS (4B)
20.	Page 30	Jockey Sea Cap Officers DRESS 4B
21.	Page 31	Jockey Sea Cap CPO's, Sailors DRESS 4B
	Page 31 Viewed by: Lt. Cdr. Pr. Mills Viewed by: Lt. Cdr. Pr	



DID OFFICE OF MD ITD NRDI (ITD WING)

PN/DID/03/5598116

58455

See Distribution

23 June 2020

CHANGE OF TITLE DRESS 4

Reference:

- A. PN/COMDEP/CSD N/03/5666972 dated 12 June 2020
- B. PN/DID/03/5622998 Dated 9 June 2020
- C. PN/NS Dte/03/2335545 Dated 5 June 2020
- D. PSO Conference 3/2020
- E. PN Specification 01/2018
- F. PN specification 02/2018
- G. PN/DGITD/03/1056882 dated 28 March 2018
- 1. It is submitted that the term Dress No 4 (Camouflage) or 4B (Digital) is to be discontinued, and replaced as Dress No 4 as directed vide reference 'C'. Therefore, PN Specifications at reference E & F, same is promulgated vide reference G have been amended.
- 2. Aforesaid in view, it is requested that Amendment at respective places may be endorsed at your end as per enclosed format.

For: Dress 4B Read: Dress 4

MUHAMMAD AYUB Cdr PN DID

Encl(s):

- 1. Amendements in PN Specification 01 2018
- 2. Amendement in PN Specification 02 2018

Distribution:
External:
Action:
NS Dte Attn: DDNS II (AOL)
CSD N Attn: EXO PNCSD
Chief Inspector of Naval Stores Attn: I O CLOTHING CINS
Attn: I O CLOTHING CINS DP Navy Attn: ADP 33 Information:
Information:
Stores Attn: CINS
DP NAVY
DNS
DP NAVY DNS CSD N Attn: CO PNCSD Internal:
Internal:
Information:
DITD S Attn: DITD (S)

PN/DID/03/5598116 approved by DID Cdr PN Muhammad Ayub on 23 Jun 2020 Note: Computer generated documents do not require signature



DGITD MATERIEL BRANCH NAVAL HEADQUARTERS NSSD AREA WEST WHARF ROAD KARACHI

PN/DGITD/03/1463776

59256

See Distribution

21 December 2018

AMENDMENT IN PN SPECIFICATION OF DRESS 4B

Reference:

- A. PN/NS Dte/03/1375033 dated: 12 Nov 2018
 B. PN/DGITD/03/1285656 dated: 10 Sep 2018
 C. PN/DGITD/03/1086039 dated: 12 Apr 2018
- D. PN/DGITD/03/1056882 dated: 28 Mar 2018

Apropos letter at reference A, following amendments may please be incorporated in PN Specification No. 01/2018 & 02/2018 promulgated vide reference D:

a. Amend Para (16) Packing Details of PN Specification No 01/2018 & 02/2018

(i) Packing details at Para 16 may be amended after addition of fabric and Jockey cap packing instruction as follows:

FABRIC PACKING DETAILS

- Accepted fabric shall be packed in the form of rolls.
- Each roll shall have length from 100 yards up to 200 yards (within multiple of 4 yds).
- The rolls should be packed/ wrapped in polyethylene sheet, vacuumed and in sealed packing.
- Each roll shall bear identification label indicating description of store, year of manufacture and contract

no, material composition, fabric width and length, contractors name, batch no. ,shrinkage

JOCKEY CAP PACKING DETAILS

- 10 X Camouflage Jockey/ Sea Caps bundles shall be packed in a neat and tidy condition in standard polyethylene packing of 0.035 mm thickness. These bags/ bundles shall be sealed with transparent adhesive tape 2.54 cm of thickness 0.04 – 0.05 mm.
- 05 X such bundles (50 caps) shall be packed in Carton Corrugated Card board box (07 ply).
- Each Carton shall contain one size of Camouflage Sea Caps only.
- Each box Board Packing shall be securely and properly packed with transparent adhesive tape 10 cm of thickness 0.04 0.05 mm.
- (ii) Amended measurement schedule and drawings are also enclosed to replace Appendix 1 and 2 of Annex B at your end please.

ASMA SOHAIL Lt Cdr PN SO TEXTILE DITD (S)

Encl(s):

- 1. Appendix 2 page 17
- 2. Appendix 2 page 18
- 3. Appendix 2 page 19
- 4. Appendix 2 page 20
- 5. Appendix 1

Distribution:

External:

Action:

DP (NAVY)

CINS

DNS

CSD N


Attn: CO PNCSD


Information:


COMDEP Attn: SSO (AOL)


PN/DGITD/03/1463776 approved by SO TEXTILE DITD (S) Lt Cdr PN Asma Sohail on 21 Dec 2018

Note: Computer generated documents do not require signature









		N	IEASUI	REMEN	T SCHE	DULE (OF DRE	SS CA	MOUF	LAGE I	BUSH .	JACKE	T (INC	HES)	?				
S.No		3XS	2XS	XXS	XSF	XSL	SF	SL	MF	ML	LF	LL	XLF	XLL	XXL	2XXL	3XXL	4XXL	TOL
	Description	30	32	34	36	36	38	38	40	40	42	42	44	46	48	50	52	54	±
01	Length from center back.	28	29	30	29	31	29	31	29	31	29	31	31	31	31	31	32	32	0.75
02	Chest.	18	19	20	21	21	22	22	23	23	24	24	25	26	27	28	29	30	0.5
03	Waist.	17	18	19	20	20	21	21	22	22	23	23	24	25	26	27	28	29	0.5
04	Bottom.	18	19	20	21	21	22	22	23	23	24	24	25	26	27	28	29	30	0.5
05	Shoulder.	16	16.25	16.75	17.25	17.25	18	18	18.75	18.75	19.5	19.5	20.25	20.25	21	21	21	21	0.25
06	Sleeve Length.	21.5	22	23	23	25	23.5	25	23	25	23.5	25	24.5	25	25	25.5	25.5	25.5	0.5
07	Sleeve opening.	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6.5	6.5	6.5	0.38
08	Arm hole.	9	9.25	9.5	10	10	10	10	10.5	10.5	10.5	10.5	11	11	11	11.5	11.5	12	0.5
09	Sleeve patch length.	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	0.25
10	Sleeve patch width top.	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	0.25
11	Sleeve patch width bottom.	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	0.25
12	Flag Velcro size.	4/6CM	4/6CM	4/6CM	4/6CM	0													
13	Flag Velcro placement from shoulder seam.	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0
14	Cuff height.	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	0.13
15	Sleeve loop length.	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	0.25
16	Sleeve loop Width.	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	0.13
17	Front flap width.	4.75	4.75	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	0.25
18	Front flap height.	2.25	2.25	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	0.13
19	Front pocket length including flap.	6	6	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	6.75	0.25
20	Front pocket side box.	1.5	1.5	1.5	1.5 🔨	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	0.13
21	Front pocket placement.	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	0.25
22	Front pocket hem.	1	1	1	1/1/	1	1	1	1	1	1	1	1	1	1	1	1	1	0.13
23	Front pocket Velcro height.	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	1
24	Front pocket Velcro width.	4.25	4.25	5	5.	5	5	5	5	5	5	5	5	5	5	5	5	5	0.25
25	Collar.	13.5	14	14.5	14.5	15	15	15.5	15.5	16	16	16.5	16.5	17	17.5	18	18	18.5	0.38
26	Collar height from center back.	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	0.13
27	Collar corner.	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	0.13
28	Side loop width.	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	0.13
29	Side loop length.	3 10	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	0.13
30	Front pocket tally Velcro (width & Length).	1/4,75	1/4.75	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	1/5.25	0.13
31	Front placket width right side.	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	0.13

32	Front placket width left side.	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	→ .75	1.75	1.75	0.13
33	Front pocket width.	4.75	4.75	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	5.25	0.13

APPENDIX I TO ANNEX B TO
PN SPECIFICATION NO 0 /2018
PROMULGATION DATE 26 Mar 2018

			<u>N</u>	MEASUF	REMENT	SCHE	DULE	OF DR	ESS C	AMOU	FLAGE	TROU	SER (I	NCHES)				
		3XS	2XS	xxs	XSF	XSL	SF	SL	MF	ML	LF	Rr.	XLF	XLL	XXL	2XXL	3XXL	4XXL	TOL
SR	DESCRIPTION	26	28	30	32	32	34	34	36	36	38	38	40	42	44	46	48	50	<u>+</u>
4	Waist.	00	00	20	32	32	24	24	200	20	O ₀	20	40	40	4.4	40	48	50	0.5
1		26	28	30			34	34	36	36	38	38	40	42	44	46		50	0.5
2	Hip (8in from belt).	35	37	39	41	41	43	43	45	45	47	47	49	51	53	55	57	59	0.5
3	Thigh.	23	24	25	26	26	27	27	28	28	29	29	30	31	32	33	34	35	0.5
4	Knee 13" from crouch.	9.25	9.5	9.75	10	10	10	10.25	10.25	10.5	10.5	10.75	10.75	11	11.25	11.5	11.75	12	0.25
5	Bottom.	8.5	8.75	9	9	9	9.25	9.25	9.25	9.25	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	0.25
6	Out seam.	41	41	41	39	42	39	42	39	42	39	42	42	42	42	42	42	42	1
7	Front rise.	10.5	10.75	11	11.25	11.5	11.5	11.75	11.75	12	12	12.25	12.5	12.75	13	13.25	13.5	13.75	0.25
8	Back rise.	15.5	15.75	16	16.25	16.5	16.5	16.75	16.75	17	17	17.25	17.5	17.75	18	18.25	18.5	18.75	0.25
9	Front patch length.	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	0.25
10	Front pocket opening waist.	2	2	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	0.25
11	Front pocket side seam.	7	7	7	7	7	76	7	7	7	7	7	7	7	7	7	7	7	0.25
12	Thigh pocket length.	7.5	7.5	8	8	8	8	8	8	8	8	8.5	8.5	8.5	8.5	8.5	8.5	8.5	0.25
13	Thigh pocket width.	7	7	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	8	8	8	8	8	8	8	0.25
14	Thigh pocket flap height.	3	3	3	3	30	3	3	3	3	3	3	3	3	3	3	3	3	0.13
15	Back pocket flap width.	5	5	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	0.25
16	Back pocket flap height.	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	0.13
17	Back patch inside length.	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	6.25	0.25
18	Waist belt.	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.13
19	Thigh pocket placement from	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	0.25
	Waist belt.			1															
20	Belt loop length.	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	0.25
21	Belt loop width bottom.	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	0.13
22	Belt loop width top.	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0.13
23	Fly width.	1.5	1,5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	0.13
24	Fly length full.	6.5	6.5	7	7	7	7	7	7	7	7	7	7.75	7.75	7.75	8	8	8	0.25

Viewed by: L. P. Rana Mehdi Hassan Go I Prics D. Dated: 03 Mov 2021 No.08.15

ANNEX A TO PN SPECIFICATIONS NO 02/2018 PROMULGATION DATE 26 MAR 2018

AMENDMENTS IN PN SPEICIFICATION 02/2018

FOR:

		Con
S NO	<u>ITEM</u>	REQUIREMENT
BASE F	ABRIC MATERIAL SPE	CIFICATION (RIBBED CAMOUFLAGE CLOTH)
4.	Color Scheme	
	Black	19-1101 TCX
	Dark Grey	18-5203 TCX
	Medium Grey	17-4405 TCX
	Light Grey	15-4003 TCX
	Grey	16-4702 TCX
	Pastel Grey	13-4303 TCX
		Or as per approved samples held with CINS

READ:

S NO	<u>ITEM</u>	REQUIREMENT			
BASE F	ABRIC MATERIAL SPE	CIFICATION (RIBE	BED CAMO	UFLAGE	CLOTH)
4.	Color Scheme	Panton Shade	OR L	a b Values	i
			L	а	b
a.	Black	19-1101 TCX	29.82	2.74	0.83
	Dark Grey	18-5203 TCX	45.71	0.50	-0.22
	Medium Grey	17-4405 TCX	53.29	0.33	0.38
	Light Grey	15-4003 TCX	63.22	-0.12	2.14
	Grey	16-4702 TCX	71.40	-1.38	2.56
	Pastel Grey	13-4303 TCX	77.05	-1.32	3.00
b.	Color Difference	(ΔE ≤ 1)			



DGITD

NSSD WEST WHARF ROAD KARACHI

PN/DGITD/03/1086039 59256

See Distribution 12 April 2018

AMENDMENT PN SPECIFICATION OF GENERAL SERVICE DIGITAL CAMOUFLAGE (GSDC) DRESS NO.4B 100 COTTON AND 60 COTTON 40 POLYESTER

Reference:

- A. PN/NS Dte/03/1078667 dated: 11 Apr 2018
- B. PN/ Chief Inspector of Naval Stores/ 03/1073494 dated 06 Apr 18
- C. PN/DGITD/03/1056882 dated: 28 Mar 2018
- D. PN/DGITD/03/1083677 dated 11 Apr 18
- 1. Apropos letter at reference A and B, following amendments may please be incorporated in PN Specification No. 01/2018 and 02/2018 promulgated vide reference C:
 - a. <u>Amend Para (3) under heading "Base Fabric Performance testing" Annex A of PN Specification No 01/2018 and 02/2018</u>

Color Fastness to Rubbing (Wet) Staining

For GS: 3 or better Read GS: 4 or better

b. Amend Para (14) under heading "Base Fabric Performance testing" Annex A of PN Specification No 01/2018 and 02/2018"

Pilling resistance after 5,000 cycles

For Grade 4
Read Grade 5

2. Letter at reference D may please be treated as cancelled.

ASMA SOHAIL Lt Cdr PN SO TEXTILE DITD (S)

Distribution:	
External:	
Action:	
DP (NAVY)	
CINS	2
DNS	
CSD N Attn: CO PNCSD	C.
Information:	8
COMDEP Attn: SSO	
DNAI	

PN/DGITD/03/1086039 approved by SO TEXTILE DITD (S) Lt Cdr PN Asma Sohail on 12 Apr 2018

Note: Computer generated documents do not require signature