

AMENDEMENTS IN PN SPECIFICATION 01/2016

FOR:

CLAUSE NO.	PAGE NO.	ITEMS
11.2	5	<p>Sole</p> <p>a. Polyurethane + Polyether Direct Injection Molded Sole in double layer to be provided. Mid sole shall be in white color and outer sole shall be in gray color having tread pattern to provide adequate slip resistance.</p> <p>b. Surface of PU + Polyether sole shall be free from air bubbles, blemishes and other visible defects. All the spew shall be neatly trimmed and shall have clean edges.</p> <p>NOTE: Shelf life of the shoes will be 3-5 years. Certificate of the hydrolysis test will be provided by the Manufacturer.</p>
16.2	7	<p>Note: Firm shall provide a shelf life certificate for a period of 4 years at the time of inspection.</p>

READ:

CLAUSE NO.	PAGE NO.	ITEMS
11.2	5	<p>Sole</p> <p>a. Polyurethane + Polyether Direct Injection Molded Sole in double layer to be provided. Mid sole shall be in white color and outer sole shall be in gray color having tread pattern to provide adequate slip resistance.</p> <p>b. Surface of PU + Polyether sole shall be free from air bubbles, blemishes and other visible defects. All the spew shall be neatly trimmed and shall have clean edges.</p> <p>NOTE: Shelf life of the shoes will be 02 years with useful life of 03 years (after issuance). Certificate of the hydrolysis test will be provided by the Manufacturer.</p>
16.2	7	<p>Note: Firm shall provide a shelf life certificate for a period of 2 years at the time of inspection.</p>