# CSC 384 Test 1 on Search

Monday, September 26, 2022

Last Name:	
First Name:	
Student Number:	


#### 1. Definitions of AI (7 marks total)

- 1.1 (2 marks) Which of the following is/are the difference(s) between the **Cognitive Modeling** and the **Rational Agent** definitions of Al? Circle all of the correct answers.
  - A. Whether we measure success against humans or rationality
  - B. Whether we care about reasoning or behaviour

- 1.2 (5 marks) Which of the following justifies choosing the **Rational Agent** definition over the **Cognitive Modeling** definition of AI?
  Circle all of the correct answers.
  - A. Humans are one of the few examples of intelligence.
  - B. Studying humans scientifically is easier than studying rationality scientifically.
  - C. Humans always behave intelligently.
  - D. Rational behaviour cannot be mathematically defined.
  - E. Rational behaviour is more general than rational thought.

#### 2. Uninformed Search (22 marks total)

2.1 (12 marks) Consider the search graph below.



(search graph continues below this level)

- **S** is the initial state.
- **D** and **E** are the goal states.

Fill in the table on the next page to show the execution of the **Iterative-Deepening Search.** Assume that this search algorithm **adds states** to the frontier in **reverse alphabetical** order and proceeds until it **terminates**. We have filled in the first few steps for you as an example.

For every step, list the following:

- The state that is being expanded,
- The state(s) being added to the frontier,
- The resulting states that are in the frontier.

If no states appear in a cell, write **None**. For the last step, indicate the state expanded and leave the other two cells in that row empty. Use as many rows in this table as you think you need.

## Provide your answer to Question 2.1 here:

Step	Depth limit	Node to expand	Nodes to add	Frontier
1	0	None	S	S
2	0	S	None	None
3	1	None	S	S
4	1	S	ВА	ВА
5				
6				
7				
8				
9				
10				
11				
12				

2.2 (5 marks) Given the search graph from part 2.1, consider what would happen if **Breadth-First Search** was used instead of **Iterative-Deepening Search**.

Which of the following would be true? Circle ALL that apply.


- A) The algorithm would work well with limited memory.
- B) The algorithm would find the optimal solution.
- C) If no solution existed, the algorithm would search every state.
- D) The algorithm's performance is unaffected by graph cycles.
- E) The algorithm's performance is unaffected by infinite paths.
- 2.3 (5 marks) Given the search graph from part 2.1, consider what would happen if **Depth-First Search** was used instead of **Iterative-Deepening Search**.

Which of the following would be true? Circle ALL that apply.

- A) The algorithm would work well with limited memory.
- B) The algorithm would find the optimal solution.
- C) If no solution existed, the algorithm would search every state.
- D) The algorithm's performance isn't affected by graph cycles.
- E) The algorithm's performance is unaffected by infinite paths.

### 3. Heuristic Search (8 marks total)

The diagram on the right illustrates a city map, where each state is an intersection and the edges between states are roads that connect intersections. Each state has a label and a heuristic estimate h for getting from that state to the goal state G.



3.1 (6 marks) Fill in the table provided. Each step includes the state being expanded, the g value for the state, and the frontier including the states and their f values. The first step has been filled in for you as an example.

If at least two states on the frontier have the smallest f values, expand the states in **alphabetical** order. For the last step, fill in the state expanded and the g value for the state only.

Step	State Expanded	g(State)	Frontier (State + its f value)
1	S	0	D(3), B(10)
2			
3			
4			
5			
6			

3.2 (1 mark) If the h value for State E was changed from 1 to 5, what path would the A\* algorithm find instead?

3.3 (1 mark) Why would changing State E's heuristic value cause the A\* algorithm to find a suboptimal path?

This page is intentionally left blank.