Bypass-LoRA: 低维循环注意力与 FFN 条件融合 v2

November 2, 2026

Abstract

本文记录 Bypass-LoRA v2 截至 2026-11-02 的结果。研究对象是冻结的 Qwen3-0.6B-Base 旁的低维侧分支。V0 用预先锁定容差的检查验证了侧分支的实现语义（E-0001 修正后 85/85 项、E-0004 130/130 项通过）。V1 在 PIQA+BoolQ 上用不含记忆的 tokenwise proxy 比较八组接口（每组 2M tokens，seed 0）：最好的 concat 接口 C_dual（78.15%）只比加法 F_out（77.80%）高 0.35 pp，未达 1 pp 门槛，两个参数相近的 LoRA（79.20%、79.05%）更高，H-0002 记为 challenged（screening）。V2 研究只保留低维记忆时的单跳读取：十组 M 线配置都没有达到运行前锁定的门槛（正常记忆对清零与打乱记忆的 EM 优势最大 +0.6 pp，门槛 10 pp），训练后答案位置权重最高的槽位总是第一个写入的槽位，H-0003 记为 challenged（screening）。用户批准计划外的修复后，记忆路线重开。诊断显示上下文中编码的 value 只对第一条事实可解码；把每条事实单独编码后写入，并先在每个 episode 只有 1 条事实的任务上训练（D5 配方），16 条事实的单跳读取在三个 seed 上都达到门槛（EM 优势 41.1、47.8、46.2 pp），H-0012 记为 supported（screening）。同一批 adapter 在 V3 的链终点任务（T2）的一跳问题上没有达到门槛（EM 优势 0.9–3.0 pp）：解码器迁移了，寻址没有迁移。V3 在 T2 上训练共同起点后检验多次读取：S2 在 2–3 跳上只比 S1 高 0.60 pp（门槛 3 pp）；冻结诊断把失败定位在两次读取之间的 query 转移，加后继槽位监督的修复 pilot 也没有通过。H-0005 记为 inconclusive，M 线暂停。V5 缩减版在官方 validation 上只开封一次：tokenwise C_up 对 28 层 rank1 LoRA 的三 seed 平均宏平均差为 -0.42 pp（95% 区间 $[-1.02, +0.20]$），按封存规则 H-0008 记为 challenged（confirmatory），这条路线停止。按 plan2 新增的残差旁路线（RB）在四层上各加一条 r32 的因果低维 linear attention 旁路。实现检查通过后，首轮筛选 RB1（seed 0，dev 每任务 1,000 条）中，单次读取的残差旁路为 77.10%，比 Base（70.15%）高 6.95 pp，但比参数接近的 LoRA（78.95%）低 1.85 pp，也比同参数、不读历史的 T0（77.30%）低 0.20 pp。H-0013 与 H-0014 记为 challenged（screening）；循环读取与 gate/up 融合的差都为正但低于 1 pp，记为 inconclusive。应用户要求把侧支加宽到 r128 后（E-0026，seed 0），残差旁路为 76.95%，仍比参数匹配的 LoRA r31（78.75%）低 1.80 pp，只比同参数 T0 高 0.15 pp，各组相对 r32 的变化都在 0.5 pp 以内，H-0018 记为 challenged（screening）。RB 线随后转向一个有上限的新问题：backbone 看不到第 1 段、只有侧支状态能跨段时，状态是否带来收益（H-0019，E-0025）。主任务 PIQA 上，保留状态的组比两个无历史对照中较好的一个只高 1.6 pp（r32）与 1.4 pp（r128），低于 3 pp 门槛；次要任务 BoolQ 在 r128 上高 4.4 pp，换掉第 1 段的状态使它下降 6.5 pp，但 r128 的两个无历史对照只比 Base_seg 高 0.3 与 0.6 pp。H-0019 记为 inconclusive。BoolQ 用两个新 seed 复现（H-0020，E-0027）后，三个 seed 的平均 gain 为 +2.93 pp（各 seed 为 +4.4、+2.6、+1.8 pp），略低于 +3 pp 门槛。保留状态组的准确率与 swap 降幅在三个 seed 上接近，gain 变小主要因为无历史的 T0 对照在新 seed 上学成。H-0020 按预登记规则记为 inconclusive，分段线暂停。用户随后提出改进 RB1 中接 FFN up 的 C_up 组（RB1-09，77.50%）：换特征来源、搜索侧支输出比例 η、与同接口的 up-only LoRA 比较、梯度子空间初始化与 Q/K 配对初始化。E-0028 把特征来源换成该层 input_layernorm 的输出后为 78.15%，比 RB1-09 高 0.65 pp（95% 区间 $[-0.25, +1.60]$），H-0021 记为 inconclusive；按 calibration 选出的 η 在两种特征来源下都不比 $\eta = 0.25$ 好，H-0022 记为 challenged（screening）。所有侧支组仍低于 LoRA r7（78.95%），按预登记规则，普通设置下不再做新的特征来源变体；已封存的 E-0029 作为有界的例外照原样运行，正在进行。除 V5 外，证据都是单 seed 或三个 seed 的筛选级证据。

1 Introduction

Bypass-LoRA v2 在冻结主干旁加一条低维循环侧分支：从注意力的 Q/K/V 取特征，压缩成低维状态，经记忆读写与循环更新，再通过 FFN 融合写回主干。计划把研究拆成几个阶段：V0 验证实现语义（H-0001）；V1 在没有记忆与循环的 tokenwise proxy 下比较融合接口，检验把信号注入 FFN 的 gate/up 是否优于加法写回（H-0002）；从 V2 起研究丢弃 support 主干 KV、只保留低维记忆时的单跳读取（H-0003），后续还有读算子选择性（H-0004）、多次读取（H-0005）与实用适配（H-0006）。V2 没有产生可用读取后，计划先缩减为 V5 的简单接口对比；用户随后批准了针对失败原因的修复（H-0009–H-0012），记忆路线与 V3/V4 因此重开。plan2 另加一条残差旁路线（RB）：侧分支在每个 token 处读取自身的因果历史，检验它的实用价值（H-0013）、对侧支历史的依赖（H-0014）、重复读取（H-0015）与 gate/up 融合（H-0016）。RB1 之后新增三条：H-0018 应用户要求检验把侧支从 r32 加宽到 r128 是否改变普通设置下的结论；H-0019 检验 backbone 看不到的信息只能经侧支状态跨过段界时，状态是否带来收益；H-0020 是 H-0019 在 BoolQ 上的两个新 seed 复现。之后按用户的方案改进 RB1 中接 FFN up 的 C_up 组（RB1-09）：把特征来源换成层输入（H-0021），搜索侧支输出比例 η（H-0022），与同接口的 up-only LoRA 比较（H-0023），A_v 用任务梯度子空间初始化（H-0024），Q/K 配对初始化（H-0025），以及只换 Q/K 的来源（H-0026）；H-0027 与 H-0028 是按结果释放的候选。本文报告 V0–V2、记忆路线修复、V3、V5 缩减版的确认结果、RB 线的实现检查、首轮筛选与 r128 宽度探针、分段检验及其 BoolQ 复现，以及 RB1-09 改进筛选中 E-0028 的结果与 E-0029 的设计（正在运行）。各假设的陈述、范围与当前状态如下。

- H-0001@1 (supported, active) V0 实现语义与恒等式正确: 新侧分支实现（QKV tap、因果 KernelMatrix、低维累加循环、FFN 融合、M/F 协议）语义正确：出口全零时与未修改 Base 输出一致；两步梯度启动后 Q/K/V 压缩与 Rq/Ro 获得非零梯度且主干参数不更新；KernelMatrix 与 KernelSlot 的输出及 Q/K/V 梯度一致；Cg=PWg、Cu=PWu 约束下 C_dual 与 F_pre 的输出及对同一 P 的梯度一致；改动后缀不改变前缀输出；一次 prefill、分块 prefill 与逐 token decode 一致；padding 不写不读、reset/batch 重排不串状态；同 token 只写一次且 S 不改变写次数；M 线 support 主干 KV 不进入 query forward。(scope: Qwen/Qwen3-0.6B-Base（锁定 revision）；FP32 小张量参考用严格阈值；GPU BF16 容差由同一 Base 的重复测量预先锁定，看到失败后不得放宽；检查围绕 plan §6.3 列出的风险，不要求重跑无关实验)

- H-0002@1 (challenged, paused) FFN gate/up 条件融合优于加法写回（V1 tokenwise proxy）: F 线（保留原 attention 上下文）、4 层 [6,13,20,27]、r32、无侧支记忆与循环的 tokenwise proxy Z=SiLU(UA) 下，把同一 Z 注入冻结 FFN 的 gate/up（C_gate/C_up/C_dual）比加法写回（F_out/F_pre）在非天花板 dev 切片上取得更好的任务准确率与更低 NLL；且该优势不能仅由线性退化组（Z=UA + C_dual，即共享 A 的 gate/up LoRA）或参数相近的 LoRA（4 层 all-7 rank10；28 层 all-7 rank2）解释。(scope: F 线；真实任务 train/dev（PIQA+BoolQ 官方 train 切分）或预先锁定的非天花板切片；每组 $\leq$2M 非 padding 输入 tokens、seed 0 单 seed 筛选（screening）；接口间不等参，只筛位置与信号，不据此宣称参数效率；无记忆 proxy 的负结果不否定有记忆 concat（V2 保留 C_dual 交互探针）)

- H-0003@1 (challenged, paused) M 线单跳：learned memory 读取产生可用信号（V2）: M 线（问答阶段丢弃 support 主干 KV，仅保留声明的低维 memory）、单层 0-based index14、r128、S=1、T1 单跳（E=16 事实、4 关系、visible_fact_delimiter 写入、all_valid_question 读取）、仅答案 CE 从 Base 训练时，2×2×2 析因（特征 direct_hidden/qknorm_pre_rope × 读算子 KernelMatrix/SoftmaxSlot × 融合 F*/C*）中至少一组在新 dev 上正常 memory 的 EM 同时比 zero 与 shuffled memory 高至少 10 pp 且 NLL 更低，并有可用正对照与非退化读出。(scope: study_id concat_loop_v2 的 V2 数据（独立 phase/seed 命名空间，不复用旧验证

集）；每组 ≤4M 输入 tokens、单 seed 筛选；门槛须在 V2 release 前锁定；是否继续有限循环探索的研究门槛，不是统计确认，也不替代旧 writer 的 80% gate)

- H-0004@1 (inconclusive, paused) 读算子选择性：SoftmaxSlot 读取比 KernelMatrix 更集中且更可用: 在相同正核 q/k 特征、相同写读位置与训练条件下，SoftmaxSlot（s0=sqrt(dk)、tau=1、g=1）比 KernelMatrix 产生更高的目标 key 权重、更少的有效读取项数、更低的归一化读误差与更高的单跳 EM；若 SoftmaxSlot 有效而 KernelMatrix 无效，瓶颈在读权重的选择性与混合，而非 memory 中的信息缺失。(scope: V2 析因内的读算子主效应与交互；单 seed 筛选；差异只称读算子差异，不归因于 "保存 KV 消除了矩阵压缩"；KernelSlot 只作恒等检查，不作训练 arm)

- H-0005@2 (inconclusive, paused) 固定记忆下演化 query 的多次读取有独立收益（V3→V4）: 固定 memory（同一 token 的各步共享 M、c）下，累加循环 S=2/4 的 hops2–3 EM 优于独立训练的 S1，且该收益不被固定 query 精确幅度对照（Z=S·eta·a·Ro）、固定总步长、同源 tokenwise 核、MAC/延迟匹配的更宽 S1、同核锚定更新与完整状态读出解释。(scope: M 线，单独编码写入协议：每条事实不带前文单独编码，在其分隔符处写入 key/value，问题侧不变；这是须声明的结构化支持输入条件，统计量与 E-0010 分开报告。单读配置沿用 H-0012 的 D5 配方：冻结 Qwen3-0.6B-Base，第 14 层，direct_hidden，SoftmaxSlot，F_out，r128，先在 E=1 上训练。任务：T2 链终点（E-0011 生成器），训练与 dev 只含 hops1–3，hops4/6/8 封存作外推。V3 各组样本预算相同，单 seed 筛选。确认（V4）需预注册：hops2–3 平均 EM 差 ≥ +3 pp，配对区间下界 > 0，3 个新 seed 方向都为正，hop1 差不低于 −1 pp。)

- H-0006@1 (untested, paused) 保留原 attention 的实用适配价值（V5）: F 线（4 层 r32，保留原 attention 上下文）的 PIQA+BoolQ 适配中，C* 多读相对参数匹配的强 LoRA（全 28 层 all-7）宏平均准确率提升至少 +1 pp 且每任务下降不超过 1 pp；并且侧支历史相对同参 tokenwise T0 与 zero/shuffle/permute 干预有可测贡献；同时报告延迟与状态成本。(scope: 官方 validation 封存为确认集，配置与分析锁定后只开一次；3 seeds × ≤12M、最多 3 epochs；95% 配对区间 + Holm 校正；WikiText-103 保留 split 的 NLL 作能力保持；参数、状态与计算不同时等量，不宣称同时公平)

- H-0007@1 (untested, paused) 冻结 S-RE：已学 K/V 换用槽位读算子后更可用（旧资产诊断）: 冻结旧 S-RE（DPFP 实际 key 768 / value 128、原读位置、memory-only）的 writer 与低维 reader，仅把原生 ridge read 在所有正常读取位置同时替换为 SoftSlot 或 HardSlot（温度/增益只在独立 calibration 上按 NLL 选择），旧 1,000 个验证 episode 的 EM 高于原生读取（旧参考 723/1,000，NLL 1.642）。(scope: 需要旧 S-RE 推理资产（writer.pt 与 looplora.llm.sq2.load_inference）；只回答既有 learned K/V 在另一读算子下能否更有效使用，不证明训练后极限；复现旧验证只证明兼容性；冻结诊断上限 1 node·h)

- H-0008@2 (challenged, retired) 保留原 attention 的 tokenwise 简单接口的实用价值（V5 缩减）: F 线（保留原 attention 上下文）、4 层 [6,13,20,27] 的 tokenwise 接口 C*（C_up，r32，Z=SiLU(UA)，524,288 参数）在 PIQA+BoolQ 官方 validation 上，相对参数匹配的强 LoRA（全 28 层 all-7 rank1，630,784 参数）宏平均准确率高至少 1 pp，且每个任务的准确率差不低于 -1 pp。(scope: V1 的切分、模板与评估；3 个新 seeds；每 run 正好 3 epochs（约 4.46M tokens，不超过 12M）；训练目标同 V1（逐样本平均）；学习率按预先登记的端点扩展校准；官方 validation 封存为确认集，配置与分析锁定后只开一次；95% 配对 bootstrap 区间只反映给定这三个训练 seed 时的数据不确定性，不代表训练过程的分布；+1 pp 与每任务 -1 pp 是点估计门槛，supported 不表示以 95% 置信保证收益至少 +1 pp，也不是逐任务非劣检验；次要比较做 Holm 校正；WikiText-103 保留 split 的 NLL 作能力保持；参数接近但不相等，不宣称参数效率或同时等计算；LoRA 结论只针对 rank1 与本合同的短校准 LR 规程；不含侧支历史与多次读取（记忆路线已停止，D-0008）)

- H-0009@1 (challenged, paused) 记忆路线修复：改变训练配方后单跳读取可用: 在 V2 的 M 线架构（冻结 Qwen3-0.6B-Base，第 14 层，r128，S=1，分隔符写入，问题位置读取）下，V2 的失败（EV-0070、EV-0072）主要来自训练动态而非容量：至少一种改动后的训练配方——更少事实或事实数课程、预先吸收答案先验的独立通路、地址权重辅助监督、或去中心化余弦寻址加可学温度——能让 T1 E=16 的单跳读取在 dev 上达到 E-0010@2 锁定的 H3 门槛（EM_normal − max(EM_zero, EM_shuffled) ≥ 10 pp，NLL_normal < min(NLL_zero, NLL_shuffled)，目标事实平均地址权重 ≥ 0.125）。(scope: M 线 T1（hop 1）; E=16 沿用 V2 数据，E ∈ {1,4,8} 为新登记的数据版本；单 seed 筛选，每 arm 与 V2 相同的步数与 batch；额外监督（目标事实索引）单独标注，结论只在其条件下陈述；不读 confirmation；不改 V2 的结论与 E-0010 判定)

- H-0010@1 (challenged, paused) E=16 上下文中 value 解码器先行：干净读取下可学成，之后寻址可从答案 CE 发现: 在 E=16 上下文里，若训练时把记忆限制为只含目标槽位（teacher-forced 单槽读取，用到目标索引，属额外监督），value→ 答案的解码器能在 6000 步内达到 teacher-forced 读取下 EM_normal − max(EM_zero, EM_shuffled) ≥ 50 pp；从该 checkpoint 恢复全部槽位、只用答案 CE 再训练 6000 步后，单跳读取在 E=16 dev 上达到 E-0010@2 的 H3 门槛。(scope: M 线 T1 hop 1，E=16 沿用 V2 数据（ATT-0039-1）; 冻结 Qwen3-0.6B-Base，第 14 层 r128 S=1，direct_hidden、SoftmaxSlot、F_out，LR 3e-3；单 seed 筛选；额外监督与协议改动单独标注；不读 confirmation；不改 V2 与 E-0014 的结论)

- H-0011@1 (challenged, paused) 槽位隐变量的边际似然训练避免塌缩并让寻址可从答案发现: 把训练目标从向量空间混合读取改为槽位隐变量的边际似然 L = −log Σ_i w_i·p(answer | 只读 v_i)，读取只在最后问题位置、寻址权重来自正常 softmax、不用目标索引，6000 步后最后位置不再塌缩到固定槽位，并在 E=16 dev 上按硬读取（argmax 槽位）协议达到 H3 门槛（EM 差 ≥ 10 pp、NLL 条件、最后位置目标权重 ≥ 0.125）。(scope: M 线 T1 hop 1，E=16 沿用 V2 数据（ATT-0039-1）; 冻结 Qwen3-0.6B-Base，第 14 层 r128 S=1，direct_hidden、SoftmaxSlot、F_out，LR 3e-3；单 seed 筛选；额外监督与协议改动单独标注；不读 confirmation；不改 V2 与 E-0014 的结论；硬读取与只读最后位置是新登记的读取协议，与 E-0010 的全问题位置统计量分开报告)

- H-0012@1 (supported, active) 每条事实单独编码后写入，消除 value 的上下文迁移: 支持中的每条事实单独编码（格式同 E=1）后在其分隔符处写入，读取协议不变，只用答案 CE：从零训练或从 R1 checkpoint 续训 6000 步后，E=16 单跳读取在 dev 上达到 H3 门槛，且最后位置不塌缩到固定槽位。(scope: M 线 T1 hop 1，E=16 沿用 V2 数据（ATT-0039-1）; 冻结 Qwen3-0.6B-Base，第 14 层 r128 S=1，direct_hidden、SoftmaxSlot、F_out，LR 3e-3；单 seed 筛选；额外监督与协议改动单独标注；不读 confirmation；不改 V2 与 E-0014 的结论；单独编码是须声明的结构化支持输入条件（写入时不看其他事实），以 E-0015 规则 5 成立为前提)

- H-0013@1 (challenged, paused) 残差旁路低维因果 linear attention 的实用价值（R_res+KernelMatrix S1，plan2 主线）: 保留原 attention 的 F 线上，在冻结 Qwen3-0.6B-Base 的四层 [6,13,20,27] 各加一个 r32 块输出残差旁路 Y=B(X)+Z·P_R（R_res），Z 由真实因果 KernelMatrix 低维 linear attention 单次读取（S1）产生；它在 PIQA+BoolQ 上的宏平均准确率比参数接近的标准 LoRA 至少高 1 pp，且每个任务的差不低于 −1 pp。(scope: RB 线。筛选（RB1）: dev 每任务 1,000 条、单 seed，对照 Base、同参数 T0 与同四层 all-7 LoRA r7（630,784 参数，比 R_res 的 663,552 少 4.94%）。确认（RB5，尚未建契约）: 新登记并封存的确认集、3 个新 seed，对照全 28 层 all-7 LoRA r1（630,784）。固定 qknorm_pre_rope、inclusive 先写一次再读、η=0.25、g=1；参数不完全相等，不宣称参数效率；同时报告延迟与状态字节；+1 pp 与每任务 −1 pp 是点估计门槛。)

- H-0014@1 (challenged, paused) 残差旁路的收益依赖侧支自身的因果历史（同参数 T0 与冻结历史干预）：在 R_res+KernelMatrix 上，同参数、同深度、没有侧支历史的同源逐 token 核 T0 的宏平均至少低 1 pp；并且保留原 attention 与其 KV、只改侧支历史的冻结干预（episode 间交换历史状态、历史内打乱 key/value 配对）各使宏平均至少下降 1 pp。(scope: RB 线、F 线。筛选：RB1-02 对 RB1-01（S1）及 RB1 的冻结干预（dev）；确认：RB5 的同深度 T0（RB5-08）与确认集上的干预。原 Q/K/V 特征本身含上下文，清空侧支历史不等于模型失去历史；干预可能带来分布偏移，单次 zero/shuffle 下降不作机制证明；T0 也改变了读函数，因此同时报告窗口、strict 与当前 token 读权重。不成立时按 plan2 §11.4 只称动态/非线性适配。)

- H-0015@1 (inconclusive, paused) 同一残差旁路内的低维重复读取有超出幅度、步长与逐 token 深度的增量（S_F*∈{2,4}）：R_res+KernelMatrix 的累加式循环 S_F*（2 或 4，由 RB1 dev 锁定）比 S1 的宏平均至少高 1 pp；该增量不能由重复同一读取的输出放大（S4 固定第 1 步 query）、累积总步长（S4 且 η=0.25/4）或同深度 T0 解释。(scope: RB 线、F 线；S_F* 只由 F 线 train/dev 决定，不移植 M 线的 S_M*。筛选：RB1-03/04 对 RB1-02，RB1-05/06 为幅度与步长对照；确认：RB5-02 对 RB5-01 与 RB5-08。RB1 的 T0 只有 S1，不能排除 S4 的逐 token 深度解释；S4 若只等于固定 query 对照，记为暂无迭代查询证据（plan2 §17.2）；不宣称因果逐跳推理；报告读取次数、MAC 与实测延迟。)

- H-0016@1 (inconclusive, paused) 同一 KernelMatrix 状态下 FFN gate/up 条件融合（C*_RB）优于块输出残差写回：在相同的四层 r32 KernelMatrix 状态与相同 S 下，把 Z 送入原 FFN gate/up 的条件融合 C*_RB（C_dual 或 C_up，按 plan2 §7.4 在 RB1 选定）比 R_res 的宏平均至少高 1 pp；确认时该收益在匹配 C*_RB 参数的 LoRA、更宽的 R_res 与 C*_RB 自己的同深度 T0 对照下仍成立。(scope: RB 线、F 线。筛选：RB1-08（C_dual）与 RB1-09（C_up）对 RB1-02；确认：RB5-03/04 对 RB5-01/02，RB5-06/07/09 作参数与历史对照。接口参数不同（C_dual 1,318,912，C_up 925,696，R_res 663,552），不宣称参数效率。V1 proxy 的结论（EV-0048、D-0004）不改写；concat 失败不影响残差主线（plan2 §6A R1.3）。)

- H-0017@1 (supported, active) RB 线新实现正确：因果前缀 KernelMatrix、T0、四层 R_res/concat 与侧支历史干预：向量化因果前缀 KernelMatrix 与已审核的逐 token 参考扫描在输出和梯度上一致；四层 R_res 与 concat 在零出口时与 Base 一致，R_res 只在本块原 FFN 之后加 Z·P_R 且原块每层只执行一次；四层两步梯度启动成立；T0 与侧支历史干预符合定义且不泄漏未来 token；参数计数与 plan2 §15 一致。(scope: RB0（E0）；FP32 小张量用运行前锁定的严格容差，GPU BF16 沿用 E-0001/E-0004 锁定的容差；只检查本线的新路径，已有 V0 与记忆路径测试作回归；不产生任务性能结论。)

- H-0018@1 (challenged, paused) RB1 无信号时一次同布局容量或特征探针（r64/r128 或 raw/activation taps）：若 RB1 的残差与 concat 组都没有信号，而 LoRA 与 T0 正对照可学、实现检查通过，则一次同布局探针（同四层、同 KernelMatrix 与 S1，只把 r 改为 64 或 128；或在 r32 下比较 qknorm_pre_rope、raw 与 SiLU(raw) taps）能让 R_res 达到 Base+1 pp 以上，且不比同布局的近预算 LoRA 低 1 pp 以上。(scope: 只在 RB1 规则 9 触发时释放，一次为限；样本预算取 plan2 §14.3 的 8M 容量/特征储备（例如三臂各 2M）；r 探针配匹配参数的同四层 LoRA；四层 r32 的负结果只界定该配置，不推广到所有低维残差旁路（plan2 §6A R1.3）。)

- H-0019@1 (inconclusive, paused) 分段信息访问：backbone 看不到第 1 段、只有侧支状态跨段时，跨段状态带来可分辨的任务收益（PIQA/BoolQ）：在分段信息访问协议下（每个样本两次 backbone 前向，段间丢弃原 KV、位置重新开始；PIQA 的目标、BoolQ 的文章只在第 1 段；只有四层 r32 KernelMatrix 侧支状态 (M, c, counts) 跨段），保留跨段状态的 R_res S1

在 PIQA dev 上的准确率比同参数无历史的 T0 与同算子段界重置两者中较好的一个至少高 3 pp，并且把第 1 段的状态换成同任务另一样本的状态，至少去掉这部分收益的一半。(scope: 分段 F 线，第三种协议，结果与 F 线、M 线分开登记（plan §2.3）。冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]、r32（预先登记的 r128 配对只条件释放一次）、qknorm_pre_rope、KernelMatrix、inclusive、S1；V1 切分、模板与候选打分；RB1 的训练顺序与样本、RBc 锁定的 LR；seed 0 筛选。PIQA 为主比较，BoolQ 用同一门槛作次要比较。T0 是同参数的当前 token 非线性门控（不是去掉历史的同一注意力），所以另设同算子的段界重置对照。不宣称压缩、长上下文或相对全上下文 LoRA 的实用优势：那需要字节匹配的显式记忆基线与实测延迟。)

- H-0020@1 (inconclusive, paused) 分段协议下 BoolQ 的 r128 跨段状态收益在新 seed 上复现，且超过最强的无历史适配器: 在 E-0025 的分段协议与 r128 配置下（PIQA+BoolQ 混合训练），BoolQ dev 上 Keep 对 max(Reset, T0) 的收益在 seed 0、1、2 上平均至少 +3 pp、两个新 seed 各自为正，swap 平均去掉至少一半收益；并且 Keep 对同 seed 分段 LoRA 的平均差至少 +1 pp。(scope: 分段 F 线，只在 BoolQ 任务层面陈述；冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]、r128、qknorm_pre_rope、KernelMatrix、inclusive、S1；E-0025 的模板、LR 锁定值与训练混合；seed 0 沿用 E-0025，新 seed 1、2；dev 每任务 1,000 条；不开封确认集；不宣称实用价值或长上下文优势；PIQA 只作描述（H-0019 维持 inconclusive）)

- H-0021@1 (inconclusive, paused) RB1-09 改用层输入 X 作投影输入（$\bar{q}$=XA_q，$\bar{k}$=XA_k，$\bar{v}$=XA_v）提高普通设置下的准确率: 在普通（全上下文）RB1 设置下，把 RB1-09（C_up + KernelMatrix S1，r32，四层）的特征来源从 attention 的 q_norm、k_norm 与 v_proj 输出换成该层归一化后的输入 X（input_layernorm 的输出），即 $\bar{q}$=XA_q、$\bar{k}$=XA_k、$\bar{v}$=XA_v，其余不变，dev 宏平均比原 RB1-09（77.50%）至少高 1 pp。(scope: 冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]；r32；KernelMatrix prefix、inclusive、S1；C_up 融合；RB1 的数据、初始化规则、训练顺序、13,115 步与 LR 1e-3；seed 0；dev 每任务 1,000 条；普通设置（backbone 看到全部输入）)

- H-0022@2 (challenged, paused) 把侧支输出比例 η 作为超参数搜索，提高 C_up + KernelMatrix S1 的准确率: 在普通 RB1 设置下，对 C_up + KernelMatrix S1（r32，四层；原 tap 与层输入 X 两种）分别搜索侧支输出比例 η：每个 η 训练到完整长度，按 calibration 宏平均准确率选出 η^*，至少一种 tap 的 dev 宏平均在 η^* 下比同 tap 的 $\eta = 0.25$ 至少高 1 pp。(scope: 冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]；r32；KernelMatrix prefix、inclusive、S1；C_up；LR 固定 1e-3；η 网格 {1/16, 1/8, 1/4, 1/2, 1, 2}，最优在端点时向外扩一次（1/32 或 4）；每个 η 完整长度训练（26,230 个样本，13,115 步），seed 0，同 tap 初始参数相同；η^* 在 V1 calibration（每任务 2,048 条）上选，dev（每任务 1,000 条）只用于判定；普通设置；A2 确认集与官方 validation 不开封)

- H-0023@1 (untested, active) 同一 up 接口下，历史混合输入不比当前 token 输入差（up-only LoRA 对照）: 在普通 RB1 设置下，同四层、只改 up_proj 输入、参数相近的 up-only LoRA（rank56 对 RB1-09，rank48 对 X tap 侧支 X-01）的 dev 宏平均不比对应侧支高 1 pp 以上。成立时，RB1-09 低于 all-7 LoRA r7 的差距主要来自 LoRA 改动的模块更多；不成立时，Z 的输入是历史混合 p_t 而不是当前 U_t 本身就是劣势。(scope: 冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]；up-only LoRA rank56（917,504 参数）对 RB1-09（925,696），rank48（786,432）对 X-01（794,624）；LoRA 的 LR 按 E-0020 短训练规则单独校准；seed 0；dev 每任务 1,000 条；普通设置)

- H-0024@1 (untested, active) A_v 用任务梯度子空间初始化（I-G）提高 C_up + KernelMatrix S1 的准确率: 在普通 RB1 设置下，把 A_v 初始化为 G_F = Σ_t p_t d_t 的前 r 个左奇异向量（p_t 是初始 Q/K 下按核权重混合的未压缩 value 特征，d_t 是 up 加法点的任务梯度），再把每层读出 RMS 匹配到同 tap 的随机初始化参照（Q/K 初值、R_q = R_o =

I、C_u = 0 不变），至少一种 tap 的 dev 宏平均比同 tap 的随机初始化至少高 1 pp。(scope: 四层、r32、S1、C_up、$\eta = 0.25$、LR 1e-3；tap 为原 qknorm_pre_rope（对 RB1-09）与层输入 N（input_layernorm 输出，对 X-01）；G_F 用固定的训练侧校准样本，前后向与 SVD 成本入账；seed 0；dev 每任务 1,000 条；普通设置；LoRA 不做对应的 LoRA-GA 初始化，若侧支因此超过 LoRA 需补这一公平对照)

- H-0025@1 (untested, active) Q/K 配对初始化让侧支读取一开始就按内容相似度加权，提高准确率: 在普通 RB1 设置下，初始化时让 A_q 与 A_k 对齐（层输入 N tap：A_q 复制 A_k；原 tap：A_q = G_group A_k，按 GQA 把每个 KV 组的两个 query 头以 $1/\sqrt{2}$ 聚合），之后两者独立训练，至少一种 tap 的 dev 宏平均比同 tap 的独立随机初始化至少高 1 pp。(scope: 四层、r32、S1、C_up、$\eta = 0.25$、LR 1e-3；A_k、A_v、R_q、R_o、C_u 的初值与随机参照相同，只改 A_q；记录 self 权重、n_eff 与最大权重，区分是否只增强了当前 token 通路；seed 0；dev 每任务 1,000 条；普通设置)

- H-0026@1 (untested, active) 只把 Q/K 换成层输入、保留原 value（N-QK），定位 tap 效应来自寻址还是 value: 在普通 RB1 设置下，$\bar{q}$ = N A_q、$\bar{k}$ = N A_k、$\bar{v}$ = V A_v（N 为 input_layernorm 输出，V 为 v_proj 输出）的 C_up + KernelMatrix S1 的 dev 宏平均比 RB1-09 至少高 1 pp。(scope: 四层、r32、S1、C_up、$\eta = 0.25$、LR 1e-3、RB1 初始化规则；与 RB1-09（原 Q/K 与 V）和 E-0028 的 X-01（N 的 Q/K/V）组成 T、N-QK、N-QKV 三格：N-QK − RB1-09 是寻址来源的效应，X-01 − N-QK 是 value 来源的效应；方案把块输入的残差流记为 X、把 input_layernorm 输出记为 N，S1 下 Q/K 用二者只差有效 ϵ 与参数化（方案 §4.1），E-0028 的 X tap 即方案的 N；seed 0；普通设置)

- H-0027@1 (untested, candidate) 从 up-only LoRA 出发、再学会混入历史读取的混合通路（local + history）: 在普通 RB1 设置下，Δup_t = $\eta[(1-\beta)$U_t A_v + β a_t]R_o C_u（β 为可训练标量，初始 0；C_u = 0）的 dev 宏平均比参数相近的 up-only LoRA 至少高 1 pp，且冻结干预 iv_swap 的降幅 >= 1。(scope: 四层、r32、S1、C_up；起点是当前 token 的 up-only LoRA 参数化，历史读取靠 β 学会混入；只在 H-0023 被 challenge（同一 up 接口下当前 token 输入明显更好）时启用；与 local-only、近参数 LoRA 和 iv_swap 一起解释；普通设置)

- H-0028@1 (untested, candidate) A_v 用历史混合特征的激活子空间初始化（I-A），区分任务对齐与激活能量: 在普通 RB1 设置下，A_v 取历史混合特征 p_t 的未中心化激活 SVD 前 r 个方向（读出 RMS 匹配随机参照），其 dev 宏平均比同 tap 的 I-G 低至少 1 pp：I-G 的收益来自与任务梯度对齐，而不是保留激活能量。(scope: 只在 H-0024 supports 时启用；同 tap、同 Q/K 初值、同校准样本与尺度规则；seed 0；普通设置)

- H-0029@1 (untested, candidate) 分段协议下跨段侧支状态的收益在 A2 确认集上成立（预登记确认，用户同意）: 在分段信息访问协议下，保留跨段侧支状态的组（Keep）在 A2 确认集的 BoolQ 上比同参数无历史的 T0 与段界重置 Reset 中较好的一个更准确：三个新训练 seed 的平均 gain 为正，且其 95% 配对区间的下界大于 0。(scope: 分段 F 线（E-0025、E-0027 的协议、模板与训练混合）；冻结 Qwen3-0.6B-Base，四层 [6,13,20,27]，KernelMatrix S1。侧支配置在开封 A2 之前按 E-0028、E-0029 的 dev 证据选定：有胜出并复现的更强算子时用它，否则沿用 E-0027 的 r128 R_res + KernelMatrix S1。A2（RB 线确认集，每任务 1,000 条）只开封一次，比较、门槛与分析脚本开封前锁定，届时其他需要确认的 RB 线比较放进同一次开封。BoolQ 为主比较，PIQA 只作描述；新 seed 重训（旧 checkpoint 已清理）。只陈述跨段状态的信息收益，不宣称实用价值或长上下文优势。)

2 Related work

目前的记录中还没有核查过的文献条目，因此这里不对相关工作作任何断言。与本工作最直接相关的是同一计划此前的 LoopLora 实现（UnbearableFate/LoopLora @ a255e81）。本研究只把它作为只读的数据重叠核对来源：E-0005 的新数据与其 registry 重叠为 0。本研究没有复现它的结果；冻结 S-RE 诊断因缺少推理资产而暂停（D-0001）。V1 中的 LoRA 只作为参数相近的对照。系统的文献核查留待后续阶段。

- none recorded

3 Method

所有实验都使用 Qwen/Qwen3-0.6B-Base（锁定 revision da87bfb6），BF16 冻结主干、FP32 新参数、eager attention，硬件为 GH200 MIG 2g.24gb；所有工作负载都在 PBS 作业中运行。E-0001 与 E-0004 是不训练的实现检查，容差在检查前由同一 Base 的重复测量锁定（BF16 atol 0.50002，FP32 2e-5），失败后不放宽。E-0002 从 PIQA 与 BoolQ 的官方 train 中切出 train、calibration 与 dev（dev 每任务 1,000 条，官方 validation 封存不读），在三个代表结构上用 0.2M tokens 比较 1e-4 与 3e-4，按 calibration NLL 选学习率，三个家族都选中 3e-4。E-0003 用 seed 0 训练八组：proxy $Z = \mathrm{SiLU}(UA)$（4 层 [6,13,20,27]，r32）分别接 F_out、F_pre、C_gate、C_up、C_dual；线性退化组 $Z = UA$ 接 C_dual；以及 4 层 rank10 与 28 层 rank2 的 LoRA。每组在累计 2M 非 padding 输入 tokens 的那一步停止（13,077 步，batch 2），warmup 5% 后 cosine；主结果用最终 checkpoint，并要求重载后复评逐条一致。主指标是 dev 上 PIQA 与 BoolQ 准确率的宏平均。F*、C*、“有效”与“concat 胜出”的规则都在第一个正式 run 之前写进契约，按点估计判定；配对 bootstrap 区间（10,000 次，按任务分层）只作描述。E-0005 生成 V2 的单跳合成任务（每个 episode 16 条事实、4 种关系、单 token 答案），并在 dev 上评估 Base 的 M 线（只有问题）与 F 线（事实在上下文中）。E-0006 实现 M 线训练与诊断流水线并做冒烟。E-0007 在 calibration 切片上诊断 Base 在 F 线上失败的原因。V2 沿用 M 线协议：support 只写不读，问题阶段丢弃 support 的主干 KV，只保留单层（index 14）、r128、S=1 的低维记忆。E-0008 先训练事实在上下文中的 F 线正对照；E-0009 按家族在 0.2M tokens 上校准学习率（KernelMatrix 1e-2，SoftmaxSlot 3e-3）。E-0010 用 seed 0 训练十组，每组 6,000 步、4,000,470 tokens，按运行前锁定的门槛判定：正常记忆的 EM 同时比清零与打乱记忆高至少 10 pp、NLL 更低、目标权重至少 0.125。它还报告 oracle 与读取诊断，以及 10,000 次配对 bootstrap 区间（只作描述）。E-0012 只做测量，不设自动判定：提取与探针正对照（L0）；冻结第 14 层特征上的线性探针与以目标事实为标签的双线性寻址探针（L1）；训练后与随机初始化投影上的探针（L2）；计划 §8.3 的独立 clean-value 与 read-value ridge 探针（L3）；读取槽位、key 几何与融合幅度（L4）。E-0011 为 V3 生成 T2 链终点数据：每个 episode 有 12 条关系事实组成若干条链，另加 4 条干扰事实；问题给出起点，答案是沿链走到的终点，问题不给出跳数。train 与 dev 只含 1–3 跳，4/6/8 跳的外推切片封存。

记忆路线重开后（D-0012），E-0014 在 V2-03 配置（第 14 层、r128、S=1、direct_hidden、SoftmaxSlot、F_out，LR 3e-3，6,000 步）上做六个单项改动：每个 episode 1 条事实（R1，value 通路正对照）、4 条事实（R2）、事实数课程 1→4→8→16（R3）、先单独训练并冻结的先验通路（R4）、最后问题位置的地址辅助 CE（R5，额外监督）、去中心化余弦寻址（R6），判定沿用 E-0010@2 的门槛。E-0015 只在 E-0014 的 checkpoint 上评估，分离 value 解码侧与寻址侧，其中包括每条事实单独编码后的 oracle 对照。E-0016 检验顾问轮次 1（AD-0001、AD-0002）的三条路线：解码器先行（D1 用 teacher-forced 单槽读取；D2a、D2b 再只用答案 CE 学寻址）、槽位边际似然（D3）、单独编码写入（D4 从零训练；D5 从 R1 的 E=1 checkpoint 续训）。单独编码写入指每条事实不带前文单独过主干，在分隔符处写入 key 与 value，问题侧不变。E-0017 用 seed 1、2 复现 D5。E-0018 不训练，检查 D5 adapter 在 T2 上的迁移，并扫描评估时的读取步数 $S_{\mathrm{eval}} \in \{1, 2, 4, 8\}$。E-0022 是 V3 的训练矩阵：先从 D5 checkpoint 在 T2 一跳问题上训练共同起点（6,000 步，须过 H3 门槛），

再从同一起点训练十组，每组 6,000 步，包括累加读取 S=1/2/4、固定总步长、固定 query 的幅度对照、不读记忆的逐 token 深度、按运算量匹配的更宽 S1（r=152）等。主指标是 T2 dev 上 2–3 跳的 EM，进入 V4 的规则在运行前写定。共同起点只在全问题位置平均目标权重一条上没有过门槛（D-0031），E-0023 因此不改封存的 E-0022，另定答案位置上的准备度规则 R。R 是看到起点的 dev 结果之后制定的，只在此前没有评估过的 T2 calibration 上检查一次。R 成立后先训 S1、S2、S4（V3-01/02/03，各 6,000 步）；选出的循环组（S_M*）比 S1 在 2–3 跳上至少高 3 pp、且 hop1 下降不超过 1 pp 时，才释放其余对照。收益不足时，先用冻结诊断定位失败位置，再按 D-0034 写定的对应关系决定是否做一次修复 pilot。

E-0013（V5 缩减版）在 F 线四层 [6,13,20,27] 上比较 tokenwise C_up（r32）、F_out（r64，两者都是 524,288 个参数）与全 28 层 all-7 rank1 LoRA（630,784 个参数），seed 1–3，各训练 3 个 epoch，每个 arm 按 calibration NLL 选学习率。配置与分析锁定后，PIQA+BoolQ 官方 validation 只开封一次。主比较是 C_up 减 LoRA 的三 seed 平均宏平均差，95% 区间来自配对、按任务分层的 bootstrap（10,000 次）；封存规则规定上界低于 +1 pp 记为 challenged。两个次要比较用 Holm 校正，另报 WikiText NLL 与延迟。

RB 线（D-0025）把侧分支放在四层的残差旁路上：每个 token 用因果前缀 KernelMatrix 读取侧分支自己的历史，读出写回块输出残差（R_res）或接 FFN gate/up；T0 是参数相同但不读历史的对照。确认集 A2 从 V1 train 中每任务分层切出 1,000 条后封存，RB 的训练数据不含这些行。E-0019（RB0）做实现检查与计时，E-0020（RBc）校准四个训练家族的学习率，E-0021（RB1）是首轮筛选。RB0 的 BF16 比较仍用锁定容差 0.50002；跨 GEMM 形状改变（逐 token decode、batch 扩展）的 BF16 比较，若未改动的 reference 给出相同的超出量，只作诊断记录，由同一比较在 FP32 下按逐张量 $\max|a-r| \le 10^{-5} + 10^{-4}\max|r|$ 判定（D-0027）。E-0020 在 calibration 上用三点网格加一次端点扩展，为四个家族各选一个学习率。E-0021 用 seed 0 训练九组：R_res 的 S1（RB1-02）、S2、S4，S4 的固定 query 与 $\eta/4$ 两个幅度与步长对照，同参数的 S1 T0（RB1-01），同四层 all-7 LoRA r7（RB1-07），以及 C_dual 与 C_up 两种 gate/up 融合。各组的初始化与数据顺序相同，训练 2,000,069 个输入 tokens（13,115 步），在 dev 每任务 1,000 条上评估；训练后的 RB1-02 另做冻结的侧支历史干预（swap 换成同任务其他 episode 的历史，permute 打乱历史内的 key/value 配对）。推进门 G0/GR/GC/GL 与规则 9、11 都在运行前写定：规则 11 规定主差值 ≤ 0 记 challenges，为正但低于门槛只作描述。E-0024 不训练，在 RB1 的四个 checkpoint 上测答案位置的读权重落在位置 0 的比例（share0）与跨 episode 的常量读取指数 C（不同 episode 读出向量的平均两两余弦），按预先登记的读法区分 sink（所有集中层 share0 > 0.5 且 C > 0.9）与内容读取（share0 < 0.2）。E-0025 采用分段信息访问协议：每个样本做两次 backbone 前向，段间丢弃原 KV，第 2 段的位置从 0 重新开始；PIQA 的目标与 BoolQ 的文章只在第 1 段，只有四层 r32 侧支状态（M、c 与计数）能跨段（R_keep）。对照是同参数 T0、段界清空状态的 R_reset 与同四层 LoRA r7，训练设置与 RB1 相同。全上下文 LoRA（RB1-07）比分段 LoRA 至少高 3 pp 的任务才算分段拿走了可用信息，主任务优先取 PIQA。主比较是 gain = R_keep − max(T0, R_reset)：gain ≥ +3 pp，且把第 1 段的状态换成同任务另一样本的状态至少去掉一半收益，记 supports；gain ≤ 0 记 challenges；介于两者之间时释放一次 r128 的三组，按 D-0044 判定。E-0026 应用户要求，在 RB1 的普通设置下把 T0 与 R_res 加宽到 r128（各 2,752,512 个参数），对照参数最接近的同四层 all-7 LoRA r31（2,793,472 个参数）；初始化、顺序、步数与 r32 的 LR 锁定值都同 RB1，不另校准；R_res 比 LoRA 低 1 pp 以上记 challenges。E-0027 按 E-0025 规则 8 复现 BoolQ 的 r128 结果：用两个新 seed 重训 r128 的三组与分段 LoRA，训练混合与其余设置同 E-0025，三个 seed 的汇总与判定在运行前锁定。三 seed 平均 gain 至少 +3 pp、两个新 seed 的 gain 都为正、平均 swap 降幅至少为平均 gain 的一半，并且保留状态的组平均比分段 LoRA 至少高 1 pp，才记 supports；平均 gain 低于 +1 pp、两个新 seed 的 gain 都不为正，或平均不高于分段 LoRA，记 challenges。E-0028 与 E-0029 来自用户对 RB1-09（C_up + KernelMatrix S1，r32）的改进方案，都沿用 RB1 的普通设置、初始化规则、训练顺序与步数，只用 seed 0。E-0028 把特征来源从 attention 的 q_norm、k_norm、v_proj 输出换成该层 input_layernorm 的输出（契约中称 X），与 KernelMatrix 和 T0 交叉成 2×2（新训 X-01、X-02、X-03，第四格是 RB1-09）；再在两种特征来源下把侧支输出比例 η

从 1/16 取到 2（最优在端点时再向外扩一次），每个候选都训练到完整长度，按 V1 calibration 的准确率选 η^*，选定之前不汇总这些候选的 dev 结果。E-0029 有八个 arm：A_v 用任务梯度子空间初始化（I-G）的三种特征来源，即在 256 个训练样本上用初始 Q/K 的核权重混合未压缩的 value 特征得到 p_t，与 loss 对 up_proj 输出的梯度 d_t 累积成 $G = \sum_t p_t^\top d_t$，取前 32 个左奇异向量，再按层把读出 RMS 匹配到随机初始化；只把 Q/K 换成层输入、保留 v_proj value 的 Q-N；Q/K 配对初始化的 P-T 与 P-N；以及同四层、只加在 up_proj 上的 LoRA（rank 56 与 48，参数量分别接近 RB1-09 与 X-01），它的学习率按 E-0020 的短训练规则单独校准。两项实验的判定都以 dev 宏平均差 +1 pp 为门槛，在运行前写定。各实验的契约摘要如下。

E-0001 V0 实现与不变量检查

- question: 新侧分支实现能否通过 plan §6.3 的针对性检查（函数保持、两步梯度启动、冻结输入 Jacobian、同核恒等、约束融合恒等、因果、cache、reset/padding、所有权、read/write 计数、M 线信息访问、导出重载），从而可以进入训练？
- intervention: 在 src/ 实现 FeatureTap（qknorm_pre_rope 为主，另有 raw_qkv、direct_hidden；K/V 在 repeat_kv 之前压缩，不重复执行原投影）、LowDimProjection、MemoryBackend（kernel_matrix、kernel_slot_reference、soft_slot；M、c 用 FP32 累积，空记忆显式输出零）、LatentReader（累加与锚定更新，readout=increment 或 full，eta=0.25 与 g=1 固定）、Fusion（F_out、F_pre、F_attnres、C_gate、C_up、C_dual，出口零初始化）、Protocol（M 线 support write-only、query read-only、support 主干 KV 不进 query；F 线 inclusive/strict 因果写入）与 Accounting；原 attention 与原 FFN 每层每次前向只执行一次；用 pytest 在 Miyabi-G 作业中检查
- comparator: 未修改的 Qwen3-0.6B-Base 前向（同输入、同 dtype）；KernelSlot 参考读取；用同一 P 构造的 F_pre；一次 prefill 对分块 prefill 与逐 token decode；固定 query 时的精确幅度关系 Z=S·eta·a·Ro
- metric: plan §6.3 每项检查的 pass/fail；输出与梯度的最大绝对/相对误差对比预先锁定的容差（FP32 严格阈值；BF16 容差由同一 Base 的重复测量锁定，并在检查运行前写入配置）；各参数组的梯度范数；主干参数更新量（应为 0）；write/read/原块调用计数
- scope: Qwen/Qwen3-0.6B-Base（锁定 model 与 tokenizer revision）；F 线 layers [6,13,20,27]、M 线 layer [14]；r ∈ {32,128}；S ∈ {1,2,4}；FP32 小张量参考与真实模型（BF16 主干 + FP32 分支）两种设置；shared→untied 复制恒等推迟到 V3 之前
- contract: E-0001@1, sealed as DOC-0003@1 (research/experiments/E-0001.md)

E-0002 V1 任务切片与家族学习率校准

- question: PIQA+BoolQ（从官方 train 切出 train/dev/calibration，纯文本固定模板）在 4 层 r32 设置下是否处于可学习且未饱和的区间？LoRA、tokenwise 加法、tokenwise concat 三个家族在 calibration 上各取哪个学习率？
- intervention: Base 只评估不训练；三个家族各两个学习率 {1e-4, 3e-4}，每个 run 0.2M 非 padding 输入 tokens，seed 0，相同数据顺序：LoRA（4 层 [6,13,20,27] all-7 rank10）、tokenwise 加法（proxy Z=SiLU(UA) + F_out）、tokenwise concat（proxy Z=SiLU(UA) + C_dual）
- comparator: Base；同一家族的两个学习率之间

- metric: calibration NLL（选择依据，运行前固定）与准确率；Base 与 LoRA 在 dev 上的 PIQA、BoolQ 准确率（地板/天花板检查）；实测吞吐（tokens/s）、每步时间、加载/评估/保存时间与 node·h
- scope: F 线 context-retained；max length 512；AdamW betas (0.9, 0.999)、eps 1e-8、矩阵 weight decay 0.01；warmup 占实际优化步数 5% 后 cosine；global-norm clip 1.0 并记录 pre-clip 范数；dropout 0；PAD 与 EOS 同 ID 时按实际 padding 位置屏蔽；模板、标签 token、候选打分与多 token 标签归一化规则在本实验内固定并写入 release；官方 validation 不开封
- contract: E-0002@1, sealed as DOC-0019@1 (research/experiments/E-0002.md)

E-0003 V1 FFN 融合接口筛选（八组）

- question: tokenwise proxy 下，哪种接口能把低维状态转成任务收益：加法写回（F_out/F_pre）还是 FFN gate/up 条件融合（C_gate/C_up/C_dual）？这种优势是否超出线性退化组与参数相近的 LoRA？
- intervention: V1-01 至 V1-05：proxy Z=SiLU(UA)（4 层 [6,13,20,27]，r32）分别接 F_out、F_pre、C_gate、C_up、C_dual；V1-06：线性 Z=UA + C_dual
- comparator: V1-07：同 4 层 all-7 LoRA rank10（约 0.92M 参数）；V1-08：全 28 层 all-7 LoRA rank2（约 1.26M 参数）；V1-06 线性退化组；Base 只评估
- metric: dev 上 PIQA、BoolQ 准确率及其宏平均（主指标）与 dev NLL；stored、trainable 与实际有梯度的参数数；实测吞吐、wall time 与 node·h；所有 arm 在相同 dev 样本上评估
- scope: F 线；沿用 V1 切片与学习率校准锁定的模板、切分、各家族学习率与优化配方；seed 0 单 seed 筛选（screening），不作确认；max length 512；checkpoint 选择规则在运行前固定且所有 arm 相同；接口间不等参，不宣称参数效率；官方 validation 不开封
- contract: E-0003@2, sealed as DOC-0040@2 (research/experiments/E-0003.md)

E-0004 记忆路径就绪检查（RV-0002 跟进）

- question: V2 用到的记忆路径在分块缓存与支持写入容量两处是否正确：FP32 下 chunk3 的记忆状态是否与整段前向一致；支持写入容量保护是否对所有 backend 一致生效？
- intervention: 按 RV-0002 两条 low 跟进：为 chunk3 比较 cache.memory[14] 的 M、c（slot backend 还有 slots）与整段前向的 FP32 状态，并记录 cache.chunk3.state.max_abs_err；在 visible_fact_delimiter 的 support 阶段，对所有 backend（含 kernel_matrix）执行 counts <= slot_capacity
- comparator: 整段前向的记忆状态；slot backend 已有的容量保护行为
- metric: 检查通过数；chunk3 状态 max_abs_err（FP32 atol/rtol 2e-5，来自已锁定的 tolerances.json）；chunk1 状态误差只作诊断；kernel_matrix 在 slot_capacity=1 时按预期报错
- scope: 单层 index14、r128（V2 默认）与 r32；KernelMatrix、KernelSlot、SoftmaxSlot；GH200 MIG 2g.24gb；容差不改
- contract: E-0004@1, sealed as DOC-0047@1 (research/experiments/E-0004.md)

E-0005 M 线合成任务生成器与 Base 上下限（concat_loop_v2）

- question: 新的 concat_loop_v2 合成关系任务能否按 plan §8.1、§13.1–13.2 的协议确定性生成、与旧 LoopLora 数据不重叠，并且 Base 在 M 线（只有问题）下接近先验基线、在 F 线（支持事实在上下文中）下明显高于先验基线，从而适合 V2 的单跳记忆读取研究？
- intervention: 实现生成器、episode registry 与切分；生成 V2 的 T1 单跳任务（E=16 个支持事实、4 种关系、固定公开渲染模板、单 token 答案）：train、calibration 2,048、dev 1,000，以及只登记身份与哈希的封存 confirmation 2,000；多跳（训练/dev hops 1–3，封存外推 hops 4/6/8）只实现接口与身份；Base 只在 dev 上评估 M 线与 F 线
- comparator: 旧 LoopLora registry（UnbearableFate/LoopLora @ a255e81，只读）；先验基线（按 train 答案频率的最佳常数答案）；M 线 Base 对 F 线 Base
- metric: 两次生成哈希一致；各 split 的 episode 身份互不相交；与旧 registry 重叠为 0；答案都是单 token；各轴统计（关系、事实数、干扰项、文本长度、名字池与 tokenization 长度、支持顺序）；每条事实恰好一个写入分隔符位置；Base dev 的完整词表 EM 与答案 NLL（M 线、F 线）
- scope: study_id=concat_loop_v2，phase V2；seed 由 derive_seed(20261029, "concat_loop_v2", phase, purpose) 派生，derive_seed 与 T-0002 的定义相同；write_scope=visible_fact_delimiter，read_scope=all_valid_question；不训练；封存切片不做任何模型评估；GH200 MIG 2g.24gb
- contract: E-0005@1, sealed as DOC-0048@1 (research/experiments/E-0005.md)

E-0006 V2 M 线训练与诊断流水线（实现与冒烟）

- question: 按 plan §8.1 的 M 线协议（support write-only、query read-only、单层 index14、r128、S=1）实现的训练与评估流水线，以及 §8.3、§8.4 规定的诊断，是否在小规模冒烟中行为正确（初始化时与 Base 相同、梯度按预期流动、因果对照与 oracle 开关按定义改变读出）?
- intervention: 实现 M 线训练/评估入口：support 阶段只写、问题阶段从同一只读快照读取、按 episode owner 索引、单 token 答案 CE、完整词表 EM 与 NLL；§8.3 诊断（寻址 top-1、margin、目标权重、熵、n_eff，读误差，输出范数，数值统计）；zero / shuffled / permuted memory 因果对照；§8.4 oracle 开关（真实 key 替换 query、直接提供目标 value、zero memory、其他 episode 的 memory，只作离线评估）
- comparator: Base（出口零初始化时应与之完全相同）；正对照小任务上 normal memory 对 zero memory
- metric: 检查通过数；初始化时与 Base 的 logits 差；各控制与 oracle 开关的读出变化；冒烟步时、显存与吞吐（为记忆家族校准与 V2 估算成本）
- scope: 特征 direct_hidden 与 qknorm_pre_rope；读算子 KernelMatrix 与 SoftmaxSlot（g=1，s0=sqrt(dk)，tau=1）；融合 F_out 与 C_dual；write_scope=visible_fact_delimiter，read_scope=all_val
  GH200 MIG 2g.24gb；只做冒烟，不做正式训练
- contract: E-0006@1, sealed as DOC-0053@1 (research/experiments/E-0006.md)

E-0007 F 线 Base 难度诊断（concat_loop_v2）

- question: E-0005 中 Base 的 F 线 EM 接近先验（dev 1.3%，先验 1.5%）；协调者只读核查已有预测，dev 上 F 线 argmax 有 94.4% 是问题主语，M 线为 76.7%。Base 是在上下文中找到了正确实体、只是被复制问题主语的倾向压过，还是在 E=16 时根本没有找到？失败是否来自提示格式或评估实现？
- intervention: 在 calibration 切片上沿用 E-0005 的 Base 提示与评分路径，逐条输出完整词表 top-5、正确答案的秩与概率、问题主语的概率与 top-1 类别；计算限定候选准确率；F 线另做事实数梯度 E ∈ {1,2,4,8,16}：保留被问事实，其余事实按派生 seed 确定性抽取并保持原相对顺序，用生成器原模板重新渲染
- comparator: E-0005 的 Base dev 结果（M 1.1%、F 1.3%、先验 1.5%）；同一 calibration 上的 M 线；按候选数计算的随机基线；E=1 作为最容易的正对照
- metric: 完整词表 EM 与答案 NLL；正确答案的秩与概率；问题主语复制率；top-1 类别分布；限定候选准确率：(a) 支持中出现的全部不同名字，(b) 同一集合去掉问题主语，(c) 与被问事实同关系的事实的不同尾实体；按 E、被问事实位置、关系、support_order 与 answer_frequency_stratum 分层
- scope: 只用 Base（Qwen3-0.6B-Base @ da87bfb608c14b7cf20ba1ce41287e8de496c0cd），不训练；只用 calibration 切片（runs/ATT-0039-1/data/calibration.jsonl，sha256 c08753365165216b5a9f4c3d629
dev 不再评估，confirmation 不读取；E 变体只是诊断视图，不是新切分；不改 E-0005 的协议、模板与数据；diagnostic 证据，不支持也不挑战 H-0003
- contract: E-0007@2, sealed as DOC-0063@2 (research/experiments/E-0007.md)

E-0008 V2 F 线训练后正对照（事实在上下文中）

- question: 在与 V2 M 线相同的数据、样本顺序与 4M 输入 tokens 预算下，事实放在上下文中、只用答案 CE 训练的标准 LoRA，能否在 E=16 的单跳任务上明显超过先验？即任务本身在该规模与预算下是否可学，从而 M 线结果可以解读。
- intervention: LoRA（4 层 [6,13,20,27]，all-7 模块，rank 10，与 V1-07 相同布局）接在冻结 Base 上；F 线提示 = support_text + question_text（与 E-0005/E-0007 的 F 线评估相同），只在答案位置计算 CE；学习率在 {1e-4, 3e-4, 1e-3} 上各跑 0.2M tokens，按 calibration 答案 NLL 选择；选中后跑完整的 4M tokens
- comparator: E-0005/E-0007 的未训练 Base F 线（calibration EM 1.42%，E=16）；按 train 答案频率的最佳常数答案（先验基线）
- metric: calibration 与 dev 上的完整词表 EM 与答案 NLL；答案不等于问题主语的子集上的 EM；问题主语复制率；学习曲线；吞吐、wall time 与 node·h
- scope: concat_loop_v2 V2 数据（E-0005，train 16,384 / calibration 2,048 / dev 1,000）；seed 0；F 线结果单独登记，不替代 M 线；confirmation 不读取；只作为 V2 的正对照与第二步的放行门槛
- contract: E-0008@1, sealed as DOC-0086@1 (research/experiments/E-0008.md)

E-0009 V2 记忆家族学习率校准与正式 M 线训练程序

- question: 正式 M 线训练程序（4M token 日程、对照评估、checkpoint 重载）能否正确运行？在 V2 共同配方下，KernelMatrix 与 SoftmaxSlot 两个读算子各应使用哪个学习率？
- intervention: 实现正式 M 线训练程序（复用 E-0006 的 collate、train_forward、evaluate_batch 与对照，加入 C_up）；代表配置 qknorm_pre_rope + F_out（层 14，r128，S=1）分别接 kernel_matrix 与 soft_slot，学习率 {3e-4, 1e-3, 3e-3} 各跑 0.2M tokens
- comparator: 同一 run 中 zero memory 与 shuffled memory 的 calibration 答案 NLL（诊断）；E-0006 的冒烟结果
- metric: calibration 答案 NLL（normal memory，选择依据）；zero 与 shuffled 的 NLL 与 EM（诊断）；梯度范数与裁剪比例；吞吐、显存、wall time 与 node·h
- scope: concat_loop_v2 V2 数据；seed 0；V2 共同训练配方（E-0008 Design 段）；校准只选学习率，不作 H-0003 的证据；选中的学习率用于 E-0010 中同一读算子的全部 arm（包括 C_dual 探针）
- contract: E-0009@1, sealed as DOC-0087@1 (research/experiments/E-0009.md)

E-0010 V2 M 线单跳记忆读取：2×2×2 析因与 C_dual 探针

- question: M 线（问答阶段丢弃 support 主干 KV，只保留低维 memory）下，哪种特征 × 读算子 × 融合组合能让 learned memory 读取产生可用信号（normal memory 明显优于 zero 与 shuffled）? SoftmaxSlot 是否比 KernelMatrix 读得更集中、更可用？
- intervention: 十组：特征 direct_hidden / qknorm_pre_rope × 读算子 kernel_matrix / soft_slot × 融合 F*=F_out / C*=C_up（V2-01 至 V2-08），以及 qknorm_pre_rope × {kernel_matrix, soft_slot} × C_dual 交互探针（V2-09、V2-10）；层 14，r128，S=1，只用答案 CE，每组 4M 输入 tokens
- comparator: 同一 checkpoint 的 zero memory、shuffled memory 与 permuted association；E-0008 的 F 线训练后正对照；key/value oracle（诊断）；先验基线
- metric: dev 上 normal/zero/shuffled/permuted 的完整词表 EM 与答案 NLL（主指标为 normal 对 zero 与 shuffled 的 EM 差与 NLL 差）；读取诊断（目标权重、n_eff、熵、读误差）；答案 ≠ 问题主语子集上的 EM；学习曲线；参数数、吞吐、wall time 与 node·h
- scope: concat_loop_v2 V2 数据（E-0005），seed 0 单 seed 筛选，不是确认；V2 共同训练配方（E-0008 Design 段）；各读算子的学习率来自 E-0009；判定规则在任何 V2 run 之前锁定；M 线结果与 F 线正对照分开登记；不替代旧 writer 的 80% gate；confirmation 不读取
- contract: E-0010@2, sealed as DOC-0083@2 (research/experiments/E-0010.md)

E-0011 V3 T2 链终点任务生成器、登记与难度检查

- question: 能否按 plan §9.1、§13.1–13.2 确定性地生成 V3 的 T2 链终点任务（训练/dev 只含 hops 1–3，封存 hops 4/6/8 与未见名字），与 V2 数据和旧 registry 不重叠，结构捷径留有余量，并且 M 线 Base 接近先验、F 线 LoRA 小 pilot 能学会 hops 1–3？

- intervention: 新模块 src/v3_data.py（不改 src/v2_data.py）：phase 参数化的 T2 链终点生成器、episode registry 与切分；生成 phase V3 的 train/calibration/dev，并登记封存切片的身份与哈希；计算无模型的结构捷径基线；Base 在 dev 上评估 M 线与 F 线；F 线 LoRA 小 pilot（复用合并后的 src/v2_fline.py，0.2M tokens）

- comparator: 先验基线（train 最佳常数答案）；无模型结构捷径基线（随机 r 终点猜测、忽略关系类型走到底、最长 r 链终点、支持中最后出现的 r 终点）；V2 T1 数据（ATT-0039-1）与旧 LoopLora registry 的内容哈希

- metric: 两次生成哈希一致；身份与语义内容在切片内外互不重复，与 V2 和旧 registry 重叠为 0；单 token 答案与答案边界检查；各轴统计（hop、链长构成、r 链数、干扰事实位置、支持顺序、名字频率层、tokens）；每个 hop 的结构捷径 EM；M 线 Base 与 F 线 Base 的 dev 完整词表 EM/NLL（分 hop）；LoRA pilot 的 calibration EM/NLL（分 hop）；node·h

- scope: study_id=concat_loop_v2，phase V3；derive_seed(20261029, "concat_loop_v2", "V3", purpose)；write_scope=visible_fact_delimiter；E=16；只用 V2 的 seen 名字池（unseen 只用于封存切片）；封存切片不做任何模型评估；不训练 M 线；GH200 MIG 2g.24gb

- contract: E-0011@2, sealed as DOC-0097@2 (research/experiments/E-0011.md)

E-0012 V2 记忆失败层次定位（表示探针与寻址几何）

- question: E-0010 十组都没有读出 episode 记忆（value oracle 也无效）。在 M 线的各层次上，答案相关信息的线性可解码性在哪里下降：冻结第 14 层特征（写入位置的尾实体、问题特征对目标事实的寻址）、训练后的 key/value/query 投影、学到的目标 value（clean-value probe）、实际读取向量（read-value probe），以及读取的槽位与融合幅度？测量结果供协调者选择 plan §8.4 允许的唯一探针，或以预期价值有限为由停止扩大记忆路线。

- intervention: 不训练 M 线：L0 提取与探针正对照；L1 冻结 Base 第 14 层特征（direct_hidden；qknorm_pre_rope 的 q_norm/k_norm 与 v_proj 输出）上的线性探针与双线性寻址探针（秩 128/256/512/满秩）；L2 E-0010 十个 checkpoint 与随机初始化投影的 key/value/query 探针；L3 plan §8.3 的独立 clean-value 与 read-value 探针（src/v2_probe.py 路径）；L4 读取槽位分布、key 几何与融合输出幅度

- comparator: 随机水平（名字 1/92，关系 1/4，寻址 1/16）与按 train 频率的常数基线；L0 正对照；随机初始化投影对训练后投影；E-0010 的 oracle 与读取诊断

- metric: calibration 上各探针的 top-1 准确率（按层次、特征集、位置、目标与秩，附正确数与样本数）；clean_to_clean、read_to_read、clean_to_read；读取 argmax 槽位分布；episode 内 key 两两余弦与目标 margin；问题位置融合输出范数与第 14 层残差范数之比；node·h

- scope: V2 T1 数据（ATT-0039-1）train、calibration 与 dev，seed 0；不读 confirmation；不训练 M 线，不改 E-0010 结论；只作诊断测量

- contract: E-0012@1, sealed as DOC-0117@1 (research/experiments/E-0012.md)

E-0013 V5 缩减版：tokenwise 简单接口对强 LoRA 的实用确认（PIQA+BoolQ 官方 validation）

- question: 记忆路线停止（D-0008）后，按 plan §14.2 把 V5 收缩为简单接口对比：F 线 4 层 [6,13,20,27] 的 tokenwise C*（C_up，r32）在 PIQA+BoolQ 官方 validation 上，宏平均准确率是否比全 28 层 all-7 rank1 LoRA 高至少 1 pp，且每个任务不低于 -1 pp？与 C* 等参数的

加法接口 F*（F_out，r64）和两者相比如何？各自的代价（参数、可合并性、训练时间、推理延迟、WikiText-103 NLL）是多少？

- intervention: 三个 arm 各用 3 个新 seed（1,2,3）独立训练：C_up r32 tokenwise SiLU（524,288 参数）；F_out r64 tokenwise SiLU（524,288）；LoRA 全 28 层 all-7 rank1（630,784，alpha=rank）。沿用 V1 的切分、模板、候选打分与 max_length 512；每 run 正好 3 epochs（约 4.46M 非 padding 输入 tokens），有效 batch 2；学习率按预登记网格逐 arm 在 calibration NLL 上选择；只用最终 checkpoint。未训练 Base 作参照

- comparator: 主比较：LoRA28 all-7 rank1（强基线，参数多约 20%）；次要：F_out r64（与 C_up 等参数的加法接口）；参照：未训练 Base

- metric: 官方 validation 上 PIQA、BoolQ 准确率与宏平均（主），seed 平均差、各 seed 差与配对分层 bootstrap 95% 区间；次要比较的 Holm 校正；dev 准确率与 NLL（只作监控）；WikiText-103 test NLL 相对 Base 的变化；可训练参数、可合并性、训练时间、峰值显存、推理延迟；node·h

- scope: F 线（保留原 attention）、Qwen3-0.6B-Base、V1 的 train/dev/calibration 切分与模板；官方 validation 封存，配置、训练规则与分析脚本锁定后只开封一次；3 个训练 seed；参数接近但不相等，不宣称同时等参数、等计算或等状态；不含侧支历史、记忆与多次读取；V1 已用这些任务的 train/dev 选择接口，不称零调参迁移；LoRA 结论只针对 rank1 与本合同的短校准 LR 规程，不代表所有合理的 LoRA 配置或完整训练长度上的最优调参；区间以三个训练 seed 为条件

- contract: E-0013@3, sealed as DOC-0128@3 (research/experiments/E-0013.md)

E-0014 记忆路线修复筛选：事实数、课程、先验吸收、寻址监督与去中心化余弦寻址

- question: V2 的失败是否主要来自训练动态？以 V2-03（direct_hidden、SoftmaxSlot、F_out）为基础，分别改变 (a) 每个 episode 的事实数（E=1、E=4），(b) 事实数课程 1→4→8→16，(c) 先训练并冻结一条吸收答案先验的通路，(d) 对最后问题位置的地址权重加辅助交叉熵（额外监督），(e) 去中心化余弦寻址加可学温度。哪些能在 E=16 dev 上达到 H3 门槛？E=1 能否说明 value 的写入、读取、解码通路本身可用？

- intervention: 六个 arm，seed 0，M 线第 14 层 r128 S=1，direct_hidden 特征，SoftmaxSlot，F_out 融合，LR 3e-3（E-0009），步数与 batch 同 V2（6000 步，每步 8 个 episode），只用最终 checkpoint：R1 E=1；R2 E=4；R3 课程 E 1→4→8→16；R4 先验通路（第 14 层 tokenwise F_out r32，先在零记忆下单独训练 1000 步后冻结）+ E=16；R5 E=16 + 地址辅助 CE（λ=1，额外监督）；R6 E=16 + 去中心化余弦寻址与可学温度

- comparator: V2-03（E-0010，ATT-0082-1）作参照；每个 arm 内的 zero、shuffled、permuted、oracle_key、oracle_value 记忆对照；R1 作 value 通路正对照

- metric: E=16 dev：EM 与 NLL（normal/zero/shuffled/permuted/oracle），目标事实平均地址权重，n_eff，最后问题位置的 argmax 槽位分布，融合增量与残差范数之比；R1/R2/R3 另报各自 E 的 dev；训练曲线；node·h

- scope: M 线 T1 hop 1；E=16 沿用 V2 数据（ATT-0039-1），E $\in$ {1,4,8} 为新登记的数据版本（新 seed 命名空间）；单 seed 筛选；额外监督只在 R5，结论单独陈述；不读 confirmation；不改 V2 结论与 E-0010 判定

- contract: E-0014@1, sealed as DOC-0135@1 (research/experiments/E-0014.md)

E-0015 记忆路线诊断：value/解码侧与寻址侧的分离（E-0014 checkpoint 上只做评估）

- question: E-0014 多事实配方的失败落在哪一侧？训练出的 value 是否仍携带尾实体信息？非末位问题位置的混合读取是否干扰解码？E=1 学到的 value 映射能否迁移到多事实上下文？
- intervention: 只做评估，不训练：E-0014 的 R1（ATT-0122-1）、R2（ATT-0123-1）、R5（ATT-0126-1）和 V2-03（ATT-0082-1）的最终 checkpoint，在 E=1、E=4、E=16 calibration 上加新的读取替换对照（last_only、oracle_last、oracle_last_only、uniform、last_only_shuffled、wrong_oracle）、增量幅度扫描、单独编码替换（每条事实单独编码后放回原槽位：iso_kv、iso_v、iso_oracle_value）、按目标位置分层，以及线性探针（训练出的 value、冻结特征、最后位置的融合增量；上下文编码与单独编码各一次）
- comparator: 同一 checkpoint、同一 split 的 normal 读取；已有的 zero、shuffled、oracle_value 对照；冻结特征探针作参照
- metric: 每个 checkpoint×split× 对照的 EM 与 NLL（calibration，按目标位置分层）；探针在 calibration 上的准确率（train 前 4,096 条上拟合）及其基线；重新加载后 dev 上的 normal 预测须与 E-0014 记录逐例一致
- scope: M 线 T1 hop 1；诊断只用 train 与 calibration，dev 只用于加载一致性检查，不读 confirmation；数据为 ATT-0039-1（E=16）与 ATT-0112-1（E=1/4）；单 seed 的已有 checkpoint；只产出 diagnostic 证据，不改变任何假设状态
- contract: E-0015@4, sealed as DOC-0157@4 (research/experiments/E-0015.md)

E-0016 记忆路线训练筛选：解码器先行、槽位边际似然、单独编码写入（顾问轮次 1 的三条路线）

- question: 在 E=16 上下文里，value→ 答案的解码器能否在干净读取下学成？之后寻址能否只从答案 CE 发现？把训练目标改成槽位隐变量的边际似然能否避免塌缩？每条事实单独编码后写入能否消除上下文迁移并让单跳读取可用？
- intervention: seed 0，E=16（ATT-0039-1），V2-03 基础配置（direct_hidden、SoftmaxSlot、F_out、第 14 层 r128 S=1、LR 3e-3），每段 6000 步 ×8 episode。D1：teacher-forced 单槽读取（记忆只留目标槽位，额外监督）；D2a/D2b：从 D1 续训，恢复全部槽位，只用答案 CE（D2a 只训练寻址参数，D2b 全部训练）；D3：槽位隐变量边际似然，只在最后问题位置读取，不用标签；D4：每条事实单独编码后写入，从零训练；D5：单独编码写入，从 R1（ATT-0122-1）续训。D4/D5 以 E-0015 规则 5 成立为前提
- comparator: V2-03（ATT-0082-1）与 E-0014 各 arm；每个 arm 内的 zero、shuffled、permuted、oracle 对照；D1 另有 teacher-forced 的 shuffled 与错误槽位对照；D3 另报软读取
- metric: E=16 dev：EM 与 NLL（各对照），目标权重（全问题位置平均与最后位置），最后位置 argmax 分布，按目标位置分层；D1 的 teacher-forced 门槛；D3 的硬读取门槛；训练曲线；node·h
- scope: M 线 T1 hop 1；单 seed 筛选；D2a/D2b 的配方在 D1 用了目标索引，结论注明；D3 的硬读取与只读最后位置、D4/D5 的单独编码写入都是新登记的协议，与 E-0010 的统计量分开报告；不读 confirmation；不改 V2 与 E-0014 的结论
- contract: E-0016@1, sealed as DOC-0160@1 (research/experiments/E-0016.md)

E-0017 记忆路线：E=1 预训练加单独编码写入（D5 配方）的 seed 复现

- question: D5 在 seed 0 上达到单独编码写入协议下的 H3（EV-0095）。换成 seed 1、2，从各自重新训练的 R1（E=1）出发走完整个配方，是否同样达到？
- intervention: 主流程 P1、P2（s=1、2）：阶段 A 按 E-0014 的 R1 配方，用 seed s 在 E=1 上训练 6000 步；阶段 B 按 E-0016 的 D5 配方，从阶段 A 的最终 adapter 续训 6000 步，单独编码写入，E=16。次要 C1、C2：从 R1 seed 0（ATT-0122-1）出发，续训 seed 取 1、2，其余同 D5，用来区分阶段 A 与续训的随机性
- comparator: 每个 run 内单独编码写入下的 zero、shuffled、permuted、oracle_key、oracle_value 对照；E-0016 的 D5（seed 0，EV-0095）与 D4（EV-0096）
- metric: E=16 dev（1000）单独编码写入下的 EM 与 NLL、目标权重（全问题位置平均与最后位置）、n_eff，按目标位置分层；阶段 A 在 E=1 dev 的 normal、zero、shuffled；E=16 calibration 与上下文编码下的描述性对照；学习曲线；node·h
- scope: M 线 T1 hop 1；单独编码写入协议：每条事实不带前文编码后写入，问题侧不变，与 E-0010 的统计量分开报告；配方含 E=1 预训练阶段，只用答案 CE，不用地址标签；screening；不读 confirmation
- contract: E-0017@1, sealed as DOC-0180@1 (research/experiments/E-0017.md)

E-0018 V3 前置：单独编码写入下 T2 链终点任务的读取迁移、无训练深度扫描与循环实现检查

- question: D5 配方训练的单读 adapter（seed 0、1、2）在 T2 链终点任务的 dev 上，按单独编码写入，hop1 能否读到目标事实并答对？不训练时把读取次数扩展到 S_eval=2/4/8，hops2–3 的 EM 与每步对路径上各跳目标事实的地址权重怎样变化？固定记忆、累加更新的 S>1 循环在单独编码写入与 T2 数据上实现是否正确，训练步耗时多少？
- intervention: E0：在单独编码写入的 M 线代码中接入 E-0011 的 T2 链终点数据（phase V3，只用 train/calibration/dev）与 S>1 累加循环（同一问题位置各步共享固定记忆 M，z 按 plan §3.5 累加），新选项默认关闭，关闭时输出与梯度同 master；S=1 时与现有 D5 评估路径逐例一致。E1 只评估：ATT-0159-1（seed 0）、ATT-0172-1（seed 1）、ATT-0173-1（seed 2）的最终 adapter，在 T2 dev 1000 上，S_eval ∈ {1,2,4,8}。计时：T2 上 S=1/2/4 的训练步冒烟各约 100 步，不作证据
- comparator: E-0011 的先验与结构捷径基线及 M 线 Base；每个 adapter 内的 zero、shuffled、permuted 对照，hop1 另报 oracle_key、oracle_value；S_eval=1 作各 adapter 的参考
- metric: 分 hop（1、2、3）的 EM 与 NLL（各对照）；每步对路径上第 j 跳目标事实的地址权重、argmax 槽位分布与 n_eff；各步 query 余弦、状态与读出范数；训练步耗时、峰值显存；node·h
- scope: M 线，单独编码写入协议（须声明的结构化支持输入，统计量与 E-0010 分开报告），H-0012 的 D5 配置；T2 链终点 phase V3 的已发布切片，封存切片（confirmation、ood_h4/6/8、ood_unseen）不做任何评估；只评估已有 adapter，不训练（计时冒烟除外）；diagnostic；不读 confirmation
- contract: E-0018@1, sealed as DOC-0202@1 (research/experiments/E-0018.md)

E-0019 RB0：残差旁路线实现与计时（因果前缀 KernelMatrix、T0、四层 R_res/concat、侧支历史干预）

- question: plan2 主线需要的新 F 线路径是否正确、训练成本是否可承受：向量化因果前缀 KernelMatrix 与已审核的逐 token 参考扫描在输出与梯度上是否一致？T0、固定 query、四层 R_res 与 concat 的零出口、残差拓扑、两步梯度启动、因果、cache、padding 与侧支历史干预是否按定义工作？各 RB1 arm 的实测步时与 node·h 是多少？

- intervention: 新增并测试（默认行为不变）：KernelMatrix 向量化因果前缀实现（impl=prefix）；T0 分支（branch=kernel_tokenwise，与 KernelMatrix 分支同参数）；AdapterConfig 的 fixed_query 与 impl；F 线推理期侧支历史干预（iv_off、iv_window1/8、iv_strict、iv_swap、iv_permute、当前 token 读权重）；RB 训练入口（arm 表与参数断言、residual_la_v21 种子、2M tokens/3 epochs 日程、LR 校准模式）；latency 脚本；按 D-0025 的方案 A2 生成 RB 确认集切分清单（从 V1 train 每任务切 1,000 条；不做任何模型评估）。不训练正式模型

- comparator: 已审核的逐 token 参考扫描 process_sequence 与 KernelSlotReference；未修改的 Base（零出口）；E-0001/E-0004 已有的不变量测试作回归；V1 tokenwise arm 的实测 0.183–0.194 s/step（research/notes/T-0003-tables.md）作计时参照

- metric: 前向输出与对 $\bar{q}/\bar{k}/\bar{v}$/Rq/Ro 的梯度的最大绝对、相对误差；四层零出口 logits 与 Base 的差；拓扑、因果、cache、padding、重排、写读计数、导出重载与干预恒等各项通过/失败；故意破坏的实现被拒绝；stored/trainable/有梯度参数；$\geq$100 个稳定步的 s/step、tokens/s、峰值显存；按 plan2 §14.4 推算的每个 RB1 arm 与 RB5 run 的 node·h

- scope: F 线（context-retained）、冻结 Qwen3-0.6B-Base、四层 [6,13,20,27]、r32（另核对 r44、r64 参数计数）、qknorm_pre_rope；实现与计时检查，不产生任务性能结论；FP32 容差在运行前写进测试，GPU BF16 容差沿用 E-0001/E-0004 的锁定值，不看结果后放宽；计时作业在 2g.24gb 上 fail-fast，其它作业的 MIG guard 只记录（D-0019）

- contract: E-0019@1, sealed as DOC-0203@1 (research/experiments/E-0019.md)

E-0020 RBc：残差旁路线四个训练家族的学习率校准（LoRA4 r7、T0、R_res+KernelMatrix、C_dual+KernelMatrix）

- question: 在 RB1 的数据、模板与优化配方下，四个训练家族（同四层 all-7 LoRA rank7；R_res+T0 S1；R_res+KernelMatrix S1；C_dual+KernelMatrix S1）的学习率按预登记规则应锁定为多少？

- intervention: 每家族 seed 0 短训练，到首次累计达到 200,000 非 padding 输入 tokens 的完整步为止（同 V1、E-0013）；初始网格：LoRA 与 T0 为 {1e-4, 3e-4, 1e-3}，R_res+KernelMatrix 与 C_dual+KernelMatrix 为 {3e-4, 1e-3, 3e-3}；初始网格的原始最小 NLL 在上端或下端时追加一个端点（LoRA/T0：3e-3 或 3e-5；两个 KernelMatrix 家族：1e-2 或 1e-4），只扩一次

- comparator: 同家族候选互比。plan2 §6.4 的建议点（LoRA/逐 token {1e-4,3e-4}，记忆 {3e-4,3e-3}）都在初始网格内；E-0002（V1 三族 3e-4，停在网格上端）、E-0013 校准（三个 arm 都是 1e-3）与 E-0009（M 线 KernelMatrix 1e-2）只作先验参照，不沿用

- metric: RB calibration 子集上的 NLL（V1 定义：各任务 gold CE 按 token 求和后取任务均值，再取两任务算术平均）；非有限值；每个候选的步数、tokens、步时与 node·h

- scope: F 线；RB 数据（V1 切分 split map SHA256 47cf5c777d07863b8def6903487697eafc970b0cd5b5d80babb
模板、max_length 512；calibration 用完整的每任务 2,048 条；train 为 V1 train 去掉 RB 确

认集行，D-0025 方案 A2）；优化配方同 RB1；初始化与训练顺序用 derive_seed(20261101, "residual_la_v21", "V0", "init"|"train", 0)；不看 dev 与任何确认集；锁定结果用于 RB1：LoRA→RB1-07，T0→RB1-01，R_res+KernelMatrix→RB1-02..06，concat→RB1-08、RB1-09；共 2.4–3.2M tokens，超出 plan2 §6.4 的 2M 部分记入 §14.3 储备

- contract: E-0020@1, sealed as DOC-0231@1 (research/experiments/E-0020.md)

E-0021 RB1：残差旁路低维因果 linear attention 首轮筛选（plan2 R1 八组 + C_up 核对）

- question: 保留原 attention 的 F 线上，四层 r32 的块输出残差旁路 R_res + 真实因果 KernelMatrix（S1）是否带来任务收益（对 Base、同参数无侧支历史的 T0、近预算同四层 LoRA）？同一旁路里 S2/S4 是否有超出幅度与总步长解释的初步信号？在同一 KernelMatrix 状态上，FFN gate/up 条件融合（C_dual、C_up）是否改善写回？

- intervention: 九个训练 arm，seed 0：RB1-01 R_res+T0 S1；RB1-02 R_res+KernelMatrix S1；RB1-03 同 S2；RB1-04 同 S4；RB1-05 S4 且 query 固定为第 1 步；RB1-06 S4 且 η=0.25/4；RB1-07 同四层 all-7 LoRA rank7；RB1-08 C_dual+KernelMatrix S1；RB1-09 C_up+KernelMatrix S1（plan2 无此组，用于核对 V1 的 C*=C_up）。共同：四层 [6,13,20,27]、r32、qknorm_pre_rope、inclusive 先写一次再读、η=0.25 与 g=1 固定、readout 为循环增量、出口零初始化；Base 只评估。训练后对 RB1-02、S_F* 对应的 arm、RB1-08、RB1-09 做冻结侧支历史干预

- comparator: Base（只评估，评估代码不变时沿用 ATT-0024-1/EV-0022）；RB1-01（同参数、无侧支历史）；RB1-07（630,784 参数，比 R_res 少 4.94%）；循环对照 RB1-05/06；concat 对照 RB1-02

- metric: dev（每任务 1,000 条）上 PIQA、BoolQ 准确率与宏平均（主）及答案 NLL；25/50/75/100% 的 dev 曲线；冻结干预下的 dev 宏平均变化、当前 token 读权重与读权重的 n_eff 和熵（定义同 M 线）；描述性配对分层 bootstrap 95% 区间（10,000 次，seed 20261101，各 arm 共用索引）；stored/trainable/有梯度参数；每 token 读写次数与原块调用数；峰值训练显存；prefill 吞吐、decode p50/p95；新增状态字节（M+c FP32 r32 为 4,224 字节/层/序列）；node·h

- scope: F 线、冻结 Qwen3-0.6B-Base、四层 r32、qknorm_pre_rope、KernelMatrix（不换 SoftmaxSlot）；V1 切分、模板与候选打分，max_length 512，按 E-0003 排除不可编码的 train 行；单 seed 筛选，不作确认；所有 arm 相同的样本预算与训练顺序 derive_seed(20261101, "residual_la_v21", "R1", "train", 0)：累计非 padding 输入 tokens 首次达到 2M 的完整步（或 3 epochs，先到为准）；LR 来自 RBc；最终 checkpoint；接口参数不等，不宣称参数效率；T0 只有 S1，不能排除 S4 的逐 token 深度解释；任何确认集都不开封

- contract: E-0021@1, sealed as DOC-0235@1 (research/experiments/E-0021.md)

E-0022 V3：T2 链终点上的循环矩阵（共同起点阶段 + plan §9.2 十组，单 seed 筛选）

- question: 在单独编码写入协议与 D5 配方下，先经共同起点阶段使 T2 hop1 达到 H3，再从同一起点训练十组：累加循环 S2/S4 在 T2 hops2–3 上是否优于独立训练的 S1，且该差不被固定 query 的幅度、匹配预算的更宽 S1 与同源 tokenwise 核解释？

- intervention: 起点阶段：从 D5 seed 0 adapter（ATT-0159-1）按 D5 续训配方在 T2 hop1 上续训全部侧支参数 6,000 步（同 D5 每段步数），取最终 checkpoint 作共同起点。十组（plan

§9.2）：V3-01 累加 S1；V3-02 S2；V3-03 S4；V3-04 S4 且 η=0.25/4；V3-05 S4 且 query 固定为第 1 步；V3-06 同源 tokenwise 核 S4；V3-07 更宽 S1（r=152，每个问题 token 的 MAC 与 V3-03 匹配）；V3-08 S4 解除 Rq/Ro 跨步共享；V3-09 同核锚定 S4；V3-10 S4 完整状态读出。各组从共同起点在 T2 train hops1–3 上续训 6,000 步，数据顺序与样本相同。

- comparator: V3-01（独立训练 S1）；V3-05（幅度）；V3-07（预算）；V3-06（无记忆的逐 token 深度）；V3-04、V3-08、V3-09、V3-10 只作描述；E-0011 的先验与结构捷径基线；各 arm 内的 zero、shuffled、permuted 对照
- metric: T2 dev 上 hops2–3 的 EM（hop2、hop3 等权平均，主）、各 hop 的 EM 与答案 NLL；S_eval∈{1,2,4,8} 扫描（V3-08 只 1/2/4）；每步状态范数、读出范数、相邻步 query cosine、目标 key 权重与 n_eff、准确率随 s 的变化；S_M* arm 的中间状态干预；按 hop 分层的配对 bootstrap 95% 区间（描述）；参数、每 token 读次数、实测 step 时间与 node·h
- scope: M 线、单独编码写入协议（H-0005@2 的范围）；冻结 Qwen3-0.6B-Base，第 14 层，direct_hidden，SoftmaxSlot，F_out，r128；D5 续训配方（LR 3e-3、AdamW 重置、warmup 300 步后 cosine、每步 8 个 episode、只用最终 checkpoint）；T2 只用已发布的 train/dev（hops1–3），hops4/6/8 不开封；单 seed 筛选，不作确认；各组样本预算相同，共用 LR，不逐组校准
- contract: E-0022@2, sealed as DOC-0211@2 (research/experiments/E-0022.md)

E-0023 V3 续：T2 准备度检查（未用过的 calibration，答案位置）与分阶段循环矩阵（先 S1/S2/S4）

- question: E-0022 的共同起点（ATT-0196-1）在未用过的 T2 calibration 上是否满足按答案位置定义的 T2 准备度？满足时，从同一起点训练的累加循环 S2/S4 在 T2 hops2-3 上是否优于独立训练的 S1（V3-01）；优于时，增益能否经得起 E-0022 的幅度、预算与无记忆深度对照？
- intervention: 阶段 0（不训练）：用已审核的评估器在 T2 calibration（2,048 条，hops1-3）上评估 ATT-0196-1 的最终 checkpoint（S=1，六个对照），按准备度规则 R 判定。阶段 A：V3-01（S1）、V3-02（S2）、V3-03（S4），设置与 E-0022 相同（共同起点 ATT-0196-1，T2 train hops1-3 上续训 6,000 步，数据顺序与样本相同，AdamW 重置，最终 checkpoint，重载一致）。阶段 B（按规则释放）：E-0022 其余各组 V3-04..V3-10，S_M*=2 时另加 V3-05b（S2，query 固定为第 1 步）作同深度幅度对照。
- comparator: V3-01（独立训练的 S1）；阶段 B 的 V3-05 或 V3-05b（同深度幅度）、V3-07（预算）、V3-06（无记忆的逐 token 深度）；V3-04、V3-08、V3-09、V3-10 只作描述；各 arm 内的 zero、shuffled、permuted 对照与 E-0011 的捷径基线
- metric: 同 E-0022：T2 dev hops2-3 EM（主）、各 hop EM 与 NLL、S_eval 扫描、轨迹、S_M* 的中间状态干预、按 hop 分层的配对 bootstrap 区间（描述）、成本。新增描述：答案位置上第 s 步对第 s 条路径事实的读权重（按 hop）；终点边 value oracle（hops2-3；原 oracle_value 改称第一条边 value oracle）；按答案名频率分层的 EM；阶段 0 的准备度统计
- scope: 同 E-0022（M 线、单独编码写入、D5 续训配方、第 14 层 direct_hidden SoftmaxSlot F_out r128、T2 只用已发布的 train/dev/calibration，hops4/6/8 不开封）；单 seed 筛选；准备度规则 R 是在看到起点阶段的 dev 结果（EV-0111）之后制定的，只在未用过的 calibration 上检查一次
- contract: E-0023@1, sealed as DOC-0239@1 (research/experiments/E-0023.md)

E-0024 RB1 状态读取的零训练诊断：位置 0 占比与跨 episode 常量读取指数

- question: RB1 残差组在答案预测位置的集中读取，是不是落在每个任务都相同的提示首位置（位置 0，正核注意力 sink），读出向量在 episode 之间是否近似常量？concat 组的读取是不是近乎均匀的前缀均值？
- intervention: 不训练。用 RB1 已有 checkpoint（RB1-02、RB1-03、RB1-08、RB1-09）、同一评估器与 dev 行，在 DOC-0263 读诊断的同一组答案预测位置，记录四层的逐位置读权重与读出向量；条件 normal、iv_strict、iv_window8（定义同 E-0021）。
- comparator: 均匀读取时位置 0 的期望占比 1/n（n 为可读前缀长度）；iv_window8（位置 0 不可读）；concat 组
- metric: 每任务每层：答案位置读权重在位置 0 上的平均占比、在位置 0-2 上的占比（先题内平均再题间平均，另报按位置加权）；最大权重位置为 0 的比例；常量读取指数：同任务内跨 episode 读出向量的平均两两余弦（每任务每层固定 seed 抽至多 200 题）；与 DOC-0263 的 n_eff 并列；node·h
- scope: 只限 RB1 的四个已训练 arm、seed 0、dev 每任务 1,000 条；诊断，不改假设状态；不训练，不开封任何确认集
- contract: E-0024@1, sealed as DOC-0272@1 (research/experiments/E-0024.md)

E-0025 分段信息访问（PIQA/BoolQ）：只有四层侧支状态跨过 backbone 的段界

- question: backbone 看不到第 1 段（PIQA 的目标、BoolQ 的文章）、只有四层 r32 KernelMatrix 侧支状态跨段时，保留跨段状态的 R_res S1 是否比同参数无历史的 T0 与同算子的段界重置有可分辨的收益？把第 1 段的状态换成同任务另一样本的，是否去掉这部分收益？
- intervention: 分段协议：每个样本两次 backbone 前向，段间丢弃原 KV、位置从 0 重新开始，不改 attention mask。PIQA 第 1 段'Goal: {goal}\n'，第 2 段'Solution:' 加候选；BoolQ 第 1 段'Passage: {passage}\n'（与 RB1 相同的截断后 tokens），第 2 段'Question: {question}\nAnswer:' 加候选。训练 arm（seed 0；RB1 的训练顺序、样本与步数；LR 取 RBc 锁定值）：SEG-01 T0_seg（R_res+T0 S1 r32，只看第 2 段）；SEG-02 R_keep（R_res+KernelMatrix S1 r32，第 1 段末四层 (M, c, counts) 作为第 2 段的初始状态，梯度经状态回传到第 1 段）；SEG-03 R_reset（同 SEG-02 的结构，段界清空状态）；SEG-04 LoRA_seg（同四层 all-7 r7，只看第 2 段）；SEG-00 Base_seg 只评估。SEG-02 训练后做 iv_off、iv_swap（第 1 段状态换成同任务另一样本的，固定 derangement）与 iv_reset（同权重，评估时段界清空）。条件释放一次：PIQA 上 $0 <$ SEG-02 $-$ max(SEG-01, SEG-03) < 3 pp 时，加 r128 的 R_keep、R_reset 与 T0_seg 三组（SEG-05..07）
- comparator: SEG-01 与 SEG-03（无跨段历史的两个对照）；SEG-04（无通道的标准适配器）；SEG-00；全上下文参考：RB1 的 Base、RB1-01、RB1-02、RB1-07（不同协议，只作上限参考，不进入门槛以外的比较）
- metric: dev（每任务 1,000 条）PIQA、BoolQ 准确率（主：PIQA）与宏平均、答案 NLL；配对按任务分层 bootstrap 95% 区间（10,000 次，seed 20261101，各 arm 共用重采样索引）；25/50/75/100% dev 曲线；SEG-02 在 iv_off、iv_swap、iv_reset 下的配对差；第 1 段写入 tokens、跨段状态字节、两段前向的训练与评估时间、node·h；stored/trainable/有梯度参数
- scope: 分段 F 线，第三种协议，结果与 F 线、M 线分开登记；冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]、r32（r128 只按规则条件释放一次）、qknorm_pre_rope、KernelMatrix、inclusive、

S1；V1 切分、模板与候选打分；seed 0 筛选；LR 沿用 RBc 锁定值（分段可能改变最优 LR，记为限制）；任何确认集都不开封；不宣称压缩、长上下文或相对全上下文 LoRA 的实用优势

- contract: E-0025@1, sealed as DOC-0273@1 (research/experiments/E-0025.md)

E-0026 RB1 宽度探针：普通（全上下文）设置下 r128 的 R_res、T0 与参数匹配 LoRA（用户要求）

- question: 在 RB1 的普通设置（backbone 看到全部输入）下，把四层侧分支从 r32 加宽到 r128，R_res+KernelMatrix S1 能否达到 Base+1 pp 以上且不比参数最接近的同四层 LoRA 低 1 pp 以上（H-0018）? 它是否比参数匹配的 LoRA 高至少 1 pp？是否比同参数、无历史的 r128 T0 高至少 1 pp，且 iv_swap 降幅至少 1 pp（D-0042 的重开条件）?

- intervention: 三个训练 arm（seed 0；RB1 的初始化规则、训练顺序、样本与 13,115 步；LR 取 RBc 锁定值，不另校准）：W-01 R_res+T0 S1 r128；W-02 R_res+KernelMatrix S1 r128；W-03 同四层 all-7 LoRA（alpha=rank），rank 取参数数最接近 W-02 的整数（按实现计数，训练前登记）。W-02 训练后做 iv_off、iv_swap、iv_permute（与 E-0021 同口径）。Base 与 r32 的 RB1 arm 不重跑，只作参考。

- comparator: W-03（参数匹配的 LoRA）；W-01（同参数、无历史的 r128 T0）；Base（E-0021 记录）；RB1-02、RB1-01、RB1-07（r32，同初始化规则与顺序，描述性参考）

- metric: dev（每任务 1,000 条）PIQA、BoolQ 准确率与宏平均（主：宏平均）、答案 NLL；配对按任务分层 bootstrap 95% 区间（10,000 次，seed 20261101，各 arm 共用重采样索引，只作描述）；25/50/75/100% dev 曲线；W-02 的 iv_off、iv_swap、iv_permute 配对差；参数（stored/trainable/有梯度）、步时、峰值显存、node·h

- scope: RB 线，F 线普通协议（同 E-0021）；冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]、qknorm_pre_rope、KernelMatrix prefix、inclusive、S1；只测 r128；seed 0 筛选；dev 同时用于判定，区间不含 seed 与选择的不确定性；LR 沿用 r32 锁定值（宽度可能改变最优 LR，记为限制）；A2 确认集与官方 validation 都不开封；结论只限 r128 与这一设置

- contract: E-0026@1, sealed as DOC-0285@1 (research/experiments/E-0026.md)

E-0027 E-0025 规则 8 的 BoolQ 复现：r128 三组加分段 LoRA，两个新 seed

- question: E-0025 中 BoolQ 的 r128 跨段收益（gain128 +4.4 pp，swap 降 6.5 pp）在两个新 seed 上是否复现？保留跨段状态的 r128 组是否也超过同 seed 的分段 LoRA（seed 0 时 65.9 对 64.2），从而排除 r128 无历史对照未学好（seed 0 时 T0 61.2、Reset 61.5，只比 Base_seg 高 0.3 与 0.6）的解释？

- intervention: 对新 seed s=1、2，各训练四组：SEG-05 Keep（R_res+KernelMatrix S1 r128，跨段状态）、SEG-06 Reset（同结构，段界清空状态）、SEG-07 T0（R_res+T0 S1 r128）、SEG-04 LoRA_seg（同四层 all-7 r7，只看第 2 段）。init 用 derive_seed(20261101,'residual_la_v21','R1','init',s)，训练顺序用 derive_seed(20261101,'residual_la_v21','R1','train',s)；分段协议、模板、PIQA+BoolQ 训练混合、样本数（26,230）、步数（13,115）、LR 锁定值（RBc-R、RBc-T 3e-3，RBc-L 3e-4）都同 E-0025。SEG-05 训练后做 iv_off、iv_swap（固定 derangement，同 E-0025）与 iv_reset。seed 0 的结果沿用 E-0025，不重跑；SEG-00 是确定性的，沿用。

- comparator: 同 seed 的 max(SEG-06, SEG-07)（E-0025 的 gain 定义）；同 seed 的 SEG-04（最强的无历史适配器参考）；SEG-00 Base_seg；E-0025 的 seed 0 结果

- metric: BoolQ dev 准确率（判定）；每个 seed 的 gain_s = SEG-05 - max(SEG-06, SEG-07)、lora_s = SEG-05 - SEG-04、swap_s = SEG-05 - SEG-05(iv_swap)，按精确分数计；三 seed 平均；每个 seed 的配对按任务分层 bootstrap 区间（10,000 次，只作描述）；PIQA、宏平均与 NLL（描述）；成本

- scope: 分段 F 线，只在 BoolQ 任务层面陈述；冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]、r128（LoRA_seg 为 r7）、qknorm_pre_rope、KernelMatrix、inclusive、S1；E-0025 的模板、LR 与训练混合；seeds 0、1、2；dev 每任务 1,000 条，同时用于判定；不开封任何确认集；不宣称实用价值或长上下文优势

- contract: E-0027@1, sealed as DOC-0302@1 (research/experiments/E-0027.md)

E-0028 RB1-09 的特征来源换成层输入 X（tap × 历史 2×2）与侧支输出比例 η 的搜索（用户要求）

- question: 在 RB1 的普通设置（backbone 看到全部输入）下，把 RB1-09（C_up + KernelMatrix S1，r32）的特征来源从 attention 的 q_norm、k_norm、v_proj 输出换成该层归一化后的输入 X，dev 宏平均是否比原 RB1-09 至少高 1 pp（H-0021）？在两种 tap 下，KernelMatrix 历史读取是否比同参数、无历史的 T0 至少高 1 pp？两种 tap 下，按 calibration 准确率选出的侧支输出比例 η^* 是否比 $\eta = 0.25$ 的 dev 宏平均至少高 1 pp（H-0022）？X 版本与同四层 LoRA r7 相比如何？

- intervention: Part A 三个训练 arm（seed 0；RB1 的初始化规则、训练顺序、26,230 个样本与 13,115 步；LR 都用 1e-3，即 RB1-09 的锁定值，不另校准；$\eta = 0.25$）：X-01 C_up+KernelMatrix S1，tap X；X-02 C_up+T0，tap X；X-03 C_up+T0，原 tap qknorm_pre_rope。X 指该层 input_layernorm 的输出。X-01 训练后做 iv_off、iv_swap、iv_window1、iv_window8、iv_strict、iv_permute（与 E-0021 同口径）。Part B：C_up+KernelMatrix S1 在两种 tap 下各取 $\eta \in \{1/16, 1/8, 1/2, 1, 2\}$ 训练到完整长度（$\eta = 1/4$ 的成员是 RB1-09 与 X-01），最优在端点时每个 tap 向外扩一次（1/32 或 4）；所有候选的最终 checkpoint 在 V1 calibration 上评估，按准确率选 η^*。RB1-09、RB1-07 与 Base 沿用 E-0021 的记录，不重训。

- comparator: RB1-09（原 tap，$\eta = 0.25$，E-0021）；X-02 与 X-03（各自 tap 下同参数、无历史的 T0）；Part B 中同 tap 的 $\eta = 0.25$ 成员（RB1-09 或 X-01）；RB1-07（同四层 all-7 LoRA r7，630,784 个参数）；Base

- metric: dev（每任务 1,000 条）PIQA、BoolQ 准确率与宏平均（主：宏平均）、答案 NLL；配对按任务分层 bootstrap 95% 区间（10,000 次，seed 20261101，各 arm 共用重采样索引，只作描述）；25/50/75/100% dev 曲线；X-01 六种干预的配对差；Part B 另有 V1 calibration（每任务 2,048 条）宏平均准确率（选 η^*）与 NLL（描述）；第 0 步各层 $\bar{v}$ 与 Z 的 RMS（描述）；参数（stored/trainable/有梯度）、步时、峰值显存、node·h

- scope: RB 线，F 线普通协议（同 E-0021）；冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]、r32、KernelMatrix prefix、inclusive、S1、C_up；seed 0 筛选；dev 同时用于判定，区间不含 seed 与选择的不确定性；LR 沿用 1e-3（新 tap 与 C_up 的 T0 可能有不同的最优 LR，η 只在这个 LR 下搜索，记为限制）；η 只对 KernelMatrix S1 的两种 tap 搜索，T0 arm 只用 0.25；η^* 只在 calibration 上选；A2 确认集与官方 validation 都不开封；结论只限这一设置

- contract: E-0028@1, sealed as DOC-0307@1 (research/experiments/E-0028.md)

E-0029 RB1-09 改进方向筛选：同接口 up-only LoRA、梯度子空间与 Q/K 配对初始化、只换 Q/K 来源（用户方案）

- question: 在 RB1 的普通设置下：同四层、只改 up_proj 输入、参数相近的 up-only LoRA 是否比对应的 C_up + KernelMatrix S1 侧支高 1 pp 以上（H-0023）? A_v 用任务梯度子空间初始化（I-G）是否比随机初始化至少高 1 pp（H-0024）? Q/K 配对初始化是否比独立随机初始化至少高 1 pp（H-0025）? 只把 Q/K 换成层输入 N、保留 v_proj 的 value（N-QK）是否比 RB1-09 至少高 1 pp（H-0026）?

- intervention: 八个训练 arm（seed 0；RB1 的初始化规则、训练顺序、26,230 个样本与 13,115 步；侧支 $\eta = 0.25$、LR 1e-3）：G-T、G-QN、G-N（三种 tap 下 A_v 用 I-G）；Q-N（Q/K 取 input_layernorm 输出 N，V 取 v_proj 输出，随机初始化）；P-T、P-N（原 tap 与 N tap 下 A_q 与 A_k 配对初始化）；L-56、L-48（同四层只加在 up_proj 上的 LoRA，rank 56 与 48，LR 按 E-0020 短训练规则单独校准）。RB1-09、RB1-07、Base 沿用 E-0021，X-01 沿用 E-0028

- comparator: 各 arm 的同 tap 随机初始化参照（RB1-09、X-01、Q-N）；Q-N 对 RB1-09 与 X-01；L-56 对 RB1-09，L-48 对 X-01；RB1-07（同四层 all-7 LoRA r7）；Base

- metric: dev（每任务 1,000 条）PIQA、BoolQ 准确率与宏平均（主：宏平均）、答案 NLL；配对按任务分层 bootstrap 95% 区间（10,000 次，seed 20261101，各 arm 共用重采样索引，只作描述）；25/50/75/100% dev 曲线；第 0 步与最终 checkpoint 的读取诊断（self 权重、最大权重、n_eff，按前缀长度分桶）；I-G 的奇异值能量与尺度因子；LoRA 校准 NLL；参数（stored/trainable/有梯度）、步时、峰值显存、node·h

- scope: RB 线，F 线普通协议（同 E-0021、E-0028）；冻结 Qwen3-0.6B-Base；四层 [6,13,20,27]；侧支 r32、KernelMatrix prefix、inclusive、S1、C_up、$\eta = 0.25$；seed 0 筛选；dev 同时用于判定，区间不含 seed 与选择的不确定性；侧支 LR 沿用 1e-3；LoRA 不做 LoRA-GA 一类的初始化；A2 确认集与官方 validation 都不开封；结论只限这一设置

- contract: E-0029@1, sealed as DOC-0310@1 (research/experiments/E-0029.md)

4 Results

下列表格给出各实验可用 attempt 的描述性均值，不是统计检验。E-0001 与 E-0004 是 diagnostic 证据：V0 修正后 85/85 项、E-0004 130/130 项检查通过。E-0003 是单 seed 的 screening 证据：Base 的 dev 宏平均为 70.15%，各训练组在 77.05%–79.20% 之间。大部分提升来自 BoolQ（Base 68.0%，训练组 80.8%–83.6%）；PIQA 只从 72.3% 升到 73.0%–74.9%。按预先固定的规则，F*=F_out（77.80%），C*=C_up（77.70%）。最好的 concat 组 C_dual（78.15%）只比 F* 高 0.35 pp（描述区间 $[-0.60, 1.35]$），记为 concat 未胜。C* 比 4 层与 28 层 LoRA 分别低 1.50 与 1.35 pp；C_dual 对线性退化组只高 0.15 pp $[-0.70, 1.00]$。E-0005 与 E-0007 是 diagnostic 证据。Base 在 dev 上的 M 线与 F 线 EM 分别为 1.1% 与 1.3%，先验基线为 1.5%。在 calibration 上，上下文事实数 E 为 1、2、4、8、16 时，F 线 EM 依次为 67.0%、6.9%、2.2%、1.4%、1.4%；$E \geq 2$ 时，91%–96% 的回答是问题主语；E=16 时，在支持中的名字（去掉主语）里选对的比例为 14.2%，随机为 3.7%。E-0007 有一项实现检查按原规则未通过：BF16 下 batch 1 与 batch 8 的逐条 NLL 平均绝对差为 0.088，门槛为 0.05。FP32 对照把该差异降到 1e-5 量级，因此判为 BF16 数值敏感。

V2 的结果如下。E-0008 的 F 线正对照通过：事实在上下文中训练后，calibration EM 为 99.95%（训练前 1.90%）。E-0010 十组的 dev 正常 EM 为 0.8%–2.1%，清零记忆为 1.1%，打乱记忆为 1.1%–1.9%；正常 EM 对两者中较大者的差最大为 +0.6 pp。所有组的平均目标权重都低于 0.125，也低于均匀的 1/16。正常与打乱记忆的 NLL 几乎相同（4.42–4.61），清零记忆为 9.25。把读取换成目

标的已学 value（value oracle）后，EM 为 1.1%–2.3%。按锁定规则没有合格组，H-0003 记为 challenged（screening）；H-0004 的读算子比较中，两种算子都只在 0/4 格占优，记为 inconclusive。E-0012 的六项正对照为 96.6%–100%。在分隔符位置，冻结特征解码尾实体的准确率为 99.6%（direct_hidden）与 92.9%（qknorm_pre_rope）。以目标事实为标签的双线性寻址探针在最后一个问题位置、秩 128–1024 下的 16 选 1 top-1 为 82.2%–90.2%，秩增大没有一致的提升。训练后，每组在全部 1,000 个 dev episode 的答案位置都把第一个写入的槽位排在最前。独立 ridge 探针下，读出向量的答案准确率为 1.8%–2.3%，已学目标 value 为 16.6%–23.0%。逐层 softmax 探针中，训练后 value 投影解码尾实体的准确率（17.0%–37.1%）不高于随机初始化投影（32.2%–38.5%）。融合增量与第 14 层残差范数之比的组均值为 18.7–608（V2-09 为 1.1e6）。

记忆路线的修复结果如下，都是 screening 或 diagnostic 证据。E-0014 中只有 R1 达到它的门槛：在 E=1 dev 上正常记忆比清零与打乱记忆高 82.6 pp。没有一组在 E=16 上达到 H3，R2 也没有达到 E=4 的门槛；R3、R4、R6 重现了 V2 的槽位 0 塌缩（D-0013）。有地址监督的 R5 在最后问题位置的目标权重为 0.518，EM 优势只有 4.6 pp，oracle_value 只有 10.7%（EV-0084）：读对了，读出也解码不好。E-0015 在 calibration 上把这一点拆开（EV-0087）：R1 的上下文编码 value 在 E=16 上只对第一条事实可用（oracle_value 第 0 条 83.4%，第 1 条及以后 1.6%），上下文中第 1–3 条事实的 value 的 L2 范数（103.1）约为第 0 条（43.5）的两倍；每条事实单独编码后，同一解码器在 E=16 上的 oracle_value 为 86.4%（第 1 条及以后 86.7%）。

E-0016 的三条路线中，只有单独编码写入加 E=1 预训练的 D5 达到 H3（EV-0095）：正常 EM 42.8%，清零 1.1%，打乱 1.7%（优势 41.1 pp），NLL 2.514 低于两个对照，全位置目标权重 0.162，最后位置 0.571。从零训练的单独编码写入 D4 读取均匀，优势 0.3 pp（EV-0096）。解码器先行在 teacher-forced 单槽读取下学成（D1，+65.5 pp，用了目标索引），但之后只用答案 CE 续训时没有学到寻址（D2a +3.2 pp，D2b +3.0 pp）；槽位边际似然 D3 停在答案先验解（+0.4 pp）。H-0010 与 H-0011 记为 challenged（screening，D-0022、D-0021）。E-0017 用 seed 1、2 复现 D5，优势为 47.8 与 46.2 pp，连同 seed 0 共 3/3 达标；全位置目标权重 0.158–0.162，最后位置最常见的槽位只占 7.6%–8.0%，没有塌缩到固定槽位。H-0012 记为 supported（screening，D-0023）。同一批 adapter 换回上下文编码写入时，EM 只有约 5%。

E-0018 把三个 D5 adapter 不经训练用到 T2（EV-0107–EV-0109）。S=1 的输出与已审核的评估器逐条一致。三个 seed 在一跳问题上都没有达到 H3：EM 优势 0.9、1.8、3.0 pp，全位置目标权重 0.036–0.038；把读取换成目标 value 后，EM 为 75.7%–80.2%。所以解码器迁移到了 T2，寻址没有迁移。不训练时把 S_{eval} 提到 2、4、8，2–3 跳的 EM 不变（2.7%–4.5%），NLL 上升。

E-0022 因此先在 T2 上训练共同起点（EV-0111）。hop1 的 EM 优势 25.4 pp 与 NLL 条件都通过，但全问题位置平均目标权重为 0.0655，低于 0.125（最后位置为 0.384），十组没有训练；T2 问题有 23–25 个 token，非末位的平均权重 0.052 拉低了全位置均值（D-0031）。E-0023 的准备度规则 R 在 T2 calibration 上四条都成立（EV-0113）。阶段 A 落在 A3（EV-0115）：2–3 跳的主指标 EM 为 S1 3.30%、S2 3.90%、S4 3.30%，S2 比 S1 高 0.60 pp（描述性区间 $[-0.60, +1.80]$），低于 +3 pp，hop1 EM 从 14.37% 降到 11.68%，阶段 B 没有释放。冻结诊断在 S2 上给出（EV-0116）：终点边的 value oracle 能解码（比对照高 40.95 pp）；把金标准桥实体放进问题主语后，第 1 步对路径第 2 条事实的平均读权重为 0.2025（同关系的错误桥 0.0724，无关桥 0.0846）；原生的第 2 步只有 0.0761。所以失败出在两次读取之间的 query 转移。按 D-0035 做的后继槽位 CE 修复 pilot 属于额外监督，两条判据都不成立（EV-0117）：正确标签只比置换标签高 1.65 pp（门槛 3 pp），第 2 步对第 2 条事实的读权重为 0.0834，低于 1/8，两组的读权重都接近均匀。H-0005@2 记为 inconclusive（screening，D-0036），M 线这一阶段暂停（D-0046）。

V5 缩减版的官方 validation 只开封一次（ATT-0179-1，EV-0110；PIQA 1,838 条，BoolQ 3,270 条）。C_up、F_out 与 LoRA 的三 seed 平均宏平均准确率分别为 77.48%、77.25%、77.90%。主比较 C_up 减 LoRA 为 −0.42 pp，95% 区间 $[-1.02, +0.20]$ pp；三个 seed 的差都为负（−0.28、−0.40、−0.58 pp），PIQA −0.74 pp，BoolQ −0.09 pp。上界低于 +1 pp，按封存规则 H-0008 记为 challenged（confirmatory，D-0028）。这个区间只反映给定三个训练 seed 时的数据不确定性；它含 0，所以既不宣称等价，也不宣称 LoRA 更好。次要比较 C_up 减 F_out 为 +0.23 pp（Holm

p=0.34），F_out 减 LoRA 为 −0.65 pp（Holm p=0.069），校正后都不拒绝。WikiText 上相对 Base（NLL 2.647）的 NLL 增量为 C_up +0.200、F_out +0.238、LoRA +0.337。

RB0（E-0019）的 397 项检查在 PBS 中全部通过（ATT-0188-1）。逐 token decode 与 batch 从 2 扩到 3 的两项 BF16 比较超出 0.50002（0.8203、0.8574），未改动的 reference 给出相同的值，按 D-0027 只作记录，对应的 FP32 检查通过。计时覆盖 21 个配置，每个配置测 100 个稳定步；RB0 共用 0.122 node·h。代码审核 RV-0060 的四条 low 发现修复后，复核 RV-0062 通过，H-0017 记为 supported（diagnostic，只限实现正确性，D-0030）。

E-0020 的 16 个候选都完成且有限，锁定的学习率为 LoRA 3e-4、T0 3e-3、R_res 3e-3、concat 1e-3（EV-0114）；T0 的最小值落在扩展后的端点上，按规则不再扩展。RB1（E-0021）的 dev 宏平均为：Base 70.15%，T0 77.30%，R_res S1 77.10%、S2 77.45%、S4 76.90%，固定 query 的 S4 77.10%，$\eta/4$ 的 S4 76.50%，C_dual 77.45%，C_up 77.50%，LoRA r7 78.95%。各训练组对 Base 的提升大多来自 BoolQ（68.0% 升到 80.3%–83.5%），PIQA 只高 0.1–2.1 pp（D-0045）。按规则 11，R_res S1 比 LoRA 低 1.85 pp（描述性配对区间 [−3.00, −0.70]），H-0013 记为 challenged（screening，D-0039）；R_res S1 比同参数 T0 低 0.20 pp [−1.30, +0.90]，H-0014 记为 challenged（screening，D-0042）。训练后 RB1-02 的输出依赖侧支状态：swap 使宏平均下降 1.85 pp [0.75, 3.00]，permute 下降 17.15 pp；后者可能主要来自状态结构被破坏，不作侧支内容带来收益的证据。锁定的循环组 S2 比 S1 高 0.35 pp [−0.55, +1.30]，S4 比固定 query 的 S4 低 0.20 pp，H-0015 记为 inconclusive（D-0040）。最好的 concat（C_up）比残差高 0.40 pp [−0.70, +1.50]，H-0016 记为 inconclusive（D-0041）。规则 9 允许的一次同布局探针（H-0018）没有释放（D-0043）：顾问轮次 3 的两位顾问都指出，探针的通过条件里没有 T0，即使通过也改变不了 H-0013 或 H-0014 的判断。

E-0024（EV-0122，diagnostic）按预先登记的读法得到 MIXED，只能逐层描述。残差组读取集中的单元（答案位置 $n_{\text{eff}} < 2$）里，读权重主要落在位置 0：share0 为 0.81–0.98（均匀读取的 $1/n$ 在 PIQA 与 BoolQ 上约为 0.057 与 0.0087），而位置 0 在同一任务的所有行里都是同一个 token（“Goal” 或 “Pass”）。常量读取指数 C 只在 PIQA 第 27 层超过 0.9（RB1-02 0.987，RB1-03 0.995），其余集中单元为 0.50–0.68，所以 sink 的判据在 C 上不成立，内容读取的判据（share0 < 0.2）也处处不成立。concat 组在 BoolQ 第 6–20 层与 PIQA 第 6–13 层接近均匀读取。所有条件的 gold NLL 与读诊断都与 E-0021 一致（差为 0）；原先写的 iv_strict 检查阈值有误，在看到检查失败之后、打开判读之前换成第 6 层的精确恒等式（D-0051）。E-0026（seed 0）的三组都学成：W-01（T0 r128）、W-02（R_res r128）与 W-03（LoRA r31）的宏平均为 76.80%、76.95%、78.75%，分别比 Base 高 6.65、6.80、8.60 pp。W-02 比 W-03 低 1.80 pp（描述性配对区间 [−3.10, −0.50]），PIQA 与 BoolQ 各低 1.80 pp，按规则 3 H-0018 记为 challenged（screening，D-0056）。W-02 比同参数的 W-01 只高 0.15 pp [−1.00, +1.35]，H-0014 的重开条件不满足。加宽本身几乎不改变结果：W-02 减 RB1-02 为 −0.15 pp，W-01 减 RB1-01 为 −0.50 pp，W-03 减 RB1-07 为 −0.20 pp。E-0026 共用 0.938 node·h。

E-0025（seed 0，16 个 attempt，共 2.596 node·h）的实现检查全部通过（EV-0130）。全上下文 LoRA 比分段 LoRA 在 PIQA 上高 7.0 pp，在 BoolQ 上高 19.3 pp，两个任务都有信息量，主任务为 PIQA。分段各组在 PIQA 与 BoolQ 上的 dev 准确率如下：Base_seg 66.1% 与 60.9%；r32 的 R_keep 69.4% 与 65.8%，T0 66.9% 与 63.8%，R_reset 67.8% 与 61.2%；分段 LoRA 67.4% 与 64.2%；r128 的 R_keep 69.3% 与 65.9%，R_reset 66.9% 与 61.5%，T0 67.9% 与 61.2%。主任务 PIQA 上，gain 在 r32 为 +1.6 pp [−0.3, 3.5]（swap 降 4.2 pp），在 r128 为 +1.4 pp [−0.4, 3.2]（swap 降 5.3 pp），都为正但低于 +3 pp，按 D-0044 只作描述，不再加宽。次要任务 BoolQ 上，r32 的 gain 为 +2.0 pp；r128 的 gain 为 +4.4 pp [1.5, 6.8]，swap 降 6.5 pp，过了任务层门槛。不过 r128 的保留状态组与 r32 几乎相同（65.9% 对 65.8%），gain 变大主要因为 r128 的两个无历史对照更弱，而保留状态组只比分段 LoRA 高 1.7 pp。评估时清空状态使 BoolQ 降到 Base_seg 以下（r32 54.5%，r128 58.4%），所以干预降幅里含分布偏移。按规则 8，H-0019 记为 inconclusive（screening，D-0057）。E-0027 用 seed 1、2 复现 BoolQ 的 r128 结果（含冒烟、训练、干预与分析，共 2.804 node·h），两个新 seed 的实现检查全部通过（EV-0143）。保留状态组在 seed 0、1、2 上的

BoolQ 准确率为 65.9%、65.7%、65.3%，swap 降幅为 6.5、6.2、7.0 pp。R_reset 为 61.5%、60.9%、61.3%，三个 seed 上都没有学成（门槛为 Base_seg 加 1 pp，即 61.9%）；T0 为 61.2%、63.1%、63.5%，在新 seed 上学成。gain 因此依次为 +4.4、+2.6、+1.8 pp，三个 seed 等权平均 G = 88/3000 = +2.933 pp，低于 +3 pp 的支持门槛。其余条件都成立：两个新 seed 的 gain 为正，平均 swap 降幅 W = +6.567 pp 不低于 G/2，对同 seed 分段 LoRA 的平均差 L = +2.067 pp 不低于 +1 pp（EV-0145、EV-0146）；三个 challenge 条件也都不成立（EV-0147）。PIQA 只作描述，新 seed 的 gain 为 +1.7 与 +1.3 pp（EV-0150）。按规则 6，H-0020 记为 inconclusive（screening，D-0062，结论审核 RV-0089 pass），不再加 seed、加宽、换 tap 或加循环；H-0019 维持 inconclusive，分段线暂停（D-0063）。

E-0028（seed 0，含冒烟、训练、干预与分析，共 4.025 node·h，上限 5.5）的实现检查全部通过（EV-0154）。dev 宏平均为：Base 70.15%，LoRA r7 78.95%，RB1-09 77.50%；特征来源换成 input_layernorm 输出的 X-01 为 78.15%，同特征来源、无历史的 T0（X-02）为 78.30%，原特征来源的 T0（X-03）为 78.15%。换特征来源的差 X-01 − RB1-09 = +0.65 pp（95% 区间 [−0.25, +1.60]），介于 0 与 +1 pp 之间，只作描述（EV-0156）。两种特征来源下，KernelMatrix 历史读取都不比同参数 T0 好（差为 −0.15 与 −0.65 pp），虽然 swap 使宏平均下降 2.00 与 1.95 pp（EV-0157）。η^* 只在 calibration 上选，并在汇总 dev 之前锁定（EV-0153）：原特征来源为 0.25，即默认值；input_layernorm 输出为 1，dev 上为 77.90%，比 $\eta = 0.25$ 低 0.25 pp（[−1.15, +0.65]）。两种特征来源下，各 η 候选的 dev 宏平均相差都不到 1 pp（EV-0158）。对 LoRA r7 的差为：X-01 −0.80 pp，所选 η 的版本 −1.05 pp，RB1-09 −1.45 pp（EV-0159）。按预登记规则，H-0021 记为 inconclusive 并暂停（D-0066），H-0022 记为 challenged（screening，D-0067）；结论审核为 RV-0091 与 RV-0093，后者余下的一条措辞问题已按审核意见修正，由协调者批准。所选 η 的版本比 LoRA r7 低 1 pp 以上，触发规则 10：普通设置下不再做新的特征来源变体（EV-0162）。E-0029 在 E-0028 出结果之前已封存，是按用户方案改编出的八组；协调者把它作为有界的例外照原样运行（D-0065）。方案中以残差流本身为输入的变体与省去的初始化组合没有检验。

Table 1: E-0001 V0 实现与不变量检查: descriptive means over usable attempts

arm	seeds	attempts	bf16_atol	check.src/test_core.py::test_kernel_matrix_eq
base_calibration	173	1 ended/success	0.5 (n=1)	-
hardware_probe	0	1 ended/failed, 1 ended/success	-	-
invariant_checks	42	2 ended/failed, 2 ended/success	-	1.176e-08 (n=2)

Per-attempt records: rl run show E-0001.

Table 2: E-0002 V1 任务切片与家族学习率校准: descriptive means over usable attempts

arm	seeds	attempts	C_dual.calibration.boolq.accuracy	C_dual.calibra
base-eval	0	1 ended/cancelled, 1 ended/success	-	-
cal-cdual-1e-4	0	1 ended/cancelled, 1 ended/success	-	-
cal-cdual-3e-4	0	1 ended/cancelled, 1 ended/success	-	-
cal-fout-1e-4	0	1 ended/cancelled, 1 ended/success	-	-
cal-fout-3e-4	0	1 ended/cancelled, 1 ended/success	-	-
cal-lora-1e-4	0	1 ended/cancelled, 1 ended/success	-	-
cal-lora-3e-4	0	1 ended/cancelled, 1 ended/success	-	-
release-schedule-estimate	0	1 ended/success	-	-
selection-boundary-audit	0	1 ended/success	-	-
selection-release-audit	0	1 ended/failed	-	-
smoke	0	1 ended/success	0.6562 (n=1)	32 (n=1)
smoke-corrected	0	1 ended/success	0.75 (n=1)	32 (n=1)
smoke-reloadfix	0	1 ended/success	0.75 (n=1)	32 (n=1)
smoke-reviewfix	0	1 ended/success	0.75 (n=1)	32 (n=1)

Per-attempt records: rl run show E-0002.

Table 3: E-0003 V1 FFN 融合接口筛选（八组）: descriptive means over usable attempts

arm	seeds	attempts	C_dual.dev.boolq.accuracy	C_dual.dev.boolq.example
Base	0	1 ended/success	-	-
V1-01	0	1 ended/success	-	-
V1-02	0	1 ended/success	-	-
V1-03	0	1 ended/success	-	-
V1-04	0	1 ended/success	-	-
V1-05	0	1 ended/success	-	-
V1-06	0	1 ended/success	-	-
V1-07	0	1 ended/success	-	-
V1-08	0	1 ended/success	-	-
analysis-regression	0	1 ended/success	-	-
base-dev-comparison	0	1 ended/success	-	-
formal-analysis	0	1 ended/success	-	-
smoke-eight-arms	0	1 ended/failed, 1 ended/success	0.625 (n=1)	32 (n=1)

Per-attempt records: rl run show E-0003.

Table 4: E-0004 记忆路径就绪检查（RV-0002 跟进）: descriptive means over usable attempts

arm	seeds	attempts	check.src/test_core.py::test_kernel_matrix_equals_slot_reference_
readiness	42	1 ended/success	1.176e-08 (n=1)

Per-attempt records: rl run show E-0004.

Table 5: E-0005 M 线合成任务生成器与 Base 上下限 (concat_loop_v2) : descriptive means over usable attempts

arm	seeds	attempts	F.elapsed_s	F.em	F.examples	F.nll	M
base-dev-MF	-	1 ended/success	4.633 (n=1)	0.013 (n=1)	1000 (n=1)	5.706 (n=1)	4.
base-dev-smoke	-	1 ended/success	0.1641 (n=1)	0 (n=1)	32 (n=1)	5.918 (n=1)	0.
data-generation	-	1 ended/success	-	-	-	-	-
data-smoke	-	1 ended/success	-	-	-	-	-
legacy-inventory	-	1 ended/success	-	-	-	-	-

Per-attempt records: rl run show E-0005.

Table 6: E-0006 V2 M 线训练与诊断流水线 (实现与冒烟) : descriptive means over usable attempts

arm	seeds	attempts	arms_completed	check.src/test_core.py::te
eight-arm-E0005-integration	2100042	1 ended/success	-	-
eight-arm-copy32	2100042	1 ended/success	8 (n=1)	-
eight-arm-timing	2100042	1 ended/success	8 (n=1)	-
invariant-checks	2100042	1 ended/success	-	1.176e-08 (n=1)
shuffled-diagnostic-regression	2100042	1 ended/failed, 1 ended/success	-	-

Per-attempt records: rl run show E-0006.

Table 7: E-0007 F 线 Base 难度诊断 (concat_loop_v2) : descriptive means over usable attempts

arm	seeds	attempts	F.E1.em	F.E1.nll	F.
diagnostic-smoke32	20261029	1 ended/failed	-	-	-
diagnostic-smoke32-fixed	20261029	1 ended/success	0.625 (n=1)	1.519 (n=1)	0.
fp32-calibration256-and-saved-bf16-audit	173	1 ended/success	-	-	-
full-calibration2048	20261029	1 ended/success	0.6699 (n=1)	1.422 (n=1)	0.
postmerge-regression	20261029	1 ended/success	-	-	-
scoring-difference-audit	20261029	1 ended/success	-	-	-

Per-attempt records: rl run show E-0007.

Table 8: E-0008 V2 F 线训练后正对照 (事实在上下文中) : descriptive means over usable attempts

arm	seeds	attempts	calibration.all.em	calibration.all.examples	calibratio
fline-4m	0	1 ended/success	0.9995 (n=1)	2048 (n=1)	0.01557 (
fline-cal-0.0001	0	1 ended/success	0.9941 (n=1)	2048 (n=1)	0.02509 (
fline-cal-0.0003	0	1 ended/success	0.998 (n=1)	2048 (n=1)	0.009097
fline-cal-0.001	0	1 ended/success	0.9995 (n=1)	2048 (n=1)	0.001602
fline-cal-0.003	0	1 ended/success	0.998 (n=1)	2048 (n=1)	0.0107 (n
fline-output-audit	0	1 ended/success	-	-	-
fline-review-regression	0	1 ended/success	0.0625 (n=1)	32 (n=1)	3.515 (n=
fline-smoke	0	1 ended/failed, 1 ended/success	0.0625 (n=1)	32 (n=1)	3.515 (n=

Per-attempt records: rl run show E-0008.

Table 9: E-0009 V2 记忆家族学习率校准与正式 M 线训练程序: descriptive means over usable attempts

arm	seeds	attempts	200000.budget	200000.steps	200000.t
final-grid-analysis	0	1 ended/success	-	-	-
formal-path-checks	0	1 ended/success	-	-	-
initial-grid-analysis	0	1 ended/success	-	-	-
kernel_matrix-lr0.0003	0	1 ended/success	-	-	-
kernel_matrix-lr0.001	0	1 ended/success	-	-	-
kernel_matrix-lr0.003	0	1 ended/success	-	-	-
kernel_matrix-lr0.01-extension	0	1 ended/success	-	-	-
reporting-max-regression-cost-report	0	1 ended/success	-	-	-
schedule-preflight	0	1 ended/success	2e+05 (n=1)	300 (n=1)	2.002e+0
soft_slot-lr0.0003	0	1 ended/success	-	-	-
soft_slot-lr0.001	0	1 ended/success	-	-	-
soft_slot-lr0.003	0	1 ended/success	-	-	-
soft_slot-lr0.01-extension	0	1 ended/success	-	-	-
twelve-arm-32step-smoke	0	1 ended/success	-	-	-

Per-attempt records: rl run show E-0009.

Table 10: E-0010 V2 M 线单跳记忆读取：2×2×2 析因与 C_dual 探针: descriptive means over usable attempts

arm	seeds	attempts	H3.eligible	H3.qualified	H4.kernel_wins	H4.soft_win
V2-01	0	1 ended/success	-	-	-	-
V2-02	0	1 ended/success	-	-	-	-
V2-03	0	1 ended/success	-	-	-	-
V2-04	0	1 ended/success	-	-	-	-
V2-05	0	1 ended/success	-	-	-	-
V2-06	0	1 ended/success	-	-	-	-
V2-07	0	1 ended/success	-	-	-	-
V2-08	0	1 ended/success	-	-	-	-
V2-09	0	1 ended/success	-	-	-	-
V2-10	0	1 ended/success	-	-	-	-
analysis-regression	0	1 ended/success	-	-	-	-
factorial-analysis	0	1 ended/success	0 (n=1)	0 (n=1)	0 (n=1)	0 (n=1)

Per-attempt records: rl run show E-0010.

Table 11: E-0011 V3 T2 链终点任务生成器、登记与难度检查: descriptive means over usable attempts

arm	seeds	attempts	F.all.em	F.all.examples	F.all.nll	F.all
F-LoRA-pilot	0	1 ended/success	-	-	-	-
base-dev	173	1 ended/success	0.009 (n=1)	1000 (n=1)	5.568 (n=1)	0.011
base-smoke	173	1 ended/success	0.03333 (n=1)	60 (n=1)	5.771 (n=1)	0.033
full-data	20261029	1 ended/success	-	-	-	-
generator-smoke	20261029	1 ended/success	-	-	-	-
generator-smoke-r2	20261029	1 ended/success	-	-	-	-
pilot-selector-smoke	0	1 ended/success	-	-	-	-

Per-attempt records: rl run show E-0011.

Table 12: E-0012 V2 记忆失败层次定位（表示探针与寻址几何）: descriptive means over usable attempts

arm	seeds	attempts	L3_s	address_s	dev_question_tokens	elap
L0-L4-artifact-audit	0	1 ended/success	-	-	7000 (n=1)	0.77
L0-L4-cost	0	1 ended/success	555.5 (n=1)	111.3 (n=1)	-	57.9
L0-L4-full	0	1 ended/success	-	-	-	945
L0-L4-smoke	0	1 ended/success	-	-	-	25.0

Per-attempt records: rl run show E-0012.

Table 13: E-0013 V5 缩减版：tokenwise 简单接口对强 LoRA 的实用确认（PIQA+BoolQ 官方 validation）: descriptive means over usable attempts

arm	seeds	attempts	Base.elapsed_s	Base.validation.
V5-C	0,1,2,3	8 ended/success	-	-
V5-F	0,1,2,3	7 ended/success	-	-
V5-L	0,1,2,3	8 ended/success	-	-
base	0	1 ended/success	-	-
confirmation-lock-preflight	0	1 ended/success	-	-
confirmation-locked-analysis-audit	-	1 ended/success	-	-
locked-confirmation-base-and-nine-final	-	1 ended/success	375.7 (n=1)	0.6667 (n=1)
mig-profile-guard	-	1 ended/success	-	-
sealed-eval-dev-rehearsal	0	1 ended/success	-	-
sealed-eval-provenance-recovery-regression	0	1 ended/success	-	-
sealed-eval-regression	0	1 ended/success	-	-
v5-cost-tabulation	1	1 ended/success	-	-
v5-final-latency	1	1 ended/success	-	-
v5-final-lr-lock	0	1 ended/success	-	-
v5-grid-report-regression	0	1 ended/success	-	-
v5-initial-grid-report	0	1 ended/success	-	-
v5-latency-map-regression	0	1 ended/success	-	-
v5-latency-smoke	0	1 ended/cancelled	-	-
v5-slice-report-regression	-	1 ended/success	-	-
v5-three-arm-smoke	0	1 ended/failed, 1 ended/success	-	-

Per-attempt records: rl run show E-0013.

Table 14: E-0014 记忆路线修复筛选：事实数、课程、先验吸收、寻址监督与去中心化余弦寻址: descriptive means over usable attempts

arm	seeds	attempts	R1.em_margin	R1.target_weight	R2.em_margin	R2.targ
R1	0	1 ended/success	-	-	-	-
R2	0	1 ended/success	-	-	-	-
R3	0	1 ended/success	-	-	-	-
R4	0	1 ended/success	-	-	-	-
R5	0	1 ended/success	-	-	-	-
R6	0	1 ended/success	-	-	-	-
analysis	0	1 ended/success	-0.007 (n=1)	0.06122 (n=1)	0.012 (n=1)	0.09126
checks	0	1 ended/success	-	-	-	-
checks-rv0040	0	1 ended/success	-	-	-	-
data	0	1 ended/success	-	-	-	-

Per-attempt records: rl run show E-0014.

Table 15: E-0015 记忆路线诊断：value/解码侧与寻址侧的分离（E-0014 checkpoint 上只做评估）: descriptive means over usable attempts

arm	seeds	attempts	analyze_exit	mig_instance_hours	node_hours	pytest_ex
analysis	0	1 ended/success	0 (n=1)	-	-	-
checks	0	4 ended/success	-	-	-	0 (n=2)
diag-R1	0	1 ended/success	-	0.1726 (n=1)	0.04316 (n=1)	-
diag-R2	0	1 ended/success	-	0.1779 (n=1)	0.04448 (n=1)	-
diag-R5	0	1 ended/success	-	0.1755 (n=1)	0.04387 (n=1)	-
diag-V2-03	0	2 ended/success	-	0.1544 (n=1)	0.0386 (n=1)	-
reload-diag	0	1 ended/success	-	-	-	-

Per-attempt records: rl run show E-0015.

Table 16: E-0016 记忆路线训练筛选：解码器先行、槽位边际似然、单独编码写入（顾问轮次 1 的三条路线）: descriptive means over usable attempts

arm	seeds	attempts	D1.curve_seconds	D1.evaluation_second
D1	0	1 ended/success	-	-
D1-D2a-D2b-D3-final-analysis	0	1 ended/success	-	-
D1-D3-interim-analysis	0	1 ended/success	-	-
D2a	0	1 ended/success	-	-
D2b	0	1 ended/success	-	-
D3	0	1 ended/success	-	-
D4	0	1 ended/failed, 1 ended/success	-	-
D5	0	1 ended/success	-	-
checks	0	3 ended/success	-	-
protocols-default-regression-smoke	0	1 ended/success	2.927 (n=1)	3.664 (n=1)
shared-hooks-smoke	0	1 ended/success	3.179 (n=1)	3.945 (n=1)
smoke	0	1 ended/failed, 1 ended/success	-	-

Per-attempt records: rl run show E-0016.

Table 17: E-0017 记忆路线：E=1 预训练加单独编码写入（D5 配方）的 seed 复现: descriptive means over usable attempts

arm	seeds	attempts	arms_completed	compare_exit	dump_new_exit	dump_old_exi
C1	1	1 ended/success (1 not usable: spec mismatch)	-	-	-	-
C2	2	1 ended/success (1 not usable: spec mismatch)	-	-	-	-
P1-A	1	1 ended/success	1 (n=1)	-	-	-
P1-B	1	1 ended/success (1 not usable: spec mismatch)	-	-	-	-
P2-A	2	1 ended/success	1 (n=1)	-	-	-
P2-B	2	1 ended/success (1 not usable: spec mismatch)	-	-	-	-
checks	0	4 ended/success	-	0 (n=2)	0 (n=2)	0 (n=2)

Per-attempt records: rl run show E-0017.

Table 18: E-0018 V3 前置：单独编码写入下 T2 链终点任务的读取迁移、无训练深度扫描与循环实现检查: descriptive means over usable attempts

arm	seeds	attempts	eval_smoke_exit	mig_instance_hours	node_hours
D5@ATT-0159-1	0	2 ended/success	-	0.05046 (n=2)	0.01261 (n=2)
D5@ATT-0172-1	1	1 ended/success	-	0.1068 (n=1)	0.0267 (n=1)
D5@ATT-0173-1	2	1 ended/success	-	0.07832 (n=1)	0.01958 (n=1)
E0-tests	-	3 ended/success	0 (n=1)	-	-

Per-attempt records: rl run show E-0018.

Table 19: E-0019 RB0：残差旁路线实现与计时（因果前缀 KernelMatrix、T0、四层 R_res/concat、侧支历史干预）: descriptive means over usable attempts

arm	seeds	attempts	RB1_core_node_h	RBc_12candidate_node_h	RI
RB0-D0026-probe	0	1 ended/failed	-	-	-
RB0-D0027-probe	0	1 ended/success	-	-	-
RB0-RB5-cost-layouts	0	1 ended/success	-	-	-
RB0-core	0	1 ended/success	-	-	-
RB0-cost-report	0	1 ended/success	2.444 (n=1)	-	-
RB0-full-timing	0	1 ended/success	-	-	-
RB0-model-probe	0	1 ended/failed	-	-	-
RB0-review-fixes	0	1 ended/success	-	0.5093 (n=1)	0.0

Per-attempt records: rl run show E-0019.

Table 20: E-0020 RBc：残差旁路线四个训练家族的学习率校准（LoRA4 r7、T0、R_res+KernelMatrix、C_dual+KernelMatrix）：descriptive means over usable attempts

arm	seeds	attempts		calibration.boolq.accuracy	calibration.boolq.examples	c
RB1-01	0	3 ended/cancelled, ended/success	4	0.7861 (n=4)	2048 (n=4)	2
RB1-02	0	3 ended/cancelled, ended/success	4	0.7825 (n=4)	2048 (n=4)	2
RB1-07	0	3 ended/cancelled, ended/success	4	0.7764 (n=4)	2048 (n=4)	2
RB1-08	0	3 ended/cancelled, ended/success	4	0.7469 (n=4)	2048 (n=4)	2
RBc-final-lock	0	1 ended/success		-	-	-
RBc-initial-report	0	1 ended/success		-	-	-

Per-attempt records: rl run show E-0020.

Table 21: E-0021 RB1：残差旁路低维因果 linear attention 首轮筛选（plan2 R1 八组 + C_up 核对）：descriptive means over usable attempts

arm	seeds	attempts	bootstrap_repeats	checks.cases	checks.exit_
RB1-01	0	2 ended/success	-	-	-
RB1-02	0	2 ended/success	-	-	-
RB1-03	0	2 ended/success	-	-	-
RB1-04	0	1 ended/success	-	-	-
RB1-05	0	1 ended/success	-	-	-
RB1-06	0	1 ended/success	-	-	-
RB1-07	0	1 ended/success	-	-	-
RB1-08	0	2 ended/success	-	-	-
RB1-09	0	2 ended/success	-	-	-
RB1-family-LR-test	0	1 ended/success	-	16 (n=1)	0 (n=1)
RB1-final-locked-analysis	0	1 ended/success	1e+04 (n=1)	-	-
RB1-intervention-cost-smoke	0	1 ended/success	-	-	-
RB1-phase1-checks	0	1 ended/failed, 1 ended/success	-	333 (n=2)	0.5 (n=2)
RB1-prefill-decode-latency	0	1 ended/success	-	-	-
RB1-review-regression	0	1 ended/failed, 1 ended/success	-	346 (n=2)	0.5 (n=2)
RB1-training-audit-and-select	0	1 ended/success	0 (n=1)	-	-

Per-attempt records: rl run show E-0021.

Table 22: E-0022 V3：T2 链终点上的循环矩阵（共同起点阶段 + plan §9.2 十组，单 seed 筛选）：descriptive means over usable attempts

arm	seeds	attempts	arm_smoke_failures	intervene_smoke_exit	mig_instance_ho
V3-S0	-	1 ended/success	-	-	0.3565 (n=1)
tests-smoke	-	3 ended/success	0 (n=2)	0 (n=2)	-

Per-attempt records: rl run show E-0022.

Table 23: E-0023 V3 续：T2 准备度检查（未用过的 calibration，答案位置）与分阶段循环矩阵（先 S1/S2/S4）: descriptive means over usable attempts

arm	seeds	attempts	failures	mig_instance_hours	node_hours	py
V3-01	0	1 ended/success	-	0.3699 (n=1)	0.09246 (n=1)	-
V3-02	0	1 ended/success	-	0.4267 (n=1)	0.1067 (n=1)	-
V3-02-frozen-transfer	0	1 ended/success (1 not usable: spec mismatch)	-	-	-	-
V3-03	0	1 ended/success	-	0.5755 (n=1)	0.1439 (n=1)	-
V3-03-succ-correct	0	1 ended/success	-	-	0.05303 (n=1)	-
V3-03-succ-permuted	0	1 ended/success	-	-	0.0547 (n=1)	-
V3-ready	0	1 ended/success	-	0.03564 (n=1)	0.008911 (n=1)	-
V3-stageA-analysis	0	1 ended/success	0 (n=1)	-	-	-
succ-compare	0	1 ended/success	-	-	0.0001079 (n=1)	-
tests	0	2 ended/failed, 5 ended/success (3 not usable: spec mismatch)	-	-	-	0 (
tests-smoke	0	1 ended/success	-	-	-	0 (

Per-attempt records: rl run show E-0023.

Table 24: E-0024 RB1 状态读取的零训练诊断：位置 0 占比与跨 episode 常量读取指数: descriptive means over usable attempts

arm	seeds	attempts	arms_written	elapsed_s	pytest_exit
RB1-02	0	2 ended/failed, 1 ended/success	4 (n=1)	1067 (n=1)	-
RB1-02,RB1-03,RB1-08,RB1-09	0	2 ended/failed, 1 ended/success	3 (n=3)	651 (n=3)	-
checks	0	1 ended/failed, 4 ended/success	-	-	0 (n=4)

Per-attempt records: rl run show E-0024.

Table 25: E-0025 分段信息访问（PIQA/BoolQ）：只有四层侧支状态跨过 backbone 的段界: descriptive means over usable attempts

arm	seeds	attempts	audited_arms	bootstrap.repeats	bootstrap.s
SEG-00	0	1 ended/success	-	-	-
SEG-01	0	1 ended/success	-	-	-
SEG-02	0	2 ended/success	-	-	-
SEG-03	0	1 ended/success	-	-	-
SEG-04	0	1 ended/success	-	-	-
SEG-05	0	2 ended/success	-	-	-
SEG-06	0	1 ended/success	-	-	-
SEG-07	0	1 ended/success	-	-	-
SEG-checks-smoke	0	1 ended/success	-	-	-
SEG-expanded-artifact-audit	0	1 ended/success	8 (n=1)	-	-
SEG-final-locked-analysis	0	1 ended/success	-	1e+04 (n=1)	2.026e+07
SEG-initial-artifact-audit	0	1 ended/success	5 (n=1)	-	-
SEG-post-review-checks	0	1 ended/success	-	-	-
SEG-r32-locked-analysis	0	1 ended/success	-	1e+04 (n=1)	2.026e+07

Per-attempt records: rl run show E-0025.

Table 26: E-0026 RB1 宽度探针：普通（全上下文）设置下 r128 的 R_res、T0 与参数匹配 LoRA（用户要求）: descriptive means over usable attempts

arm	seeds	attempts	bootstrap_repeats	dev.boolq.accuracy	dev.boolq.exam
W-01	0	1 ended/success	-	0.813 (n=1)	1000 (n=1)
W-02	0	1 ended/success	-	0.812 (n=1)	1000 (n=1)
W-02-interventions	0	1 ended/success (1 not usable: spec mismatch)	-	-	-
W-03	0	1 ended/success	-	0.83 (n=1)	1000 (n=1)
W-analysis	0	1 ended/success	1e+04 (n=1)	-	-
W-preflight	0	1 ended/success	-	-	-
W-smoke	0	1 ended/failed	-	-	-
W-tests	0	1 ended/failed, 1 ended/success	-	-	-

Per-attempt records: rl run show E-0026.

Table 27: E-0027 E-0025 规则 8 的 BoolQ 复现：r128 三组加分段 LoRA，两个新 seed: descriptive means over usable attempts

arm	seeds	attempts	bootstrap.repeats	bootstrap.seed	checks.cases	checks.failed
SEG-04	1,2	2 ended/success	-	-	-	-
SEG-05	1,2	4 ended/success	-	-	-	-
SEG-06	1,2	2 ended/success	-	-	-	-
SEG-07	1,2	2 ended/success	-	-	-	-
analysis	0	1 ended/success	1e+04 (n=1)	2.026e+07 (n=1)	-	-
checks	1	1 ended/success	-	-	354 (n=1)	0 (n=1)
smoke	1	1 ended/success	-	-	354 (n=1)	0 (n=1)

Per-attempt records: rl run show E-0027.

Table 28: E-0028 RB1-09 的特征来源换成层输入 X（tap × 历史 2×2）与侧支输出比例 η 的搜索（用户要求）: descriptive means over usable attempts

arm	seeds	attempts	calibration.boolq.accuracy	calibration.boolq.exan
E0028-cost-reference-audit	0	1 ended/success	-	-
E0028-eta-lock	0	1 ended/success	-	-
E0028-eta-plan	0	1 ended/success	-	-
E0028-locked-analysis	0	1 ended/success	-	-
E0028-smoke	0	1 ended/success	-	-
E0028-smoke-D0060	0	1 ended/success	-	-
ETA-QK-0.0625	0	1 ended/success	0.8306 (n=1)	2048 (n=1)
ETA-QK-0.125	0	1 ended/success	0.8267 (n=1)	2048 (n=1)
ETA-QK-0.5	0	1 ended/success	0.8267 (n=1)	2048 (n=1)
ETA-QK-1	0	1 ended/success	0.8291 (n=1)	2048 (n=1)
ETA-QK-2	0	1 ended/success	0.8281 (n=1)	2048 (n=1)
ETA-X-0.0625	0	1 ended/success	0.8296 (n=1)	2048 (n=1)
ETA-X-0.125	0	1 ended/success	0.8311 (n=1)	2048 (n=1)
ETA-X-0.5	0	1 ended/success	0.8271 (n=1)	2048 (n=1)
ETA-X-1	0	1 ended/success	0.8311 (n=1)	2048 (n=1)
ETA-X-2	0	1 ended/success	0.8218 (n=1)	2048 (n=1)
RB1-09	0	1 ended/success	0.8335 (n=1)	2048 (n=1)
X-01	0	1 ended/success	0.8271 (n=1)	2048 (n=1)
X-01-interventions	0	1 ended/success	-	-
X-02	0	1 ended/success	-	-
X-03	0	1 ended/success	-	-

Per-attempt records: rl run show E-0028.

Table 29: E-0029 RB1-09 改进方向筛选：同接口 up-only LoRA、梯度子空间与 Q/K 配对初始化、只换 Q/K 来源（用户方案）: descriptive means over usable attempts

arm	seeds	attempts	calibration_seconds	diagnostic_seconds	ela
E0029-SVD-diagnostic	0	1 ended/success	-	-	37.
E0029-eight-arm-smoke	0	2 ended/failed, 2 ended/success	294.2 (n=2)	3.612 (n=2)	628
E0029-inherited-test-coverage	0	1 ended/cancelled	-	-	-
E0029-tests	0	1 ended/success	-	-	-
G-N	0	2 ended/success	-	-	47.
G-QN	0	2 ended/success	-	-	47.
G-T-IG-scale-diagnostic	0	1 ended/failed (1 not usable: spec mismatch)	-	-	-
L-56	0	3 queued/unknown	-	-	-

Per-attempt records: rl run show E-0029.

Evidence (level, validity):

- EV-0001 [diagnostic, valid] Allocated environment probe passed on mg1098 GH200 MIG 2g.24gb; driver615.71.09; outbound HTTPS available. No adapter correctness evidence yet.; scope: Execution environment only [code review: ATT-0001-2 not needed: Environment discovery only; no model or core operator execution]
- EV-0002 [diagnostic, valid] 54/60 checks passed; six failures all at suffix-causality comparison including two padded rows. Cache comparisons before assertion passed. Pinned eager masking

uses finite minimum then softmax, so padded query outputs need Base diagnosis; no hypothesis conclusion.; scope: Implementation checks with pending padding-test diagnosis [code review: ATT-0003-1 not needed: Deterministic E0 invariant checks before code review; no training or costly run]

- EV-0003 [diagnostic, valid] 61/61 V0 tests passed on GH200 MIG 2g.24gb, fixed FP32 and Base-calibrated BF16 tolerances. Zero exits match Base; two-step grads and frozen backbone checks pass; kernel output/QKV gradient and constrained-fusion identities, causality on valid tokens, cache, padding/reset, ownership, counts, M-line access and export/reload pass. Base-only diagnostic confirms previous failures were padded query logits (13.443359375 vs valid-prefix 0). Code review RV-0001 pending; no training or mechanism claim. (supports H-0001@1) [code review: ATT-0004-1 not needed: Deterministic E0 checks and Base padding diagnosis; unchanged production code and tolerances]

- EV-0004 [diagnostic, valid] RV-0001 fixes: 79/85 pass; six new positive-control failures measure rank32 effects only .359-.781 and swapped support effect .383, below detection thresholds based on unchanged BF16 calibration. Strengthen only nonzero test exits to demonstrate sensitivity before recheck; no production initialization change.; scope: Positive-control fixture adequacy [code review: ATT-0005-1 not needed: Deterministic checks of RV-0001 fixes before recheck; no training]

- EV-0005 [diagnostic, valid] 85/85 expanded V0 checks pass after RV-0001 fixes: real mutation controls rejected, delimiter support mask/capacity and stale-cache/missing-memory guards pass, masked/reset/empty kernel gradient identities pass, observed read accounting and configured key epsilon verified, actual fusion hook gradient identity passes. Nonzero fixture effects1.84375-6.890625 and swapped-owner effects3.53125-3.6484375 exceed unchanged BF16 thresholds. No training or mechanism claim; recheck pending. (supports H-0001@1) [code review: ATT-0006-1 not needed: Deterministic review-fix checks with stronger positive-control fixture; fixed production init and tolerances]

- EV-0006 [diagnostic, valid] V1 initial smoke:96 invariant tests passed and three20-step train/eval/reload paths passed;11586 train tokens. Training loss reduction subsequently superseded by coordinator MSG-0025; smoke establishes engineering compatibility/timing only, not LR or interface evidence. [code review: ATT-0007-1 not needed: deterministic regressions and 20-step three-family smoke before code review]

- EV-0007 [diagnostic, valid] Corrected equal-example V1 smoke:98 invariant tests passed including loss reduction and failed-LR continuation;three5-step training/evaluation/reload paths passed with exact reload equality.2943tokens,116s,.032222MIGh. Engineering diagnostic only; no LR selection or interface comparison. [code review: ATT-0008-1 not needed: corrected loss and divergence invariant regression plus5-step three-family smoke before review]

- EV-0008 [diagnostic, valid] RV0003fix smoke:104 invariant tests passed, including nongold NaN/Inf evaluation, retained failed-LR usage/continuation, Base nonfinite and finite reload mismatch errors, strict smoke acceptance.3families completed5steps and exact reload,2943tokens,114s,.031667 No calibration or interface claim. [code review: ATT-0009-1 not needed: RV-0003 failure-path fixes deterministic checks and5step smoke before recheck]

- EV-0009 [diagnostic, valid] Reload classification fix:106checks passed, including finite initial evaluation then actual NaN/Inf candidate guard during reload -> partial engineering error re-

taining usage without failed-LR flags. Existing initial-evaluation failure and finite reload mismatch behaviors pass.3families complete5steps/exact reload;2943tokens,119s,.033056MIGh=.008264nodeh. [code review: ATT-0010-1 not needed: RV-0004 reload error classification regression before coordinator-required new review round]

- EV-0010 [diagnostic, valid] base-eval complete finite calibration NLL 2.3312495373933837, calibration accuracies PIQA 0.72802734375 BoolQ 0.689453125; dev PIQA 0.723 BoolQ 0.68; exact reload passed. Base no training. Diagnostic LR/slice evidence only, not interface comparison. [code review: ATT-0011-2 covered by RV-0004 issues, medium open, approved by the coordinator, RV-0005 pass, RV-0006 pass]

- EV-0011 [diagnostic, valid] cal-lora-1e-4 complete finite calibration NLL 1.6253322842401003, calibration accuracies PIQA 0.7255859375 BoolQ 0.78955078125; dev PIQA 0.723 BoolQ 0.766; exact reload passed. 200280 input tokens,1103 steps,280 overshoot. Diagnostic LR/slice evidence only, not interface comparison. [code review: ATT-0012-2 covered by RV-0004 issues, medium open, approved by the coordinator, RV-0005 pass, RV-0006 pass]

- EV-0012 [diagnostic, valid] cal-lora-3e-4 complete finite calibration NLL 1.6021037854622986, calibration accuracies PIQA 0.728515625 BoolQ 0.80419921875; dev PIQA 0.733 BoolQ 0.78; exact reload passed. 200280 input tokens,1103 steps,280 overshoot. Diagnostic LR/slice evidence only, not interface comparison. [code review: ATT-0013-2 covered by RV-0004 issues, medium open, approved by the coordinator, RV-0005 pass, RV-0006 pass]

- EV-0013 [diagnostic, valid] cal-fout-1e-4 complete finite calibration NLL 1.6600830964101538, calibration accuracies PIQA 0.71923828125 BoolQ 0.7958984375; dev PIQA 0.723 BoolQ 0.777; exact reload passed. 200280 input tokens,1103 steps,280 overshoot. Diagnostic LR/slice evidence only, not interface comparison. [code review: ATT-0014-2 covered by RV-0004 issues, medium open, approved by the coordinator, RV-0005 pass, RV-0006 pass]

- EV-0014 [diagnostic, valid] cal-fout-3e-4 complete finite calibration NLL 1.6157966926032628, calibration accuracies PIQA 0.72119140625 BoolQ 0.79833984375; dev PIQA 0.725 BoolQ 0.78; exact reload passed. 200280 input tokens,1103 steps,280 overshoot. Diagnostic LR/slice evidence only, not interface comparison. [code review: ATT-0015-2 covered by RV-0004 issues, medium open, approved by the coordinator, RV-0005 pass, RV-0006 pass]

- EV-0015 [diagnostic, valid] cal-cdual-1e-4 complete finite calibration NLL 1.6392950516932028, calibration accuracies PIQA 0.72607421875 BoolQ 0.7919921875; dev PIQA 0.722 BoolQ 0.767; exact reload passed. 200280 input tokens,1103 steps,280 overshoot. Diagnostic LR/slice evidence only, not interface comparison. [code review: ATT-0016-2 covered by RV-0004 issues, medium open, approved by the coordinator, RV-0005 pass, RV-0006 pass]

- EV-0016 [diagnostic, valid] cal-cdual-3e-4 complete finite calibration NLL 1.6024291552247223, calibration accuracies PIQA 0.72705078125 BoolQ 0.798828125; dev PIQA 0.728 BoolQ 0.777; exact reload passed. 200280 input tokens,1103 steps,280 overshoot. Diagnostic LR/slice evidence only, not interface comparison. [code review: ATT-0017-2 covered by RV-0004 issues, medium open, approved by the coordinator, RV-0005 pass, RV-0006 pass]

- EV-0017 [diagnostic, valid] Deterministic E0002 audit selects3e-4 allfamilies; relative NLL gaps1.4499%,2.7408%,2.3006%; slice gate passes. E3 full train audit finds exactly1PIQA row id5528 candidates537/537tokens (.007654% of13065), BoolQ0/6379. Not in calibration prefix. E3 filter authorized MSG0058, production implementation deferred next task. No H0002

interface claim. [code review: ATT-0019-1 not needed: deterministic selection audit and identification of overlength E3 examples; unchanged data/encoding rules]

- EV-0018 [diagnostic, valid] Diagnostic-only post-shuffle/pre-interleave exclusion of PIQA5528 under MSG0058 yields E3 schedule13077steps,2000040tokens,26154examples,epoch index1; dev steps3270/6539/9808. Production filter not implemented; next task must implement/review and verify same schedule. Costs are family-based projections,28layer LoRA only conservative unmeasured bound. [code review: ATT-0020-1 not needed: cost/schedule estimate only under coordinator MSG0058; production filter and review deferred next task]

- EV-0019 [diagnostic, invalid] ATT-0021-1: 116 passed, one new audit fixture incorrectly expected success for 100 percent excluded train rows; actual guard correctly rejected >1 percent. No arm trained. Fixture repaired to exactly 1 percent without changing production guard. PBS21s, 0.005833333333333333 MIGh / 0.0014583333333333333 nodeh.; scope: Engineering regression fixture failure, not scientific evidence [code review: ATT-0021-1 not needed: Pre-review regression and twenty-step smoke for all eight arms]

- EV-0020 [diagnostic, valid] 126 tests passed; all eight arms match Base at initialization and reload exactly after20steps; parameter counts match contract, intermediate evaluation preserves training trajectory in regression, identical full 13077step/2000040token schedule with one excluded PIQA5528 row and points3270/6539/9808. LoRA28 measured steady .435291s/step. Cost .122778 MIGh=.0306945nodeh,30896inputtokens; not interface-effectiveness evidence.; scope: Implementation readiness only, eight twenty-step smokes on 32 dev examples/task [code review: ATT-0022-1 not needed: Pre-review regression and twenty-step smoke after fixture fix; revised E3 analysis]

- EV-0021 [diagnostic, valid] 145tests passed with0failures/errors/skips on e55eea3, including actual ATT0022 smoke rejection, duplicate/aliased paths, incorrect arm/config/schedule/data/order/paramet membership, and complete correctlymapped fixture acceptance. Existing paired bootstrap/selection arithmetic and V0/V1 suite preserved. PBS28s=.007778MIGh=.0019445nodeh; no trainingtokens.; scope: RV0007 formal-input validation regression only [code review: ATT-0023-1 not needed: Regression of RV-0007 validation fix before recheck]

- EV-0022 [diagnostic, valid] Rerun Base full1000/task dev and reload passed. PBS comparison validated formal Base input and exact equality of all2000 prediction records including scores/NLL, dev metric dictionary and split map againstATT0011-2. PIQA.723 BoolQ.680 macro.7015 devNLL2.3374779898760703. Base307s=.085278MIGh=.0213195nodeh; comparator1s=.000278MIGh=.0000695nodeh; no trainingtokens.; scope: Full untrained Base dev rerun and exact E-0002 comparison [code review: ATT-0024-1 covered by RV-0008 pass; ATT-0033-1 not needed: Cheap deterministic equality comparison using reviewed Base reader; no training or selection]

- EV-0023 [diagnostic, valid] E-0004 deterministic readiness checks: 130/130 V0, V1, and added state cases pass. Chunk3 FP32 state max_abs_err r32=0 and r128=3.814697265625e-6 across all three backends, inclusive/strict, S=1/4; chunk1 diagnostics r32=0.17662876844406128 and r128=0.2529714107513428. Capacity boundary 2 accepted and overflow at 1 rejected for all backends. Per-component state corruption controls rejected. Fixed tolerances unchanged. Code review pending; no training or mechanism claim. (supports H-0001@1) [code review: ATT-0034-1 not needed: Deterministic E0 readiness checks; review requested after validation per task contract]

- EV-0024 [diagnostic, valid] Read-only probe succeeded on mg1098/PBS 3760163.opbs: 169 run registry rows, 129 distinct referenced sample paths with zero locally available; nine committed sample archives contain episode/query IDs and predictions but no support facts or question text. Content-level overlap remains unverified. Pinned Qwen tokenizer confirms semicolon ID 26 and space-semicolon ID 2587. Measured PBS 9s = 0.0025 MIG-instance-h = 0.000625 node-h; usage imported from executor observation.; scope: Legacy public assets at a255e814740ff85ab3b4ec4836c88f0a8f802b2d only; no claim about H-0003 or content-level overlap. [code review: ATT-0035-1 not needed: Read-only data schema and tokenizer smoke; no model evaluation]

- EV-0025 [diagnostic, valid] 123 core/model/M-line tests passed in 46.37 seconds on registered GH200 MIG job. Eight-arm M-line Base identity, two-step gradient startup, owner reorder and snapshot isolation, offline controls/oracles and hand-computed read metrics passed. Extended smoke and code review pending.; scope: Pipeline correctness only; no support or challenge to H-0003 [code review: ATT-0036-1 not needed: Deterministic protocol checks and two-step gradient smoke before code review; no costly run]

- EV-0026 [diagnostic, valid] Eight PBS regression tests passed; 80 smoke identities and canonical contents unique; independent regeneration SHA256 matched; 92 seen and 89 unseen single-leading-token names. Legacy pinned source/registry checks establish zero labeled fact-set+question overlap by disjoint relation construction (MSG-0093), not by enumerating legacy episode content. Full dataset generation and Base evaluation pending.; scope: Generator and metric code smoke only; no Base results or H-0003 claim. [code review: ATT-0037-1 not needed: Deterministic generator and metric regression smoke before code review; no Base model evaluation]

- EV-0027 [diagnostic, valid] Eight two-step copy-fixture arms completed, 672 training input tokens, application elapsed 9.26s. Stable step about 0.128-0.172s, 244-328 tokens/s; initialization max_abs=0. Two-step positive-control normal-vs-zero/shuffled criterion not yet met; planned longer smoke follows.; scope: Timing only; two updates are not the positive-control completion test [code review: ATT-0038-1 not needed: Two-step eight-arm timing smoke after 123 passing invariant checks, before review]

- EV-0028 [diagnostic, valid] All eight arms completed 32 smoke updates, all have normal-memory answer NLL below zero and shuffled; 10752 input tokens, 42.53s application elapsed, 303-317 input tokens/s. Validates learnability on tiny copy positive control only.; scope: Two-example copy fixture only; not evidence supporting H-0003 or single-hop generalization [code review: ATT-0040-1 not needed: Task-authorized 32-step tiny copy-fixture smoke before review; measured pilot 9.26s, expected under one minute, no formal training]

- EV-0029 [diagnostic, valid] Full V2 dataset generated twice with matching hashes and 21432 unique episode identities and semantic contents: train16384/calibration2048/dev1000/sealed confirmation2000. 8 tests pass, delimiter and single-token answer checks pass. Train has1381843 input tokens per epoch, 4145529 in three epochs, covering4M per arm. Constant prior dev EM0.015. Legacy overlap0 by authorized disjoint-relation construction proof, not empirical episode enumeration. RV-0010 code review passes with zero findings.; scope: Full generator/data contract validation; no Base or memory-mechanism claim. [code review: ATT-0039-1 not needed: Deterministic data materialization after 8 passing PBS invariants; approximately 30s; no model evaluation]

- EV-0030 [diagnostic, valid] Exact commit 94fb78b integration passed 124 regression tests, eight four-update E16 smoke arms, checkpoint roundtrip and independent train/calibration probe path. 5248 smoke forwarded input tokens; 672 protocol-gradient tokens separately reported. 800-959 tokens/s, training-only V2 extrapolation 2.424 node-hours; two-backend two-LR calibration 0.0588-0.0653 node-hours. Tiny sample is not scientific validation.; scope: E-0005 provisional interface and timing; excludes shuffled address fields pending RV-0011; no H-0003 conclusion [code review: ATT-0041-1 not needed: Coordinator MSG-0106 authorizes provisional E-0005 integration smoke while RV-0010/RV-0011 pending. Four updates per eight arms, plus split probe and regression checks; no formal training.]

- EV-0031 [diagnostic, valid] Reviewed frozen Base evaluator ran with finite full-vocabulary metrics. M32 EM0 NLL9.32865; F32 EM0 NLL5.91752. Measured model load0.849s, M0.287s, F0.164s; used for full-dev walltime sizing, without changing data or protocol.; scope: 32-example dev-prefix timing smoke only; not a task-suitability estimate. [code review: ATT-0042-1 covered by RV-0010 pass]

- EV-0032 [diagnostic, valid] Full dev fixed-protocol Base: M EM0.011 NLL9.2494026874; F EM0.013 NLL5.7063963076; train-selected constant prior EM0.015. M<=prior+0.05 passes; F>=prior+0.20 fails (required0.215). Per E-0005 outcome_actions this is task-difficulty information for V2 design, not a reason to tune the protocol or a memory-mechanism refutation. Review RV-0010 passed; metrics/predictions complete and finite. Qwen3-0.6B-Base pinned revision, BF16 eager, no training.; scope: Frozen Base dev1000 M/F bounds only. Does not support or challenge H-0003 memory-read hypothesis; no confirmation evaluation. [code review: ATT-0043-1 covered by RV-0010 pass]

- EV-0033 [diagnostic, invalid] Five of six focused checks passed; SoftSlot regression hit exact NLL equality using fused mean CE vs evaluator none-then-mean CE, despite identical logits. Difference 4.77e-7. Corrected test to use defined evaluator reduction without changing production code or tolerance.; scope: Test-reference reduction mismatch; not mechanism evidence [code review: ATT-0044-1 not needed: Focused deterministic regression for RV-0011 medium diagnostic fix before recheck; no training]

- EV-0034 [diagnostic, valid] Six focused checks passed; both backends omit shuffled target-dependent address metrics and preserve entropy/neff. Distinct facts and differing targets with owners[1,0,1] produce identical diagnostic/unhooked logits and defined NLL/EM. Original-target read errors agree within1.27e-7 overall and4.47e-8 shuffled. Normal/permuted address metrics unchanged. PBS3760300.opbs exit0,12s.; scope: RV-0011 diagnostic correction only, no training [code review: ATT-0045-1 not needed: Focused deterministic RV-0011 regression rerun with matching CE reduction; no training]

- EV-0035 [diagnostic, valid] Post-merge regression on commit 3ccde7d: 155 tests passed, zero failures/errors/skips, 46.759s pytest, 49s PBS GH200 MIG; 0.013611 MIG h = 0.00340275 node h. No hypothesis inference. [code review: ATT-0046-1 not needed: post-merge regression]

- EV-0036 [diagnostic, valid] Initial diagnostic smoke: 13 tests passed, then strict E16 original-path NLL check failed. Independent PBS audit reproduced CPU versus CUDA CE reduction difference on identical logits (max 0.00006485 first M batch), zero top1 disagreements in M/F smoke. This is implementation diagnostic only; smoke scientific summaries not produced. Fix

preserves original CUDA batch scoring without tolerance changes. [code review: ATT-0047-1 not needed: diagnostic Base evaluation, seconds; reviewed with outputs before delivery; ATT-0048-1 not needed: bounded diagnostic of failed smoke outputs]

- EV-0037 [diagnostic, valid] Fixed 32-calibration smoke: 13 tests passed; diagnostic E16 exactly matches original batch8 predictions and NLL. Prefix-only batch1/8 F top1 agreement 0.96875 and NLL MAD 0.10860 miss stability thresholds; this is timing/smoke evidence, full2048 comparison still required. Application6.635s. [code review: ATT-0049-1 not needed: diagnostic Base evaluation, seconds; reviewed with outputs before delivery]
- EV-0038 [diagnostic, valid] Full calibration2048: diagnostic E16 exactly matches original batch8 EM/NLL. Implementation gate fails: F batch1/8 NLL MAD0.088144 exceeds0.05 (top1 agreement99.2676% passes99%); M passes both. E1 F NLL1.421515 below M9.233152 passes. Per E0007@2 first outcome, investigate implementation and do not use F results for V2 design yet. Descriptive full-vocab EM M0.8301%, F E16 1.4160%, F E1 66.9922%. No H0003 inference; independent code/output review pending. [code review: ATT-0050-1 not needed: diagnostic Base evaluation, seconds; reviewed with outputs before delivery]
- EV-0039 [diagnostic, valid] MSG0135 follow-up after strict BF16 gate failure: true FP32/eager first256 calibration, TF32 off, batch1/8 top1 agreement100% M/F; NLL MAD M3.98e-6 F9.56e-6 versus same-prefix BF16 M0.01325 F0.10252. Supports BF16 numerical batch/padding sensitivity rather than an observed scoring/masking defect in tested path. Full BF16 F absDeltaNLL correlation padding +0.2240, prompt length -0.2165;347 unpadded rows zero difference. Saved12288 records/6 groups audited. Strict original @2 failure retained; MSG0135 diagnostic interpretation allows weak E16 retrieval branch (candidate-b14.209%<50%). No H0003 inference; review pending. [code review: ATT-0051-1 not needed: coordinator MSG0135 authorized bounded FP32 diagnosis; reviewed with outputs before delivery]
- EV-0040 [screening, valid] V1-01 F_out: dev PIQA 0.738, BoolQ 0.818, macroNLL 1.5767698148424294. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0025-1 covered by RV-0008 pass]
- EV-0041 [screening, valid] V1-02 F_pre: dev PIQA 0.73, BoolQ 0.811, macroNLL 1.567339824867386. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0026-1 covered by RV-0008 pass]
- EV-0042 [screening, valid] V1-03 C_gate: dev PIQA 0.734, BoolQ 0.808, macroNLL 1.5777984531278557. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0027-1 covered by RV-0008 pass]
- EV-0043 [screening, valid] V1-04 C_up: dev PIQA 0.736, BoolQ 0.818, macroNLL 1.5652449947787976. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0028-1 covered by RV-0008 pass]

- EV-0044 [screening, valid] V1-05 C_dual: dev PIQA 0.739, BoolQ 0.824, macroNLL 1.5619847145143861. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0029-1 covered by RV-0008 pass]

- EV-0045 [screening, valid] V1-06 linear: dev PIQA 0.735, BoolQ 0.825, macroNLL 1.5582456389768808. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0030-1 covered by RV-0008 pass]

- EV-0046 [screening, valid] V1-07 LoRA4: dev PIQA 0.748, BoolQ 0.836, macroNLL 1.5496020224121514. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0031-1 covered by RV-0008 pass]

- EV-0047 [screening, valid] V1-08 LoRA28: dev PIQA 0.749, BoolQ 0.832, macroNLL 1.5535729848258581. Complete13077steps/2000040inputtokens/40overshoot,26154examples,388094loss tokens, matching order and parameters, exact reload. Full paired analysis and comparisons in ATT-0052-1. Single-seed screening only.; scope: E-0003@2 seed0 final checkpoint; 1000 dev examples per task; no confirmation [code review: ATT-0032-1 covered by RV-0008 pass]

- EV-0048 [screening, valid] Reviewed PBS analysis selects Fstar=F_out77.80%, Cstar=C_up77.70%. Best concat Cdual78.15% exceeds Fstar by0.35pp<1pp, hence concat_not_win. Cdual exceeds Cgate by1.05pp (fixed flag true), but nonlinear-vs-linear difference only0.15pp95CI[-.70,1.00]. Cstar trails LoRA4 by1.50pp95CI[-2.40,-.60] and LoRA28 by1.35pp[-2.50,-.20]. All8complete/exactı schedule2,000,040tokens. 10000paired stratified bootstrap seed20261029 descriptive only. Challenges broad H0002 superiority in this setting; no hypothesis-state change or V2 conclusion. Full tables and limitations in T-0003-results.md. (challenges H-0002@1); scope: E-0003@2 tokenwise F-line proxy, seed0, full fixed dev1000/task, final checkpoint; screening only [code review: ATT-0025-1, ATT-0026-1, ATT-0027-1, ATT-0028-1, ATT-0029-1, ATT-0030-1, ATT-0031-1, ATT-0032-1, ATT-0052-1 covered by RV-0008 pass]

- EV-0049 [diagnostic, valid] Verified shared V2 schedule on sealed train: order hash 0d4b55ed8655d91cf0d0532l 0.2M=>300 steps,200170 tokens,warmup15; 4M=>6000 steps,4000470 tokens,warmup300. Engineering schedule only, no hypothesis evidence. [code review: ATT-0053-1 not needed: Deterministic schedule preflight only, no training]

- EV-0050 [diagnostic, valid] 146 broad core/model and V2 checks passed in60.43s, source f7c4d2b, including twelve-arm zero-exit/protocol, exact checkpoint reload, fixed donor composition and microbatch mean-CE equivalence. No scientific conclusion. [code review: ATT-0055-1 not needed: Deterministic regression tests before review and calibration]

- EV-0051 [diagnostic, valid] F-line smoke:11 tests passed9.39s;four actual training steps2681tokens, fresh checkpoint reload32calibration+32dev exact per-row match; independent shared sample-order hash and 300/6000step counts match researcher-2. Smoke is not positive-control evidence. Earlier ATT0054-1 cwd failure cost3s and retry24s imported; combined0.001875nodeh. [code review: ATT-0054-2 not needed: Correct cwd for same four-step smoke]

- EV-0052 [diagnostic, valid] All12 arms32step smoke complete; zero-exit logits exact Base, final checkpoint dev predictions identical after reload, controls/curves finite; formal sample schedule independently matches F line. Timing only, not H0003 evidence. [code review: ATT-0056-1 not needed: Twelve-arm bounded smoke before code review;146 regression checks passed]
- EV-0053 [diagnostic, valid] Three300step200170token F calibrations finite/exact reload on2048calibration. LR1e-4/3e-4/1e-3 NLL0.02508849/0.00909726/0.00160201 EM99.414/99.805/99.951percent. Best at upper endpoint requires one3e-3 extension. Calibration signals context task learnability; formal4M and dev remain pending, no H0003 inference. [code review: ATT-0058-1, ATT-0059-1, ATT-0060-1 not needed: E0008 permits 200k calibration after tests and smoke;20tests and real4step smoke passed ATT0057;formal4M awaits review]
- EV-0054 [diagnostic, valid] Reporting-only RV0017 max aggregation fix passed focused regression,1 selected test; no model/metric-selection behavior changed. PBS-generated12-arm forecast1467-1544s per6000step arm including full final eval/curves/reload, requests2201-2316s. Forecast only. [code review: ATT-0068-1 not needed: Focused low-severity RV0017 reporting fix regression and arithmetic timing forecast]
- EV-0055 [diagnostic, valid] Required single upper endpoint3e-3 completed300steps200170tokens,calibrationNI reload. Reviewed PBS selector used calibration only across four candidates and finalized1e-3 (NLL0.00160201). No further extension;formal4M pending. [code review: ATT-0067-1 covered by RV-0018 pass]
- EV-0056 [diagnostic, valid] Six initial backend x LR calibration runs completed successfully,300steps/200170tokens each, all manifests validated. Selection pending registered arithmetic analysis ATT0070-1. Diagnostic LR calibration only; does not support or challenge H0003. [code review: ATT-0061-1, ATT-0062-1, ATT-0063-1, ATT-0064-1, ATT-0065-1, ATT-0066-1 not needed: E0009 explicitly allows calibration after tests/smoke while review RV0017 is pending;146tests and12arm smoke passed; rerun affected calibration if review changes path]
- EV-0057 [diagnostic, valid] Initial grid finite and verified300steps/200170tokens/reload. Kernel NLL5.138646/4.704182/4.627133 and soft5.130321/4.682995/4.627491 for LR3e-4/1e-3/3e-3. Both select upper endpoint0.003; sealed E0009 rule triggers single extension0.01. No H0003 conclusion. [code review: ATT-0070-1 not needed: Deterministic arithmetic analysis of already reviewed training results; no model execution]
- EV-0058 [diagnostic, invalid] T-0010 generator smoke: 9 PBS invariant tests pass; 480 rows independently reproduce with 480 unique identities and contents, zero raw and normalized V2 overlap, verified legacy relation-label disjointness and passing smoke shortcut gates. Not a full dataset or hypothesis test.; scope: E-0011 implementation smoke only; no model evaluation; no H-0005 support/challenge [code review: ATT-0073-1 not needed: deterministic smoke and invariant checks before code review; ATT-0060-1 not needed: E0008 permits 200k calibration after tests and smoke;20tests and real4step smoke passed ATT0057;formal4M awaits review]
- EV-0059 [diagnostic, valid] T-0010 generator smoke: 9 PBS invariant tests pass; 480 rows independently reproduce with 480 unique identities and contents, zero raw and normalized V2 overlap, verified legacy relation-label disjointness and passing smoke shortcut gates. Corrects the result-link recording error in invalid EV-0058.; scope: E-0011 implementation smoke only; no model evaluation; no H-0005 support/challenge [code review: ATT-0073-1 not needed: deterministic smoke and invariant checks before code review]

- EV-0060 [diagnostic, valid] Both prescribed LR0.01 endpoint extensions completed with passing artifacts at300steps/200170tokens. Final selection uses all8 candidates in registered ATT0074-1; no further extensions prescribed. Diagnostic only. [code review: ATT-0071-1, ATT-0072-1 covered by RV-0017 issues, RV-0019 pass]
- EV-0061 [diagnostic, valid] Final sealed-rule choice after single endpoint extension: KernelMatrix LR0.01 normal calibration NLL4.584628655; SoftmaxSlot LR0.003 NLL4.627490530. SoftLR0.01 rawNLL4.606242569 differs by<0.5%, so smallerLR wins. All8 candidates finite. Diagnostic calibration only; no H0003 claim. [code review: ATT-0074-1 not needed: Deterministic final calibration selection using reviewed selector; no model execution]
- EV-0062 [diagnostic, valid] Final reviewed F-line seed0 LoRA6000steps4000470tokens: calibration2047/2048 EM99.95117% vs prior1.90430% passes +20pp gate;dev1000/1000. Nonself2020/2021 and987/987,zero nonselfsubjectcopy. Exact full checkpoint reload;PBS savedoutput audit matches all summaries/counts and curve checkpoints. Single cal error NLL31.875/rank486 explains increased mean NLL0.0155656. Diagnostic context-task learnability only;neither supports nor challenges H0003. Joint E0010 release requires E0009 finite LRs and coordinator decision. [code review: ATT-0069-1 covered by RV-0018 pass; ATT-0076-1 not needed: Readonly deterministic saved-output audit; no inference or training]
- EV-0063 [diagnostic, valid] E-0011@2 rotation repair: 10 PBS tests pass, inspecting actual terminal edges in all 12 hop/order/noise combinations and the expected 83/84 dev cell sizes; all six hop-by-order ignore-relation scores equal 0.5 in calibration and dev smoke. 480 records reproduce byte-identically with zero V2 overlap and passing shortcut gates.; scope: RV-0020 regression repair; 60 rows per slice, implementation evidence only; no model evaluation or H-0005 support/challenge [code review: ATT-0075-1 not needed: deterministic smoke and regression checks for RV-0020 fix before re-check]
- EV-0064 [diagnostic, valid] Full E-0011@2 T2 preparation passes 10 tests and all data gates: train 18432, calibration 2048, dev 1000, sealed confirmation 2000 and four OOD slices of 1000. All 27480 identities/semantic contents are unique and independently reproduce; zero raw/normalized V2 overlap and legacy label disjointness rechecked. Three training epochs cover 5527605 prompt tokens. No model evaluation yet.; scope: V3 data engineering and structural shortcut gates only; no support/challenge of H-0005 [code review: ATT-0077-1 covered by RV-0022 pass]
- EV-0065 [diagnostic, valid] Base evaluator runtime smoke completes on 60 released V3 dev episodes with finite full-vocabulary scores and hop/order strata, M EM 0 and F EM 0.0333333, before full dev evaluation. Smoke is timing/engineering evidence only.; scope: E-0011 Base evaluator runtime and startup validation, not full difficulty result [code review: ATT-0079-1 covered by RV-0022 pass]
- EV-0066 [diagnostic, pending] T-0011 analysis implementation:21 synthetic PBS regressions passed in2.06s,0 failures/errors/skips. Covers H3/H4 threshold and probe rules, strict V3 near-ties, exact shared bootstrap draws, factorial normalization and formal-artifact corruption rejection. RV-0023 pass0 findings. PBS3762004.opbs on mg1098 exit0,3s walltime=0.000833 MIG-h=0.00020825 node-h. No formal training efficacy or hypothesis conclusion tested.; scope: Source9145309f16231d52bb121118779c986e875951e5; analysis-only synthetic checks; full ten-arm CLI and10000 real-artifact replicates remain pending [code review: ATT-0078-1 not needed: Low-cost synthetic analysis regression before analysis review; no training or scientific decision run]

- EV-0067 [diagnostic, valid] Full 1000-episode V3 Base dev: M EM 0.0, NLL 9.5821453819; F EM 0.009, NLL 5.5676069493, subject-copy 0.079; train-selected dev prior 0.011. M is within prior+5pp overall and for every hop. Per-hop/order outputs retained. Difficulty diagnostic only, no hypothesis support/challenge.; scope: E-0011@2 frozen M/F Base on released dev only; full-vocabulary metrics [code review: ATT-0090-1 covered by RV-0022 pass]

- EV-0068 [diagnostic, valid] Integrated V3 F-line selector smoke: all 26 PBS tests pass, including unchanged V2 defaults/failure boundaries plus V3 release pins, phase-order seeds, sealing and stratum joins. Real V3 LoRA completes four steps/3158 prompt tokens at LR1e-3 and exact fresh-Base adapter reload on 32 calibration/dev rows. Engineering readiness only, not the full 0.2M pilot.; scope: E-0011 pilot selector and checkpoint smoke; no H-0005 support/challenge [code review: ATT-0091-1 not needed: four-step engineering smoke before scoped review of V3 data selector; common F-line engine previously reviewed RV-0018]

- EV-0069 [diagnostic, valid] Fixed V3 F-line LoRA pilot completes 251 steps and 200281 support+question tokens at LR1e-3. Full2048 calibration: EM0.92529296875, NLL0.3153590976. Hop1 EM0.9297218, hop2 EM0.9604685, hop3 EM0.8856305; hops2-3 pooled EM0.9230769 vs prior0.0205128. Both per-hop and pooled +20pp gates pass. Fresh-Base adapter reload exactly matches all2048 per-episode records and file hashes. No dev or sealed model evaluation in this pilot.; scope: E-0011@2 context-retained T2 learnability under fixed 0.2M pilot; not evidence for H-0005 or permission to start M-line V3 [code review: ATT-0092-1 covered by RV-0022 pass, RV-0024 pass]

- EV-0070 [screening, valid] E-0010@2 locked H3 output: challenged, screening only, seed0 final dev1000. No arm qualifies: max normal-minus-max(zero,shuffled) EM margin is+0.6pp vs required10pp; all target weights are below0.125. Per-arm inputs in V2 order (EM normal/zero/shuffled %, NLL normal/zero/shuffled, target weight):01 [0.9/1.1/1.9;4.427822/9.248186/4.427827;0
[1.7/1.1/1.5;4.448453/9.248186/4.449490;0.059004];03 [1.6/1.1/1.2;4.422075/9.248186/4.423024;0.053784];04
[1.9/1.1/1.3;4.442024/9.249403/4.441777;0.054220];05 [0.8/1.1/1.5;4.427029/9.248186/4.426557;0.058403];06
[1.8/1.1/1.2;4.446569/9.248186/4.447419;0.057738];07 [1.7/1.1/1.1;4.425355/9.248186/4.423455;0.055640];08
[2.0/1.1/1.5;4.445451/9.248186/4.447843;0.058278];09 [2.1/1.1/1.5;4.610641/9.249403/4.609989;0.059095];10
[1.8/1.1/1.9;4.497515/9.248186/4.499404;0.052307]. Qualified0/10; eligible0/10; V3 selection none. Released E-0008 positive control passed, ATT-0069-1. ATT-0093-1/RES-0094 full real-artifact validation and10000 paired bootstrap replicates passed, PBS3762550.opbs on mg1098 exit0/5s. Normal EM0.8-2.1% and value-oracle EM1.1-2.3%: contract qualitative oracle rule points to value-writing/fusion diagnosis, without isolating the cause or ruling out addressing. Confirmation unread. (challenges H-0003@1); scope: E-0010@2 final checkpoints, ten fixed arms including C_dual, dev1000,4M budget/6000steps/4000470tokens each, seed0 screening; not confirmation or a general impossibility claim; coordinator owns conclusion review and hypothesis decision [code review: ATT-0080-1, ATT-0081-1, ATT-0082-1, ATT-0083-1, ATT-0084-1, ATT-0085-1, ATT-0086-1, ATT-0087-1, ATT-0088-1, ATT-0089-1 covered by RV-0019 pass (RV-0023 pending); ATT-0093-1 covered by RV-0023 pass]

- EV-0071 [screening, valid] E-0010@2 locked H4 output inconclusive: SoftmaxSlot better0/4 cells, KernelMatrix better0/4; neither reaches3/4. No supports/challenges flag. Four cell inputs kernel->soft (normal EM%; target weight; n_eff; normalized read error): direct/F_out [0.9->1.6;0.060240->0.053784;9.969244->1.110847;0.165140->2.492829]; direct/C_up [1.7->1.9;0.059004->0.054220;6.274531->1.033493;0.354737->0.488782]; qknorm/F_out [0.8->1.7;0.058403->0.055640;5.618480->2.537960;0.392928->0.289613]; qknorm/C_up [1.8->2.0;0.057738->0.058278;4.044499->5.774581;0.433630->0.245538]. Soft EM is higher in all four cells, but none also has both higher target weight

and lower n_eff. C_dual probes excluded. Reader normal-EM factorial effect+0.50pp, paired bootstrap95% interval[-0.05,+1.05]pp; intervals descriptive,10000 draws seed20261029, same episode indices across arms/controls. This does not establish a useful read operator or explain differences by matrix compression.; scope: H-0004 four feature-by-fusion cells only F_out/C_up, final dev1000, seed0 screening; strict simultaneous rule unchanged; hypothesis status remains coordinator-owned [code review: ATT-0080-1, ATT-0081-1, ATT-0082-1, ATT-0083-1, ATT-0084-1, ATT-0085-1, ATT-0086-1, ATT-0087-1, ATT-0089-1 covered by RV-0019 pass (RV-0023 pending); ATT-0093-1 covered by RV-0023 pass]

- EV-0072 [diagnostic, valid] E-0012 L0-L4 measurements complete and independently audited: sixL0 controls96.6278%-100% (min31663/32768; question2048/2048). L1 delimiter-tail direct32648/32768,qknorm30433/32768; last-question supervised address acrossr128/256/512/1024 direct1804-1847/2048,qknorm1684-1756/2048. L2 trained value-tail direct8151-12148/32768,qknorm5556-8615/32768 versus random12609/32768,10539/32768. L3clean-to-clean341-472/2048,read-to-read37-47/2048,clean-to-read38-62/2048 acrossten checkpoints. L4 every trainedarm last-question argmaxslot0 in1000/1000 dev episodes, target52/1000,same-relation249/1000; key cosine means0.888802-0.999020 with120000pairs/arm; last fusion/residual mean18.6638-1.12365e6 withn1000/arm under stated increment definitions. RV-0027 pass; exact120probe/10L3/14L4 entries; independent counts/baseline/selection/hash/manifest/histogram checks passed; five earlier regressions passed. TotalE0012=1071MIGs=.074375nodeh. Descriptive diagnostic evidence only; no information-absence, causal or route conclusion.; scope: E-0012@1 fixed V2 T1 seed0; train16384 with14336 fit/2048 internal selection, calibration2048, dev1000; L3train4096/calibration2048 ridge1; no confirmation, M-line training, hypothesis update or route selection [code review: ATT-0096-1 covered by RV-0027 pass; ATT-0097-1 not needed: Deterministic independent artifact validator; no extraction, fitting, training, evaluation, split or metric change; measurement core covered by RV-0027]

- EV-0073 [diagnostic, valid] V5 three-arm engineering smoke passed:36 V1/V5 regressions;39 optimizer steps per arm;FP32 trainable counts524288/524288/630784;exact zero-exit Base logits and fresh-Base dev reload for all arms;three epoch-end monitoring points. Full plan19443 rows x3=58329 presentations,29165 steps,4173300 input tokens; same seed0 order across arms. This is implementation evidence only, not hypothesis support.; scope: E-0013@3 code f4b2c19;GH200 MIG2g.24gb on mg1098/PBS3764329;dev32 per task for smoke, no official validation. Stable step seconds C0.1990/F0.1950/L0.4083. Measured181MIGseconds=0.01256944 node-h;launcher failure separate2seconds. [code review: ATT-0098-2 not needed: Low-cost V5 regression and end-to-end smoke before code review; no LR selection or formal training]

- EV-0074 [diagnostic, invalid] 8 focused latency regression tests pass on2250925: synthetic LoRA merge weight update/wrapper removal;null,empty,whitespace,non-string checkpoint path rejection;both checkpoint files required before loading. RV-0035 pass. No full256 timing measured yet.; scope: Engineering only;PBS3764470 mg1100,10MIGseconds=0.00069444 node-h;no task-data or trained checkpoint inference. [code review: ATT-0110-1 not needed: Focused low-cost regression before recheck RV-0034;no full latency benchmark or confirmation data; ATT-0099-1 not needed: Cheap synthetic regression, dev-only software rehearsal and one Base WikiText timing before review; no validation access, training or selection]

- EV-0075 [diagnostic, valid] 8 focused latency regression tests pass on2250925: synthetic LoRA merge weight update/wrapper removal;null,empty,whitespace,non-string checkpoint path rejection;both checkpoint files required before loading. RV-0035 pass. No full256 timing measured yet. Corrects the administrative result-link error in invalid EV-0074.; scope: Engineering

only;PBS3764470 mg1100,10MIGseconds=0.00069444 node-h;no task-data or trained checkpoint inference. [code review: ATT-0110-1 not needed: Focused low-cost regression before recheck RV-0034;no full latency benchmark or confirmation data]

- EV-0076 [diagnostic, valid] 4 initial-grid report regressions passed on87bbb59:raw-minimum extension before tie choice,incomplete/mismatched budgets rejected,unflagged null NLL rejected,explicit failed LR with partial usage accepted. RV0038 pass. This does not yet execute report on actual grid results.; scope: Synthetic manifest fixtures only;PBS3764578 mg1098 Exit0,10MIGseconds=0.00069444 node-h;no official validation or model inference. [code review: ATT-0114-1 not needed: Focused low-cost regression for RV-0037 low finding before recheck;no selection from actual results or training]

- EV-0077 [diagnostic, valid] All9 initial seed0 LR calibrations completed with finite NLL,matched1101steps/220 Reviewed report requires3e-3 extension for all3arms;initial best1e-3 is provisional,not a final lock. Calibration only;no support/challenge claim.; scope: ATT0117 retains automatic stale review flag:per coordinator MSG0363,executed report/trainer exactly match RV0038/RV0033;stale entries were T0014 files absent from old branch and never imported. Master merge5cad3e restores covered status for all3endpoint registrations;byte-identical checks passed. Initial9 actual5996MIGseconds=0.41638889node-h;report10seconds separate. [code review: ATT-0101-1, ATT-0102-1, ATT-0103-1, ATT-0104-1, ATT-0105-1, ATT-0106-1, ATT-0107-1, ATT-0108-1, ATT-0109-1 covered by RV-0033 pass, RV-0034 issues; ATT-0117-1 stale: research/artifacts/T-0014/sealed-manifest.json changed since RV-0039; research/notes/T-0014-RV-0036-fixes.md changed since RV-0039; research/notes/T-0014-lock-schema.md changed since RV-0039; 8 more]

- EV-0078 [diagnostic, valid] Untrained Base dev1000 per task:PIQA accuracy0.723 NLL2.750281812879043;Bo accuracy0.680 NLL1.9246741668730973;task-mean NLL2.3374779898760703. Fresh Base repeat produced exactly identical per-example scores/predictions and metrics. No official validation read.; scope: Same-device dev repeat onGH200 MIG2g.24gb,mg1100/PBS3764504;344MIGseconds=0.023 h. Diagnostic baseline/noise only. [code review: ATT-0113-1 covered by RV-0033 pass, RV-0034 issues, RV-0035 pass (RV-0036 pending, RV-0037 pending)]

- EV-0079 [diagnostic, valid] Required3e-3 endpoints all finite and paired1101steps/200103tokens;all12 calibration manifests passed reviewed lock CLI. Final LR1e-3 for C,F,L;exact lock committed before any seed1–3 run. LockSHA25670ba5356203afc128cbf3e4c14a7b4474ece54a55d28b8401b852d957069e01 No dev or official-validation selection.; scope: E0013@3;lock source5cad3e,committed config2b5c809. Endpoint2047MIGseconds=0.14215278node-h;lock14seconds separate. Diagnostic selection/provenance only. [code review: ATT-0118-1, ATT-0119-1, ATT-0120-1, ATT-0128-1 covered by RV-0033 pass, RV-0034 issues, RV-0035 pass, RV-0037 issues, RV-0038 pass, RV-0039 pass]

- EV-0080 [screening, valid] R1 (train E=1): value path usable. E=1 dev normal/zero/shuffled correct 836/9/10 → margin +82.6 pp (R1 gate ≥50 pp: pass; normal−zero 95% CI 80.3–85.0 pp); NLL 0.538 vs 9.265/18.229. Addressing parameters get no gradient at E=1, so on E=16 dev: 4/11/6 correct (−0.7 pp), NLL 18.74 vs 9.25/18.90, target weight 0.061, last-position argmax hits target 4.9%; H3 fail. Fusion/residual at last position ≈18.5×.; scope: E-0014@1 seed 0 final checkpoint, M-line T1 hop 1, E=16 dev n=1000 (ATT-0039-1); single-seed screening; CIs are paired-bootstrap descriptive only [code review: ATT-0122-1, ATT-0138-1 covered by RV-0041 pass]

- EV-0081 [screening, valid] R2 (train E=4): E=4 dev correct 82/0/16 → +6.6 pp, NLL 3.687 < 5.955, target weight 0.371 → R2 gate fail (needs ≥10 pp and ≥0.5). E=16 dev 23/11/8 → +1.2 pp (normal−shuffled CI 0.5–2.6 pp), NLL 6.222 < 6.724, target weight 0.091 → H3 fail. Last-position argmax picks a same-relation fact 99.8% of the time (target 24.2%): addressing keys on relation, not head entity.; scope: E-0014@1 seed 0 final checkpoint, M-line T1 hop 1, E=16 dev n=1000 (ATT-0039-1); single-seed screening; CIs are paired-bootstrap descriptive only [code review: ATT-0123-1, ATT-0138-1 covered by RV-0041 pass]

- EV-0082 [screening, valid] R3 (curriculum E 1→4→8→16 by step): E=16 dev 10/11/12 → −0.2 pp, NLL 4.4315 vs 4.4296 shuffled, target weight 0.052, last-position argmax slot 0 in 100% (n_eff 1.000): the V2-03 collapse recurs; H3 fail. Calibration monitors at segment ends: E=1 EM 15.3% (step 1000), E=4 1.6%, E=8 1.6%, E=16 2.1%. End-of-training E=1 dev 64/9/20 (+4.4 pp), E=4 dev 30/0/10 (+2.0 pp).; scope: E-0014@1 seed 0 final checkpoint, M-line T1 hop 1, E=16 dev n=1000 (ATT-0039-1); single-seed screening; CIs are paired-bootstrap descriptive only [code review: ATT-0124-1, ATT-0138-1 covered by RV-0041 pass]

- EV-0083 [screening, valid] R4 (prior path r32 trained 1000 steps at zero memory then frozen, verified unchanged): the prior path alone gives E=16 dev NLL 4.740 (vs 9.248 zero memory without it). After memory training: 6/11/12 → −0.6 pp, NLL normal 4.4303 = shuffled 4.4303, target weight 0.061, last-position argmax slot 0 100%; H3 fail. Absorbing the answer prior did not stop the slot-0 collapse.; scope: E-0014@1 seed 0 final checkpoint, M-line T1 hop 1, E=16 dev n=1000 (ATT-0039-1); single-seed screening; CIs are paired-bootstrap descriptive only [code review: ATT-0125-1, ATT-0138-1 covered by RV-0041 pass]

- EV-0084 [screening, valid] R5 (with address supervision: +1·(−log w_target) at last question position, extra supervision): E=16 dev 62/11/16 → +4.6 pp (normal−shuffled CI 3.1–6.2 pp), NLL 4.102 < min(9.248, 4.970) pass, token-mean target weight 0.143 ≥ 0.125 pass, EM margin < 10 pp → H3 fail. Last position: target weight 0.518, argmax = target 60.2%, same relation 100%. oracle_value EM only 10.7% (NLL 3.64), oracle_key 6.7%: even a correct read decodes poorly at E=16.; scope: E-0014@1 seed 0 final checkpoint, M-line T1 hop 1, E=16 dev n=1000 (ATT-0039-1); single-seed screening; CIs are paired-bootstrap descriptive only [code review: ATT-0126-1, ATT-0138-1 covered by RV-0041 pass]

- EV-0085 [screening, valid] R6 (centered cosine address, learnable tau init 10): E=16 dev 15/11/13 → +0.2 pp, NLL 4.4205 vs 4.4244 shuffled, target weight 0.060, n_eff 5.73, last-position argmax slot 0 86.3%; H3 fail. Fusion/residual at last position ≈41.7×.; scope: E-0014@1 seed 0 final checkpoint, M-line T1 hop 1, E=16 dev n=1000 (ATT-0039-1); single-seed screening; CIs are paired-bootstrap descriptive only [code review: ATT-0127-1, ATT-0138-1 covered by RV-0041 pass]

- EV-0086 [diagnostic, valid] ATT-0144-1 (V2-03) failed the E-0015 dev reload check (normal 51/1000, zero 12/1000, shuffled 37, oracle_value 11 mismatches; NLL max |diff| 0.14-0.23) because it ran on mg1098_mig3, which nvidia-smi reports as a MIG 1g.24gb device with 26 SMs (the ledger labels it 2g.24gb). ATT-0146-1 on the same slice, same code, evaluator settings identical to E-0010 (batch 16, right padding, episode order sha b52c83a6...): R1 also mismatches (normal 4, zero 12), V2-03 repeats the same 51/12 in-process, and the Base-only zero forward differs from the recorded zero predictions (12/1000). So BF16 kernel choice on the other MIG profile changes results; the checkpoint is not at fault. ATT-0144-2 on a 2g.24gb slice (guarded by nvidia-smi) reproduces all four recorded V2-03 dev controls exactly, as R1/R2/R5 (ATT-0141..0143) did. Bitwise cross-job reproducibility in this project needs 2g.24gb slices.;

scope: E-0015 reload check; Miyabi debug-mig slice mg1098_mig3 [code review: ATT-0144-1 stale: src/v2_train.py changed since RV-0041 (RV-0042 pending); ATT-0146-1 not needed: diagnostic of the reload check / tests for the RV-0042 recheck; included in the recheck]

- EV-0087 [diagnostic, valid] R1 calibration EM normal E=1/4/16 = 84.1/1.1/0.5%. Contextual oracle_value 84.1/21.9/7.6%, high only for target fact 0 (E=16: 83.4% t0 vs 1.6% t>=1). Isolated-encoding iso_oracle_value 85.3% (E=4) and 86.4% (E=16; 83.4% t0, 86.7% t>=1); iso_wrong_oracle 1.5% vs answer prior 1.9%; iso_v/iso_kv E=16 2.1/2.5%. Probes: Pv context 74.5/47.9/37.6%, Pv isolated 77.6% (E=16), Pv iso->ctx 7.1% (E=16), Pf context 99.8/97.4/94.9%. Contextual values at fact positions >=1 have ~2x the L2 of position 0 / isolated values (E=16: 43.5 vs 103.1 (1-3), 89.2 (>=4)); frozen delimiter features do not change in L2 (~57). Sweep at E=1: alpha 0.1/0.3 EM 1.0/55.7%, non-final-only 82.4/83.6%. Rules 4 and 5 hold on R1.; scope: E-0015@4 diagnostics, checkpoint R1 (ATT-0122-1 final), calibration E=1/4/16 (2048 rows each); E=16 dev reload bitwise identical [code review: ATT-0141-1 stale: src/v2_train.py changed since RV-0041 (RV-0042 pending); ATT-0148-1 stale: src/v2_train.py changed since RV-0041]

- EV-0088 [diagnostic, valid] R2 calibration EM normal E=1/4/16 = 11.9/9.7/2.8%; oracle_value 11.9/9.5/4.1%; last_only - normal E=4 -1.5 pp; iso_v - normal +1.7 pp (E=4), +1.1 pp (E=16); iso_oracle_value 12.2/10.9% (E=4/16); uniform 3.7% (E=4). Probes: Pv context 71.1/45.9/38.8%, Pv isolated 75.2/75.3% (E=4/16), Pf context 99.8/97.4/94.9%, Pz normal 46.1/21.7/3.5%. Magnitude sweep at E=4: alpha 0.1/0.3 EM 0.9/5.7% (normal), 1.4/5.9% (oracle_value), 8.1/8.9% (non-final only), all below alpha=1. Contextual values keep one dominant coordinate (dim 63) at every position; L2 rises from 70.7 (pos 0) to 88.9 (pos >=4, E=16). Rule 1 does not hold (Pv 45.9% < 80%); rule 2 holds here (Pv < 50%, Pf >= 90% at E=4/16); rules 3, 6, 7 do not.; scope: E-0015@4 diagnostics, checkpoint R2 (ATT-0123-1 final), calibration E=1/4/16 (2048 rows each); E=4 and E=16 dev reload bitwise identical [code review: ATT-0142-1 stale: src/v2_train.py changed since RV-0041 (RV-0042 pending); ATT-0148-1 stale: src/v2_train.py changed since RV-0041]

- EV-0089 [diagnostic, valid] R5 calibration EM normal E=1/4/16 = 6.1/7.6/6.4%; oracle_value 6.1/7.2/10.4%; last_only - normal E=16 -0.9 pp; iso_v - normal -3.2 pp (E=4), -3.3 pp (E=16); iso_oracle_value 4.7/6.0% (E=4/16); uniform 2.1% (E=16). Probes: Pv context 69.4/45.8/45.8%, Pv isolated 74.8/75.1% (E=4/16), Pf context 99.8/97.4/94.9%, Pz normal 44.4/22.2/11.7%. Magnitude sweep at E=16: alpha 0.1/0.3 EM 0.5/3.7% (normal), 0.9/6.0% (oracle_value), 6.2/6.0% (non-final only). Values have L2 ~77-82 with one dominant coordinate (dim 27) at every position, contextual and isolated. Rule 1 does not hold (Pv 45.8% < 80%, oracle_value 10.4%); rule 2 holds here; rules 3, 6, 7 do not.; scope: E-0015@4 diagnostics, checkpoint R5 (ATT-0126-1 final), calibration E=1/4/16 (2048 rows each); E=16 dev reload bitwise identical [code review: ATT-0143-1 stale: src/v2_train.py changed since RV-0041 (RV-0042 pending); ATT-0148-1 stale: src/v2_train.py changed since RV-0041]

- EV-0090 [diagnostic, invalid] V2-03 is at chance under every control: calibration EM 1.0-2.2% for all controls at E=1/4/16 (normal 1.6/1.7/1.5%, oracle_value 1.6/1.7/1.3%, iso_oracle_value 1.7/1.3%), answer prior 1.4-1.9%. Probes: Pv context 69.3/38.4/32.9%, Pv isolated 73.7/74.3% (E=4/16), Pf context 99.8/97.4/94.9%, Pz normal 35.7/5.3/1.4%. Contextual values shrink with fact position (E=16 L2 109.7 at pos 0, 68.3 at 1-3, 44.4 at >=4); isolated values stay at 109.7. Rule 2 holds here (Pv < 50%, Pf >= 90% at E=4/16).; scope: E-0015@4 diagnostics, reference V2-03 (ATT-0082-1 final), calibration E=1/4/16 (2048 rows each); E=16 dev reload

bitwise identical on a MIG 2g.24gb slice (ATT-0144-1 on a 1g slice mismatched, see EV-0086) [code review: ATT-0144-2, ATT-0148-1 stale: src/v2_train.py changed since RV-0041]

- EV-0091 [diagnostic, valid] V2-03 is at chance under every control: calibration EM 1.0-2.2% for every non-zero control at E=1/4/16 (normal 1.6/1.7/1.5%, oracle_value 1.6/1.7/1.3%, iso_oracle_value 1.7/1.3%), zero 0.7/0.9/0.8%, answer-prior EM 1.4/1.3/1.9%. Probes: Pv context 69.3/38.4/32.9%, Pv isolated 73.7/74.3% (E=4/16), Pf context 99.8/97.4/94.9%, Pz normal 35.7/5.3/1.4%. Contextual values shrink with fact position (E=16 L2 109.7 at pos 0, 68.3 at 1-3, 44.4 at >=4); isolated values stay at 109.7. Rule 2 holds here (Pv < 50%, Pf >= 90% at E=4/16). Replaces EV-0090.; scope: E-0015@4 diagnostics, reference V2-03 (ATT-0082-1 final), calibration E=1/4/16 (2048 rows each); E=16 dev reload bitwise identical on a MIG 2g.24gb slice (ATT-0144-1 on a 1g slice mismatched, see EV-0086) [code review: ATT-0144-2, ATT-0148-1 stale: src/v2_train.py changed since RV-0041]

- EV-0092 [diagnostic, valid] Hardware audit:two original calibration manifests report1g.24gb(C1e-3 ATT0103 and L1e-4 ATT0107),other14 completed model manifests report2g;old manifest hashes match the unchanged LR lock. New allocated-UUID guard passed live2g on mg1098 and7 regressions including1g masked by unrelated2g. No inference/timing method changed.; scope: D0015 preserves original valid LR rule/lock and9formal runs;two diagnostic2g sensitivity reruns authorized,not yet complete. Guard sourcefbf97b4,ATT0149/PBS3765777 Exit0,2MIGs. No retroactive nvidia-smi evidence claimed for prior jobs. [code review: ATT-0103-1, ATT-0107-1 covered by RV-0033 pass, RV-0034 issues; ATT-0149-1 not needed: Infrastructure fail-fast guard per coordinatorMSG0408;no model path or timing method changed;fixtures and live inventory only]

- EV-0093 [diagnostic, valid] Two completed duplicate calibration attempts imported as plain diagnostic records under D0018/MSG0472. No slice comparison,lock recomputation or LR-selection analysis performed. Original lr-lock.json is final and unchanged.; scope: Same original RunSpecs,seed0,1101steps/2202examples/200103tokens;execution and raw outputs only. Profiles metadata only;no sensitivity caveat and no retraining. [code review: ATT-0103-2, ATT-0107-2 not needed: D0015 slice sensitivity rerun;identical RunSpec/model code reviewed RV0033;no new model path. Tested guard fbf97b4 is launcher-only. Unexecuted T0014 files absent from original snapshot.]

- EV-0094 [diagnostic, valid] All six C/F seed1–3 training runs complete:29165steps,58329presentations,4173300 tokens each;all3epoch dev monitoring,final checkpoint/inventory and exact fresh-Base reload. Original LRlock hash matches;C/F training orders paired within each seed. Three LoRA runs remain in progress.; scope: Training/dev/provenance only,not confirmation evidence. Hardware profiles retained as metadata per D0018/D0019;no rerun or flag based on slice. Official validation not accessed. [code review: ATT-0129-1, ATT-0130-1, ATT-0131-1, ATT-0132-1, ATT-0133-1, ATT-0134-1 covered by RV-0033 pass, RV-0034 issues, RV-0035 pass, RV-0037 issues, RV-0038 pass, RV-0039 pass]

- EV-0095 [screening, valid] D5 passes the E-0010@2 H3 thresholds under the isolated write: EM normal 42.8% vs zero 1.1%, shuffled 1.7% (margin 411/1000 = 41.1 pp); NLL 2.514 < 9.248, 7.977; target weight all positions 0.162 (>= 0.125), last position 0.571. Passes in both strata: target 0 (n=52) EM 44.2, margin 38.5 pp, weight 0.140; target >=1 (n=948) EM 42.7, margin 41.2 pp, weight 0.163. Isolated permuted 2.4, oracle_key 24.5, oracle_value 73.6. Contextual-encoding normal (descriptive) 5.7% (t0 65.4 / t>=1 2.4), NLL 15.05. Curve EM normal 4.3/20.6/35.3/42.8 at 25/50/75/100%. Reload identical; R1 replay 0/1000 mismatches. Single

seed screening. (supports H-0012@1); scope: E-0016@1 D5 (R1 ATT-0122-1 adapter-only continuation, 6000 steps, seed 0), isolated-encoding write protocol (new; reported separately from E-0010 H3), E=16 dev 1000 episodes, code 415cac3 [code review: ATT-0159-1 stale: src/v2_train.py changed since RV-0041, RV-0045]

- EV-0096 [screening, valid] D4 does not meet the H3 thresholds under the isolated write: EM normal 1.4% vs zero 1.1%, shuffled 1.1% (margin 3/1000 = 0.3 pp); NLL normal 4.423 < zero 9.248 but not < shuffled 4.424; target weight all positions 0.058 (< 0.125), last position 0.063 with last-position n_eff 16.0 (uniform over the 16 slots). Fails in both strata (t0 n=52 margin 1.9 pp, weight 0.049; t>=1 n=948 margin 0.2 pp, weight 0.058). oracle_key 1.4, oracle_value 1.4, permuted 1.7. The memory acts as a content-independent bias (normal NLL = shuffled NLL). Train CE plateau ~4.41 from step ~2500; curve EM normal 1.0/1.0/1.8/1.4 at 25/50/75/100%. Contextual normal (descriptive) 2.2%. Reload identical; initial zero-exit = Base (0.0). Single seed screening.; scope: E-0016@1 D4 (from scratch, 6000 steps, seed 0), isolated-encoding write protocol (new; reported separately from E-0010 H3), E=16 dev 1000 episodes, code 415cac3 [code review: ATT-0158-2 stale: src/v2_train.py changed since RV-0041, RV-0045]

- EV-0097 [screening, valid] D1 seed0 supports the stage1 decoder portion of H0010 under explicit target-slot supervision: tf_normal668/1000 vs zero11 and tf_shuffled13,margin65.5pp passes the50pp point gate; tf_wrong8. OLS fitted decline0.052743nat,plateau=false. Standard all-slot normal23/1000; oracle_value668/1000. Complete6000steps,full1000dev and exact same-run reload; all checkpoint/audit checks pass. No supports/challenges edge or hypothesis verdict.; scope: E0016@1 D1 only; supervised teacher-forced stage1,seed0 screening; final-window LR max7.3896%peak,plateau label schedule-conditioned; descriptive intervals conditional on trained seed; no confirmation. [code review: ATT-0154-1 stale: src/test_v2r_diagnostics.py changed since RV-0043; src/v2r_diagnostics.py changed since RV-0043; src/v2r_reload_check.py changed since RV-0043 (RV-0046 pending); ATT-0169-1 stale: src/test_v2r16_isolated.py changed since RV-0046, RV-0048; src/test_v2r_diagnostics.py changed since RV-0043; src/v2_isolated.py changed since RV-0046; 3 more]

- EV-0098 [screening, valid] D2a seed0 addressing-only continuation from supervised D1: normal50/1000,zero11,shuffled18 =>3.2pp margin below10pp; normalNLL5.302961 below both controls; all-question target weight0.069221<0.125. Standard H3 point gate not passed. Last-position target weight0.161943 is descriptive. Full6000 continuation steps,full1000dev/E1,exact same-run reload and final artifact audit pass; decoder A_v/Ro/P remains bitwise equal to D1 and all three addressing tensors changed. No supports/challenges edge or hypothesis verdict.; scope: E0016@1 D2a seed0 screening; total recipe includes supervised D1 prewarm,adapter-only load,fresh optimizer/warmup and derived order; H3 uses token-weighted all-question positions; profile metadata only D0018/19; no confirmation. [code review: ATT-0162-1, ATT-0169-1 stale: src/test_v2r16_isolated.py changed since RV-0046, RV-0048; src/test_v2r_diagnostics.py changed since RV-0043; src/v2_isolated.py changed since RV-0046; 3 more]

- EV-0099 [screening, valid] D2b seed0 all-adapter continuation from supervised D1: normal48/1000,zero11,shuffled18 =>3.0pp margin below10pp; normalNLL4.349222 below both controls; all-question target weight0.086935<0.125. Standard H3 point gate not passed. Last-position target weight0.135142 is descriptive; oracle_value170/1000. Full6000 continuation steps,full1000dev/E1,exact same-run reload and final artifact audit pass. No supports/challenges edge or hypothesis verdict.; scope: E0016@1 D2b seed0 screening; recipe includes supervised D1 prewarm,adapter-only load,fresh optimizer/warmup and derived order;

H3 uses token-weighted all-question positions; profile metadata only D0018/19; no confirmation. [code review: ATT-0163-1, ATT-0169-1 stale: src/test_v2r16_isolated.py changed since RV-0046, RV-0048; src/test_v2r_diagnostics.py changed since RV-0043; src/v2_isolated.py changed since RV-0046; 3 more]

- EV-0100 [screening, valid] D3 seed0 latent-slot marginal training: hard last-only normal15/1000,zero11,shuffle =>0.4pp margin below10pp; normalNLL4.424336 below both controls; last-position target weight0.061145<0.125. Registered hard H3 point gate not passed. Soft normal16/1000,NLL4.425512;marginal normal9/1000,NLL4.424916. Complete6000steps,full1000dev and exact same-run reload; final audit passed. No supports/challenges edge or hypothesis verdict.; scope: E0016@1 D3 seed0 screening; no target-index training input; hard/soft/marginal use the new last-question-position protocol and are distinct from standard E0010 H3. Descriptive paired intervals only; profile metadata D0018/19; no confirmation. [code review: ATT-0155-1 stale: src/test_v2r_diagnostics.py changed since RV-0043; src/v2r_diagnostics.py changed since RV-0043; src/v2r_reload_check.py changed since RV-0043 (RV-0046 pending); ATT-0169-1 stale: src/test_v2r16_isolated.py changed since RV-0046, RV-0048; src/test_v2r_diagnostics.py changed since RV-0043; src/v2_isolated.py changed since RV-0046; 3 more]

- EV-0101 [diagnostic, valid] All nine final V5 training runs complete/passed at E0013@3, LR0.001,29165steps/58329examples/4173300inputtokens each; exact within-job saved checkpoint reload. PBS ATT0174 preflight authenticates all9 inventories/configs/weights and matching per-seed sample orders. Training/dev implementation evidence only.; scope: T0013 training/checkpoint readiness and descriptive dev/cost;original LR lock final;profiles metadata only;no official validation access,no H0008 supports/challenges,no slice comparison [code review: ATT-0129-1, ATT-0130-1, ATT-0131-1, ATT-0132-1, ATT-0133-1, ATT-0134-1, ATT-0135-1, ATT-0136-1, ATT-0137-1 covered by RV-0033 pass, RV-0034 issues, RV-0035 pass, RV-0037 issues, RV-0038 pass, RV-0039 pass]

- EV-0102 [screening, valid] P1 passes the E-0010@2 H3 thresholds under the isolated write: EM normal 49.7% vs zero 1.1%, shuffled 1.9% (margin 239/500 = 47.8 pp); NLL 2.279 < 9.249, 8.583; target weight all positions 0.162, last 0.610; last-position n_eff 1.97, most common last slot rate 0.076 (no fixed-slot collapse). Strata: t0 (n=52) EM 50.0, margin 48.1 pp, weight 0.152; t>=1 (n=948) EM 49.7, margin 47.8 pp, weight 0.162 - both pass. Isolated permuted 2.3, oracle_key 23.2, oracle_value 77.1. Stage A (ATT-0166-1, R1 recipe seed 1): E=1 dev EM normal 82.7 / zero 0.9 / shuffled 1.1 (R1 seed 0: 83.6). Descriptive: E=16 calibration isolated normal 49.5 / zero 0.8 / shuffled 1.6; contextual dev normal 4.9 (t0 67.3 / t>=1 1.5). Curve EM 6.0/22.7/41.1/49.7. Start adapter digest pinned (b5b2aec9...) and matched; replay of stage A's recorded dev predictions 4/1000 mismatches on a 1g slice (recorded only, D-0018/D-0019); reload identical. (supports H-0012@1); scope: E-0017@1, isolated-encoding write protocol (reported separately from E-0010 H3), E=16 dev 1000 episodes, code 7d53d5d (RV-0054), D5 recipe 6000 steps, single run per arm; P1: stage A R1 recipe seed 1 (ATT-0166-1) -> stage B continuation seed 1 (ATT-0172-1); replication arm [code review: ATT-0166-1 not needed: D-0020: RV-0049 found nothing on the stage-A path; v2_train.py/v2_schedule.py byte-identical 64331a4..f01b036; ATT-0172-1 covered by RV-0054 pass]

- EV-0103 [screening, valid] P2 passes the E-0010@2 H3 thresholds under the isolated write: EM normal 48.0% vs zero 1.1%, shuffled 1.8% (margin 231/500 = 46.2 pp); NLL 2.378 < 9.248, 8.241; target weight all positions 0.158, last 0.600; last-position n_eff 2.01, most common last slot rate 0.077. Strata: t0 (n=52) EM 50.0, margin 48.1 pp, weight 0.143; t>=1 (n=948)

EM 47.9, margin 46.1 pp, weight 0.159 - both pass. Stage A (ATT-0167-1, R1 recipe seed 2): E=1 dev EM normal 81.1 / zero 0.9 / shuffled 0.9. Start adapter digest pinned (aa3919e2...) and matched; replay 0/1000 mismatches; reload identical. (supports H-0012@1); scope: E-0017@1, isolated-encoding write protocol (reported separately from E-0010 H3), E=16 dev 1000 episodes, code 7d53d5d (RV-0054), D5 recipe 6000 steps, single run per arm; P2: stage A R1 recipe seed 2 (ATT-0167-1) -> stage B continuation seed 2 (ATT-0173-1); replication arm [code review: ATT-0167-1 not needed: D-0020: RV-0049 found nothing on the stage-A path; v2_train.py/v2_schedule.py byte-identical 64331a4..f01b036; ATT-0173-1 covered by RV-0054 pass]

- EV-0104 [screening, valid] C1 (descriptive) passes the H3 thresholds under the isolated write: EM normal 45.3% vs zero 1.1%, shuffled 2.3% (margin 43/100 = 43.0 pp); NLL 2.406 < 9.249, 8.205; target weight all 0.150, last 0.589. Strata: t0 EM 42.3, margin 34.6 pp, weight 0.131; t>=1 EM 45.5, margin 43.5 pp, weight 0.151 - both pass. Start adapter = trusted R1 digest 9ea30adb...; replay 4/1000 mismatches on a 1g slice (recorded only); reload identical. (supports H-0012@1); scope: E-0017@1, isolated-encoding write protocol (reported separately from E-0010 H3), E=16 dev 1000 episodes, code 7d53d5d (RV-0054), D5 recipe 6000 steps, single run per arm; C1 (descriptive, not in the replication verdict): R1 seed 0 (ATT-0122-1) -> continuation seed 1 [code review: ATT-0170-1 covered by RV-0054 pass]

- EV-0105 [screening, valid] C2 (descriptive) passes the H3 thresholds under the isolated write: EM normal 46.5% vs zero 1.1%, shuffled 2.3% (margin 221/500 = 44.2 pp); NLL 2.394 < 9.248, 8.245; target weight all 0.157, last 0.598. Strata: t0 EM 44.2, margin 38.5 pp, weight 0.152; t>=1 EM 46.6, margin 44.5 pp, weight 0.157 - both pass. Start adapter = trusted R1 digest; replay 0/1000 mismatches; reload identical. (supports H-0012@1); scope: E-0017@1, isolated-encoding write protocol (reported separately from E-0010 H3), E=16 dev 1000 episodes, code 7d53d5d (RV-0054), D5 recipe 6000 steps, single run per arm; C2 (descriptive, not in the replication verdict): R1 seed 0 (ATT-0122-1) -> continuation seed 2 [code review: ATT-0171-1 covered by RV-0054 pass]

- EV-0106 [diagnostic, valid] Final seed1 fixed256-dev latency complete on allocation-verified mg1098 with existing2g timing guard; all5 models have768timings. Independent PBS artifact tabulation verifies all3840 raw timings positive/finite and summary statistics match. Nine-checkpoint provenance and measured costs packaged.; scope: Descriptive cost and engineering readiness only;single fixed GPU/seed1 input workload;merged LoRA timing only. No official validation,no H0008 outcome claim,no slice comparison;original LR lock final. [code review: ATT-0174-1 covered by RV-0033 pass, RV-0034 issues, RV-0035 pass, RV-0037 issues, RV-0038 pass, RV-0039 pass, RV-0047 pass; ATT-0175-1 not needed: Bounded metadata/timing-file validation and descriptive table generation only;no model execution,no new training/eval/loading path,no scientific conclusion;source latency reviewed RV0035 and complete RES0172]

- EV-0107 [diagnostic, valid] D5 seed 0 on T2: S=1 implementation check exact vs reviewed evaluator (4 controls). Hop1 H3 fails: EM normal/zero/shuffled 9/0/6 of 334 (margin 0.9 pp), target weight all 0.036 (<0.125, below 1/16), last 0.054; NLL 7.74<8.81<9.58. oracle_value hop1 EM 75.7% (decoder transfers, address does not). S_eval 2/4/8: hops2-3 EM 3-4.5% unchanged, NLL rises, step-2 weight does not move to hop-2 fact (descriptive).; scope: E-0018@1 E1, isolated-write D5 adapter ATT-0159-1 (seed 0) on T2 dev (1000; hops 1-3), S_eval 1/2/4/8, no training; reviewed code 7f3b5a0 (RV-0057) [code review: ATT-0182-1 covered by RV-0057 pass]

- EV-0108 [diagnostic, valid] D5 seed 1 (P1) on T2: S=1 exact vs reviewed evaluator on T2 and T1 E=16 dev; T1 S=1 vs P1 recorded predictions 0/1000 mismatches, identical NLL (4 controls). Hop1 H3 fails: EM 10/0/4 of 334 (margin 1.8 pp), target weight all 0.037, last 0.056; oracle_value hop1 EM 80.2%. S_eval>1 no gain on hops 2-3; NLL rises with S. Ran on 1g slice (metadata only, D-0018).; scope: E-0018@1 E1, isolated-write D5 adapter ATT-0172-1 (seed 1, P1) on T2 dev (1000; hops 1-3), S_eval 1/2/4/8, no training; reviewed code 7f3b5a0 (RV-0057) [code review: ATT-0183-1 covered by RV-0057 pass]

- EV-0109 [diagnostic, valid] D5 seed 2 on T2: S=1 exact vs reviewed evaluator. Hop1 H3 fails: EM 15/0/5 of 334 (margin 3.0 pp), target weight all 0.038, last 0.069; oracle_value hop1 EM 76.3%. S_eval>1 no gain on hops 2-3 (2.7-3.9%), NLL rises with S, no step-2 shift toward the hop-2 fact (descriptive).; scope: E-0018@1 E1, isolated-write D5 adapter ATT-0173-1 (seed 2) on T2 dev (1000; hops 1-3), S_eval 1/2/4/8, no training; reviewed code 7f3b5a0 (RV-0057) [code review: ATT-0184-1 covered by RV-0057 pass]

- EV-0110 [confirmatory, valid] E0013@3 single authorized official-validation opening: C_up r32 vs all28/all7 rank1 LoRA seed-mean macro difference -0.417652pp,paired stratified10000-bootstrap95CI[-1.020109,+0.197062]pp. Upper bound<+1pp triggers only the sealed challenged edge; interval includes0,so this does not establish equivalence or LoRA superiority. Seed differences[-0.275412,-0.401297,-0.576248]pp;task means PIQA-0.743562pp,BoolQ-0.091743pp. Macro means C77.484174%,F77.250252%,L77.901827%. S1 C-F+0.233922pp,rawCI[-0.239300,+0.708736],HolmP0.3356;S2 F-L-0.651575pp,rawCI[-1.252136,-0.037860],HolmP0.0692;neither rejects afterHolm. WikiText deltaNLL C+0.200122,F+0.238017,L+0.336505 vsBase2.647376. All10 bundles authenticated,single complete receipt,PIQA1838/BoolQ3270,zero exclusions/deviations;exact full locked analysis reproduced from saved predictions. RV0039/RV0056 passed; no methods/lock/source/data/checkpoint changes and no inference rerun. Hypothesis status decision remains coordinator. (challenges H-0008@2); scope: H0008@2,E0013@3;Qwen3-0.6B-Base,F-line attention retained,3 fixed training seeds1/2/3,final three-epoch checkpoints,allLR0.001 selected by sealed short calibration protocol;C/F524288 parameters,L630784. Intervals represent data uncertainty conditional on these trained seeds;no seed resampling. +1pp/per-task-1pp are point gates;challenged is not equivalence. Secondary intervals raw,not Holm simultaneous;S1 budget comparison changes rank and interface together. LoRA conclusion limited to rank1 and this calibration/training recipe. Training/latency costs reused authenticatedT0013 records;LoRA mergeable and merged timing only,confirmation scoring unmerged. No zero-tuning-transfer or parameter-efficiency claim. Validation consumed once;cannot be reused to confirm modified methods. [code review: ATT-0179-1, ATT-0194-1 stale: research/artifacts/T-0020/confirmation-lock.json changed since RV-0056; research/artifacts/T-0020/preflight-allocation.json changed since RV-0056; research/artifacts/T-0020/preflight-result.json changed since RV-0056; 5 more]

- EV-0111 [diagnostic, valid] Start stage fails the hop1 H3 gate (E-0022 rule 1), so the ten arms were not trained. EM margin 85/334 = 25.4 pp passes. NLL 3.626 < min control 8.175 passes. All-question-position target weight 0.0655 < 0.125 fails; the last position is 0.384. Hop1 normal EM is 26.6% (zero 0%, shuffled 1.2%, permuted 2.7%), oracle_key 12.0% (target weight 0.175), oracle_value 66.8%. Hop2/hop3 normal EM 4.2%/0.9%. Against the E-0018 D5 seed-0 T2 baseline: EM 2.7% -> 26.6%; target weight all 0.036 -> 0.066, last 0.054 -> 0.384; oracle_value 75.8% -> 66.8%. The all-position mean dilutes the last-position read on T2's 23-25 token questions, versus 7 tokens on T1 (T1 D5 all 0.162 / last 0.571); non-last positions average 0.052. Curves at 25/50/75/100% give EM 3.0/9.6/22.5/26.6% and all-

position weight 0.050/0.058/0.064/0.066, still rising. Reload byte-identical; gate recomputed from records matches. 0.090 node-h.; scope: E-0022@2 V3-S0 common start stage: D5 seed-0 continued 6000 steps on T2 train hop1, isolated write, S=1, T2 dev hops1-3 (reviewed E-0016 evaluator); single seed [code review: ATT-0196-1 covered by RV-0059 pass]

- EV-0112 [diagnostic, valid] RB0 implementation diagnostics pass:408 PBS regressions and three actual trainer CLI smokes with exact reload/inventory,causal prefix/T0/fixed-query/history/counts/top compatibility and A2 split checks. RV0060 plus RV0062 passed;all4 low findings fixed,0open. Twenty-one100stable-step timing cases and seven512/128latency cases verified;max prefix side-layout0.243899s,RB1core2.443961node_h,RBc12-16candidates0.509314-0.679085node_h. Actual1918MIGs=0.1331944444node_h. Implementation/compute evidence only. (supports H-0017@1); scope: E-0019@1 and H-0017@1 implementation invariants. FP32 per-tensor1e-5+1e-4*maxref gate fixed before runs;D0026/D0027 exact topology and decisive FP32 gates pass while unchanged0.50002 BF16 cross-shape exceedances0.8203125/0.857421875 remain explicit reference-matched diagnostics. CPUFP32 gradient equivalence plus GPU model gates,not GPU gradient-equality proof. Swap/permutation require valid prefixes from0. Only engineering tests/smokes/timing,no formal training or task-performance claim. Forecasts exclude frozen interventions/analysis/planning/cold-cache overhead and conditional RB5 gaps. Earlierfailed ATT0186/0187 are preserved in the sealed note as engineering history. Coordinator owns scientific release/hypothesis status. [code review: ATT-0180-1 not needed: Low-cost RB0 synthetic regression and IDs-only split generation before required code review;no formal training,calibration or task-performance evaluation; ATT-0188-1 not needed: Required low-cost RB0 validation/startup before timing and code review;coordinator D0026/27 comparison convention,thresholds and fixtures unchanged;no formal training; ATT-0189-1 not needed: Required low-cost RB0 implementation/cost benchmark before the task-mandated code review;397checks and all10startup cases passed RES0183 at identical model/training code;no formal calibration or task-performance experiment; ATT-0191-1 not needed: RB0 required cost coverage for RB5 layouts missing from RB1 matrix;unchanged tested operators/trainer,397checks passed;cheap timing before required code review,no formal RB5 experiment; ATT-0193-1 not needed: Cheap artifact-integrity and descriptive cost tabulation before required RB0 code review;no model imports/execution,new scientific analysis or heldout data; ATT-0197-1 not needed: Low-cost targeted fixes/regressions and CLI smoke requested by RV0060 and coordinator MSG0599 before its one focused recheck;no formal RBc/RB1 training or performance evidence]

- EV-0113 [diagnostic, valid] Readiness rule R holds on T2 calibration (all four criteria). (1) hop1 EM margin $193/683 - \max(0,12)/683 = 181/683 = 26.5$ pp ≥ 10 pp; (2) hop1 NLL $3.466 < \min(9.541, 7.848)$; (3) answer-position weight on the first path fact 0.411 / 0.394 / 0.408 for hops 1/2/3, each ≥ 0.125; (4) hop1 most common answer-position argmax slot share $53/683 = 7.8\% \leq 25\%$. Descriptive: all-position target weight 0.057/0.054/0.055 (not part of R); answer-position argmax = first fact 52.7/52.3/52.9%; normal EM hops2/3 2.0%/4.0% (shuffled 1.6/1.9%); first-edge oracle_value hop1 67.8%. Origin: the readiness rule was fixed after the start-stage dev results were seen and checked once on the previously unused T2 calibration split. Stage A (V3-01/02/03) is released.; scope: E-0023 stage 0; common start ATT-0196-1 (adapter f70ea08e…), T2 calibration 2048 rows (683/683/682), reviewed E-0016 evaluator, isolated write, S=1, six controls, single seed; M line, layer 14 direct_hidden SoftmaxSlot F_out r128 [code review: ATT-0227-1 not needed: stage 0 per T-0026 brief: thin wrapper around the reviewed E-0016 evaluator (RV-0059 path); rule R computed deterministically from records]

- EV-0114 [diagnostic, valid] E-0020@1 RBc LR calibration: all16 candidates complete/finite; reviewed one-time upper extensions and 1% rule lock L=3e-4,T=3e-3,R=3e-3,C=1e-3. T minimum is the new endpoint (grid boundary; no further expansion). Lock SHA256 38b8ee24af3ded8aee398a4cc3d Exact full task usage 9677 MIG seconds=0.6720138888888889 node-h. Diagnostic preparation for H-0013, no efficacy support/challenge.; scope: E-0020@1 / H-0013@1 calibration preparation only: seed0,V0,paired200k-complete-step budget,full2048calibration rows/task,A2 exclusion,preregistered grids/one extension/1%choice. No dev/confirmation/RB1, slice analysis or hypothesis-status change. [code review: ATT-0210-1, ATT-0211-1, ATT-0212-1, ATT-0213-1, ATT-0214-1, ATT-0215-1, ATT-0216-1, ATT-0217-1, ATT-0218-1, ATT-0219-1, ATT-0220-1, ATT-0221-1, ATT-0223-1, ATT-0224-1, ATT-0225-1, ATT-0226-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass; ATT-0222-1 not needed: Low-cost deterministic verification of existing calibration artifacts and invocation of unchanged RV-0062-reviewed extension_lr; no core/training/scoring/data/tolerance changes or novel LR rule; ATT-0236-1 not needed: Coordinator-authorized artifact-only final verification using rbc_report already runtime-validated in ATT-0222-1; invokes unchanged RV-0062-reviewed rb_train lock CLI with no new LR rule, training/scoring/data/core/dependency/tolerance change]

- EV-0115 [screening, valid] Rule 3 case A3 (descriptive only; stage B not released). Primary (hop2+hop3)/2 EM: V3-01 1100/333 = 3.30 pp, V3-02 1300/333 = 3.90 pp, V3-03 1100/333 = 3.30 pp; S_M* = V3-02 (V3-03 not >= V3-02 + 0.5). S_M* - V3-01 = 200/333 = +0.60 pp (0 < gain < 3); hop1 S_M* - V3-01 = -450/167 = -2.69 pp (14.37 -> 11.68%). Paired hop-stratified bootstrap 95% (descriptive): V3-02-V3-01 primary [-0.60, +1.80] pp, hop1 [-5.09, -0.60]; V3-03-V3-01 primary [-1.20, +1.20]. Shuffled-memory hops2-3 EM 0.3-1.2%. Diagnostics (descriptive): end-edge value oracle decodes the chain end (hops 2/3 EM 44.7/46.5% V3-01, 46.2/45.6% V3-02, 45.3/46.5% V3-03) while the first-edge oracle is ~0-1.5%; answer-position weight of step 2 on path fact 2 at hop 2 is 0.069 (V3-02) / 0.066 (V3-03), about 1/16 and below 1/8 (rule 5); step-1 weight on the first fact fell from 0.38-0.42 at the start to 0.19-0.23 after hops 1-3 training, and hop1 EM fell from 26.6% (start) to 10.5-14.4%. EM concentrates on answers with above-median train frequency (V3-02: 51/500 high vs 14/500 low). Readiness rule origin: fixed after the start-stage dev results were seen; checked once on the previously unused T2 calibration split (EV-0113). Next per rule 4: frozen-transfer diagnostic on V3-02 and at most one repair arm.; scope: E-0023 stage A, H-0005 main question (does a looped latent read S2/S4 beat S1 on T2 hops 2-3?). Common start ATT-0196-1 released by readiness R (ATT-0227-1); 6000 steps T2 train hops 1-3, same order; T2 dev 334/333/333; M line isolated write, layer 14 direct_hidden SoftmaxSlot F_out r128; single seed. Not tested: stage B controls (V3-04..V3-10), seeds, hops 4/6/8. [code review: ATT-0233-1, ATT-0234-1, ATT-0235-1 stale: src/test_v3_train.py changed since RV-0059; src/v3_train.py changed since RV-0059; ATT-0251-1 covered by RV-0059 pass, RV-0067 pass]

- EV-0116 [screening, valid] D-0034 mapping: (a) holds, end-edge value oracle EM 581/1365 = 42.56% minus max(zero 0/1365, shuffled 22/1365 = 1.61%) = 860/21 = 40.95 pp >= 10 pp; (b) holds, gold-bridge-as-subject mean step-1 weight on path fact 2 = 0.2025 >= 1/8, wrong-bridge (same relation) 0.0724 < 1/8 and donor-bridge 0.0846 < 1/8 (wrong-bridge rows 1365, 0 excluded); (c) holds, native mean step-2 weight on path fact 2 = 0.0761 < 1/8. Mapping (a)(b)(c) -> successor-slot CE S4 pilot with the permuted-successor-label control. Descriptive: native EM 55/1365 = 4.03% (step 1 on fact 1 0.2085, step 2 stays on fact 1 0.1908); bridge-subject EM 104/1365 (hop2 81/683 = 11.86%, hop3 23/682), step-1 argmax on fact 2 in 35.4% of rows vs 6.1% native, 8.4% donor, 6.4% wrong; the wrong bridge's own off-path fact gets 0.2079 at step 1. forced_first (step-2 onward native after $z^{(1)}$ set to the

correct first-edge read) EM 22/1365 = 1.61%, step-2 weight on fact 2 0.0991 (< 1/8); its step-1 entries are the native step-1 weights replaced by the forced state, not a forced read (RV-0070). First-edge oracle 8/1365. So the frozen reader addresses the next edge when given the bridge as the subject, and the end value decodes, but its own step-2 transition does not move to path fact 2. Readiness rule origin: fixed after the start-stage dev results were seen; checked once on the previously unused T2 calibration split (EV-0113). Cost 0.04 MIG-h = 0.01 node.h.; scope: E-0023 rule 4 (case A3): frozen-transfer diagnostic of S_M* = V3-02 (ATT-0234-1, adapter af22f59e...) from the readiness-checked common start ATT-0196-1/ATT-0227-1; T2 calibration hops 2-3 pooled (683+682 = 1365 rows), answer position, scored at S_train = 2 with the chain end as label; D-0034 criteria; code reviewed RV-0070 (1 low finding, reporting only). No training. Not tested: hop 1, dev, hops 4/6/8, other arms, seeds. [code review: ATT-0253-1 stale: src/test_v3_train.py changed since RV-0059; src/v3_train.py changed since RV-0059]

- EV-0117 [screening, valid] D-0035: correct labels do not beat permuted; the repair route stops (AD-0003 drop condition). (i) fails: primary EM correct (16+14)/666 = 1500/333 = 4.50 pp vs permuted (11+8)/666 = 950/333 = 2.85 pp, difference 550/333 = +1.65 pp < +3. (ii) fails: hop-2 mean answer-position step-2 weight on path fact 2 = 0.0834 (correct) and 0.0624 (permuted), the correct arm below 1/8. Descriptive: hop1 EM 11/334 (correct) and 10/334 (permuted), difference 50/167 pp, both far below V3-01 48/334 and the start; answer-position read weights became nearly flat in both arms (step-1 weight on fact 1 0.086 / 0.067 vs about 0.40 at the start; every step about 0.082-0.087 on every path fact in the correct arm, 0.062-0.068 in the permuted arm; uniform over 16 slots is 0.0625); last-100-step successor CE 2.51 (correct) and 2.77 (permuted) vs ln 16 = 2.77. V3-03 (6,000 steps, no successor CE) for reference: primary 1100/333 = 3.30 pp, hop2 step 2 on fact 2 0.066. Both runs: reload records identical, replay error <= 3e-5 relative, MIG 2g. Readiness rule origin: fixed after the start-stage dev results were seen; checked once on the previously unused T2 calibration split (EV-0113). Cost 0.23 MIG-h = 0.058 node.h for the pilots and comparison.; scope: E-0023 rule 4 repair under D-0035 (extra supervision, not unsupervised H-0005 evidence): successor-slot CE S4 pilot vs permuted-successor-label control, each 2,000 steps (first 16,000 stage-A episodes, 100 warmup, LR 3e-3) from the readiness-checked common start ATT-0196-1/ATT-0227-1 in the V3-03 configuration, coefficient 1, 16,013 labels each (hop2 5,329, hop3 10,684); T2 dev 334/333/333 at S=4; single seed; code RV-0071 -> RV-0072 pass. Not tested: other coefficients, longer training, seeds, hops 4/6/8. [code review: ATT-0256-1, ATT-0257-1, ATT-0259-1 stale: src/test_v3_train.py changed since RV-0059; src/v3_train.py changed since RV-0059]

- EV-0118 [screening, valid] E-0021 rule11 main-utility screening (H-0013@1): RB1-02 macro77.10% versus LoRA4r7 RB1-07 78.95%, difference -1.85pp [95% descriptive paired interval -3.00,-0.70]; task differences PIQA-2.00pp and BoolQ-1.70pp. RB1-02 exceeds Base by6.95pp [5.25,8.70], but fails GR (LoRA minus1pp allowance) and the stronger H13 +1pp advantage/task point gates. Rule11 therefore records challenges; this is single-seed dev evidence, not a hypothesis-status decision or equivalence claim. (challenges H-0013@1); scope: H-0013@1,E-0021@1,D-0032; four-layer r32 F-line,Qwen3-0.6B-Base,2M paired training tokens,seed0,1000dev/task. Paired task-stratified bootstrap10000,default_rng20261101,shared draws; point gates use exact counts. Intervals conditional on these trained models; exclude training-seed and same-dev selection uncertainty, no simultaneous guarantee. LoRA630784 vs R663552 parameters; no parameter-efficiency claim, no RB5/confirmation/generalization conclusion. [code review: ATT-0240-1, ATT-0245-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062

pass, RV-0064 pass; ATT-0267-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass, RV-0064 pass, RV-0069 pass]

- EV-0119 [screening, valid] E-0021 rule11 history screening (H-0014@1): RB1-02 minus equal-parameter S1 T0 RB1-01 is -0.20pp [95% descriptive paired interval -1.30,+0.90]. Relative to the same-checkpoint normal condition, swap drops1.85pp [0.75,3.00] and key/value permutation drops17.15pp [14.70,19.60]. GH is false because the trained memory arm does not exceed T0 by1pp; rule11 records challenges from the nonpositive primary contrast. Frozen off/Base and T0 swap identities pass; sensitivity to a shifted side-history distribution does not establish beneficial memory or equivalence. (challenges H-0014@1); scope: H-0014@1,E-0021@1,D-0032; seed0,1000dev/task,four target layers simultaneously; original attention/KV retained,normal same-checkpoint donors,causal within-task derangement. T0 onlyS1; Q/K/V already contextual. Paired task-stratified10000 bootstrap seed20261101 uses shared draws. Descriptive row uncertainty conditional on trained models, excludes seed/selection uncertainty; no hypothesis-status decision. [code review: ATT-0239-1, ATT-0240-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass, RV-0064 pass; ATT-0262-1, ATT-0266-1, ATT-0267-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass, RV-0064 pass, RV-0069 pass]

- EV-0120 [screening, valid] E-0021 rule11 loop screening (H-0015@1): locked S_F*=S2/RB1-03, because S2 exceeds S4 by0.55pp. Selected S2 minus S1 RB1-02 is +0.35pp [95% descriptive paired interval -0.55,+1.30], positive but below the1pp GL point gate, so descriptive only with no supports/challenges edge. S4 minus fixed-query S4 is -0.20pp [-1.10,+0.70]; eta/4 minus S1 is -0.60pp and S4 minus eta/4 is +0.40pp. RB1 has no same-depth T0 and cannot establish the full mechanistic claim.; scope: H-0015@1,E-0021@1,D-0032; identical R1 seed0/order/2M tokens,r32 four-layer residual prefix KernelMatrix,native shared LatentReader. S_F* is selected on these same1000dev/task outcomes. Shared paired task-stratified10000 bootstrap seed20261101; intervals conditional on trained models, exclude selection and seed uncertainty. No confirmation, same-depth tokenwise control, causal-hop or hypothesis-status claim. [code review: ATT-0240-1, ATT-0241-1, ATT-0242-1, ATT-0243-1, ATT-0244-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass, RV-0064 pass; ATT-0267-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass, RV-0064 pass, RV-0069 pass]

- EV-0121 [screening, valid] E-0021 rule11 concat screening (H-0016@1): C_up/RB1-09 macro77.50% and C_dual/RB1-08 77.45% versus residual S1 RB1-02 77.10%. Best concat minus residual is +0.40pp [95% descriptive paired interval -0.70,+1.50], positive but below1pp, so rawGC=false,resolvedGC=fa and descriptive only with no supports/challenges edge. Both concat arms are effective versus Base and strictly within1pp of the best; fewer parameters locks C*_RB=C_up. No GC-dependent RB5 release or C-S1/S4 pilot; no parameter-matched LoRA,wider residual or concat-T0 confirmation was tested.; scope: H-0016@1,E-0021@1,D-0032; single-seed four-layer r32 S1 KernelMatrix on1000dev/task. C_up925696,C_dual1318912,residual663552 trainable parameters; no parameter-efficiency claim. Paired task-stratified10000 bootstrap seed20261101 with shared draws; conditional row uncertainty only, excludes trained-seed and same-dev selection uncertainty. Positive subthreshold estimate is neither support nor equivalence/challenge under rule11. H0002/EV0048/D0004 unchanged. [code review: ATT-0240-1, ATT-0246-1, ATT-0247-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass, RV-0064 pass; ATT-0267-1 covered by RV-0002 pass, RV-0009 pass, RV-0060 pass, RV-0062 pass, RV-0064 pass, RV-0069 pass]

- EV-0122 [diagnostic, valid] E-0024 zero-training read diagnostic: preregistered reading is

MIXED (per-layer description, no unified conclusion). In every residual concentrated cell (DOC-0263 normal answer-position n_eff<2; RB1-02 BoolQ L27, PIQA L6/13/20/27; RB1-03 BoolQ L27, PIQA L6/20/27), position 0 dominates the read: question-level share0 is 0.81-0.98 vs uniform 1/n 0.057 (PIQA) / 0.0087 (BoolQ), and argmax0 is >=0.996. Position 0 is the same token in all rows of a task ('Goal' / 'Pass'). Cross-episode constant-read index C>0.9 holds only at PIQA L27 (RB1-02 0.987, RB1-03 0.995); the other concentrated cells have C 0.50-0.68. So the sink criterion (share0>0.5 and C>0.9 in all concentrated layers) fails on C, and the content criterion (share0<0.2) fails everywhere. Concat RB1-08/09: near uniform 1/n at BoolQ L6-20 and PIQA L6-13, and 0.37-0.75 on position 0 at L27 (descriptive). Implementation checks: every condition matches E-0021 with 0 difference in gold NLL and every read summary (RB1-02 against a same-allocation evaluate_history, D-0050); iv_window8 late share0 = 0; iv_strict checked by the layer-6 identity, max error 1.8e-7 over 9,330 positions. The original strict bound was replaced after it failed, by D-0051.; scope: E-0024@1; diagnostic only, no supports/challenges and no H-0014 status change. RB1-02/03/08/09, seed 0, 1000 dev rows per task, gold candidates, batch-one forwards, conditions normal/iv_strict/iv_window8, C from 200 seeded questions per task at the first answer position. Arms come from attempts ATT-0275-1 (ee5d8f6: RB1-03/08/09), ATT-0283-1 (ec88f08: RB1-02) and ATT-0285-1 (582b444: identity and summary). Amendment D-0051 replaced the iv_strict <0.01 bound after seeing it fail at 4 cells (max 0.0152). RB1-02 differs from its 1g E-0021 record by slice rounding (gold NLL max 1.86), descriptive only per D-0018/D-0019. Budget 0.234 of 0.25 node-h (D-0047/D-0048). Code review RV-0076/RV-0077; ee5d8f6/ec88f08/582b444 accepted without a new round under D-0048/D-0050/D-0051. The rl stale flag on src/test_rb1_artifacts.py comes from the test-only commit 8bf0146, which no run executes (MSG-0739). The value-norm explanation for moderate C is untested. [code review: ATT-0275-1, ATT-0283-1, ATT-0285-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0123 [screening, valid] E-0026 rule 3 (H-0018, r128 width probe, ordinary full-context RB1 setting): W-02 R_res+KernelMatrix S1 r128 macro 76.95% (PIQA 72.70, BoolQ 81.20) vs parameter-matched four-layer all-7 LoRA r31 W-03 78.75% (74.50/83.00). d_L = W-02 - W-03 = -1.80 pp exactly (-9/500) [95% descriptive paired interval -3.10,-0.50]; both task differences -1.80 pp. W-02 exceeds Base 70.15% by +6.80 pp [5.00,8.55], so the Base+1 condition holds but d_L < -1 pp fails. Rule 3 outcome: challenges (screening, r128 only). LoRA control learned (W-03 - Base +8.60 pp), so the level stays screening per rule 2. Per rule 8, no further widening or tap change in the ordinary setting under this contract. Single-seed dev screening; not a hypothesis-status decision or an equivalence claim. (challenges H-0018@1); scope: H-0018@1,E-0026@1,D-0052; four-layer [6,13,20,27] F-line (full context), qknorm_pre_rope, KernelMatrix prefix inclusive S1, r128 only; Qwen3-0.6B-Base frozen; seed0; RB1 init/order (order SHA 33759bc2...), 13,115 steps/2,000,069 tokens; r32 LR lock reused (RBc-R 3e-3, RBc-L 3e-4); 1000 dev/task used for the decision. Paired task-stratified bootstrap 10000, default_rng 20261101, shared draws across all labels; intervals descriptive, conditional on the trained models, exclude seed and same-dev selection uncertainty. W-02 2,752,512 vs W-03 LoRA r31 2,793,472 parameters (nearest by implementation count). Training source c9f78b9 (RV-0080/RV-0081, D-0053), intervention/analysis 81ad3de/3678f60 (RV-0082, D-0054). No A2 confirmation or official validation opened. [code review: ATT-0296-1, ATT-0297-1 stale: src/rb_history.py changed since RV-0060, RV-0062, RV-0064; src/rb_read_diagnostics.py changed since RV-0064, RV-0069; src/test_rb1_artifacts.py changed since RV-0064, RV-

0069; 2 more; ATT-0300-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_read_diagnostics.py changed since RV-0064, RV-0069]

- EV-0124 [diagnostic, valid] E-0026 rule 1 implementation checks: all four pass. (a) W-02 iv_off predictions equal both the same-allocation Base (rows identical) and the pinned ATT-0024-1 Base; (b) step-0 dev predictions of W-01/W-02/W-03 equal Base for all 2000 rows; (c) all three formal runs reload identically; (d) stored/trainable/with-grad counts equal the registration ATT-0294-1 at c9f78b9 (W-01=W-02=2,752,512; W-03 LoRA r31=2,793,472, nearest of r28..34 to W-02), and W-01/W-02 start from elementwise-identical parameters (24 tensors). Rule outcomes 2-8 are therefore admissible.; scope: H-0018@1,E-0026@1,D-0052; four-layer [6,13,20,27] F-line (full context), qknorm_pre_rope, KernelMatrix prefix inclusive S1, r128 only; Qwen3-0.6B-Base frozen; seed0; RB1 init/order (order SHA 33759bc2...), 13,115 steps/2,000,069 tokens; r32 LR lock reused (RBc-R 3e-3, RBc-L 3e-4); 1000 dev/task used for the decision. Paired task-stratified bootstrap 10000, default_rng 20261101, shared draws across all labels; intervals descriptive, conditional on the trained models, exclude seed and same-dev selection uncertainty. W-02 2,752,512 vs W-03 LoRA r31 2,793,472 parameters (nearest by implementation count). Training source c9f78b9 (RV-0080/RV-0081, D-0053), intervention/analysis 81ad3de/3678f60 (RV-0082, D-0054). No A2 confirmation or official validation opened. [code review: ATT-0294-1 not needed: pre-training regression and parameter registration at the training source; RV-0081 covers production code; ATT-0295-1, ATT-0296-1, ATT-0297-1 stale: src/rb_history.py changed since RV-0060, RV-0062, RV-0064; src/rb_read_diagnostics.py changed since RV-0064, RV-0069; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 2 more; ATT-0299-1, ATT-0300-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_read_diagnostics.py changed since RV-0064, RV-0069]

- EV-0125 [screening, valid] E-0026 rule 2 learnability (descriptive): all arms reach Base+1 pp. W-01 r128 T0 76.80% (+6.65 pp [4.85,8.45]), W-02 r128 R_res 76.95% (+6.80 [5.00,8.55]), W-03 LoRA r31 78.75% (+8.60 [6.85,10.35]) vs Base 70.15%. The LoRA control learned, so rules 3-5 carry screening level (not diagnostic).; scope: H-0018@1,E-0026@1,D-0052; four-layer [6,13,20,27] F-line (full context), qknorm_pre_rope, KernelMatrix prefix inclusive S1, r128 only; Qwen3-0.6B-Base frozen; seed0; RB1 init/order (order SHA 33759bc2...), 13,115 steps/2,000,069 tokens; r32 LR lock reused (RBc-R 3e-3, RBc-L 3e-4); 1000 dev/task used for the decision. Paired task-stratified bootstrap 10000, default_rng 20261101, shared draws across all labels; intervals descriptive, conditional on the trained models, exclude seed and same-dev selection uncertainty. W-02 2,752,512 vs W-03 LoRA r31 2,793,472 parameters (nearest by implementation count). Training source c9f78b9 (RV-0080/RV-0081, D-0053), intervention/analysis 81ad3de/3678f60 (RV-0082, D-0054). No A2 confirmation or official validation opened. [code review: ATT-0295-1, ATT-0296-1, ATT-0297-1 stale: src/rb_history.py changed since RV-0060, RV-0062, RV-0064; src/rb_read_diagnostics.py changed since RV-0064, RV-0069; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 2 more; ATT-0300-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_read_diagnostics.py changed since RV-0064, RV-0069]

- EV-0126 [screening, valid] E-0026 rule 4 practical advantage: not recorded. d_L = W-02 - W-03 = -1.80 pp [-3.10,-0.50] (PIQA -1.80, BoolQ -1.80), below the +1 pp threshold; the r128 side branch is not above the parameter-matched LoRA on dev. No W-02/W-03 new-seed replication or A2 confirmation is triggered.; scope: H-0018@1,E-0026@1,D-0052; four-layer [6,13,20,27] F-line (full context), qknorm_pre_rope, KernelMatrix prefix inclusive S1,

r128 only; Qwen3-0.6B-Base frozen; seed0; RB1 init/order (order SHA 33759bc2...), 13,115 steps/2,000,069 tokens; r32 LR lock reused (RBc-R 3e-3, RBc-L 3e-4); 1000 dev/task used for the decision. Paired task-stratified bootstrap 10000, default_rng 20261101, shared draws across all labels; intervals descriptive, conditional on the trained models, exclude seed and same-dev selection uncertainty. W-02 2,752,512 vs W-03 LoRA r31 2,793,472 parameters (nearest by implementation count). Training source c9f78b9 (RV-0080/RV-0081, D-0053), intervention/analysis 81ad3de/3678f60 (RV-0082, D-0054). No A2 confirmation or official validation opened. [code review: ATT-0296-1, ATT-0297-1 stale: src/rb_history.py changed since RV-0060, RV-0062, RV-0064; src/rb_read_diagnostics.py changed since RV-0064, RV-0069; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 2 more; ATT-0300-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_read_diagnostics.py changed since RV-0064, RV-0069]

- EV-0127 [screening, valid] E-0026 rule 5 side-history dependence: descriptive only; the D-0042 reopen condition for H-0014 is not met. d_T = W-02 - W-01 (same-parameter, same-init r128 T0) = +0.15 pp [-1.00,1.35] (0 < d_T < +1). W-02 iv_swap (within-task derangement donor history) lowers macro by 2.25 pp [1.15,3.40] (PIQA -1.50, BoolQ -3.00), meeting the >=1 pp drop, but d_T fails the >=+1 pp condition. iv_permute drop 32.30 pp [29.40,35.20] is descriptive and may mainly reflect distribution shift. Not recorded as 'no measurable contribution' because d_T > 0. T0 is a current-token nonlinear gate, not history-free attention.; scope: H-0018@1,E-0026@1,D-0052; four-layer [6,13,20,27] F-line (full context), qknorm_pre_rope, KernelMatrix prefix inclusive S1, r128 only; Qwen3-0.6B-Base frozen; seed0; RB1 init/order (order SHA 33759bc2...), 13,115 steps/2,000,069 tokens; r32 LR lock reused (RBc-R 3e-3, RBc-L 3e-4); 1000 dev/task used for the decision. Paired task-stratified bootstrap 10000, default_rng 20261101, shared draws across all labels; intervals descriptive, conditional on the trained models, exclude seed and same-dev selection uncertainty. W-02 2,752,512 vs W-03 LoRA r31 2,793,472 parameters (nearest by implementation count). Training source c9f78b9 (RV-0080/RV-0081, D-0053), intervention/analysis 81ad3de/3678f60 (RV-0082, D-0054). No A2 confirmation or official validation opened. [code review: ATT-0295-1, ATT-0296-1 stale: src/rb_history.py changed since RV-0060, RV-0062, RV-0064; src/rb_read_diagnostics.py changed since RV-0064, RV-0069; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 2 more; ATT-0299-1, ATT-0300-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_read_diagnostics.py changed since RV-0064, RV-0069]
- EV-0128 [screening, valid] E-0026 rule 6 width effects (descriptive, r128 minus the matching E-0021 r32 arm, same init rule/order/LR): W-02 - RB1-02 = -0.15 pp [-1.15,0.85]; W-01 - RB1-01 = -0.50 [-1.50,0.50]; W-03 (LoRA r31) - RB1-07 (LoRA r7) = -0.20 [-1.20,0.80]. Widening from r32 to r128 (and LoRA r7 to r31) shows no measurable dev change at this budget; r128 reuses the r32 LR lock, so a width-specific optimum LR is not excluded.; scope: H-0018@1,E-0026@1,D-0052; four-layer [6,13,20,27] F-line (full context), qknorm_pre_rope, KernelMatrix prefix inclusive S1, r128 only; Qwen3-0.6B-Base frozen; seed0; RB1 init/order (order SHA 33759bc2...), 13,115 steps/2,000,069 tokens; r32 LR lock reused (RBc-R 3e-3, RBc-L 3e-4); 1000 dev/task used for the decision. Paired task-stratified bootstrap 10000, default_rng 20261101, shared draws across all labels; intervals descriptive, conditional on the trained models, exclude seed and same-dev selection uncertainty. W-02 2,752,512 vs W-03 LoRA r31 2,793,472 parameters (nearest by implementation count). Training source c9f78b9 (RV-0080/RV-0081, D-0053), intervention/analysis 81ad3de/3678f60 (RV-0082, D-0054). No A2 confirmation or official validation opened. [code review: ATT-0295-1, ATT-0296-1, ATT-0297-1 stale: src/rb_history.py changed since RV-0060, RV-0062, RV-0064;

src/rb_read_diagnostics.py changed since RV-0064, RV-0069; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 2 more; ATT-0300-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_read_diagnostics.py changed since RV-0064, RV-0069]

- EV-0129 [screening, valid] E-0026 rule 7 per-task, NLL and curves (descriptive). PIQA/BoolQ accuracy: W-01 72.30/81.30, W-02 72.70/81.20, W-03 74.50/83.00, Base 72.30/68.00. Gold-answer NLL PIQA/BoolQ: W-01 2.565/0.433, W-02 2.575/0.478, W-03 2.519/0.615, Base 2.750/1.925. Macro dev curve at 0/25/50/75/100%: W-01 70.15/73.90/74.70/76.80/76.80; W-02 70.15/68.25/72.15/76.15/76.95; W-03 70.15/74.75/76.60/77.90/78.75 (W-02 dips below Base at 25%). Training: steady step 0.185/0.220/0.219 s, peak 3.13/3.26/3.22 GiB; W-02 persistent M+c 264,192 bytes (4 layers x 66,048).; scope: H-0018@1,E-0026@1,D-0052; four-layer [6,13,20,27] F-line (full context), qknorm_pre_rope, KernelMatrix prefix inclusive S1, r128 only; Qwen3-0.6B-Base frozen; seed0; RB1 init/order (order SHA 33759bc2...), 13,115 steps/2,000,069 tokens; r32 LR lock reused (RBc-R 3e-3, RBc-L 3e-4); 1000 dev/task used for the decision. Paired task-stratified bootstrap 10000, default_rng 20261101, shared draws across all labels; intervals descriptive, conditional on the trained models, exclude seed and same-dev selection uncertainty. W-02 2,752,512 vs W-03 LoRA r31 2,793,472 parameters (nearest by implementation count). Training source c9f78b9 (RV-0080/RV-0081, D-0053), intervention/analysis 81ad3de/3678f60 (RV-0082, D-0054). No A2 confirmation or official validation opened. [code review: ATT-0295-1, ATT-0296-1, ATT-0297-1 stale: src/rb_history.py changed since RV-0060, RV-0062, RV-0064; src/rb_read_diagnostics.py changed since RV-0064, RV-0069; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 2 more; ATT-0300-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_read_diagnostics.py changed since RV-0064, RV-0069]

- EV-0130 [diagnostic, valid] Rule1 passes all four implementation checks: both widths' same-allocation iv_off/Base identity and initial/Base identity; no-channel with/without discarded segment1 exact identity at reviewed source; all7trained arms' complete same-job reloads. Locked PBS final audit additionally binds all raw rows,checkpoint/source inventories and fixed R1 donors. Interpretation permitted.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc53b00/RV0079/D0049; D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Intervals descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0276-1 not needed: Targeted deterministic regression for the three low RV-0078 findings, before the one recheck; unchanged training/scoring cost smoke already passed; ATT-0287-1, ATT-0302-1, ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0131 [screening, valid] Rule2: both tasks informative. Full-context RB1-07 minus segmented LoRA SEG04 is exact+7.0pp PIQA(descriptive95%CI[4.8,9.2]) and+19.3pp BoolQ([16.1,22.5]),each> range gate only; protocols differ.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc53b00/RV0079/D0049; D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Intervals descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0281-1, ATT-0303-1 stale: src/test_rb1_artifacts.py

changed since RV-0064, RV-0069]

- EV-0132 [screening, valid] Rule3 selects PIQA as primary because PIQA is informative; BoolQ remains secondary. BoolQ success cannot replace the primary-task gate. No no-information stop condition fires.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc53b00/RV0079/D0049; D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Intervals descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0133 [screening, valid] Rule4 learnability is descriptive: primary Base_seg66.1%,inclusive Base+1 threshold67.1%.SEG01=66.9% andSEG06=66.9% fail;SEG02=69.4%,SEG03=67.8%,SEG04=67.4%, pass.SEG01 andSEG04 are not both unlearned,so no diagnostic downgrade of the main comparison.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d1 D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Interval descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0134 [screening, valid] Rule5 r32 primary PIQA gain SEG02-max(SEG01,SEG03)=exact2/125=+1.6pp,de 0.3,3.5].Own-IV-normal swap drop=4.2pp[1.7,6.6],but gain<3pp,so no r32 support;descriptive r32 outcome preserved from pre-width ATT0288/RES0266.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc53b00/RV0079/D0049; D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Interval descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0288-1, ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0135 [screening, valid] Rule6 released r128 once from0<primarygain32=1.6<3pp;all3width arms completed.Primary gain128=exact7/500=+1.4pp,descriptive95%CI[-0.4,3.2];swap drop=5.3pp[3.0,7.6].I descriptive/inconclusive,neither support(gain<3)nor challenge(both gains>=1).No further widening,tap or loop.D0052 exploratory fallbackunused.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc53b00/RV0079/D0049; D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Interval descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0288-1, ATT-0290-1, ATT-0291-1, ATT-0292-1, ATT-0302-1, ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0136 [screening, valid] Rule7 r32 challenge does not fire:primarygain32=exact2/125>0.The no-width branch does not apply;the sealed conditional triplet was already released and com-

pleted.No hypothesis challenge edge.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc53b00/RV0079/D0049; D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Intervals descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0288-1, ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0137 [screening, valid] Rule8 BoolQ secondary:gain32=+2.0pp[-0.8,4.9];gain128=exact11/250=+4.4pp[1.5 normal swap drop128=6.5pp[3.4,9.5025]>=gain128/2=2.2pp.With informative BoolQ,this meets the r128 task-level point gates only.Primary PIQA does not meet support,so overall reducer=inconclusive_secondary_only,eligible_edge=null.The locked rule calls for two new BoolQ-seed replications before a conclusion;none launched or authorized by this evidence.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc5 D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Interval descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0288-1, ATT-0290-1, ATT-0291-1, ATT-0292-1, ATT-0302-1, ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0138 [screening, valid] Rule9 macro accuracy and answer NLL are descriptive only.Keep r32/r128 both macro67.60%;macro gain over the better matched control=+2.25pp[0.5,3.95]/+3.05pp[1.35,4.55 analysis contains every task/condition NLL and shared paired interval.No hypothesis status change;no supports/challenges edge;all16compute attempts cost2.595972nodeh(native),2.595972222exact scheduler basis,under3.; scope: E-0025@1/H-0019@1 segmented F dev screening, seed0; scientific source7d8b3464b6145504d155268f4c667fa3ecc53b00/RV0079/D0049; D0044 fixed before outcomes.1000dev/task;10000shared task-stratified bootstrap draws seed20261101.Intervals descriptive conditional on trained seed0,exclude seed/task/width selection uncertainty,not simultaneous;thresholds exact point-estimate gates.Frozen r32 ATT0288/RES0266 preserved.D0052 fallbackunused.No confirmation or hypothesis status change.Overall eligible_edge=null;no supports/challenges hypothesis link. [code review: ATT-0303-1 stale: src/test_rb1_artifacts.py changed since RV-0064, RV-0069]

- EV-0139 [diagnostic, valid] E-0028 pre-review smoke at a6afccbec614e594ddf3c882787d86b5a2721b94 passed99regression tests, all-arm paired-init/normalized-input/eta-config/count checks, four80step export/reload smokes and one full4096row calibration timing. Steady step0.21988-0.23056s, peak2.716-2.740GB, full calibration360.328s. Diagnostic engineering result only; smoke quality discarded. ReviewRV-0087 requires identity-gate fixes and a new exact-source smoke before formal release; this is not final rule1 evidence. [code review: ATT-0314-1 not needed: pre-review deterministic checks and smoke only; no scientific outcome read]

- EV-0140 [diagnostic, valid] E-0028 revised preformal diagnostics at scientific source0f22cd60f45674ec20b800fd ATT-0315-1/RES-0284 passed112tests, full init registration and32row same-job accepted-source/new-source GPU compatibility on observed1g.24gb. ATT-0316-1/RES-0289 PBS audit verifies all4representative initial predictions equal same-allocation Base, noT0calibration artifacts, and projected4.542691585initial/5.207572029worst nodeh from comparable2g timing,

both measured smokes and allfallback/extension reserves. Diagnostic implementation/cost evidence only, smoke quality discarded; formalrelease still awaitsRV-0088. [code review: ATT-0315-1 not needed: pre-recheck deterministic checks and smoke for RV0087 fixes; no scientific quality aggregation; ATT-0316-1 not needed: bounded deterministic cost and identity audit from already completed smokes; no formal ML run]

- EV-0141 [diagnostic, valid] E-0029 initial code 0bc591a: 110 deterministic and inherited regression tests passed in verified Miyabi-G allocation mg1097, job 3775145.opbs. Includes Q-N exact feature capture, Q/K copy independence/GQA mapping, full-value prefix versus explicit weights, up-gradient collection versus virtual full-rank autograd for all three taps, SVD/RMS algebra, up-only LoRA target/count/identity/reload checks, exact rule thresholds and LR artifact reconstruction. Unit/fixture scope only; full real-data I-G scaling, eight-arm timing, dev initialization identity, final reload and scientific effects remain pending. [code review: ATT-0317-1 not needed: deterministic tests before new-path code review]

- EV-0142 [diagnostic, valid] Paired same-gradient numerical diagnostic on the four actual G-T matrices isolates the initialization failure to CUDA FP32 gesvdj: true FP64-measured stored-basis orthogonality errors0.0004707..0.0004843 and leading singular residuals0.0002009..0.0004459. TF32 was disabled (highest matmul precision). On the identical FP32-accumulated G matrices, FP64 gesvd stored to FP32 gives orthogonality errors5.62e-9..1.41e-8 and FP64 leading singular residuals1.80e-15..6.75e-15. FP32 gesvd also passes the unchanged1e-4 gate, while both FP64 solvers agree. Full-spectrum condition numbers4.43e6..3.52e7; top32 condition numbers114..186. This verifies the SVD repair, not full-arm implementation gates or any scientific accuracy hypothesis; real readout RMS and all-arm smoke remain for ATT-0338-1. [code review: ATT-0337-1 not needed: bounded solver diagnostic for failed smoke; no dev or optimizer updates]

- EV-0143 [diagnostic, valid] E-0027 rule1 implementation, both new seeds pass all five checks: (a) SEG-05 iv_off == same-allocation Base_seg row-for-row (ATT-0319-1, ATT-0320-1); (b) zero-initialized SEG-05 dev predictions == Base_seg (ATT-0307-1, ATT-0311-1); (c) seeded no-channel bitwise identity for SEG-04/06/07 at seeds 1,2 at exact source (ATT-0305-1, 354 tests); (d) same-job reload identical for all 8 arms; (e) SEG-05/06/07 initial adapter sha256 identical within seed (s1 cfe01ba0cb7b..., s2 5fe32303dadc...). Intervention normal == training predictions (0 flips) both seeds. Action: interpret.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0144 [screening, valid] E-0027 rule2 per-seed BoolQ (exact): seed0 gain=11/250=+4.40 lora=+1.70 swap=+6.50 (E-0025); seed1 SEG-05 65.7, SEG-06 60.9, SEG-07 63.1, SEG-04 63.4, iv_swap 59.5 -> gain=+2.60 [0.1,5.1] (better control T0), lora=+2.30 [-0.6,5.2], swap=+6.20 [3.1,9.3]; seed2 SEG-05 65.3, SEG-06 61.3, SEG-07 63.5, SEG-04 63.1, iv_swap 58.3 -> gain=+1.80 [-0.9,4.6] (better control T0), lora=+2.20 [-0.7,5.1], swap=+7.00 [3.9,10.1]. Intervals descriptive.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds

0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0145 [screening, valid] E-0027 rule3 three-seed equal-weight means (exact): G=88/3000=+2.933 pp, L=62/3000=+2.067 pp, W=197/3000=+6.567 pp.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0146 [screening, valid] E-0027 rule4 supports NOT met: G=+2.933 < +3 fails; other conditions hold (gain1=+2.6>0, gain2=+1.8>0, W=6.567>=G/2=1.467, L=2.067>=1). Gain shrank from +4.4 (seed0) to +2.6/+1.8 mainly because the T0 control learned at seeds 1,2 (63.1/63.5 vs 61.2).; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0147 [screening, valid] E-0027 rule5 challenges NOT met: G=+2.933 not <1; gain1, gain2 both >0; L=+2.067 not <=0.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0148 [screening, valid] E-0027 rule6 outcome inconclusive (descriptive only): H-0020 neither supports nor challenges; per the locked rule no further seeds, widening, tap change or loops.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000

draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0149 [screening, valid] E-0027 rule7 learnability (BoolQ >= Base_seg 60.9+1 = 61.9): SEG-04 and SEG-05 learned at all seeds; SEG-06 Reset unlearned at all seeds (61.5/60.9/61.3); SEG-07 T0 unlearned at seed0 (61.2) but learned at seeds 1,2 (63.1/63.5). 'r128 no-history controls unlearned' holds only for seed0. Descriptive.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0150 [screening, valid] E-0027 rule8 descriptive only: PIQA gain/lora/swap seed1 +1.7/+1.6/+3.8, seed2 +1.3/+1.2/+4.3 (seed0 +1.4/+1.9/+5.3); macro gain seed1 +2.15, seed2 +1.55; SEG-05 BoolQ answer NLL 0.644/0.635 vs SEG-04 0.828/0.809; iv_reset drop on BoolQ seed1 +3.1, seed2 +4.1 pp. No gate uses these.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0151 [screening, valid] E-0027 rule9: H-0019 remains inconclusive; H-0020 inconclusive so no stage-report trigger from rules 4/5 and no supports/challenges edge. Cost 11.217 MIG-h = 2.804 node-h (12 accounted attempts + analysis 0.003 MIG-h) <= 3.2 cap. Status change awaits conclusion review.; scope: E-0027@1/H-0020@1 segmented F, BoolQ task level, r128, seeds 0,1,2 (seed0 from E-0025 locked ATT-0303-1, not rerun); source 054a54a (RV-0085/RV-0086, coverage exception D-0058); dev 1000/task, exact point-estimate gates; per-seed bootstrap 10000 draws seed20261101 descriptive, conditional on each trained model, excludes seed variation; no confirmation set; no hypothesis status change. [code review: ATT-0306-1, ATT-0307-1, ATT-0308-1, ATT-0309-1, ATT-0310-1, ATT-0311-1, ATT-0312-1, ATT-0313-1, ATT-0319-1, ATT-0320-1, ATT-0339-1 stale: src/rb1_analysis.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_artifacts.py changed since RV-0064, RV-0069, RV-0078, RV-0079; src/rb1_intervene.py changed since RV-0064; 6 more]

- EV-0152 [diagnostic, valid] E-0029 source df20616 pre-review checks passed:112 tests; all eight prescribed arms completed80 train-only steps with registered stored/trainable/gradient counts and0.2040-0.2388s steady steps; no new dev access. All three I-G taps completed

the identical256-training-example calibration (16766 tokens plus a full actual RMS verification pass), changed only four A_v matrices, and passed stored-basis orthogonality (<3.3e-8) and relative readout RMS (<1.5e-7). Full smoke measured660s; remaining G-QN/G-N checks62s each, all in verified Miyabi-G allocations. Updated conservative total projection2.5033858733nodeh includes prior0.019097 and PBS startup overhead, below3.5nodeh. This is partial rule1 diagnostic evidence only: formal step0 dev identities and final reload checks remain, and no accuracy hypothesis is assessed. [code review: ATT-0338-1 not needed: smoke and deterministic initialization checks; no dev or formal training; ATT-0340-1, ATT-0341-1 not needed: bounded full-sample deterministic initialization check before code review; no dev or optimizer updates]

- EV-0153 [screening, valid] E-0028 rule 5, calibration-only eta selection: all 12 initial final-checkpoint calibration producers are finite and pass source/init/budget/row checks. The prescribed exact accuracy/tie rule requests no endpoint extension for either tap. Final eta-lock ATT-0343-1 selects QK eta=0.25 and X eta=1, neither at an extended boundary. SHA256 e6c1399c683b50cabb05c727e37df84be165109a2ae4dd1ba5bcf93d3349fe60 binds every input manifest/prediction plus reviewed0f22 registration. Lock and hash were written and recorded before any Part B dev aggregate. This records selection, not dev improvement; no hypothesis support/challenge edge. [code review: ATT-0321-1 stale: src/bypass_model.py changed since RV-0002, RV-0009, RV-0060, RV-0064; src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 1 more; ATT-0324-1, ATT-0325-1, ATT-0326-1, ATT-0327-1, ATT-0329-1, ATT-0330-1, ATT-0331-1, ATT-0332-1, ATT-0333-1, ATT-0334-1, ATT-0335-1, ATT-0342-1, ATT-0343-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0154 [diagnostic, valid] E-0028 rule 1 passes at exact0f22cd6: all eight grouped implementation checks are true, covering all new step0/Base predictions, Cu-zero/off identity, reloads, registered stored/trainable/with-gradient counts, paired initial parameters, exact input_layernorm X tap, eta-only configuration/init identity, unchanged RB1-09 dev predictions and source-bound selector tests. D-0060 same-allocation gates were used for1g arms; all pinned comparisons also happened to match. X-01 intervention normal equals its final training rows exactly. RV-0088 passed; inherited stale auxiliary paths are covered by D-0061. [code review: ATT-0315-1 not needed: pre-recheck deterministic checks and smoke for RV0087 fixes; no scientific quality aggregation; ATT-0344-1, ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0155 [screening, valid] E-0028 rule 2 descriptive learnability: every one of the13new training arms exceeds Base+1pp on dev. Base macro70.15%; new arms range76.90% to78.30%, gains6.75 to8.15pp. This does not establish a tap/history/eta advantage. [code review: ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0156 [screening, valid] E-0028 rule 3 / H-0021: at eta0.25, X-01 macro78.15% minus accepted RB1-09 macro77.50% is exact13/2000=+0.65pp. The preregistered outcome is descriptive (0<gain<1pp), with no support/challenge edge. Descriptive paired95% interval is[-0.25,+1.60]pp; single seed, fixed LR0.001. [code review: ATT-0321-1 stale: src/bypass_model.py changed since RV-0002, RV-0009, RV-0060, RV-0064; src/rb_sink_read.py changed since RV-

0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 1 more; ATT-0335-1, ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0157 [screening, valid] E-0028 rule 4: matched history gains at eta0.25 are X-01-X-02=-0.15pp and RB1-09-X-03=-0.65pp. Swap drops are2.00pp for X (new interventions) and1.95pp for QK (accepted E-0021, preregistered). Neither history gain reaches+1pp, so neither conjunction triggers the request to reopen H-0014. Nonzero swap sensitivity alone does not show a gain over matched T0. [code review: ATT-0321-1 stale: src/bypass_model.py changed since RV-0002, RV-0009, RV-0060, RV-0064; src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 1 more; ATT-0322-1, ATT-0323-1, ATT-0335-1, ATT-0344-1, ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0158 [screening, valid] E-0028 rule 6 / H-0022@2: eta-lock was fixed on calibration before dev aggregation, QK eta*=0.25 and X eta*=1. QK d_eta=0pp by identity; X d_eta=77.90%-78.15%=-0.25pp (descriptive95% interval[-1.15,+0.65]pp). Both tap outcomes are challenges, so the preregistered overall direction is challenges at screening level. This is not a universal no-effect claim; LR is fixed, one seed, and eta-selection uncertainty is excluded. Hypothesis status remains for coordinator conclusion review. (challenges H-0022@2) [code review: ATT-0321-1 stale: src/bypass_model.py changed since RV-0002, RV-0009, RV-0060, RV-0064; src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; 1 more; ATT-0327-1, ATT-0335-1, ATT-0343-1, ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0159 [screening, valid] E-0028 rule 7 descriptive LoRA comparison: accepted same-four-layer LoRA r7 macro78.95%. X-01 eta0.25 is-0.80pp, calibration-selected X eta1 is-1.05pp, and selected QK eta0.25 is-1.45pp relative to LoRA. None is at least+1pp above LoRA; no new-seed advantage replication trigger fires. The side branch additionally searched eta. [code review: ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0160 [screening, valid] E-0028 rule 8 descriptive outputs are retained in analysis.json: X-02-X-03=+0.15pp; selected X(eta1)-QK(eta0.25)=+0.40pp; all PIQA/BoolQ accuracy and answer-NLL results, eta/calibration curves, 25/50/75/100% dev curves and step0 vbar/Z RMS. RMS compares both taps on the same51-token first R1 training candidate; it is descriptive, not a gate or selector. [code review: ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0161 [screening, valid] E-0028 rule 9 evidence scope: implementation evidence is diagnostic and each other rule outcome is screening. PIQA/BoolQ/NLL, curves and interventions are descriptive. Bootstrap uses10000 shared task-stratified draws with seed20261101 on1000dev rows per task, excludes training-seed and eta-selection uncertainty and is not a simultaneous/multiplicity-adjusted guarantee. No confirmation or official validation data was opened; hypothesis status and route actions require coordinator conclusion review. [code review: ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0162 [screening, valid] E-0028 rule 10 point-estimate condition is true because calibration-selected X(eta1) macro77.90% is1.05pp below LoRA78.95%, strictly below the-1pp threshold. The alternative H-0021-challenges/d_tap_star conjunction is false. The descriptive selected-X-minus-LoRA95% interval[-2.15,+0.10]pp does not establish confirmed inferiority. This records the preregistered stop-condition trigger only; researcher-1 makes no stop/status decision and leaves conclusion review to the coordinator. [code review: ATT-0345-1 stale: src/rb_sink_read.py changed since RV-0077; src/test_rb1_artifacts.py changed since RV-0064, RV-0069; src/test_rb_sink_read.py changed since RV-0077]

- EV-0163 [diagnostic, valid] Source f46a13d revalidation after all four RV-0090 lows:124 tests passed, including typed nonfinite calibration exclusions versus OOM, empty step-log binding, finite original-grid endpoint decisions and lock reconstruction, pending_X01 independent rules, stale reference rejection and runtime reporting. Full smoke completed all8 80-step train-only timing arms and full G-T256-sample I-G. Fresh G-QN/G-N256-sample checks also completed, sharing the sample SHA and changing only A_v, with orthogonality/RMS gates passed. Smoke measured647s; all outputs imported. Updated conservative projection2.4743083792nodeh includes prior0.07354125 and measured scheduler overhead, below3.5. No new dev, calibration or full training yet; diagnostic scope only, formal identities/reloads remain pending. [code review: ATT-0346-1, ATT-0347-1, ATT-0348-1 not needed: bounded smoke and deterministic checks after RV-0090 low findings; no dev or formal training]

5 Discussion

证据支持以下几点。第一，V0 的侧分支与 RB 线的新实现在所测试的恒等式与隔离项上正确（diagnostic，D-0003、D-0030）。第二，在信息全部留在 backbone 里的 F 线设置下，侧支没有显示出实用价值。没有侧支历史的 tokenwise gate/up 接口没有超过加法写回 1 pp（V1，screening，D-0004），也没有超过参数相近的 28 层 rank1 LoRA（V5，confirmatory，D-0028）。带因果侧支历史的残差旁路比近预算 LoRA 低 1.85 pp，也不比同参数、不读历史的 T0 好（RB1，screening，D-0039、D-0042），加宽到 r128 后仍比参数匹配的 LoRA 低 1.80 pp（E-0026，D-0056）；训练后它的输出依赖侧支状态（swap 使宏平均下降 1.85 pp），但没有带来超过 T0 的收益。E-0024 中，残差组的集中读取主要落在每行相同的位置 0；读位置 0 且跨 episode 读出近似常量的 sink 式读取只在 PIQA 第 27 层成立（EV-0122）。第三，记忆路线的结果与这样一种解释相容：V2 的失败包含 value 的上下文迁移。上下文中编码的 value 只对第一条事实可解码；每条事实单独编码、并先在 E=1 上训练后，只用答案 CE、不用地址标签，E=16 的单跳读取在三个 seed 上都达到门槛（screening，D-0023）。在这个设置下单独编码本身不够：从零训练的 D4 失败，解码器先行后只用答案 CE 续训（D2a、D2b）与槽位边际似然（D3）也没有学到寻址（D-0021、D-0022）。第四，在 T1 句式上学到的寻址没有迁移到 T2，解码器迁移了（diagnostic，E-0018）。第五，多次读取没有显示独立收益。M 线中 S2 比 S1 只高 0.60 pp，失败出在两次读取之间的 query 转移，后继槽位监督也没有修好它（D-0036）；RB 线中 S2 比 S1 高 0.35 pp，S4 的读数可以由幅度与步长解释（D-0040）。两条线合起来只能写成“本模型规模下暂无迭代查询证据”（D-0046）。第六，把信息移出 backbone 后，侧支状态被模型使用，但收益不大：分段协议下主任务 PIQA 的 gain 为 +1.6 pp（r32）与 +1.4 pp（r128）；BoolQ 在 r128 上的 gain 三个 seed 平均为 +2.93 pp，略低于 +3 pp 门槛，而换掉第 1 段的状态在三个 seed 上都使 BoolQ 下降 6 pp 以上（D-0057、D-0062）。第七，用户提出的 RB1-09 改进中，换特征来源只带来 +0.65 pp（区间跨零），按 calibration 搜索 η 没有带来提升，两种特征来源下历史读取都不比同参数 T0 好，所有侧支组都低于 LoRA r7（screening，D-0066、D-0067）。

证据不支持以下推断：上下文编码的记忆可用（D5 的 adapter 在上下文编码写入下只有约 5% EM），所以单独编码是须声明的结构化输入条件；D5 的结论适用于 T1 一跳、E=16、V2-03 配置

之外；读算子选择性（H-0004，inconclusive）的任何结论；tokenwise 接口在其他任务、层或训练长度上同样无效；侧支状态在任何设置下都无用，或残差旁路与 LoRA、T0 等价。RB1 是单 seed、dev 每任务 1,000 条的筛选，只能分辨约 2 pp 以上的差别，区间不含 seed 与选择的不确定性，A2 确认集也没有开封。RB1 的 T0 是当前 token 的非线性门控，与 R_res 共用参数，但不是去掉历史的同一注意力，所以它是 "同参数、无历史的非线性适配器" 对照（D-0043）。RB1、E-0026、E-0028 与 V3 的负结果都不推广到其他层、宽度、特征、任务或训练预算；E-0026 的 r128 沿用 r32 的 LR 锁定值。E-0028 的 η 结论只限所测的网格、一个 seed 与固定学习率，不含 η 选择的不确定性。分段线的 BoolQ 结果只有三个 seed，dev 既用于选择也用于判定，r128 沿用 r32 的 LR 锁定值。swap 后的准确率低于 Base_seg，降幅里可能含换入状态带来的分布偏移，所以它不能证明收益来自哪种机制。分段各组都远低于全上下文 LoRA（PIQA 至少低 5.0 pp，BoolQ 至少低 17.6 pp），所以这些结果只说明侧支状态能把一部分信息带过段界，不说明实用价值。除 V5 外，所有结果都是单 seed 或三个 seed 的筛选级证据。官方 validation 已经用掉；A2 确认集是否开封，按 D-0045 的重开条件决定。

- D-0001 route:pause — 旧 S-RE 推理资产（writer.pt、sq2 loader 所需文件）不在本文件系统：/work/xg24i002/x10041/LoopLora 目录不存在，只有 GitHub 源码 a255e81 可读。用户 2026-11-01 选择按计划 fallback 跳过冻结 S-RE 诊断（plan §6.1），新方案直接从 Base 实现；不声称旧指标已复现。(reopen if: 用户提供 S-RE 推理资产（writer.pt 及 looplora.llm.sq2.load_inference 所需的归一化 buffers 与配置）的位置，并为该诊断分配 $\leq$1 node·h)

- D-0002 route:continue — V0 实现检查 85/85 通过（ATT-0006-1/RES-0006/EV-0005，GH200 MIG 2g.24gb，容差在适配代码前锁定且未改动）；代码审核 RV-0001 的问题全部修复，RV-0002 通过，两条 low 跟进（FP32 chunk3 状态比较、KernelMatrix 支持容量保护）只约束分块/缓存记忆实验与 V2，不影响 V1 tokenwise 路径。按用户授权的 V0+V1 里程碑进入 V1：先做 E-0002（PIQA/BoolQ 切片与三个家族的学习率校准），再按实测成本生成 E-0003 八组 release。H-0001 的证据状态暂不改为 supported，等 V1 阶段报告时一并做结论审核。V0 实际用量 0.045 MIG instance-h，0 训练 tokens。

- D-0003 route:continue->supported — V0 侧分支实现语义在测试范围内成立（diagnostic，E0）：E-0001 修正后 85/85 项检查通过（RV-0002 pass），E-0004 130/130 项通过（RV-0009 pass）。覆盖陈述中的全部恒等式与隔离项；prefill、分块与逐 token decode 的输出在预先锁定的 BF16 容差内一致；chunk3 FP32 记忆状态在 2e-5 内一致。逐 token（chunk1）记忆状态的 FP32 差异 0.18–0.25 只作诊断记录，不宣称相等；全 padding 的 query 行无语义约定。结论审核 RV-0014 通过、零发现。范围只是实现正确性，不涉及学习效果或机制价值。下一步：实现作为 V1/V2 的基础继续使用；用到逐 token 缓存记忆的实验前，先查清 chunk1 差异的来源。[conclusion review RV-0014 pass (same_family_unverified)]

- D-0004 route:pause->challenged — 按 E-0003@2 运行前固定的规则（RV-0008 代码审核通过；RV-0015 结论审核通过、零发现）：在 Qwen3-0.6B-Base、F 线、四层 r32 tokenwise proxy、预先锁定的家族校准配方（三族均为 3e-4）、seed 0、每任务 1,000 条 dev、最终 checkpoint 的条件下，最佳 concat（C_dual 78.15%）只比 F*（F_out 77.80%）高 0.35 pp，未达到 +1 pp 的筛选标准，记为 concat 未胜；所选 C*（C_up 77.70%）的观测准确率低于两个 LoRA（79.20%、79.05%）；非线性 proxy 对线性退化组只高 0.15 pp [-0.70, 1.00]。因此 H-0002 在该设置下记为 challenged（screening）。这不排除其他训练 seed、接口专属调参或总体上 $\geq$1 pp 的真实效应（最佳 concat 对 F* 的描述区间上限为 1.35 pp），也不否定有记忆的 concat（H-0003）。按契约，V2 保留 C_dual 作为交互探针，融合用 F*=F_out 与 C*=C_up。此决定不释放 V2 预算。(reopen if: V2 中有记忆的 C*（C_up）或 C_dual 交互探针明显优于 F*（F_out），或用户要求用多个 seed 复核 V1 筛选) [conclusion review RV-0015 pass (same_family_unverified)]

- D-0005 stage:continue_probe — V0+V1 里程碑完成，总用量 11.25 MIG-h ≈ 2.81 node·h（预算 200）。V1 没有发现 gate/up 融合相对加法写回的优势（H-0002 暂停），但 V2 的问题（有记忆的单跳读取，H-0003）不由无记忆的 V1 proxy 决定；按 E-0003 契约，V2 融合用 F*=F_out 与 C*=C_up，并保留 C_dual 交互探针。E-0007 显示 E=16 的 F 线对 Base 很难（问题主语复制 96%，限定候选 (b) 14.2%，随机 3.7%；E=1 时 EM 67%），所以建议 V2 分两步：先用训练后的 F 线正对照确认任务在上下文中可学，同时做记忆家族学习率校准；正对照达到预先锁定的水平后，再跑八组析因。V2 是否释放、预算多少由用户决定。

- D-0006 route:pause->inconclusive — E-0010@2 locked H4 rule: SoftmaxSlot better in 0/4 cells and KernelMatrix in 0/4, neither reaches 3/4. With no arm producing a usable episode-memory read (EV-0070), a read-operator comparison cannot separate selectivity from absent memory content; soft EM is higher in all four cells by under 1.2 pp but its target weights are lower in three. No further H-0004 runs until memory reads work. (reopen if: An M-line configuration produces a usable episode-memory read (H-0003 gate met, or the single plan 8.4 probe shows a signal), so the two read operators can be compared on working memory.)

- D-0007 route:diagnose->challenged — E-0010@2 locked rule: 0/10 arms qualify (max EM margin +0.6 pp vs 10 pp; every arm-mean target weight below 0.125 and 1/16; normal and shuffled NLL nearly equal) after the E-0008 positive control passed. Screening only: one seed, released configuration and 4M tokens per arm; not a general impossibility result. The learned-value oracle failure points at values and the downstream path without isolating the cause; LR/schedule, implementation and write-position alternatives are neither shown nor excluded. Per plan 8.4 the next step is E-0012 diagnostic measurement (no automatic mapping), then one preregistered and reviewed probe of at most 4M tokens or a reviewed stop for limited expected value. V3 stays closed. Conclusion review RV-0025 (medium finding on the E-0012 draft mapping) resolved in RV-0026 (pass). [conclusion review RV-0026 pass (same_family_unverified)]

- D-0008 route:stop — Expected-value stop of further spending on the new memory route (M line); H-0003 stays challenged (screening). Basis: E-0010 locked gate 0/10 released arms (EV-0070) and the E-0012 diagnostic measurements (EV-0072; L0 controls 96.6-100%). Observations (single seed, diagnostic): at the last question position the highest-weight slot (argmax of mixture weights) is slot 0 in 1000/1000 dev episodes for every trained arm, so its target rate equals the slot-0 base rate (52/1000); reads remain weighted mixtures (E-0010 mean n_eff 4.0-10.0 kernel, 1.0-5.8 soft); arm-mean target margins there are negative (soft -2.1 to -16.8, kernel -1247 to -3501); arm-mean fused-increment to layer-14 residual norm ratios are 18.7-608 (1.1e6 for V2-09). Under the L3 ridge probes (4,096 train episodes, calibration held-out) actual-read accuracy is near the prior (1.8-2.3%; clean-to-read 1.9-3.0%) and learned target values give 16.6-23.0%; in the separate L2 softmax probes trained value projections decode the tail no better than random-init projections (17.0-37.1% vs 32.2-38.5%). Frozen layer-14 features give 92.9-99.6% tail decoding and 82.2-90.2% supervised (target-labelled bilinear) addressing top-1 among 16 facts at the last question position across ranks 128-1024, with no consistent gain with rank. Normal and shuffled NLL are nearly equal (4.42-4.61, near the 4.39-nat train answer-prior entropy; zero memory 9.25), while normal is below permuted in V2-03 (-0.18) and V2-10 (-0.11 nats), so outputs are not fully content-independent. Interpretation (not established): predominantly prior-like adaptation through the memory path without demonstrated useful episode-specific retrieval; an optimization cause under answer-only CE is plausible but not isolated; information absence is not shown. Rationale: ten released arms failed; the diagnostics show coupled difficulties; no permitted rescue has demonstrated benefit

and their expected value is judged too low to prioritize over the reduced F-line work. Accepted uncertainty: plan 8.2 temperature/gain calibration with a registered restart or paired continuation, S=2 training and wider value/fusion width remain untested and are not falsified; the single plan 8.4 probe (at most 4M tokens) stays available as a reopen path. Scope: one seed, 4M tokens per arm, answer-only CE from Base, layer 14, visible-delimiter writes, E=16, released LRs. Conclusion review RV-0028 (two medium findings) resolved in RV-0029 (pass, two low wording corrections applied here). (reopen if: The user approves a change outside the plan 8.4 probes that targets the observed failure (for example fewer facts per episode or a curriculum, a separate path that absorbs the answer prior, or addressing supervision), or a reason appears to spend the single permitted probe (temperature/gain calibration with restart, S=2, or same-layout width; at most 4M tokens).) [conclusion review RV-0029 issues (cross_model_unverified)]

- D-0009 route:pause — V3/V4 test multi-read gains on a fixed memory that a single read can already use (plan 5.1: V3 only after a usable V2 read). No released V2 arm produced a usable single-hop memory read (EV-0070) and the memory route is stopped (D on H-0003, RV-0029). The T2 chain-end data contract and generator (E-0011, T-0010) are ready and kept for reuse. (reopen if: A working single-hop M-line memory read (H-0003 locked gate met, or a reopened memory route shows the gate signal).)

- D-0010 stage:stop — V2 delivers a stop of the memory route as an expected-value decision (D-0008, RV-0029): no released arm met the locked single-hop gate, diagnostics show a fixed top-ranked slot, read-out increments far above the residual scale and near-prior read decodability, while frozen features remain linearly informative. Per plan 5.1 and 14.2 the project continues with V5 reduced to a simple-interface comparison (V1 tokenwise F_out and C_up against a parameter-matched strong LoRA, F line, PIQA+BoolQ, three seeds, sealed validation opened once). Changes that target the observed failure but lie outside the permitted probes (fewer facts per episode or a curriculum, a separate prior-absorbing path, addressing supervision) are listed for the user; changing facts per episode is the user's decision. [conclusion review RV-0029 issues (cross_model_unverified), RV-0030 issues (cross_model_unverified)]

- D-0011 route:expand — Release the reduced V5 as one confirmatory experiment, E-0013@3 (DOC-0128@3), testing H-0008@2. Basis: plan 5.1/14.2 allow V5 to shrink to a simple-interface comparison after the memory route stops (D-0008 stop, D-0009 V3/V4 paused, D-0010 V2 stage stop). The V1 screening evidence EV-0048 (C_up trails LoRA4 r10 by 1.50 pp and LoRA28 r2 by 1.35 pp on dev, seed 0) sets modest expectations, so the experiment is a preregistered estimate rather than an expected win. Design: C_up r32 and F_out r64 (524,288 parameters each) against all-28-layer all-7 rank-1 LoRA (630,784) with seeds 1-3, exactly 3 epochs, the V1 example-mean objective, per-arm LR selection on calibration NLL with one endpoint expansion per side, and the final checkpoint only. The sealed official validation is opened once, after code reviews, a dev rehearsal and a lock manifest. Gates are fixed in E-0013. Intervals are conditional on the three trained seeds, and the +1 pp and per-task -1 pp rules are point-estimate gates. Budget at most 12 node-h (estimate 7.8; project total 4.2 of 200). Conclusion review RV-0031 found two issues (medium objective mismatch, low wording), both fixed in E-0013@2 and H-0008@2. Re-check RV-0032 passed; its low provenance finding was fixed in E-0013@3, which adds a tests relation to H-0008@2.

- D-0012 route:reopen — The D-0008 reopen condition is met: on 2026-11-01 the user approved out-of-plan changes that target the observed failure (fewer facts per episode or a curriculum,

a separate prior-absorbing path, addressing supervision), including changes to the sealed data protocol through new registered data versions, and authorized all meaningful attempts without further approval (docs/constraints.md). H-0003 stays challenged at screening level for the released V2 recipe (EV-0070); that result is not rewritten. The reopened route tests modified training recipes as H-0009 (derived from H-0003) in the screening experiment E-0014: six single-change arms on the V2-03 configuration, judged by the locked E-0010@2 H3 gate on T1 E=16 dev, plus an E=1 value-transport control. The memory route resumes beyond E-0014 only if a recipe meets the gate and replicates with new seeds; V3/V4 (D-0009) stay paused until then.

- D-0013 route:consult — E-0014 outcome: only R1 passed its value gate (E=1 dev +82.6 pp); no E=16 arm met H3; R2 failed its E=4 gate. This is the pre-registered branch ' 只有 R1/R2 达标 -> 试组合，需要时请顾问'. Three single changes (curriculum R3, prior path R4, centered cosine R6) reproduced the V2 slot-0 collapse, so combining them is unlikely to help. Diagnostics point beyond addressing: R2 on E=4 dev has last-position target weight 0.983 (argmax=target 100%) yet 8.2% EM; R5 oracle_value at E=16 is 10.7%; R1 oracle_value drops from 83.6% (E=1) to 5.8% (E=16). Surviving explanations (slow coupled address/value learning, mixed reads at non-final question positions, context shift of support features, oversized fusion exit) are not separated by existing tests, so one advice round (AD-0001, AD-0002) informs the next screening contract. H-0009 stays untested; V3/V4 stay paused (D-0012).

- D-0014 route:expand — Advice round 1 (AD-0001, AD-0002) agrees: continue one bounded round rather than pause. Both checked from per-episode files that one value map does not transfer between 'fact 0' and 'facts with a prefix': R1 oracle_value 45/52 at target position 0 vs 13/948 later; R5 the mirror image, 1/52 vs 106/948. No E=16 arm has trained its decoder on clean reads. Magnitude and clipping do not explain the failure: R1 succeeded at E=1 at about 9x residual with about 99.6% of steps clipped. Correction to EV-0083's last sentence: R4's prior path reached only NLL 4.74 at zero memory vs 4.42 for the collapse solution, so 'prior absorbed yet still collapses' is not shown. Next round: E-0015@4 (eval-only diagnostics on calibration, T-0016) plus E-0016 (training screen, sealed) testing three advice-derived hypotheses: H-0010 decoder first (D1 teacher-forced single-slot, D2a/D2b address learning from answer CE), H-0011 slot-marginal likelihood with last-position read (D3), H-0012 per-fact isolated writes (D4/D5, only if E-0015 rule 5 holds). Budget 0.25 + 0.9 node·h. Rejected candidates: plain R1 warm start with contextual writes, mixed E=1/E=16 batches, longer runs of the old arms, a magnitude cap as a standalone arm.

- D-0015 route:continue — V5 LR 校准的 12 条 run 中有 2 条在 MIG 1g.24gb 上（ATT-0103：C@1e-3，即 C 的选中值；ATT-0107：L@1e-4），其余在 2g.24gb（MSG-0421）。处理如下。(1) 原 lr-lock.json 保留为正式输入：它按登记规则（取 calibration NLL 在最小值 1% 以内的最小 LR）从有效 run 得出；E-0013 没有规定校准的硬件，1g 与 2g 的差别是 BF16 舍入级的数值差异，不是计算错误。(2) 敏感性检查（diagnostic）：用相同代码、配置与 seed 0，在 guard 确认的 2g 上重跑这两条，报告各自 calibration NLL 的差；用已审核的 lock CLI 在全 2g 的 12 条 manifest 上重算 lock，输出到单独文件，不覆盖 lr-lock.json。(3) 预先规定：重算结果与原 lock 相同，记为 LR 选择对切片稳健；若不同（只可能发生在 C：2g 下 C@1e-3 的 NLL 比 C@3e-3 的 1.6025 高出 1% 以上，即约大于 1.6185），也保留原 lock 与九个正式 run，不重训、不加 run，并在 V5 分析与 H-0008 结论中把 C 的 LR 选择列为对硬件数值敏感的限制。(4) 正式 run 不因训练所在切片重跑，每个 run 的硬件 profile 按最终 manifest 记录；validation 开封评估与延迟测量都在 guard 确认的 2g 上进行，九个 checkpoint 与 Base 的确认评估用同一种切片。

- D-0016 route:continue — Coverage exception for the E-0016 formal runs ATT-0154-1 (D1) and ATT-0155-1 (D3), and for D2a/D2b later run from the same reviewed source 6da33b3. run register marks them stale on src/test_v2r_diagnostics.py, src/v2r_diagnostics.py and src/v2r_reload_check.py. Those are E-0015 files that RV-0046 (the T-0018 review of the same experiment) also lists. All three paths are absent from commit 6da33b3: the coordinator checked with git ls-tree and git grep that the T-0017 sources neither contain nor import them. So the runs cannot execute them. RV-0045 (pass, 0 findings) reviewed every path these runs execute, and ATT-0152-1 verified the final source. Decision: run without a re-check. A model re-check of files that the run does not contain cannot change what the run computes. The stale label stays on the attempts with this reason. It does not apply to T-0018 runs, which do execute the isolated-write code under RV-0046.

- D-0017 route:continue — Coverage of T-0018's D4 (ATT-0158-1) and D5 (ATT-0159-1) at 415cac3. run register marks them stale on src/v2_train.py. In that commit the file is master 8cccbb1 plus T-0017's train() hook. researcher-3 checked that the hook is byte-identical to the one RV-0045 reviewed. The rest of the file differs from 6da33b3 by T-0016's evaluate() change, which RV-0042 and RV-0043 reviewed and ATT-0140-1 regression-tested bitwise. The two hunks merged automatically and sit in different functions. All shared v2r16_* files are byte-identical to 6da33b3. Unlike D-0016, this file is executed, and no reviewer has seen this combination. So, instead of a model re-check, a deterministic check comes first. In one guarded 2g PBS job at 415cac3 (no training), run the full test suites of T-0016, T-0017 and T-0018: test_v2r_diagnostics, test_v2r16_analysis, test_v2r16_objective, test_v2r16_schedule, test_v2r16_memory, test_v2r16_isolated, plus T-0017's exact default-identity check. If everything passes, D4/D5 run at 415cac3 under this decision without a re-check, and the stale label stays with this reason. If anything fails, stop and report.

- D-0018 route:continue — User instruction 2026-11-01 (about 23:10 JST): **不要考虑 BF 的舍入这一点误差**. This supersedes D-0015 items (2) and (3). The V5 slice-sensitivity comparison and the all-2g lock recomputation are dropped. The two finished reruns (ATT-0103-2, ATT-0107-2) are kept only as plain diagnostic records. The original lr-lock.json is final, with no sensitivity caveat. Project-wide: BF16 rounding differences between MIG 1g.24gb and 2g.24gb slices are not treated as an error source. Nothing is rerun, analysed or flagged because of the slice it ran on, and the profile is recorded as metadata only. A cross-job bitwise mismatch that a different slice explains is not a failure. Existing 2g guards stay where they are already wired in, because they cost nothing and prevent false exact-match alarms. No new slice checks are added.

- D-0019 route:continue — Follow-up to D-0018. D4 (ATT-0158-1, PBS 3766228) failed in 1 s on its 2g guard. PBS placed it on mg1109_mig3, which is a 1g.24gb slice. Slot 3 on these nodes is 1g, so a fail-fast guard rejects a large share of placements. Under D-0018 that buys nothing: the remaining E-0016 reload checks run in the same job, so they use the same slice. Rule from now on: MIG guards record the profile and never fail the job. The one exception is a job that measures time for comparison (latency or throughput), which keeps fail-fast on 2g. A job that already failed only on the guard is resubmitted as a new attempt with the guard in record-only mode. Jobs already queued are not cancelled.

- D-0020 route:continue — E-0017 stage A (R1 recipe at seeds 1 and 2) may run at f01b036 before the stage-B review round closes. RV-0049 reviewed the stage-A seed path at 64331a4 (v2_train.py --seed: initialization and the appended-seed order rule; v2_schedule.py) and

raised no finding on it: it answered that seed 0 stays exact and that the positive-seed derivation is a reasonable, documented reading of the contract. Its two findings are in v2r16_isolated.py (stage B) and src/test_e0017_seeds.py. The coordinator checked with git diff that only those two files changed between 64331a4 and f01b036, and with git grep that v2_train.py does not import v2r16_isolated.py, so the stage-A runs execute only code that RV-0049 saw unchanged and judged sound. run register may label the stage-A attempts as not covered because the RV-0049 round still has a medium finding open; that label stays with this reason. Stage B (C1, C2 and the P continuations) still waits for a passing review of the stage-B fix and of the start-adapter hash pinning.

- D-0021 route:pause->challenged — H-0011 被挑战，证据级别 screening，范围限于从零训练（没有解码器预热）：单 seed 0，E=16 上下文编码写入，V2-03 配置，6000 步。D3 硬读取 15/11/10，+0.4 pp，最后位置目标权重 0.061。NLL 只比 shuffled 低 0.004 nat，是答案先验解。失败方式（RV-0052）：逐槽解码器没有学成事实相关的映射，oracle_value 17/1000，NLL 4.421，和 normal 差不多；所有非零记忆的对照都在 4.42–4.43；边际目标几乎不给寻址信号。最后位置权重接近均匀：n_eff 7.9，argmax 77.5% 落在槽位 0。训练 CE 在 2001–2500 步为 4.53，2501–3000 步为 4.52，结束时 4.41，当时学习率仍高（RV-0053 的更正）。这次没有检验' 有可用解码器时边际似然能否发现寻址'。按 E-0016 的 outcome_actions（D1 达标，D2a、D2b、D3 都未达标）暂停。记忆路线经 H-0012/E-0017 继续。RV-0053 通过。(reopen if: (a) 要在已有可用解码器（如 D1 checkpoint ATT-0154-1）上检验边际似然能否发现寻址；(b) E-0017 没有复现 D5，需要另一条不用标签的路线；(c) 后续阶段在单独编码写入下需要换训练目标。) [conclusion review RV-0052 issues, medium open (same_family_independent_session), RV-0053 pass (same_family_independent_session)]

- D-0022 route:pause->challenged — H-0010 是两段的合取，记为 challenged，证据级别 screening：单 seed 0，E=16 上下文编码写入，V2-03 配置，每段 6000 步。阶段 1 成立：D1 用 teacher-forced 单槽读取，用了目标索引，属额外监督；668/11/13，+65.5 pp，达到 50 pp（EV-0097）。阶段 2 不成立：只用答案 CE 续训后，D2a 只训寻址 50/11/18，+3.2 pp，全位置目标权重 0.069（EV-0098）；D2b 全部训练 48/11/18，+3.0 pp，权重 0.087，oracle_value 从 668 降到 170（EV-0099）。读法（RV-0051）：只能说明干净读取下有解码容量，而这个答案 CE 配方没能发现寻址；不是唯一的因果识别，也不说寻址学不会。按 E-0016 的 outcome_actions 暂停，不在上下文编码写入下用监督寻址开展 V3 机制研究。不用标签的 D5（单独编码写入）已在 seed 0 达到 H3（EV-0095），记忆路线经 H-0012/E-0017 继续。RV-0051 通过，0 个问题。(reopen if: E-0017 没有复现 D5，而 V3 机制研究需要一条声明额外监督的寻址路线；或者要在单独编码写入下检验解码器先行。) [conclusion review RV-0051 pass (same_family_unverified)]

- D-0023 route:continue->supported — H-0012 记为 supported，证据级别 screening，只限 R1 续训这一支（D5 配方）：先按 E-0014 R1 配方在 E=1 上训练 6000 步，再在 E=16 上用单独编码写入续训 6000 步，只用答案 CE，不用地址标签。按 E-0017 的预先规则，P1、P2 都达到 E-0010@2 的 H3（单独编码写入协议，统计量与 E-0010 分开报告），连同 seed 0 共 3/3。三者的差分别是 41.1、47.8、46.2 pp（EV-0095、EV-0102、EV-0103），NLL 低于 zero 与 shuffled，全位置目标权重 0.158–0.162，两个目标位置分层都达标。最后位置没有塌缩到固定槽位：最常见的最后位置槽位占 7.6–8.0%（RV-0055 的更正）。描述性的 C1、C2 也达标（EV-0104、EV-0105）。' 从零训练' 这一支不成立：D4 失败，读取均匀（EV-0096）。同一批 adapter 在上下文编码写入下只有约 5%，第 1 条及以后约 1.4–2.4%（RV-0055 的更正）；所以单独编码是绕开上下文迁移的、须声明的结构化支持输入条件，不是让上下文编码的 value 变得可用。四条结果的 arm 标签不一致只是命名问题（RV-0055 同意），见各证据的 validity 说明。范围：M 线 T1 hop 1，E=16，V2-03 配置，每个 seed 一个 run，不读

confirmation。RV-0055 通过，只有一个 low（描述范围），已在本文更正。动作：按 E-0017/E-0016 的 outcome_actions，用这个配方与协议重开 V3/V4 路线（H-0005）。[conclusion review RV-0055 issues (cross_model_unverified)]

- D-0024 route:reopen — 按 E-0016 与 E-0017 的 outcome_actions 重开 V3/V4 路线（D-0023）：在单独编码写入的 D5 配方下，单跳读取在 3/3 seed 达到 H3，满足 plan §8.4 进入循环的条件，只限这个协议与配方。H-0005 的范围已改为这个协议、配方与 T2 链终点任务（E-0011）。先做 V3 的前置诊断：D5 adapter 在 T2 hop1 上能否迁移，以及不训练时扫描 S_eval 1/2/4/8；然后再定 V3 的训练矩阵。

- D-0025 route:continue — plan2 作为 RB 线加入（用户 2026-11-02）。新增 H-0013..H-0018 与契约 E-0019（RB0）、E-0020（RBc）、E-0021（RB1），由 Opus 5.5 subagent 先在记录副本中建出，协调者审核后在主项目重放（research/notes/plan2-commands.sh，提取见 research/notes/plan2-extraction.md）。协调者对待定问题的决定如下。Q1 RB 线确认集选方案 A2，而不是 subagent 推荐的 A1：从 V1 train 中每任务切出 1,000 条，按 derive_seed(20261101,'residual_la_v21','RB5','confirma 分层抽取，登记 id 清单与 SHA256 后封存；RB 线的 train 为 V1 train 去掉这些行；calibration 与 dev 不变。理由是 A1 的行已被 E-0002 与 E-0013 的 LR 选择用过，A2 的行从未影响任何选择；官方 validation 将由 E-0013 开封，之后不再作确认。这符合' 改方法后的确认用新数据'，没有改变确认集规则。Q2 保留 RB1-09（C_up）。Q3 采用 RB1 Design 中的推进规则 G0/GR/GH/GL/GC 与规则 11：GR 只是释放 RB5 的资源门槛，主线主张仍要求确认集上 +1 pp。Q4 RBc 用三点网格加一次端点扩展。Q5 F 线干预的操作定义按 RB0 Design 第 4 项，由 RB0 的代码审核核对。Q6 T-0013 已合并（f0d9283）。Q7 KernelMatrix 版的 D5 配方与 H-0004 的重开，放到 M 线 V3/V4 设计时决定。Q8 RB0 现在开始；RB5 最晚 11-18 释放。Q9 RB 线的固定字段与确认集安排写入 docs/constraints.md，标为协调者默认。

- D-0026 route:modify — RB0 检查 ATT-0186-1 三项 BF16 比较失败的处理：拓扑改用逐位恒等（零容差）并逐层检查 FFN 输入；cache 保留 BF16 锁定容差并照实记录 chunk1 超出，另加 FP32 决定性检查与状态清空负对照。不放宽任何锁定容差。全文见 rationale-file。

- D-0027 route:modify — D-0026 的处理推广为一条通则（ATT-0187-1：395/397 通过；剩下两项是 cache 重排测试中 order=[1,0,0] 把 batch 从 2 扩到 3，BF16 logits 差 0.857421875 > 0.50002，prefix 与未改动的 reference 在同一位置给出相同值）。通则：BF16 比较若跨越 GEMM 形状的改变（逐 token decode、batch 扩展），且超出量在未改动的 reference 上完全相同，就只作诊断，照实记录，0.50002 不改；决定性门槛是同一比较在 FP32（关闭 TF32）下按 E-0019 的 FP32 门槛（逐张量 $\max|a-r| \le 1e\text{-}5 + 1e\text{-}4 \cdot \max|r|$）。形状不变的比较仍按 BF16 0.50002 判定。对本项：契约的 "batch 重排" 用同 B 的真置换判定（BF16 0.50002，输出须随行移动）；B2→B3 扩展另做 FP32 的扩展与所有权检查（每个扩展行等于其来源行）；BF16 下 prefix 与 reference 的差仍须 ≤ 0.50002。FP32 检查不过 -> 按真实问题修复后重测，不进入训练。

- D-0028 route:stop->challenged — H-0008@2 记为 challenged（confirmatory，按 E-0013@3 运行前封存的规则），停止这条路线。PIQA+BoolQ 官方 validation 只开封一次（ATT-0179-1，EV-0110）：F 线四层 [6,13,20,27] 的 tokenwise C_up（r32，524,288 参数）对全 28 层 all-7 LoRA rank1（630,784 参数），3 个 seed 平均的宏平均差 −0.42 pp，配对按任务分层 bootstrap 95% 区间 [−1.02, +0.20] pp（只反映给定这三个训练 seed 时的数据不确定性）；上界 < +1 pp，按封存规则记 challenges。三个 seed 的差都为负（−0.28、−0.40、−0.58 pp）；每任务 PIQA −0.74、BoolQ −0.09 pp。区间含 0，不宣称等价，也不宣称 LoRA 更好。次要比较 S1（C−F +0.23 pp，Holm p=0.34）与 S2（F−L −0.65 pp，Holm p=0.069）在 Holm 校正后都不拒绝。WikiText ΔNLL：C +0.20、F +0.24、L +0.34。范围：V1 切分、模板与评估，每 run 正好 3 epochs，短校准 LR（三族都锁定为 1e-3），LoRA 结论只针对 rank1，

不含侧支历史与多次读取。官方 validation 已用掉，H-0008 不能在该集上再确认，所以 stop。父假设 H-0006 仍为 paused/untested；带因果侧支历史的版本由 RB 线的 H-0013/H-0014 在 D-0025 的 A2 确认集上检验，不复用 V5 的 checkpoint。来源（按 RV-0061 更正）：a09c318 封存了确认锁；03de68f 加入 preflight 结果与 allocation、说明与开封 launcher；RV-0056 覆盖两者。ATT-0179-1/ATT-0194-1 的代码审核标签 stale 来自这些任务分支输入不在 2b5c809 中，以及未使用的切片检查路径，不是执行源码的漂移。[conclusion review RV-0061 issues (cross_model_unverified)]

- D-0029 stage:stop — V5 缩减版（H-0008）阶段结束：无侧支历史的 tokenwise C_up 接口在官方 validation 上没有超过参数相近的 LoRA28 r1，按封存规则记 challenged 并停止（路线决定 D-0028，结论审核 RV-0061）。官方 validation 已用掉；带因果侧支历史的实用价值问题转由 RB 线（H-0013/H-0014，A2 确认集）检验。[conclusion review RV-0061 issues (cross_model_unverified)]

- D-0030 route:continue->supported — H-0017 记为 supported，证据级别 diagnostic（E0），范围只是 RB0 的实现正确性（EV-0112；结论审核 RV-0063 通过，零发现）。ATT-0188-1 的 397 项与 ATT-0197-1 的 408 项 PBS 检查通过，另有三个真实的 rb_train CLI 冒烟（重载一致，inventory 与 lock 字段齐全）。覆盖：因果前缀 KernelMatrix 与已审核的逐 token 参考在输出、M/c/counts 与梯度上一致（梯度只在 CPU FP32 上比较）；四层 R_res 与 concat 零出口等于 Base；R_res 只在块 FFN 之后加 Z·P_R，拓扑逐位一致，各层 FFN 输入一致，每层只调一次 FFN；两步梯度启动，主干冻结；T0 与侧支历史干预符合定义，不泄漏未来 token；参数计数与 plan2 §15 一致。与陈述中容差条款的偏离（D-0026、D-0027）：跨 GEMM 形状改变的 BF16 比较超出 0.50002（逐 token decode 0.8203，B2→B3 扩展 0.8574），未改动的 reference 给出相同的值，只作诊断；形状不变的 BF16 门槛与决定性的 FP32 门槛通过，锁定容差没有放宽。代码审核 RV-0060（4 条 low 已修复）与 RV-0062（零发现）通过。不涉及任务性能、GPU 上的梯度一致，也不涉及尚未编写的 RB1 干预运行器与分析脚本。下一步：RBc（T-0024，E-0020）在这套实现上校准学习率。[conclusion review RV-0063 pass (same_family_unverified)]

- D-0031 route:modify — 按 E-0022 规则 1 做了顾问轮次 2。两位顾问（AD-0003、AD-0004）都建议继续，结论一致：起点阶段只在 “全部问题位置平均目标权重” 一条上失败。这条量的是问题长度：T2 问题 23-25 个 token，非末位均值 0.052，即使答案位置读权重为 1，全位置均值也只有约 0.09。AD-0004 核对了全部已有门槛判定，改用答案位置不改变任何一条。EV-0111 的原门槛失败保留，不改写。采用的做法：(1) 新契约 E-0023，不修改已封存的 E-0022。准备度规则 R 在看到 dev 起点结果后制定，只在此前没有评估过的 T2 calibration 上检查一次。R 包括 hop1 EM 差 ≥ 10 pp、hop1 NLL 条款、hops 1-3 答案位置上第一条路径事实的读权重各 ≥ 0.125（AD-0003）、hop1 最常见末位槽位 ≤ 0.25（AD-0004）。(2) 先训 V3-01/02/03（约 0.44 node·h）。S_M* − V3-01 ≥ 3 且 hop1 差 ≥ -1 时，才释放其余对照。依据 AD-0004 的结构事实：S=1 的读取不能依赖另一次读取，V3-01/05/06/07 在 hops2-3 上是地板。S_M*=2 时加同深度的固定 query 对照 V3-05b（AD-0003）。hop1 下降时先训 V3-09/V3-10（AD-0004）。(3) 新增描述性诊断：每步对第 s 条路径事实的读权重；终点边 value oracle（原 oracle_value 在 hops2-3 上插入的是第一条边，AD-0003）；按答案频率分层的 EM。(4) 结果为空或增益不足时，先做一次冻结转移诊断，再按事先写定的对应关系至多做一个修复 arm：后继槽位 CE pilot（额外监督，单独陈述）或线性起步 S4。暂不采用：开始前先跑第二起点周期（AD-0004 P2，改作 R 不成立时的备用，因为各 arm 本身也训练 hop1，AD-0003 也不建议先花在 hop1 上）；事实头 token key（AD-0004 P3，作暂停时的重开候选）；冻结读位置消融（AD-0003 P2）；改模板或停止（两位都不建议）。T-0023 以起点阶段交付；新任务按 E-0023 进行。

- D-0032 route:continue — 运行前澄清 E-0021 预登记规则的两处空隙（RB1 尚无训练或 dev

结果；researcher-1 在 MSG-0630 提出）。（1）规则 10 与规则 1-9 在恰好 Base + 1 处重叠：按规则 2，宏平均 '>= Base + 1'（精确分数，含等号）的 arm 是有效的，不算规则 10 的"在 Base ± 1 内"；规则 10 只在每个训练 arm 都满足 'Base - 1 <= arm < Base + 1' 时适用，不推翻任何已成立的门（G0、GR、GC、GL 照原文含等号判定）。理由：规则 10 来自 plan2 §7.4，前提是连正对照都学不动；G0 成立即说明正对照按本契约的定义在学习；G0 不成立时规则 1 给出与规则 10 相同的动作。（2）GC 成立但 RB1-08、RB1-09 都未达到 Base + 1 时，C*_RB 无定义：规则 7 的 GC 追加组（RB5-03/04/06/07/09）与规则 8 的 RB1p pilot 都不释放；放行判断按 GC 不成立处理（此时 GR 必不成立，因为 GR 与 GC 同时成立意味着 concat '>= Base + 2'），即 G0 成立走规则 9，G0 不成立走规则 1。规则 11 的证据方向不变（GC 照原文判定），记录中写明两个 concat arm 都未有效。分析脚本同时输出原始门值与按本决定解析后的动作。

- D-0033 route:pause->challenged — 按 RV-0068（复核通过，0 条发现）记录 H-0009@1 为 challenged（screening，seed 0，限登记的 V2 M 线配置、原上下文写入协议与训练预算）：E-0014 的 R2 至 R6 都没有在 E=16 dev 达到 H3（EM 差 +1.2、-0.2、-0.6、+4.6、+0.2 pp，门槛 +10 pp），R1 只通过 E=1 value 门。这挑战了"这些单项配方足以修复读取"的预测，不区分训练动态、表示迁移与容量哪个是主因。E-0015 的上下文迁移诊断只限 R1 的 calibration；R2、R5 没有同等的单独编码救援。范围外的 D4、D5 结果记在 H-0012 名下，写入协议、预训练与总训练预算各自的必要性未分离。EV-0096 的 NLL 描述已更正（RV-0066 第 3 条）。暂停本路线：记忆线已改用单独编码写入（H-0012 supported），现在接着做 V3（H-0005@2，E-0023）。(reopen if: 某条线必须用原上下文写入（非单独编码）在 E=16 读取时：再检验 R 配方的组合与多 seed，并加入匹配总训练预算的对照) [conclusion review RV-0066 issues, medium open (cross_model_unverified), RV-0068 pass (cross_model_unverified)]

- D-0034 route:continue — 运行冻结转移诊断之前，把 E-0023 规则 4 的修复对应关系定成数值判据（researcher-3 在 MSG-0676 报告阶段 A 为 A3，诊断尚未运行）。三个判据都在 S_M*（V3-02）上算，用 hops 2-3 合并的 calibration 子集，取答案位置，EM 按精确分数计算。（a）终点 value 能解码：终点边 value oracle 的 EM 减 max(EM_zero, EM_shuffled) 至少 10 pp（沿用 H3 的差值门）。（b）桥查询能寻址到下一条边：问题主语换成金标准桥实体后，第 1 步对路径第 2 条事实的平均读权重至少 0.125，并且错误桥（同关系）与无关 donor 桥两种对照在同一事实上的平均读权重都低于 0.125。（c）原生转移不能：原生第 2 步对路径第 2 条事实的平均读权重低于 0.125。0.125 沿用准备度规则 R 与规则 5 已登记的比较值，不另定新常数。对应关系：（a）不成立，不修复，只作描述；（a）（b）（c）都成立，做后继槽位 CE 的 S4 pilot 加置换后继标签对照；（a）成立而（b）不成立，做线性起步 S4；（a）（b）成立而（c）不成立，三条对应都不适用，不修复，只作描述，直接写结论。第 1 步强制为正确第一条边 value 的读取只作描述。说明：（a）与（c）的数值已在阶段 A 的诊断里看到（终点 value oracle 约 45-47%，第 2 步权重 0.069），（b）尚未看到；判据只用已登记的常数，以限制事后选择。

- D-0035 route:continue — E-0023 规则 4 的冻结转移诊断（ATT-0253-1，EV-0116）按 D-0034：（a）（b）（c）都成立，对应修复为后继槽位 CE 的 S4 pilot 加置换后继标签对照。运行前确认 researcher-3 在 MSG-0686 提出的定义，并固定 pilot 判据。定义：两组都从共同起点 ATT-0196-1（准备度 ATT-0227-1）出发，用 V3-03 配置（S4），2,000 步，取阶段 A 顺序的前 16,000 个 episode，5% warmup，LR 0.003，日程形状压缩到 2,000 步，两组的初始化与数据顺序相同。标签：hop h 的训练行在答案位置（最后一个有效问题 token），第 s 步（s = 2 至 min(4, h)）的读取以 path.fact_indices[s-1] 为标签；第 1 步与超过 h 的步不加标签。损失：答案 CE 加 1 倍的有标签 (行, 步) 对上 SoftmaxSlot logits 的 -log_softmax[label] 平均，无标签的 batch 加 0。置换对照：每个 episode 用带种子的 16 槽错排 π，标签换成 π(正确标签)，标签数与位置不变。判据，在 T2 dev 的 hops 2-3 上以 S=4 正常读取评估，两条都

成立才算正确标签胜过置换：(i) 主指标 (EM_hop2 + EM_hop3)/2 的差 (正确减置换) 至少 +3 pp，按精确分数；(ii) hop 2 行上答案位置第 2 步对路径第 2 条事实的平均读权重，正确组至少 1/8，置换组低于 1/8。否则修复路线到此为止 (AD-0003 的停止条件)。hop1 与 V3-03 只作描述。结果记为额外监督下的 screening 证据，不作 H-0005 的无监督证据；之后按 E-0023 的 A3 路径写结论并做结论审核。代码放在新模块 v3_succ.py，不改共享类，运行前做代码审核；预算不超过规则 4 的 0.25 node·h。

- D-0036 route:pause->inconclusive — 按 RV-0073 (通过，只有 1 条 low，已采纳) 记录 H-0005@2 为 inconclusive (screening，seed 0，限 E-0023 的设置：M 线单独编码写入、冻结 Qwen3-0.6B-Base、第 14 层 r128、T2 hops1-3、从通过准备度规则 R 的共同起点出发、S1/S2/S4 各训练 6,000 步)，暂停该路线；E-0023 按 stop 条件结束，V4 不起草。R 在未用过的 T2 calibration 上成立 (EV-0113)。阶段 A 为 A3：S_M* = V3-02，S_M* - V3-01 = 200/333 = +0.60 pp (描述性 bootstrap 区间 [-0.60, +1.80])，低于 +3 pp，也不满足挑战条件；hop1 下降 450/167 pp (EV-0115)；阶段 B 未释放，GL_M 与解释性对照都没有检验。D-0034 冻结诊断 (EV-0116)：V3-02 上终点 value 能解码、给定桥后能寻址到第 2 条事实，原生第 2 步不能 (0.0761)，失败出在两次读取之间的 query 转移，只限 V3-02。D-0035 修复 pilot (额外监督，EV-0117) 两条判据都不成立 (+550/333 pp < +3；正确组权重 0.0834 < 1/8)，最后 100 步后继 CE 为 2.51 (正确标签) 与 2.77 (置换标签，约等于 ln 16)，都没有带来达到 D-0035 判据的转移；这不作 H-0005 的无监督证据。结论不推广到其他层、宽度、数据或训练预算。跨线 (E-0021 的循环条款) 在 RB1 结论审核后并列写入阶段报告。(reopen if: 有一种 query 更新设计，在冻结检查中使原生第 2 步对路径第 2 条事实的平均读权重 >= 1/8 且 hop1 下降不超过 1 pp；或有新的文献或证据给出可学的 query 转移办法)

- D-0037 route:pause — D-0012 为 H-0009 的配方修复重开了 H-0003。该修复路线已暂停：D-0033 依据 RV-0068 把 H-0009 记为 challenged，限上下文写入协议。记忆线之后改用单独编码写入 (H-0012 supported)，其 V3 续作也已暂停 (D-0036，H-0005@2 inconclusive)。H-0003 维持 challenged (screening，E-0010 锁定门 0/10)，不再有开放工作，所以暂停；不改写其证据状态。(reopen if: 某条线必须用原上下文写入 (非单独编码) 在 E=16 读取时：再检验 R 配方的组合与多 seed，并加入匹配总训练预算的对照 (同 D-0033))

- D-0038 route:consult — E-0021 规则 9 已触发 (G0 成立，GR、GC 都不成立；EV-0118 至 EV-0121)。按规则 9 先判前提：RB1-01 (T0 正对照) 有效，比 Base 高 7.15 pp [5.40, 8.90]；梯度启动有实现测试记录 (ATT-0197-1：第一次反向时融合出口梯度非零，一次更新后四层所有投影与读取梯度有限且非零)，正式运行的前三步 pre-clip 范数有限，663,552 个参数都有梯度。所以实现与可学性成立，规则 9 允许至多一次容量或特征探针 (H-0018)。跨线条款的读取选择性：RB1-02 答案位置的读取只在 BoolQ 第 6 层弥散 (相对 n_eff 0.753)，其余 7 个任务层组合都集中 (0.010 至 0.080)，当前 token 权重处处很低；所以 "读取选择性不足" 不是普遍的解释，只作为 BoolQ 第 6 层的观察写入阶段报告，不占用探针名额。探针怎么选 (同布局 r64 加匹配参数的 LoRA；r32 下 raw 与 SiLU(raw) taps；或不放)，以及换成一个需要侧支因果历史的任务是否更值得，交给顾问轮次 3；在此之前不启动任何探针。

- D-0039 route:pause->challenged — 按 E-0021 规则 11 与结论审核 RV-0074 (pass，无发现)，把 H-0013@1 记为 challenged，证据层级 screening：seed 0，只限 RB1 的设置 (冻结 Qwen3-0.6B-Base，四层 [6,13,20,27] r32 R_res+KernelMatrix S1，qknorm_pre_rope，锁定 LR 3e-3，2,000,069 输入 tokens，PIQA 与 BoolQ 的 dev 各 1,000 条)。RB1-02 宏平均 77.10%，参数接近的四层 all-7 LoRA r7 为 78.95%，差 -1.85 pp (描述性配对 95% 区间 [-3.00, -0.70])，PIQA -2.00、BoolQ -1.70 pp；主差值 <= 0，所以记 challenges。RB1-02 比 Base 高 6.95 pp，旁路本身能学；不成立的是 "比参数接近的 LoRA 至少高 1 pp"。限制：单 seed，dev 同时用于选择，区间不含 seed 与选择的不确定性，LoRA 少 4.94% 参数，RB5 确认集与全 28 层

LoRA r1 对照没有运行；不说明两者等价，不排除更小的效应，不推广到其他层、宽度、特征或任务。路线：E-0021 规则 9 已触发（D-0038），不建 RB5，H-0013 暂停；规则 9 允许的唯一探针（H-0018）由顾问轮次 3 之后决定。(reopen if: 规则 9 的唯一探针（H-0018）在同布局下让 R_res 达到 Base+1 pp 以上且不比匹配参数的 LoRA 低 1 pp 以上；或出现需要侧支因果历史、且 RB1 未覆盖的新任务证据。满足时重开 H-0013 并重新规划 RB5。) [conclusion review RV-0074 pass (same_family_unverified)]

- D-0040 route:pause->inconclusive — 按 E-0021 规则 11（EV-0120，screening，seed 0，dev 每任务 1,000 条，S_F* 在同一 dev 上选定）：S_F* 锁定为 S2（RB1-03），S2 比 S1（RB1-02）高 +0.35 pp（描述性配对 95% 区间 [-0.55, +1.30]），为正但低于 GL 的 +1 pp 门槛，只作描述，不支持也不否定。对照：S4 减固定 query 的 S4 为 -0.20 pp [-1.10, +0.70]；$\eta/4$ 减 S1 为 -0.60 pp，S4 减 $\eta/4$ 为 +0.40 pp，所以 S4 的读数可以由幅度与步长解释。GL 不成立，不做 RB1p，RB5 不含循环组。RB1 的 T0 只有 S1，不能排除逐 token 深度的解释。按 plan2 §17.2 写作 “本模型规模下暂无迭代查询证据”，与 M 线 V3 停在 A3、H-0005@2 暂停（D-0036）一致；跨线写法放到阶段报告。H-0015 记为 inconclusive 并暂停，不再加循环组。(reopen if: 新的 RB 轮次（H-0018 探针或需要侧支历史的任务之后）在带同深度 T0 对照的筛选中，循环 S_F* 比 S1 高至少 1 pp；或 M 线出现迭代查询的独立收益。)

- D-0041 route:pause->inconclusive — 按 E-0021 规则 11（EV-0121，screening，seed 0，dev 每任务 1,000 条）：C_up（RB1-09）宏平均 77.50%，C_dual（RB1-08）77.45%，残差 S1（RB1-02）77.10%；最好的 concat 比残差高 +0.40 pp（描述性配对 95% 区间 [-0.70, +1.50]），为正但低于 +1 pp，原始与解析后的 GC 都不成立，只作描述，不支持也不否定。两个 concat 组都比 Base 有效且相差在 1 pp 以内，参数较少的 C_up 锁定为 C*_RB。GC 不成立，不建 RB5 的 concat 组，也不做 C-S1/S4 pilot；参数匹配的 LoRA、更宽的残差与 concat 自己的 T0 都没有测。接口参数不同（C_up 925,696，C_dual 1,318,912，残差 663,552），不宣称参数效率。V1 proxy 的结论（EV-0048、D-0004）不改写。H-0016 记为 inconclusive 并暂停。(reopen if: 新的 RB 轮次中残差旁路先有信号（H-0018 探针或需要侧支历史的任务），并且 C*_RB 在筛选中比残差至少高 1 pp；或计划参数匹配的 concat 对照。)

- D-0042 route:pause->challenged — 按 E-0021 规则 4 与规则 11，以及结论审核 RV-0075（pass，3 条 low 发现都已在下面的措辞中处理），把 H-0014@1 记为 challenged，证据层级 screening：seed 0，只限 RB1 的同一设置。依据 EV-0119：RB1-02 减同参数、没有侧支历史的 S1 T0（RB1-01）为 -0.20 pp（PIQA -0.90，BoolQ +0.50），主差值 <= 0，按规则 11 记 challenges；描述性配对 95% 区间 [-1.30, +0.90] 的上限也低于 H-0014 要求的 +1 pp。这个区间只对 dev 行重采样，不含 seed 与选择的不确定性，不表示两者等效；T0 仍经原 attention 与含上下文的 Q/K/V 获得上下文。训练后 RB1-02 的输出依赖侧支状态：换成同任务其他 episode 的历史（swap）使宏平均降低 1.85 pp [0.75, 3.00]，H-0014 的干预部分达到各 >= 1 pp 的门槛；打乱 key/value 配对（permute）降低 17.15 pp，但读权重集中在少数非当前位置，这一幅度可能主要来自状态结构被破坏（分布偏移），不作侧支内容带来收益的证据。所以挑战只来自 T0 对照（plan2 §11.3 的决定性对照）。对照检查：iv_off 与 Base 逐条一致在 RB1-02（以及 RB1-03、08、09）上检查，T0 的 swap 无变化在 RB1-01 上检查，不一致时程序报错；RES-0243 的 T0_swap_noop=false 与 RES-0247 的 iv_off_identical_to_Base=false 按 arm 设置（src/rb1_intervene.py:156-157），意思是该 arm 不运行这项检查，不是检查失败。学习率锁定若有偏向，也偏向 RB1-02（T0 的 3e-3 在网格上端）。按 H-0014 的 scope（plan2 §11.4），这里只称动态或非线性适配，不称收益依赖侧支的因果历史。限制：T0 只有 S1，没有 S2、S4 的同深度 T0；单 seed；干预可能带来分布偏移；RB5-08 与确认集上的干预没有运行；不推广到其他配置或任务。路线：规则 9 已触发（D-0038），不建 RB5，H-0014 暂停；唯一探针由顾问轮次 3 之后决定。(reopen if: 在需要侧支因果历史的设置（H-0018 探针或新任务）中，带同参数同深度 T0 对照的筛选显示历史组比 T0 至少高 1 pp，且 swap 降幅

>= 1 pp。满足时重开 H-0014。) [conclusion review RV-0075 pass (same_family_unverified)]

- D-0043 route:pause — E-0021 规则 9 的唯一探针不释放（选项 d）。顾问轮次 3 的两位顾问（AD-0005、AD-0006）独立给出相同结论，理由我核对后采纳：(1) H-0018 的通过条件（R_res >= Base+1 且不比匹配 LoRA 低 1 pp 以上）没有 T0，同布局加宽或换 tap 即使通过，也只说明适配器变好，不能移动 H-0014；T0 与 R_res 随宽度、特征一起变化。(2) RB1 中 R_res 与同参数 T0 相差 -0.20 pp，状态没有被用满，看不出容量不足；读取在答案位置大多已经集中（BoolQ 第 6 层除外），选择性也不是缺的东西。(3) +1 pp 的单 seed 门槛在每任务 1,000 条 dev 的行级区间半宽（约 1.1 pp）以内，同一设置下再测一个旋钮得不到可分辨的结果。(4) 实用问题已在两个设置中测过：RB1 的 R_res 比近预算 LoRA 低 1.85 pp，E-0013（3 seed、官方 validation）的 tokenwise C_up 比 LoRA28 r1 低 0.42 pp。另外核对了 src/bypass_core.py 的 process_kernel_tokenwise：T0 是 SiLU(norm(z)Rq + norm(k)) v 的当前 token 非线性门控，与 R_res 共用参数，但不是去掉历史的同一归一化注意力；所以 RB1 的 T0 对照是“同参数、无历史的非线性适配器”，下一步加一个同算子的段界重置对照。H-0018 暂停；规则 9 的 8M tokens 储备不使用。按两位顾问的建议，下一步是一个新的、有上限的问题：只有侧支状态能跨过 backbone 看不到的边界时，状态是否带来收益（分段信息访问协议，新的假设与契约，另行登记）。(reopen if: 分段信息访问协议（新契约）中，四层 r32 的跨段状态收益为正但低于预先登记的门槛，并且契约预先登记了宽度阶梯：此时在该协议内做 r128 的 R_res/T0 配对，而不是在原 RB1 设置中加宽。)

- D-0044 route:continue — 运行前澄清 E-0025@1 规则 6 的一处空隙（还没有任何 SEG 训练或 dev 结果；researcher-1 在 MSG-0723 提出）。规则 6 写的是 gain128 < +1 记 challenges，括号里的理由是“r32 与 r128 都没有 >= +1 的收益”；但 r32 的 gain 在 [+1, +3) 时这个理由不成立。按顾问 AD-0006 的停止条件（r32 与 r128 都 < +1 才停）与 E-0021 规则 11 的惯例（为正但低于门槛只作描述），规则 6 释放 r128 之后按下面判定：(a) gain128 >= +3 且 iv_swap 使 SEG-05 在主任务上下降 >= gain128/2：supports（只限 r128）；(b) gain32 < +1 且 gain128 < +1：challenges（两个宽度都没有 >= +1 的收益）；(c) 其余情况只作描述（包括 gain32 在 [+1, +3) 而 gain128 < +1，以及任一宽度在 [+1, +3)），H-0019 记 inconclusive，不再加宽、换 tap 或加循环，写进阶段报告。规则 3 与规则 6 中的“主任务”都指按规则 3 选定的主任务（PIQA 没有信息量时退到 BoolQ）。其余规则不变。

- D-0045 stage:pause — RB1 阶段结束。按 E-0021 的预登记规则：G0 成立，GR、GC 不成立，触发规则 9；T0 正对照有效、梯度启动正常，但顾问轮次 3 的两位顾问都认为同布局探针不能改变 H-0013 或 H-0014 的判断，所以不释放探针，也不建 RB5。所有带侧支状态的组（S1、S2、S4、C_dual、C_up）都在 76.9%-77.5% 之间，都低于 LoRA 的 78.95%；对 Base 的提升大多来自 BoolQ（PIQA 只有 +0.1 至 +2.1 pp），每任务 1,000 条 dev 的单 seed 设计只能分辨约 2 pp 以上的差别。在信息全部留在 backbone 里的设置下，没有证据说明侧支状态有用。这条线暂停，各假设的重开条件已登记。下一步换一个问题：只有侧支状态能跨过 backbone 看不到的边界时，状态是否有用（H-0019，E-0025，$\leq$ 3 node·h）；同时用 E-0024（$\leq$ 0.1 node·h）确定 RB1 干预表的读法，然后写阶段报告。(reopen if: H-0019（E-0025）在分段协议下显示跨段状态的收益并在新 seed 上复现；或出现需要侧支因果历史、RB1 没有覆盖的任务证据。满足时重新评估 RB 线，包括是否建 RB5 与开封 A2 确认集。)

- D-0046 stage:pause — M 线 V3 与修复阶段结束。单跳记忆读取在单独编码写入下可用（H-0012，3 个 seed），这是 M 线保留的正结果；在它之上的多次读取（V3）停在 A3，没有超过幅度与步长解释的收益，冻结诊断指出的后继槽位修复也没有通过 pilot；上下文写入下的配方修复（H-0009）没有通过。所有登记的路线都到了预先写定的停止点，没有可以继续的单项修复。这一阶段暂停，各假设的重开条件沿用 D-0033、D-0036、D-0037。跨线：RB 线的 GL 不成立，M 线 GL_M 未检验（阶段 B 未释放），两线一起只写“本模型规模下暂无迭代

查询证据”。下一步在分段协议里检验侧支状态跨段的收益（H-0019，E-0025）；它是上下文中逐 token 写入，与 H-0012 的单独编码写入不互相推广。(reopen if: 有一种 query 更新设计，在冻结检查中使原生第 2 步对路径第 2 条事实的平均读权重 >= 1/8，且 hop1 下降不超过 1 pp（D-0036）；或某条线必须用原上下文写入在 E=16 读取（D-0033）；或 E-0025 显示上下文写入的侧支状态能跨段带来收益。)

- D-0047 route:modify — E-0024 的预算上限从 0.1 提到 0.15 node·h（还没有任何 E-0024 诊断结果）。原因：RV-0076（2 条 medium）要求经验证的评估路径与硬门槛；ATT-0270-1 的工程检查显示右填充 batch 在 BF16 下对形状敏感，Base 上也有（单行只加填充时 BoolQ gold NLL 最大差 1.37 nats），不能复现 E-0021，所以改用 E-0021 的逐条（batch 1）只评 gold 候选的路径，并对 E-0021 设紧的一致性门槛。researcher-1… researcher-3 按 E-0021 实测时间估计约 0.11 node·h，加上测试与检查约 0.01（已用 0.007）。只改预算；arm、条件、指标与预登记判读都不变，不删条件或 arm。

- D-0048 route:modify — E-0024 的完整运行 ATT-0273-1 在 RB1-03/iv_window8 按硬门槛失败关闭（PBS 3770151，0.147 MIG-h）：gold NLL 与 E-0021 的最大差 1.22e-4，门槛 1e-4；该条件的读诊断汇总与 E-0021 逐位相同。差值正好是 1 个 FP32 ulp（这些行的 NLL 为 1324-1997 nats），来源是求和顺序：E-0021 先算逐 token loss 再求和，本实现用 cross_entropy(reduction='sum')。处理：(1) 修复 ee5d8f6（2 行加 1 个测试）改为 reduction='none' 再.sum()，与 E-0021 的运算顺序相同；门槛仍为 1e-4，GPU 测试要求与 E-0021 的差恰为 0（ATT-0274-1）。这一改动只影响一致性门槛所用的 gold NLL，不影响 share0、argmax0、常量读取指数 C 等要解释的读诊断，正确性由硬门槛与零差测试直接检验，所以不另开代码审核轮次；测试通过后才提交正式重跑。(2) 预算上限从 0.15（D-0047）提到 0.25 node·h：实测每个条件 167-171 s，干净的完整重跑约 0.149 node·h，加上已用约 0.051，合计约 0.20，45 分钟 walltime 的最坏情况约 0.24。采用完整重跑（单一 commit 的来源），不拼接 ATT-0273-1 已通过门槛的 RB1-03 normal/strict 输出。arm、条件、指标与预登记判读都不变。

- D-0049 route:continue — 代码审核覆盖的例外，只限一个继承来的测试文件。run register 把 E-0025 的正式 attempt（从 ATT-0277-1 SEG-00 起，源码 7d8b346）以及 E-0024 的 ATT-0273-1、ATT-0275-1 标为 stale，原因只有 src/test_rb1_artifacts.py 在 RV-0064、RV-0069 之后有改动。核对结果：这次改动是 T-0025 合并进 master 的 8bf0146，只在该测试文件里加 16 行，用来恢复错误 LR 家族被拒绝的回归测试（RV-0069 的 low），ATT-0250-1 中通过；仓库里只有 src/rb1_check.py 与 research/notes/T-0025-artifact-test.pbs 引用它；seg_*.py 不 import rb1_check 或任何测试文件，rb_sink_read.py 与 T-0027 的作业脚本也不引用它。所以这些运行执行的代码没有被这次改动触及：E-0025 的分段路径由 RV-0078（pass，3 条 low 已修）与复核 RV-0079（pass，无发现）覆盖，E-0024 的读诊断路径由 RV-0077 覆盖（加上 D-0048 的求和顺序修复）。这些 attempt 在审核覆盖上按已覆盖处理；证据的 scope 注明本决定。

- D-0050 route:modify — E-0024 重跑 ATT-0275-1（ee5d8f6，PBS 3770205，0.3925 MIG-h）中，RB1-03、RB1-08、RB1-09 的三个条件与 E-0021 在 gold NLL 和每项读诊断上逐位相同，sink.json 完整；只有最后的 RB1-02/normal 按硬门槛失败关闭：本次在 2g 切片上，E-0021 的 RB1-02 参考在 1g 切片上，gold NLL 最大差 1.86、平均 0.079，读诊断相对差 <= 1.9e-3。另外三个 arm 在同一 2g 档上逐位相同，所以差异来自 MIG 档的 BF16 运算路径（D-0018/D-0019 所说的切片舍入），不是实现错误。采用 researcher-3 的方案 A：只对 RB1-02 再做一次 attempt（小改动，只加一个驱动开关），在同一个分配里先用 E-0021 审核过的逐条 evaluate_history 算 normal、iv_strict、iv_window8 的参考，再用相同容差把只评 gold 的路径对这个同分配参考设门槛；与 E-0021 1g 参考的差只作描述。RB1-03、08、09 沿

用 ATT-0275-1 的结果（同一 commit 谱系，逐位门槛已通过），汇总按 arm 写明 attempt 与 commit；这与 D-0048 不拼接的要求不冲突，因为那三个 arm 是完整且逐位通过的。不另开审核轮次，但要求：一个单元测试证明参考来自 evaluate_history 而不是 gold 路径本身，且对 gold 路径输出加扰动时门槛会失败；GPU 测试通过后再提交。方案 B（放宽到跨档容差）同样要重跑 RB1-02，却削弱门槛，不采用；方案 C 无法控制切片，不采用。预算上限 0.25 node·h 不变（已用约 0.149，方案 A 约 0.077）。

- D-0051 route:modify — E-0024 一致性检查的修订（在看到检查失败之后，读诊断的判读尚未打开）。ATT-0283-1：12 个 arm-条件都通过 E-0021 门槛，RB1-02 与同分配的 evaluate_history 参考逐位一致（gold NLL 差 0，读诊断相对差 0）；与 E-0021 1g 参考的差（normal NLL 最大 1.86、平均 0.079；strict 1.77/0.078；window8 2.83/0.164）按 D-0018/D-0019 只作切片舍入的描述；iv_window8 检查在所有 arm 上通过（窗口外 share0 最大 0.0）。失败的是我在 Design 中写的 iv_strict 检查 $|\text{strict} - \text{normal share0}| < 0.01$：在 4 个单元超出（RB1-02 boolq L13 −0.0102；RB1-03 piqa L20 −0.0108；RB1-09 piqa L20 +0.0152；RB1-08 最大 0.0095）。这个阈值写错了：去掉当前位置后读权重重新归一化，同一层的 share0 机械地变为 share0/(1−cw)，cw 可达 0.047；第 13 层以后，前面各层的 strict 读取还会改变隐藏状态与 q/k。所以它不是实现检查。采用 researcher-3 的方案 1：用一个精确的实现检查替换它。第 6 层是第一个旁路层，strict 不改变它的输入，所以逐位置必须有 $\text{share0_strict} = \text{share0_normal}/(1 - \text{cw_normal})$（S2 只在第 1 步成立）；在 RB1-02 的 normal 与 strict 上、每任务 50 条、保存第 6 层逐位置张量，验证到浮点精度。成立时，用已有的 sink.json 重新汇总，检查项按本决定修订，并在结果中写明 “检查在看到失败后修订”；share0 > 0.5、C > 0.9、< 0.2 等判读阈值与指标都不变。不成立时停止，写工程报告，不作判读。成本约 0.007-0.009 node·h，总计约 0.233，上限 0.25 不变。

- D-0052 route:reopen — 用户 2026-11-02 在协调者会话中要求：’ 我们当前项目给侧分支的低秩设为 32 是不是小了点, 测试一下 r=128 呢’。这一明确要求优先于 D-0043 中’ 不在原 RB1 设置中加宽’ 的选择（那是协调者依据顾问轮次 3 作出的选择）。重开 H-0018 的 r 探针，只做 r128，在普通（全上下文）RB1 设置下进行：R_res+KernelMatrix S1 r128 对参数最接近的同四层 all-7 LoRA；按 D-0043 指出的缺口，加一个同参数、同深度的 r128 T0 对照，使结果能对应 D-0042 的 H-0014 重开条件。契约 E-0026，预算 <= 1.5 node·h，判定规则在运行前锁定。分段协议中的 r128（E-0025 规则 6，SEG-05..07）照原登记进行，与本探针分开记录；若规则 6 不释放，按同一用户要求作为探索性对照运行。限制沿用 D-0043：单 seed、dev 每任务 1,000 条只能分辨约 2 pp 以上的差别；r128 沿用 r32 的 LR 锁定值；T0 是当前 token 的非线性门控，不是去掉历史的同一注意力。

- D-0053 route:continue — 代码审核覆盖的例外，只限 E-0026 的三个训练 attempt（ATT-0295-1、ATT-0296-1、ATT-0297-1，源码 c9f78b9）。run register 把它们标为 stale，原因是 src/rb_history.py 与 src/rb_read_diagnostics.py 在 E-0021 的审核之后有改动（来自 T-0027/E-0024，已在 RV-0076/RV-0077 一轮审核）。核对：rb_train 不导入这两个模块；bypass_model 只在设置了 intervention、capture_history 或 trace_reads 时才惰性导入 rb_history，而这条路径在 self.training、梯度开启、带 cache 或非 F 阶段时直接报错（c9f78b9 的 src/bypass_model.py:199-202 与 305-318），所以训练不执行这两个文件。训练路径的改动由 RV-0080（被改动作废）与复核 RV-0081（只剩 1 条 low，已在 c9f78b9 修好）覆盖。这三个训练 attempt 按已覆盖处理，可以与新一轮审核并行开始。W-02 的干预与锁定分析要等新一轮审核：它覆盖 81ad3de（researcher-3 发现 validate_read_summary 只接受 E-0021 的五个读摘要字段，会拒绝 E-0024 之后的扩展字段；修复只改分析路径，并加端到端测试），以及当前 rb_history.py、rb_read_diagnostics 在 W-02 r128 干预路径上的用法。

- D-0054 route:continue — 代码审核覆盖的例外，只限 W-02 干预 attempt ATT-0299-1（源码 81ad3de，训练 run ATT-0296-1，训练源码 c9f78b9）。run register 标 stale 的只有两个测试文

件 src/test_rb1_artifacts.py 与 src/test_rb_read_diagnostics.py（在 RV-0064/RV-0069 之后有改动）。核对 81ad3de：rb1_intervene.py 只导入 calibrate、rb_history、rb_read_diagnostics、rb_train、v1_data、v1_run、v5_train，以及函数内的 rb1_artifacts 与 rb1_rules，不导入任何测试文件；research/notes/T-0029-intervene.pbs 只 exec src/rb1_intervene.py，不运行 pytest。干预实际执行的生产文件由 RV-0082（pass，0 条发现）与 RV-0080/RV-0081 一轮覆盖。所以 ATT-0299-1 按已覆盖处理（同 D-0049 的做法），可以用 PBS 依赖 afterok:3772067 在 W-02 训练成功后自动开始。

- D-0055 route:continue — D-0054 的覆盖例外同样适用于锁定分析 attempt ATT-0300-1（源码 3678f60）。核对：3678f60 相对已审核的 81ad3de 只新增 research/artifacts/T-0029/analysis-input.json 与 costs.json 两个数据文件，没有代码改动；src/rb_width_analysis.py 只导入 rb1_analysis、rb1_artifacts、rb1_intervene、rb1_rules、rb_train、v1_analysis，不导入测试文件；research/notes/T-0029-analysis.pbs 只 exec rb_width_analysis。run register 标 stale 的只有 src/test_rb1_artifacts.py 与 src/test_rb_read_diagnostics.py 两个测试文件，所以 ATT-0300-1 按已覆盖处理。另记：RES-0273（ATT-0299-1）spec_match=False 只因 manifest 的 arm 字段写 W-02，而 RunSpec 登记为 W-02-interventions；条件、来源与数值都经锁定分析核对，输出有效。

- D-0056 route:pause->challenged — 按 E-0026 规则 3 与结论审核 RV-0083（pass，0 条发现），把 H-0018@1 记为 challenged，证据层级 screening：seed 0，只限 r128 与普通（全上下文）RB1 设置（冻结 Qwen3-0.6B-Base，四层 [6,13,20,27]，qknorm_pre_rope，KernelMatrix prefix S1，沿用 r32 的 LR 锁定值，13,115 步，dev 每任务 1,000 条）。W-02（R_res r128）宏平均 76.95%，比 Base 高 6.80 pp [5.00, 8.55]；比参数最接近的同四层 all-7 LoRA r31（78.75%）低 1.80 pp，两个任务各 -1.80。判定按点估计：d_L = -1.80 pp 低于 H-0018 允许的 -1 pp；描述性配对区间 [-3.10, -0.50] 跨过 -1，只对 dev 行重采样，不含 seed 与选择的不确定性，不表示两者等价或差距一定大于 1 pp。实现检查全部通过（EV-0124），LoRA 对照学成，所以层级为 screening。描述：r128 相对 r32 的变化都在 ±0.5 pp 以内（W-02 - RB1-02 = -0.15，W-01 - RB1-01 = -0.50，W-03 - RB1-07 = -0.20）；W-02 比同参数 r128 T0 高 0.15 pp [-1.00, +1.35]，iv_swap 降 2.25 pp，D-0042 的 H-0014 重开条件不满足，H-0013 维持 challenged。按 E-0026 规则 8，普通设置下不再加宽或换 tap，H-0018 暂停。不推广到其他层、任务、LR 或更大模型。(reopen if: 需要侧支因果历史的设置（例如 E-0025 的分段协议）中 r128 带来达到预登记门槛的收益，并有具体理由认为普通设置下的结论会改变；或用户要求在普通设置下检验其他宽度、tap 或为 r128 单独校准的 LR。) [conclusion review RV-0083 pass (cross_model_unverified)]

- D-0057 route:continue->inconclusive — 按 E-0025 的预登记规则、D-0044 与结论审核 RV-0084（pass，0 条发现），把 H-0019@1 记为 inconclusive（screening，seed 0，分段协议，四层 KernelMatrix S1，r32 与 r128，dev 每任务 1,000 条）。两个任务都有信息量（全上下文 LoRA 减分段 LoRA：PIQA +7.0 [4.8, 9.2]，BoolQ +19.3 [16.1, 22.5]），主任务 PIQA。PIQA：r32 gain +1.6 [-0.3, 3.5]（swap 降 4.2），r128 gain128 +1.4 [-0.4, 3.2]（swap 降 5.3），都为正但低于 +3，属于 D-0044(c)，只作描述；按规则 6 不再加宽、换 tap 或加循环。次要任务 BoolQ：r32 gain +2.0 [-0.8, 4.9]；r128 gain128 +4.4 [1.5, 6.8]，swap 降 6.5 >= gain/2，满足 r128 的任务层点估计门槛。按规则 8（主任务不成立而次要任务成立）记 inconclusive，下一步是 BoolQ 两个新 seed 的复现。描述：BoolQ 上 r128 保留状态组与 r32 几乎相同（65.9 vs 65.8），gain 上升主要因为 r128 的无历史对照更低（T0 61.2 vs 63.8），所以复现要重训全部三组 r128 arm；评估时清空状态使 BoolQ 降到 Base_seg 以下，干预降幅含分布偏移。限制：单 seed，dev 同时用于判定，区间只含数据不确定性；全上下文 LoRA 远高于所有分段组，不宣称实用价值。按 RV-0084 的提醒，复现契约保留原训练混合（PIQA+BoolQ 一起训练），seed 汇总与成功规则在运行前锁定。

- D-0058 route:continue — 代码审核覆盖的例外，只限 E-0027 在源码 054a54a 上的正式 attempt：八个训练 attempt ATT-0306-1 到 ATT-0313-1，以及之后在同一源码上的 SEG-05 干预与锁定分析 attempt。E-0027 的全部改动由 RV-0085 与复核 RV-0086（都 pass，0 条发现）覆盖。run register 把这些 attempt 标为 stale，原因是 src/rb1_analysis.py、rb1_artifacts.py、rb1_intervene.py、rb_history.py、rb_read_diagnostics.py、rb_train.py 与三个 RB 测试文件在 E-0021/E-0025 的审核（RV-0060、RV-0062、RV-0064、RV-0069、RV-0078、RV-0079）之后被其他任务改过：ded77c2（E-0024）、075af4a（T-0027），已在 RV-0076/RV-0077 一轮审核；44f880c、b9ef167、81ad3de（T-0029/E-0026），已在 RV-0080/RV-0081 与 RV-0082 审核。协调者核对了 7d8b346（E-0025 已审核的源码）到 054a54a 的差异：分段代码只调用 rb_train.adapter_config（只传 RB1-01 或 RB1-02）、LAYERS、load_data，rb1_artifacts.read、reference、finite_tree、verify_lr_lock 与 validate_formal_run（只传 RB1-07），rb1_analysis.measured_cost，rb_history.donor_indices。对这些调用，函数行为没有变：adapter_config 对 RB1-01/02 仍是同一个 rank 32 配置；validate_formal_run 对 RB1 arm 仍钉在 E-0021 的训练源码与契约；run_history 的改动只在 trace_reads 下执行，而分段代码不设 intervention、capture_history 或 trace_reads。分段代码不导入 rb1_intervene 与 rb_read_diagnostics；bypass_model、bypass_core、rb_data、rb1_rules、v1_run、v1_data、v1_lora 自 7d8b346 起没有改动。ATT-0305-1（RES-0282）在 054a54a 上 354/354 项检查通过。这些 attempt 按已覆盖处理；054a54a 之后 src/ 的任何改动都使这条例外失效，需要新的审核。

- D-0059 route:continue — 用户 2026-11-02 在协调者会话中要求：'RB1-09 的方法里, 我们修改为一开始不计算 Q_t 等等, 而是直接用这一层的输入 X dot A_q, X dot A_k, X dot A_v 怎么样'。这满足 D-0056 登记的重开条件之一（用户要求在普通设置下检验其他 tap），并优先于 D-0045 对 RB1 阶段的暂停与 E-0026 规则 8 的' 普通设置下不再换 tap'（那是协调者依据记录作出的选择）。代码里已有 direct_hidden tap：特征取该层 input_layernorm 的输出 X，q、k、v 都从 X 投影（A_q 由 2048×32 变为 1024×32，参数从 925,696 降到 794,624）。取归一化后的 X 而不是原始残差流，是为了避开原始残差的尺度问题。新建 H-0021（由 H-0016 派生）与契约 E-0028：在普通 RB1 设置下做 2×2（tap：qknorm_pre_rope 或 X；历史：KernelMatrix S1 或同参数 T0），融合都用 C_up，seed 0，RB1 的初始化规则、顺序、13,115 步，LR 都用 1e-3；新训练三个 arm（X 的 KernelMatrix、X 的 T0、原 tap 的 T0），RB1-09、RB1-07 LoRA 与 Base 沿用 E-0021 的记录。原 tap 的 C_up T0 补上 D-0041 指出的缺口（C_up 自己的同参数 T0 没有测）。预期：普通设置下 RB1 各组相差都在约 0.5 pp 以内，tap 改动未必能补上与 LoRA 的 1.45 pp 差距；E-0012 中直接隐藏状态在分隔符处解码尾实体的准确率高于 qknorm 特征（99.6% 对 92.9%），说明 X 含的信息不少于 qknorm 特征，但那是 M 线的探针，不直接推广。预算 <= 1.3 node·h，判定规则在运行前锁定。

- D-0060 route:modify — E-0028 规则 1(a)(b)(g) 的解释（在任何正式结果之前，按 RV-0087 finding 1 与 D-0018/D-0019/D-0050）：规则 1 的目的是查实现错误，不同 MIG 档（1g/2g）之间的 BF16 差别按用户的 D-0018/D-0019 不算错误，D-0050 已采用同分配参考、否决跨档容差与控档。因此：(a) 第 0 步预测对 Base 的门槛，在硬件与已接受的 2g 参考相同时照旧比对固定的 Base 记录；硬件不同时在同一分配里重评 Base 并对它设门槛，跨作业差别只作描述；(b) iv_off 以同分配的 Base 为门槛，与固定 Base 的比对在硬件不同时只作描述；(g) 硬件与 E-0021 参考（ATT-0247-1）不同时，在同一作业里用已接受的 7bf091d 源码重评 RB1-09 的最终 checkpoint，新旧源码逐条一致为门槛，与 E-0021 记录的差别只作描述；硬件相同时照旧逐条比对 E-0021 记录；calibration 评估放在任何门槛报错之前，不因门槛失败丢掉；normal_same_as_final 不是封存的规则 1 项，改为描述（沿用 rb1_analysis.normal_training_agreement）。两边都是 2g 而预测不同仍算失败。不放宽容差，不限制切片。需按 RV-0087 列出的单元测试验证，修复后向同一审核者做一次 re-check。

- D-0061 route:continue — E-0028 正式 run 在 0f22cd6 上的审核覆盖（MSG-0857，正式提交之

前）：registration 报告 4 个路径 stale。协调者核对：(1) src/bypass_model.py 在 7d8b346 与 0f22cd6 之间 git diff 为空，与 RV-0078、RV-0079（均 pass）审过的版本逐字节相同，RV-0088 也看过；所有 E-0028 registration 加 --review RV-0078,RV-0079 即覆盖。(2) src/rb_sink_read.py 只被 rb_sink_batchcheck.py 与它自己的测试导入，不在 E-0028 的训练、评估、干预或分析路径上；src/test_rb_sink_read.py、src/test_rb1_artifacts.py 是测试文件，不在运行路径上，0f22cd6 上选定的 112 项测试通过。因此批准按 0f22cd6 放行全部 E-0028 正式 run，stale 记录保留，本决定作为理由；已登记的 ATT-0321-1 同样适用。

- D-0062 route:pause->inconclusive — 按 E-0027 的预登记规则与结论审核 RV-0089（pass，0 条发现），把 H-0020@1 记为 inconclusive（screening：seed 0、1、2，分段协议，BoolQ 任务层面，r128，dev 每任务 1,000 条，dev 既用于选择也用于判定，确认集未开封）。三个 seed 等权的 G = 88/3000 = +2.933 pp，低于 +3 pp 的支持门槛；两个新 seed 的 gain 为 +2.6 与 +1.8 pp，都为正；swap 均值 W = +6.567 pp，不低于 G/2；Keep 对同 seed 分段 LoRA 的均值 L = +2.067 pp，不低于 +1 pp（EV-0145、EV-0146）。三个 challenge 条件都不成立（EV-0147）。Keep 的 BoolQ 准确率（65.9%、65.7%、65.3%）与 swap 降幅（6.5、6.2、7.0 pp）在三个 seed 上接近；gain 变小主要因为 r128 T0 对照在 seed 1、2 学成（61.2% 升到 63.1% 与 63.5%，EV-0149）。这些只描述三次运行，不构成总体层面的复现，也不证明机制。按规则 6 不再加 seed、加宽、换 tap 或加循环（EV-0148），这条路线暂停；H-0019 维持 inconclusive（EV-0151）。两个新 seed 的实现检查全部通过（EV-0143）；正式 attempt 的代码由 RV-0085、RV-0086 覆盖，stale 路径按 D-0058 处理。E-0027 用了 2.804 node·h（上限 3.2）。(reopen if: 只在新的封存契约改变侧支算子或比较方式时重开，不再对 E-0025/E-0027 的配置加 seed、加宽、换 tap 或加循环。例如 RB1-09 改进线（E-0028、E-0029）中某个算子在普通设置下比 RB1-07 高至少 1 pp 并通过复现后，在分段协议下用该算子重测；或用户另行要求。)

- D-0063 route:pause — E-0025 之后，分段线唯一登记的后续是 H-0020 的 BoolQ 三 seed 复现（E-0027）。它按规则 6 记为 inconclusive（D-0062，结论审核 RV-0089 pass），E-0027 规则 9 写明 H-0019 维持 inconclusive（EV-0151），并且不再加 seed、加宽、换 tap 或加循环。分段线没有其他登记的工作，所以暂停 H-0019，证据状态不变（inconclusive，screening）。这不是对分段线的否定：主任务 PIQA 的 gain 为正但低于 +3 pp，BoolQ 的三 seed 均值为 +2.933 pp，swap 在三个 seed 上都去掉 6 pp 以上，说明跨段状态被模型使用，但收益没有达到预先登记的门槛。(reopen if: 只在新的封存契约改变侧支算子或比较方式时重开，不再对 E-0025/E-0027 的配置加 seed、加宽、换 tap 或加循环。例如 RB1-09 改进线（E-0028、E-0029）中某个算子在普通设置下比 RB1-07 高至少 1 pp 并通过复现后，在分段协议下用该算子重测；或用户另行要求。)

- D-0064 route:continue — E-0029 在 f46a13d 上的审核覆盖（MSG-0895，LR 校准与正式提交之前）：registration 报告 src/test_rb1_artifacts.py、src/test_rb_read_diagnostics.py 相对 RV-0064、RV-0069 stale。协调者核对：两者都是测试文件；E-0029 的训练、评估、干预与分析模块都不导入它们（rb_improve*.py 没有 test_ 模块或 rb1_check 的导入），只有独立的 rb1_check.py 把它们列入测试清单；E-0029 作业脚本 research/notes/T-0032-run.pbs 的 pytest 清单含 test_rb1_artifacts.py，不含 test_rb_read_diagnostics.py，ATT-0346-1 在 f46a13d 上 124 项测试通过。E-0029 的核心范围由 RV-0090、RV-0092（round 结束，pass）覆盖。因此按 D-0061 的先例，不为这两个测试文件另做代码审核：E-0029 的 LR 校准与之后的正式 run 按 f46a13d 登记时加 --review RV-0090,RV-0092，stale 记录保留，本决定作为理由。正式 arm 是否全部放行，另由 RV-0091 一轮的结论与随后的决定处理。

- D-0065 route:continue — E-0028 规则 10 已触发（EV-0162）。本决定是协调者在现有用户授权下作出的有界例外，是一项路线决定，不是规则 10 预先登记的条款，也不是它的含义

(RV-0091 finding 1)。内容：E-0029@1 (DOC-0310@1) 按封存原样运行，包括 LoRA LR 的校准与锁定、八个训练 arm (G-T、G-QN、G-N、Q-N、P-T、P-N、L-56、L-48)、它们的干预与锁定分析，在 3.5 node·h 上限内 (保守预计 2.47)。其中与 tap 有关的 arm：Q-N (Q/K 取 input_layernorm 的输出 N，value 取 v_proj 输出；H-0026) 与它的 I-G 版本 G-QN 是新来源的比较；G-N 与 P-N 只改 X-01 所用 N tap 上的初始化；L-48 是以 X-01 为参照的 up-only LoRA 对照。G-T、P-T 与 L-56 用原 tap 或 LoRA。理由：E-0029 在 2026-11-02 09:22:47 UTC 封存，早于 E-0028 的任何正式准确率结果；它实现的是用户提供的 RB1-09 改进方案中选出的 N 输入与初始化实验。方案 §13.1 告诫不要只凭随机初始化的一格就否定字面 D-QK，§13.4 把停止当前方法放在 T 与 D 的所有初始化都输给匹配 LoRA 之后；E-0028 没有检验任何初始化。E-0029 有意改编了方案：Q-N、G-QN 用 N，不检验方案中字面的残差流输入 D-QK，也不覆盖方案计划的全部初始化组合。方案 §4.1 只在给定条件下联系二者的函数族，并不说明初始化或优化相同。这些省去的变体仍未检验；把它们排除在外是协调者的范围选择，不是证据覆盖或否定了它们 (RV-0093)。描述上，规则 10 的触发余量是 0.05 pp，即一条 dev 预测；这只作描述，不替代封存的门槛。边界：在 E-0029@1 之外，规则 10 照常有效，不再开新的普通设置 tap 或来源契约 (包括方案 K01、K02 的来源与归一化分支，以及字面残差流 X 的变体)。对 E-0029 中 tap arm 结果的任何后续，包括它的规则在新侧支 arm 比 RB1-07 高至少 1 pp 时要求的两个新 seed 复现，都需要一个明确处理规则 10 的新决定，并有自己的结论审核。H-0026 的证据状态只按 E-0029 自己的规则判定，E-0028 不给它任何状态。依据：EV-0162，E-0028@1 (DOC-0307@1) 规则 10，E-0029@1 (DOC-0310@1)，结论审核 RV-0091 与 RV-0093。研究者在协调者确认之前不提交八个正式 arm (MSG-0888)；本决定即为这一确认。

- D-0066 route:pause->inconclusive — 按 E-0028@1 的预登记规则与结论审核 RV-0091、RV-0093，把 H-0021@1 记为 inconclusive 并暂停 (screening：seed 0，RB1 普通设置，C_up + KernelMatrix S1 r32，LR 1e-3，dev 每任务 1,000 条，dev 既用于选择也用于判定，确认集未开封)。规则 3：d_tap = X-01 − RB1-09 = 78.15% − 77.50% = +0.65 pp (13/2000，描述性 95% 区间 [−0.25, +1.60])，在 0 与 +1 之间，只作描述 (EV-0156)。规则 4：同 tap 的历史收益 X-01 − X-02 = −0.15 pp、RB1-09 − X-03 = −0.65 pp，都没有达到 +1 pp，虽然 iv_swap 分别使宏平均下降 2.00 与 1.95 pp；不请求重开 H-0014 (EV-0157)。规则 7：对 LoRA r7 (RB1-07，78.95%)，X-01 −0.80、X(η 1) −1.05、原 tap −1.45 pp，没有触发 (EV-0159)。规则 10 的封存条件与触发：X(η*_X) = 77.90% < RB1-07 − 1 = 77.95%，按点估计触发 (EV-0162)；选中的 X 减 LoRA 为 −1.05 pp，区间 [−2.15, +0.10]，这是停止条件，不是确认的劣势。规则 10 的动作照原文执行：普通设置下不再做 tap 变体。暂停这条路线与把 H-0021 记为 challenged 不同。已封存的 E-0029 照常运行，是 D-0065 记录的有界协调者例外，不属于规则 10 的含义。实现检查全部通过 (规则 1，EV-0154)；正式 run 的审核覆盖见 RV-0087、RV-0088 与 D-0060、D-0061。E-0028 共用 4.025 node·h (上限 5.5)。(reopen if: 普通设置下按 E-0028 规则 10 不再做新的 tap 变体。只在以下情况重开：E-0029 (D-0065 的有界例外) 中 N tap 上的某个 arm 比 RB1-07 高至少 1 pp，按它的规则需要两个新 seed 复现；分段协议的新契约需要选择 tap；或用户另行要求。重开需要一个明确处理规则 10 的新决定与结论审核。)

- D-0067 route:pause->challenged — 按 E-0028@1 的预登记规则与结论审核 RV-0091、RV-0093，把 H-0022@2 记为 challenged 并暂停 (screening：seed 0，RB1 普通设置，C_up + KernelMatrix S1 r32，LR 固定 1e-3，dev 每任务 1,000 条，确认集未开封)。η* 只按 calibration 准确率选，在汇总任何 Part B dev 结果之前锁定 (ATT-0343-1，EV-0153)，两个 tap 都不需要端点外扩：原 tap 的 η* = 0.25，d_η = 0 (按定义)；X tap 的 η* = 1，d_η = 77.90% − 78.15% = −0.25 pp (描述性 95% 区间 [−1.15, +0.65])。两个 tap 都不高于 0，规则 6 给出 challenges (EV-0158)，不需要两个新 seed 的复现。描述上，dev 宏平均在原 tap 的 η 候选间为 76.90% 至 77.55% (η = 0.25 的 RB1-09 为 77.50%)，在 X tap 的候

选间为 77.45% 至 78.15%（$\eta = 0.25$ 的 X-01 最高），各候选之差都在 1 pp 以内。范围：只限这个 η 网格（1/16 至 2）、一个 seed、固定 LR，不含 η 选择的不确定性；不是说 η 永远不重要。之后的 C_up arm 沿用 $\eta = 0.25$。(reopen if: 只在新的封存契约改变侧支算子、宽度或信息访问设置，使 $\eta = 0.25$ 不再是合适的参照时，或多 seed 结果显示 η 的效应达到 1 pp 时重开；不再对 E-0028 的配置单独搜索 η。) [conclusion review RV-0091 issues, medium open (same_family_unverified), RV-0093 issues, medium open, approved by the coordinator (same_family_unverified)]

6 Conclusion

在锁定的配置与预算内，信息全部留在 backbone 时，低维侧分支没有显示出超过参数相近的 LoRA 的实用价值。没有侧支历史的 tokenwise gate/up 接口在 V1 与 V5 中都没有优于加法写回或参数相近的 LoRA，V5 的确认比较按封存规则记为 challenged，这条路线停止；带因果侧支历史的残差旁路在 RB1 中比近预算 LoRA 低 1.85 pp，也不比同参数 T0 好（H-0013、H-0014 记为 challenged，screening），RB1 阶段暂停。只保留低维记忆的单跳读取在 V2 配方下失败；改成每条事实单独编码写入、并先在 E=1 上训练后，三个 seed 都达到门槛。这是 M 线保留的正结果，但它依赖声明的结构化支持输入，学到的寻址也没有迁移到 T2 句式；在它之上的多次读取停在 A3（H-0005 inconclusive），M 线暂停。两条线都没有迭代查询的证据。把侧支加宽到 r128 也没有改变普通设置下的结论（H-0018 challenged，screening）。在 backbone 看不到第 1 段、只有四层侧支状态能跨段的分段设置下，主任务 PIQA 的收益为正但低于 3 pp，H-0019 记为 inconclusive；BoolQ 的 r128 收益在三个 seed 上平均为 +2.93 pp，略低于 +3 pp 门槛，H-0020 也记为 inconclusive，分段线按预登记规则暂停。用户提出的 RB1-09 改进中，换特征来源与搜索 η 都没有达到 1 pp 门槛（E-0028：H-0021 inconclusive，H-0022 challenged），其余方向（E-0029）正在筛选。截至 2026-11-02 23:30，作业账本记录的已结束作业用量约为 27.8 node·h（上限 200）。

A Records

- records at data_version 4589; plan DOC-0001@1 (docs/plan.md); constraints docs/constraints.md
- experiments: E-0001@1 (DOC-0003@1), E-0002@1 (DOC-0019@1), E-0003@2 (DOC-0040@2), E-0004@1 (DOC-0047@1), E-0005@1 (DOC-0048@1), E-0006@1 (DOC-0053@1), E-0007@2 (DOC-0063@2), E-0008@1 (DOC-0086@1), E-0009@1 (DOC-0087@1), E-0010@2 (DOC-0083@2), E-0011@2 (DOC-0097@2), E-0012@1 (DOC-0117@1), E-0013@3 (DOC-0128@3), E-0014@1 (DOC-0135@1), E-0015@4 (DOC-0157@4), E-0016@1 (DOC-0160@1), E-0017@1 (DOC-0180@1), E-0018@1 (DOC-0202@1), E-0019@1 (DOC-0203@1), E-0020@1 (DOC-0231@1), E-0021@1 (DOC-0235@1), E-0022@2 (DOC-0211@2), E-0023@1 (DOC-0239@1), E-0024@1 (DOC-0272@1), E-0025@1 (DOC-0273@1), E-0026@1 (DOC-0285@1), E-0027@1 (DOC-0302@1), E-0028@1 (DOC-0307@1), E-0029@1 (DOC-0310@1)
- attempts: 368 (21 ended/cancelled, 27 ended/failed, 317 ended/success, 3 queued/unknown)
- reviews and advice: AD-0001 answered, AD-0002 answered, AD-0003 answered, AD-0004 answered, AD-0005 answered, AD-0006 answered, RV-0001 answered issues, RV-0002 answered pass, RV-0003 answered issues, RV-0004 answered issues, RV-0005 answered pass, RV-0006 answered pass, RV-0007 answered issues, RV-0008 answered pass, RV-0009 answered pass, RV-0010 answered pass, RV-0011 answered issues, RV-0012 answered pass, RV-0013 answered pass, RV-0014 answered pass, RV-0015 answered pass, RV-0016 answered issues, RV-0017 answered issues, RV-0018 answered pass, RV-0019 answered pass, RV-0020 answered issues,

RV-0021 answered pass, RV-0022 answered pass, RV-0023 answered pass, RV-0024 answered pass, RV-0025 answered issues, RV-0026 answered pass, RV-0027 answered pass, RV-0028 answered issues, RV-0029 answered issues, RV-0030 answered issues, RV-0031 answered issues, RV-0032 answered issues, RV-0033 answered pass, RV-0034 answered issues, RV-0035 answered pass, RV-0036 answered issues, RV-0037 answered issues, RV-0038 answered pass, RV-0039 answered pass, RV-0040 answered blocking, RV-0041 answered pass, RV-0042 answered blocking, RV-0043 answered pass, RV-0044 answered issues, RV-0045 answered pass, RV-0046 answered issues, RV-0047 answered pass, RV-0048 answered pass, RV-0049 answered issues, RV-0050 answered issues, RV-0051 answered pass, RV-0052 answered issues, RV-0053 answered pass, RV-0054 answered pass, RV-0055 answered issues, RV-0056 answered pass, RV-0057 answered pass, RV-0058 answered issues, RV-0059 answered pass, RV-0060 answered pass, RV-0061 answered issues, RV-0062 answered pass, RV-0063 answered pass, RV-0064 answered pass, RV-0065 answered issues, RV-0066 answered issues, RV-0067 answered pass, RV-0068 answered pass, RV-0069 answered pass, RV-0070 answered issues, RV-0071 answered issues, RV-0072 answered pass, RV-0073 answered issues, RV-0074 answered pass, RV-0075 answered pass, RV-0076 answered issues, RV-0077 answered issues, RV-0078 answered pass, RV-0079 answered pass, RV-0080 answered issues, RV-0081 answered issues, RV-0082 answered pass, RV-0083 answered pass, RV-0084 answered pass, RV-0085 answered pass, RV-0086 answered pass, RV-0087 answered issues, RV-0088 answered pass, RV-0089 answered pass, RV-0090 answered pass, RV-0091 answered issues, RV-0092 answered pass, RV-0093 answered issues, RV-0094 answered pass

- resource use: 0.00583333 mig_instance_hours compute on GH200-MIG-2g.24gb (measured); 5.81063 node_h compute on GH200 MIG 2g.24gb (measured); 0.000138889 node_h compute on GH200 MIG 2g.24gb (guard verified) (measured); 6.94444e-05 node_h compute on GH200 MIG allocation; profile not measured (artifact tabulation only) (measured); 0.00263889 node_h compute on GH200 MIG allocation;profile metadata only (measured); 0.000694444 node_h compute on GH200 MIG2g.24gb (measured); 0.119236 node_h compute on GH200 MIG2g.24gb verified timing guard (measured); 0.01125 node_h compute on GH200 MIG2g.24gb;record-only profile metadata (measured); 0.502083 node_h compute on GH200 MIG; allocated profile recorded separately as metadata (measured); 0.169931 node_h compute on GH200 MIG; profile metadata only (measured); 6.94444e-05 node_h compute on Miyabi-G GH200 MIG allocation;artifact-only CPU tabulation;profile not inspected (measured); 84.1403 mig_instance_hours gpu_mig_instance on GH200 MIG 2g.24gb (measured); 0.012778 mig_instance_hours gpu_mig_instance on NVIDIA GH200 120GB MIG 1g.24gb (runtime reported) (measured); 0.431665 mig_instance_hours gpu_mig_instance on NVIDIA GH200 120GB MIG 2g.24gb (measured); 1.2221e+06 input_tokens training on - (measured)