Contents

VQ-VAE with PixelCNN Prior for Synthetic Prostate MRI (COMP3710 Project 2.4) 2
Abstract . . . 2
Contents . . . 2
Key Contributions . . . 3
Quick Start . . . 3
1. Problem and description . . . 3
2. How the algorithm works . . . 3
2.1 VQ-VAE Architecture . . . 3
2.2 VQ-VAE-2 Extension . . . 5
2.3 PixelCNN Prior . . . 5
2.4 Transformer Prior and Long-Range Context . . . 5
2.5 DCGAN Baseline . . . 6
3. Feasibility review . . . 7
4. Data . . . 7
4.1 Source and layout . . . 7
4.2 Audit findings . . . 7
4.3 Preprocessing . . . 7
4.4 Splits . . . 8
5. Experiments . . . 8
5.1 Baseline VQ-VAE and the codebook collapse . . . 8
5.2 Longer training and reconstruction loss . . . 8
5.3 Codebook and downsampling variants . . . 8
5.4 Prior variants . . . 8
5.5 DCGAN baseline . . . 8
5.6 What did not work . . . 9
6. Results . . . 9
6.1 Quantitative results . . . 9
6.2 Qualitative results . . . 10
6.3 Memorisation screen . . . 10
6.4 Failure autopsies . . . 10
6.5 Generation Failure Investigation . . . 14
6.5.1 Initial Observation: Statistical Mismatch . . . 14
6.5.2 Decoder Isolation Experiment . . . 15
6.5.3 Root Cause: PixelCNN Blind Spot . . . 15
6.5.4 Attempted Solutions . . . 15
6.5.5 Why This Matters . . . 17
6.5.6 Training Curves . . . 17
6.6 Transformer Generation Quality Analysis . . . 20
6.7 Summary: What Worked and What Didn't . . . 24
7. Limitations and Future Work . . . 24
8. Recommendation for the project manager . . . 25
Phase 1: Research evaluation of reconstruction . . . 25
Phase 2: Validation of synthetic cohorts . . . 25
Phase 3: Alternative baselines . . . 25
Cost-Benefit Analysis . . . 25
Critical Success Factor . . . 26
Next Steps . . . 26
9. Dependencies and reproducibility . . . 26
10. Artificial Intelligence Usage Disclosure . . . 26
11. References . . . 27
Appendix A: Additional Experimental Figures . . . 27
A.1 Experiment Comparison Overview . . . 27
A.2 Receptive Field Visualization . . . 27
A.3 Transformer Sample Grid . . . 28

A.4 Distribution Analysis (Experiment 6) . . . 28
Appendix B: Complete Feasibility Review (As Submitted) . . . 28
COMP3710 Project 2.4: Feasibility Review . . . 28
1. User Need, Scope & Acceptance Criteria . . . 28
2. Model Choice & Course Concepts . . . 31
3. Preliminary Feasibility Evidence . . . 31
4. Experimental Plan & Next Steps . . . 31
5. Risks, Budget & Fallback . . . 32
References . . . 32

VQ-VAE with PixelCNN Prior for Synthetic Prostate MRI (COMP3710 Project 2.4)

Student: Ben Evans (48828514) — Hard difficulty — PyTorch

Final submission for COMP3710 Project 2.4 (Oct 30, 2026).

Abstract

This project investigates synthetic prostate MRI generation using vector-quantised autoencoders and autoregressive priors, with a DCGAN as a baseline. Patient-disjoint evaluation separates reconstruction quality, generation fidelity, diversity and memorisation risk. The hierarchical VQ-VAE-2 achieved a mean reconstruction SSIM of approximately 0.937, whereas samples from the initial PixelCNN prior did not reproduce coherent anatomy. Decoder-isolation and alternative-prior experiments suggested that modelling the fine-level codes was an important bottleneck.

A causal Transformer prior produced samples with recognizable anatomical structure in the author's visual review, although their mean intensity was 0.159 compared with 0.180 for the training reference, and their fraction of bright pixels remained approximately half that of the reference. The results illustrate the distinction between successful reconstruction and plausible unconditional generation, while highlighting the need for independent clinical validation and more comprehensive privacy assessment.

Opening visual summary: the first two saved, uncurated samples from the Experiment 6 Transformer prior at temperature 1.0. Both use the same display range, [0, 1]. This illustration is not a clinical assessment; the full sample grid and distribution analysis appear in Sections 6.5.4 and 6.6.

Contents

Section	Topic
Abstract and key contributions	Research question and principal findings
Quick Start	Running the supplied baseline code
1. Problem and description	Clinical motivation and scope
2. How the algorithm works	VQ-VAE, priors and DCGAN
3. Feasibility review	Initial plan and acceptance criteria
4. Data	Dataset, preprocessing and patient-disjoint splits
5. Experiments	Baselines, variants and selection
6. Results	Quantitative and qualitative results
6.3. Memorisation screen	Nearest-neighbour screening and its limitations
6.4. Failure autopsies	Case-based analysis
6.5. Generation failure investigation	Isolation experiments and alternative priors
6.5.6. Training curves	Recorded VQ-VAE-2 and fine-prior histories
6.6. Generation quality analysis	Diversity and distribution differences
6.7. Summary	Comparison of approaches
7. Limitations and future work	Interpretation, uncertainty and further validation
8. Recommendation	Practical implications and deployment considerations

Section	Topic
9. Dependencies and reproducibility	Environment and experimental setup
10. Artificial intelligence usage disclosure	Scope of AI assistance
11. References	Sources
Appendix A and Appendix B	Supplementary figures and original feasibility review

Key Contributions

The project combines a patient-disjoint reconstruction evaluation with a systematic investigation of the gap between reconstruction and generation. The selected single-level VQ-VAE achieved test SSIM of 0.9425, while the hierarchical model achieved approximately 0.937. Decoder-isolation experiments indicated that fine-level codes carried much of the observable anatomical structure, motivating comparisons between the original PixelCNN and alternative priors.

The resulting analysis reports both strengths and limitations rather than relying on a single score. The Transformer samples displayed recognizable structure in visual review, but remained darker than the training reference and had a lower bright-pixel fraction. Pairwise sample distances and nearest-neighbour checks provide preliminary diversity and memorisation screens; neither establishes a privacy guarantee or clinical validity.

Quick Start

The supplied command-line scripts train and evaluate the single-level VQ-VAE and its prior or the DCGAN baseline. Set `DATA_ROOT` to the local `keras_slices_data` directory before running from this project directory:

```
python train.py --model vqvae --data-root "$DATA_ROOT" --epochs 100 --seed 0 --out checkpoints/vqvae
python train.py --model prior --prior-type pixelcnn --data-root "$DATA_ROOT" --vqvae-checkpoint checkpoints
python predict.py --data-root "$DATA_ROOT" --vqvae checkpoints/vqvae/vqvae_best.pt --prior checkpoints/pri
```

The scripts also expose `--prior-type transformer` for the single-level prior. The hierarchical VQ-VAE-2 experiments described in Section 6.5 used separate experimental scripts; the commands above do not reproduce that pipeline. `dataset.py` loads the data, `modules.py` defines the models, `train.py` trains them, `predict.py` performs generation and evaluation, and `runtime.py` provides shared checkpoint and runtime utilities. The HipMRI dataset and model checkpoints are not included in the repository. The evaluation requires the dependencies described in Section 9; a CUDA-capable GPU is recommended.

1. Problem and description

Medical imaging research is limited by patient privacy rules (HIPAA, GDPR) and by how few clinical scans are available. Synthetic scans could help, but a generator that memorises training scans leaks patient data, and one that produces anatomically impossible structures would mislead downstream models. This project builds a VQ-VAE with a PixelCNN prior (van den Oord et al., 2017) that generates synthetic 2D prostate MRI slices from the HipMRI study, and compares it with a DCGAN baseline (Radford et al., 2016). The aim is to investigate the trade-off between fidelity, memorisation and privacy.

2. How the algorithm works

2.1 VQ-VAE Architecture

A VQ-VAE (Vector Quantised Variational AutoEncoder) compresses images into discrete codes and reconstructs them. The architecture has three main components:

Encoder: Maps a 256×128 grayscale MRI slice through two stride-2 convolutions (4×4 kernels) to a 64×32 spatial grid, followed by two residual blocks. Each position in the grid produces a 64-dimensional continuous vector.

Vector Quantisation: Each continuous vector is replaced by its nearest entry from a learned codebook of 512 vectors (each 64-dimensional). This discretisation creates a bottleneck: the decoder must reconstruct the full image from




Figure 1: Two generated MRI slices

only 64×32 = 2,048 discrete code indices. The quantisation uses a straight-through estimator to pass gradients: the forward pass snaps to the nearest code, but the backward pass treats it as an identity function.

Decoder: Mirrors the encoder in reverse: two residual blocks, then two stride-2 transposed convolutions (4×4 kernels) to upsample from 64×32 back to 256×128. The final layer outputs a single-channel grayscale image.

The loss function combines three terms: - Reconstruction loss (MSE or L1): measures pixel-level fidelity - Codebook loss: pulls codebook entries toward the encoder outputs - Commitment loss (β=0.25): encourages the encoder to commit to codes

2.2 VQ-VAE-2 Extension

After initial experiments showed that a single 64×32 code grid was insufficient for high-quality reconstruction, the architecture was extended to VQ-VAE-2 (Razavi et al., 2019), which uses a two-level hierarchy:

Coarse level (16×8 grid, 128 codes): Captures global structure and layout. The encoder downsamples by 16× (four stride-2 layers) to produce a 16×8 grid, quantised with a 128-entry codebook.

Fine level (64×32 grid, 2,048 codes): Captures local texture and detail. The encoder downsamples by 4× (two stride-2 layers) to produce a 64×32 grid, quantised with a separate 2,048-entry codebook. The fine encoder is conditioned on the upsampled coarse codes.

Decoder: Takes both coarse and fine codes as input. The coarse codes are upsampled and concatenated with the fine codes before the decoder processes them. This hierarchical structure allows the model to represent both global anatomy (coarse) and fine texture (fine) separately.

2.3 PixelCNN Prior

A VQ-VAE alone cannot generate new images—it only compresses and reconstructs. To sample, we need a prior that models which code sequences are plausible.

PixelCNN (van den Oord et al., 2016) is an autoregressive model that predicts each code based on all previous codes in raster order (left-to-right, top-to-bottom). It uses masked convolutions to enforce causality: when predicting position (i,j), the model can only see positions (i',j') where i' < i, or i' = i and j' < j.

The architecture uses: - Type-A mask (7×7) for the first layer: sees only strictly previous positions - Type-B masks (3×3) for residual blocks: sees previous positions plus current position - Four residual blocks with two masked convolutions each - Width 128, learned embedding dimension 32

Blind spot problem: The masked convolution has a limited receptive field. With 3×3 kernels and 4 residual blocks, each position can only see about 19 rows above it in a 64-row grid. This becomes critical for generation quality (see section 6.5).

Sampling: To generate, start with an empty 64×32 grid. For each position in raster order, the PixelCNN predicts a probability distribution over 512 codes. Sample from this distribution (with optional temperature scaling), fill in that position, and continue. After 2,048 sequential predictions, pass the completed code grid through the VQ-VAE decoder to get an image.

2.4 Transformer Prior and Long-Range Context

After discovering the PixelCNN blind spot problem (section 6.5.3), we replaced the fine prior with a causal Transformer that uses full self-attention over all 2,048 code positions.

The 64×32 fine-code grid is flattened into 2,048 tokens in raster order. The prior uses learned positional embeddings, six Transformer layers, eight attention heads and an embedding dimension of 256. Causal masking permits each position to attend to preceding positions only, and the output at each position is a probability distribution over code indices.

Key difference from PixelCNN:

Aspect	PixelCNN	Transformer
Receptive field	~19 rows (limited by kernel stack)	All previous positions
Attention mechanism	None (local convolutions)	Full self-attention
Long-range dependencies	Cannot model	Fully captured
Computational cost	O(n)	O(n²)

For example, the tested PixelCNN at row 60 and column 15 has limited access to earlier rows and cannot directly use information from row 10. The causal Transformer at the same location can attend to the 1,935 preceding positions in raster order. Access to this context is a plausible explanation for the observed improvement, although other architectural and training differences also affect the comparison.

Training: 40 epochs, batch size 32, learning rate 3e-4, AdamW optimizer. Validation NLL converged to 3.84 (vs PixelCNN's 4.05).

Sampling: Same as PixelCNN—sequential generation in raster order—but each position now has full context of all previous codes, enabling anatomically coherent generation.

2.5 DCGAN Baseline

The DCGAN (Deep Convolutional GAN) baseline maps 100-dimensional Gaussian noise directly to 256×128 images through a generator network, trained adversarially against a discriminator. The generator uses: - Nearest-neighbor upsampling followed by convolution (to avoid checkerboard artifacts) - Batch normalization and ReLU activations - Tanh output activation

The discriminator uses: - Strided convolutions for downsampling - Spectral normalization (Miyato et al., 2018) for training stability - LeakyReLU activations

Training alternates between updating the discriminator (to distinguish real from fake) and the generator (to fool the discriminator). Real labels are smoothed to 0.9 to reduce discriminator overconfidence.




Figure 2: VQ-VAE-2 Architecture

Figure 1: VQ-VAE-2 architecture showing hierarchical coarse (16×8) and fine (64×32) quantization levels, with the Transformer prior replacing PixelCNN for anatomically coherent generation.

3. Feasibility review

Summary of the one-page feasibility review written before the experiments (source: *feasibility_review.tex*).

User need. Synthetic scans could support research when real data is limited or cannot be shared. Generated images must keep anatomical structure without copying training scans.

Acceptance criteria (as planned). - Reconstruction: mean SSIM ≥ 0.6 between held-out slices and their reconstructions. - Generation: 500 samples per unconditional model, compared with held-out real slices by Kernel Inception Distance (KID). - Diversity: codebook use and distinct entries; uncurated grids. - Memorisation: exact duplicate checks and nearest-neighbour screening against held-out real-to-training similarities. This is a screen, not a privacy guarantee. - Compute: 3 hours of training, and 500 samples within 15 minutes.

Preliminary evidence. A 5-epoch smoke test gave held-out SSIM 0.624 but used only 13 of 512 codes (perplexity 6.8). A PixelCNN on those codes cut cross-entropy from 6.24 to 0.63. A 3-epoch DCGAN produced banded, near-identical samples (pixel standard deviation 0.067 against 0.130 for real slices). The pipeline fitted the compute budget; sample quality was the open risk.

Planned mitigations. Codebook tuning (initialisation, dead-code handling, size), a commitment-weight sweep, a reconstruction-loss comparison, and resize-convolution upsampling with spectral normalisation for the DCGAN.

4. Data

4.1 Source and layout

The HipMRI prostate study provides 2D slices in `keras_slices_data`, split into train, validation and test folders. The dataset is not redistributed in this repository.

4.2 Audit findings

Property	Finding	Consequence
Slices	12,660 in total; 11,460 train (31 patients, 191 scans), 660 validation (4 patients), 540 test (3 patients)	Splits are about 90.5 / 5.2 / 4.3% by slice
Patient overlap	None between splits	Patient-disjoint evaluation
Size	256×128 float32, except one scan (patient 019, week 1) at 256×144	That scan is centre-cropped to 256×128
Intensity	0–1212; median slice maximum 397	Per-slice normalisation is required
Labels	Six classes; prostate (label 5) about 0.4% of pixels	Segmentation is not used by these models; the class imbalance is noted for future work
Load speed	about 230 slices/s; about 1.7 GB in RAM	Full set kept in memory

The audit was performed with a separate exploration script; its summary statistics are the source of the table above. The exploration figures are not included in this repository, which contains only the model code and the figures referenced in this report.

4.3 Preprocessing

Each slice is divided by its own maximum to map it to [0, 1]. Raw intensity scales differ between scans, so a global scale would vary with the scan. The single 256×144 scan is centre-cropped to 256×128 so every input has the same shape. The grayscale value is kept as a single channel.

4.4 Splits

The splits come from the dataset provider and are kept patient-disjoint. Every training script re-checks this at startup, because one leaked patient would invalidate the privacy claims. The validation split is used for all model and hyperparameter selection. The test split is used once, for the final reported numbers, and was not used to choose settings.

5. Experiments

Experiments were run in order. The variants below were compared on validation metrics; test numbers are reported but were not used to choose between them.

5.1 Baseline VQ-VAE and the codebook collapse

The first model followed van den Oord et al. (2017): two 4×4 stride-2 convolutions, two residual blocks, a 512-entry codebook of dimension 64, $\beta = 0.25$, Adam at 2×10^{-4}, and width 128. In the 5-epoch smoke test it reached validation SSIM 0.624, but only 13 codes were used (perplexity 6.8). This codebook collapse is a known failure mode, and the campaign was designed to test whether longer training recovers code use.

5.2 Longer training and reconstruction loss

Training for 100 epochs raised code use to 199–338 of 512 on the test set, depending on seed and configuration. The L1 reconstruction variant was selected on validation SSIM (0.93164), against 0.93111 for the main configuration with seed 0. The difference is very small, so the choice is not strong evidence that L1 is better. It was made by the predeclared validation rule, not by test performance.

5.3 Codebook and downsampling variants

Variant	Validation SSIM	Codes used (test)	Decision
Baseline (L1, 4× downsampling, 512 codes)	0.9316	199	Selected
Data-based codebook initialisation	0.9287	236	Not selected
128 codes	0.9184	128	Not selected; lower perplexity (66)
8× downsampling (32×16 grid)	0.7850	187	Not selected; large loss of detail

Eight-fold downsampling makes sampling about four times cheaper, but the reconstruction quality drops sharply, so it was rejected. Reducing the codebook to 128 entries lowered perplexity and did not help.

5.4 Prior variants

The PixelCNN prior was trained on the frozen selected VQ-VAE. The selected prior reached a validation NLL of 3.455 nats per code. Other prior variants ranged from 2.924 to 3.602 nats. The selected prior's validation loss improved only slowly in its last ten epochs (about 3.468 at epoch 30 and 3.457 at epoch 40), so the prior was not expected to gain much from longer training.

5.5 DCGAN baseline

The first DCGAN produced banded samples, a known artefact of transposed convolutions (Odena et al., 2016). The final generator uses nearest-neighbour upsampling followed by convolution, with spectral normalisation in the discriminator. The baseline was trained for 50 epochs with two seeds.

5.6 What did not work

- 8× downsampling: reconstructions lost too much detail (see 5.3).
- 128 codes: lower perplexity and no gain in quality.
- Longer prior training on its own: validation NLL improvement had slowed by the final epochs.
- The first DCGAN: banded samples. The upsampling change in 5.5 was made to address this, but the fix has not yet been checked on a visual comparison.

6. Results

All numbers come from the frozen campaign. Test numbers use the 540 held-out test slices from 3 patients, and each number is a single run unless stated.

6.1 Quantitative results

Reconstruction (test, SSIM). The selected VQ-VAE reaches mean SSIM 0.9425, with 540/540 reconstructions at or above 0.6. Seeds 0 and 1 of the main configuration give 0.9414 and 0.9432. The 0.6 target applies to reconstructions, following the teaching-team clarification.

Generation (unpaired SSIM, supplementary). Each generated slice is compared with its nearest held-out real slice by pixel L2. The same protocol on real scans gives mean 0.2504, so this measure cannot reach 0.6 even for real data.

Cohort	Mean SSIM to nearest reference	Fraction ≥ 0.6
Real test scans (control)	0.2504	0.000
VQ-VAE + PixelCNN prior (selected)	0.1827	0.000
DCGAN (seed 0)	0.2154	0.000

Distribution fidelity (KID, 1,500 samples per model).

Run	VQ-VAE + prior	DCGAN
Seed 0	0.4218 (selected) / 0.3734 (main)	0.4890
Seed 1	0.4308 (main)	0.2830

Lower is better. The two seeds disagree about which model is better, so this report does not claim a consistent winner. The K128 variant scored 0.3478 on the test set, but it was not chosen on test results.

Resources (A100-PCIE-40GB).

Model	Epoch time (s)	Peak training VRAM (GB)	Time for 500 samples
VQ-VAE (selected)	8.21	1.03	-
PixelCNN prior (selected)	7.85	0.68	about 40 s
DCGAN	8.65	1.01	about 0.08 s

The campaign did not record parameter counts. Preliminary parameter counts from the smoke tests were 1.18 M (VQ-VAE), 2.13 M (PixelCNN prior), and 3.2 M / 2.8 M (DCGAN generator / discriminator). Total GPU allocation was 3.03 hours, of which 2.53 hours was training.




Figure 3: Test reconstructions

6.2 Qualitative results

Test-set reconstructions from the selected VQ-VAE, uncurated.

Uncurated samples from the VQ-VAE + PixelCNN prior, fixed seed 0.

Uncurated samples from the DCGAN baseline, fixed seed 0.

Distances from generated and real slices to their nearest training slices.

Side-by-side comparison. Visual inspection of the uncurated grids shows that VQ-VAE + PixelCNN prior samples lack recognizable hip anatomy: the bone structures are absent or distorted, and the tissue boundaries do not match real MRI patterns. Some DCGAN samples show recognizable anatomy, although artifacts and variation in quality remain visible. Visual resemblance is not sufficient to establish clinical fidelity or adequate diversity, and the quantitative comparisons in Sections 6.1 and 6.7 provide important context.

Closest training pairs. The audit figures show generated samples next to their nearest training slices by pixel L2 distance. In all cases, the generated samples are visually distinct from their nearest training matches, confirming that exact memorisation has not occurred. However, this distinctness does not imply clinical validity: the generated samples are distinct because they lack anatomical structure, not because they represent novel realistic cases.

6.3 Memorisation screen

No generated slice exactly matches a training slice after uint8 conversion, and all sampled slices are unique. For the selected prior, 3.9% of samples fall below the validation-calibrated nearest-neighbour threshold, and 13.2% do at lower sampling temperature.

Caveat found in the review. Nearest-neighbour RMSE is strongly correlated with the mean brightness of the generated sample (Pearson r = 0.84 across all 1,500 samples). Dark samples have low RMSE to dark training slices for reasons unrelated to copying. The threshold-based screen above therefore overstates memorisation risk, and the flagged “close” cases are mostly dark slices, not evidence of copying. This is a limitation of the screen, not evidence that the samples are safe. It is not a privacy guarantee, and it cannot rule out near-copies.

6.4 Failure autopsies

Four cases were selected by fixed numeric rules from the selected model’s audit files (`vqvae_prior_audit.csv`, `reconstruction_scores.csv`), not by eye. The table records the selected rule, numerical evidence and author’s visual review.




Figure 4: VQ-VAE + prior samples, seed 0



Figure 5: DCGAN samples, seed 0




Figure 6: Nearest-neighbour distances

Case	Rule	Evidence	Nearest training slice	Visual description
A. Sample #731	Lowest nearest-reference SSIM (generated)	SSIM 0.086; L2 RMSE to training 0.203	case_019, week 1, slice 51	Dark, noisy texture with no anatomical structure; nearest training slice shows clear hip anatomy
B. Sample #1004	Closest to any training slice	RMSE 0.1025, below the calibrated 0.1207 screen; SSIM 0.26	case_019, week 1, slice 57	Very dark sample (mean 0.091); low RMSE due to brightness, not copying
C. Sample #227	Furthest from training (most distinct)	RMSE 0.2514	case_010, week 5, slice 59	Bright, high-contrast noise pattern; maximally different from any training slice
D. Reconstruction, patient 042	Lowest reconstruction SSIM	SSIM 0.9135 (the minimum is still above 0.6)	itself	Clear hip anatomy with fine detail; reconstruction quality still excellent

Observation to check: two of the four cases (A and B) have their nearest training slice from patient 019, the scan that was cropped from 256×144. This may be a coincidence, or the cropped scan may be over-represented in the training data. It needs checking before any claim is made.

Brightness check (Case B). The three case-B samples (indices 1004, 1151, 786) have mean intensities of 0.091, 0.073 and 0.115, against a median of 0.150 across all samples. They are in the dark tail, which explains their low

nearest-training RMSE (see section 6.3).

Author's visual review of the grids. In cases A and C, the generated samples lacked recognizable anatomical organisation relative to their nearest training slices. Case B samples were dark and similarly lacked recognizable hip structures. The reconstruction in case D retained recognizable anatomy despite having the lowest reconstruction SSIM. The author also reviewed the uncurated fixed-seed grid (`vqvae_prior_seed0.png`) and did not identify recognizable hip anatomy in those samples. This suggests that the selected PixelCNN's visual limitations extend beyond the numerically selected outliers; the assessment remains an informal visual review rather than a blinded clinical evaluation.

6.5 Generation Failure Investigation

While the selected VQ-VAE achieved excellent reconstruction (SSIM 0.9425), the initial PixelCNN-based generation produced anatomically unrealistic samples. This section documents the investigation into that failure, the attempted fixes, and the subsequent Transformer results.

6.5.1 Initial Observation: Statistical Mismatch

Generated samples from the PixelCNN prior showed clear statistical differences from real data:

Metric	Training data	Generated samples	Ratio
Mean intensity	0.180	0.136	0.76×
Std deviation	0.169	0.111	0.66×
Bright pixels (>0.5)	9.69%	3.70%	0.38×
Across-sample std	-	0.075	Low diversity




Figure 7: Structural diagnosis

Comparison of intensity distributions: generated samples are systematically darker and less variable than real scans.




Figure 8: Temperature comparison

Sampling temperature sweep (T=0.7, 1.0, 1.3): higher temperature increases diversity but does not fix anatomical structure.

6.5.2 Decoder Isolation Experiment

Hypothesis: Perhaps the VQ-VAE decoder is the bottleneck, unable to produce realistic anatomy even from good codes.

Method: Test the decoder in isolation by feeding it different combinations of real and sampled codes: - Row A: Real coarse + real fine codes → reconstruct real images (control) - Row B: Real coarse + sampled fine codes → test if fine prior is the problem - Row C: Sampled coarse + sampled fine codes → full generation pipeline - Row D: Sampled coarse + real fine codes → test if coarse prior is the problem

Decoder isolation grid showing different code combinations.

Finding: Row D (shuffled coarse + real fine) produces images nearly identical to Row A (both real). This proves that the decoder takes anatomical structure primarily from the fine 64×32 codes, not the coarse 16×8 codes. The coarse codes contribute mainly to global intensity/contrast, not anatomy.

Rows B and C (any sampled fine codes) both produce anatomically incoherent samples, confirming that the fine PixelCNN prior is the root cause of generation failure.

6.5.3 Root Cause: PixelCNN Blind Spot

The PixelCNN prior uses masked 3×3 convolutions with 4 residual blocks. This gives each position a receptive field of approximately: - Horizontal: full row (due to raster-order causality) - Vertical: ~19 rows above the current position

On a 64-row grid, a position near the bottom cannot directly access rows far above its local receptive field. Anatomical structures can span a much larger vertical distance, so this limited context is a plausible contributor to incoherent global structure. The failure is consistent with this hypothesis, but the comparison does not independently establish causation.

6.5.4 Attempted Solutions

After identifying the blind spot problem, multiple alternative approaches were tested:

Hierarchical VQ-VAE-2 and PixelCNN priors (26–27 October). The model was extended to use a 16×8 coarse grid and a 64×32 fine grid, with separate priors for the two levels. Reconstruction SSIM reached approximately 0.937, but the generated images remained anatomically incoherent, with mean intensity 0.136 and bright-pixel fraction 0.037. The improvement in reconstruction therefore did not transfer automatically to unconditional generation. Fine-level conditioning was investigated separately in Experiment 2.




Figure 9: Decoder isolation experiment

Transformer coarse prior (Experiment 4). The coarse PixelCNN was replaced with a causal Transformer comprising six layers, eight attention heads and embedding dimension 256. After 150 training epochs, samples showed improved global structure and a mean intensity of 0.168, with bright-pixel fraction 0.053, but did not display coherent anatomy. This result is consistent with the isolation experiment: improving coarse codes alone was insufficient when the fine prior remained unchanged.

Conditioned fine prior (Experiment 2). The fine PixelCNN was explicitly conditioned on coarse codes and trained for 150 epochs, reaching validation NLL of approximately 4.0. Its bright-pixel fraction was 0.054, and visual quality did not improve substantially. Conditioning supplies information from the coarse representation, but does not by itself enlarge the fine prior's spatial receptive field.

Latent-space alternatives (Experiment 7). PCA sampling projected training codes into a lower-dimensional space, sampled from a Gaussian, and mapped the result back to discrete codes. Images were blurred and lacked clear anatomy despite a mean intensity of 0.189 and bright-pixel fraction of 0.051. Dirichlet-weighted latent mixup produced overlapping structures, with mean 0.155 and bright-pixel fraction 0.026. In prefix-conditioned completion, the first 16 or 32 rows were taken from real codes and the remaining rows sampled by the PixelCNN. The 32-row prefix produced mean intensity 0.208 and bright-pixel fraction 0.087, but visual quality remained limited. Because the completion methods use real codes, their results are not unconditional samples.

Gated PixelCNN (Experiment 8). A 22-layer gated prior with 7×7 kernels was trained to increase the spatial receptive field. Its validation NLL was 4.05; generation was not evaluated within the available time. It is therefore not possible to conclude from this experiment whether the larger convolutional receptive field would have improved the samples.

Transformer fine prior (Experiment 6). The fine PixelCNN was replaced by a causal Transformer with six layers, eight attention heads, embedding dimension 256 and attention across the 2,048-token sequence. After 40 epochs its validation NLL was 3.84, compared with approximately 4.05 for the PixelCNN comparison. At temperature 1.0, the samples had mean intensity 0.159 and bright-pixel fraction 0.049, corresponding to approximately 88% and 51% of the training-reference values. The author observed recognizable hip structures in the sample grid. The diversity and memorisation screens are discussed separately in Section 6.6; they do not constitute clinical or privacy certification.

Uncurated samples from the Transformer fine prior (T=1.0). Unlike PixelCNN samples, these show recognizable anatomical structure.

Side-by-side comparison: real test reconstructions (left) vs Transformer-generated samples (right). Generated samples are systematically darker but anatomically coherent.

Interpretation. Causal self-attention gives each token access to all preceding tokens, whereas the tested PixelCNN has a limited local receptive field. This provides a plausible mechanism for the improvement in global structure. The experiments support this interpretation but do not isolate receptive field as the sole cause: the models also differ in architecture, capacity and optimisation.

6.5.5 Why This Matters

The experiments demonstrate why reconstruction and unconditional generation must be assessed separately. The VQ-VAE-2 reconstructed held-out images with SSIM of approximately 0.937, and the isolation experiment showed that the decoder could retain recognizable structure when supplied with real fine codes. Replacing those codes with samples from the tested PixelCNN caused a marked degradation, implicating the fine-code distribution as a substantial bottleneck in this pipeline.

The Transformer results suggest that greater access to preceding context can improve the generated structures, although the experiments do not prove that receptive field alone explains the difference. The gated PixelCNN was not evaluated for generation, and the Transformer samples retain measurable intensity-distribution differences. Consequently, neither the Transformer nor the rejected alternatives should be treated as clinically validated solely on the basis of this comparison.

6.5.6 Training Curves

VQ-VAE-2 training and validation loss (log scale) and validation SSIM over 100 epochs, plotted from the saved training history.



Figure 10: Transformer-generated samples




Figure 11: Real vs Generated comparison




Figure 12: VQ-VAE training curves

Validation SSIM rises from 0.645 in epoch 1 to 0.936 at epoch 100, while validation loss falls from 0.0725 to 0.00133. The later improvements are much smaller than the initial gains, suggesting diminishing returns from further reconstruction training. These curves assess reconstruction, not the quality of unconditional generation; the strong reconstruction result does not establish that the sampled latent codes follow the true data distribution.




Figure 13: Prior training curves

Fine PixelCNN prior training and validation negative log-likelihood (NLL), in nats per code, over 150 epochs, plotted from the saved prior history.

Training NLL decreases from 4.956 to 3.645, while validation NLL decreases from 4.845 to 4.036. The gap at the final epoch is approximately 0.39 nats per code: training continues to improve more than validation, which is consistent with overfitting or limited generalisation. These are teacher-forced code-prediction scores, not direct measures of image realism. During sampling, predictions are conditioned on previously sampled rather than ground-truth codes, so errors can accumulate. Together with the isolation experiment, this explains why a decreasing NLL can coexist with anatomically poor generated images. The saved history does not separately record the reconstruction and codebook losses, so they are not presented as separate curves.

6.6 Transformer Generation Quality Analysis

With the Transformer prior successfully generating anatomically coherent samples, we conducted detailed analysis of diversity, memorization, and distribution fidelity.

6.6.1 Diversity Analysis Samples at T=0.9 (top row) and T=1.0 (bottom row) showing generation diversity.

Temperature	Mean Pairwise L2 Distance	Std of Pairwise Distance
T=0.9	37.3	9.3
T=1.0	36.0	5.8




Figure 14: Diversity across temperatures

The average pairwise distances indicate measurable variation among the sampled images; the T=0.9 set has a slightly higher mean and a wider spread than the T=1.0 set. Pixel-space distance is affected by brightness and texture as well as anatomy, however, and cannot establish coverage of the real population. These generated-to-generated distances also do not test whether a sample is similar to a training image.




Figure 15: Memorization check

6.6.2 Memorization Check Left: Distribution of pairwise L2 distances between generated samples. Right: The most similar pair of generated samples (still visually distinct).

Key findings: - Minimum pairwise distance: 20.9 (far from zero) - Mean pairwise distance: 36.0 - Maximum pairwise distance: 49.4

The minimum distance of 20.9 is between two generated samples; it indicates that the examined set does not contain identical generated images under this metric. It does not measure distance to training data and cannot by itself exclude memorisation. The earlier nearest-neighbour analysis concerns the PixelCNN campaign rather than establishing the Transformer model's privacy. A separate generated-to-training audit would be required for the latter.

6.6.3 AI vs Real Detection: Distribution Differences Comparison of statistical distributions between generated and real training images.

Metric	Training	Generated (T=1.0)	Ratio
Mean intensity	0.180	0.159	88.2%
Std deviation	0.169	0.170	100.7%
Bright pixels (>0.5)	9.69%	4.95%	51.1%

The generated samples are approximately 12% darker on average and contain about half the fraction of bright pixels observed in the training reference. Their overall pixel standard deviation is similar, but a match in this aggregate statistic does not establish that local textures or anatomical structures have the correct distribution. Mean intensity and bright-pixel fraction are potential detection features; a classifier based on them would require a separately defined evaluation before its accuracy could be claimed.

For research augmentation, these systematic differences could become shortcuts for a downstream classifier. Possible interventions include intensity calibration, histogram-based matching and explicit distribution constraints during training. Each would need evaluation on patient-disjoint data, since matching marginal intensity statistics alone would not necessarily correct anatomical errors.




Figure 16: AI vs Real distributions

6.7 Summary: What Worked and What Didn't

Approach	Reconstruction	Generation	Notes
VQ-VAE (single level)	SSIM 0.93	Failed	Codebook collapse initially
VQ-VAE-2 (hierarchical)	SSIM 0.94	Failed	Better reconstruction, same generation issues
PixelCNN prior	-	Failed	Limited context is a plausible contributing factor
Transformer coarse prior	-	Partial	Improved global structure, fine prior still fails
Conditioned fine prior	-	Failed	Conditioning doesn't fix receptive field
Latent sampling (PCA, mixup)	-	Failed	Not true learned priors
Transformer fine prior	-	Improved	Recognizable structure in visual review; distribution gaps remain
DCGAN baseline	-	Partial	Some recognizable anatomy; diversity and fidelity need further assessment

DCGAN diversity analysis: Some DCGAN samples show recognizable anatomy, but visual plausibility alone does not establish that the generator covers the full range of patient anatomy. In the separate one-epoch, 32-sample smoke test, across-sample pixel standard deviation was 0.0028, with no exact uint8 training matches. This smoke-test statistic must not be attributed to the 50-epoch final DCGAN. The earlier three-epoch feasibility test reported 0.067 versus 0.130 for real slices. The final campaign's KID varied substantially across its two seeds (0.489 and 0.283), so a single favourable grid is not enough to establish consistent distributional fidelity or diversity. Exact-match checks and the nearest-neighbour screen are useful warnings, but do not prove absence of memorisation. More samples, patient-level coverage analysis, and direct generated-to-training comparisons are needed before recommending augmentation.

Interpretation: The isolation and prior-comparison experiments indicate that modelling the fine-code distribution is an important factor in generation quality. The limited context of the tested PixelCNN is a plausible explanation, but the present experiments do not exclude other architectural or optimisation effects.

7. Limitations and Future Work

The central limitation is that reconstruction and generation answer different questions. A reconstruction starts from the codes of a real input; an unconditional generator must also reproduce the distribution of those codes. High reconstruction SSIM therefore supports the capacity of the encoder and decoder, but cannot by itself establish that synthetic samples are clinically faithful. Likewise, qualitative resemblance is an observation by the author, not a blinded clinical assessment. The brightness and bright-pixel differences in Section 6.6.3 are particularly important because a downstream model could learn these systematic artefacts instead of clinically relevant anatomy.

The small patient-disjoint evaluation set makes the reported results sensitive to individual patients and acquisition variation. Slices from the same patient are correlated, so hundreds of slices should not be treated as hundreds of independent patients. KID provides a distribution-level comparison but uses features trained on natural images; it may miss medically important errors. Similarly, nearest-neighbour distances are affected by brightness and do not constitute a formal privacy guarantee. A larger, external cohort, patient-level uncertainty estimates, blinded expert assessment and a dedicated privacy audit would address different aspects of these limitations rather than relying on a single score.

Current Limitations: - Unpaired generated-slice SSIM cannot reach 0.6 even for real scans, so the target is evaluated on reconstructions only. - Patient numbers are small (3 test patients, 4 validation patients), so per-patient

variation is large and statistical power is limited. - KID uses ImageNet features on grayscale MRI and is not clinical validation. - Nearest-neighbour screening does not prove the absence of memorisation; it is a heuristic screen, not a privacy guarantee. - No formal differential-privacy bound (ε-δ guarantees) was applied. - Parameter counts were not systematically recorded during the campaign.

Recommended Future Work: - Multi-center validation: Evaluate on larger held-out cohorts from multiple clinical sites to assess generalization and per-patient variability. - Clinical expert validation: Conduct blinded radiologist review studies to assess anatomical plausibility and diagnostic utility. - Formal privacy guarantees: Implement differential privacy training (DP-SGD) with formal ε-δ bounds for clinical deployment. - Distribution calibration: Post-processing intensity adjustment or adversarial training to match real MRI statistics (address 12% darkness, 51% bright pixel deficit). - Perceptual metrics: Evaluate with medical-imaging-specific metrics (FID on medical features, radiologist Turing tests) rather than ImageNet-based KID. - Conditional generation: Extend to patient-specific or anatomy-conditioned generation for targeted data augmentation.

8. Recommendation for the project manager

Based on the comprehensive experimental investigation, we provide the following phased deployment recommendation:

Phase 1: Research evaluation of reconstruction

The reconstruction results justify further investigation of lossy compression and retrieval, but not immediate clinical deployment. The hierarchical model achieved mean SSIM of approximately 0.937, while the selected single-level campaign model achieved 0.9425 with 540/540 test slices above 0.6. The single-level campaign recorded approximately 8.21 seconds per training epoch and 1.03 GB peak training VRAM. A deployment decision would require validation of clinically relevant details, compression rate and performance on external patients; SSIM alone does not establish diagnostic equivalence.

Phase 2: Validation of synthetic cohorts

Transformer samples showed recognizable structures in the author's review, but their mean intensity was 0.159 versus 0.180 in the reference, and their bright-pixel fraction was 4.95% versus 9.69%. The mean generated-to-generated pairwise distance of 36.0 and minimum of 20.9 describe variation within the examined sample set, not privacy relative to training data. Before considering research augmentation, the model should be evaluated for patient-level distribution coverage, nearest-training similarity and utility in a downstream task, together with independent expert review. Intensity calibration is a candidate intervention, but should be evaluated rather than assumed to repair anatomical errors.

Phase 3: Alternative baselines

The tested PixelCNN prior did not produce coherent anatomy in the visual review, but larger-receptive-field variants remain an open research question. The DCGAN produced some recognizable anatomy and remains a useful fast baseline; its KID varied across seeds and coverage needs further assessment. PCA and mixup alternatives did not yield comparable anatomical quality in the reported visual review.

Cost-Benefit Analysis

Approach	Anatomical Quality	Speed (500 samples)	Recommendation
VQ-VAE Reconstruction	Excellent (SSIM 0.937)	N/A	Research evaluation
VQ-VAE + Transformer	Coherent in visual review	Not measured here	Further validation
VQ-VAE + PixelCNN	Poor in visual review	40s	Further study
DCGAN	Some recognizable anatomy	0.08s	Retain as a baseline

Critical Success Factor

The experiments highlight the importance of matching the prior's available context to the structure of the data. The Transformer result is consistent with a benefit from wider context, but does not prove that self-attention is the only viable architecture. A controlled comparison with the unevaluated gated PixelCNN would help separate receptive-field effects from other model and training differences.

Next Steps

1. Immediate: Evaluate reconstruction for research compression applications
2. Short-term (1-2 months): Implement distribution calibration for Transformer-generated samples
3. Medium-term (3-6 months): Conduct clinical validation study with radiologists
4. Long-term (6-12 months): Evaluate formal differential privacy bounds for clinical deployment

9. Dependencies and reproducibility

- Python 3.11, torch 2.13.0+cu130, torchvision 0.28.0+cu130, torchmetrics 1.9.0, torch-fidelity 0.4.0, nibabel 5.4.2, scikit-image 0.26.0, matplotlib 3.11.2, tqdm 4.70.0, NumPy.
- KID requires torch-fidelity and Inception weights, cached outside Git.
- Training runs are seeded (`--seed 0` default) and check patient-level split disjointness at startup.
- The Quick Start above describes the supplied command-line scripts; the separate hierarchical experiments are not reproduced by those commands.

The historical test suite is not included in the cleaned submission directory. The supplied scripts require the dependencies above and access to the dataset for end-to-end execution.

10. Artificial Intelligence Usage Disclosure

This submission was created with substantial assistance from AI tools. The following disclosure describes how these tools were used throughout the project.

AI Tools Used:

1. Claude Sonnet 3.5 (Anthropic) - Used extensively for report writing and analysis:
    - Synthesizing this README from experimental findings, statistical results, graphs, and observations
    - Improving sentence structure, grammar, and clarity throughout the document
    - Organizing sections and creating narrative flow
    - Interpreting experimental results and articulating technical concepts
    - Drafting the Key Contributions section and experimental analysis
2. DeepSeek (Agentic Coding Assistant) - Used for code development:
    - Implementing model architectures (VQ-VAE, VQ-VAE-2, PixelCNN, Transformer prior, DCGAN)
    - Writing training loops, evaluation metrics, and data pipelines
    - Creating plotting scripts and figure generation code
    - Developing the campaign system for experiment orchestration
    - Implementing unit tests and validation checks
3. Additional AI Tools:
    - GitHub Copilot for code completion and suggestions
    - ChatGPT for technical queries and debugging assistance
    - AI-assisted documentation lookup for libraries (PyTorch, Matplotlib, NumPy)

Scope of AI Assistance:

AI tools contributed to: - Code implementation (models, training, evaluation, visualization) - Report writing (structure, grammar, technical explanations) - Data analysis interpretation and presentation - Figure generation and plotting scripts - Documentation and code comments

Verification and Validation:

All AI-generated content was verified through: - Running unit tests on all model implementations - Executing the full pipeline on real HipMRI data with patient-disjoint splits - Cross-checking reported numbers against raw output

files (`campaign_results.json`) - Visual inspection of generated samples and figures - Independent recomputation of statistical analyses - Validation of experimental claims against logged results

Work Checked and Verified:
Benjamin Evans (Student ID: 48828514)

All code was tested, all results were validated, and all claims were verified against experimental evidence before inclusion in this submission.

11. References

- van den Oord, A., Vinyals, O. & Kavukcuoglu, K. (2017). Neural Discrete Representation Learning. NeurIPS.
- van den Oord, A., et al. (2016). Conditional Image Generation with PixelCNN Decoders. NeurIPS.
- Razavi, A., van den Oord, A. & Vinyals, O. (2019). Generating Diverse High-Fidelity Images with VQ-VAE-2. NeurIPS.
- Radford, A., Metz, L. & Chintala, S. (2016). Unsupervised Representation Learning with Deep Convolutional GANs. ICLR.
- Odena, A., Dumoulin, V. & Olah, C. (2016). Deconvolution and Checkerboard Artifacts. Distill.
- Miyato, T., et al. (2018). Spectral Normalization for GANs. ICLR.
- Binkowski, M., et al. (2018). Demystifying MMD GANs (KID). ICLR.
- Structure of the report was informed by the 2025 COMP3710 VQ-VAE README by S. Subramaniam (PatternAnalysis-2025, s4858817_VQVAE). No text was copied.

Appendix A: Additional Experimental Figures

This appendix contains supplementary figures from the experimental investigation that provide additional context and visual evidence for the findings reported in Section 6.

A.1 Experiment Comparison Overview




Figure 17: Experiment comparison

Figure A.1: Side-by-side comparison of all eight experimental approaches tested during the investigation, showing the progression from PixelCNN failure to Transformer success.

A.2 Receptive Field Visualization

Figure A.2: Visual comparison of PixelCNN's limited receptive field (~19 rows) versus Transformer's full attention over all 2,048 code positions.




Figure 18: Receptive field comparison

A.3 Transformer Sample Grid

Figure A.3: Extended grid of Transformer-generated samples (32 samples) demonstrating diversity and anatomical consistency across multiple generations.

A.4 Distribution Analysis (Experiment 6)

Figure A.4: Detailed statistical analysis from Experiment 6 (Transformer prior) showing intensity distributions, bright pixel fractions, and pairwise distance metrics.

Appendix B: Complete Feasibility Review (As Submitted)

This is the exact 1-page feasibility review submitted before experiments began.

COMP3710 Project 2.4: Feasibility Review

The Fidelity–Memorisation–Privacy Dilemma in Synthetic Medical Imaging
Hard VQ-VAE with PixelCNN Prior | DCGAN Baseline

---

1. User Need, Scope & Acceptance Criteria

Synthetic medical images could support research when real patient data is limited or cannot be shared due to privacy constraints. However, generated images must preserve anatomical structure without simply reproducing training examples. This project investigates these trade-offs using 2D HipMRI slices, comparing a VQ-VAE with a PixelCNN prior against a DCGAN baseline.

The project will assess the following criteria:

- Reconstruction fidelity: achieve mean SSIM ≥ 0.6 between held-out images and their corresponding VQ-VAE reconstructions.
- Generation: generate 500 samples from each unconditional model and compare their Kernel Inception Distance (KID) against held-out real images. Lower KID indicates greater similarity in feature distributions.




Figure 19: Transformer sample grid




Figure 20: Distribution analysis

- Diversity: report codebook utilisation and distinct entries used; assess sample variety and distribution coverage using generated grids and feature-space metrics.
- Memorisation risk: check for exact duplicates and compare generated-to-training image similarity against held-out real-to-training similarities. Investigate unusually similar samples; this is a screening test, not a privacy guarantee.
- Computational feasibility: record peak GPU memory, training time and generation time. Use a provisional training budget of 3 hours and target generation of 500 images within 15 minutes, with 1 hour as an upper target, subject to available hardware.

2. Model Choice & Course Concepts

The main model is a VQ-VAE trained on the provided HipMRI dataset. Its encoder maps images to latent features, which are quantised to learned codebook entries; its decoder reconstructs images from these discrete representations (van den Oord et al., 2017).

A VQ-VAE alone does not learn how to sample new latent grids. A PixelCNN autoregressive prior will therefore learn the distribution of code indices, allowing new grids to be sampled and decoded into synthetic slices. A DCGAN (Radford et al., 2016) provides an alternative unconditional generation baseline: its convolutional generator creates images from random noise, while its discriminator distinguishes generated from real images. It offers a useful architectural comparison and fast sampling, although adversarial training may be unstable.

The course content has covered a practical implementation of a VQ-VAE and a GAN model, as well as their concepts, and will be used to underpin this experiment.

3. Preliminary Feasibility Evidence

Baseline configuration. The VQ-VAE follows the architecture and settings of van den Oord et al. (2017): two 4×4 stride-2 convolutions (a 64×32 latent grid), two residual blocks, a 512-entry codebook of dimension 64, β=0.25, straight-through gradients and Adam at 2×10^{-4}, with the width reduced to 128 channels. It was implemented directly from the paper and left untuned, as were the masked-convolution PixelCNN prior and the DCGAN. A previous-year COMP3710 VQ-VAE on this dataset (PatternAnalysis-2025, s4858817) is cited only as external evidence: it reconstructs without a generative prior and reached validation SSIM 0.757, with codebook perplexity rising from ~5 to ~100 over ~50 epochs.

Data audit (Rangpur, keras_slices_data). The 2D data contain 12,660 slices: 11,460 train (31 patients, 191 scans), 660 validation (4 patients) and 540 test (3 patients), a 90.5/5.2/4.3% slice split with zero patient overlap between splits. Images are 256×128 float32 with paired, index-aligned masks; one scan (patient 019, week 1) is 256×144 and must be cropped. Raw intensities span 0–1212 (median slice maximum 397), so per-slice normalisation is needed. Masks carry six labels; the prostate (label 5) is only ~0.4% of pixels. Loading runs at ~230 slices/s; the full set is ~1.7 GB in RAM.

GPU smoke test (A100-40GB, 5 epochs). The VQ-VAE (1.18M parameters) trained at 6.9 s/epoch and 3.39 GB peak, reaching held-out mean SSIM 0.624 (78% of slices ≥0.6; MSE 0.0043), though reconstructions are blurry. Only 13/512 codes were used (perplexity 6.8), resembling the early-epoch collapse reported in the cited work, so longer training may recover utilisation but must be verified. A 2.13M-parameter PixelCNN on the frozen codes cut cross-entropy from 6.24 (uniform) to 0.63, an easy target while only 13 codes are active; measured sampling cost extrapolates to 2.8 min (fp32; 1.4 min bf16) for 500 images, inside the 15-minute target. A 3-epoch DCGAN (3.2M/2.8M parameters, 3.6 s/epoch, 1.46 GB) generates 500 images in 0.12 s but gives banded, near-identical samples (pixel std 0.067 vs 0.130 real). The pipeline fits the budget; sample quality is the open risk.

Fig. 1. Real vs VQ-VAE reconstruction pairs (blurry, SSIM 0.62); DCGAN samples (banded, near-identical).

4. Experimental Plan & Next Steps

VQ-VAE: - Retrain for 50–100 epochs with validation-SSIM checkpointing and per-epoch perplexity, testing whether the 13/512 collapse is transient. - If utilisation stays low: EMA codebook updates, k-means initialisation, dead-code reset; sweep $K\in\{256,512\}$, $D\in\{64,128\}$ and β. - To reduce blur: add an L1/SSIM loss and compare 4× (2048 tokens)




Figure 21: Feasibility figure

with 8× downsampling (512 tokens: ~4× cheaper PixelCNN sampling, possible detail loss). Select on validation SSIM, MSE, utilisation.

PixelCNN, DCGAN and evaluation: - Freeze the chosen VQ-VAE, encode all splits, train PixelCNN (try gated blocks; vary depth, width, receptive field) selected on validation NLL; sample with temperature. - DCGAN: remove banding (resize-convolution upsampling, spectral norm, label smoothing), train 50+ epochs; WGAN-GP only if unstable. - 500 samples per model: KID vs held-out real images, codebook use, fixed-seed grids, nearest-training-neighbour audit. Select on validation, report test once; with 4 validation and 3 test patients, report per-patient spread and limited statistical power. Log time and peak GPU memory.

5. Risks, Budget & Fallback

Risks: Blurry reconstructions, codebook under-utilisation, poor generated samples, DCGAN instability, memorisation and limited computing resources.

- Poor fidelity or codebook use: investigate loss weighting, model capacity, downsampling and codebook settings.
- Memorisation: inspect suspicious matches; test early stopping, regularisation or anatomically appropriate augmentation, then reassess fidelity.
- Unstable generation: tune learning rates and model settings; document persistent mode collapse or poor sample quality.
- Resource constraints: reduce model size, latent-grid resolution or training duration. If PixelCNN cannot be completed, report reconstruction results separately and acknowledge that unconditional generation remains unverified.

References

van den Oord, A., Vinyals, O. & Kavukcuoglu, K. (2017). Neural Discrete Representation Learning. NeurIPS.

Radford, A., Metz, L. & Chintala, S. (2016). Unsupervised Representation Learning with Deep Convolutional Generative Adversarial Networks. ICLR.