

The title is framed by a large dashed rectangular border. A dashed arrow on the right side points upwards, and a dashed arrow on the bottom left points to the right.

TRANSITIONING FROM WINDOWS TO POSIX

DIFFERENCES

- gcc vs. g++
- No initialization
- No "socket" type
- Separate header files
- errno & error constants
- File handles vs. sockets
- Non-blocking IO differences

gcc vs. g++

Issue

Visual Studio just has one compiler, and picks the compilation mode (C vs. C++) based on filename. GNU has separate compilers for straight-C and C++.

Warning Sign

Error messages like
"undefined reference to
__gxx_personality_v0".

Solution

Use the right compiler for your project--gcc for C, g++ for C++.

Google is your friend.

No Initialization or Cleanup

Issue

Winsock is a separate library that has to be loaded and unloaded. POSIX sockets are integral to the OS, so there's no equivalent to `WSAStartup()` or `WSACleanup()`.

Warning Sign

Error messages like "WSAStartup was not defined in this scope".

Solution

Surround platform-specific code with conditional blocks:

```
#ifdef WIN32
// Do Windows things
#else
// Do *nix things
#endif
```

Don't Repeat Yourself! Hide platform-specific code behind consistent APIs within your program.

No “socket” Type

Issue

POSIX sockets are simply ints; there is no “socket” type.

Warning Sign

Error messages like “socket does not name a type”.

Solution

Create a conditionally-compiled typedef for socket.

```
#ifndef WIN32
typedef int socket;
#endif
```

Or, in C++, hide sockets entirely behind a custom class.

Separate Header Files

Issue

All of Winsock is in one header file. POSIX socket code is spread across several.

Warning Sign

Error messages like "socket was not defined in this scope".

Solution

Typing "man *function*" in a command shell will tell you what header file you're missing.

Make one "sockets.h" header that includes all the others.

```
#include <sys/socket.h>
#include <netdb.h>
#include <netinet/in.h>
#include <netinet/ip.h>
#include <arpa/inet.h>
```


errno and Error Constants

Issue

The POSIX equivalent of `WSAGetLastError()` is a global variable, `errno`.

Error constants are different--strip the "WSA" part off.

Warning Sign

Error messages like "WSAECONNRESET was not defined in this scope".

Solution

Create your own "GetLastError()" function, wrapping a conditional-compilation block.

Define your own error codes for the errors you care about... or better yet use an enum for clarity and type-safety.

File Handles vs. Sockets

Issue

POSIX sockets are the same as file handles. Existing POSIX code may take advantage of this.

Also, the same `close()` call destroys both, unlike Winsock.

Warning Sign

Error messages like "closesocket was not defined in this scope".

Solution

When reading POSIX code, understand that `read()` is equivalent to `recv()`.

When writing portable code, avoid usage like that.

Call `close()` instead of `closesocket()`... and again, hide this behind an internal API.

Non-blocking IO Differences, Part I

Issue

As with `close()` vs. `closesocket()`, you have to call a general-purpose function rather than `ioctlsocket()`.

You can *mostly* rely on `ioctl()`... mostly.

Warning Sign

Error messages like "ioctlsocket was not defined in this scope".

Solution

You can call `ioctl()` with the exact same parameters as `ioctlsocket()`, on virtually every *nix you encounter.

Formal POSIX standard specifies `fcntl()`, which is inconvenient.

Hide this from the rest of your program.

continued...

Non-blocking IO Differences, Part II

Issue

The POSIX standard defines the “call would block” response as EAGAIN, not EWOULDBLOCK. But older Unixes still use EWOULDBLOCK.

Warning Sign

You expect EWOULDBLOCK, but you get some unrecognized other error value.

Solution

Whenever you check for EWOULDBLOCK, also check for EAGAIN at the same time.

The compiler knows what values these actually represent, and will optimize away the duplication wherever possible.

As always, hide this from the rest of your program.

SUMMARY

- Understand the gcc toolchain
- Use conditional compilation
- Hide calls, types and return values/error codes behind your own API
- While you're at it, solve the `getaddrinfo()` blocking problem as well.

