



Gradient Descent

Towards Neural Networks

Justin Stevens
Undergraduate AI Society
April 2nd, 2019

Outline

- 1 Decision Making
 - Perceptrons
 - Activation Functions
- 2 Classifying Digits through MNIST

Should I Stay or Should I Go?

Let's say I'm deciding on a given day whether or not to go to an Edmonton Oilers game. Here are the factors that will influence my decision:

Should I Stay or Should I Go?

Let's say I'm deciding on a given day whether or not to go to an Edmonton Oilers game. Here are the factors that will influence my decision:

- Are the tickets cheap or expensive?
- Do I have the time to go?
- Do I care about the team they're playing?

Should I Stay or Should I Go?

Let's say I'm deciding on a given day whether or not to go to an Edmonton Oilers game. Here are the factors that will influence my decision:

- Are the tickets cheap or expensive?
- Do I have the time to go?
- Do I care about the team they're playing?

We'll make my decision by encoding each possible input as a vector \bar{x} :

Should I Stay or Should I Go?

Let's say I'm deciding on a given day whether or not to go to an Edmonton Oilers game. Here are the factors that will influence my decision:

- Are the tickets cheap or expensive?
- Do I have the time to go?
- Do I care about the team they're playing?

We'll make my decision by encoding each possible input as a vector \bar{x} :

Ticket Prices	Availability	Interest	\bar{x}
Cheap	Yes	Yes	(1, 1, 1)
Cheap	No	No	(1, 0, 0)
Cheap	Yes	No	(1, 1, 0)
Cheap	No	Yes	(1, 0, 1)
Expensive	Yes	Yes	(0, 1, 1)
Expensive	No	No	(0, 0, 0)
Expensive	No	Yes	(0, 0, 1)
Expensive	Yes	No	(0, 1, 0)

How Will I Make my Decision?

Let's say I don't care much about price, but I do care about my availability and interest. In this case, the corresponding weights might be $\bar{w} = (1, 6, 3)$.

How Will I Make my Decision?

Let's say I don't care much about price, but I do care about my availability and interest. In this case, the corresponding weights might be $\bar{w} = (1, 6, 3)$. We can then compute the dot product $\bar{w} \cdot \bar{x}$ for each possible input:

Ticket Prices	Availability	Interest	\bar{x}	$\bar{w} \cdot \bar{x}$
Cheap	Yes	Yes	$(1, 1, 1)$	10
Cheap	No	No	$(1, 0, 0)$	1
Cheap	Yes	No	$(1, 1, 0)$	7
Cheap	No	Yes	$(1, 0, 1)$	4
Expensive	Yes	Yes	$(0, 1, 1)$	9
Expensive	No	No	$(0, 0, 0)$	0
Expensive	No	Yes	$(0, 0, 1)$	3
Expensive	Yes	No	$(0, 1, 0)$	6

How Will I Make my Decision?

Let's say I don't care much about price, but I do care about my availability and interest. In this case, the corresponding weights might be $\bar{w} = (1, 6, 3)$. We can then compute the dot product $\bar{w} \cdot \bar{x}$ for each possible input:

Ticket Prices	Availability	Interest	\bar{x}	$\bar{w} \cdot \bar{x}$
Cheap	Yes	Yes	$(1, 1, 1)$	10
Cheap	No	No	$(1, 0, 0)$	1
Cheap	Yes	No	$(1, 1, 0)$	7
Cheap	No	Yes	$(1, 0, 1)$	4
Expensive	Yes	Yes	$(0, 1, 1)$	9
Expensive	No	No	$(0, 0, 0)$	0
Expensive	No	Yes	$(0, 0, 1)$	3
Expensive	Yes	No	$(0, 1, 0)$	6

We can now define my **activation threshold**, t , which will determine whether or not I go to the game, represented in binary.

Formula for Decision Making

The general formula for my decision to go to the Oilers game is

$$\text{output} = \begin{cases} 0 & \text{if } \bar{w} \cdot \bar{x} < t \\ 1 & \text{if } \bar{w} \cdot \bar{x} \geq t. \end{cases}$$

Formula for Decision Making

The general formula for my decision to go to the Oilers game is

$$\text{output} = \begin{cases} 0 & \text{if } \bar{w} \cdot \bar{x} < t \\ 1 & \text{if } \bar{w} \cdot \bar{x} \geq t. \end{cases}$$

For instance, if $t = 9$, we see I'll only go if I'm both available and interested.

Formula for Decision Making

The general formula for my decision to go to the Oilers game is

$$\text{output} = \begin{cases} 0 & \text{if } \bar{w} \cdot \bar{x} < t \\ 1 & \text{if } \bar{w} \cdot \bar{x} \geq t. \end{cases}$$

For instance, if $t = 9$, we see I'll only go if I'm both available and interested. If $t = 7$, I'll also go if the tickets are cheap and I'm available:

Ticket Prices	Availability	Interest	\bar{x}	$\bar{x} \cdot \bar{w}$
Cheap	Yes	Yes	(1, 1, 1)	10
Cheap	No	No	(1, 0, 0)	1
Cheap	Yes	No	(1, 1, 0)	7
Cheap	No	Yes	(1, 0, 1)	4
Expensive	Yes	Yes	(0, 1, 1)	9
Expensive	No	No	(0, 0, 0)	0
Expensive	No	Yes	(0, 0, 1)	3
Expensive	Yes	No	(0, 1, 0)	6

Perceptrons

This is a simplified model of a **perceptron**. The idea was developed by Frank Rosenblatt at Cornell in 1957, and is often used in psychology.

Perceptrons

This is a simplified model of a **perceptron**. The idea was developed by Frank Rosenblatt at Cornell in 1957, and is often used in psychology.




Figure 1: *Source: Nielsen*

Perceptrons

This is a simplified model of a **perceptron**. The idea was developed by Frank Rosenblatt at Cornell in 1957, and is often used in psychology.




Figure 1: *Source: Nielsen*

Each of these lines collect evidence and are weighted to produce an output.

Perceptrons

This is a simplified model of a **perceptron**. The idea was developed by Frank Rosenblatt at Cornell in 1957, and is often used in psychology.




Figure 1: *Source: Nielsen*

Each of these lines collect evidence and are weighted to produce an output. In practice, our inputs and outputs don't necessarily have to be binary; they can be real-valued. We therefore have to define a new activation function.

Introducing the Bias

Instead of comparing our weighted sum to a threshold, we instead *add* a bias, b , to our weighted sum. We write this as $\bar{w} \cdot \bar{x} + b$ instead.

Introducing the Bias

Instead of comparing our weighted sum to a threshold, we instead *add* a bias, b , to our weighted sum. We write this as $\bar{w} \cdot \bar{x} + b$ instead. Then

$$\text{output} = \begin{cases} 0 & \text{if } \bar{w} \cdot \bar{x} + b < 0 \\ 1 & \text{if } \bar{w} \cdot \bar{x} + b \geq 0. \end{cases}$$

This is known as the *heaviside step function*. We'll extend our model to multiple outputs soon, but first we'll examine other activation functions.

Introducing the Bias

Instead of comparing our weighted sum to a threshold, we instead *add* a bias, b , to our weighted sum. We write this as $\bar{w} \cdot \bar{x} + b$ instead. Then

$$\text{output} = \begin{cases} 0 & \text{if } \bar{w} \cdot \bar{x} + b < 0 \\ 1 & \text{if } \bar{w} \cdot \bar{x} + b \geq 0. \end{cases}$$

This is known as the *heaviside step function*. We'll extend our model to multiple outputs soon, but first we'll examine other activation functions.



Rectified Linear Unit

If we want our outputs to be non-negative, we use the **rectified linear unit**,

$$f(x) = \max\{0, x\}.$$

Rectified Linear Unit

If we want our outputs to be non-negative, we use the **rectified linear unit**,

$$f(x) = \max\{0, x\}.$$

Graphically, we can see:




Figure 2: Rectifier, and a smooth approximation $\log(1 + e^x)$. (Source: Wikipedia).

Sigmoid Function

As we saw above, our output doesn't necessarily have to be a 0 or 1; using a rectified linear unit, it can be any non-negative number. However, for computational purposes, it's easiest if our outputs live in the range $(0, 1)$.

Sigmoid Function

As we saw above, our output doesn't necessarily have to be a 0 or 1; using a rectified linear unit, it can be any non-negative number. However, for computational purposes, it's easiest if our outputs live in the range $(0, 1)$. We now define the **sigmoid** or logistic function, $\sigma(z) = \frac{1}{1+e^{-z}}$.

Sigmoid Function

As we saw above, our output doesn't necessarily have to be a 0 or 1; using a rectified linear unit, it can be any non-negative number. However, for computational purposes, it's easiest if our outputs live in the range (0, 1). We now define the **sigmoid** or logistic function, $\sigma(z) = \frac{1}{1+e^{-z}}$. Graphically,




Figure 3: As $z \rightarrow \infty$, we see $\sigma(z) \rightarrow 1$. Alternatively, as $z \rightarrow -\infty$, $\sigma(z) \rightarrow 0$. (Source: *Towards Data Science*).

Supervised Learning

In **supervised learning** problems, we're given a set of training data with labels, which we try to learn. We'll use a generalization of the perceptron with different neurons, for which we try to learn the best possible weights.

Supervised Learning

In **supervised learning** problems, we're given a set of training data with labels, which we try to learn. We'll use a generalization of the perceptron with different neurons, for which we try to learn the best possible weights.




Figure 4: Source: Daniel Alvarez, InTech

Outline

1 Decision Making

2 Classifying Digits through MNIST

- Defining the Problem
- References

Example Images



Figure 5: How would you devise a system for a **computer** to classify the digits? How can we best utilize the data set, known as MNIST? (*Source: Nielsen*)

MNIST Dataset

- The MNIST database contains seventy thousand handwritten digits.

MNIST Dataset

- The MNIST database contains seventy thousand handwritten digits.
 - Each data-point contains both an image, and the desired digit.
 - 60,000 images are designated for training, and 10,000 for testing:

```
import tensorflow as tf
from tensorflow import keras
(x_train, y_train), (x_test, y_test) = keras.datasets.mnist.load_data()
```

MNIST Dataset

- The MNIST database contains seventy thousand handwritten digits.
 - Each data-point contains both an image, and the desired digit.
 - 60,000 images are designated for training, and 10,000 for testing:

```
import tensorflow as tf
from tensorflow import keras
(x_train, y_train), (x_test, y_test) = keras.datasets.mnist.load_data()
```

- Each image contains pixels ranging 0 to 255, in decreasing darkness.

MNIST Dataset

- The MNIST database contains seventy thousand handwritten digits.
 - Each data-point contains both an image, and the desired digit.
 - 60,000 images are designated for training, and 10,000 for testing:

```
import tensorflow as tf
from tensorflow import keras
(x_train, y_train), (x_test, y_test) = keras.datasets.mnist.load_data()
```

- Each image contains pixels ranging 0 to 255, in decreasing darkness.
- An individual image is a 28×28 array of pixels.

MNIST Dataset

- The MNIST database contains seventy thousand handwritten digits.
 - Each data-point contains both an image, and the desired digit.
 - 60,000 images are designated for training, and 10,000 for testing:

```
import tensorflow as tf
from tensorflow import keras
(x_train, y_train), (x_test, y_test) = keras.datasets.mnist.load_data()
```

- Each image contains pixels ranging 0 to 255, in decreasing darkness.
- An individual image is a 28×28 array of pixels.
- The desired digit is represented as a number from 0 to 9.

MNIST Dataset

- The MNIST database contains seventy thousand handwritten digits.
 - Each data-point contains both an image, and the desired digit.
 - 60,000 images are designated for training, and 10,000 for testing:

```
import tensorflow as tf
from tensorflow import keras
(x_train, y_train), (x_test, y_test) = keras.datasets.mnist.load_data()
```

- Each image contains pixels ranging 0 to 255, in decreasing darkness.
- An individual image is a 28×28 array of pixels.
- The desired digit is represented as a number from 0 to 9.

We'll build a model from the training images that will learn to classify digits!

What we're building towards




Figure 6: A simple neural network structure. The input vectors on the left hand side have $28 \times 28 = 784$ inputs for each pixel, and the output layer has 10 digits. (Source: Nielsen)

Hidden Layer

The role of the **hidden layer** is to hold intermediate calculations. These will in turn be used to compute the output layer. To produce the hidden layer, we must have an 784×15 weight matrix, as seen below:

$$W = \begin{pmatrix} w_{11} & w_{12} & \cdots & w_{1,15} \\ w_{21} & w_{22} & \cdots & w_{2,15} \\ \vdots & \vdots & \vdots & \vdots \\ \vdots & \vdots & \vdots & \vdots \\ \vdots & \vdots & \vdots & \vdots \\ w_{784,1} & w_{784,2} & \cdots & w_{784,15} \end{pmatrix}, \quad \bar{x} = \begin{pmatrix} x_1 \\ x_2 \\ \vdots \\ \vdots \\ \vdots \\ x_{784} \end{pmatrix}.$$

We take the dot product of each **column** with our input vector \bar{x} . We then add our bias vector, \bar{b} , which is 15×1 . We finally apply our activation:

$$\bar{h} = \sigma(W^T \bar{x} + \bar{b}).$$

References

- › Michael Nielsen: Using neural nets to recognize handwritten digits
- › Towards Data Science: A Beginner's Guide to Neural Networks