	1000	AOI					-	175	516	NAC	NT	1					
			10.73	50	ATT						37						
		n h									57						
		2 11	OLV I			a			3	102	7 /	40					
100	ES		1														
	63		5)		10	~				1.	20	10	0		1		
		a	1)		10		=							(8	BIT		
					- 10	90	=		1	00	111	01.	1 + 1 =				
-									1	00.	11	100	-				
											00						
-				-10)O T	10	0	(1)	0 (-	_			
-		763							CC								
		de		7	=		00	00	(011	1	(88	п)				
	100	1		13	-		00	90	1	10	1	(8)	3 17)				
			/-	13			11	11	0	91	0.4						
		1.7		/		7			/	/	9 =						
1 5	, .		4	7			11	11	00	11	14						
			1	10				0	C	1							
				13 :	- 13	+ -		00	00	0	111	+					
		7			7			90	00	1	101	2					
					2.9	10	Q	00	01	01	00 c c						
7																	
	5		(۲)_					11	01	0	11 (2	(16	В П)		100
-					0	000	9	toc									
-				20)	C	000	0	01	01	0	011	1	001	(16	- BIT)		
		Ñ.															
<u> </u>																	

5a. Generators parameters are different in order to change the clock speed from top left to right period is 1, 2, 4, and 8 (seconds).

