

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0		
funct7							rs2					rs1					funct3			rd			opcode						R-type				
imm[11:0]												rs1					funct3			rd			opcode						I-type				
imm[11:5]							rs2					rs1					funct3			imm[4:0]			opcode						S-type				
imm[12 10:5]							rs2					rs1					funct3			rd			opcode						B-type				
imm[31:12]																								rd			opcode						U-type
imm[20 10:1 11 19:12]																								rd			opcode						J-type

Zbb: “Basic bit-manipulation” Extension

31	25 24						20 19						15 14			12 11			7 6		0				
0	1	0	0	0	0	0	rs2			rs1			1 1 1			rd			0 1 1 0 0 1 1		ANDN				
0	1	0	0	0	0	0	rs2			rs1			1 1 0			rd			0 1 1 0 0 1 1		ORN				
0	1	0	0	0	0	0	rs2			rs1			1 0 0			rd			0 1 1 0 0 1 1		XNOR				
0	1	1	0	0	0	0	0 0 0 0 0 0			rs1			0 0 1			rd			0 0 1 0 0 1 1		CLZ				
0	1	1	0	0	0	0	0 0 0 0 1			rs1			0 0 1			rd			0 0 1 0 0 1 1		CTZ				
0	1	1	0	0	0	0	0 0 0 1 0			rs1			0 0 1			rd			0 0 1 0 0 1 1		CPOP				
0	0	0	0	1	0	1	rs2			rs1			1 1 0			rd			0 1 1 0 0 1 1		MAX				
0	0	0	0	1	0	1	rs2			rs1			1 1 1			rd			0 1 1 0 0 1 1		MAXU				
0	0	0	0	1	0	1	rs2			rs1			1 0 0			rd			0 1 1 0 0 1 1		MIN				
0	0	0	0	1	0	1	rs2			rs1			1 0 1			rd			0 1 1 0 0 1 1		MINU				
0	1	1	0	0	0	0	0 0 1 0 0			rs1			0 0 1			rd			0 0 1 0 0 1 1		SEXT.B				
0	1	1	0	0	0	0	0 0 1 0 1			rs1			0 0 1			rd			0 0 1 0 0 1 1		SEXT.H				
0	0	0	0	1	0	0	0 0 0 0 0			rs1			1 0 0			rd			0 1 1 0 0 1 1		ZEXT.H				
0	1	1	0	0	0	0	rs2			rs1			0 0 1			rd			0 1 1 0 0 1 1		ROL				
0	1	1	0	0	0	0	rs2			rs1			1 0 1			rd			0 1 1 0 0 1 1		ROR				
0	1	1	0	0	0	0	shamt			rs1			1 0 1			rd			0 0 1 0 0 1 1		RORI				
0	0	1	0	1	0	0	0 0 1 1 1			rs1			1 0 1			rd			0 0 1 0 0 1 1		ORC.B				
0	1	1	0	1	0	0	1 1 0 0 0			rs1			1 0 1			rd			0 0 1 0 0 1 1		REV8				

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
funct7								rs2				rs1				funct3			rd			opcode							R-type			
imm[11:0]												rs1				funct3			rd			opcode							I-type			
imm[11:5]								rs2				rs1				funct3			imm[4:0]			opcode							S-type			
imm[12 10:5]								rs2				rs1				funct3			rd			opcode							B-type			
imm[31:12]																						rd			opcode							U-type
imm[20 10:1 11 19:12]																						rd			opcode							J-type

Zri: “Load/Store indirect with Index” Extension

31							25 24		20 19			15 14			12 11		7 6		0			
0	0	0	0	0	0	0	rs2			rs1			1 1 1		rd		0 0 0 0 0 1 1			LB.R		
0	0	0	0	0	0	1	rs2			rs1			1 1 1		rd		0 0 0 0 0 1 1			LH.R		
0	0	0	0	0	1	0	rs2			rs1			1 1 1		rd		0 0 0 0 0 1 1			LW.R		
1	0	0	0	0	0	0	rs2			rs1			1 1 1		rd		0 0 0 0 0 1 1			LBU.R		
1	0	0	0	0	0	1	rs2			rs1			1 1 1		rd		0 0 0 0 0 1 1			LHU.R		
0	0	0	0	0	0	0	rs3			rs1			1 1 1		rs2		0 1 0 0 0 1 1			SB.R		
0	0	0	0	0	0	1	rs3			rs1			1 1 1		rs2		0 1 0 0 0 1 1			SH.R		
0	0	0	0	0	1	0	rs3			rs1			1 1 1		rs2		0 1 0 0 0 1 1			SW.R		

```

lb    rd, rs2(rs1)
lh    rd, rs2(rs1)
lw    rd, rs2(rs1)
lbu   rd, rs2(rs1)
lhu   rd, rs2(rs1)
sb    rs2, rs3(rs1)
sh    rs2, rs3(rs1)
sw    rs2, rs3(rs1)

```

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0								
funct7							rs2							rs1					funct3					rd					opcode					R-type					
imm[11:0]												rs2							rs1					funct3					rd					opcode					I-type
imm[11:5]							rs2							rs1					funct3					imm[4:0]					opcode					S-type					
imm[12 10:5]							rs2							rs1					funct3					rd					opcode					B-type					
imm[31:12]																	rd					opcode					U-type												
imm[20 10:1 11 19:12]																	rd					opcode					J-type												

Zor: “Objective RISC” Extension

Unprivileged:

31	25	24	20			19	15	14	12	11	7	6	0																						
0	0	0	0	0	0	0	rs2			rs1			0	0	0	rs3			0	0	0	1	0	1	1	1	SP.R	R							
0	0	0	0	0	0	0	rs2			rs1			0	0	0	rd			0	0	0	1	0	1	1	1	LP.R	R							
0	0	0	0	0	0	1	0	index[4:0]			frame			0	0	0	rs1			0	0	0	1	0	1	1	1	SV	R						
0	0	0	0	0	0	1	1	index[4:0]			frame			0	0	0	rd			0	0	0	1	0	1	1	1	RST	R						
0	0	0	0	0	1	0	0	zero			rs1			0	0	0	rd			0	0	0	1	0	1	1	1	QDTB	R						
0	0	0	0	0	1	0	1	zero			rs1			0	0	0	rd			0	0	0	1	0	1	1	1	QDTH	R						
0	0	0	0	0	1	1	0	zero			rs1			0	0	0	rd			0	0	0	1	0	1	1	1	QDTW	R						
0	0	0	0	0	1	1	1	zero			rs1			0	0	0	rd			0	0	0	1	0	1	1	1	QDTD	R						
0	0	0	0	1	0	0	0	zero			rs1			0	0	0	rd			0	0	0	1	0	1	1	1	QPI	R						
0	0	0	0	1	0	0	1	zero			zero			0	0	0	rd			0	0	0	1	0	1	1	1	GCP	R						
0	0	0	0	1	1	0	0	zero			frame			0	0	0	frame			0	0	0	1	0	1	1	1	POP	R						
0	0	0	1	0	0	0	0	zero			zero			0	0	0	zero			0	0	0	1	0	1	1	1	RTLIB	R						
0	0	0	1	0	0	1	0	zero			zero			0	0	0	zero			0	0	0	1	0	1	1	1	CPFC	R						
0	0	0	1	0	0	1	1	zero			zero			0	0	0	zero			0	0	0	1	0	1	1	1	CHECK	R						
imm[11:5]							rs2			rs1			0			0	1	imm[4:0]			0			0	0	1	0	1	1	1	SP	S			
imm[11:0]										rs1			0			1	0	rd			0			0	0	1	0	1	1	1	LP	I			
imm[11:0]										rs1			0			1	1	ra			0			0	0	1	0	1	1	1	JLIB	I			
0	0	0	0	0	0	0	0	rs2			rs1			1			0	0	rd			0			0	0	1	0	1	1	1	ALC	R		
pi[11:0]										rs1			1			0	1	rd			0			0	0	1	0	1	1	1	ALCI.P	I			
dt[11:0]										rs1			1			1	0	rd			0			0	0	1	0	1	1	1	ALCI.D	I			
dt[6:0]							0	0	0	0	0	0	rd			1			1	1	pi[4:0]			0			0	0	1	0	1	1	1	ALCI	S
dt[6:0]							0	0	0	0	1	0	frame			1			1	1	pi[4:0]			0			0	0	1	0	1	1	1	PUSHG	S
dt[6:0]							0	0	0	0	1	1	frame			1			1	1	pi[4:0]			0			0	0	1	0	1	1	1	PUSH	S

Machine Mode:

31	26 25 24			20 19			15 14			12 11			7 6			0				
1 1 1 1 1 1	0	0 0 0 0 0	0	0 0 0 0 0	0	0 0 0	rd	1 1 1 0 0 1 1	ALCB	R										
1 1 1 1 1 1	1	rs2		rs1		0 0 0	rd	1 1 1 0 0 1 1	CIOP	R										
1 1 1 1 1 1	0	1 0 0 0 0	rs1		0 0 0	rd	1 1 1 0 0 1 1	CCP	R											
1 1 1 1 1 1	0	1 0 0 0 1	rs1		0 0 0	rd	1 1 1 0 0 1 1	RPR	R											
1 1 1 1 1 1	0	1 0 1 0 0	rs1		0 0 0	rd	1 1 1 0 0 1 1	QPIR	R											
1 1 1 1 1 1	0	1 0 1 0 1	rs1		0 0 0	rd	1 1 1 0 0 1 1	QDTR	R											
1 1 1 1 1 1	0	1 0 1 1 0	rs1		0 0 0	rd	1 1 1 0 0 1 1	QPTR	R											
1 1 1 1 1 1	0	0 0 0 0 0	0	0 0 0 1 0	0 0 0	rd	1 1 1 0 0 1 1	SEAL	R											
1 1 1 1 1 1	0	0 0 0 0 0	0	0 0 0 1 1	0 0 0	rd	1 1 1 0 0 1 1	UNSL	R											

Misc:

reg	alias	reg	alias
x0	zero	x16	a6
x1	ra fix	x17	a7
x2	frame	x18	s2
x3	red /root/core	x19	s3
x4	ctxt	x20	s4
x5	t0	x21	s5
x6	t1	x22	s6
x7	t2	x23	s7
x8	s0	x24	s8
x9	s1	x25	s9
x10	a0	x26	s10/bm
x11	a1	x27	cnst
x12	a2	x28	t3
x13	a3	x29	t4
x14	a4	x30	t5
x15	a5	x31	t6

Implementation:

Instruction	rdst	rdat	rptr	raux	imm
sb/h/w	zero	ra.rix	rs1	rs2	imm
lb/bu/h/hu/w	rd	---	rs1	ra	imm
sp	zero	ra.rix	rs1	rs2	imm
lp	rd	---	rs1	ra	imm
sb/h/w.r	zero	rs3	rs1 (# frame)	rs2	---
lb/bu/h/hu/w.r	rd	rs2	rs1 (# frame)	---	---
sp.r	zero	rs3	rs1 (# frame)	rs2	---
lp.r	rd	rs2	rs1 (# frame)	---	---
sv	zero	ra.rix	frame	rs1	index
rst	rd	ra.rix	frame	bm	index
qdtx					
qpi					
gcp					
pop	frame	ra.rix	frame	---	---
jlib	ra	frame	rs1	ra	imm
jal	rd	frame	---	ra	imm
jr	rd	frame	rs1	ra	imm
rtlib	ra	ra.rix	ra	frame	---
alc	rd (# frame)	rs1	alc_params	rs2	---
alci.p	rd (# frame)	rs1	alc_params	---	pi
alci.d	rd (# frame)	rs1	alc_params	---	dt
alci	rd	ra.rix	alc_params	frame	pi & dt
pushg	rd	ra.rix	alc_params	frame	pi & dt
push	rd	ra.rix	alc_params	frame	pi & dt
alcb					
ciop	rd	rs1	---	rs2	---
rpr					
qpir					
qdtr					
qptr					
seal					
unsl					

31 30 29		3 2 1 0			
ra.rix	lib entry	rix(30:1)			
frame		frame(31:3)			color
pi	uini	pi(30:2)			color
dt	rc ri	dt(29:0)			

instruction	condition	action
jlib	ra.rix(color) != frame(color) target ptr != ra.rcd	set ra.rix(lib entry), toggle rix(color)
jal ra, ... or jr ra, ...	ra.rix(color) != frame(color)	clear ra.rix(lib entry), toggle rix(color)
pushx	ra.rix(color) = frame(color)	toggle frame(color)
pop	ra.rix(color) != frame(color)	toggle frame(color)
jr ..., 0(ra)	ra.rix(color) = frame(color)	toggle ra.rix(color) if ra.rix(lib entry) = 1 do cross code-object return else stay in this code-object

OBJECTS

Ordinary

31 30 29	2 1 0	
gc	size(29:2)	0 0
...		

Frame

31 30 29		6 5 4 3 2 1 0					
gc	key(23:0)	r	1	1	1	1	1
00	old_key	0	1	1	1	1	1
ra-ptr?							
fp-eop!							
ra-ix!							
fp-ptr!							
...							

Data only

31 30 29		2 1 0	
gc	size(29:2)		0 1
...			

Code

31	2 1 0
eoc(30:1)	1 1
eop(30:1)	1 1
...	

Immediate (Primitive)

31	0
integer	

Immediate (Pointer)

31	0
ptr	
ix	
attr	

POINTERS & DATA

(in memory)

	31	1 0
immediate (prim) pointer:	ptr(31:2) 0 1	

	31	3 2 1 0
ord./code/d.o.-ptr:	ptr(31:4)	0 0 1 1

	31	3	2	1	0
immediate (ptr) pointer:	ptr(31:4)			0	1
pc pointer:				1	1

(*immediate (ptr) pointers* shall never be present in the register-file. pc pointers shall never be stored to memory, except in the hidden ra-ptr spot of stack-frames)

	31	5 4 3 2 1 0						
io pointer:	dev	size	g	0	1	1	1	1

	32	31	25	24	17	16	9	8	1	0
Small Data (w):	31	int(30:0)								0
Small Data (h):	15	h1(14:0)				h0(15:0)				0
Small Data (b):	7	b3		b2		b1		b0		0

Allocate immediate primitive if:

- sw and rs(30) ≠ rs(31)
- sh at h1 and rs(14) ≠ rs(15)
- sb at b3 and (rs(7) = 1 or rs < 0)

REGISTER FILE & PIPELINE

data	T	31	0			
	0	value(31:0)	alc_addr	alc_lim		
ordinary pointer	T	31	4 3 2 1 0	31	0	313029 2 1 0
	1	ptr(31:4)	0 0 0 0	index(31:0)	0 0	size(29:2) 0 0
code pointer	T	31	4 3 2 1 0	31	0	3130 1 0
	1	ptr(31:4)	0 1 0 0	eop(31:0)	0	eoc(30:1) 0
pc pointer	T	31	4 3 2 1 0	31	0	3130 1 0
	1	ptr(31:4)	1 0 0 0	index(31:0)	0	eoc(30:1) 0
sp/fp	T	31	4 3 2 1 0	31	0	31 0
	1	base-ptr(31:4)	0 0 0 1	index(31:0)		eop(31:0)
contents of sp (x2) and fp (x8) may be moved to another register, but stack-frames may only be allocated using sp and the public area may only be increased by operations on sp. Contents of the public area of past frames may only be accessed using fp.						
highest valid address for memory access using fp-types: fp(eop)						
lowest valid address for memory access using fp-types: sp						
copies of sp/fp	T	31	4 3 2 1 0	31	0	31 0
	1	ptr(31:4)	0 0 1 0	index(31:0)		key
io pointer	T	31	4 3 2 1 0	31	0	313029 2 1 0
	1	dev(27:0)	1 1 0 0	index(31:0)	g	size(29:2) 0 0

FRAME OPERATIONS


Dangling references are tracked by a key associated with registers containing pointers on stack frames. When such a register is supposed to be stored to memory, it will always be emitted into an immediate pointer, so the key-attribute of such pointers is not lost.

Contents on a stack frame may only be accessed (apart from `sp` and `fp`) via a special stack pointers. These stack pointers are composed of a (unmodifiable) base pointer of the stack frame and a (also unmodifiable) index to where the local data is stored. The header field of a stack frame contains a key, which identifies the stack frames age. Only if the base pointer and the key of the register match the base pointer and the key it tries to load/store to, the access is granted. Otherwise, a dangling reference exception is thrown.

The key is realized by a simple “pop counter”. With every deallocation operation of a stack frame (header), the pop counter is increased. It can only be decreased by the garbage collector, after a successful rearranging sweep over all stack frames. If the pop counter overflows, a stack overflow exception is thrown.


Example: trying to load from a dangling reference

❶ 3 Stack frames with keys and pointers on their content




`lw t0, 0(s2)` and `sw t0, 0(s2)` would first load address 24 and compare its key with the key stored at that address. In this case, the keys would match and the load/store operation at memory address 2C can be operated.

❷ The last stack frame gets deallocated – `s2` becomes dangling



`lw t0, 0(s2)` and `sw t0, 0(s2)` would first load address 24 and compare its key with the key stored at that address. In this case, memory address 24 does not contain a key anymore, so the match is not successful and an exception is thrown.


❸ A new stack frame is allocated



`lw t0, 0(s2)` and `sw t0, 0(s2)` would first load address 24 and compare its key with the key stored at that address. In this case, the key in memory does not match the key of the register, which also causes an exception.


Example: garbage collector freeing stack frame keys (work in progress)

❶ 4 Stack frames with keys and pointers on their content



In this scenario, the stack frames with keys 3 and 4 can be bumped up to keys 1 and 2 respectively, to free up keys for future allocations.

❷ First Cycle




In a first iteration, the garbage collector would notice the available space between frame 0 and frame 3. As a consequence, the garbage collector would re-assign the lowest possible key to stack frames 3 and subsequently update all pointers with key 3 to key 1.

While this collection cycle is in progress, keys 1 and 3 are both valid for this stack frame. This is marked by the gc-bit in the key field of the frame being set. After the cycle finished, the gc-bit will be cleared again and only key 1 will be valid from then on.

If the garbage collector encounters a dangling reference on a frame where the key is being changed, the pointer is replaced to a null pointer. (Does this cause too many memory accesses? This may be needed tho!)

❸ Second Cycle



In the second iteration, the garbage collector would notice the available space between frame 1 and 4. Just as the first iteration, the collector would bump key 4 and all its pointers to key 2.



This process continues, until the end of stack is reached. If that happens, the current value of the counter csr is subtracted by the difference of the last frames original key and the last frames new key.

E.g. frame 4 was the last frame on stack and the csr had a value of 7, then the csr will be updated to 5.

Instruction	rdst	rdat	rptra	raux	imm
lui	rd	---	---	---	imm
auipc	rd	---	---	---	imm
jal	rd	---	---	---	imm
jalr	rd	---	rs1	---	imm
bcc	---	rs1	---	rs2	imm
lb/bu/h/lu/w	rd	---	rs1	ra	imm
sb/h/w	(sp)	ra.rix	rs1	rs2	imm
addi	rd	ra.rix	sp	rs1	imm
arithi	rd	rs1	---	---	imm
arith	rd	rs2	---	rs1	---
alc	rd	rs1	alc_params	---	---
alci	rd	---	alc_params	---	imm
alc.d	rd	rs1	alc_params	---	---
alci.d	rd	---	alc_params	---	imm
qsz	rd	---	rs1	---	---

addi

dc	if rs1 = sp then set me_mode = alloc else set alu_mode = add
ex	if color(sp) ≠ color(ra) and rs1 = sp then set alloc_frame_header = true and generate frame header struct else alloc_frame_header = false
me	if me_mode = alloc then init stack-frame if alloc_frame_header then store frame header
at	---



	TAG	WERT		ATTRIBUT 1	ATTRIBUT 2
<i>Daten</i>	0	Data		null	null
<i>Datenobjektzeiger</i>	1	Pointer	000	Größe Zeigerbereich (π)	Größe Datenbereich (δ)
<i>Code-Objektzeiger</i>	1	Pointer	010	Ende öffentlicher Bereich (ρ)	Ende Code-Objekt (ξ)
<i>PC-Zeiger</i>	1	Pointer	011	Index (χ)	Ende Code-Objekt (ξ)

<i>s0</i>	0	Data		null	null
<i>s1</i>	1	Pointer	000	π	δ
<i>a0</i>	1	Pointer	010	ρ	ξ
<i>a1</i>	1	Pointer	011	χ	ξ
<i>a2</i>	0	Data		null	null

a3	0	Data		null	null
a4	1	Pointer	000	π	δ

